

AD-A197 364

DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS DTIC FILE COPY	
2a. SECURITY CLASSIFICATION AUTHORITY S JUL 06 1988		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		4. PERFORMING ORGANIZATION REPORT NUMBER H 10	
5a. NAME OF PERFORMING ORGANIZATION Naval Ocean Systems Center		5b. OFFICE SYMBOL (if applicable) NOSC	
6a. ADDRESS (City, State and ZIP Code) San Diego, California 92152-5000		7a. NAME OF MONITORING ORGANIZATION Naval Ocean Systems Center	
6b. ADDRESS (City, State and ZIP Code) San Diego, CA 92152-5000		7b. ADDRESS (City, State and ZIP Code) San Diego, CA 92152-5000	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION David Taylor Research Center		8b. OFFICE SYMBOL (if applicable) DTNSRDC	
8c. ADDRESS (City, State and ZIP Code) David Taylor Labs Bethesda, MD 20084		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
10. SOURCE OF FUNDING NUMBERS		11. TITLE (include Security Classification)	
PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	AGENCY ACCESSION NO.
62121N	CM41	RH21 S20	DN 088 509
THE DESIGN OF ANTENNA MATCHING NETWORKS USING A MICROCOMPUTER			
12. PERSONAL AUTHOR(S) S.T. Li and D.W.S. Tam			
13a. TYPE OF REPORT presentation/paper	13b. TIME COVERED FROM Mar 1988 TO Mar 1988	14. DATE OF REPORT (Year, Month, Day) May 1988	15. PAGE COUNT
16. SUPPLEMENTARY NOTATION			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	
			VSW (voltage standing-wave ratio)
			multicouplers
			broadband matching network
19. ABSTRACT (Continue on reverse if necessary and identify by block number)			
In a communication system one of the primary concerns is maximum efficiency in signal transmission and reception. For maximum power transfer there must be an impedance match between the antenna and transmitter (or receiver). A basic problem is to design a coupling network between a given source and a given load so that the transfer of power from the source to the load is maximized over a given frequency band of interest. The device used to perform this impedance matching is called an antenna matching network. The number of pieces of equipment requiring an antenna connection in some applications may exceed the number of acceptable locations available for antennas. One solution is the use of broadband antennas that have a low VSWR (voltage standing-wave ratio) over the operating band. Broadband antennas are used in conjunction with multicouplers (filters with multiple inputs) to provide a sufficient number of antenna connections. Despite the aid of Smith Charts, the traditional design of an antenna matching network by engineering experience and manual calculation means is an extremely time-consuming task. This paper is intended to relieve the engineer of the tedious numerical calculation involved in the network design. An interactive BASIC language computer program to aid in the design of a matching network for a broadband antenna is described (S.T. Li and D.W.S. Tam, NOSC TD 1148, September 1987). Guidelines for the design of a broadband matching network are presented. The Antenna Matching (ANTMAT) program provides a computer-aided design tool for determining network topology and component values of the networks. It improves the speed and accuracy of the broadband matching network design procedures. An optimization algorithm finds the values of the components that minimize the input reflection coefficient. At first, the optimization algorithm with an exponential weighting function is employed for determining a list of network candidates (either a pi network or a T network) from which a network topology is selected. After a topology is specified, the optimization algorithm with other weighting functions is used for finding optimum element values. Presented at the Fourth Annual Review of Progress in Applied Computational Electromagnetics, 22-24 March 1988, Monterey, CA.			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT		21. ABSTRACT SECURITY CLASSIFICATION	
☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT ☐ DTIC USERS		UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL S.T. Li		22b. TELEPHONE (include Area Code) (619) 553-5089	22c. OFFICE SYMBOL Code 822

①

THE DESIGN OF ANTENNA MATCHING NETWORKS USING A MICROCOMPUTER

S. T. Li and D. W. S. Tam
Naval Ocean Systems Center, Code 822
271 Catalina Blvd.
San Diego, California 92152-5000

PA #
048A

In a communication system one of the primary concerns is maximum efficiency in signal transmission and reception. For maximum power transfer there must be an impedance match between the antenna and transmitter (or receiver). A basic problem is to design a coupling network between a given source and a given load so that the transfer of power from the source to the load is maximized over a given frequency band of interest. The device used to perform this impedance matching is called an antenna matching network.

The number of pieces of equipment requiring an antenna connection in some applications may exceed the number of acceptable locations available for antennas. One solution is the use of broadband antennas that have a low VSWR (voltage standing-wave ratio) over the operating band. Broadband antennas are used in conjunction with multicouplers (filters with multiple inputs) to provide a sufficient number of antenna connections.

Despite the aid of Smith Charts, the traditional design of an antenna matching network by engineering experience and manual calculation means is an extremely time-consuming task. This paper is intended to relieve the engineer of the tedious numerical calculation involved in the network design. (KR) ←

An interactive BASIC language computer program to aid in the design of a matching network for a broadband antenna is described (S. T. Li and D. W. S. Tam, NOSC TD 1148, September 1987). Guidelines for the design of a broadband matching network are presented. The Antenna Matching (ANTMAT) program provides a computer-aided design tool for determining network topology and component values of the networks. It improves the speed and accuracy of the broadband matching network design procedures. An optimization algorithm finds the values of the components that minimize the input reflection coefficient. At first, the optimization algorithm with an exponential weighting function is employed for determining a list of network candidates (either a pi network or a T network) from which a network topology is selected. After a topology is specified, the optimization algorithm with other weighting functions is used for finding optimum element values.



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

88 7 06 018