

DTIC FILE COPY

4

AD-A198 782

TECHNOLOGY FOR USE OF VARIABLE QUALITY FUELS

INTERIM REPORT
BFLRF No. 239

By

J.N. Bowden

D.M. Yost

A.F. Montemayor

L.L. Stavinoha

Belvoir Fuels and Lubricants Research Facility (SwRI)
Southwest Research Institute
San Antonio, Texas



Under Contract to

U.S. Army Belvoir Research, Development
and Engineering Center
Materials, Fuels and Lubricants Laboratory
Fort Belvoir, Virginia

Contract No. DAAK70-87-C-0043

Approved for public release; distribution unlimited

December 1987

88 9 20

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Trade names cited in this report do not constitute an official endorsement or approval of the use of such commercial hardware or software.

DTIC Availability Notice

Qualified requestors may obtain copies of this report from the Defense Technical Information Center, Cameron Station, Alexandria, Virginia 22314.

Disposition Instructions

Destroy this report when no longer needed. Do not return it to the originator.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION <u>Unclassified</u>			1b. RESTRICTIVE MARKINGS <u>None</u>	
2a. SECURITY CLASSIFICATION AUTHORITY <u>N/A</u>			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE <u>None</u>			5. MONITORING ORGANIZATION REPORT NUMBER(S)	
4. PERFORMING ORGANIZATION REPORT NUMBER(S) Interim Report BFLRF No. 239			7a. NAME OF MONITORING ORGANIZATION	
6a. NAME OF PERFORMING ORGANIZATION Belvoir Fuels and Lubricants Research Facility (SwRI)		6b. OFFICE SYMBOL (If applicable)	7b. ADDRESS (City, State, and ZIP Code)	
6c. ADDRESS (City, State, and ZIP Code) Southwest Research Institute 6220 Culebra Road San Antonio, TX 78284			9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER DAAK70-85-C-0007, WD 8; DAAK70-87-C-0043	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION U.S. Army Belvoir Research, Development and Engineering Center		8b. OFFICE SYMBOL (If applicable) STRBE-VF	10. SOURCE OF FUNDING NUMBERS	
8c. ADDRESS (City, State, and ZIP Code) Ft. Belvoir, VA 22060-5606		PROGRAM ELEMENT NO. 62733A	PROJECT NO. IL7627 33AH20	TASK NO. VM
11. TITLE (Include Security Classification) Technology for Use of Variable Quality Fuels (U)				
12. PERSONAL AUTHOR(S) Bowden, John N.; Yost, Douglas M.; Montemayor, Alan F., Stavinoha, Leo L.				
13a. TYPE OF REPORT <u>Interim</u>		13b. TIME COVERED FROM <u>Oct 1984</u> to <u>Sept 1987</u>		14. DATE OF REPORT (Year, Month, Day) 1987 December
15. PAGE COUNT 69				
16. SUPPLEMENTARY NOTATION				
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	Diesel Fuel, Diesel Engine, Stability	
			Fuel, Cetane Number,	
			Fuel Oils, Viscosity	
19. ABSTRACT (Continue on reverse if necessary and identify by block number)				
This program was intended to determine the specification properties of diesel fuel that can be varied and relaxed with little or no performance or handling penalties by using modified bench and engine tests. Specially blended test fuels were used that had selected properties outside of specified limits in Federal Specification VV-F-800D, Fuel Oil, Diesel, Grade DF-2. The properties investigated were cetane number, viscosity, distillation temperature limits at 90-percent recovered and end point, accelerated stability values, and carbon residue on 10-percent bottoms. Cold-starting tests to investigate the effect of fuel cetane numbers and viscosities were conducted with engines common to the Army inventory as follows: Detroit Diesel 6V-53T, Continental LDT-465-1C, Cummins NHC-250, and General Motors 6.2L. The effect of higher 90-percent distillation and end-point temperatures than specified was investigated using a Petter model PH1W single-cylinder diesel engine. To investigate the effect of high accelerated stability values on injector deposit formation, several fuels were evaluated by the Injector Fouling Bench Test (IFBT) using two injector systems: the Detroit				
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION <u>Unclassified</u>	
22a. NAME OF RESPONSIBLE INDIVIDUAL Mr. F.W. Schaeckel			22b. TELEPHONE (Include Area Code) (703) 664-3576	22c. OFFICE SYMBOL STRBE-VF

19. ABSTRACT (Cont'd)

Diesel and the Bosch APE 113. The same methodology was used to investigate the effect of a fuel that exceeded the specification limit for carbon residue on injector deposit formation. The overall conclusions from this work are that the fuel properties investigated cannot be relaxed to any significant extent and still permit adequate long-term performance in all engines and components currently in the Army system under all climate conditions. Some engines and systems are very tolerant of fuels that do not meet current DF-2 specification requirements, while others will **not** operate satisfactorily on fuels that fail to meet certain specification limits. Using the least tolerant engines, the chemical and physical property limits for a variable quality fuel specification are suggested for limited time frame use on local procurements for high throughput maneuvers where ambient temperatures exceed 45°F (7°C).

Cold weather operations as well as vehicles experiencing low utilization require standard specification fuels for trouble-free operation.

FOREWORD

This work was performed at the Belvoir Fuels and Lubricants Research Facility, Southwest Research Institute, under DOD Contract Nos. DAAK70-85-C-0007, Work Directive No. 8 and DAAK70-87-C-0043. The project was administered by the Fuels and Lubricants Division, U.S. Army Belvoir Research, Development and Engineering Center, Ft. Belvoir, VA 22060-5606, with Mr. F.W. Schaekel, STRBE-VF, serving as Contracting Officer's Representative, and Mr. M.E. LePera, Chief of Fuels and Lubricants Division (STRBE-VF), the project technical monitor. This report covers the period of performance from October 1984 through September 1987.



Accession For	
NTIS GRA&I	☒
DTIC Tab	☐
Unannounced	☐
Justification	
By	
Distribution	
Availability	
Availability	
Dist	
A-1	

ACKNOWLEDGMENTS

The authors express their appreciation to Ms. Lona Bundy and Debbie Toles for their efforts in collecting and graphing data for this project and to Mr. Jim Pryor, Ms. Cindy Sturrock, Sherry Douvry, and LuAnn Pierce for their editorial contributions to this report.

The technical guidance and review provided by Messrs. E.C. Owens and S.J. Lestz during the performance of this project is acknowledged.

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
I. INTRODUCTION	1
II. OBJECTIVES	2
III. APPROACH	3
IV. EXPERIMENTAL AND DISCUSSION OF RESULTS	4
A. Cetane Number and Viscosity	4
1. Cold-Start Engine Tests	5
2. Cold-Start Test Results	9
3. Effect of Front-End Volatility and Viscosity on Fuel Injection Systems	21
B. 90-Percent Distillation and End Point	22
C. Accelerated Stability	24
D. Carbon Residue	33
V. SUMMARY OF RESULTS	39
VI. CONCLUSIONS	40
VII. RECOMMENDATIONS	41
VIII. REFERENCES	42
 APPENDICES	
A. Army Cold Startability Procedure	45
B. Cold-Start Test Data	49
C. Injector Fouling Bench Test Methodology for Diesel Fuel Thermal Stability	55
D. Diesel Fuel Specification Comparisons	63
E. Interrelationship of Physical/Chemical Properties of Fuels	67

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	"40" Cetane Number Fuels - DD 6V-53T Engine	10
2	"35" Cetane Number Fuels - DD 6V-53T Engine	10
3	"30" Cetane Number Fuels - DD 6V-53T Engine	11
4	"40" Cetane Number Fuels - LDT-465-1C Engine	12
5	"35" Cetane Number Fuels - LDT-465-1C Engine	13
6	"30" Cetane Number Fuels - LDT-465-1C Engine	13
7	"40" Cetane Number Fuels - NHC-250 Engine	15
8	"35" Cetane Number Fuels - NHC-250 Engine	15
9	"30" Cetane Number Fuels - NHC-250 Engine	16
10	"40" Cetane Number Fuels - GM 6.2L Engine	17
11	"35" Cetane Number Fuels - GM 6.2L Engine	18
12	"30" Cetane Number Fuels - GM 6.2L Engine	18
13	Viscosity Temperature Relationships of Test Fuels	20
14	Pintle Demerits for Detroit Diesel IGBT	29
15	Pintle Demerits for Bosch APE 113 IGBT	30
16	Airflow for Detroit Diesel IGBT	30
17	Airflow for Bosch APE 113 IGBT	31
18	TDR for Detroit Diesel IGBT	31
19	TDR for Bosch APE 113 IGBT	32
20	DMD for Detroit Diesel IGBT	32
21	DMD for Bosch APE 113 IGBT	33

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 Composition and Properties of Test Fuel Blends	4
2 Engine Specifications for the DD 6V-53T Engine	6
3 Engine Specifications for the Continental LDT-465-1C Engine	6
4 Engine Specifications for the Cummins NHC-250 Engine	6
5 Engine Specifications for the General Motors 6.2L Engine	7
6 Summary of Effect of Certain Fuel Properties on Cold Startability	19
7 Summary of Property Effects on Fuel Injection Systems	21
8 Fuel Properties	22
9 Fuels and Lubricants Used in Petter Engine Test	22
10 New Oil Properties	23
11 100-Hour Petter Engine Test Results	24
12 Fuel Properties	26
13 Detroit Diesel IFBT Operating Conditions and Test Results	27
14 CLR-D Bosch APE 113 IFBT Operating Conditions and Test Results	28
15 Results of Stability Tests Compared to IFBT Pintle Deposits	34
16 Properties of Marine Fuel Oil Sample	35
17 Test Fuel Blend	36
18 Detroit Diesel IFBT Operating Conditions and Test Results	37
19 CLR-D Bosch APE 113 IFBT Operating Conditions and Test Results	38

I. INTRODUCTION

Within the Army Mobility Fuels Research and Development Program, there are concerns with development of more fuel-tolerant engines (a long-term goal), and improved fuels' availability (a short-term goal). The specific tasks covered within this activity are to (1) determine engine performance parameters, (2) define fuels' influence on engine operations, and (3) define engine-fuel operating limits. One of the major program goals is to improve the capability for using commercially available fuels and fuel substitutes without significant impairment of mission requirements. Within the plan, specific goals were requested in three general areas of mobility fuels technology: (1) Broaden Specifications, (2) Alternative Sources, and (3) Fuel Tolerance of Current Equipment. One specific goal within the area of Broaden Specifications is the development of interim specifications for variable-quality ground fuels.(1,2)*

The government currently has a variable quality fuel specification, with the properties being varied based on the expected low temperature in the region. For higher ambient temperatures, the DF-2 property levels are used, while for colder locations, the DF-1 or DF-A limits are applied. Furthermore, outside of CONUS, the above property limitations are relaxed somewhat in order to increase fuel availability.

While there are times at many locations where current VV-F-800 specifications may be overly restrictive, one problem that must be taken into consideration before relaxing the procurement requirements is that of fuel stock turnover. There have been instances (3) where Army bases are procuring DF-2 during summer months, but, because of low turnover rates, the fuel is still being used during the winter with resulting problems due to high cloud point.

The work described in this report addresses the goal to develop variable quality fuel specifications through evaluation of fuels with marginal properties with respect to effects on engine performance. Under a separate phase of this project, fuels with marginal properties were investigated with respect to their effects on combustion, power, and performance. The results are discussed in a separate report.

* Underscored numbers in parentheses refer to the list of references at the end of this report.

Federal Specification VV-F-800D, Fuel Oil, Diesel (4), covers fuels suitable for use in automotive diesel and/or compression-ignition and gas turbine engines other than aircraft under all climate conditions. Three grades of diesel fuel are described:

DF-A	Arctic Grade
DF-1	Winter Grade
DF-2	Regular Grade

The regular grade, DF-2, is classified further into standard and NATO F-54. The properties of these grades of fuel are limited by the specification to test values that will ensure good handling and satisfactory engine performance.

The bulk of the diesel fuel procured by the U.S. Government for use in CONUS is the regular grade DF-2. When the fuels meet the specification requirements, they perform satisfactorily in the equipment in which they are used. Frequently, fuels meeting all the requirements of DF-2 cannot be supplied, and petroleum companies have been requesting waivers on certain properties before bids are submitted. This occurrence is largely a result of the lesser quality of crude oils available for refining into fuels and the necessity for blending into finished fuel stocks from cracking and recycling processes.

Most of the fuels that fail to meet every specification requirement and are granted waivers are still expected to give satisfactory performance with little or no penalty. The degree of property relaxation that can be allowed without severely jeopardizing engine operation is not known. This project is intended to provide data on which variation allowance of fuel properties can be based without jeopardizing performance.

A general definition for variable quality fuels is fuels procured against relaxed specification limits.

II. OBJECTIVES

A need existed to investigate the effect of varying fuel properties on engine performance and to determine the conditions under which fuel property limits can be relaxed with little or no engine performance degradation or reduction of vehicle mission

readiness. The objectives of this program are to determine the specification properties of diesel fuel that can be varied or relaxed with little or no engine performance or handling penalties and to provide a basis for the development of interim specifications for variable-quality ground fuels.

A cross section of Army vehicles/equipment was used to evaluate effects of different fuel property variations. Test fuels were blended to emphasize specific property/equipment concerns. Test fuels and equipment are described in the respective report sections.

III. APPROACH

Possible variation in limits for the properties listed were investigated as outlined.

Cetane Number and Viscosity - Cetane number and viscosity affect startability probably more than any other performance parameters. Therefore, a matrix of test fuels with varying cetane numbers and viscosities was used in cold starting tests with four military engines. Under a separate phase, the effects of front end volatility and viscosity on the performance of three fuel injection systems were investigated.

90-Percent Distillation and End Point - Fuels with high 90-percent and end-point distillation temperatures tend to cause carbonaceous engine deposits and crankcase oil dilution. Therefore, fuel blends having 90-percent distillation and end-point temperatures above the DF-2 specification limits were evaluated in 100-hour Petter engine tests for deposit-forming tendencies and crankcase dilution.

Accelerated Stability - With respect to engine performance, it is anticipated that fuels with poor accelerated stability test results may produce deposits in fuel injector systems, resulting in plugged injectors. As a result, fuels with accelerated stability values above the limit specified in VV-F-800D were evaluated in an injector fouling bench test.

Carbon Residue - Fuels with high carbon residue may form harmful deposits in the combustor of a gas turbine engine and in the fuel injectors of a diesel engine. In both situations, the combustion process may be disrupted. Thus, a fuel with carbon residue value above the limit shown in VV-F-800D was evaluated in an injector fouling bench test.

IV. EXPERIMENTAL AND DISCUSSION OF RESULTS

A. Cetane Number and Viscosity

The effects of cetane number and viscosity on the low-temperature startability of four military engines were evaluated using a test matrix of six fuels described in TABLE 1. Two fuel sets of three fuels each were blended. Both sets had fuels with cetane numbers of approximately 40, 35, and 30; and the viscosities at 40°C for one set were about 1.0 cSt, and 5 to 6 cSt for the other set. To provide the desired properties for each blend, several fuels and special refinery products were used. These products included a

TABLE 1. Composition and Properties of Test Fuel Blends
(10-Gallon Batches)

Blend No. AL-Code No.	A40 <u>14010</u>	A35 <u>14011</u>	A30 <u>14012</u>	B40 <u>14013</u>	B35 <u>14014</u>	B30 <u>14015</u>
<u>Composition, vol%</u>						
Kerosene	81	69	62	--	--	--
Xylene Tower Bottoms	19	31	38	--	--	--
Burner No. 2	--	--	--	28	--	50
Telura [®] 126	--	--	--	--	--	50
Telura [®] 309	--	--	--	72	--	--
Telura [®] 705	--	--	--	--	82	--
Cat 1H2/1G2	--	--	--	--	18	--
<u>Properties</u>						
K. Vis. at 40°C, cSt, D 445	1.13	1.03	0.99	5.90	5.20	5.69
K. Vis. at 0°C, cSt, D 445	2.12	2.15	1.85	24.0	24.2	25.5
Cetane No., D 613	38.9	33.3	30.2	41.1	34.8	31.8
Gravity, °API, D 1298	43.6	40.7	39.9	27.9	40.1	22.6
Distillation, °F(°C), D 86						
IBP	305(152)	313(156)	307(153)	341(172)	472(244)	350(177)
10% recovered	342(172)	335(168)	332(167)	479(248)	504(262)	417(214)
50% recovered	379(193)	364(184)	359(182)	594(312)	526(274)	600(316)
90% recovered	421(216)	416(213)	414(212)	652(344)	564(296)	694(368)
EP	445(259)	450(232)	454(234)	700(371)	616(324)	760(404)
Carbon, mass%, D 3178	86.06	86.85	86.97	87.21	85.71	87.06
Hydrogen, mass%, D 3178	13.27	12.62	12.28	12.71	14.24	11.58
Sulfur, mass%, D 2622	0.01	0.01	0.01	0.31	0.09	0.84
Net Heat Comb., D 240 Btu/lb	18,373	18,127	18,111	18,122	18,587	17,808

kerosene, a reference DF-2 fuel known as Cat 1H2/1G2, a No. 2 burner fuel, xylene tower bottoms, and special products described as industrial process oils as follows: Telura[®] 126 is a high-aromatic (67 mass%), high-viscosity (24 cSt at 40°C) fraction; Telura[®] 309 is a naphthenic, intermediate viscosity (0.1 cSt at 40°C) fraction; and Telura[®] 705 is a nonaromatic (1.0 mass% aromatics), intermediate viscosity (6.1 cSt at 40°C) fraction.

1. Cold-Start Engine Tests

The four engines investigated in this program were the Detroit Diesel 6V-53T, the Continental LDT-465-1C, the Cummins NHC-250, and the GM 6.2L. Specifications for these engines are listed in TABLES 2, 3, 4, and 5, respectively. For cold-start evaluations using the fuels described in TABLE 1, each engine was installed in a cold room capable of being chilled to -40°C (-40°F). The engines were not coupled to a dynamometer or any other power absorption device.

The normal engine-mounted fuel lines and pumps supplied with the engines were used. If primary and secondary fuel filters were standard equipment, the primary filter was removed, and only the secondary was used to increase flushing efficiency between fuels. The fuel supply was provided from a vented 1-gallon container, resting on a fuel scale located inside the cold room. The fuel supply line and return line from the engine were routed so they did not touch the container.

The normal lubricating oil systems for each engine were used in these tests. The lubricant used was a 15W-40 grade, MIL-L-2104D reference oil, qualification number MC 231.

The standard 24-volt starting motors supplied with the engines were used for these evaluations. The batteries were maintained fully charged and located externally to the cold room. Minimum length cables were used to supply voltage to the starter in order to avoid voltage drops in the lines. An external manually operated starter switch was provided. This switch was a momentary contact type, which energized the starter when depressed and de-energized it when released.

TABLE 2. Engine Specifications for the DD 6V-53T Engine

Model:	5063-5395
Engine Type:	Two-Cycle, Compression Ignition, Direct Injection, Turbo-Supercharged
Starting Aids:	Air Box Heater
Cylinders:	6, V Configuration
Displacement:	5.21L (318 cubic inches)
Bore:	9.8 cm (3.875 inches)
Stroke:	11.4 cm (4.5 inches)
Compression Ratio:	18.7:1
Injection Pump Type:	DD N 70 Unit Injectors
Maximum Rated Power:	224 kW (300 BHP) at 2800 rpm
Maximum Rated Torque:	858 NM (633 lb-ft) at 2200 rpm

TABLE 3. Engine Specifications for the Continental LDT-465-1C Engine

Model:	LDT-465-1C
Engine Type:	Four-cycle, Compression Ignition, M.A.N. Combustion System, Turbocharged
Starting Aids:	Manifold Heater
Cylinders:	6, Inline
Displacement:	7.83 (478 cubic inches)
Bore:	11.58 cm (4.56 inches)
Stroke:	12.37 cm (4.87 inches)
Compression Ratio:	22:1
Fuel Injection:	Bosch Rotary Distributor w/Density Compensation
Rated Power:	145-156 kW (194-209 BHP) at 2800 rpm
Rated Torque:	597 NM (429 lb-ft) at 2000 rpm

TABLE 4. Engine Specifications for the Cummins NHC-250 Engine

Model:	Cummins NHC-250
Engine Type:	Normally Aspirated, Direct Injection
Starting Aids:	Manifold Heater (Glow Plug and Spray Nozzle)
Cylinders:	6 Cylinder; 4 Cycle; Inline
Displacement:	14.01 L (855 cubic inches)
Bore:	14.97 cm (5.5 inches)
Stroke:	15.24 cm (6 inches)
Compression Ratio:	15.8:1
Fuel Injection:	Cummins PT Fuel Pump and Injectors
Rated Power:	179.5 kW (240 BHP) at 2100 rpm
Rated Torque:	892 NM (658 lb-ft) at 1500 rpm

TABLE 5. Engine Specifications for the General Motors 6.2L Engine

Model:	GM 6.2L
Engine Type:	Four-Cylinder, Compression Ignition, Ricardo Comet V Combustion Chamber
Starting Aids:	Glow Plug
Cylinders:	8, V-Configuration
Displacement:	6.217 L (379 cubic inches)
Bore:	10.1 cm (3.98 inches)
Stroke:	9.7 cm (3.82 inches)
Compression Ratio:	21.3:1
Fuel Injection:	Stanadyne DB-2 Fuel Injection Pump, Bosch Pintle Injectors
Rated Power:	116 kW (155 BHP) at 3600 rpm
Rated Torque:	355 NM (262 lb-ft) at 2200 rpm

Instrumentation was provided to measure the following parameters:

Fuel Consumption - Fuel consumption was measured using the 1-gallon container and scale arrangement described earlier. The fuel scale was capable of measuring in the 0 to 10 kg range with a resolution of 0.05 kg. A readout for the weight of the fuel and container was provided on the control panel.

Engine Speed - Engine speed (rpm) was measured with an electronic speed sensor that had a resolution of 10 rpm. A digital readout and a chart recorder were provided for rpm measurements.

Temperatures - Temperatures were measured using Type J thermocouples with a readout device on the control panel at the following locations:

- Inlet air stream. Air box temperature for the DD 6V-53T engine, intake manifold temperature for the other engines.
- Cooling water inlet
- Oil sump
- Fuel in supply container
- Exhaust
- Air in cold room

More detail of preparation and completion of each test are described in Appendix A.

a. Cold Starting With the DD 6V-53T Engine

The cold start test procedure for the DD 6V-53T engine was patterned after the one found in technical manual TM 9-2350-230-10.(5) At temperatures below 4.4°C (40°F), an air box heater is used as a starting aid. The starter button was depressed for 20 seconds, and at the same time, the air box heater switch was engaged for 1 second and released for 2 seconds. If no start occurred, the starter and heater button were released for 20 seconds, and the process was repeated until the engine started, or 20 seconds elapsed. The sequence was repeated for a total of 120 seconds cranking time. If the engine did not start in that time frame, the test was recorded as "no start." An unaided starting procedure similar to this was used in previous work with a DDA 4-53T engine.(6)

b. Cold Starting With the Continental LDT-465-1C Engine

The procedure for starting the LDT-465-1C engine was patterned after the one found in TM 9-2320-209-10 (7) and was similar to that used with the 6V-53T engine. The temperature below which the starting aid was used was -7°C (20°F). A manifold heater is used in this engine as the starting aid. Again if the engine did not start within 120 seconds cranking time, the test was recorded as "no start."

c. Cold Starting With the Cummins NHC-250 Engine

TM 9-2320-260-10-1, the tech manual for the 5-ton 6x6 M809 series trucks with the Cummins NHC-250 engine, describes the procedure for starting this engine at temperatures below 0°C (32°F).(8) This procedure was adapted for this test engine as follows: The manifold heater switch was engaged. After 15 seconds, the primer pump was activated and immediately the starter button was depressed and held. The primer pump was released for 2 seconds and engaged again for 2 seconds. If no start occurred, the sequence was repeated for 10 seconds and all buttons were released for 10 seconds. The process was then repeated until the engine started, or for a total of 120 seconds cranking time. As with the two previous engines, if no start occurred within 120 seconds cranking time, the test was recorded as "no start."

d. Cold Starting With the General Motors 6.2L Engine

The GM 6.2L engine has a glow plug installed in the manifold that is activated when the ignition switch is turned on. The switch also illuminates a "wait to start" light that goes out when the glow plug is sufficiently hot for the starter to be engaged. The net effect is that the glow plug is a starting aid that operates at all ambient temperatures. However, when the temperature is below 0°C (32°F), special procedures adapted for these tests are to be used.⁽⁹⁾ The ignition switch was turned on, and after the "wait to start" light went out, the fuel pump was engaged and the starter button depressed. If the engine did not start in 15 seconds, the pump and starter were released for 15 seconds before attempting to start again. If no start occurred, the sequence was repeated for a maximum of 90 seconds cranking time, and, at the end of this period, the test was recorded as "no start."

2. Cold-Start Test Results

a. DD 6V-53T Engine

The data for all the cold-start tests conducted with the DD 6V-53T engine are shown in TABLE B-1 of Appendix B. The first seven tests were conducted with a referee grade diesel fuel meeting the requirements of Military Specification MIL-F-46162B ⁽¹⁰⁾ to establish a baseline for these tests. The effects of cetane number and viscosity on the starting times for the "40" cetane number test fuels at low temperatures are shown in Fig. 1. Blend A40 produced starts at 7°C oil sump temperature without the starting aid and at 0°C and -2°C with the starting aid. The DD 6V-53T engine started readily on Blend B40, the higher viscosity fuel, at 3°C without starting aid and at -2°C with aid. The higher viscosity fuel gave quicker starts in these tests.

Fig. 2 is a plot of the test data for blends A35 and B35. At approximately 6°C oil sump temperature, five starts were attempted on blend A35, without use of the air box heater. Three tests resulted in "no starts," and two tests gave starts after 80 and 100 seconds. No starts occurred at 3°C without the air box heater or at 0°C with the heater engaged. The engine started readily on Blend B35 at 3°C without aid and as low as -3°C with the starting aid. At -4°C, the starting time was much longer, and no starts occurred at lower temperatures.




Figure 1. "40" cetane number fuels - DD 6V-53T engine

◆, ◈ - B40; ■, □ - A40




Figure 2. "35" cetane number fuels - DD 6V-53T engine

◆, ◈ - B35; ■, □ - A35

Fig. 3 shows the relationships between starting time and oil sump temperatures of blends A30 and B30 in the DD 6V-53T engine. The engine would not start on Blend A30 without or with starting aid in the oil sump temperature range of 7°C down to -1°C. With Blend B30, the engine started with the oil sump temperature at 7°C but not at lower temperatures without the air box heater. With the heater on, the lowest temperature for a start to occur was 4°C. Faster starts occurred with the higher viscosity fuel.




Figure 3. "30" cetane number fuels - DD 6V-53T engine
 ◆, ◇ - B30; ■, □ - A30

The DD 6V-53T engine appears to be limited to a 40 minimum cetane number fuel to ensure starting in cold ambient temperatures. The higher viscosity fuels produced faster starts than the lower viscosity ones.

b. LDT-465-1C Engine

The data for the cold-start tests with the LDT-465-1C engine are presented in TABLE B-2 of Appendix B. Fig. 4 depicts the cold-start performance of the "40" cetane number test fuels in the LDT-465-1C engine. The engine started on fuel A40 with relative ease at -4°C oil sump temperature. At -7°C, with assistance, the engine was more difficult




Figure 4. "40" cetane number fuels - LDT-465-1C engine
 ◆, ◇ - B40; ■, □ - A40

to start, and at -15°C , it would not start. Similar behavior occurred with fuel B40; however, more cranking time was required for the engine to start on this fuel. At -8°C , the use of the starting aid did not result in starts in two out of four attempts.

The cold-starting characteristics of the LDT-465-1C engine on fuels A35 and B35 are shown in Fig. 5. The engine started on both fuels within 20 seconds cranking time at oil sump temperatures down to -5°C without the starting aid. At -7°C and below, utilizing the manifold heater, much longer cranking times were required for starts, and at -9°C and below no starts occurred with either fuel.

Fig. 6 shows the cold start performance of the LDT-465-1C engine on test fuels A30 and B30. With fuel A30 the engine started readily without aid at -2°C . At -8°C , with starting aid engaged, starts occurred with longer cranking times, and at -10°C and -17°C the engine did not start after 120 seconds cranking time. Starts occurred with fuel B30 at -2° to -3°C after about 80 seconds cranking time. Utilizing the manifold heater with fuel B30, no starts occurred below oil sump temperatures of -9°C .




Figure 5. "35" cetane number fuels - LDT-465-IC engine
 ◆, ◇ - B35; ■, □ - A35




Figure 6. "30" cetane number fuels - LDT-465-IC engine
 ◆, ◇ - B30; ■, □ - A30

The data developed in this program indicates that the LDT-465-1C engine was started at lower temperatures than the DD 6V-53T engine on the same test fuels. The LDT-465-1C engine started more readily on the lower viscosity fuels.

c. NHC-250 Engine

The data developed in the cold-starting test with NHC-250 engine using the six-fuel test matrix are presented in TABLE B-3 of Appendix B.

The cold-start performance of the NHC-250 engine on fuel blends A40 and B40 is depicted in Fig. 7. With no starting aid, the engine started within 30 seconds cranking time at 20°C oil sump temperature with fuel A40 and at 50°C with fuel B40. Below 0°C, the NHC-250 engine started with assistance from the manifold heater within 40 seconds in every attempt. Oil sump temperatures were as low as -26°C. Start attempts with fuel B40 generally required longer cranking time as the temperature was lowered. At -20°C oil sump temperature the engine did not start in two attempts.

The cold-start performance of the NHC-250 engine with test fuels A35 and B35 is presented in Fig. 8. The cold-starting characteristics of the engine were very similar for both fuels. At 20° to 30°C oil sump temperatures, the engine started on both fuels within 30 seconds cranking time. With the manifold heater operating between 0° and -21°C oil sump temperature, all starts but one were successful within 30 seconds cranking time. One start at -20°C occurred with fuel A35 after 86 seconds cranking time.

Fig. 9 depicts the cold startability of the NHC-250 engine with the "30" cetane fuels A30 and B30. Longer cranking time was required for starts with "30" cetane fuels and at 20°C oil sump temperature, the engine did not start on fuel B30. With the starting aid, the NHC-250 engine started on fuel A30 within 32 seconds at -24°C. With fuel B30 the engine was more difficult to start, and at -24°C the engine did not start after 120 seconds cranking time.

The Cummins NHC-250 engine started readily at low temperatures, with low cetane number fuels. It was observed that the higher viscosity fuels appear to hinder the starting of the NHC-250 engine at low temperatures. It is surmised that at these low temperatures, the fuel viscosity become so high that the fuel pump can not handle it properly.




Figure 7. "40" cetane number fuels - NHC-250 engine

◆, ◇ - B40; ■, □ - A40




Figure 8. "35" cetane number fuels - NHC-250 engine

◆, ◇ - B35; ■, □ - A35




Figure 9. "30" cetane number fuels - NHC-250 engine
 ◆, ◊ - B30; ■, □ - A30

d. GM 6.2L Engine

The data for the cold-start tests with the GM 6.2L engine are presented in Table B-4 of Appendix B.

Fig. 10 shows the cold-start performance of the 6.2L engine on test fuels A40 and B40. The engine started on fuel A40 within 12 seconds cranking time with the oil sump temperature at -22°C. At -29°C, the engine did not start after 90 seconds of cranking time. With fuel B40 the 6.2L engine started about 0°C oil sump temperature, but below that temperature, no starts occurred. The Detroit Diesel Allison Division of General Motors has indicated that the Stanadyne fuel injection pump used in the 6.2L engine is designed to handle fuel with a maximum viscosity of 20 cSt.⁽¹¹⁾ It appears that this fuel, and the other high viscosity fuels in the test matrix, exceed this viscosity at the cold temperatures in this program.




Figure 10. "40" cetane number fuels - GM 6.2L engine
 ◆ - B40; ■ - A40

The cold-starting performance of the 6.2L engine on test fuels A35 and B35 is depicted in Fig. 11. The engine started on fuel A35 within 30 seconds cranking time at oil sump temperatures as low as -23°C . The engine did not start after 90 seconds at -25°C and at -29°C . With fuel B35 the engine started at 0°C within 20 seconds and at -2° to -3°C within 50 seconds in several attempts. Two tests at 0° and -6°C resulted in starts after 88 and 89 seconds cranking time, respectively. At -10°C , the engine did not start.

The cold-start tests with the 6.2L engine using fuels A30 and B30 are plotted in Fig. 12. Starts were obtained with fuel A30 within 30 seconds cranking time at -21°C oil sump temperatures. Two starts occurred at -20°C after 60 seconds cranking time, and four no-starts were observed at -19° down to -20°C . The higher viscosity fuel B30 gave scattered results. Several successful starts occurred between 4° and 16°C within 20 seconds cranking time. Between 0° and 8°C , there were starts in less than 20 seconds, some in 50 to 60 seconds and three "no starts."




Figure 11. "35" cetane number fuels - GM 6.2L engine

◆ - B35, ■ - A35




Figure 12. "30" cetane number fuels - GM 6.2L engine

◆ - B30, ■ - A30

The results of the evaluation of the GM 6.2L engine indicate that this engine appears to be more limited by viscosity for cold starting than by cetane number. However, with the A30 fuel, the engine failed to start at a higher temperature than with the higher cetane number, low viscosity fuels. The implication is that adequate cetane numbers are also important for cold startability of the GM 6.2L engine.

The viscosities of the test fuels were measured at 40° and 0°C as shown in TABLE 1. The values at 0°C for fuels B40, B35 and B30 are above the 20-cSt limit stated by Detroit Diesel Allison Division for the Stanadyne fuel injection pump used in the GM 6.2L engine. When these viscosity values are plotted on ASTM Standard Viscosity-Temperature Chart, Fig. 13, it appears that all three fuels have a kinematic viscosity of 20 cSt at about 4°C. The cold-start attempts with the 6.2L engine using these high viscosity fuels were erratic at oil sump temperatures of 0°C and below. TABLE 6 summarizes the results of the cold-starting evaluations showing effects of some selected fuel properties on cold startability.

TABLE 6. Summary of Effect of Certain Fuel Properties on Cold Startability

<u>Engine</u>	<u>Cetane Number</u>	<u>Lowest Starting Temperature, °C</u>	<u>K. Vis. at 40°C, cSt</u>
Detroit Diesel 6V-53T	38.9	0	1.13
	34.8	-3	5.20
Continental LDT-465-1C	30.2	-8	0.99
	34.8	-9	5.20
Cummins NHC-250	30.2	-24	0.99
	31.8	-20	5.69
GM 6.2L	30.2	-21	0.99
	31.8	0	5.67




Figure 13. Viscosity temperature relationships of test fuels

3. Effect of Front-End Volatility and Viscosity on Fuel Injection Systems

Under a separate phase, three different fuel injection systems from three classes of engines represented by the Continental LDT-465-1A, the Cummins NHC-250, and the Detroit Diesel 6V-53T, were evaluated on three fuels for front-end volatility and viscosity effects. The test fuels were a JP-4 (kinematic viscosity at 40°C = 0.64 cSt, 68°C at 10-percent recovered), DF-2 (kinematic viscosity at 40°C = 2.89 cSt, 207°C at 10-percent recovered), and an industrial solvent Telura® 323 (kinematic viscosity at 40°C = 21.4 cSt, 331°C at 10-percent recovered). This work was reported in "Evaluation of Three Military Diesel Injection Systems on Alternative Fuels," Interim Report BFLRF No. 214.(12) The results showed that there was no evidence of vapor lock due to front-end volatility effects at high test temperatures for any of the injection systems tested. Viscosity was observed to affect the fuel flow rate. For the LDT-465-1A and 6V-53T injection systems, fuels with relatively low viscosities tended to leak past the barrel and plunger assemblies, resulting in a decreased fuel flow rate. Leakage did not appear to be a problem with the NHC-250 injection system. The fuels with higher viscosities tended to have problems completely filling the pump in the time available, resulting also in decreased fuel flow.

In TABLE 7, the effects of front-end volatility and viscosity on the injection systems of three military engines are summarized.

TABLE 7. Summary of Property Effects on Fuel Injection Systems

<u>Engine/Injection System</u>	<u>Front-End Volatility</u>	<u>Viscosity</u>
Continental LDT-465-1A	No vapor lock	Low - leaked High -no pump filling
Cummins NHC-250	No vapor lock	Low - no leakage High - no pump filling
Detroit Diesel 6V-53T	No vapor lock	Low - leaked High - no pump filling

B. 90-Percent Distillation and End Point

Fuels with 90-percent distillation and final boiling point temperatures above the current limits for DF-2 fuels were evaluated for performance in a Petter model PH1W single-cylinder diesel engine. A reference DF-2 (Cat 1H2/1G2), an experimental referee grade Type II, and a special fuel blend with high distillation temperatures, whose properties are shown in TABLE 8, were the fuels selected for this program. Six 100-hour tests listed in TABLE 9 under controlled conditions were conducted with these two fuels and selected lubricants.

TABLE 8. Fuel Properties

Properties	ASTM Test Method	AL-14823-F Cat 1H2/1G2	AL-14751-F Type II	AL-15515-F Special Blend
Gravity, °API	D 1298	34.5	24.8	32.7
Density, kg/L at 15°C	D 1298	0.8520	0.9048	0.8613
Sulfur, wt%	D 2622	0.42	0.92	0.28
K. Vis. at 40°C, cSt	D 445	3.11	7.0	7.07
Carbon residue on 10% bottoms, wt%	D 524	0.10	0.15	0.18
Distillation, °C	D 86			
IBP		210	196	187
10% recovered		240	241	282
50% recovered		272	314	328
90% recovered		324	385	383
95% recovered		341	404	404
EP		350	404	404

TABLE 9. Fuels and Lubricants Used in Petter Engine Test

Test	Fuel	Lubricant
1-JB	Cat 1H2/1G2	MIL-L-2104D
2-JB	Type II	MIL-L-2104D
3-JB	Type II	95-cSt Oil
4-JB	Cat 1H2/1G2	95-cSt Oil
5-JB	High Boiling	100 Neutral
6-JB	Cat 1H2/1G2	100 Neutral

The lubricating oil used in Tests 1-JB and 2-JB was MIL-L-2104D (13), 30-grade reference oil, a fully compounded oil containing a high level of dispersant-detergent additive. The oil used in Tests 3-JB and 4-JB was a 95-cSt hydraulic oil that contained an oxidation inhibitor. The lubricant in tests 5-JB and 6-JB was a 100 neutral basestock with no additives. The new oil properties are shown in TABLE 10.

TABLE 10. New Oil Properties

Lubricant	Test Method	MIL-L-2104D	Hydraulic Oil	100 Neutral
		AL-14726-L	AL-15201-L	AL-15709-L
K. Vis. at 40°C, cSt	D 445	95.8	95.2	20.04
K. Vis. at 100°C, cSt	D 445	11.1	10.7	4.00
Viscosity Index	D 2270	101	95	92
Total Acid No., mg KOH/g	D 664	2.6	0.75	0.01
Total Base No., mg KOH/g	D 664	7.4	0.25	0.10

The data for the six tests conducted in this phase are shown in TABLE 11. Tests 1-JB and 2-JB, which used the MIL-L-2104D lubricant, resulted in very clean engine parts attributed to the detergency in the oil. Engine wear based on used oil iron content was very similar for both tests. The use of high sulfur fuel in test 2-JB resulted in a slightly lower used oil total base number. Unexplained high used oil copper content was observed in test 1-JB. Tests 3-JB and 4-JB, using the nondispersant oil, showed differences that could be due to the different fuels. As indicated by the higher iron content of the used oil, Test 3-JB with the Type II fuel showed more wear than Test 4-JB using the Cat 1H2/1G2 fuel. This difference could be due to the higher sulfur content of the Type II fuel. Test 5-JB, with the high boiling fuel and 100 neutral lubricant, showed a higher level of wear (based on the iron content in the used oil) and measured ring wear than Test 6-JB with Cat 1H2/1G2 fuel and 100 neutral lubricant. The piston weighted total demerits (WTD) rating was slightly worse with the Cat 1H2/1G2 fuel. Although the lubricant thickened considerably in all the tests, it was proportionally more pronounced with the 100 neutral, which had no additives present.

The high boiling fuel may have caused a higher wear rate in Test 5-JB; however, the evidence is not conclusive. The data obtained in this series of tests with the Petter

TABLE 11. 100-Hour Petter Engine Test Results

Test No. Fuel	1-JB Cat 1H2/1G2	2-JB Type II	3-JB Type II	4-JB Cat 1H2/1G2	5-JB High Boiling	6-JB Cat 1H2/1G2
Used Oil Properties						
K. Vis., 40°C, cSt	104.01	119.25	149.61	153.35	48.03	92.72
K. Vis., 100°C, cSt	13.01	15.46	25.42	26.93	17.85	37.82
TAN, mg KOH/g, D 664	3.67	3.91	1.93	1.33	0.74	0.92
TBN, mg KOH/g, D 664	6.09	4.66	0.01	0.22	0.07	0.01
Pentane Insolubles "A", %	0.21	0.59	3.59	3.25	3.80	5.15
Toluene Insolubles "A", %	0.18	0.55	3.38	3.08	3.63	5.03
Pentane Insolubles "B", %	2.90	4.55	3.52	3.18	3.76	5.13
Toluene Insolubles "B", %	2.73	4.31	3.30	2.99	3.49	4.91
Fuel Dilution, %	1.0	0.5	0.2	0.8	0.09	0.95
Metals, XRF						
Fe, ppm	82	65	233	90	480	230
Cu, ppm	150	< 10	< 10	< 10	< 10	< 10
Cr, ppm	< 15	< 15	< 15	< 15	40	< 10
Pb, ppm	< 60	< 60	< 60	< 60	< 60	< 60
S, %	0.56	0.58	0.40	0.35	0.10	0.11
ICP, Elements, ppm						
Fe	101	79	261	86	491	208
Cr	1	1	1	3	31	25
Cu	203	13	12	8	8	9
Si	14	6	17	6	8	5
Pb	28	1	2	< 1	< 1	< 1
Zn	1485	1592	353	346	14	9
P	1269	1276	420	331	125	31
Mg	1715	1854	11	3	4	2
Piston WTD Rating	19.6	18.8	135.2	149.1	142.2	162.6
Ring End Gap, in.	0.003	0.001	0.005	0.003	0.012	0.003
Ring Side Clearance, in.	0.001	0.001	0.000	0.000	0.000	0.000
Liner Avg. Wear, in.	0.0007	0.0001	0.0002	0.0003	0.0001	0.0002
Lubricant	— MIL-L-2104D —		Hydraulic	Hydraulic	100 Neutral	100 Neutral
	Grade 30	Grade 30	Oil	Oil		
Oil Sump Temp., °F (°C)	168 (76)	169 (76)	170 (77)	172 (78)	168 (76)	168 (76)
Oil Consumption, lb.	3.75	4.23	1.05	2.52	3.88	6.97
Coolant Out Temp. °F (°C)	179 (82)	179 (82)	180 (82)	180 (82)	180 (82)	179 (82)
Fuel Rate, lbs/hr	3.80	3.80	3.79	3.80	3.81	3.81
Load, lb-ft	26.8	27.5	26.9	24.8	28.9	26.1

engine do not provide a basis for recommending changes in the limits for the maximum 90 percent and end point distillation temperatures in Federal Specification VV-F-800D.

C. Accelerated Stability

VV-F-800D diesel fuels are required to meet the accelerated stability limit of 1.5 mg/100 mL maximum total insolubles. It is presumed that fuels failing this requirement

may cause injector fouling to occur in engines operating on the nonspecification fuel for an undetermined time period. A procedure being developed at Belvoir Fuels and Lubricants Research Facility (BFLRF) at Southwest Research Institute (SwRI) for evaluating injector nozzle fouling tendencies of fuels was utilized to evaluate a series of fuels with accelerated stability values both within and above the specification limits.⁽¹⁴⁾ The Injector Fouling Bench Test (IFBT) employed in this program was described in Appendix B of the report "Thermal Oxidative Stability of Diesel Fuels," Interim Report BFLRF No. 205 ⁽¹⁵⁾, and is Appendix C of this report.

The IFBT was conducted with two injector systems: the Detroit Diesel and the Bosch APE 113 injectors. For each injector system, the procedure requires 22 gallons of fuel heated to 78°C and injected through the heated nozzle so that the fuel spray temperature is about 288°C. Each test is run 8 hours per day for five days for a total of 40 hours. The procedure is described in more detail in Appendix C. Six fuels have been evaluated in this program, and their properties are shown in TABLE 12. The fuels include a reference DF-2, a commercial diesel fuel, a MIL-F-46162B referee grade fuel with no stabilizer additive, a MIL-F-46162B referee grade fuel with the stabilizer additive, an experimental referee grade Type II fuel, and a naval distillate fuel. Both the MIL-F-46162B referee fuels were prepared from the same base fuel.

The results of seven tests are shown in TABLE 13 for Detroit Diesel injector and in TABLE 14 for the Bosch system. The first test conducted in both systems was with Cat 1H2/1G2 as the test fuel. The test in the Detroit Diesel system was not completed because the temperature of the nozzle tip heating block was excessively high at the beginning. Some wires in the apparatus were damaged and had to be replaced. The pintle eventually stuck, and the test was stopped. The Bosch system was operational during the first test, but the fuel supply was exhausted at 39.5 hours.

The last three items in TABLES 13 and 14 - Airflow, Pintle Demerits, and Tube Deposit Ratings - are approaches to measuring the deposits or effect of deposits formed on the injector pintles while flowing the hot test fuel through the injection system for 40 hours. Airflow is measured through the clean injectors before the test and after 40 hours of test. Any loss in airflow represents the restriction in the injector caused by deposits formed on the pintle and orifice surfaces. Pintle demerits represent a visual rating of the deposits on the pintle surfaces based on a CRC scale. Tube deposit ratings are

TABLE 12. Fuel Properties

Properties	ASTM Test Method	AL-14823-F	AL-14941-F	AL-14940-F	AL-14948-F MIL-F-46162B With MIL-S-53021 Stabilizer	AL-14751-F	AL-13279-F
		Cat 1H2/1G2	Lo S Diesel	MIL-F-46162B With No Stabilizer		Type II Ref. Gr.	MIL-F-16884H NDF
Gravity, °API,	D 1298	34.5	33.7	31.6	31.2	24.8	35.2
Density at 15°C,	D 1298	0.8520	0.8526	0.8671	0.8692	0.9048	0.8484
Distillation, °C	D 86						
IBP		210	177	172	173	196	192
10% recovered		240	223	207	204	231	222
50% recovered		272	291	271	276	314	262
90% recovered		324	332	337	339	385	322
End point		350	373	367	371	>404	348
% residue		1.5	1.0	1.5	1.0	ND*	1.5
Flash point, °C		88	74	67	62	83	77
Cloud point, °C		-9	-2	-16	-18	-19	-11
Pour point, °C		-13	-3	-23	-23	-25	-30
K. Vis. at 40°C,							
cSt	D 445	3.11	3.31	2.86	2.94	7.0	2.75
Cetane number	D 613	50.5	50.5	48.0	43.3	40.2	50.5
Cetane index	D 976	47.7	49.5	42.6	43.1	39.3	46.6
Sulfur, wt%	D 2622	0.42	0.12	1.02	1.05	0.92	0.20
Total Acid No., mg KOH/g	D 664	0.02	0.04	0.01	0.03	ND	0.09
Cu corrosion, 3 hr at 99°C	D 130	1A	1A	1A	1A	1A	1A
Ash, wt%	D 482	<0.01	<0.001	0.001	<0.001	<0.01	0
Carbon residue on 10% bottoms, wt%	D 524	0.01	0.13	0.17	0.13	0.15	0.16
Carbon, wt%	D 3178	86.35	86.66	85.89	86.28	ND	86.12
Hydrogen, wt%	D 3178	12.95	12.69	12.31	12.31	ND	12.89
Net heat of combus- tion,	D 240						
MJ/kg		42.586	42.327	42.033	42.124	ND	42.68
Btu/lb		18,309	18,200	18,071	18,110	ND	18,349
Existent gum, mg/100 mL	D 381	10.1	7.1	24.2	7.5	326	29.5
Accelerated stability, mg/100 mL	D 2274	3.97	0.17	0.23	1.74	0.56	3.24
Particulates, mg/L	D 2276	2.5	0.8	1.8	5.3	6.5	103
Appearance	D 4176	C and B	C w/s tr sed	Cloudy	C and B	ND tr sed	ND

* ND = Not determined.

another means of evaluating the pintle deposits using two different procedures: a visual rating scale and a light reflectance measuring device. These rating techniques were adapted from procedures used for rating JFTOT tubes in ASTM D 3241. Another technique also used to evaluate the extent of deposits formed on the pintle surfaces was the Deposit Measuring Device developed at BFLRF. This technique measures the dielectric strength of the deposits. The dielectric rating can then be converted to deposit thickness. Measurements are made at numerous points all along the surface of the pintle.

TABLE 13. Detroit Diesel IFBT Operating Conditions and Test Results

Test No. Code No.	Test 1D AL-14823-F	Test 2D AL-14823-F	Test 3D AL-14941-F	Test 4D AL-14940-F	Test 5D AL-14948-F MIL-F-46162B	Test 7D AL-14751-F	Test 10D AL-13279-F
Fuel	Cat 1H2/1G2	Cat 1H2/1G2	Low S Diesel	MIL-F-46162B With No Stabilizer	MIL-S-53021 With Stabilizer	Type II Referee Grade	MIL-F-16884H NDF
Test hours	37*	40	40	40	40	40	40
Speed rpm	1000	1000	1000	1000	1000	1000	1000
Fuel flow, gal/h	-	-	-	-	-	-	-
Fuel reservoir temp, °C, avg	79	79	78	78	77	78	78
Spray temp, °C, avg	280	263	261	260	261	260	260
Nozzle tip heating block temp, °C, avg	-	303	308	321	320	315	314
Injection pressure, psi before/after	-	139/143	138/132	144/142	137/136	135/133	142/138
Leak down, (dP: 15 sec minimum) before/after	-	30/stuck	26/23	38/32	52/28	48/55	51/46
Fuel flow, mL/1000 strokes before/after	-	89/8	96/96	96/93	94/94	93/94	94/92
Airflow gauge before/after	-	6/stuck	6.5/5.0	5.2/3.8	5.0/4.7	4.5/4.45	2.8/2.85
Percent loss	-	(2)**	24	27	6	1.1	(1.8)
Pintle demerits	-	-	-	-	-	-	-
Nonrubbing	-	8.85	7.25	8.75	6.40	2.80	6.70
Rubbing	-	6.60	5.20	6.40	6.15	5.25	6.55
Tip	-	5.66	5.75	4.20	5.80	5.20	6.35
Tube deposit rating (TDR)***	-	-	-	-	-	-	-
Spun/station	43/31	46/31	37/27	43/26	39/47	25/30	38/47
Visual rating	4	4.5	4.5	4.5	4	4	4

* During the first two hours of this test, the nozzle tip heating block temperature was well above 600°F, which may have distorted the pintle.

** Number in () represent a gain in airflow.

*** Highest TDR measured on pintle. See Appendix C.

TABLE 14. CLR-D Bosch APE 113 IFBT Operating Conditions and Test Results

Test No. Code No.	Test 1B AL-14823-F	Test 2B AL-14823-F	Test 3B AL-14941-F	Test 4B AL-14940-F	Test 5B AL-14948-F MIL-F-46162B With MIL-S-53021 Stabilizer	Test 7B AL-14751-F Type II Referee Grade	Test 10B AL-13279-B MIL-F-16884H NDF
Fuel	Cat 1H2/1G2	Cat 1.2/1G2	Low S Diesel	MIL-F-46162B With No Stabilizer			
Test hours	39.5	40	40	40	40	40	40
Speed rpm	1000	1000	1000	1000	1000	1000	1000
Fuel flow, gal/h	-	-	-	-	-	-	-
Fuel reservoir temp, °C, avg	78	78	78	78	77	77	77
Spray temp, °C, avg	261	261	261	260	261	261	260
Nozzle body heating block temp, °C, avg	153	155	154	154	159	159	150
Nozzle tip heating block temp, °C, avg	311	316	306	295	295	297	283
Injection pressure, psi before/after	2500/2400	2500/2375	2500/2500	2500/2440	2500/2500	2500/2450	2500/2450
Spray pattern before/after	VG*/G**	VG/VG	VG/VG	VG/VG	VG/VG	VG/VG	G/VG
Airflow, cu. ft./min at 100% lift before/after	0.090/0.086	0.085/0.087	0.121/0.093	0.903/0.076	0.085/0.078	0.082/0.076	0.0815/0.08
Percent loss	4.4	(2.4)**	23	18.9	8.2	7.2	0
Pintle demerits	4.60	5.85	3.20	4.75	4.85	2.20	2.70
Nonrubbing	2.75	3.35	3.25	6.45	5.30	0	1.05
Rubbing	5.55	5.25	7.25	7.60	7.60	5.05	6.90
Tip							
Tube deposit rating (TD%R)****	34/72	26/70	20/72	31/42	33/48	9/47	23/69
Spun/station	4+	3.5	3.5	4.5	4.5	2	2.5
Visual rating							

* VG - Very good.

** G - Good.

*** Number in () represents gain in airflow.

**** Highest TDR measured on pintle. See Appendix C.

Graphical representation of the data from these tests are shown in Figs. 14 through 21. Figs. 14 and 15 depict in bar charts the demerit ratings for the pintles from the Detroit Diesel and the Bosch systems, respectively, for each fuel. It is obvious that these ratings do not correlate with the accelerated stability values of the fuels. Figs. 16 and 17 are plots of percent airflow loss versus accelerated stability in the Detroit Diesel and Bosch systems. The unexpected trend observed in these plots is that the airflow loss is lower with the fuels having higher accelerated stability values. Figs. 18 and 19 show the TDR spun ratings plotted against accelerated stability ratings for the Detroit Diesel and Bosch systems, respectively. No correlation between TDR spun ratings and accelerated stability values is apparent. The last set of plots, Figs. 20 and 21, show the dielectric strength of the deposits formed by each fuel versus the accelerated stability values. As indicated earlier, the dielectric strength was measured at numerous points along the surface of the pintles. The values used in these plots were the highest measured values for each test fuel. Again there is no apparent correlation between the DMD measurements and accelerated stability values.




Figure 14. Pintle demerits for Detroit Diesel IFTB




Figure 15. Pintle demerits for Bosch APE 113 IFBT




Figure 16. Airflow for Detroit Diesel IFBT




Figure 17. Airflow for Bosch APE 113 IFBT




Figure 18. TDR for Detroit Diesel IFBT




Figure 19. TDR for Bosch APE 113 IFBT




Figure 20. DMD for Detroit Diesel IFBT




Figure 21. DMD for Bosch APE 113 IGBT

No correlation between D 2274 stability, D 3241 (thermal stability) breakpoint temperature of tube deposit, and IGBT pintle deposits (based on average deposit breakdown voltage by DMD) was apparent for the data summarized in TABLE 15. Based on these data, it appears that the level of accelerated stability is not the only fuel property that affects deposit formation on the pintles of the Detroit Diesel and the Bosch injector systems used in the Injector Fouling Bench Test procedure. The data do not provide a basis for recommending a variation in the level of accelerated stability limit as stated in VV-F-800D.

D. Carbon Residue

The carbon residue test is a measure of the carbonaceous material left in a fuel after all the volatile components are vaporized in the absence of air under prescribed test conditions. It is thought to give an approximation of the carbon-depositing tendencies of a fuel. Federal Specification VV-F-800D for diesel fuel, Grade DF-2, has a requirement

TABLE 15. Results of Stability Tests Compared to IFBT Pintle Deposits
(December 1986)

AL-Code Number	Fuel Description	Accelerated Stability, D 2274		Thermal Oxidation Stability Test, D 3241					Volume of Deposit by DMD, cm ³ X 10 ⁻⁷
		Total Insolubles, mg/100 mL	Test No.	Temperature, °C (°F)	Breakpoint Temperature*, °C	Change in Pressure, mm of Hg	Preheater Deposit Code	TDR Spun Deposit Rating	
14823-F	Cat 1H2/1G2 Diesel	4.0	1163-J	232 (450)	260	0	0	0	25
			1165-J	238 (460)		0	<2	8 at 51	43
			1168-J	243 (470)		0	<3 (Blue)	5 at 51	31
			1161-J	246 (475)		0	<3 (Blue)	4 at 48	32
			1176-J	260 (500)		0	<3 (Blue)	5 at 51	39 (80)*
14941-F	Low Sulfur Diesel	0.2	1178-J	232 (450)	240	0	2 (Blue)	4 at 51	36
			1170-J	246 (475)		0	3	10 at 51	55
			1174-J	260 (500)		0	>4P	14 at 51	112 (100)*
14940-F	MIL-F-46162B With No Stabilizer	0.2	1169-T	191 (375)	191	0	4P	37 at 48	29
			1166-T	218 (425)		0	>4P	32 at 40	45
			1164-T	232 (450)		3 at 150 min	>4P	35 at 32	38
			1162-T	246 (475)		125 at 92 min	>4P	30 at 26	40
			1177-T	260 (500)		125 at 41 min	>4P	27 at 22	48 (93)*
14948-F	MIL-F-46162B With MIL-S-53021 Stabilizer	1.7	1173-T	232 (450)	254	0	2	8 at 51	61
			1171-T	246 (475)		0	<3	10 at 51	43
			1204-G	252 (485)		0	<3	9 at 44	30
			1175-T	260 (500)		0	>4	16 at 51	69 (55)*
13279-F	MIL-F-16884-H NDF	3.2	1408-J	232 (450)	241	1 at 150 min	<2	12 at 54	54
			1411-J	288 (460)		0	<2	15 at 54	70
			1414-J	240 (464)		0	2	14 at 54	51
			1412-G	242 (468)		36 at 150 min	3	27 at 54	79
			1410-G	246 (475)		125 at 89 min	>4	25 at 54	72
			1413-G	260 (500)		125 at 37 min	>4	31 at 53	676 (404)*
14751-F	Type II Referee Grade	0.6	1370-J	204 (400)	206	0	1	6 at 51	37
			1372-J	208 (406)		0	<4	11 at 51	65
			1371-J	210 (410)		0	4	12 at 51	31
			1369-J	213 (415)		0	>4	12 at 44	47
			1368-J	218 (425)		0	>4	12 at 43	51
			1373-J	260 (500)		0	>4P	35 at 38	235 (75)*

* Breakpoint temperature, Code 3 inception temperature approximation.

** Simple addition of voltage reading along length of pintle divided by number of stations (31 for the Bosch and 24 for the Detroit).

+ Values determined in early 1988.

of 0.35 wt% maximum, carbon residue on 10-percent bottoms, measured by the Ramsbottom carbon residue procedure, ASTM D 524.

To attempt to determine the effect of a fuel with over-specification-limit carbon residue value, 99.65 vol% of a reference fuel (Cat 1H2/1G2) with a carbon residue on 10-percent bottoms value of 0.01 wt%, was blended with 0.35 vol% of marine fuel oil that had a carbon residue of 13.5 wt%. The resulting blend had a carbon residue on 10-percent bottoms value of 0.54 wt%. The properties of the Cat 1H2/1G2 fuel are given in TABLE 10, those of the marine fuel oil are shown in TABLE 16, and those for the blend are given in TABLE 17. As can be observed, the addition of the small amount of marine fuel oil to the reference fuel had a great effect on the accelerated stability, particulate contaminant, and existent gum values, which was not altogether anticipated.

TABLE 16. Properties of Marine Fuel Oil Sample

Fuel Sample No.	Test Method	Marine F.O. FL-0348-F
Gravity, °API	D 287	12.0
Specific Gravity, 60°F		0.9861
Density, lb/gallon		8.212
Viscosity at 104°F (40°C), cSt	D 445	710.71
at 122°F (50°C), cSt	D 445	328.88
Flash Point, °F	D 93	199
Carbon Residue, wt%	D 524	13.5
Sulfur, wt%	XRF	2.40
Corrosion, Cu. Strip, 50°C	D 130	1B
Pentane Insolubles, wt%	D 893	10.10
Toluene Insolubles, wt%	D 893	1.69
Carbon, wt%	--	86.52
Hydrogen, wt%	--	10.40
Heat of Combustion	D 240	
Gross, Btu/lb		17,966
Net, Btu/lb		17,016
Net, Btu/gallon		139,735

TABLE 17. Test Fuel Blend

<u>Composition</u>	<u>AL-16238-F</u>
Cat 1H2/1G2, vol% (AL-15706-F)	96.65
Marine Fuel Oil, vol% (FL-0348F)	0.35
<u>Properties</u>	
Gravity, °API	34.1
Density at 15°C	0.8540
Visual Appearance	Dark
Color, D 1500	>8
Flash Point, °C	84
Pour Point, °C	-21
Distillation, °C	
IBP	209
10% recovered	241
50% recovered	273
90% recovered	323
End Point	348
% Residue	1
% Recovered	99
Kinematic Viscosity at 40°C	3.17
Accelerated Stability, mg/100 mL	10.2
Particulate Contaminants, mg/L	27.3 mg/100 mL
Existent Gum, Steam Jet, mg/100 mL	201
Sulfur, wt%	0.42
Cu Corrosion, 3 hr at 50°C	1A
Ash, wt%	<0.01
Total Acid Number, mg HOH/100 g	0.03
Cetane Number	48
Cetane Index	47
Carbon Residue on 10% Bottoms	0.54
Water, Karl Fischer Method, ppm	192
JFTOT at 260°C	
ΔP	0*
Visual Rating	>4 (P)
DMD Maximum Thickness, cm x 10 ⁻⁷	285 at 32
Deposit Volume, cm ³ x 10 ⁻⁷	637

* Filter plugged at 100 minutes and was removed to complete test.

The blend, identified as AL-16238-F, was used in an injector fouling bench test, employing the Detroit Diesel and the Bosch APE 113 injector systems. The results of the 40-hour test are given in TABLE 18 for the Detroit Diesel and TABLE 19 for the Bosch. Tests of the airflow through the injector nozzles for both systems, before and

**TABLE 18. Detroit Diesel IFBT Operating Conditions
and Test Results**

Test No. Code No. Fuel	<u>Goal</u>	Test 11D AL-16238-F High Carbon Residue Fuel
Test Hours	40	40
Speed rpm	1000	1000
Fuel Flow, gal/h	0.5	--
Fuel Reservoir Temp., °C, Avg.	--	80
Spray Temp., °C, Avg.	288	260
Nozzle Tip Heating Block Temp., °C, Avg.	--	303
Injection Pressure, psi		
Before/After	--	152/140
Leak Down, (dP: 15 sec Minimum)		
Before/After	--	58.9/53.6
Fuel Flow, mL/1000		
Strokes Before/After	--	98/90
Airflow Gauge		
Before/After	--	2.88/1.95 (Pintle Stuck)
Percent Loss	--	32
Pintle Demerits		
Nonrubbing	--	8.60
Rubbing	--	6.50
Tip	--	7.55
Tube Deposit Rating (TDR)		
Spun/Station	--	44/30
Visual Rating	--	4
DMD, average voltage	--	40

**TABLE 19. CLR-D Bosch APE 113 IFBT Operating
Conditions and Test Results**

Test No. Code No. Fuel		Test 11B AL-16238-F High Carbon Residue Fuel
	<u>Goal</u>	
Test Hours	40	40
Speed rpm	1000	1000
Fuel Flow, gal/h	0.5	--
Fuel Reservoir Temp., °C, Avg.	--	79
Spray Temp., °C, Avg.	288	257
Nozzle Body Heating Block Temp., °C, Avg.	154	155
Nozzle Tip Heating Block Temp., °C, Avg.	404	293
Injection Pressure, psi Before/After	--	2500/2500
Spray Pattern Before/After	--	VG*/VG
Airflow, cu. ft/min at 100% Lift Before/After	--	0.0816/0.0535
Percent Loss	--	34
Pintle Demerits		
Nonrubbing	--	4.90
Rubbing	--	3.25
Tip	--	6.65
Tube Deposit Rating (TDR)		
Spun/Station	--	29/73
Visual Rating	--	4
DMD, average voltage	--	29

* VG = Very Good.

after the 40-hour runs, gave a 32-percent reduction for the Detroit Diesel (which also had a stuck pintle) and 34-percent reduction for the Bosch system. The reduction in airflow apparently was caused by deposits formed in the injectors; however, these deposits cannot be attributed solely to the high carbon residue value for this fuel since existent gum, accelerated stability, and particulate content were also high.

V. SUMMARY OF RESULTS

The overall conclusion from this work is that the fuel properties investigated cannot be relaxed to any significant extent and still permit optimum performance in all the engines and components currently in the Army system, under all climatic conditions.

Based on the cold-starting work reported here, the cetane number limit cannot be lowered below the current 40 minimum because the DD 6V-53T engine does not start readily in cold temperatures on low cetane number fuel. There may be other engines in the system that have low tolerance for low cetane number fuels. In contrast, the LDT-465-1C, the NHC-250, and 6.2L engines started at much lower temperatures on lower cetane number fuel. The data in this work tend to indicate that the NHC-250 is the most tolerant toward cetane number of the engines tested in this program.

The evaluation of viscosity effects show that the injection systems are critically affected by the viscosity of the fuel. For the LTD-465 and the 6V-53T systems, fuels with low viscosities tended to leak past the barrel and plunger assemblies, resulting in a decreased flow rate. The fuels with higher viscosities tended not to fill the pump in the time available, also resulting in decreased fuel flow. The DD 6V-53T engine appeared to start more readily on higher viscosity fuels of equivalent cetane number. The LDT-465-1C and the NHC-250 engines started more readily on the lower viscosity fuels. Personnel at Detroit Diesel Allison have stated that the injection pump used in the 6.2L engine is limited to handling fuel with a maximum kinematic viscosity of 20 cSt; therefore, when higher viscosity fuels are chilled, they cannot be injected into the combustion chamber. Due to the characteristics of different engines and injection systems, it is concluded that current viscosity limits in VV-F-800D cannot be varied significantly.

Under certain specific conditions, fuels with cetane numbers lower than 40, perhaps as low as 35, could be used. These conditions are: 1) in cold climates if no sensitive engines such as the 6V-53T are in the fleet and 2) in warm climates where the ambient temperature will not go below 7°C (45°F).

The evaluation of fuels with high 90-percent and end-point distillation did not provide conclusive data for recommending variations to distillation limits found in Federal Specification VV-F-800D.

The data developed with seven different fuels having a range of accelerated stability values evaluated in the Injector Fouling Bench Test with the Detroit Diesel and Bosch injector systems showed little, if any, correlation between the level of accelerated stability values and injector plugging. Apparently other fuel properties also affect the level of deposit formation in the injectors of these systems.

The fuel with high carbon residue value evaluated on the Injector Fouling Bench Test resulted in significant deposit formation in both the Detroit Diesel and Bosch injection systems; however, these deposits cannot be attributed solely to the carbon residue value, since other properties of this fuel were excessively over limits.

VI. CONCLUSIONS

Variations in the limits of the properties investigated cannot be recommended for Federal Specification VV-F-800D; however, an example of a variable quality diesel fuel specification is shown in Appendix D.

Opportunities exist for relaxing some of the VV-F-800 specification requirements without impacting vehicle operations. An obvious area is relaxing the cetane and upper viscosity limits in regions where the ambient temperature remains above 7°C. Relaxed fuel properties can improve fuel availability (cost and quality related) to commanders for local procurements over limited time periods for accomplishing high fuel quantity maneuvers. Increased maintenance (reduced oil change period and fuel filters, and premature maintenance for unstable fuels) may be experienced with prolonged use of relaxed specification fuels. Economic advantages of low-viscosity (low-density) fuels may be offset by higher fuel volume use to accomplish equivalent missions. High-energy content (high-density) fuels may lead to engine overfueling and increased visible signature (smoke). Minimum relaxed deviations from VV-F-800 specifications in the direction of fully relaxed values in the variable quality fuel specification could cause reduced engine power, performance, and endurance debits. Appendix D presents an

example of a variable quality fuel specification compared with the standard VV-F-800 and the emerging ASTM emergency fuel requirements.

Since fuel physical properties are all reflections of the fuel's underlying chemical structure, these physical properties are necessarily interrelated, as illustrated in Appendix E. Engine response to fuel physical and chemical properties is a complex function of all these properties, while the current specifications place limits on each individual property. The specifications thus may not adequately consider synergistic effects in fuel properties. This synergism can be seen in the impacts of both fuel viscosity and cetane number on startability in the Detroit Diesel 6V-53T engine (Fig. 1). Based on this figure, for example, the cetane requirement could be reduced as fuel viscosity increased.

There is potential for relaxing other specification requirements, but with some long-term disadvantages. These disadvantages could include increased routine maintenance, shortened engine life, or increased component replacement rates. Unfortunately, there is insufficient data to quantify these costs.

VII. RECOMMENDATIONS

The following actions for development of variable quality fuels specifications are recommended:

- Improve bench tests for correlation of properties with engine dynamometer tests and full-scale vehicle performance.
- Develop vehicle/equipment performance models for variable quality fuels.
- Conduct limited vehicle tests to validate practical limits of a variable quality fuel specification developed from performance model(s).
- Initiate development of specification handbook and expert system for proper implementation of locale-dependent variable quality fuel specification.

A de facto variable quality fuel specification currently exists in the Defense Fuel Supply Center (DFSC) specification waivers. Formalization of this system by allowing additional waiver opportunities may encourage fuel suppliers to further reduce the quality of fuels offered to the government without compensating reductions in cost. This

possibility could be investigated by determining if DFSC issuance of a waiver to a fuel supplier increases the likelihood of the supplier requesting other waivers.

Fuel properties affect the costs of operation of a vehicle, and a procurement specification is an attempt to control these costs to a minimum level consistent with obtaining adequate supplies of fuel. The current VV-F-800 specification is based on experience in balancing fuel costs, fuel availability, and vehicle operating costs. The cost impacts of variations in individual fuel properties needs to be studied so that informed decisions on either granting waivers (current system) or allowing regional adjustments in specification limits (variable quality) can be made. Such a cost study would be valuable even without a variable quality fuel specification, if properly applied. For example, one could visualize an expert system that would provide DFSC cost estimates of the increase in fleet operating costs, in cents per gallon, that would result from fuel specifications that depart from some optimal value. This estimate would be used in evaluating fuel bids in order to procure fuels that would minimize total fleet operating costs.

VIII. REFERENCES

1. The Army Mobility Fuels Research and Development Plan, Belvoir Research, Engineering and Development Center, 13 May 1983.
2. Service Plan on Army Mobility Fuels Research and Development Program, Belvoir Research, Engineering and Development Center, 15 September 1983.
3. Westbrook S.R., et al., "Establishment of Procedural Methodology and Data Interpretation for Fuel Quality Evaluation," Interim Report BFLRF No. 212, AD A173872, March 1986.
4. Federal Specification VV-F-800D, Fuel Oil, Diesel, October 27, 1987.
5. Technical Manual TM 9-2300-230-10, Operator's Manual (Crew) for Armored Reconnaissance/Airborne Assault Vehicle, 10 June 1976.
6. Montemayor, A.F., Owens, E.C., "Fuel Property Effects on the Unaided Cold Starting of a Two-Cycle Diesel Engine," Interim Report BFLRF No. 186, AD A162658, December 1985.
7. Technical Manual TM 9-2320-209-10-1, Operation, Installation and Reference Data, Operator Level for 2.5-ton 6x6 M44A1 and M44A2 Series Trucks (Multifuel), September 1980.
8. Technical Manual TM 9-2320-260-10-1, Operation, Installation and Reference Data, Operator Level for 5-ton 6x6 M809 Series Trucks (Diesel), August 1980.

9. Technical Manual TM 9-2320-280-10, Operator's Manual for the High Mobility Multi-Purpose Wheel Vehicle (HMMWV) M998 Series Vehicle, April 1985.
10. Military Specification MIL-F-46162B, Fuel, Diesel, Referee Grade, 14 August 1981.
11. Letter (Attachment I) to Mr. David A. Patterson, Administrative CUCV Service, Chevrolet Central Office, from Donald A. Brownson, 6.2L Product Engineering, Detroit Diesel Allison, dated 23 June 1986.
12. Callahan, T.J., Bowden, J.N., "Evaluation of Three Military Diesel Injection Systems on Alternative Fuels," Interim Report BFLRF No. 214, AD A180257, February 1987.
13. Military Specification MIL-L-2104D, Lubricating Oil, Internal Combustion Engine, Tactical Service, 1 April 1983.
14. Stavinocha, L.L., Yost, D.M., Barbee, J.G., "Thermal Stability of Diesel Fuels," Paper presented at 2nd International Conference on Long-Term Storage of Liquid Fuels, San Antonio, TX, July 29 - August 1, 1986.
15. Stavinocha, L.L., Barbee, J.G., Yost, D.M., "Thermal Oxidative Stability of Diesel Fuels," Interim Report BFLRF No. 205, AD A173850, February 1986.

APPENDIX A
Army Cold Startability Procedure

APPENDIX A

Army Cold Startability Procedure

8:00 AM

Check battery condition by measuring and recording hydrometer reading and temperature for each cell of the batteries.

Disconnect battery charger.

Record the before test information on the data form.

Reset the timer.

Turn on chart recorder.

Crank engine until it starts, according to procedure for each engine, for a maximum of 2 minutes (1.5 minutes for the GM 6.2L).

Record the after information on the data form.

Turn off chart recorder.

Connect battery charger.

3:00 PM

Repeat above procedure on same fuel.

Change fuel as indicated below after 2 valid runs on each fuel.

Turn off cooling.

Remove the suction line and return line from the fuel can. Place the suction line into the can containing approximately 1 gallon of the new fuel. Place the return line into the dump can.

Fire the engine, letting it run for 20 seconds before shutting down.

Change the secondary filter.

Fire the engine and run at least 1 gallon of the new fuel through the engine. The fuel should be emptied from the engine into the dump can. After 1 gallon has been run through, shut down the engine.

Place both fuel lines into the fuel can containing 1 gallon of new fuel. Fire the engine and burn approximately 0.25 gallons of fuel while the engine runs at 800 to 900 rpm. After 0.25 gallons has been burned, shut down the engine.

Refill the fuel can with the test fuel and turn on the cooling for the next day's testing.

APPENDIX B
Cold-Start Test Data

TABLE B-1. Cold-Start Tests
With DD 6V-53T Engine

	AI No	Test No	Date	Time	Cranking Speed, rpm	Sec. to Start*	Fuel at Before, lb	Fuel at After, lb	Fuel Used, lb	Wear In Before, in	Wear In After, in	Oil Temp Before, °C	Oil Temp After, °C	Air Box Before, °C	Air Box After, °C	Exhaust Before, °C	Exhaust After, °C	Fuel Before, °C	Fuel After, °C	Kinematic Visc. at 50°C	Starting Mode	Sec Temp, °C
Reference	13998	1. 4-24	000	205	3.8	3.31	3.26	.05	19.1	20.8	16.2	18.8	18.9	19.4	15.4	42.8	19.4	19.3	3.35	n	10.0	
	13999	2. 4-25	000	200	120.0	2.78	2.62	.16	2.2	3.2	1.2	2.0	2.1	2.1	1.9	56.1	1.6	1.6	5.2	n	1.7	
	13999	3. 5-6	1400	224	95.4	1.59	1.26	.33	3.8	9.0	2.9	12.0	3.6	6.0	3.1	56.1	3.2	3.6	4.9	n	1.7	
	13999	4. 5-7	000	226	94.8	1.29	.928	.37	3.8	13.9	2.6	19.9	3.5	1.6	3.1	60.6	2.3	3.4	4.9	n	1.7	
	13999	5. 5-7	1400	225	94.1	2.51	2.19	.32	3.6	10.1	2.7	10.7	3.6	4.3	1.5	55.6	1.1	4.5	6	n	1.7	
	13999	6. 5-8	000	220	92.2	2.20	1.78	.42	3.6	14.6	1.6	20.4	3.4	7.9	1.2	61.7	1.3	3.6	4.9	n	1.7	
	13999	7. 5-8	1500	230	88.3	1.83	1.47	.36	3.8	12.2	1.3	19.2	3.6	3.2	1.1	61.1	1.2	3.8	4.2	n	1.7	
A40	14010	8. 5-9	000	232	120.0	2.97	2.79	.18	3.8	5.4	1.4	5.1	3.6	3.8	1.2	4.5	1.2	3.4	2.16	n	4.4	
	14010	9. 5-9	1500	230	118.9	2.79	2.48	.39	4.0	19.7	1.3	21.7	3.7	8.9	1.1	63.0	1.1	5.9	2.16	n	4.4	
	14010	10. 5-10	000	230	120.0	2.35	2.15	.20	3.7	5.4	2.7	5.4	3.3	3.5	1.2	6.7	1.2	1.2	1.6	n	4.4	
	14010	11. 5-10	1500	228	60.0	2.19	1.88	.31	7.1	17.2	6.1	22.7	7.0	10.6	6.4	60.9	6.3	6.7	1.88	n	7.2	
	14010	12. 5-13	000	230	72.3	1.88	1.51	.39	7.0	17.7	8.0	23.7	6.8	10.9	6.2	60.4	6.3	6.8	1.88	n	7.2	
	14010	13. 5-13	1500	226	59.0	1.26	1.05	.21	6.9	15.3	6.0	23.7	6.8	10.1	6.3	56.9	6.4	7.0	1.88	n	7.2	
	14010	14. 5-14	000	356	53.5	1.87	1.62	.25	6.9	15.9	5.9	20.9	6.8	10.4	6.4	60.4	6.9	6.7	1.88	n	7.2	
	14010	15. 5-14	1500	288	39.1	1.66	.000	.00	10.8	15.2	3.8	18.3	10.7	12.4	10.1	57.6	10.3	10.2	1.75	n	10.0	
	14010	16. 5-15	000	286	31.4	2.61	2.47	.14	10.6	11.0	9.7	15.7	10.5	12.6	9.6	57.4	10.0	10.6	1.76	n	10.0	
	14010	17. 5-15	1500	280	50.5	2.46	2.29	.27	10.8	16.6	3.7	17.6	10.6	12.4	10.0	55.7	10.1	10.2	1.75	n	10.0	
	14010	18. 5-16	000	310	31.3	2.29	2.13	.16	10.4	15.0	9.4	18.4	10.2	12.6	9.7	57.9	9.6	10.4	1.77	n	10.0	
	14010	77. 6-28	1500	246	40.0	2.52	2.24	.28	1.9	9.7	0.0	12.9	1.1	4.2	8	56.3	1.7	1.3	2.15	v	-1.1	
	14010	78. 7-1	000	281	34.5	2.21	1.57	.64	-1.1	5.1	-2.3	8.4	-1.6	2.6	-2.2	63.6	-1.5	-8	2.18	v	-1.1	
	14010	79. 7-1	1500	256	44.2	1.96	1.77	.19	-4	3.3	-1.4	4.4	-2.2	7.9	-1.3	58.1	-1.7	-4	2.17	v	-1.1	
B40	14013	19. 5-16	1500	290	5.4	2.98	2.83	.15	10.7	16.8	3.6	18.2	10.2	15.7	1.3	63.6	3.8	10.6	1.53	n	10.0	
	14013	20. 5-17	000	280	6.0	2.82	2.71	.11	10.6	14.5	9.6	15.7	10.4	13.1	9.8	61.9	10.0	10.3	1.53	n	10.0	
	14013	21. 5-17	1500	280	4.9	2.70	2.57	.13	10.8	15.9	9.7	18.1	10.5	13.7	3.9	65.4	10.1	10.6	1.53	n	10.0	
	14013	22. 5-21	000	306	8.0	2.56	2.40	.16	10.7	18.1	9.3	16.6	10.5	13.2	9.9	56.5	10.1	10.8	1.53	n	10.0	
	14013	25. 5-22	1500	290	11.2	2.16	1.98	.18	7.8	14.8	6.6	17.6	7.4	11.9	5.7	68.2	7.0	7.9	1.75	n	7.2	
	14013	26. 5-23	000	230	3.8	2.81	1.84	.97	12.9	19.3	9.7	21.8	12.9	16.6	13.0	66.4	12.9	13.7	1.40	n	10.0	
	14013	27. 5-23	1500	228	15.9	1.83	1.66	.17	7.0	13.3	6.1	15.7	6.8	10.7	6.1	66.8	6.2	7.0	1.80	n	7.2	
	14013	28. 5-24	000	230	14.7	1.66	1.44	.22	6.1	14.7	5.1	19.2	6.0	10.9	5.4	69.0	5.6	6.6	1.80	n	4.4	
	14013	29. 5-24	1500	246	38.4	1.44	1.26	.18	4.7	8.8	3.6	10.7	4.1	3.1	3.6	65.7	3.8	4.1	2.02	n	4.4	
	14013	30. 5-27	000	213	20.0	1.27	1.04	.23	4.1	11.9	3.2	15.7	3.9	8.6	3.4	66.8	3.6	4.2	2.03	n	4.4	
	14013	31. 5-27	1500	258	25.7	1.05	.868	.19	4.3	11.8	3.3	15.7	4.2	9.8	3.8	68.9	4.2	4.3	2.00	n	4.4	
	14013	80. 7-2	000	248	18.0	2.74	2.61	.13	-6	6.8	-1.7	7.1	-9	2.8	-1.3	55.4	-1.2	-8	25.8	v	-1.1	
	14013	81. 7-2	1500	248	16.1	2.61	2.42	.19	-2	4.9	-1.4	8.0	-7	4.2	-1.2	65.3	-1.2	-8	25.8	v	-1.1	
A35	14011	32. 5-28	000	230	120.0	2.73	2.49	.24	4.1	6.3	3.1	7.3	3.7	4.0	3.3	11.4	3.4	3.7	2.0	n	4.4	
	14011	33. 5-28	1500	288	120.0	2.46	2.05	.41	4.3	6.2	3.2	6.8	4.1	4.7	3.6	12.8	3.8	4.0	1.97	n	4.4	
	14011	34. 5-29	000	248	120.0	2.05	1.85	.20	4.1	5.4	3.1	5.4	4.0	4.2	3.5	2.5	3.7	3.9	1.98	n	4.4	
	14011	35. 5-29	1500	234	120.0	1.82	1.62	.20	4.3	6.1	3.2	5.9	4.0	4.4	3.6	3.5	3.8	4.1	1.97	n	4.4	
	14011	36. 5-30	000	268	120.0	1.62	1.38	.24	6.8	9.9	5.8	11.2	6.6	7.0	6.1	27.0	6.1	6.2	1.88	n	7.2	
	14011	37. 5-30	1500	248	100.4	1.36	.970	.39	7.3	25.3	6.2	30.3	7.2	14.7	6.7	64.9	6.8	7.3	1.85	n	7.2	
	14011	38. 5-31	000	268	88.2	.88	.688	.28	7.4	18.9	6.3	23.9	7.2	12.9	6.7	68.9	6.8	7.4	1.85	n	7.2	
	14011	39. 5-31	1500	278	120.0	2.15	1.64	.51	7.4	10.7	6.5	11.4	7.2	7.8	7.1	16.4	6.6	7.1	1.85	n	7.2	
	14011	40. 6-3	000	228	120.0	1.98	1.38	.20	7.4	8.7	6.2	9.6	7.1	7.6	6.8	7.8	6.7	6.7	1.84	n	7.2	
	14011	41. 6-3	1500	289	45.4	2.54	2.27	.27	11.7	20.9	9.8	24.7	11.0	16.1	10.6	69.1	10.2	11.3	1.72	n	10.0	
	14011	42. 6-4	000	257	78.9	2.24	1.88	.36	9.9	23.4	8.8	28.6	9.7	16.7	10.2	73.1	9.4	11.9	1.75	n	10.0	
	14011	43. 6-4	1500	232	120.0	1.76	1.55	.21	-2	6.6	-7	4.6	-1.2	2.1	-7	60.4	-7	-8	2.2	v	-1.1	
	14011	44. 6-5	000	234	120.0	2.68	.000	.00	-5	6.3	-1.9	3.2	-1.1	1.0	-1.6	52.9	-1.7	-2	2.25	v	-1.1	
B35	14014	45. 6-8	000	238	40.3	2.82	2.48	.34	-4	10.0	-8	13.7	8.9	6.4	-1.4	70.6	-7	0	24.3	v	-1.1	
	14014	46. 6-6	000	240	31.3	2.46	2.13	.33	-4	10.6	-1.9	14.0	-8	6.1	-1.7	72.9	-1.6	1	27.0	v	-1.1	
	14014	47. 6-6	1500	230	44.5	2.16	1.86	.30	-2	8.6	-7	12.0	-8	5.8	-9	69.8	-4	1	26.0	v	-1.1	
	14014	49. 6-7	1500	266	37.5	1.72	1.48	.24	-3.2	6.6	-3.7	11.1	-2.3	3.2	-4.1	65.0	-7.1	-2	30.0	v	-1.1	
	14014	50. 6-10	000	288	120.0	1.25	1.08	.17	-5.0	-1.8	-5.1	-2.2	-5.0	-3.9	-4.8	11.1	-4.8	-4	32.0	v	-1.1	
	14014	53. 6-11	1500	228	98.5	2.59	2.22	.37	-3.8	4.6	-4.3	9.6	-3.8	1.6	-4.0	69.8	-4.4	-7	31.0	v	-1.1	
	14014	54. 6-12	000	288	119.0	2.15	1.76	.39	-3.6	5.7	-4.3	9.7	-3.8	2.3	-4.7	66.6	-4.6	-7	32.0	v	-1.1	
	14014	56. 6-14	1500	288	40.0	1.72	1.51	.21	4.2	11.8	3.2	14.5	4.2	9.7	2.9	68.6	4.0	4.8	2.00	n	4.4	
	14014	57. 6-14	1500	268	32.6	1.51	1.27	.24	5.1	11.1	4.1	13.2	4.8	9.8	4.2	68.3	4.3	4.7	1.98	n	4.4	
	14014	58. 6-17	000	297	34.0	1.26	1.05	.21	4.9	10.0	7.7	12.7	4.8	10.1	7.2	68.1	7.3	4.2	2.00	n	4.4	
A30	14012	59. 6-17	1500	259	120.0	2.46	2.33	.13	5.4	6.8	4.4	7.1	5.3	5.6	4.6	1.7	4.5	4.3	1.70	n	4.4	
	14012	60. 6-18	000	248	120.0	2.26	2.12	.14	4.9	6.1	3.4	5.5	4.8	4.8	4.1	7	4.2	4.2	1.71	n	4.4	
	14012	61. 6-18	1500	239	120.0	1.97	1.81	.16	5.2	6.4	4.0	5.4	4.8	4.0	8	4.1	4.1	1.71	n	4.4		
	14012	62. 6-19	000	258																		

TABLE B-2. Cold-Start Tests
With LDT-465-1C Engine

	AL No	Test No	Date	Time	Cranking Speed rpm	Sec. to Start	Fuel in Before Ig	Fuel in After Ig	Fuel Used lb	Water in Before Ig	Water in After Ig	Oil Temp Before Ig	Oil Temp After Ig	Manifold Before Ig	Manifold After Ig	Exhaust Before Ig	Exhaust After Ig	Fuel Before Ig	Fuel After Ig	Kinematic Vis. (cSt)	Starting Aid	Set Temp. °C
Reference	13998	1	7-10	800	240	6.5	2.62	2.54	.08	2.3	5.9	2.7	5.2	3	2	1.1	21.6	1.3	1.6	5.20	n	1.7
	13998	2	7-10	1500	240	2.2	2.59	2.45	.14	2.3	4.9	1.2	3.6	1.0	1.7	1.2	71.2	1.1	1.3	5.30	n	1.7
	13998	57	8-19	1500	209	54.3	2.36	2.22	.14	-17	-17	-8.6	-3.5	-18	-17	-17	97.2	-17	-16	10.0	n	-18
	13998	58	8-20	800	193	120.0	2.21	2.14	.07	-19	-19	-17	-17	-20	-20	-13	-22.4	-13	-18	10.5	n	-18
13998	59	8-20	1500	190	120.0	1.84	1.76	.08	-17	-17	-14	-14	-17	-17	-16	-19.7	-16	-16	9.80	n	-18	
A40	14010	3	7-11	800	248	2.5	2.61	2.58	.03	2.2	4.4	1.3	3.5	0.0	5	1.0	68.7	1.0	1.2	2.08	n	1.7
	14010	4	7-11	1500	0	1	5	2.55	2.50	.05	2.2	4.3	1.2	3.4	6	1.5	72.6	1.1	1.3	2.08	n	1.7
	14010	5	7-12	800	244	11.9	2.44	2.38	.06	-2.9	1.0	-4.1	-6	-4.3	-4.4	-3.9	77.1	-4.1	-3.7	2.31	n	-4.4
	14010	6	7-12	1500	244	14.3	2.34	2.26	.08	-3.3	1.1	-3.6	0.0	-5.2	-5.3	-4.3	78.7	-4.4	-3.9	2.32	n	-4.4
	14010	7	7-15	1500	224	9.7	2.07	1.99	.08	-4.4	-4.4	-3.2	-5	-4.2	-4.3	-4.3	73.7	-4.1	-4.3	2.31	n	-4.4
	14010	8	7-16	800	276	11.5	1.92	1.85	.07	-5.0	-5.0	-4.2	-6	-6.0	-5.4	-4.6	80.9	-4.4	-4.3	2.32	n	-4.4
	14010	9	7-16	1500	221	75.8	1.81	1.68	.13	-9.6	-9.4	-6.9	-5.1	-10	-10	-9.3	78.8	-9.2	-9.1	2.56	v	-9.4
	14010	10	7-17	800	209	54.7	1.67	1.48	.19	-9.8	-9.9	-9.0	-5.2	-11	-9.9	-3.7	93.2	-9.4	-9.3	2.58	y	-9.4
	14010	11	7-17	1500	189	51.4	1.45	1.30	.15	-9.3	-9.6	-7.4	-5.6	-9.2	-9.0	-9.2	80.6	-9.1	-9.1	2.55	v	-9.4
	14010	47	8-12	1300	204	120.0	2.07	2.07	.00	-17	-17	-15	-15	-17	-17	-16	-7.7	-16	-16	3.01	y	-18
14010	48	8-13	800	210	120.0	1.92	1.92	.00	-17	-17	-16	-16	-17	-18	-16	-20.0	-17	-17	3.02	y	-18	
B40	14013	12	7-18	800	185	120.0	3.11	3.04	.07	-10	-10	-8.5	-8.4	-9.7	-11	-9.5	-5.4	-9.2	-9.4	37.5	v	-9.4
	14013	13	7-18	1500	188	120.0	2.67	2.59	.08	-9.6	-9.6	-7.7	-7.5	-9.8	-9.8	-8.8	-6.7	-9.2	-9.0	37.5	v	-9.4
	14013	14	7-19	800	254	36.5	2.58	2.41	.17	-4.3	-4.3	-3.9	-8	-3.9	-4.1	-3.8	91.2	-3.7	-3.3	28.8	n	-3.9
	14013	15	7-19	1500	244	51.8	2.41	2.25	.16	-4.4	-4.3	-2.8	0.0	-4.2	-3.7	-3.9	89.2	-3.7	-3.4	28.8	n	-3.9
	14013	16	7-22	800	255	28.8	2.22	2.11	.11	6	4	1.2	5.6	-1	-1	8	78.0	1.1	1.2	22.7	n	1.7
14013	17	7-22	1500	219	14.9	2.10	2.01	.09	6	7	1.6	5.3	1.2	1.0	1.0	88.2	1.1	1.3	22.7	n	1.7	
14013	42	8-8	800	224	95.7	2.59	2.42	.17	-9.1	-9.0	-7.4	-5.6	-9.3	-9.7	-8.8	79.4	-8.6	-8.6	36.8	v	-9.4	
14013	43	8-8	1500	186	104.2	2.41	2.24	.17	-8.1	-8.2	-7.7	-5.3	-8.8	-9.0	-8.4	83.2	-8.6	-8.0	36.8	y	-9.4	
14013	44	8-9	800	191	120.0	2.19	2.13	.06	-17	-17	-16	-15	-17	-17	-17	-20.6	-17	-17	60.0	y	-18	
14013	45	8-9	1500	181	120.0	1.88	1.82	.06	-16	-16	-14	-14	-17	-17	-16	-18.8	-16	-16	57.0	y	-18	
A40	14011	18	7-23	800	245	5.7	2.29	2.15	.14	6	8	1.8	4.9	0.0	3	1.1	81.4	1.8	1.1	2.12	n	1.7
	14011	19	7-23	1500	228	2.0	2.15	2.05	.10	8	7	1.4	2.5	2	8	1.3	75.7	1.3	1.0	2.12	n	1.7
	14011	20	7-24	800	248	5.6	2.01	1.89	.12	-1.9	-1.9	-1.6	7	-2.4	-2.5	-1.8	79.4	-1.8	-1.6	2.23	n	-3.9
	14011	21	7-24	1500	224	12.0	1.87	1.76	.11	-2.7	-2.6	-2.3	-7	-2.7	-3.0	-3.0	77.7	-3.1	-2.8	2.32	n	-3.9
	14011	22	7-25	915	201	60.2	1.71	1.53	.18	-9.8	-9.8	-9.2	-6.2	-9.8	-9.9	-9.5	81.6	-9.6	-9.2	2.70	v	-9.4
14011	23	7-25	1500	201	88.5	1.51	1.37	.14	-9.3	-9.2	-8.7	-7.2	-10	-9.3	-9.5	77.1	-9.5	-9.3	2.70	v	-9.4	
14011	49	8-13	1500	192	120.0	2.53	2.53	.00	-16	-16	-10	-11	-17	-17	-16	-19.8	-16	-16	3.30	y	-18	
14011	50	8-14	800	204	120.0	2.53	2.51	.02	-17	-18	-16	-17	-17	-18	-18	-21.3	-18	-18	3.40	y	-18	
B40	14014	24	7-26	800	226	94.9	2.44	2.28	.16	-9.4	-9.4	-8.8	-5.1	-10	-9.8	-9.7	89.0	-9.6	-9.1	43.0	v	-9.4
	14014	25	7-26	1500	212	80.7	2.27	2.11	.16	-8.6	-8.6	-8.3	-5.7	-10	-9.4	-9.3	87.9	-9.6	-9.2	43.0	v	-9.4
	14014	26	7-29	800	209	38.5	2.13	2.02	.11	-5.1	-5.0	-4.6	-2.6	-5.9	-5.8	-4.4	72.4	-4.6	-4.3	32.0	n	-3.9
	14014	27	7-29	1500	223	34.6	2.01	1.89	.12	-4.3	-4.2	-4.4	-2.2	-4.7	-4.4	-4.5	91.7	-4.6	-4.1	32.0	n	-3.9
	14014	28	7-30	800	231	8.4	1.90	1.80	.10	1.2	1.1	1.2	3.3	6	9	1.3	88.3	1.2	1.6	22.7	n	1.7
14014	29	7-30	1500	234	9.4	1.79	1.71	.08	1.2	1.1	1.6	2.6	8	1.2	1.6	76.1	1.4	1.8	22.5	n	1.7	
14014	53	8-15	1500	189	120.0	2.29	2.29	.00	-17	-17	-9.9	-11	-18	-19	-17	-10.3	-16	-16	68.0	y	-18	
14014	54	8-16	800	197	120.0	2.15	2.07	.08	-18	-18	-17	-17	-18	-19	-17	-9.0	-18	-17	77.8	y	-18	
A40	14012	30	7-31	800	248	8.8	2.54	2.44	.10	1.1	1.3	2.2	3.8	1.0	9	1.5	80.1	1.4	1.7	1.88	n	1.7
	14012	31	7-31	1500	242	2.7	2.47	2.37	.10	1.2	1.2	1.7	2.9	-3	0.0	1.6	72.2	1.4	1.6	1.90	n	1.7
	14012	32	8-1	800	242	19.5	2.39	2.26	.13	-2.8	-2.8	-2.4	-7	-4.8	-3.2	-2.6	71.1	-2.6	-2.3	1.95	n	-3.9
	14012	33	8-1	1500	254	7.3	2.26	2.12	.13	-2.4	-2.2	-2.2	-6	-3.1	-3.2	-2.5	88.3	-2.4	-2.1	1.94	n	-3.9
	14012	34	8-2	800	215	60.4	2.08	1.86	.16	-9.2	-9.2	-8.4	-5.7	-10	-11	-9.1	82.3	-8.8	-8.7	2.21	v	-9.4
14012	35	8-2	1500	212	82.9	1.84	1.63	.21	-8.4	-8.5	-8.0	-4.4	-9.4	-9.8	-8.8	72.6	-8.8	-8.4	2.21	v	-9.4	
14012	51	8-14	1500	194	120.0	2.26	2.25	.01	-14	-14	-10	-10	-17	-17	-17	-20.3	-17	-16	2.63	y	-18	
14012	52	8-15	800	187	120.0	2.23	2.19	.04	-17	-18	-17	-17	-18	-19	-18	-22.2	-19	-18	2.73	y	-18	
B40	14015	36	8-5	800	211	120.0	2.52	2.44	.08	-3.0	-3.1	-8.9	-8.5	-9.7	-8.9	-8.9	-5.9	-8.9	-8.3	42.0	v	-9.4
	14015	37	8-5	1500	198	120.0	2.43	2.35	.08	-8.6	-8.6	-8.3	-8.3	-9.3	-9.3	-8.6	-10.6	-8.8	-8.8	42.0	v	-9.4
	14015	38	8-6	800	219	98.4	2.35	2.14	.21	-3.8	-3.9	-3.7	-6	-3.8	-4.1	-3.3	95.0	-3.4	-3.1	31.3	n	-3.9
	14015	39	8-6	1500	206	96.9	2.13	1.91	.22	-3.0	-2.9	-2.4	-1	-3.0	-3.3	-3.2	95.0	-3.3	-2.8	31.3	n	-3.9
	14015	40	8-7	800	225	26.5	1.89	1.79	.10	2.1	2.0	2.2	3.4	1.6	1.9	2.2	79.8	2.1	2.3	23.0	n	1.7
14015	41	8-7	1500	220	29.0	1.77	1.68	.09	1.9	1.9	2.0	2.9	2.1	1.8	2.2	79.1	2.1	2.3	23.0	n	1.7	
14015	55	8-16	1500	187	120.0	2.52	2.45	.07	-17	-17	-9.2	-11	-18	-18	-17	-21.4	-17	-17	73.5	y	-18	
14015	56	8-19	800	215	120.0	2.43	2.37	.06	-19	-19	-17	-17	-21	-20	-18	-23.1	-19	-19	85.0	y	-18	

*120 sec recorded as a "no start" test.

+Kinematic viscosity at fuel test temperature estimated from ASTM viscosity-temperature chart.

TABLE B-3. Cold-Start Tests With NHC-250 Engine

	Alt. No	Test No	Date	Time	Cranking Speed, rpm	Sec. to Start	Fuel Air Before Ig	Fuel Air After Ig	Fuel Load, lb	Water in Before Ig	Water in After Ig	Oil Temp Before Ig	Oil Temp After Ig	Mantle Temp Before Ig	Mantle Temp After Ig	Exhaust Temp Before Ig	Exhaust Temp After Ig	Fuel Temp Before Ig	Fuel Temp After Ig	Kinematic Viscosity at Test	Starting Air Temp, °C	Air Temp, °C	
Reference	13998	1	8-26	800	198		40.0	2.17	1.94	23	-4	-3	-1	-6	-4	0.0	-4	60.9	-2	4	5.4	n	1.7
	13998	2	8-26	1500	207		27.0	1.83	1.32	51	1.6	1.7	1.4	1.7	1.4	2.1	2.4	64.1	2.2	2.4	5.1	n	1.7
	13998	3	8-27	800	236		7.0	3.42	3.26	16	-1.4	3.4	-3.8	-3.8	-4.6	-3.7	-7	71.5	-3.4	-3.4	6.1	y	-3.9
	13998	4	8-27	1500	179		51.6	2.23	3.02	21	-6.5	-2.2	-3.5	-3.6	-3.9	-2.7	-3.3	30.2	-3.5	-3.1	6.1	y	-3.9
	13998	5	8-28	800	227		72.2	2.99	2.75	24	-1.6	2.8	-3.8	-4.1	-5.3	-4.6	-3.2	72.0	-3.8	-3.6	6.2	y	-3.9
	13998	6	8-28	1500	159		120.0	2.67	2.43	24	-2.9	-4.3	-9.8	-5.4	-9.1	-8.9	-8.1	-9.9	-9.8	-8.6	7.2	y	-9.4
	13998	7	8-29	800	151		120.0	2.42	2.19	23	-6.9	-6.1	-9.3	-9.4	-10	-10	-8.6	-11.1	-9.2	-9.1	7.3	y	-9.4
	13998	8	8-29	1500	253		75.9	2.19	1.66	53	-5.0	4.8	-6.4	-5.4	-9.4	-7.6	-6.1	69.4	-8.4	-5.5	7.2	y	-9.4
	13998	9	8-30	800	218		47.2	1.44	53	96	-7.0	-2.5	-9.1	-9.3	-10	-7.7	-8.8	98.3	-5.3	-7.3	7.3	y	-9.4
	13998	10	8-30	1500	224		7.8	2.89	2.48	41	-5.1	4	-6.2	-5.9	-9.1	-7.1	-7.7	88.5	-8.6	-6.9	2.52	y	-9.4
A40	14010	11	9-3	1500	184		120.0	2.43	2.25	18	-6.4	-5.3	-8.6	-8.6	-9.7	-9.3	-7.1	-11.3	-8.8	-8.7	2.54	y	-9.4
	14010	12	9-9	800	215		3.3	2.89	2.64	25	-3.4	1.7	-5.9	-5.8	-4.1	-3.8	-3.9	86.5	-5.0	-4.2	2.35	y	-3.9
	14010	13	9-9	1500	235		2.0	2.67	2.44	23	-1.6	3.2	-3.9	-3.6	-4.2	-3.8	-3.2	92.3	-3.4	-2.7	2.28	y	-3.9
	14010	14	9-10	1300	235		2.6	2.40	1.94	46	-5.7	4.7	-7.6	-6.8	-9.7	-8.4	-8.1	99.4	-9.7	-6.2	2.52	y	-9.4
	14010	15	9-10	1600	244		24.1	1.96	1.47	49	-5.3	2.2	-7.7	-7.3	-9.3	-9.1	-8.0	94.8	-9.6	-7.4	2.52	y	-9.4
	14010	16	9-11	800	248		10.0	1.62	1.43	19	3.1	6.4	1.2	1.6	1.2	2.2	1.8	82.0	1.4	2.7	2.07	n	1.7
	14010	17	9-11	1115	248		10.3	1.35	1.29	66	4.0	7.3	2.1	3.3	1.2	2.4	2.7	84.4	2.0	2.9	2.05	n	1.7
	14010	49	11-26	800	165		23.0	3.16	2.66	50	-16	-16	-15	-15	-16	-11	-15	98.1	-15	-13	2.92	y	-15
	14010	50	11-26	1500	234		6.0	2.64	2.30	34	-14	-14	-13	-14	-15	-13	-14	85.6	-14	-12	2.83	y	-15
	14010	51	11-27	800	135		120.0	2.24	2.04	20	-21	-21	-21	-21	-21	-21	-21	-9.8	-20	-20	3.30	y	-21
B40	14010	52	11-27	1500	123		120.0	2.04	1.87	17	-21	-21	-21	-21	-21	-21	-21	-9.8	-20	-20	3.30	y	-21
	14010	62	12-6	1500	253		6.7	2.06	1.82	24	-18	-7.4	-19	-19	-22	-19	-20	99.4	-21	-17	3.40	y	-21
	14010	63	12-9	800	254		8.0	1.82	1.29	53	-19	-3.9	-21	-14	-22	-17	-20	92.3	-21	-15	3.40	y	-21
	14010	64	12-9	1100	250		2.3	1.32	1.04	28	-11	-5.0	-14	-14	-15	-12	-13	85.5	-14	-12	2.93	y	-15
	14010	65	12-9	1500	258		2.0	1.08	0.69	39	-12	-5.1	-14	-14	-15	-12	-14	95.4	-14	-12	2.93	y	-15
	14010	86	1-15	1500	206		120.0	3.15	2.89	26	-15	-14	-18	-18	-19	-20	-19	-20.8	-19	-19	3.20	y	-21
	14010	87	1-16	800	200		120.0	2.91	2.69	22	-17	-16	-20	-20	-20	-19	-19	-21.3	-20	-19	3.30	y	-21
	14010	88	1-16	1500	204		4.0	3.30	3.13	17	-3.0	4.7	-5.9	-6.2	-21	-18	-15	49.0	-10	-12	2.60	y	-21
	14010	89	1-17	800	249		3.5	3.13	2.82	31	-17	-7.0	-19	-20	-20	-17	-19	81.8	-20	-18	3.30	y	-21
	14010	90	1-17	1500	248		40.0	2.92	2.38	44	-19	-7.4	-23	-23	-24	-21	-23	94.8	-23	-21	3.55	y	-26
A45	14010	91	1-20	800	250		6.0	2.28	1.60	68	-22	-9.6	-26	-19	-26	-22	-24	83.2	-25	-24	3.80	y	-26
	14010	92	1-20	1500	192		37.6	1.63	1.19	44	-22	-14	-25	-25	-26	-22	-25	81.8	-26	-24	3.85	y	-26
	14010	93	1-21	800	251		7.7	2.64	2.04	60	-22	-6.9	-25	-19	-26	-22	-25	81.2	-25	-22	3.80	y	-26
	14013	18	9-11	1500	211		27.2	3.43	3.21	22	6.7	10.3	4.7	7.0	1.4	2.6	3.1	78.8	3.4	3.4	20.5	n	1.7
	14013	19	9-12	1100	252		9.2	3.13	3.06	07	7.4	10.7	5.0	6.8	1.7	2.2	3.2	75.8	3.6	3.4	20.3	n	1.7
	14013	20	9-12	1500	233		3.3	3.02	2.84	18	-9	4.4	-2.1	6	-4.3	-2.7	-2.7	92.3	-3.1	-2.9	28.0	y	-3.9
	14013	21	9-13	800	253		3.1	2.87	2.53	34	-1.5	4.4	-3.7	-2.4	-3.3	-3.6	-2.8	96.9	-3.3	-3.0	28.2	y	-3.9
	14013	22	9-13	1115	173		13.3	2.54	2.30	24	-5.3	-7	-6.9	-6.9	-9.8	-7.6	-7.9	90.2	-9.1	-7.7	36.0	y	-9.4
	14013	23	9-13	1500	233		13.8	2.29	2.02	27	-5.8	-3	-7.4	-7.6	-9.4	-8.4	-7.9	98.7	-8.3	-7.2	36.2	y	-9.4
	14013	53	12-2	800	112		120.0	2.47	2.16	31	-20	-21	-20	-20	-21	-21	-20	-14.2	-20	-20	75.0	y	-21
B45	14013	54	12-2	1300	121		120.0	2.17	2.16	01	-21	-21	-20	-21	-20	-20	-21	-19.6	-20	-20	75.0	y	-21
	14013	55	12-4	800	252		1.8	1.97	1.64	23	-13	-7.5	-15	-15	-15	-14	-14	90.8	-14	-12	50.0	y	-15
	14013	56	12-4	1100	253		4.1	1.65	1.32	33	-12	-4.3	-14	-14	-15	-14	-14	91.1	-14	-11	50.0	y	-15
	14013	81	1-13	800	188		58.1	3.46	3.03	43	-12	-6	-15	-14	-15	-13	-14	83.2	-14	-14	50.0	y	-15
	14013	82	1-13	1500	195		53.7	3.03	2.77	26	-12	-1.3	-14	-14	-15	-13	-14	86.9	-14	-14	50.0	y	-15
	14013	101	1-27	800	237		43.2	4.06	3.63	43	-16	-1.5	-20	-19	-20	-18	-19	77.7	-19	-17	69.0	y	-21
	14013	102	1-27	1500	200		67.1	3.63	3.28	35	-16	-2	-19	-19	-20	-18	-19	80.2	-18	-18	65.0	y	-21
	14011	24	9-16	1230	245		1.9	3.14	2.93	21	0.0	2.8	-2.7	-3.2	-9.1	-9.2	-6.4	66.3	-5.3	-5.2	2.42	y	-9.4
	14011	25	9-16	1530	236		12.2	2.95	2.60	35	-5.3	-4	-6.9	-5.2	-9.3	-9.2	-7.7	87.4	-8.2	-7.1	2.61	y	-9.4
	14011	26	9-17	1100	259		6.9	2.61	2.31	30	-7	6.2	-1.4	0.0	-4.4	-2.7	-2.6	88.7	-2.9	-1.3	2.30	y	-3.9
A50	14011	27	9-17	1500	226		1.6	2.32	2.08	24	-1.2	2.7	-2.9	-1.3	-4.6	-3.9	-3.2	73.1	-3.6	-2.7	2.36	y	-3.9
	14011	28	9-18	800	243		27.5	2.13	1.82	31	3.3	7.6	1.5	2.4	8	1.2	2.2	98.0	1.8	3.3	2.05	n	1.7
	14011	29	9-18	1100	218		28.5	1.84	1.60	24	4.0	7.4	2.2	3.4	1.2	2.1	2.3	89.7	1.8	3.4	2.05	n	1.7
	14011	57	12-4	1600	265		3.1	3.83	3.51	32	-11	-2.3	-13	-12	-15	-12	-14	89.2	-14	-13	3.10	y	-15
	14011	58	12-5	800	268		2.9	3.55	3.36	19	-12	-4.7	-14	-14	-14	-13	-14	95.9	-14	-13	3.10	y	-15
	14011	59	12-5	1100	202		13.3	3.30	2.91	39	-17	-7.9	-18	-19	-22	-19	-20	90.1	-20	-18	3.70	y	-21
	14011	60	12-5	1600	223		85.6	2.93	2.43	50	-18	-3.2	-20	-20	-22	-19	-20	93.6	-21	-16	3.80	y	-21
	14011	61	12-6	800	255		12.9	2.42	2.06	26	-19	-8.6	-21	-21	-21	-19	-20	83.2	-21	-18	3.80	y	-21
	14014	30	9-18																				

TABLE B-4. Cold-Start Tests
With GM 6.2L Engine

AI No	Date	Fuel Wt Before, kg	Fuel Wt After, kg	Water In Before, °C	Water In After, °C	Oil Temp Before, °C	Oil Temp After, °C	Cold Box Before, °C	Cold Box After, °C	Fuel Before, °C	Fuel After, °C	Exhaust Before, °C	Exhaust After, °C	Manifold Before, °C	Manifold After, °C	Cooling Speed, rpm	Start?	Sec to Start	Starting Aid
4010	5-14	14.22	13.87	-10	-5.6	-9.4	-10	-11	-11	-11	-10.6	-10	39.4	-11	-9.4	210	Y	3.6	Y
4010	5-14	14.07	13.74	-13	-12	-12	-12	-13	-14	-13	-12.8	-12	22.8	-12	-14	196	Y	5.4	Y
4010	5-15	13.85	13.53	-12	-7.2	-12	-12	-12	-12	-11	-12.2	-11	28.3	-12	-10	246	Y	5.4	Y
4010	5-15	13.69	13.48	-18	-16	-19	-16	-19	-18	-18	-17.8	-16	20.0	-17	-19	196	Y	7.2	Y
4010	5-18	13.50	13.16	-18	-17	-17	-17	-19	-19	-19	-18.3	-16	52.3	-19	-17	193	Y	5.4	Y
4010	5-19	13.36	13.05	-23	-22	-21	-21	-24	-22	-23	-22.8	-20	29.9	-22	-21	196	Y	6.4	Y
4010	5-20	14.58	14.32	-22	-21	-21	-23	-22	-23	-22	-22.8	-20	17.8	-22	-21	190	Y	9.6	Y
4010	5-21	14.57	14.22	-29	-28	-27	-30	-31	-30	-30	-30.0	-29	3.9	-30	-30	155	Y	88	Y
4010	5-21	14.39	14.10	-31	-31	-29	-32	-31	-31	-31	-31.7	-29	-15.6	-31	-31	154	N	98	Y
4010	5-21	14.26	13.88	-32	-28	-28	-30	-31	-31	-32	-22.4	-23	22.8	-23	-23	153	Y	99	Y
4011	5-21	15.10	14.88	-29	-27	-25	-26	-31	-31	-29	-29.4	-29	-3.3	-29	-23	154	N	90	Y
4011	5-22	14.98	14.79	-29	-27	-29	-28	-29	-29	-30	-30.0	-29	-8.3	-29	-29	150	N	90	Y
4011	5-22	14.79	14.54	-21	-21	-23	-23	-22	-22	-22	-22.2	-21	7.3	-21	-21	199	Y	26	Y
4011	5-25	14.52	14.26	-23	-22	-22	-22	-24	-24	-23	-23.3	-21	26.1	-23	-23	191	Y	22	Y
4011	5-25	14.15	13.84	-16	-16	-17	-17	-18	-18	-17	-17.2	-16	24.4	-17	-17	197	Y	7.2	Y
4011	5-26	14.04	14.03	-16	-16	-15	-19	-19	-19	-17	-17.2	-15	51.7	-17	-17	204	Y	12	Y
4011	5-26	13.98	13.98	-16	-16	-15	-15	-17	-17	-17	-16.7	-14	44.4	-16	-16	199	Y	11	Y
4011	5-27	13.81	13.67	-9.4	-9.4	-9.4	-11	-11	-12	-11.7	-11.7	-11	-10	205	Y	5.4	Y		
4011	5-27	13.71	13.63	-10	-10	-10	-11	-12	-12	-12.0	-9.4	27.8	-11	-9.4	204	Y	5.0	Y	
4012	5-28	14.79	0.00	-14	-12	-14	-14	-14	-15	-14	-14.4	-13	2.2	-13	-11	233	Y	70	Y
4012	5-28	0.08	14.36	-13	-11	-13	-13	-14	-14	-13.9	-13	27.2	-13	-12	239	Y	20	Y	
4012	5-29	14.29	14.20	-16	-15	-15	-16	-16	-17	-16.1	-15	30.0	-16	-13	230	Y	20	Y	
4012	5-29	14.20	14.20	-17	-16	-16	-18	-17	-17	-17.9	-16	28.9	-16	-13	236	Y	29	Y	
4012	6-1	14.86	14.89	-22	-19	-21	-23	-19	-22	-21.7	-22	3.4	-22	-19	164	N	90	Y	
4012	6-2	14.34	14.28	-22	-22	-22	-23	-23	-22	-22.2	-22	-21.7	-22	-23	154	N	30	Y	
4012	6-2	8.67	7.88	-24	-28	-22	-24	-23	-24	-23.9	-23	75.0	-23	-22	174	Y	61	Y	
4012	6-3	8.04	7.93	-24	-21	-22	-21	-24	-22	-22.8	-22	31.1	-22	-21	215	Y	18	Y	
4012	6-4	8.03	7.81	-23	-28	-22	-25	-23	-24	-23.9	-22	23.3	-23	-22	197	Y	60	Y	
4012	6-4	7.81	7.76	-28	-25	-26	-26	-31	-30	-30.0	-27	18.9	-28	-27	190	N	90	Y	
4012	6-5	7.79	7.75	-27	-26	-27	-27	-29	-29	-28.9	-27	-5.6	-28	-27	168	N	28	Y	
4013	6-10	11.15	11.11	-14	-12	-14	-14	-15	-16	-15.6	-14	10.6	-15	-14	188	N	30	Y	
4013	6-10	11.16	11.11	-17	-14	-16	-16	-17	-18	-17.8	-16	11.7	-17	-16	193	N	30	Y	
4013	6-11	12.06	11.91	-11	-8.3	-8.9	-8.3	-11	-10	-11	-11.1	-11	11.1	-11	-10	186	N	30	Y
4013	6-11	11.37	10.88	-12	-8.9	-12	-12	-13	-13	-13.3	-11	8.3	-12	-11	188	N	30	Y	
4013	6-12	12.48	12.17	-6.1	2.8	-6.1	-6.1	-6.7	-5.0	-7.2	-6.1	47.8	-7.2	-4.4	184	Y	89	Y	
4013	6-12	12.38	12.28	-6.7	-6	-6.1	-6.1	-7.2	-6.1	-6.7	-6.1	36.1	-6.1	-3.9	196	Y	89	Y	
4013	6-25	13.91	13.72	0.0	1.1	-6	-6	-6	-6	-1.1	-1	6	38.9	-1.1	6	203	Y	29	Y
4013	6-25	13.74	13.53	-6	2.8	-6	-6	-1.1	-6	-1.1	-1	6	48.0	-1.1	-1.1	205	Y	15	Y
4013	6-26	16.34	16.02	-5.0	-6	-5.0	1.1	-5.0	-3.9	-5.6	-4.4	50.6	-6.7	-2.2	195	Y	82	Y	
4013	6-26	16.58	16.38	-6	7.0	-1.1	-6	-6	-6	-1.1	-1	0.0	46.7	-6	1.1	208	Y	21	Y
4013	6-29	16.04	15.88	-5.6	-3.3	-6.1	-6.1	-6.7	-6.7	-6.1	-6.7	-6.1	10.6	-6.7	-5.6	190	N	30	Y
4013	6-29	14.88	14.67	-5.6	-2.8	-4.4	-4.4	-6.1	-6.1	-6.1	-6.1	5.6	11.7	-5.6	-5.0	175	N	30	Y
4013	6-30	14.66	14.52	-6.1	-2.8	-6.1	-6.1	-7.2	-6.7	-6.7	-5.6	11.7	-7.2	-6.7	162	N	30	Y	
4013	6-8	18.94	18.95	-27	-25	-28	-29	-28	-29	-27.8	-27	-8.9	-28	-28	150	N	30	Y	
4013	6-8	18.99	18.94	-28	-26	-28	-28	-31	-30	-30	-28.9	-27	-16.7	-29	-28	150	N	30	Y
4013	6-9	18.88	18.81	-23	-21	-23	-22	-24	-23	-23	-23.3	-21	2.2	-23	-23	164	N	30	Y
4013	6-9	18.94	18.94	-22	-22	-22	-22	-23	-24	-23	-23.3	-21	3.9	-23	-22	156	N	30	Y
4014	6-15	13.42	13.38	-6.7	0.8	-6.7	-6.1	-7.8	-7.2	-7.8	-7.0	32.8	-6.1	-5.6	186	Y	87	Y	
4014	6-16	8.38	8.39	-6.7	-5.6	-6.7	-6.1	-6.1	-5.6	-6.7	-7.2	-6.1	39.4	-6.7	-5.6	185	Y	24	Y
4014	6-16	8.48	8.27	2.2	2.8	2.8	2.8	1.7	1.7	1.7	2.2	2.8	37.8	2.2	2.8	248	Y	15	Y
4014	6-17	8.28	8.05	2.2	2.2	1.7	2.8	1.7	1.7	1.1	1.7	1.7	36.1	1.7	1.1	208	Y	16	Y
4014	6-18	13.23	13.05	-1.7	1.7	-1.1	-1.1	-2.8	-2.8	-2.2	-2.2	-1.1	34.4	-2.2	-1.7	211	Y	19	Y
4014	6-18	12.78	12.24	-1.1	5.6	-1.1	-6	-1.7	-1.1	-2.2	-1.7	-1.1	58.0	-1.1	0.0	198	Y	86	Y
4014	6-19	11.98	11.61	-1.1	5.6	-1.7	-1.1	-2.2	-2.8	-2.2	-2.0	-1.1	58.0	-1.7	-1.7	215	Y	18	Y
4014	6-19	11.53	11.23	-5.8	-1.7	-5.8	-5.8	-6.7	-5.6	-6.1	-6.1	-5.0	51.7	-5.6	-4.4	287	Y	46	Y
4014	6-22	14.79	14.68	-12	-9.9	-11	-11	-12	-13	-12	-12.2	-12	15.0	-12	-11	174	N	30	Y
4014	6-22	8.88	14.83	-5.6	-2.8	-5.6	-7.2	-6.1	-5.0	-6.1	-5.0	47.8	-5.6	-5.0	210	Y	33	Y	
4014	6-23	14.64	14.49	-11	-8.3	-11	-11	-12	-12	-13	-11.7	-12	3.3	-12	-9.4	169	N	20	Y
4015	6-23	15.28	14.83	-3.3	16.7	6.7	7.8	1.7	2.8	2.8	2.8	3.3	65.0	2.8	6.7	191	Y	39	Y
4015	6-24	14.65	14.51	2.2	8.3	1.7	2.2	1.7	1.7	1.7	2.2	2.2	30.0	2.2	3.3	196	N	30	Y
4015	6-24	14.95	14.62	2.2	9.4	1.7	1.7	1.7	1.7	1.7	1.7	2.2	62.8	2.2	3.9	199	Y	84	Y
4015	7-10	16.36	16.18	4.4	10.6	3.9	3.9	3.9	3.9	3.9	3.9	4.4	51.7	4.4	4.4	202	Y	6.4	Y
4015	7-10	16.16	16.08	1.7	10.8	1.7	2.2	1.7	2.2	1.7	2.8	2.2	67.2	1.7	2.8	193	Y	59	Y
4015	7-13	16.82	16.68	2.2	11.7	1.7	1.7	1.7	2.2	1.7	1.7	1.7	41.1	1.7	3.3	198	Y	84	Y
4015	7-13	15.78	15.47	8.0	5.6	-6	0.0	-1.1	-6	-6	-6	0.0	57.8	-6	1.1	189	Y	52	Y
4015	7-14	15.38	15.14	-1.1	2.8	-1.7	-6	-6	-6	-1.7	-1.1	-1.1	25.6	-6	6	190	N	30	Y
4015	7-14	15.46	15.38	-1.1	2.2	-1.1	-1.1	-1.7	-6	-1.7	-1.1	-1.1	30.6	-1.1	6	191	N	30	Y
4015	7-2	17.35	17.06	16.1	18.9	15.6	15.6	15.6	15.6	15.6	15.6	15.6	73.3	16.1	15.6	191	Y	3.6	Y
4015	7-6	17.34	17.11	16.1	20.8	15.6	16.1	16.1	15.0	15.6	15.6	15.6	89.4	15.6	15.0	208	Y	3.6	Y
4015	7-6	17.21	17.09	13.3	17.8	12.8	13.3	11.7	12.8	12.2	12.8	12.8	85.6	12.8	13.3	215	Y	5.4	Y
4015	7-7	16.98	16.89	10.6	13.9	10.0	10.0	10.6	9.4	10.0	10.0	10.0	60.6	10.0	10.0	212	Y	14	Y
4015	7-7	17.18	17.99	12.8	14.4	12.8	12.8	12.2	11.7	12.2	12.2	12.8	52.2	12.8	12.8	215	Y	5.4	Y
4015	7-8	16.98	16.75	10.6	16.7	10.0	10.0	9.4	9.4	9.4	10.0	10.0	70.0	9.4	10.6	216	Y	6.4	Y
4015	7-8	16.77	16.61	7.2	12.8	7.2	7.2	7.2	6.7	6.7	7.2	7.2	51.7	7.2	7.2	212	Y	17	Y
4015	7-9	16.58	16.35	4.4	10.6	4.4	4.4	3.9	5.0	3.9	4.4	5.0	39.4	4.4	5.6	202	Y	47	Y
4015	7-9	16.71	16.54	7.2	14.4	6.7													

APPENDIX C

Injector Fouling Bench Test Methodology for Diesel Fuel Thermal Stability

INJECTOR FOULING BENCH TEST METHODOLOGY FOR DIESEL FUEL THERMAL STABILITY

1.0 Scope

1.1 This methodology is being developed for evaluating the thermal oxidative deposition/sticking and/or fouling tendencies (under accelerated test conditions) of diesel injector.

1.2 This methodology will be used to determine the tendency of diesel fuel to cause sticking and/or fouling of injector parts in service operation.

2.0 Apparatus

2.1 References

2.1.1 CLR-Diesel Engine Manual

2.1.2 Detroit Diesel Series 53 Service Manual

2.1.3 Cummins P-T Injector System Manual

2.1.4 ISO 4010-1977 (E)

2.2 Injector Systems

2.2.1 The injector systems used for IFBT evaluations represent the three most common injection systems used in diesel engines. The three IFBT apparatus were developed to examine the sensitivity of each unique injection system to fuel thermal stability.

2.2.1.1 The CLR-Diesel IFBT apparatus represents a jerk pump-line-nozzle type of injection system. The jerk pump meters and pressurizes the fuel, which is carried to a remote nozzle by a high pressure line. All fuel recirculation occurs in the jerk pump and the bypassed fuel does not see high injector temperatures.

The IFBT apparatus was designed to simulate the injector pintle deposition of the CLR-Diesel hot test engine. The apparatus is shown in Fig. C-1. Thermal mapping of the pintle in the CLR-Diesel engine determined the temperatures at which the injector is controlled.

2.2.1.2 The IFBT Detroit Diesel (DD) apparatus was developed to determine the injector deposition tendencies of the DD unit injector. The unit injector contains the metering/pressurizing assembly and nozzle in a single unit; thus the bypassed fuel is exposed to high injector temperatures. The interest in developing the DD rig spawned from the high fuel return rates of the unit injector in which the fuel is used to cool the injector in the cylinder head. The high recycle rate and the additional thermal stressing of the fuel are considered important factors governing the pintle deposition with the DD rig. Fig. C-2 is a schematic of the Detroit Diesel test apparatus.

2.2.1.3 The IFBT Cummins apparatus was developed to examine the relative deposition tendencies of the Cummins PT-fuel injection system. The PT-fuel system uses a low pressure/high volume pump to supply fuel to the injectors at a constant pressure dependent on load. All metering occurs through an orifice in the injector. When the injector plunger is lifted off its seat, all remaining unmetered fuel is recirculated. The bypassed fuel is used to cool the injector, where it is exposed to high temperatures. Fig. C-3 depicts the Cummins IFBT apparatus.

2.3 Preparation for Test

2.3.1 Prior to the test, the injectors for the respective bench test rigs are examined, based on the procedures outlined in their respective manuals. Additional tests include a nozzle airflow check and a TDR spun rating for baseline data of a clean pintle/plunger. The test undergoes a battery of tests listed in TABLE C-1.

TABLE C-1. Fuel Tests

JFTOT Breakpoint
ASTM D 2276
ASTM D 2274

2.4 Test Procedures

2.4.1 For each of the three IFBT rigs, 20 gallons of the test fuel is procured. The injector rigs are operated at their respective conditions described in TABLE C-2.

TABLE C-2. IFBT Operating Conditions

Condition	Bosch APE CLR-D	Detroit Diesel	Cummins
Test hours	40	40	40
Speed, rpm	1000	1000	1000
Fuel flow, gal/hr	0.5	0.5	0.5
Fuel pressure, psi	---	---	140
Fuel spray temp, °C (°F)	288 (550)	204 (400)	204 (400)

After-test performance evaluations include the evaluations described in the respective injector references, plus the air flow test for the determination of nozzle hole plugging. The air flow evaluation is a modification of the ISO 4010-1977 (E) standard.

Also, following the completion of the test, the pintle/plungers are rated for deposition by the methods listed in TABLE C-3 and compared to their respective before-test measurements. Results are then listed in the respective work sheets (Figs. C-4 through C-6).

TABLE C-3. IFBT Deposition ratings

Visual CRC lacquer demerit scale
TDR spun rating
Dielectric breakdown
JFTOT visual rating scale




Figure C-1. CLR-D injector fouling bench test apparatus




Figure C-2. Detroit Diesel injector fouling bench test apparatus




Figure C-3. Cummins injector fouling bench test apparatus

APPENDIX D

Diesel Fuel Specification Comparisons

APPENDIX D

Diesel Fuel Specification Comparisons

ASTM ES-XX-XX, Emergency 2-D Specification is to be held in abeyance at ASTM headquarters, to be used in the event of an emergency.

TABLE D-1 compares the physical and chemical requirements for VV-F-800D, ASTM ES-XX-XX (Emergency 2-D) and VV-F-XXX, example--Variable Quality Diesel Fuel specifications.

TABLE D-1. Physical and Chemical Requirements for VV-F-800,
ASTM ES-XX-XX, and Variable Quality Diesel Fuel

Properties	VV-F-800D Values				VV-F-XXX Variable Quality Diesel Fuel Ambient at or above 45°F
	Grade DF-A	Grade DF-1	Grade DF-2		
			CONUS	OCNUS	
Density, kg/L at 15°C	Report	Report	Report	0.815 to 0.860	0.78 to 0.89
Flash Point, °C, min	38	38	52	56 ^{1/}	38
Cloud Point, °C, max	-51	2/	2/	2/	Local
Pour Point, °C, max	Report	Report	Report	3/	--
K. Vis. at 20°C, cSt	--	--	--	1.8 to 9.5	--
K. Vis. at 40°C, cSt	1.1 to 2.4	1.3 to 2.9	1.9 to 4.4	(1.4 to 5.5)	1.3 to 5.5
Distillation, °C,					
50% evaporated	Report	Report	Report	Report	Report
90% evaporated, max	288	288	338	357	360
End Point, max	300	330	370	370	--
Residue, vol%, max	3	3	3	3	--
Carbon Residue on 10%					
Bottoms, mass%, max ^{4/}	0.10	0.15	0.35	0.20	0.35
Sulfur, mass%, max ^{5/}	0.25	0.50	0.50	0.30	0.7 (or legal)
Copper Strip Corrosion, 3 hr at 50°C,					
max rating	3	3	3	1	3
Ash, mass%, max	0.01	0.01	0.01	0.02	0.01
Accelerated Stability,					
Total Insolubles,					
mg/100 mL, max	1.5	1.5	1.5	1.5	--
Neutralization Number,					
TAN, max	0.05	--	--	0.10	--
Particulate Contamination,					
mg/L, max	10	10	10	10	15
Cetane Number, min ^{6/}	40	40	40	45	35 ^{7/}

- ^{1/} DF-2 intended for entry into the Central European Pipeline System shall have a minimum value of 58°C.
- ^{2/} As specified by the procuring activity. DF-2 for Europe and S. Korea shall have a maximum limit of -13°C.
- ^{3/} As specified by the procuring activity. DF-2 for Europe and S. Korea shall have a maximum limit of -18°C.
- ^{4/} If the fuel contains cetane improvers, the test must be performed on the base fuel blend only.
- ^{5/} Diesel fuel intended for consumption in southern California shall meet the requirements of the Southern California Air Quality Management District and Air Resources Board, which currently limits sulfur in diesel fuel to 0.05 mass% maximum.
- ^{6/} If cetane quality is determined as calculated cetane index, the minimum cetane index shall be 43 for grades DF-A, DF-2, and CONUS DF-2.
- ^{7/} High altitudes may require higher cetane numbers.

APPENDIX E


Interrelationship of Physical/Chemical Properties of Fuels

APPENDIX E

Interrelationship of Physical/Chemical Properties of Fuels

A chart showing the approximate relationship between 50-percent and 90-percent recovery temperatures from the ASTM distillation, API gravity, cetane number, viscosity, cloud point, and net heating value is shown below. These interrelationships may not be applicable to all distillate fuels produced from current crude oils by current refining processes. Because of these limitations, this chart should only be used to estimate fuel properties in the absence of complete data, and should not be used to establish specifications.

It can be noted, however, that, in general, the higher 90-percent distillation point fuel coupled to lower °API gravity and higher viscosity give higher net heating value fuels, which can show increased mission range compared to less viscous lower boiling point fuels having high API gravities.



Related properties of distillate diesel fuels

(Source: "Update Proposed for Diesel Fuel Specs.," Automotive Engineering, Vol. 78, No. 11, pp. 34-40, 1970.)

DISTRIBUTION LIST

DEPARTMENT OF DEFENSE

DEFENSE TECHNICAL INFORMATION
CTR
CAMERON STATION 12
ALEXANDRIA VA 22314

DEPT. OF DEFENSE
ATTN: OASD/A&L (EP)
(MR DYCKMAN) 1
WASHINGTON DC 20301-8000

CDR
DEFENSE FUEL SUPPLY CTR
ATTN: DFSC-Q (MR MARTIN) 1
DFSC-DF (MR FRENCH) 1
CAMERON STATION
ALEXANDRIA VA 22304-6160

CDR
DEFENSE GENERAL SUPPLY CTR
ATTN: DGSC-SSM (MR REYNOLDS) 1
ATTN: DGSC-STC (MR DOYLE) 1
RICHMOND VA 23297-5000

DOD
ATTN: DUSDRE (RAT) (DR DIX) 1
ROOM 3-D-1089, PENTAGON
WASHINGTON DC 20301

DEFENSE ADVANCED RES PROJ
AGENCY
DEFENSE SCIENCES OFC 1
1400 WILSON BLVD
ARLINGTON VA 22209

DEPARTMENT OF THE ARMY

CDR
U.S. ARMY BELVOIR RESEARCH,
DEVELOPMENT & ENGINEERING CTR
ATTN: STRBE-VF 10
STRBE-BT 2
FORT BELVOIR VA 22060-5606

HQ, DEPT OF ARMY
ATTN: DALO-TSE (COL BLISS) 1
DALO-TSZ-B (MR KOWALCZYK) 1
DALO-AV 1
SARD-TN (DR CHURCH) 1
SARD-TR (MR APPEL) 1
WASHINGTON DC 20310-0005

CDR
US ARMY MATERIEL COMMAND
ATTN: AMCDE-SS 1
AMCSM-WST 1
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

CDR
US ARMY TANK-AUTOMOTIVE CMD
ATTN: AMSTA-RG 1
AMSTA-TSL (MR BURG) 1
AMSTA-MTC (MR GAGLIO),
AMSTA-MC, AMSTA-MV 1
AMSTA-RGP (MR RAGGIO) 1
AMSTA-MLF (MR KELLER) 1
AMCPM-LA-E
WARREN MI 48397-5000

DIRECTOR
US ARMY AVIATION RESEARCH &
TECHNOLOGY ACTIVITIES (AVSCOM)
ATTN: SAVRT-R (MR ANDRE) 1
AMES RESEARCH CENTER
(MAIL STOP 207-5)
MOFFETT FIELD CA 94035-1099

DIRECTOR
US ARMY MATERIEL SYSTEMS
ANALYSIS ACTIVITY
ATTN: AMXSY-CM (MR NIEMEYER) 1
AMXSY-CR 1
ABERDEEN PROVING GROUND MD
21005-5006

DIRECTOR
APPLIED TECHNOLOGY DIRECTORATE
U.S. ARMY R&T ACTIVITIES (AVSCOM)
ATTN: SAVDL-ATL-ATP (MR MORROW) 1
SAVDL-ATL-ASV 1
FORT EUSTIS VA 23604-5577

HQ, 172D INFANTRY BRIGADE (ALASKA)
ATTN: AFZT-DI-L 1
DIRECTORATE OF INDUSTRIAL
OPERATIONS
FORT RICHARDSON AK 99505

CDR
THEATER ARMY MATERIAL MGMT
CENTER (200TH)-DPGM
DIRECTORATE FOR PETROL MGMT
ATTN: AEAGD-MMC-PT-Q
(MR CARLONE) 1
APO NY 09052

CDR
US ARMY GENERAL MATERIAL &
PETROLEUM ACTIVITY
ATTN: STRGP-F (MR ASHBROOK) 1
STRGP-FE, BLDG 85-3
(MR GARY SMITH) 1
STRGP-FT (MR FOSTER) 1
NEW CUMBERLAND PA 17070-5008

HQ
US ARMY ARMAMENT, MUNITIONS, AND
CHEMICALS COMMAND
ATTN: AMSAR-LEM 1
ROCK ISLAND ARSENAL IL 61299-6000

CDR
US ARMY COLD REGION TEST CENTER
ATTN: STECR-TA 1
APO SEATTLE 98733

HQ, DEPT. OF ARMY
ATTN: DAEN-DRM 1
WASHINGTON DC 20310

CDR
US ARMY LABORATORY COMMAND
ATTN: AMSLC-AS-SE (DR ODOM) 1
AMSLC-TP-AL
(LTC SCHRADER) 1
ADELPHI MD 20783-1145

CDR
US ARMY FORCES COMMAND
ATTN: AFLG-REG 1
AFLG-POP 1
FORT MCPHERSON GA 30330

CDR
US ARMY RES & STDZN GROUP
(EUROPE)
ATTN: AMXSN-UK-RA (DR OERTEL) 1
BOX 65
FPO NEW YORK 09510

CDR
US ARMY TANK-AUTOMOTIVE CMD
PROGR EXEC OFF CLOSE COMBAT
PM ABRAMS, ATTN: AMCPM-ABMS 1
PM BFVS, ATTN: AMCPM-BFVS 1
PM 113 FOV, ATTN: AMCPM-M113 1
PM M60, ATTN: AMCPM-M60 1
WARREN MI 40397-5000

CDR, US ARMY AVIATION SYSTEMS
CMD
ATTN: AMSAV-EP (MR EDWARDS) 1
AMSAV-NS 1
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
US ARMY BALLISTIC RESEARCH LAB
ATTN: SLCBR-TB-E 1
SLCBR-SE-D (MR THOMAS) 1
ABERDEEN PROVING GROUND MD
21005-5006

CDR
US ARMY YUMA PROVING GROUND
ATTN: STEYP-MT-TL-M
(MR DOEBBLER) 1
YUMA AZ 85364-9103

CDR
US ARMY RESEARCH OFC
ATTN: SLCRO-EG (DR MANN) 1
SLCRO-CB 1
P O BOX 12211
RSCH TRIANGLE PARK NC 27709-2211

CDR
US ARMY TANK-AUTOMOTIVE CMD
PROGR EXEC OFF COMBAT SUPPORT
PM LIGHT TACTICAL VEHICLES
ATTN: AMCPM-TVL 1
PM MEDIUM TACTICAL VEHICLES
ATTN: AMCPM-TVM 1
PM HEAVY TACTICAL VEHICLES
ATTN: AMCPM-TVH 1
WARREN MI 40397-5000

CDR
US ARMY DEVELOPMENT AND
EMPLOYMENT AGENCY
ATTN: MODE-FDD-CSSB 1
FT LEWIS VA 98433-5000

CDR, US ARMY TROOP SUPPORT
COMMAND
ATTN: AMSTR-ME 1
AMSTR-S 1
AMSTR-E 1
AMSTR-WL 1
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
CHEMICAL R&D CENTER
ATTN: SMCCR-MMS
ABERDEEN PROVING GRD MD
21010-5423

PROJ MGR, MOBILE ELECTRIC POWER
ATTN: AMCPM-MEP-TM
7500 BACKLICK ROAD
SPRINGFIELD VA 22150

PROJ OFF, AMPHIBIOUS AND WATER
CRAFT
ATTN: AMCPM-AWC-R
4300 GOODFELLOW BLVD
ST LOUIS MO 63120

DIR
AMC PACKAGING, STORAGE, AND
CONTAINERIZATION CTR
ATTN: SDSTO-TE-S
TOBYHANNA PA 18466-5097

CDR
TRADOC COMBINED ARMS TEST
ACTIVITY
ATTN: ATCT-CA
FORT HOOD TX 76544

CDR
US ARMY DEPOT SYSTEMS CMD
ATTN: AMSDS-RM-EFO
CHAMBERSBURG PA 17201

CDR
US ARMY LEA
ATTN: DALO-LEP
NEW CUMBERLAND ARMY DEPOT
NEW CUMBERLAND PA 17070

HQ, EUROPEAN COMMAND
ATTN: J4/7-LJPO (LTC WEINER)
VAIHINGEN, GE
APO NY 09128

CDR
US ARMY FOREIGN SCIENCE & TECH
CENTER
ATTN: AIAST-RA-ST3 (MR BUSI)
AIAST-MT-1
FEDERAL BLDG
CHARLOTTESVILLE VA 22901

CDR
US ARMY GENERAL MATERIAL &
PETROLEUM ACTIVITY
ATTN: STRGP-PW (MR PRICE)
BLDG 247, DEFENSE DEPOT TRACY
TRACY CA 95376-5051

CDR
US ARMY ORDNANCE CENTER &
SCHOOL
ATTN: ATSL-CD-CS
ABERDEEN PROVING GROUND MD
21005

CDR
AMC MATERIEL READINESS SUPPORT
ACTIVITY (MRSA)
ATTN: AMXMD-MO (MR BROWN)
LEXINGTON KY 40511-5101

HQ, US ARMY T&E COMMAND
ATTN: AMSTE-TO-O
AMSTE-TE-T (MR RITONDO)
ABERDEEN PROVING GROUND MD
21005-5006

CDR
US ARMY ARMAMENT RESEARCH,
DEVELOPMENT & ENGRG CTR
ATTN: AMSMC-LC
AMSMC-SC
DOVER NJ 07801-5001

CDR
CONSTRUCTION ENG RSCH LAB
ATTN: CERL-EM
CERL-ES (MR CASE)
P O BOX 4005
CHAMPAIGN IL 61820

TRADOC LIAISON OFFICE
ATTN: ATFE-LO-AV
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

HQ
US ARMY TRAINING & DOCTRINE CMD
ATTN: ATCD-SL-5
FORT MONROE VA 23651-5000

CDR
US ARMY NATICK RES & DEV CENTER
ATTN: STRNA-YE (DR KAPLAN) 1
STRNA-U 1
NATICK MA 01760-5000

CDR
US ARMY QUARTERMASTER SCHOOL
ATTN: ATSM-CD 1
ATSM-PFS (MR ELLIOTT) 1
FORT LEE VA 23801

DIRECTOR
US ARMY RSCH & TECH ACTIVITIES
(AVSCOM)
PROPULSION DIRECTORATE
ATTN: SAVDL-PL-D (MR ACURIO) 1
21000 BROOKPARK ROAD
CLEVELAND OH 44135-3127

CDR
US ARMY TRANSPORTATION SCHOOL
ATTN: ATSP-CD-MS (MR HARNET) 1
FORT EUSTIS VA 23604-5000

PROJ MGR, PATRIOT PROJ OFFICE
ATTN: AMCPM-MD-T-C 1
U.S. ARMY MISSILE COMMAND
REDSTONE ARSENAL AL 35898

HQ, US ARMY ARMOR CENTER AND
FORT KNOX
ATTN: ATSB-CD 1
FORT KNOX KY 40121

CDR
COMBINED ARMS COMBAT
DEVELOPMENT ACTIVITY
ATTN: ATZL-CAT-E 1
FORT LEAVENWORTH KS 66027-5300

CDR
US ARMY LOGISTICS CTR
ATTN: ATCL-MS (MR A MARSHALL) 1
ATCL-C 1
FORT LEE VA 23801-6000

PROJECT MANAGER
PETROLEUM & WATER LOGISTICS
ATTN: AMCPM-PWL 1
4300 GOODFELLOW BLVD
ST LOUIS MO 63120-1798

CDR
US ARMY FIELD ARTILLERY SCHOOL
ATTN: ATSF-CD 1
FORT SILL OK 73503-5600

CDR
US ARMY ENGINEER SCHOOL
ATTN: ATZA-TSM-G 1
ATZA-CD 1
FORT BELVOIR VA 22060-5606

CDR
US ARMY INFANTRY SCHOOL
ATTN: ATSH-CD-MS-M 1
FORT BENNING GA 31905-5400

DIR
US ARMY MATERIALS TECHNOLOGY
LABORATORY
ATTN: SLCMT-M 1
SLCMT-MCM-P (DR FOPIANO) 1
WATERTOWN MA 02172-2796

CDR
US ARMY ARMOR & ENGINEER BOARD
ATTN: ATZK-AE-AR 1
FORT KNOX KY 40121

CDR
US ARMY MEDICAL R&D LABORATORY
ATTN: SGRD-USG-M (MR EATON) 1
FORT DETRICK, MD 21701

CDR
US ARMY AVIATION CTR & FT RUCKER
ATTN: ATZQ-DI 1
FORT RUCKER AL 36362

DEPARTMENT OF THE NAVY

CDR
NAVAL AIR PROPULSION CENTER
ATTN: PE-33 (MR D'ORAZIO) 1
PE-32 (MR MANGIONE) 1
P O BOX 7176
TRENTON NJ 06828

CDR
NAVAL SEA SYSTEMS CMD
ATTN: CODE 05M4 1
WASHINGTON DC 20362-5101

CDR
DAVID TAYLOR RESEARCH CTR
ATTN: CODE 2830 (MR SINGERMAN) 1
CODE 2759 (MR STRUCKO) 1
CODE 2831 1
ANNAPOLIS MD 21402-5067

JOINT OIL ANALYSIS PROGRAM -
TECHNICAL SUPPORT CTR 1
BLDG 780
NAVAL AIR STATION
PENSACOLA FL 32508-5300

CDR
NAVAL SHIP ENGINEERING CENTER
ATTN: CODE 6764 1
PHILADELPHIA PA 19112

PROJ MGR, M60 TANK DEVELOPMENT
ATTN: USMC-LNO 1
US ARMY TANK-AUTOMOTIVE
COMMAND (TACOM)
WARREN MI 48397

CDR
NAVAL AIR SYSTEMS CMD
ATTN: CODE 53645 (MR MEARNES) 1
WASHINGTON DC 20361

CDR
NAVAL AIR DEVELOPMENT CTR
ATTN: CODE 6061 1
WARMINSTER PA 18974

CDR
NAVAL RESEARCH LABORATORY
ATTN: CODE 6170 1
CODE 6180 1
CODE 6110 (DR HARVEY) 1
WASHINGTON DC 20375-5000

CDR
NAVAL FACILITIES ENGR CTR
ATTN: CODE 1202B (MR R BURRIS) 1
200 STOVAL ST
ALEXANDRIA VA 22322

DEPUTY COMMANDING GENERAL
US MARINE CORPS RESEARCH,
DEVELOPMENT & ACQUISITION CMD
ATTN: CBAL 1
QUANTICO VA 22134-5080

OFFICE OF THE CHIEF OF NAVAL
RESEARCH
ATTN: OCNR-126 (DR ROBERTS) 1
ARLINGTON, VA 22217-5000

CDR
NAVY PETROLEUM OFC
ATTN: CODE 43 (MR LONG) 1
CAMERON STATION
ALEXANDRIA VA 22304-6180

DEPARTMENT OF THE AIR FORCE

HQ, USAF
ATTN: LEYSF (COL LEE) 1
WASHINGTON DC 20330

CDR
USAF 3902 TRANSPORTATION
SQUADRON
ATTN: LGTVP (MR VAUGHN) 1
OFFUTT AIR FORCE BASE NE 68113

CDR
US AIR FORCE WRIGHT AERONAUTICAL
LAB
ATTN: AFWAL/POSF 1
AFWAL/POSL (MR JONES) 1
AFWAL/MLSE 1
AFWAL/MLBT (MR SNYDER) 1
WRIGHT-PATTERSON AFB OH
45433-6563

CDR
SAN ANTONIO AIR LOGISTICS
CTR
ATTN: SAALC/SFT (MR MAKRIS) 1
SAALC/MMPRR 1
KELLY AIR FORCE BASE TX 78241

CDR
DET 29
ATTN: SA-ALC/SFM 1
CAMERON STATION
ALEXANDRIA VA 22314

HQ AIR FORCE SYSTEMS CMD
ATTN: AFSC/DLF (DR DUES) 1
ANDREWS AFB MD 20334

CDR
WARNER ROBINS AIR LOGISTIC CTR
ATTN: WRALC/MMTV
ROBINS AFB GA 31098

1

US DEPARTMENT OF ENERGY
ATTN: MR ECKLUND
MAIL CODE CE-151
FORRESTAL BLDG.
1000 INDEPENDENCE AVE, SW
WASHINGTON DC 20585

1

OTHER GOVERNMENT AGENCIES

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION
ATTN: AWS-110
800 INDEPENDENCE AVE, SW
WASHINGTON DC 20590

1

ENVIRONMENTAL PROTECTION
AGENCY
AIR POLLUTION CONTROL
2565 PLYMOUTH ROAD
ANN ARBOR MI 48105

1

NATIONAL AERONAUTICS AND
SPACE ADMINISTRATION
LEWIS RESEARCH CENTER
CLEVELAND OH 44135

1

END

DATE

FILMED

11-88

DTIC