

MEMORANDUM REPORT BRL-MR-3714

BRL

1938 - Serving the Army for Fifty Years - 1988

AD-A201 634

**SPECTRAL STUDIES OF PROPELLANT COMBUSTION:
EXPERIMENTAL DETAILS AND EMISSION RESULTS
FOR M-30 PROPELLANT**

JOHN A. VANDERHOFF

DECEMBER 1988

**DTIC
ELECTE
DEC 27 1988
S E D**

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

U.S. ARMY LABORATORY COMMAND

**BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

88 12 27 009

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; distribution unlimited.		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) BRL-MR-3714			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION US Army Ballistic Research Laboratory		6b. OFFICE SYMBOL (if applicable) SLCBR-IB	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) Aberdeen Proving Ground, MD 21005-5066			7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO. 61102A	PROJECT NO. AH43	TASK NO.
			WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) SPECTRAL STUDIES OF PROPELLANT COMBUSTION: EXPERIMENTAL DETAILS AND EMISSION RESULTS FOR M-30 PROPELLANT					
12. PERSONAL AUTHOR(S) John A. Vanderhoff					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM Jun 87 TO Jun 88		14. DATE OF REPORT (Year, Month, Day)	
15. PAGE COUNT					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP			
21	02		Emission, Spectroscopy, Solid Propellant, Combustion, Steady State Burning, hydroxides, Nitrogen compounds, cyanides. (origin)		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
A windowed strand burner has been constructed and used to characterize the steady state burning of propellants at moderate pressure using uv - visible spectroscopic techniques. Emission spectroscopy has been performed on a triple base propellant (M-30) and three reactive transient combustion species (CN, NH and OH) have been profiled over a pressure range from 0.66 to 1.5 MPa. Reaction zone lengths on the order of 1 mm were determined from the CN and NH profiles. The strand burner is expected to be useful for future planned absorption and laser induced fluorescence studies on a variety of propellants.					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL DR. JOHN A. VANDERHOFF			22b. TELEPHONE (Include Area Code) 301-278-7069		22c. OFFICE SYMBOL SLCBR-IB-I

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES.....	5
I. INTRODUCTION.....	7
II. EXPERIMENTAL.....	8
III. RESULTS.....	13
IV. FUTURE WORK.....	19
REFERENCES.....	21
DISTRIBUTION LIST.....	23

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Strand Burner Assembly Drawing.....	9
2	Cross Section of Strand Burner.....	10
3	Top View of Strand Burner and Associated Optical Systems.....	10
4	Multiple Emission Spectra Versus Wavelength.....	12
5	Detail of the Optical Collection System Showing the Geometry that can Cause a Shadowing Effect.....	12
6	A Comparison of Burn Rate Data for M-30 Propellant at Moderate Pressures.....	13
7	Calibrated Emission Intensity Versus Wavelength from 300 to 680 nm for M-30 Burning at 0.66 MPa.....	14
8	Calibrated Emission Intensity Versus Wavelength Over a Much Reduced Range, 390 to 530 nm.....	15
9	Emission Intensity Versus Wavelength for M-30 Burning at 0.66 MPa.....	16
10	Emission Intensity for CN Versus Distance from the Propellant Surface Using M-30 Propellant Burning at 1.0 MPa.....	17
11	Emission Intensity for NH Versus Distance from the Propellant Surface Using M-30 Propellant Burning at 1.0 MPa.....	17
12	Emission Intensity for OH Versus Distance from the Propellant Surface Using M-30 Propellant Burning at 1.0 MPa.....	18
13	Emission Intensity for NH (Solid Line) and CN (Dotted Line) Versus Distance from the Propellant Surface.....	19

I. INTRODUCTION

There is considerable uncertainty about the chemical and physical processes occurring in solid propellant combustion. Detailed probing of the gas phase region adjacent to the burning surface of the propellant is necessary for a more complete understanding of the combustion process. Spectroscopic experiments which identify and track the behavior of intermediate combustion products can provide information for developing reaction networks which assist in the characterization of the combustion chemistry.

Many articles have been written concerning the detailed chemical processes occurring in solid propellant combustion and two review articles by Fifer¹ and Lengelle, et al.,² well describe the important contributions. When considering only the spectral studies that employ visible and/or uv radiation the publication list is much smaller. Double base propellants have been studied with emission and absorption techniques.^{3,4} In these studies blackbody temperature estimates, line emission signals from impurity metallic species and a C_2 radical species were reported for the final flame zone (explosion zone). Ammonium perchlorate (AP) and nitramine propellants (HMX - cyclotetramethylenetetranitramine and RDX - cyclotrimethylenetrinitramine) have been studied more extensively in the recent past. Emission intensity profiles of several chemically active transient species have been obtained for AP and nitramine propellants. CN^{5-7} and $OH^{6,7}$ profiles were measured for both types of propellants whereas an NH profile is published only for a nitramine propellant.⁶ Equilibrium may not be achieved during combustion; thus, energetic species which emit visible/uv radiation are not necessarily equilibrated with respect to the partitioning of energy in their electronic, vibrational and rotational energy levels. Consequently emission intensity profiles are not always good indicators of actual species concentration. Nonetheless there is such a scarcity of actual data on transient species occurring in propellant combustion (absolute concentrations are virtually nonexistent) that the shortcomings of the emission technique are not yet a serious drawback. A number of techniques which optically probe the region of interest have a better potential for determining absolute concentrations. Laser induced fluorescence (LIF) measurements have been published which illustrate fluorescence intensity profiles of CN and OH^8 in AP propellant combustion and of CN,^{8,9} NH,⁹ OH,⁹ and NO_2^9 in nitramine propellant combustion. A gas phase temperature profile has also been determined from the rotational structure of OH.⁹ Coherent anti-Stokes Raman scattering (CARS)¹⁰ has been applied to a nitramine propellant burning in room air. Several transient species were identified (HCN and NO) and a two point profile with concentration estimates has been determined.

In this paper M-30, a common triple base propellant used for long range artillery and tank rounds, has been chosen for the initial studies. See Table 1 for the composition. Several reasons led to this choice of propellant. First, it has no apparent dark zone; thus the flame sits close to the propellant surface providing one local-hot region for spectral emission of intermediate species. Second, cylindrical sticks of this propellant were available. Spectroscopic studies have been carried out in a windowed strand burner. Spatially resolved uv-visible emission spectra for M-30 burning in a nitrogen environment have been obtained over a pressure range from 0.35 to 1.5 MPa. Species identification, spatial profiles of CN, NH and OH and a

blackbody temperature estimate have been extracted from these emission spectra. Moreover, estimates of reaction zone lengths have been made from NH and CN emission intensity profiles. These results are then compared with other published reaction zone length values.

Table 1. Propellant Ingredients

<u>Composition Wt. %</u>	<u>M-30</u>	<u>AP</u>	<u>API</u>	<u>HMX1</u>	<u>HMX2</u>
Nitroquanidine	47.7				
Nitrocellulose	28.0				
Nitroglycerin	22.5				
Ethyl Centralite	1.5				
Sodium Aluminum Fluoride	0.3				
Ammonium Perchlorate		78	87		
Polybutadiene Binder		22	13		
HMX				73	80
TMETN*				17	
Polyester Binder					20

*Trimethylolethanetrinitrate

II. EXPERIMENTAL

An assembly drawing of the windowed strand burner constructed and used for the data reported here is shown on Figure 1. The goal of this design was to produce a compact vessel that would be versatile and time efficient. It is composed of four distinct parts: a base plate, main chamber, top piece and five window assemblies. All of these pieces screw rather than bolt together thus minimizing the time it takes to change propellant samples and windows. A video camera, used for burn rate measurements, eliminates the need for the time consuming operation of installing fuse wires in the propellant samples. This vessel was constructed from 304 stainless steel and has an overall height of 25 cm. It has an outside diameter of 15 cm and an inside diameter of 7.6 cm. The internal volume is approximately 0.9 liters. Five optical ports with a 2.5 cm clear aperture are available for use. Depending upon the experiment either normal incidence or Brewster's angle windows can be installed. The four ports which are opposed are currently used for experiments. The fifth port, located at the top, is for possible future use in radiation-augmented burning studies. To have the propellant burn in a cigarette fashion a flow of a nonreactive gas (nitrogen) around the propellant stick is required. The route of regulated nitrogen through the flow straighteners and out the exit orifice is illustrated on Figure 2. A 0.64 mm exit orifice was used. This provided a nitrogen flow rate of about four times the propellant gasification rate over the pressure range studied. Possible pressure transients which may occur during a propellant burn are minimized by the four liter surge tank plumbed to the strand burner. Ignition of the propellant, not shown, is accomplished by rapidly heating a small diameter nickel wire which has been placed on the propellant surface. The helium-neon (HeNe) laser is used for several purposes: optimizing the collection optics used for gathering the emission signals, measuring the transparency of the combustion gas and determining the position of the burning propellant surface.




Figure 1. Strand Burner Assembly Drawing

A top view of the strand burner and associated optical systems are shown on Figure 3. Burn rates of the propellant samples are obtained with a video camera and macro lens. These video records also verify whether the propellant burns in a cigarette fashion with a horizontal, flat burning surface. Emission signals from the propellant sample are collected and focussed onto a 0.1 mm horizontally oriented entrance slit by two convex lenses with a magnification of two. The resulting spatial resolution is 0.1 mm full width at half maximum (FWHM). This resolution has been experimentally verified by recording the signal produced from various size illuminated slits as a function of position. A 0.25 m monochromator disperses the emission signal onto an intensified linear photodiode array and a computer is used for acquisition, manipulation and storage of the optical data. For the emission spectra taken here a 1180 grooves per mm grating has been used in the monochromator. This combination gives a spectral resolution of about 0.3 nm.

In a typical experiment the following sequence of events would occur. The propellant sample and ignition wire are installed in the strand burner. After closing the vessel it is then pressurized to the desired pressure and the video recording system turned on. Propellant burning is now initiated by




Figure 2. Cross Section of Strand Burner




Figure 3. Top View of Strand Burner and Associated Optical Systems

switching on a power supply to heat the ignition wire. This switch also triggers a digital oscilloscope which records the HeNe photodiode output. Two methods have been used to initiate emission spectrum accumulation by the photodiode array. The simpler method is a manual start performed by the experimenter. The video camera real-time display provides the experimenter with a rough idea of when to start. Alternatively, the change in the HeNe photodiode output that occurs when the HeNe laser impinges on it has been used as an automatic start for emission spectra accumulation. Unfortunately this triggering method misses part of the data where the propellant surface is just entering the sampling volume but has not burned down to a position where there is no solid blocking the path of the HeNe. Once the photodiode array is triggered it repetitively scans and resets 120 times while storing each of these 120 scans into buffer memory. The total data accumulation time (typically 5 to 10 s) as well as the time for each scan can be varied over a wide range. An example of a portion of the multiple emission spectra obtained during a single propellant burn is shown on Figure 4. In this case the time used for each scan was 16 ms and the time between active scans was 48 ms; thus the emission was sampled every 64 ms. In the wavelength region shown on Figure 4 the time variation for CN (388 nm region or equivalently 3880 angstroms region) and K (405 nm) are represented for M-30 burning in 0.66 MPa (6.6 atm) of nitrogen. This temporal variation of the emission spectra can be converted to a distance from the propellant surface by using the burn rate of the propellant as determined from the video record. Emission intensities for individual species, calculated by integration of their spectral features, can be determined as a function of distance from the propellant surface. It should be noted that the CN and NH (336 nm) species are relatively short lived; that is, they appear close to the propellant surface and typically are consumed at distances less than 2 mm from the burning surface. Considering this small extent, a shadowing effect occurs which can alter the emission intensity profile; see Figure 5. Previous investigators have discussed this effect^{5,8,11} and in one case a trial and error method⁵ was used to extract a "corrected" profile. Since future experiments to measure the transient species involve a technique (optical absorption) that is not influenced by shadowing, no significant attempt has been made to account for shadowing. A final comment about this effect is that it goes in a direction that makes the intensity profiles appear narrower than the actual case. This observation, together with a comparison of the present data for NH and CN with the published data of Branch, et al.,¹² on a low pressure flame suggests one possible correction. The low pressure flame data look much more symmetric than the present data which have a rather abrupt rise. If this abrupt rise were altered to be symmetric with the fall off, the FWHMs reported here for CN and NH would be increased by about 25%. Non-horizontal burning of the propellant surface will also compromise the spatial resolution of the emission intensity profiles. The video record has a resolution of about 0.15 mm for the detection of this effect and provides a quality control on acceptable propellant strand burns. Lastly, the propellant surface moves during the data accumulation and readoff of the photodiode array. For these experiments the scan time was 16 ms and the burning rate varied from about 1 to 3 mm/s depending on the pressure. Thus the burning surface moves at most 0.05 mm during an emission scan.




Figure 4. Multiple Emission Spectra Versus Wavelength.
Here only a portion of the 120 emission spectra taken for each
propellant burn is shown. These spectra are 64 ms apart in time.




Figure 5. Detail of the Optical Collection System Showing the Geometry
that can Cause a Shadowing Effect. The angle of collection has been
exaggerated for clarity. At positions where the propellant surface is
closer to the optical focus point of the collection lens part of the
light emission will be blocked from view by the propellant.

III. RESULTS

One of the more important measurements for characterizing a propellant is the burn rate as a function of pressure. Moreover, this parameter is required in the present context to be able to plot emission intensity as a function of distance. The propellant samples for study are small solid cylinders 6 mm in diameter and 20 mm long. To minimize ignition effects and different temperature gradients close to the propellant strand stand, only the middle 10 mm was observed for burn rate measurements. A macro lens magnified the propellant strand nine times and the video record of the burn enabled the burn rate to be determined with an estimated absolute accuracy of $\pm 8\%$. A comparison of the present results with unpublished data of Miller¹³ is shown on Figure 6 and the agreement is excellent.




Figure 6. A Comparison of Burn Rate Data for M-30 Propellant at Moderate Pressures

A coarse emission spectrum for M-30 burning at 0.6 MPa (6.6 atm) is shown on Figure 7. The wavelength range extends from 300 to 680 nm. The emission detection system could only capture approximately 50 nm of spectra at a time so Figure 7 is a result of piecing together eight individual spectra. A standards lamp was employed to calibrate the detection system for wavelength sensitivity and geometric effects; hence the emission intensity is an accurate relative intensity profile with small line emissions omitted. Enormous sodium D lines emissions are observed which dominate the detection system for more than a 50 nm range. The small amount of sodium aluminum fluoride used as a muzzle flash suppressant has produced the overwhelming majority of visible

emission. A portion of the spectrum removed from the sodium line emission is shown in greater detail on Figure 8. Assuming the emission to be dominated by continuum blackbody radiation and the emissivity to be wavelength independent over this range a temperature characteristic of the combustion gas can be calculated from Planck's radiation equation. A least squares fit to the data results in a temperature of 2587 K with a standard deviation of 189 K. This temperature is less than the calculated adiabatic value of 3040 K; this is not too surprising since the measurements were made at 0.66 MPa (6.6 atm) where it is probable that the chemistry has not reached completion. What is assumed in the above analysis is that continuum chemiluminescence is negligible. This means concentrations of common combustion species such as NO_2 and combustion reactions like $\text{CO} + \text{O}$ that exhibit broad band chemiluminescence over this wavelength region are neglected. In some cases this is certainly not true; i.e., close to the propellant surface where these species can exist. On the positive side the data of Figure 8 are evenly distributed about the least squares fit which means that the emission data have a wavelength dependence characteristic of blackbody emission. A serious attempt to obtain gas phase temperature profiles using this technique should employ a much coarser grating so that at any given time a larger portion of the wavelength spectrum would be sampled.




Figure 7. Calibrated Emission Intensity Versus Wavelength from 300 to 680 nm for M-30 Burning at 0.66 MPa. Only the overwhelming line emission from the sodium D lines have been included in this coarse emission spectrum.




Figure 8. Calibrated Emission Intensity Versus Wavelength Over a Much Reduced Range, 390 to 530 nm. This profile is a subset of the profile of Figure 7. The solid line is a least squares fit to the data to extract a blackbody temperature.

Spectroscopic observation of the 388, 336, and 307 nm wavelength regions provided the necessary emission data to allow spatial profiling of CN, NH, and OH over a pressure range from .35 to 1.5 MPa. Representative emission spectra from the region which includes CN, NH, and OH emission are shown on Figures 9a, b, c, respectively. Multiple emission spectra are used to obtain the CN, NH and OH emission intensity versus distance from the propellant surface. These profiles are shown on Figures 10, 11, and 12, respectively. The negative distances indicate that the propellant has not burned past the detection volume. Reaction zone lengths have been determined from the FWHMs of these types of profiles and the results together with other published values^{5,6,8,9} for other propellants are listed in Table 2. The propellant ingredients are listed in Table 1. There is such a scarcity of reaction zone length data for solid propellant combustion that the data in Table 2 include two formulations of ammonium perchlorate (AP and AP1) which are composite propellants, three kinds of nitramine propellants (HMX - neat; HMX1 and HMX2 - composite) and a triple base propellant (M-30). HMX and HMX2 are reported to have dark zones while HMX1, AP, and M-30 do not. These and other differences in the various propellants studied make quantitative comparisons of dubious value and point out a need for experimental efforts to focus on a few standard propellants. Qualitatively, the values of Table 2 generally agree to well within a factor of three and the reaction zone lengths are mostly larger than that of a simple atmospheric pressure flame (0.5 mm). In the present study it




Figure 9. Emission Intensity Versus Wavelength for M-30 Burning at 0.66 MPa. These spectra have not been corrected for either wavelength sensitivity or geometric effects. (a) CN emission is readily observed over the region from 385 to 390 nm. Potassium emission is detected at 405 nm. (b) NH emission is observed at 336 nm, CN at 359 nm, and Na at 330 nm. (c) OH emission is observed in the 305 to 310 nm region. A prominent peak at about 295 nm has not been identified.




Figure 10. Emission Intensity for CN Versus Distance from the Propellant Surface Using M-30 Propellant Burning at 1.0 MPa




Figure 11. Emission Intensity for NH Versus Distance from the Propellant Surface Using M-30 Propellant Burning at 1.0 MPa




Figure 12. Emission Intensity for OH Versus Distance from the Propellant Surface Using M-30 Propellant Burning at 1.0 MPa

Table 2. Summary of Reaction Zone Lengths for Various Propellants

<u>Species</u>	<u>Reaction Zone Length</u>	<u>Pressure</u>	<u>Propellant</u>	<u>Investigator & Technique</u>
CN	2.0 mm	1 atm	AP	Povinelli - Emiss
CN	2.5 mm	1 atm	AP1	Edwards - Emiss
CN	0.7 mm	1 atm	HMX	Parr - PLIF
CN	0.6-0.4 mm	1-8 atm	AP1	Edwards - LIF
CN	0.5 mm	7-35 atm	HMX1	Edwards - LIF
CN	1.8-0.5 mm	18-35 atm	HMX2	Edwards - LIF
CN	1.5-1.2 mm	6-15 atm	M-30	Present work - Emiss
NH	0.5 mm	1 atm	HMX	Parr - PLIF
NH	1.2 mm	35 atm	HMX1	Edwards - Emiss
NH	1.0-0.7 mm	6-15 atm	M-30	Present work - Emiss

has also been observed that to about 0.1 mm both NH and CN appear at the same place but CN extends further out in the propellant combustion gas. The data that supports this conclusion comes from the larger reaction zone lengths observed for CN and from the data of Figure 13. In order to produce the data in Figure 13 the spectrometer was set analogous to that for recording the emission spectrum shown on Figure 9b. Here NH appears at 336 nm but now a vibrationally excited band of CN can be observed at 359 nm. This excited band of CN is much weaker than the 388 nm band but its emission intensity profile indicates that CN appears about 0.1 mm closer to the propellant surface than NH.




Figure 13. Emission Intensity for NH (Solid Line) and CN (Dotted Line) Versus Distance from the Propellant Surface. The emission intensities were recorded simultaneously for M-30 burning at 0.66 MPa.

Better signal-to-noise characteristics are observed for CN and NH emission profiles relative to the OH emission profile shown on Figure 12. Nonetheless, the OH emission intensity rises sharply and extends further out into the flame zone than does either CN or NH. This behavior is found in most flame systems.

IV. FUTURE WORK

Future studies include determining the applicability of employing broadband uv-visible absorption as a combustion diagnostic for these strand burner studies. Should absorption measurements prove feasible a variety of concentration profiles for intermediate combustion species could be obtained. With sufficient spectral resolution temperature profiles may also be extracted.

LIF is also planned to be used to profile intermediate combustion species such as NCO.

REFERENCES

1. R.A. Fifer, "Chemistry of Nitrate Ester and Nitramine Propellants," in Fundamentals of Solid Propellant Combustion, edited by K. Kuo and M. Summerfield, AIAA Progress in Astronautics and Aeronautics Series, Vol. 90, 1984.
2. G. Lengelle, A. Bizot, J. Duterque, and J.F. Trubert, "Steady-State Burning of Homogeneous Propellants," in Fundamentals of Solid Propellant Combustion, edited by K. Kuo and M. Summerfield, AIAA Progress in Astronautics and Aeronautics Series, Vol. 90, 1984.
3. G.A. Heath and R. Hirst, "Some Characteristics of the High Pressure Combustion of Double-Base Propellant," 8th Symposium (International) on Combustion, p. 711, 1962.
4. R.G. Rekers and D.S. Villars, "Flame Zone Spectroscopy of Solid Propellants. II. Double Base Propellant JPN^{*}," J. Opt. Soc. Amer., Vol. 46(9), p. 534, 1956.
5. L.A. Povinelli, "A Study of Composite Solid-Propellant Flame Structure Using a Spectral Radiation Shadowgraph Technique," AIAA Journal, Vol. 3(9), p. 1593, 1965.
6. T. Edwards, D.P. Weaver, D.H. Campbell, and S. Hulsizer "Investigation of High Pressure Solid Propellant Chemistry Using Emission Spectroscopy," J. Propulsion, Vol. 2(3), p. 228, 1986.
7. V.M. Mal'tsev, A.G. Stasenko, V.A. Selezner, and P.F. Pokhil, "Spectroscopic Investigation of Combustion Zones of Flame Flares of Condensed Systems," Fizika Goreniya i Vzryva, Vol. 9(2), p. 220, 1973.
8. T. Edwards, D.P. Weaver, and D.H. Campbell, "Laser-Induced Fluorescence in High Pressure Solid Propellant Flames," Applied Optics, Vol. 26(17), p. 3496, 1987.
9. T. Parr and D.H. Parr, "Species and Temperature Profiles in Ignition and Deflagration of HMX," Western States Section/Combustion Institute, Paper WSS/CI 87-8, April 1987.
10. K. Aron and L.E. Harris, "CARS Probe of RDX Decomposition," Chem. Phys. Lett., Vol. 103(5), p. 413, 1984.
11. W.R. Anderson, L.J. Decker, and A.J. Kotlar, "Concentration Profiles of NH and OH in a Stoichiometric CH₄/N₂O Flame by Laser Excited Fluorescence and Absorption," Combustion and Flame, Vol. 48, p. 179, 1982.
12. M.C. Branch, A. Alfarayedhi, and M. Sadeqi, "Laser Induced Fluorescence Measurements of the Structure of CH₄/NO₂/O₂ Flames," Proceedings, Second ASME/JSME Thermal Engineering Conference, Vol. 1, p. 181, 1987.
13. M.S. Miller, unpublished data, Ballistic Research Laboratory, April 1988.

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander US Army Aviation Systems Command ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798
1	HQ DA (SARD-TR) Washington, DC 20310	1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	4	Commander US Army Research Office ATTN: R. Ghirardelli D. Mann R. Singleton R. Shaw P.O. Box 12211 Research Triangle Park, NC 27709-2211
1	Commander US Army Laboratory Command ATTN: AMSLC-TD Adelphi, MD 20783-1145	1	Commander US Army Communications - Electronics Command ATTN: AMSEL-ED Fort Monmouth, NJ 07703
1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-MSI Picatinny Arsenal, NJ 07806-5000	2	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCA-G, D.S. Downs J.A. Lannon Dover, NJ 07801
1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-LC-G, L. Harris Dover, NJ 07801
1	Director Benet Weapons Laboratory Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCB-TL Watervliet, NY 12189-4050		
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-7300		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-SCA-T, L. Stiefel Dover, NJ 07801	1	Office of Naval Research Department of the Navy ATTN: R.S. Miller, Code 432 800 N. Quincy Street Arlington, VA 22217
2	Commander US Army Missile Command ATTN: AMSMI-RD AMSMI-AS Redstone Arsenal, AL 35898-5000	1	Commander Naval Air Systems Command ATTN: J. Ramnarace, AIR-54111C Washington, DC 20360
2	Commander US Army Missile Command ATTN: AMSMI-RK, D.J. Ifshin W. Wharton Redstone Arsenal, AL 35898	2	Commander Naval Ordnance Station ATTN: C. Irish P.L. Stang, Code 515 Indian Head, MD 20640
1	Commander US Army Missile Command ATTN: AMSMI-RKA, A.R. Maykut Redstone Arsenal, AL 35898-5249	1	Commander Naval Surface Weapons Center ATTN: J.L. East, Jr., G-23 Dahlgren, VA 22448-5000
1	Commander US Army Tank Automotive Cmd ATTN: AMSTA-DI Warren, MI 48090	2	Commander Naval Surface Weapons Center ATTN: R. Bernecker, R-13 G.B. Wilmot, R-16 Silver Spring, MD 20902-5000
1	Director US Army TRADOC Analysis Cmd ATTN: ATAA-SL White Sands Missile Range, NM 88002-5502	5	Commander Naval Research Laboratory ATTN: M.C. Lin J. McDonald E. Oran J. Shnur R.J. Doyle, Code 6110 Washington, DC 20375
1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5400	1	Commanding Officer Naval Underwater Systems Center Weapons Dept. ATTN: R.S. Lazar/Code 36301 Newport, RI 02840
1	Commander US Army Development and Employment Agency ATTN: MODE-ORO Fort Lewis, WA 98433-5000	1	Superintendent Naval Postgraduate School Dept. of Aeronautics ATTN: D.W. Netzer Monterey, CA 93940

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
4	AFRPL/DY, Stop 24 ATTN: R. Corley R. Geisler J. Levine D. Weaver Edwards AFB, CA 93523-5000	1	Applied Combustion Technology, Inc. ATTN: A.M. Varney P.O. Box 17885 Orlando, FL 32860
1	AFRPL/MKPB, Stop 24 ATTN: B. Goshgarian Edwards AFB, CA 93523-5000	2	Applied Mechanics Reviews The American Society of Mechanical Engineers ATTN: R.E. White A.B. Wenzel 345 E. 47th Street New York, NY 10017
1	AFOSR ATTN: J.M. Tishkoff Bolling Air Force Base Washington, DC 20332	1	Atlantic Research Corp. ATTN: M.K. King 5390 Cherokee Avenue Alexandria, VA 22314
1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000	1	Atlantic Research Corp. ATTN: R.H.W. Waesche 7511 Wellington Road Gainesville, VA 22065
1	AFWL/SUL Kirtland AFB, NM 87117	1	AVCO Everett Rsch. Lab. Div. ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149
1	NASA Langley Research Center Langley Station ATTN: G.B. Northam/MS 168 Hampton, VA 23365	1	Battelle Memorial Institute Tactical Technology Center ATTN: J. Huggins 505 King Avenue Columbus, OH 43201
4	National Bureau of Standards ATTN: J. Hastie M. Jacox T. Kashiwagi H. Semerjian US Department of Commerce Washington, DC 20234	1	Cohen Professional Services ATTN: N.S. Cohen 141 Channing Street Redlands, CA 92373
1	OSD/SDIO/UST ATTN: L.H. Caveny Pentagon Washington, DC 20301-7100	1	Exxon Research & Eng. Co. ATTN: A. Dean Route 22E Annandale, NJ 08801
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, CA 95813		

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Ford Aerospace and Communications Corp. DIVAD Division Div. Hq., Irvine ATTN: D. Williams Main Street & Ford Road Newport Beach, CA 92663	1	Honeywell, Inc. Government and Aerospace Products ATTN: D.E. Broden/ MS MN50-2000 600 2nd Street NE Hopkins, MN 55343
1	General Applied Science Laboratories, Inc. 77 Raynor Avenue Ronkonkama, NY 11779-6649	1	IBM Corporation ATTN: A.C. Tam Research Division 5600 Cottle Road San Jose, CA 95193
1	General Electric Armament & Electrical Systems ATTN: M.J. Bulman Lakeside Avenue Burlington, VT 05401	1	IIT Research Institute ATTN: R.F. Remaly 10 West 35th Street Chicago, IL 60616
1	General Electric Company 2352 Jade Lane Schenectady, NY 12309	2	Director Lawrence Livermore National Laboratory ATTN: C. Westbrook M. Costantino P.O. Box 808 Livermore, CA 94550
1	General Electric Ordnance Systems ATTN: J. Mandzy 100 Plastics Avenue Pittsfield, MA 01203	1	Lockheed Missiles & Space Co. ATTN: George Lo 3251 Hanover Street Dept. 52-35/B204/2 Palo Alto, CA 94304
2	General Motors Rsch Labs Physics Department ATTN: T. Sloan R. Teets Warren, MI 48090	1	Los Alamos National Lab ATTN: B. Nichols T7, MS-B284 P.O. Box 1663 Los Alamos, NM 87545
2	Hercules, Inc. Allegany Ballistics Lab. ATTN: R.R. Miller E.A. Yount P.O. Box 210 Cumberland, MD 21501	1	National Science Foundation ATTN: A.B. Harvey Washington, DC 20550
1	Hercules, Inc. Bacchus Works ATTN: K.P. McCarty P.O. Box 98 Magna, UT 84044	1	Olin Corporation Smokeless Powder Operations ATTN: V. McDonald P.O. Box 222 St. Marks, FL 32355

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Paul Gough Associates, Inc. ATTN: P.S. Gough 1048 South Street Portsmouth, NH 03801	1	Stevens Institute of Tech. Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030
2	Princeton Combustion Research Laboratories, Inc. ATTN: M. Summerfield N.A. Messina 475 US Highway One Monmouth Junction, NJ 08852	1	Textron, Inc. Bell Aerospace Co. Division ATTN: T.M. Ferger P.O. Box 1 Buffalo, NY 14240
1	Hughes Aircraft Company ATTN: T.E. Ward 8433 Fallbrook Avenue Canoga Park, CA 91303	1	Thiokol Corporation Elkton Division ATTN: W.N. Brundige P.O. Box 241 Elkton, MD 21921
1	Rockwell International Corp. Rocketdyne Division ATTN: J.E. Flanagan/HB02 6633 Canoga Avenue Canoga Park, CA 91304	1	Thiokol Corporation Huntsville Division ATTN: R. Glick Huntsville, AL 35807
4	Sandia National Laboratories Combustion Sciences Dept. ATTN: R. Cattolica S. Johnston P. Mattern D. Stephenson Livermore, CA 94550	3	Thiokol Corporation Wasatch Division ATTN: S.J. Bennett P.O. Box 524 Brigham City, UT 84302
1	Science Applications, Inc. ATTN: R.B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364	1	TRW ATTN: M.S. Chou MSR1-1016 1 Parke Redondo Beach, CA 90278
1	Science Applications, Inc. ATTN: H.S. Pergament 1100 State Road, Bldg. N Princeton, NJ 08540	1	United Technologies ATTN: A.C. Eckbreth East Hartford, CT 06108
3	SPI International ATTN: G. Smith D. Crosley D. Golden 333 Ravenswood Avenue Menlo Park, CA 94025	3	United Technologies Corp. Chemical Systems Division ATTN: R.S. Brown T.D. Myers (2 copies) P.O. Box 50015 San Jose, CA 95150-0015

DISTRIBUTION LIST

<u>No. Of Copies</u>	<u>Organization</u>	<u>No. Of Copies</u>	<u>Organization</u>
1	Universal Propulsion Company ATTN: H.J. McSpadden Black Canyon Stage 1 Box 1140 Phoenix, AZ 85029	2	University of Southern California Dept. of Chemistry ATTN: S. Benson C. Wittig Los Angeles, CA 90007
1	Veritay Technology, Inc. ATTN: E.B. Fisher 4845 Millersport Highway P.O. Box 305 East Amherst, NY 14051-0305	1	Case Western Reserve Univ. Div. of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135
1	Brigham Young University Dept. of Chemical Engineering ATTN: M.W. Beckstead Provo, UT 84601	1	Cornell University Department of Chemistry ATTN: T.A. Cool Baker Laboratory Ithaca, NY 14853
1	California Institute of Tech. Jet Propulsion Laboratory ATTN: MS 125/159 4800 Oak Grove Drive Pasadena, CA 91103	1	Univ. of Dayton Rsch Inst. ATTN: D. Campbell AFRPL/PAP Stop 24 Edwards AFB, CA 93523
1	California Institute of Technology ATTN: F.E.C. Culick/ MC 301-46 204 Karman Lab. Pasadena, CA 91125	1	University of Florida Dept. of Chemistry ATTN: J. Winefordner Gainesville, FL 32611
1	University of California, Berkeley Mechanical Engineering Dept. ATTN: J. Daily Berkeley, CA 94720	3	Georgia Institute of Technology School of Aerospace Engineering ATTN: E. Price W.C. Strahle B.T. Zinn Atlanta, GA 30332
1	University of California Los Alamos Scientific Lab. P.O. Box 1663, Mail Stop B216 Los Alamos, NM 87545	1	University of Illinois Dept. of Mech. Eng. ATTN: H. Krier 144MEB, 1206 W. Green St. Urbana, IL 61801
2	University of California, Santa Barbara Quantum Institute ATTN: K. Schofield M. Steinberg Santa Barbara, CA 93106	1	Johns Hopkins University/APL Chemical Propulsion Information Agency ATTN: T.W. Christian Johns Hopkins Road Laurel, MD 20707

DISTRIBUTION LIST

<u>No. Of</u> <u>Copies</u>	<u>Organization</u>	<u>No. Of</u> <u>Copies</u>	<u>Organization</u>
1	University of Michigan Gas Dynamics Lab Aerospace Engineering Bldg. ATTN: G.M. Faeth Ann Arbor, MI 48109-2140	1	Purdue University Department of Chemistry ATTN: E. Grant West Lafayette, IN 47906
1	University of Minnesota Dept. of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455	2	Purdue University School of Mechanical Engineering ATTN: N.M. Laurendeau S.N.B. Murthy TSPC Chaffee Hall West Lafayette, IN 47906
3	Pennsylvania State University Applied Research Laboratory ATTN: K.K. Kuo H. Palmer M. Micci University Park, PA 16802	1	Rensselaer Polytechnic Inst. Dept. of Chemical Engineering ATTN: A. Fontijn Troy, NY 12181
1	Pennsylvania State University Dept. of Mechanical Engineering ATTN: V. Yang University Park, PA 16802	1	Stanford University Dept. of Mechanical Engineering ATTN: R. Hanson Stanford, CA 94305
1	Polytechnic Institute of NY Graduate Center ATTN: S. Lederman Route 110 Farmingdale, NY 11735	1	University of Texas Dept. of Chemistry ATTN: W. Gardiner Austin, TX 78712
2	Princeton University Forrestal Campus Library ATTN: K. Brezinsky J. Glassman P.O. Box 710 Princeton, NJ 08540	1	University of Utah Dept. of Chemical Engineering ATTN: G. Flandro Salt Lake City, UT 84112
1	Princeton University MAE Dept. ATTN: F.A. Williams Princeton, NJ 08544	1	Virginia Polytechnic Institute and State University ATTN: J.A. Schetz Blacksburg, VA 24061
1	Purdue University School of Aeronautics and Astronautics ATTN: J.R. Osborn Grissom Hall West Lafayette, IN 47906	1	Commandant USAFAS ATTN: ATSF-TSM-CN Fort Sill, OK 73503-5600
		1	F.J. Seiler Research Lab (AFSC) ATTN: S.A. Shakelford USAF Academy, CO 80840-6528

DISTRIBUTION LIST

<u>No. Of</u> <u>Copies</u>	<u>Organization</u>
	<u>Aberdeen Proving Ground</u>
	Dir, USAMSAA
	ATTN: AMXSY-D
	AMXSY-MP, H. Cohen
	Cdr, USATECOM
	ATTN: AMSTE-TO-F
	Cdr, CRDEC, AMCCOM
	ATTN: SMCCR-RSP-A
	SMCCR-MU
	SMCCR-SPS-IL

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____ Date of Report: _____
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. How specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS	_____
	Name

	Organization

	Address

	City, State, Zip

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

----- FOLD HERE -----

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS


PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO 12062 WASHINGTON, DC

POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-9989



----- FOLD HERE -----