

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

AD-A206 889

2

REPORT DOCUMENTATION PAGE

1. REPORT NUMBER		DTIC FILE COPY	
4. TITLE (and Subtitle)		5. TYPE OF REPORT & PERIOD COVERED	
Ada Compiler Validation Summary Report: Harris Corporation, Harris Ada Compiler, Version 4.0, Harris HCX-9 (Host) and (Target), 880603W1.09059		6 June 1988 to 6 June 1988	
7. AUTHOR(s)		6. PERFORMING ORG. REPORT NUMBER	
Wright-Patterson AFB Dayton OH		8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION AND ADDRESS		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
Wright-Patterson AFB Dayton OH			
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE	
Ada Joint Program Office United States Department of Defense Washington, DC 20301-3081			
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES	
Wright-Patterson AFB Dayton OH			
16. DISTRIBUTION STATEMENT (of this Report)		15. SECURITY CLASS (of this report)	
Approved for public release; distribution unlimited.		UNCLASSIFIED	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20 If different from Report)		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
UNCLASSIFIED		N/A	
18. SUPPLEMENTARY NOTES		<p style="text-align: center;">DTIC ELECTED</p> <p style="text-align: center;">13 APR 1989</p> <p style="text-align: center;">S E D</p> <p style="text-align: center;">[Signature]</p>	
19. KEYWORDS (Continue on reverse side if necessary and identify by block number)			
Ada Programming language, Ada Compiler Validation Summary Report, Ada Compiler Validation Capability, ACVC, Validation Testing, Ada Validation Office, AVO, Ada Validation Facility, AVF, ANSI/MIL-STD-1815A, Ada Joint Program Office, AJPO			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)			
Harris Corporation, Harris Ada Compiler, Version 4.0, Wright-Patterson AFB, Harris HCX-9 under HCX/UX, Version 3.0 (Host) to Harris HCX-9 under HCX/UX, Version 3.0 (Target), ACVC 1.9.			

UNCLASSIFIED

Ada COMPILER
VALIDATION SUMMARY REPORT:
Certificate Number: 880603W1.09059
Harris Corporation
Harris Ada Compiler, Version 4.0
Harris HCX-9

Completion of On-Site Testing:
06 June 1988

Prepared By:
Ada Validation Facility
ASD/SCEL
Wright-Patterson AFB OH 45433-6503

Prepared For:
Ada Joint Program Office
United States Department of Defense
Washington DC 20301-3081

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input checked="" type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



Ada Compiler Validation Summary Report:

Compiler Name: Harris Ada Compiler, Version 4.0

Certificate Number: 880603W1.09059

Host:

Harris HCX-9 under
HCX/UX, Version 3.0

Target:

Harris HCX-9 under
HCX/UX, Version 3.0

Testing Completed 06 June 1988 Using ACVC 1.9

This report has been reviewed and is approved.



Ada Validation Facility
Steven P. Wilson
Technical Director
ASD/SCEL
Wright-Patterson AFB OH 45433-6503



Ada Validation Organization
Dr. John F. Kramer
Institute for Defense Analyses
Alexandria VA 22311



Ada Joint Program Office
William S. Ritchie
Acting Director
Department of Defense
Washington, DC 20301

Ada Compiler Validation Summary Report:

Compiler Name: Harris Ada Compiler, Version 4.0

Certificate Number: 880603W1.09059

Host:

Harris HCX-9 under
HCX/UX, Version 3.0

Target:


Harris HCX-9 under
HCX/UX, Version 3.0

Testing Completed 06 June 1988 Using ACVC 1.9

This report has been reviewed and is approved.



Ada Validation Facility
Steven P. Wilson
Technical Director
ASD/SCEL
Wright-Patterson AFB OH 45433-6503



Ada Validation Organization
Dr. John F. Kramer
Institute for Defense Analysis
Alexandria VA 22311

Ada Joint Program Office
Virginia L. Castor
Director
Department of Defense
Washington DC 20301

TABLE OF CONTENTS

CHAPTER 1	INTRODUCTION	
1.1	PURPOSE OF THIS VALIDATION SUMMARY REPORT	1-2
1.2	USE OF THIS VALIDATION SUMMARY REPORT	1-2
1.3	REFERENCES	1-3
1.4	DEFINITION OF TERMS	1-4
1.5	ACVC TEST CLASSES	1-5
CHAPTER 2	CONFIGURATION INFORMATION	
2.1	CONFIGURATION TESTED	2-1
2.2	IMPLEMENTATION CHARACTERISTICS	2-2
CHAPTER 3	TEST INFORMATION	
3.1	TEST RESULTS	3-1
3.2	SUMMARY OF TEST RESULTS BY CLASS	3-1
3.3	SUMMARY OF TEST RESULTS BY CHAPTER	3-2
3.4	WITHDRAWN TESTS	3-2
3.5	INAPPLICABLE TESTS	3-2
3.6	TEST, PROCESSING, AND EVALUATION MODIFICATIONS	3-4
3.7	ADDITIONAL TESTING INFORMATION	3-4
3.7.1	Prevalidation	3-4
3.7.2	Test Method	3-4
3.7.3	Test Site	3-5
APPENDIX A	DECLARATION OF CONFORMANCE	
APPENDIX B	APPENDIX F OF THE Ada STANDARD	
APPENDIX C	TEST PARAMETERS	
APPENDIX D	WITHDRAWN TESTS	

CHAPTER 1
INTRODUCTION

This Validation Summary Report (VSR) describes the extent to which a specific Ada compiler conforms to the Ada Standard, ANSI/MIL-STD-1815A. This report explains all technical terms used within it and thoroughly reports the results of testing this compiler using the Ada Compiler Validation Capability (ACVC). An Ada compiler must be implemented according to the Ada Standard, and any implementation-dependent features must conform to the requirements of the Ada Standard. The Ada Standard must be implemented in its entirety, and nothing can be implemented that is not in the Standard.

Even though all validated Ada compilers conform to the Ada Standard, it must be understood that some differences do exist between implementations. The Ada Standard permits some implementation dependencies--for example, the maximum length of identifiers or the maximum values of integer types. Other differences between compilers result from the characteristics of particular operating systems, hardware, or implementation strategies. All the dependencies observed during the process of testing this compiler are given in this report.

The information in this report is derived from the test results produced during validation testing. The validation process includes submitting a suite of standardized tests, the ACVC, as inputs to an Ada compiler and evaluating the results. The purpose of validating is to ensure conformity of the compiler to the Ada Standard by testing that the compiler properly implements legal language constructs and that it identifies and rejects illegal language constructs. The testing also identifies behavior that is implementation dependent but permitted by the Ada Standard. Six classes of tests are used. These tests are designed to perform checks at compile time, at link time, and during execution.

INTRODUCTION

1.1 PURPOSE OF THIS VALIDATION SUMMARY REPORT

This VSR documents the results of the validation testing performed on an Ada compiler. Testing was carried out for the following purposes:

- . To attempt to identify any language constructs supported by the compiler that do not conform to the Ada Standard
- . To attempt to identify any language constructs not supported by the compiler but required by the Ada Standard
- . To determine that the implementation-dependent behavior is allowed by the Ada Standard

Testing of this compiler was conducted by SofTech, Inc. under the direction of the AVF according to procedures established by the Ada Joint Program Office and administered by the Ada Validation Organization (AVO). On-site testing was completed 06 June 1988 at Ft. Lauderdale, FL.

1.2 USE OF THIS VALIDATION SUMMARY REPORT

Consistent with the national laws of the originating country, the AVO may make full and free public disclosure of this report. In the United States, this is provided in accordance with the "Freedom of Information Act" (5 U.S.C. #552). The results of this validation apply only to the computers, operating systems, and compiler versions identified in this report.

The organizations represented on the signature page of this report do not represent or warrant that all statements set forth in this report are accurate and complete, or that the subject compiler has no nonconformities to the Ada Standard other than those presented. Copies of this report are available to the public from:

Ada Information Clearinghouse
Ada Joint Program Office
OUSDRE
The Pentagon, Rm 3D-139 (Fern Street)
Washington DC 20301-3081

or from:

Ada Validation Facility
ASD/SCEL
Wright-Patterson AFB OH 45433-6503

Questions regarding this report or the validation test results should be directed to the AVF listed above or to:

Ada Validation Organization
Institute for Defense Analyses
1801 North Beauregard Street
Alexandria VA 22311

1.3 REFERENCES

1. Reference Manual for the Ada Programming Language, ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
2. Ada Compiler Validation Procedures and Guidelines, Ada Joint Program Office, 1 January 1987.
3. Ada Compiler Validation Capability Implementers' Guide, SofTech, Inc., December 1986.
4. Ada Compiler Validation Capability User's Guide, December 1986.

INTRODUCTION

1.4 DEFINITION OF TERMS

ACVC	The Ada Compiler Validation Capability. The set of Ada programs that tests the conformity of an Ada compiler to the Ada programming language.
Ada Commentary	An Ada Commentary contains all information relevant to the point addressed by a comment on the Ada Standard. These comments are given a unique identification number having the form AI-ddddd.
Ada Standard	ANSI/MIL-STD-1815A, February 1983 and ISO 8652-1987.
Applicant	The agency requesting validation.
AVF	The Ada Validation Facility. The AVF is responsible for conducting compiler validations according to procedures contained in the <u>Ada Compiler Validation Procedures and Guidelines</u> .
AVO	The Ada Validation Organization. The AVO has oversight authority over all AVF practices for the purpose of maintaining a uniform process for validation of Ada compilers. The AVO provides administrative and technical support for Ada validations to ensure consistent practices.
Compiler	A processor for the Ada language. In the context of this report, a compiler is any language processor, including cross-compilers, translators, and interpreters.
Failed test	An ACVC test for which the compiler generates a result that demonstrates nonconformity to the Ada Standard.
Host	The computer on which the compiler resides.
Inapplicable test	An ACVC test that uses features of the language that a compiler is not required to support or may legitimately support in a way other than the one expected by the test.
Passed test	An ACVC test for which a compiler generates the expected result.
Target	The computer for which a compiler generates code.
Test	A program that checks a compiler's conformity regarding a particular feature or a combination of features to the Ada Standard. In the context of this report, the term is used to designate a single test, which may comprise one or more files.
Withdrawn test	An ACVC test found to be incorrect and not used to check conformity to the Ada Standard. A test may be incorrect

because it has an invalid test objective, fails to meet its test objective, or contains illegal or erroneous use of the language.

1.5 ACVC TEST CLASSES

Conformity to the Ada Standard is measured using the ACVC. The ACVC contains both legal and illegal Ada programs structured into six test classes: A, B, C, D, E, and L. The first letter of a test name identifies the class to which it belongs. Class A, C, D, and E tests are executable, and special program units are used to report their results during execution. Class B tests are expected to produce compilation errors. Class L tests are expected to produce compilation or link errors.

Class A tests check that legal Ada programs can be successfully compiled and executed. There are no explicit program components in a Class A test to check semantics. For example, a Class A test checks that reserved words of another language (other than those already reserved in the Ada language) are not treated as reserved words by an Ada compiler. A Class A test is passed if no errors are detected at compile time and the program executes to produce a PASSED message.

Class B tests check that a compiler detects illegal language usage. Class B tests are not executable. Each test in this class is compiled and the resulting compilation listing is examined to verify that every syntax or semantic error in the test is detected. A Class B test is passed if every illegal construct that it contains is detected by the compiler.

Class C tests check that legal Ada programs can be correctly compiled and executed. Each Class C test is self-checking and produces a PASSED, FAILED, or NOT APPLICABLE message indicating the result when it is executed.

Class D tests check the compilation and execution capacities of a compiler. Since there are no capacity requirements placed on a compiler by the Ada Standard for some parameters--for example, the number of identifiers permitted in a compilation or the number of units in a library--a compiler may refuse to compile a Class D test and still be a conforming compiler. Therefore, if a Class D test fails to compile because the capacity of the compiler is exceeded, the test is classified as inapplicable. If a Class D test compiles successfully, it is self-checking and produces a PASSED or FAILED message during execution.

Each Class E test is self-checking and produces a NOT APPLICABLE, PASSED, or FAILED message when it is compiled and executed. However, the Ada Standard permits an implementation to reject programs containing some features addressed by Class E tests during compilation. Therefore, a Class E test is passed by a compiler if it is compiled successfully and executes to produce a PASSED message, or if it is rejected by the compiler for an allowable reason.

INTRODUCTION

Class L tests check that incomplete or illegal Ada programs involving multiple, separately compiled units are detected and not allowed to execute. Class L tests are compiled separately and execution is attempted. A Class L test passes if it is rejected at link time--that is, an attempt to execute the main program must generate an error message before any declarations in the main program or any units referenced by the main program are elaborated.

Two library units, the package REPORT and the procedure CHECK_FILE, support the self-checking features of the executable tests. The package REPORT provides the mechanism by which executable tests report PASSED, FAILED, or NOT APPLICABLE results. It also provides a set of identity functions used to defeat some compiler optimizations allowed by the Ada Standard that would circumvent a test objective. The procedure CHECK_FILE is used to check the contents of text files written by some of the Class C tests for chapter 14 of the Ada Standard. The operation of REPORT and CHECK_FILE is checked by a set of executable tests. These tests produce messages that are examined to verify that the units are operating correctly. If these units are not operating correctly, then the validation is not attempted.

The text of the tests in the ACVC follow conventions that are intended to ensure that the tests are reasonably portable without modification. For example, the tests make use of only the basic set of 55 characters, contain lines with a maximum length of 72 characters, use small numeric values, and place features that may not be supported by all implementations in separate tests. However, some tests contain values that require the test to be customized according to implementation-specific values--for example, an illegal file name. A list of the values used for this validation is provided in Appendix C.

A compiler must correctly process each of the tests in the suite and demonstrate conformity to the Ada Standard by either meeting the pass criteria given for the test or by showing that the test is inapplicable to the implementation. The applicability of a test to an implementation is considered each time the implementation is validated. A test that is inapplicable for one validation is not necessarily inapplicable for a subsequent validation. Any test that was determined to contain an illegal language construct or an erroneous language construct is withdrawn from the ACVC and, therefore, is not used in testing a compiler. The tests withdrawn at the time of this validation are given in Appendix D.

CHAPTER 2

CONFIGURATION INFORMATION

2.1 CONFIGURATION TESTED

The candidate compilation system for this validation was tested under the following configuration:

Compiler: Harris Ada Compiler, Version 4.0

ACVC Version: 1.9

Certificate Number: 880603W1.09059

Host Computer:

Machine: Harris HCX-9

Operating System: HCX/UX, Version 3.0

Memory Size: 32 megabytes

Target Computer:

Machine: Harris HCX-9

Operating System: HCX/UX, Version 3.0

Memory Size: 32 megabytes

CONFIGURATION INFORMATION

2.2 IMPLEMENTATION CHARACTERISTICS

One of the purposes of validating compilers is to determine the behavior of a compiler in those areas of the Ada Standard that permit implementations to differ. Class D and E tests specifically check for such implementation differences. However, tests in other classes also characterize an implementation. The tests demonstrate the following characteristics:

- . Capacities.

The compiler correctly processes tests containing loop statements nested to 65 levels, block statements nested to 65 levels, and recursive procedures separately compiled as subunits nested to 17 levels. It correctly processes a compilation containing 723 variables in the same declarative part. (See tests D55A03A..H (8 tests), D56001B, D64005E..G (3 tests), and D29002K.)

- . Universal integer calculations.

An implementation is allowed to reject universal integer calculations having values that exceed `SYSTEM.MAX_INT`. This implementation processes 64-bit integer calculations. (See tests D4A002A, D4A002B, D4A004A, and D4A004B.)

- . Predefined types.

This implementation supports the additional predefined types `SHORT_INTEGER`, `LONG_FLOAT`, and `TINY_INTEGER` in the package `STANDARD`. (See tests B86001C and B86001D.)

- . Based literals.

An implementation is allowed to reject a based literal with a value exceeding `SYSTEM.MAX_INT` during compilation, or it may raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` during execution. This implementation raises `NUMERIC_ERROR` during execution. (See test E24101A.)

- . Expression evaluation.

Apparently no default initialization expressions for record components are evaluated before any value is checked to belong to a component's subtype. (See test C32117A.)

CONFIGURATION INFORMATION

Assignments for subtypes are performed with the same precision as the base type. (See test C35712B.)

This implementation uses no extra bits for extra precision and all extra bits for extra range. (See test C35903A.)

Sometimes `NUMERIC_ERROR` is raised when an integer literal operand in a comparison or membership test is outside the range of the base type. (See test C45232A.)

Apparently `NUMERIC_ERROR` is raised when a literal operand in a fixed-point comparison or membership test is outside the range of the base type. (See test C45252A.)

Apparently underflow is not gradual. (See tests C45524A..Z.)

. Rounding.

The method used for rounding to integer is apparently round away from zero. (See tests C46012A..Z.)

The method used for rounding to longest integer is apparently round away from zero. (See tests C46012A..Z.)

The method used for rounding to integer in static universal real expressions is apparently round away from zero. (See test C4A014A.)

. Array types.

An implementation is allowed to raise `NUMERIC_ERROR` or `CONSTRAINT_ERROR` for an array having a `'LENGTH` that exceeds `STANDARD.INTEGER'LAST` and/or `SYSTEM.MAX_INT`. For this implementation:

Declaration of an array type or subtype declaration with more than `SYSTEM.MAX_INT` components raises no exception. (See test C36003A.)

`NUMERIC_ERROR` is raised when `'LENGTH` is applied to an array type with `INTEGER'LAST + 2` components. (See test C36202A)

`NUMERIC_ERROR` is raised when `'LENGTH` is applied to an array type with `SYSTEM.MAX_INT + 2` components. (See test C36202B.)

A packed `BOOLEAN` array having a `'LENGTH` exceeding `INTEGER'LAST` raises `NUMERIC_ERROR` when the array type is declared. (See test C52103X.)

CONFIGURATION INFORMATION

A packed two-dimensional BOOLEAN array with more than INTEGER'LAST components raises NUMERIC_ERROR when the array subtype is declared. (See test C52104Y.)

A null array with one dimension of length greater than INTEGER'LAST may raise NUMERIC_ERROR or CONSTRAINT_ERROR either when declared or assigned. Alternatively, an implementation may accept the declaration. However, lengths must match in array slice assignments. This implementation raises NUMERIC_ERROR when the array type is declared. (See test E52103Y.)

In assigning one-dimensional array types, the expression appears to be evaluated in its entirety before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. In assigning two-dimensional array types, the expression does not appear to be evaluated in its entirety before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- Discriminated types.

During compilation, an implementation is allowed to either accept or reject an incomplete type with discriminants that is used in an access type definition with a compatible discriminant constraint. This implementation accepts such subtype indications during compilation. (See test E38104A.)

In assigning record types with discriminants, the expression appears to be evaluated in its entirety before CONSTRAINT_ERROR is raised when checking whether the expression's subtype is compatible with the target's subtype. (See test C52013A.)

- Aggregates.

In the evaluation of a multi-dimensional aggregate, all choices appear to be evaluated before checking against the index type. (See tests C43207A and C43207B.)

In the evaluation of an aggregate containing subaggregates, all choices are evaluated before being checked for identical bounds. (See test E43212B.)

All choices are evaluated before CONSTRAINT_ERROR is raised if a bound in a nonnull range of a nonnull aggregate does not belong to an index subtype. (See test E43211B.)

CONFIGURATION INFORMATION

- Representation clauses.

An implementation might legitimately place restrictions on representation clauses used by some of the tests. If a representation clause is used by a test in a way that violates a restriction, then the implementation must reject it.

Enumeration representation clauses containing noncontiguous values for enumeration types other than character and boolean types are supported. (See tests C35502I..J, C35502M..N, and A39005F.)

Enumeration representation clauses containing noncontiguous values for character types are supported. (See tests C35507I..J, C35507M..N, and C55B16A.)

Enumeration representation clauses for boolean types containing representational values other than (FALSE => 0, TRUE => 1) are supported. (See tests C35508I..J and C35508M..N.)

Length clauses with SIZE specifications for enumeration types are supported. (See test A39005B.)

Length clauses with STORAGE_SIZE specifications for access types are supported. (See tests A39005C and C87B62B.)

Length clauses with STORAGE_SIZE specifications for task types are supported. (See tests A39005D and C87B62D.)

Length clauses with SMALL specifications are not supported. (See tests A39005E and C87B62C.)

Length clauses with SIZE specifications for derived integer types are supported. (See test C87B62A.)

- Pragmas.

The pragma `INLINE` is supported for procedures and functions. (See tests LA3004A, LA3004B, EA3004C, EA3004D, CA3004E, and CA3004F.)

- Input/output.

The package `SEQUENTIAL_IO` can be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101C, EE2201D, and EE2201E.)

The package `DIRECT_IO` can be instantiated with unconstrained array types and record types with discriminants without defaults. (See tests AE2101H, EE2401D, and EE2401G.)

CONFIGURATION INFORMATION

Modes IN_FILE and OUT_FILE are supported for SEQUENTIAL_IO.
(See tests CE2102D and CE2102E.)

Modes IN_FILE, OUT_FILE, and INOUT_FILE are supported for DIRECT_IO. (See tests CE2102F, CE2102I, and CE2102J.)

RESET and DELETE are supported for SEQUENTIAL_IO and DIRECT_IO.
(See tests CE2102G and CE2102K.)

Dynamic creation and deletion of files are supported for SEQUENTIAL_IO and DIRECT_IO. (See tests CE2106A and CE2106B.)

Overwriting to a sequential file truncates the file to last element written. (See test CE2208B.)

An existing text file can be opened and created in OUT_FILE mode, and can be created in IN_FILE mode. (See test EE3102C.)

More than one internal file can be associated with each external file for text I/O for both reading and writing. (See tests CE3111A..E (5 tests), CE3114B, and CE3115A.)

More than one internal file can be associated with each external file for sequential I/O for both reading and writing. (See tests CE2107A..D (4 tests), CE2110B, and CE2111D.)

More than one internal file can be associated with each external file for direct I/O for both reading and writing. (See tests CE2107F..I (5 tests), CE2110B, and CE2111H.)

An internal sequential access file and an internal direct access file can be associated with a single external file for writing. (See test CE2107E.)

An external file associated with more than one internal file can be deleted for SEQUENTIAL_IO, DIRECT_IO, and TEXT_IO. (See test CE2110B.)

Temporary sequential files are given names. Temporary direct files are given names. Temporary files given names are deleted when they are closed. (See tests CE2108A and CE2108C.)

CONFIGURATION INFORMATION

. Generics.

Generic subprogram declarations and bodies can be compiled in separate compilations. (See tests CA1012A and CA2009F.)

Generic package declarations and bodies can be compiled in separate compilations. (See tests CA2009C, BC3204C, and BC3205D.)

Generic unit bodies and their subunits can be compiled in separate compilations. (See test CA3011A.)

CHAPTER 3

TEST INFORMATION

3.1 TEST RESULTS

Version 1.9 of the ACVC comprises 3122 tests. When this compiler was tested, 27 tests had been withdrawn because of test errors. The AVF determined that 322 tests were inapplicable to this implementation. All inapplicable tests were processed during validation testing except for 285 executable tests that use floating-point precision exceeding that supported by the implementation. Modifications to the code, processing, or grading for 26 tests were required to successfully demonstrate the test objective. (See section 3.6.)

The AVF concludes that the testing results demonstrate acceptable conformity to the Ada Standard.

3.2 SUMMARY OF TEST RESULTS BY CLASS

RESULT	TEST CLASS						TOTAL
	A	B	C	D	E	L	
Passed	108	1048	1536	17	18	46	2773
Inapplicable	2	3	317	0	0	0	322
Withdrawn	3	2	21	0	1	0	27
TOTAL	113	1053	1874	17	19	46	3122

TEST INFORMATION

3.3 SUMMARY OF TEST RESULTS BY CHAPTER

RESULT	CHAPTER														TOTAL
	2	3	4	5	6	7	8	9	10	11	12	13	14		
Passed	184	468	483	245	166	98	140	326	137	36	234	3	253	2773	
Inapplicable	20	104	191	3	0	0	3	1	0	0	0	0	0	322	
Withdrawn	2	14	3	0	0	1	2	0	0	0	2	1	2	27	
TOTAL	206	586	677	248	166	99	145	327	137	36	236	4	255	3122	

3.4 WITHDRAWN TESTS

The following 27 tests were withdrawn from ACVC Version 1.9 at the time of this validation:

B28003A	E28005C	C34004A	C35502P	A35902C
C35904A	C35904B	C35A03E	C35A03R	C37213H
C37213J	C37215C	C37215E	C37215G	C37215H
C38102C	C41402A	C45332A	C45614C	A74106C
C85018B	C87B04B	CC1311B	BC3105A	AD1A01A
CE2401H	CE3208A			

See Appendix D for the reason that each of these tests was withdrawn.

3.5 INAPPLICABLE TESTS

Some tests do not apply to all compilers because they make use of features that a compiler is not required by the Ada Standard to support. Others may depend on the result of another test that is either inapplicable or withdrawn. The applicability of a test to an implementation is considered each time a validation is attempted. A test that is inapplicable for one validation attempt is not necessarily inapplicable for a subsequent attempt. For this validation attempt, 322 tests were inapplicable for the reasons indicated:

- . C35702A uses SHORT_FLOAT which is not supported by this implementation.
- . A39005E and C87B62C use length clauses with SMALL specifications which are not supported by this implementation.

TEST INFORMATION

- . A39005G uses a record representation clause which is not supported by this compiler.
- . The following 13 tests use LONG_INTEGER, which is not supported by this compiler:

C45231C	C45304C	C45502C	C45503C	C45504C
C45504F	C45611C	C45613C	C45631C	C45632C
B52004D	B55B09C	C55B07A		

- . C45231D requires a macro substitution for any predefined numeric types other than INTEGER, SHORT_INTEGER, LONG_INTEGER, FLOAT, SHORT_FLOAT, and LONG_FLOAT. This compiler does not support any such types.
- . C45531I, C45531J, C45532I, and C45532J use fine 32-bit fixed-point base types which are not supported by this compiler.
- . C45531K, C45531L, C45532K, and C45532L use coarse 32-bit fixed-point base types which are not supported by this compiler.
- . C45531M, C45531N, C45532M, and C45532N use fine 48-bit fixed-point base types which are not supported by this compiler.
- . C45531O, C45531P, C45532O, and C45532P use coarse 48-bit fixed-point base types which are not supported by this compiler.
- . B86001D requires a predefined numeric type other than those defined by the Ada language in package STANDARD. There is no such type for this implementation.
- . C86001F redefines package SYSTEM, but TEXT_IO is made obsolete by this new definition in this implementation and the test cannot be executed since the package REPORT is dependent on the package TEXT_IO.
- . C96005B requires the range of type DURATION to be different from those of its base type; in this implementation they are the same.
- . The following 285 tests require a floating-point accuracy that exceeds the maximum of 9 digits supported by this implementation:

C24113F..Y (20 tests)	C35705F..Y (20 tests)
C35706F..Y (20 tests)	C35707F..Y (20 tests)
C35708F..Y (20 tests)	C35802F..Z (21 tests)
C45241F..Y (20 tests)	C45321F..Y (20 tests)
C45421F..Y (20 tests)	C45521F..Z (21 tests)
C45524F..Z (21 tests)	C45621F..Z (21 tests)
C45641F..Y (20 tests)	C46012F..Z (21 tests)

TEST INFORMATION

3.6 TEST, PROCESSING, AND EVALUATION MODIFICATIONS

It is expected that some tests will require modifications of code, processing, or evaluation in order to compensate for legitimate implementation behavior. Modifications are made by the AVF in cases where legitimate implementation behavior prevents the successful completion of an (otherwise) applicable test. Examples of such modifications include: adding a length clause to alter the default size of a collection; splitting a Class B test into subtests so that all errors are detected; and confirming that messages produced by an executable test demonstrate conforming behavior that wasn't anticipated by the test (such as raising one exception instead of another).

Modifications were required for 26 Class B tests.

The following Class B tests were split because syntax errors at one point resulted in the compiler not detecting other errors in the test:

B24009A	B24204A	B24204B	B24204C	B25002A
B2A003A	B2A003B	B2A003C	B33301A	B36002A
B37201A	B38003A	B38003B	B38009A	B38009B
B44001A	B64001A	B67001A	B67001B	B67001C
B67001D	B91003B	B95001A	B97102A	BC1303F
BC3005B				

3.7 ADDITIONAL TESTING INFORMATION

3.7.1 Prevalidation

Prior to validation, a set of test results for ACVC Version 1.9 produced by the Harris Ada Compiler was submitted to the AVF by the applicant for review. Analysis of these results demonstrated that the compiler successfully passed all applicable tests, and the compiler exhibited the expected behavior on all inapplicable tests.

3.7.2 Test Method

Testing of the Harris Ada Compiler using ACVC Version 1.9 was conducted on-site by a validation team from the AVF. The configuration consisted of a Harris HCX-9 host and target operating under HCX/UX, Version 3.0.

A magnetic tape containing all tests except for withdrawn tests and tests requiring unsupported floating-point precisions was taken on-site by the validation team for processing. Tests that make use of implementation-specific values were customized before being written to the magnetic tape. Tests requiring modifications during the prevalidation testing were included in their modified form on the magnetic tape.

TEST INFORMATION

The contents of the magnetic tape were loaded directly onto the host computer. After the test files were loaded to disk, the full set of tests was compiled on the Harris HCX-9, and all executable tests were linked and run on the Harris HCX-9. Results were printed from the host computer.

The compiler was tested using command scripts provided by Harris Corporation and reviewed by the validation team. The compiler was tested using the following options:

<u>Option</u>	<u>Effect</u>
-el	Produce error listing. Used on all tests.
-w	Suppress warning messages. Used on Class A, C, D, L and support tests.

Tests were compiled, linked, and executed (as appropriate) using a single host computer and a single target computer. Test output, compilation listings, and job logs were captured on magnetic tape and archived at the AVF. The listings examined on-site by the validation team were also archived.

3.7.3 Test Site

Testing was conducted at Ft. Lauderdale, FL and was completed on 06 June 1988.

APPENDIX A

DECLARATION OF CONFORMANCE

Harris Corporation has submitted the following
Declaration of Conformance concerning the Harris Ada
Compiler.

DECLARATION OF CONFORMANCE

DECLARATION OF CONFORMANCE

Compiler Implementor: Harris Corporation
Ada Validation Facility: Ada Validation Facility, ASD/SCEL,
Wright-Patterson AFB OH 45433-6503
Ada Compiler Validation Capability (ACVC) Version: 1.9

Base Configuration

Base Compiler Name: Harris Ada Compiler Version: Version 4.0
Host Architecture ISA: Harris HCX-9 OS&VER #: HCX/UX, Version 3.0
Target Architecture ISA: Harris HCX-9 OS&VER #: HCX/UX, Version 3.0

Implementor's Declaration

I, the undersigned, representing Harris Corporation, have implemented no deliberate extensions to the Ada Language Standard ANSI/MIL-STD-1815A in the compiler(s) listed in this declaration. I declare that Harris Corporation is the owner of record of the Ada language compiler(s) listed above and, as such, is responsible for maintaining said compiler(s) in conformance to ANSI/MIL-STD-1815A. All certificates and registrations for Ada language compiler(s) listed in this declaration shall be made only in the owner's corporate name.

Date: _____
Harris Corporation
Wendell E. Norton, Director of Contracts

Owner's Declaration

I, the undersigned, representing Harris Corporation, take full responsibility for implementation and maintenance of the Ada compiler(s) listed above, and agree to the public disclosure of the final Validation Summary Report. I further agree to continue to comply with the Ada trademark policy, as defined by the Ada Joint Program Office. I declare that all of the Ada language compilers listed, and their host/target performance, are in compliance with the Ada Language Standard ANSI/MIL-STD-1815A.

Date: _____
Harris Corporation
Wendell E. Norton, Director of Contracts

APPENDIX B

APPENDIX F OF THE Ada STANDARD

The only allowed implementation dependencies correspond to implementation-dependent pragmas, to certain machine-dependent conventions as mentioned in chapter 13 of the Ada Standard, and to certain allowed restrictions on representation clauses. The implementation-dependent characteristics of the Harris Ada Compiler, Version 4.0, are described in the following sections, which discuss topics in Appendix F of the Ada Standard. Implementation-specific portions of the package STANDARD are also included in this appendix.

package STANDARD is

...

type INTEGER is range -2_147_483_648 .. 2_147_483_647;

type SHORT_INTEGER is range -32768 .. 32767;

type TINY_INTEGER is range -128 .. 127;

type FLOAT is digits 6 range -2#0.1111111111_1111111111_1111#E127 ..
2#0.1111111111_1111111111_1111#E127;

type LONG_FLOAT is digits 9 range
-2#0.1111111111_1111111111_1111111111_1111111111_1111111111_1111111111_1111111111#E127 ..
2#0.1111111111_1111111111_1111111111_1111111111_1111111111_1111111111_1111111111#E127;

type DURATION is delta 2#1.0#E-13 range -2#1000000000_00000000.0# ..
2#1111111111_11111111.1111111111_1111#;

...

end STANDARD;

CHAPTER 5

IMPLEMENTATION-DEPENDENT CHARACTERISTICS

(Note: This chapter operates as Appendix F of the Ada RM.)

5.1 IMPLEMENTATION-DEPENDENT PRAGMAS

HAPSE provides for sharing of generic bodies (procedures and packages), when the generic parameters are restricted to enumeration types, integer types, and floating types.

PRAGMA SHARE_BODY is used to indicate desire to share or not share an instantiation. The pragma may reference the generic unit or the instantiated unit. When it references a generic unit, it gets sharing on/off for all instantiations of the generic, unless overridden by specific SHARE_BODY pragmas for individual instantiations. When it references an instantiated unit, sharing is on/off only for that unit. The default is to share all generics that can be shared, unless the unit uses PRAGMA IN_LINE.

PRAGMA SHARE_BODY is only allowed in the following places: immediately within a declarative part, immediately within a package specification, or after a library unit in a compilation, but before any subsequent compilation unit. The form of this pragma is

```
pragma SHARE_BODY (generic_name, boolean_literal)
```

Note that a parent instantiation is independent of any individual instantiation, therefore recompilation of a generic with different parameters has no effect on other compilations that reference it. The unit that caused compilation of a parent instantiation need not be referenced in any way by subsequent units that share the parent instantiation.

Sharing generics causes a slight execution time penalty because all type attributes must be indirectly referenced (as if an extra calling argument were added). However, it substantially reduces compilation time in most circumstances and reduces program size.

Harris has compiled a unit, SHARED_IO, in the standard library that instantiates all Ada generic I/O packages. Thus, any instantiation of an Ada I/O generic package will share one of the parent instantiation generic bodies. The PRAGMA SHARE_BODY takes the name of a generic instantiation or a generic unit as the first argument and one of the identifiers TRUE or FALSE as the second argument. This pragma is only allowed immediately at the place of a declarative item in a declarative part or package specification, or after a library unit in a compilation, but before any subsequent compilation unit.

When the first argument is a generic unit, the pragma applies to all instantiations of that generic. When the first argument is the name of a generic instantiation the pragma applies only to the specified instantiation, or overloaded instantiation.

If the second argument is TRUE, the compiler will try to share code generated for a generic instantiation with code generated for other instantiations of the same generic. When the second argument is FALSE, each instantiation will get a unique copy of the generated code. The extent to which code is shared between instantiations depends on this pragma and the kind of generic formal parameters declared for the generic unit.

Pragma EXTERNAL_NAME provides a method for specifying an alternative link name for variables, functions and procedures. The required parameters are the simple name of the object and a string constant representing the link name. Note that this pragma is useful for referencing functions and procedures that have had pragma interface applied to them, in such cases where the functions or procedures have link names that do not conform to Ada identifiers. The pragma must occur after any such applications of pragma interface and within the same declarative part or package specification that contains the object.

Pragma INTERFACE_OBJECT provides an interface to objects defined in foreign languages. This pragma has a required first parameter that is the simple name of an Ada variable to be associated with the foreign object. The optional second parameter is a string constant that defines the link name of the object. By default, the link name of the object is the symbolic representation of the simple name converted to lowercase. The variable declaration must occur before the pragma and both must occur within the same declarative part or package specification.

5.2 IMPLEMENTATION-DEPENDENT ATTRIBUTES

There are no implementation-dependent attributes in HAPSE.

5.3 SPECIFICATION OF PACKAGE SYSTEM

```
package SYSTEM is
  type ADDRESS is private;
  type NAME is (hcx_ux);

  SYSTEM_NAME      :constant NAME :=hcx_ux

  --System-Dependent Constraints

  STORAGE_UNIT     :constant :=8;
  MEMORY_SIZE      :constant :=3_221_225_469;

  --System-Dependent Named Numbers

  MIN-INT          :constant :=-2_147_483_647-1;
  MAX_INT          :constant :=2_147_483_647;
  MAX_DIGITS       :constant :=9;
  MAX_MANTISSA     :constant :=30;
  FINE_DELTA       :constant :=2.0**(-30);
  TICK             :constant :=0.01;

  --Other System-dependent Declarations

  subtype PRIORITY is INTEGER range 0.. 99;

  MAX_REC_SIZE     : INTEGER :=64*1024

private
  type ADDRESS is new INTEGER;

end SYSTEM;
```

5.4 RESTRICTIONS ON REPRESENTATION CLAUSES

5.4.1 Pragma PACK

Bit packing is not supported. Certain objects and components can be packed to the nearest whole STORAGE_UNIT.

5.4.2 Length Clauses

The specification T'SIZE is supported, but the size required for a type is a multiple of STORAGE_UNIT. The specification T'SMALL is not supported.

5.4.3 Record Representation Clauses

Component clauses must be aligned on STORAGE_UNIT boundaries.

5.4.4 Address Clauses

Address clauses are supported for the following entities.

- objects
- entries

The function PHYSICAL_ADDRESS is defined in the package SYSTEM to provide conversion from INTEGER values to ADDRESS values.

5.4.5 Interrupts

Interrupt entries (UNIX signals) are supported. This feature allows Ada programs to bind a UNIX signal to an interrupt entry by using a for clause with a signal number. There is no protection against two tasks binding the same signal. The result is undefined. Interrupt entries should have no parameters and can be called explicitly by the program. See SIGVEC(2).

The HAPSE runtime uses SIGALRM (14) to perform time slicing and delays. The result of establishing a signal handler for SIGALRM is undefined.

The following example program uses an interrupt entry that prints a message when the process receives SIGINT.

```
with TEXT_IO, SYSTEM;
use TEXT_IO;
procedure INTR is
-- This program waits for the user to generate SIGINT (<CONTROL>C)

SIGINT_NUMBER : constant := 2;

task SIGINT_HANDLER is
  entry SIGINT;
  for SIGINT use at SYSTEM.PHYSICAL_ADDRESS(SIGINT_NUMBER);
end SIGINT_HANDLER;

task body SIGINT_HANDLER is
  begin
    accept SIGINT;
    PUT_LINE("Control-C received");
  end SIGINT_HANDLER;

begin
  null;
end INTR;
```

5.5 OTHER REPRESENTATION IMPLEMENTATION-DEPENDENCIES

Change of representation is not supported for record types.

The ADDRESS attribute is not supported for the following entities: static constants, packages, tasks, labels, and entries.

5.6 CONVENTIONS FOR IMPLEMENTATION-GENERATED NAMES

There are no implementation generated names.

5.7 RESTRICTIONS ON UNCHECKED CONVERSIONS

The predefined generic function UNCHECKED_CONVERSION cannot be instantiated with a target type that is an unconstrained array type or an unconstrained record type with discriminants.

5.8 IMPLEMENTATION CHARACTERISTICS OF I/O PACKAGES

5.8.1 Interpretation of Strings as Applied to External Files

Strings that contain names of external files are interpreted in the following manner: File names may be composed of up to 256 characters of the ASCII character set except for "/", with a total path name of up to 1024 characters. Further, the first character of a file must be alpha-numeric, ".", or "_". If the "/" character is encountered in a string, it is interpreted as a separator between file names that specify directories.

5.8.2 Implementation-Dependent Characteristics of DIRECT I/O

Instantiations of DIRECT_IO use the value MAX_REC_SIZE as the record size (expressed in STORAGE_UNITS) when the size of ELEMENT_TYPE exceeds that value. For example, for unconstrained arrays such as a string where ELEMENT_TYPE'SIZE is very large, MAX_REC_SIZE is used instead. MAX_RECORD_SIZE is defined in SYSTEM and can be changed by a program before instantiating DIRECT_IO to provide an upper limit on the record size. In any case, the maximum size supported is 64*1024 STORAGE_UNIT bits. DIRECT_IO raises USE_ERROR if MAX_REC_SIZE exceeds this absolute limit.

5.8.3 Implementation-Dependent Characteristics of SEQUENTIAL I/O

Instantiations of SEQUENTIAL_IO use the value MAX_REC_SIZE as the record size (expressed in STORAGE_UNITS) when the size of ELEMENT_TYPE exceeds that value. For example, for unconstrained arrays such as a string where ELEMENT_TYPE'SIZE is very large, MAX_REC_SIZE is used instead. MAX_RECORD_SIZE is defined in SYSTEM and can be changed by a program before instantiating SEQUENTIAL_IO to provide an upper limit on the record size. In any case, the maximum size supported is 64*1024 STORAGE_UNIT bits. SEQUENTIAL_IO raises USE_ERROR if MAX_REC_SIZE exceeds this absolute limit.

5.9 MACHINE CODE INSERTIONS

The general definition of package MACHINE_CODE provides an assembly language interface for the target machine including the necessary record types needed in the code statement, an enumeration type containing all the opcode mnemonics, a set of register definitions, and a set of addressing mode functions. Also supplied (for use only in units that WITH MACHINE_CODE) are pragma IMPLICIT_CODE and the attribute 'REF.

Machine code statements take operands of type OPERAND, a private type that forms the basis of all machine code address formats for the target.

The general syntax for a machine code statement is

```
CODE_ n'(opcode, operand {, operand}));
```

In the example shown below, code_2 is a record 'format' whose first argument is an enumeration value of type OPCODE followed by two operands of type OPERAND.

```
CODE_2'(ADDA, a'ref, b'ref);
```

The opcode must be an enumeration literal (i.e., it can not be an object, attribute, or a rename). An operand can only be an entity defined in MACHINE_CODE or the 'REF attribute.

For an object, arguments to any of the functions defined in MACHINE_CODE must be static expressions, string literals, or the functions defined in MACHINE_CODE. The 'REF attribute may not be used as an argument in any of these functions.

'REF - The 'REF attribute denotes the effective address of the first of the storage units allocated to the object. For a subprogram, package, task unit, or label, it refers to the address of the machine code associated with the corresponding body or statement. The attribute is of type OPERAND defined in package MACHINE_CODE and is allowed only within a machine code procedure. 'REF is not supported for a package, task unit, or entry.

Registers - The supported register operands are R0, R1, ..., R15, SP, FP, PC.

Addressing Modes - All of the HCX's addressing modes are supported by the compiler. They are accessed through the following functions provided in MACHINE_CODE.

Address Mode	Assembler Notation	Ada Function Call
Register	Rn (n=0..13)	Rn
Register Deferred	(Rn) (n=0..14)	def(Rn)
Register + Displacement	<disp>(Rn) (n=0..15)	disp(Rn, <disp>)
Register + Displacement Deferred	*<disp>(Rn) (n=0..15)	disp_def(Rn, <disp>)
Autodecrement SP	-(SP), -(R14)	decr(SP)
Autoincrement SP	(SP)+, (R14)+	incr(SP)
Autoincrement Deferred SP	*(SP)+, *(R14)+	incr_def(SP)
Absolute Address	*\$<addr>	absol(<addr>)
Index Register	[Rx]i	index(i, Rx)
Displacement Relative	<disp>	rel(<disp>)
Displacement Relative Deferred	*<disp>	rel_def(<disp>)
Immediate	\$<disp>	immed(<disp>) (<disp> is int)
Immediate	\$<disp>	immed(<disp>) (<disp> is float)
Immediate	\$<disp>	immed(<disp>) (<disp> is a character)
External Name	\$<name> <disp>	ext(<name>) +<disp>, -<disp>

pragma IMPLICIT_CODE - The IMPLICIT_CODE pragma specifies that implicit code generated by the compiler is allowed (ON) or disallowed (OFF) and is used only within the declarative part of a machine code procedure. Implicit code includes preamble and postamble code (e.g., code used to move parameters from and to the stack). Implicit code does not eliminate code generated for runtime checks, nor does it eliminate call/return instructions (these can be eliminated by pragma SUPPRESS and pragma INLINE, respectively). A warning is issued if OFF is used and any implicit code needs to be generated. This pragma should be used with caution.

APPENDIX C
TEST PARAMETERS

Certain tests in the ACVC make use of implementation-dependent values, such as the maximum length of an input line and invalid file names. A test that makes use of such values is identified by the extension .TST in its file name. Actual values to be substituted are represented by names that begin with a dollar sign. A value must be substituted for each of these names before the test is run. The values used for this validation are given below.

<u>Name and Meaning</u>	<u>Value</u>
\$BIG_ID1 Identifier the size of the maximum input line length with varying last character.	(1..498 =>'A', 499 =>'1')
\$BIG_ID2 Identifier the size of the maximum input line length with varying last character.	(1..498 =>'A', 499 =>'2')
\$BIG_ID3 Identifier the size of the maximum input line length with varying middle character.	(1..249 251..499 =>'A', 250 =>'3')
\$BIG_ID4 Identifier the size of the maximum input line length with varying middle character.	(1..249 251..499 =>'A', 250 =>'4')
\$BIG_INT_LIT An integer literal of value 298 with enough leading zeroes so that it is the size of the maximum line length.	(1..496 =>'0', 497..499 =>"298")

TEST PARAMETERS

<u>Name and Meaning</u>	<u>Value</u>
\$BIG_REAL_LIT A universal real literal of value 690.0 with enough leading zeroes to be the size of the maximum line length.	(1..493 =>'0', 494..499 =>"69.0E1")
\$BIG_STRING1 A string literal which when catenated with BIG_STRING2 yields the image of BIG_ID1.	(1..249 =>'A')
\$BIG_STRING2 A string literal which when catenated to the end of BIG_STRING1 yields the image of BIG_ID1.	(1..249 =>'A', 250 =>'1')
\$BLANKS A sequence of blanks twenty characters less than the size of the maximum line length.	(1..479 =>' ')
\$COUNT_LAST A universal integer literal whose value is TEXT_IO.COUNT'LAST.	2_147_483_647
\$FIELD_LAST A universal integer literal whose value is TEXT_IO.FIELD'LAST.	2_147_483_647
\$FILE_NAME_WITH_BAD_CHARS An external file name that either contains invalid characters or is too long.	"/illegal/filename/2{]}\$bad"
\$FILE_NAME_WITH_WILD_CARD_CHAR An external file name that either contains a wild card character or is too long.	"/illegal/filename/wild*char"
\$GREATER_THAN_DURATION A universal real literal that lies between DURATION'BASE'LAST and DURATION'LAST or any value in the range of DURATION.	100_000.0

TEST PARAMETERS

<u>Name and Meaning</u>	<u>Value</u>
\$GREATER_THAN_DURATION_BASE_LAST A universal real literal that is greater than DURATION'BASE'LAST.	10_000_000.0
\$ILLEGAL_EXTERNAL_FILE_NAME1 An external file name which contains invalid characters.	"/no/such/directory/illegal_name1"
\$ILLEGAL_EXTERNAL_FILE_NAME2 An external file name which is too long.	"/no/such/directory/illegal_name2"
\$INTEGER_FIRST A universal integer literal whose value is INTEGER'FIRST.	-2_147_483_648
\$INTEGER_LAST A universal integer literal whose value is INTEGER'LAST.	2_147_483_647
\$INTEGER_LAST_PLUS_1 A universal integer literal whose value is INTEGER'LAST + 1.	2_147_483_648
\$LESS_THAN_DURATION A universal real literal that lies between DURATION'BASE'FIRST and DURATION'FIRST or any value in the range of DURATION.	-100_000.0
\$LESS_THAN_DURATION_BASE_FIRST A universal real literal that is less than DURATION'BASE'FIRST.	-10_000_000.0
\$MAX_DIGITS Maximum digits supported for floating-point types.	9
\$MAX_IN_LEN Maximum input line length permitted by the implementation.	499
\$MAX_INT A universal integer literal whose value is SYSTEM.MAX_INT.	2_147_483_647
\$MAX_INT_PLUS_1 A universal integer literal whose value is SYSTEM.MAX_INT+1.	2_147_483_648

TEST PARAMETERS

<u>Name and Meaning</u>	<u>Value</u>
<p>\$MAX_LEN_INT_BASED_LITERAL A universal integer based literal whose value is 2#11# with enough leading zeroes in the mantissa to be MAX_IN_LEN long.</p>	(1..2 =>"2:", 3..496 =>'0', 497..499=>"11:")
<p>\$MAX_LEN_REAL_BASED_LITERAL A universal real based literal whose value is 16:F.E: with enough leading zeroes in the mantissa to be MAX_IN_LEN long.</p>	(1..3 =>"16:", 4..495 =>'0', 496..499=>"F.E:")
<p>\$MAX_STRING_LITERAL A string literal of size MAX_IN_LEN, including the quote characters.</p>	(1 =>'"', 2..498 =>'A', 499 =>'")
<p>\$MIN_INT A universal integer literal whose value is SYSTEM.MIN_INT.</p>	-2_147_483_648
<p>\$NAME A name of a predefined numeric type other than FLOAT, INTEGER, SHORT_FLOAT, SHORT_INTEGER, LONG_FLOAT, or LONG_INTEGER.</p>	SHORT_SHORT_INTEGER
<p>\$NEG_BASED_INT A based integer literal whose highest order nonzero bit falls in the sign bit position of the representation for SYSTEM.MAX_INT.</p>	16#FFFFFFFD#

APPENDIX D
WITHDRAWN TESTS

Some tests are withdrawn from the ACVC because they do not conform to the Ada Standard. The following 27 tests had been withdrawn at the time of validation testing for the reasons indicated. A reference of the form "AI-ddddd" is to an Ada Commentary.

- . B28003A: A basic declaration (line 36) incorrectly follows a later declaration.
- . E28005C: This test requires that "PRAGMA LIST (ON);" not appear in a listing that has been suspended by a previous "PRAGMA LIST (OFF);"; The Ada Standard is not clear on this point, and the matter will be reviewed by the AJPO.
- . C34004A: The expression in line 168 yields a value outside the range of the target type T, but there is no handler for CONSTRAINT_ERROR.
- . C35502P: The equality operators in lines 62 and 69 should be inequality operators.
- . A35902C: The assignment in line 17 of the nominal upper bound of a fixed-point type to an object raises CONSTRAINT_ERROR, for that value lies outside of the actual range of the type.
- . C35904A: The elaboration of the fixed-point subtype on line 28 wrongly raises CONSTRAINT_ERROR, because its upper bound exceeds that of the type.
- . C35904B: The subtype declaration that is expected to raise CONSTRAINT_ERROR when its compatibility is checked against that of various types passed as actual generic parameters, may, in fact, raise NUMERIC_ERROR or CONSTRAINT_ERROR for reasons not anticipated by the test.

WITHDRAWN TESTS

- . C35A03E and C35A03R: These tests assume that attribute 'MANTISSA returns 0 when applied to a fixed-point type with a null range, but the Ada Standard does not support this assumption.
- . C37213H: The subtype declaration of SCONS in line 100 is incorrectly expected to raise an exception when elaborated.
- . C37213J: The aggregate in line 451 incorrectly raises CONSTRAINT_ERROR.
- . C37215C, C37215E, C37215G, and C37215H: Various discriminant constraints are incorrectly expected to be incompatible with type CONS.
- . C38102C: The fixed-point conversion on line 23 wrongly raises CONSTRAINT_ERROR.
- . C41402A: The attribute 'STORAGE_SIZE is incorrectly applied to an object of an access type.
- . C45332A: The test expects that either an expression in line 52 will raise an exception or else MACHINE_OVERFLOW is FALSE. However, an implementation may evaluate the expression correctly using a type with a wider range than the base type of the operands, and MACHINE_OVERFLOW may still be TRUE.
- . C45614C: The function call of IDENT_INT in line 15 uses an argument of the wrong type.
- . A74106C, C85018B, C87B04B, and CC1311B: A bound specified in a fixed-point subtype declaration lies outside of that calculated for the base type, raising CONSTRAINT_ERROR. Errors of this sort occur at lines 37 & 59, 142 & 143, 16 & 48, and 252 & 253 of the four tests, respectively.
- . BC3105A: Lines 159 through 168 expect error messages, but these lines are correct Ada.
- . AD1A01A: The declaration of subtype SINT3 raises CONSTRAINT_ERROR for implementations which select INT'SIZE to be 16 or greater.
- . CE2401H: The record aggregates in lines 105 and 117 contain the wrong values.
- . CE3208A: This test expects that an attempt to open the default output file (after it was closed) with mode IN_FILE raises NAME_ERROR or USE_ERROR; by Commentary AI-00048, MODE_ERROR should be raised.