

AD-A207 379

TECHNICAL REPORT BRL-TR-2992

BRL

IMPROVED ACCURACY AND COLLIMATION
PROCEDURES OF THE M-26/27
MUZZLE BORESIGHT DEVICE

CPT CURTIS L. McCOY
SFC MICHAEL R. WOMER Sr.
LAWSON F. NARVELL
BRUCE E. AMREIN

MAY 1989

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

DTIC
ELECTE
MAY 02 1989
S E D
ch

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

089 5 02 042

DESTRUCTION NOTICE

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
4. PERFORMING ORGANIZATION REPORT NUMBER(S) BRL-TR-2992			7a. NAME OF MONITORING ORGANIZATION		
6a. NAME OF PERFORMING ORGANIZATION US Army Ballistic Research Laboratory		6b. OFFICE SYMBOL (If applicable) SLCBR-DD-T	7b. ADDRESS (City, State, and ZIP Code)		
6c. ADDRESS (City, State, and ZIP Code) Aberdeen Proving Ground, MD 21005-5066			9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	10. SOURCE OF FUNDING NUMBERS		
8c. ADDRESS (City, State, and ZIP Code)		PROGRAM ELEMENT NO. 62618A	PROJECT NO. 1L1626 18AH80	TASK NO. 00	WORK UNIT ACCESSION NO. 001AJ
11. TITLE (Include Security Classification) Improved Accuracy and Collimation Procedures for the M-26/27 Muzzle Boresight Defice					
12. PERSONAL AUTHOR(S) McCoy, Curtis L. CPT; Womer, Michael R. Sr. MSG; Narvell, Lawson F. (HEL); Amrein, Bruce E. (HEL)					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM Feb87 TO Feb88		14. DATE OF REPORT (Year, Month, Day) February 1989	
15. PAGE COUNT 34					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	CAT, Standard Army "G" Pattern, Gunners Primary Sight (GPS),		
19	03		Muzzle Boresight Device (MBD), Optical Reticle Wedge,		
19	04		Collar Wrench, Tank Gun Accuracy, Boresighting, (Cont'd)		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) During normal use the M-26/27 muzzle boresight device is a very accurate device for boresighting tank cannons. This report proposes technical improvements to the tool used for the collimation of the M-26/27 muzzle boresight device (MBD). In addition, this report makes recommendations to improve present allowable tolerances in these MBDs and suggests a field expedient method of correcting MBDs which exceed tolerances under field conditions. <i>Keywords: Tank gun accuracy; Field collimation system alignment; M-26/27; M-256; Gun sights; Collimation reticle wedge.</i>					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL CPT McCoy/MSG Womer			22b. TELEPHONE (Include Area Code) 301-278-6648		22c. OFFICE SYMBOL SLCBR-SE-B

18. Subject Terms (Cont'd)

M68 cannon, M256 cannon

ACKNOWLEDGEMENTS

The authors would like to thank the following people and organizations for their ideas and assistance. Without their help this work could not have been done.

SFC Edward A.H. Braese of Company A 2nd Battalion 64th Armor for suggesting that we address the problem of modifying the tools.

SFC James E. Dale of the United States Army Armor School, Weapons Department for technical assistance in formalizing the procedures for collimation of the muzzle boresight device.

The metal workers of the US Army Ballistic Research Laboratory, Experimental Fabrication Division for procuring the necessary stock and fabrication of the test tools.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



The following page is blank.

TABLE OF CONTENTS

	Page
ACKNOWLEDGEMENTS.....	3
TABLE OF CONTENTS.....	5
LIST OF FIGURES.....	7
I. THE PROBLEM AND ITS BACKGROUND.....	9
II. OBJECTIVE.....	10
III. DESIGN AND MANUFACTURE OF THE IMPROVED TOOLS.....	10
IV. FIELD EXPEDIENT PROCEDURES FOR COLLIMATION/ALIGNMENT OF THE M-26/27 MUZZLE BORESIGHT DEVICE.....	10
V. BORESIGHT DEVICE ERROR.....	17
VI. OBSERVATIONS AND CONCLUSIONS.....	17
VII. RECOMMENDATIONS.....	24
REFERENCES.....	25
APPENDIX A - THE FIELD EXPEDIENT METHOD OF ALIGNMENT/ COLLIMATION OF THE M-26/27 MUZZLE BORESIGHT DEVICE ON THE M1/M1A1 MAIN BATTLE TANK.....	27
DISTRIBUTION LIST.....	33

The following page is blank.

LIST OF FIGURES

	Page
1. Engineering Drawings of Original MBD Tool	11
2. Retainer/Sealer Plugs/Adjusting Screw and Associated Parts.	12
3. Optical Unit and Related Parts.	13
4. Engineering Drawings of Improved MBD Tools.	14-16
5. Predicted Impact at 900m; M490 TP-T.	18
6. Predicted Impact at 1200m; M490 TP-T.	19
7. Predicted Impact at 1500m; M490 TP-T.	20
8. Predicted Impact at 900m; M724 TPDS-T.	21
9. Predicted Impact at 1200m; M724 TPDS-T.	22
10. Predicted Impact at 1500m; M724 TPDS-T.	23
A-1. Reticle Movement In MBD.	31

The following page is blank.

AN INVESTIGATION INTO THE ACCURACY AND COLLIMATION PROCEDURES OF THE M-26/27 MUZZLE BORESIGHT DEVICE

I. THE PROBLEM AND ITS BACKGROUND

The accuracy of tank cannons has long been considered extremely important to a crew's survivability on the modern battlefield. One of the integral components of a crew's tank gun accuracy is their ability to accurately align the cannon's center of bore with the optics of the fire control system (boresight).

The United States Army has two doctrinal methods of boresighting tank cannons. The primary method requires the use of the M-26/27 Muzzle Boresight Device (MBD). The alternate is known as the "two-point method" which requires thread, tape, and a pair of binoculars. The two-point method is used only when a MBD is not available or the MBD can not be used because of excessive gun tube wear.

In November 1986, the Science Advisor to the Commander in Chief, US Army Europe (USAREUR) and the 7th Army, requested the US Army Ballistic Research Laboratory (BRL), Aberdeen Proving Ground (APG), MD, to present possible enhancements to tank gun accuracy available to support the Canadian Army Trophy (CAT) Teams of the US Army. During the presentations in Germany to the CAT 87 teams it was brought to BRL's attention by SFC Edward Braese, Master Gunner for Company A, 2nd Battalion, 64th Armor, that there was a need to improve the current tools required to collimate the M26/27 MBD and that the allowable tolerance for the MBD excessive. After discussion with the Science Advisor, it was agreed that the BRL would look for a solution to the problem.

The MBD can be collimated to an error of 0.15 mil, but a problem arises on how to achieve this level of accuracy under field conditions. The Department of the Army (DA) Field Manual 17-12-1 and DA Field Circular 17-12-1A1 allow the device to have 1.0 mil of error in elevation and 0.50 mil of error in deflection. According to the MBD operator's manual (TM 9-4933-249-24&P) as well as the M1 and M1A1 Abrams operator's manual (TM9-2350-255-10 and TM 9-3908-4312-10) for the tank, there is no allowance for any error. Both of the above technical manuals simply state that upon rotating the MBD 180 degrees the aiming dot must remain on the same aiming point. If not, then the MBD is to be turned in to organizational maintenance. The organizational maintenance manual (TM 9-4933-249-24&P) states that there can be up to 1.0 mil of tolerance in both elevation and deflection.

Under current maintenance repair procedures, the device must be evacuated through direct support maintenance to general support maintenance for collimation and alignment if it exceeds established tolerances. The ensuing delay is extremely time consuming and can cost training time. Even after repair/realignment, there is a possibility that the M-26/27 could return with a large amount of error just under the tolerance windows because of the tools used to adjust the aiming dot of the MBD.

The tools required for the actual adjustment of the optical wedge in the MBD require improvement to consistently obtain the 0.15 mil accuracy. The actual tools required for alignment are a collar/spanner wrench and a 5/32 hex wrench (Figure 1). The MBD is designed

with the retainer plug concentric about the adjusting screws (Figure 2) used to adjust the optical wedge of the MBD (Figure 3). Since the adjusting screws are not held in position while tightening the retainer plugs, the adjusting screws are able to move, and error is induced. Given the proper tools this procedure can be done more efficiently and expeditiously.

II. OBJECTIVE

The objectives of this effort were first, to improve the tools necessary for collimation of the M-26/27 MBD; second, to demonstrate to the user that the amount of allowable error in boresight devices was excessive and suggest recommendations for improvement; and last, to formalize and submit for approval a field expedient method of collimating MBDs.

III. DESIGN AND MANUFACTURE OF THE IMPROVED TOOLS

After a careful look at the tools in use, it was determined that the current tools could be slightly modified to provide the desired results. The modification required drilling a hole 13/64 inch in diameter through the collar/spanner wrench and the manufacturing of a handle type assembly with a 5/32 inch hex wrench end attached to it. Figure 4 shows the engineering drawings that were prepared.¹ The results of this effort provided a pair of tools that could achieve the maximum acceptable error, 0.15 mil, when collimating the MBD.


IV. FIELD EXPEDIENT PROCEDURES FOR COLLIMATION/ALIGNMENT OF THE M-26/27 MUZZLE BORESIGHT DEVICE

The U.S. Army's goal is to issue a MBD per tank in the inventory. Most USAREUR units have achieved the Army's goal of one MBD per tank. It became clear that a field expedient method for collimation and alignment of the MBD was being used by US troops in Germany, although the procedure had never been formalized. Since the method is very useful, we have developed a description of the procedure and coordinated with the proponent, the Weapons Department, US Army Armor Center and School. This description is included at Appendix A.²


The procedure enables a tank crew to fine tune a MBD in an existing tube without sending the device to maintenance for repair. The process of MBD collimation at the operator level was demonstrated very successfully during CAT 87.

¹ *Rough sketches were prepared by MSG Michael R. Womer Sr, US Army Ballistic Research Laboratory, and engineering drawings were prepared by Mr. Lawson F. Narvell, Human Engineering Laboratory.*

² *Point of contact for boresighting and muzzle boresighting device was SFC James E. Dale, US Army Armor School, Fort Knox, Ky.*




Standard Locking Tool




Standard 5/32 Allen Wrench

Figure 1. Engineering Drawings of Original MBD Tools



Item	Description
1	Adjusting Screw
2	Plug, Retaining
3	Plug Sealing

Figure 2. Retainer/Sealer Plugs/Adjusting Screw and Associated Parts



Item	Description
1	Prism, Optical Wedge Reticle
2	Prism, Optical Instrument

Figure 3. Optical Unit and Related Parts






Figure 4. Engineering Drawings of Improved MBD Tools



Locking Tool
 Matl. Steel FS-4130 or 4140
 Provide Carburized Finish

Figure 4a. Engineering Drawings of Improved MBD Tools



Adjusting Tool
 Matl. Steel FS-4130 or 4140
 Provide Carburized Finish

Figure 4b. Engineering Drawings of Improved MBD Tools

V. EFFECTS OF BORESIGHT DEVICE ERROR ON TANK GUN ACCURACY

It is essential that the allowable tolerance in MBDs be reduced to more acceptable levels. Currently, the amount of tolerance is up to 1.0 mil in elevation and 0.50 mil in deflection. These values are in accordance with DA Field Manual 17-12-1 and DA Field Circular 17-12-1A1. There are other publications which allow for even greater tolerances; however, the previously stated publications are the primary references used by Armor units in the Army today.

During the actual boresight procedure one must rotate the MBD 180 degrees to determine its accuracy in locating the exact center of bore of the gun tube. If after rotating the MBD 180 degrees, its aiming dot does not exactly realign with the original aiming point, the difference must be divided by two to determine the mean boresight readings (actual center of bore). The greater the difference between the first boresight reading and the second, the greater the opportunity for crew error in applying a correct boresight to their fire control system. The ability of a crew to accurately collimate a M26/27 MBD to their specific tank, would enhance the crew's confidence that their tank will be able to hit targets through a more accurately boresighted fire control system.

If the maximum errors stated above actually existed, then one would induce 1/2 of those errors into the fire control system by splitting the differences as directed in the boresighting procedures. This error could be eliminated by performing an independent zero of the gun. However, it is policy that individual zero exercises are not conducted. Instead, the gun is fired from the boresight with a common computer correction factor for a specific type of ammunition. This procedure does not allow for an error in the strike of the round from the aimpoint as a result of different gun tube characteristics or fire control errors induced as a result of a faulty MBD.

Assuming all other error sources were corrected, the effects of a faulty MBD can be examined. The results of a .5 mil (elevation) by .25 mil (deflection) MBD error induced during boresighting procedures on M490 TP-T ammunition are depicted in Figures 5-7. The range is varied from 900 meters to 1500 meters to demonstrate the increasing effect at the greater ranges. The same conditions and ranges were examined for M724 TPDS-T ammunition (Figures 8-10). The plots clearly show the M1 fire control system cannot hit its desired aim point because of the error induced by the MBD. When the MBD error is coupled with all other error sources, the tank fire control system Ph is lowered.

VI. OBSERVATIONS AND CONCLUSIONS

This effort has been a quick reaction to provide the soldiers in the field with an alternative to accurately align MBDs when boresighting a tank cannon. If a MBD is out of tolerance, the Ph of the tank main gun ammunition is greatly reduced. The purpose of the boresighting is to accurately calibrate a main gun.

105mm M490 TP-T
Range = 900 meters




Figure 5. Predicted Impact at 900m; M490 TP-T.




Figure 6. Predicted Impact at 1200m: M490 TP-T.

105mm M490 TP-T
Range = 1500 meters




Figure 7. Predicted Impact at 1500m; M490 TP-T.

105mm M724 TPDS-T
(using M392A2 solution)
Range = 900 meters




Figure 8. Predicted Impact at 900m; M724 TPDS-T.

105mm M724 TPDS-T
(using M392A2 solution)
Range = 1200 meters




Figure 9. Predicted Impact at 1200m; M724 TPDS-T.

105mm M724 TPDS-T
(using M392A2 solution)
Range = 1500 meters




Figure 10. Predicted Impact at 1500m; M724 TPDS-T.

VII. RECOMMENDATIONS

The authors make the following recommendations:

- That the Army review and accept the new configuration of these tools.
- That the Army review the field expedient procedures for alignment/collimation of the M-26/27 muzzle boresight and adopt a policy for its use under special conditions.
- That the Army review the amount of acceptable tolerance in the M-26/27 MBD and reduce those tolerances accordingly.

REFERENCES

FM17-12-1, Tank Combat Tables M-1, 3 Nov 86.
FM17-12-1A1, Tank Combat Tables M-1A1, 30 Apr 86.
TM9-4933-249-24&P, M-26 Boresight w/case, 9 Jul 85.
TM9-3908-4312-10, M-26 Muzzle Boresight, 13 Dec 82.
TM9-2350-264-10-2, Tank Combat FT 120mm M1A1, 30 Dec 85.
TM9-2350-255-10-2, Tank Combat FT 105mm M1, 30 Nov 81.

The following page is blank.

APPENDIX A

**THE FIELD EXPEDIENT METHOD OF ALIGNMENT/COLLIMATION OF THE
M-26/27 MUZZLE BORESIGHT DEVICE ON THE M1/M1A1 MAIN BATTLE TANK**

**MSG MICHAEL R. WOMER SR.
US ARMY BALLISTIC RESEARCH LABORATORY**

**SFC JAMES E. DALE
US ARMY ARMOR SCHOOL**

The following page is blank.

APPENDIX A

THE FIELD EXPEDIENT METHOD OF ALIGNMENT/COLLIMATION OF THE M-26/27 MUZZLE BORESIGHT DEVICE ON THE M1/M1A1 MAIN BATTLE TANK

1. Purpose: To fine tune the MBD to a specific gun tube or align the device without the support of intermediate general support maintenance.

2. Procedure:

- a. Position the vehicle on level ground.
- b. Prepare the gunners station for operation IAW TM9-2350-264-10-2 (see page 2-194 through 2-222).
- c. Select a boresight target as close to 1200 meters away as possible. Target should be placed so the main gun is over the front of the tank when it is aligned with target.
- d. Make sure that gunner's hydraulic pressure gage shows 1500 to 1700 psi.
- e. Set GUN SELECT switch to MAIN.
- f. Set MAGNIFICATION lever to 10X.
- g. Make sure FILTER/CLEAR/SHUTTER switch is set to CLEAR.
- h. Make sure DAY ballistic door is open.
- i. Set FIRE CONTROL MODE switch to EMERGENCY.
- j. Using the gunner's power control handles, look in gunner's primary sight (GPS) eyepiece, lay reticle aiming circle on center of target, and lase to the target.
- k. Set FIRE CONTROL MODE switch to MANUAL.
- l. Remove muzzle plug from main gun.
- m. Remove protective cover from MBD. (Note: Two individuals required).
- n. Remove the two sealing plugs in order to expose the retaining plugs and the adjusting shoulder screws.
- o. Insert the MBD into the end of the gun tube. The locating pad assembly should be at the 12 o'clock position.

p. With the master gunner looking through the MBD and giving directions, the gunner will use manual controls to lay the aimpoint of the MBD to the upper left hand corner of the boresight target. The standard US Army "G" Pattern (method used to manipulate gun controls) will be used. This becomes the starting point.

q. Rotate the MBD to the 6 o'clock position. If the aiming dot has moved away more than $\frac{1}{3}$ the width of the dot, the device is out of alignment.

(Note: Rotating the MBD while still in the main gun may result in damage to the device and or the main gun. Remove the MBD from the gun barrel for rotating.)

r. To adjust, slightly loosen the retainer plugs that secure the optical wedge shoulder screws.

s. Utilizing the $\frac{5}{32}$ hex wrench, adjust the aiming dot $\frac{1}{2}$ the distance between the aiming points in step p and q above by turning the optical wedge adjusting screws.

(Note: The reticle in the MBD does not move left to right or up and down as normal sight reticles, but in a curve as shown in Figure A-1. It should also be noted that the adjusting screws do not have a mechanical stop.)

t. Repeat steps p through s as many times as necessary in order to align the device to within .15 mil.


(Note: If after several attempts to align the device the aiming dot is still off, gun tube wear (muzzle bell) may be present.

u. After alignment is complete use the improved tool set to hold the adjusting screw in place and tighten the retainer plugs. Make sure that the aiming dot does not move during this step.

v. Replace the sealing plug.

w. Replace the protective cover.

x. The device is now aligned for the specific gun in which it was adjusted. If used in another gun, check the alignment and adjust as needed.



The following page is blank.

Figure A-1. Reticle Movement in MBD.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22305-6145	1	Commander US Army Aviation Systems Command ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798
1	HQDA (SARD-TR) Washington, DC 20310-0001	1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001		
1	Commander US Army Laboratory Command ATTN: AMSLC-DL Adelphi, MD 20783-1145	1	Commander US Army Missile Command ATTN: AMSMI-AS Redstone Arsenal, AL 35898-5000
1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-MSI Picatinny Arsenal, NJ 07806-5000	1	Commander US Army Tank Automotive Command ATTN: AMSTA-TSL Warren, MI 48090-5000
1	Commander Armament R&D Center US Army AMCCOM ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	1	Director US Army TRADOC Analysis Command ATTN: ATAA-SL White Sands Missile Range, NM 88002
1	Director Benet Weapons Laboratory Armament R&D Center US Army AMCCOM ATTN: SMCAR-LCB-TL Watervliet, NY 12189-4050	1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-5000	1	AFWL/SUL Kirtland AFB, NM 87177
		1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000

DISTRIBUTION LIST (Cont'd)

<u>No of Copies</u>	<u>Organization</u>
1	Commander FORSCOM ATTN: AFCCG-CG Fort McPherson, GA 30330-6000
1	Commander US Army Combined Arms Center ATTN: ATZL-CG Fort Leavenworth, KS 66048
1	Commander US Army Logistic Center ATTN: ATCL-CG Fort Lee, VA 23801
1	Commander III Corps ATTN: AFZF-CG Fort Hood, TX 76544
3	Commandant US Army Armor School ATTN: ATZK-CG ATSB-CD-ML (Mr. Montgomery) (2 cys) Fort Knox, KY 40121
3	CINCUSAREUR ATTN: AEAGC-CG AEAGX-SA (Mr. Eckles) (2 cys) APO, NY 09403

Aberdeen Proving Ground

Dir, USAMSAA

ATTN: AMXSY-D
 AMXSY-MP, H. Cohen
 AMXSY-LBDAR (Mr. Fox)
 (Mr. Astor)

Cdr, USATECOM

ATTN: AMSTE-TO-F

Cdr, CRDC, AMCCOM

ATTN: SMCCR-RSP-A
 SMCCR-MU
 SMCCR-SPS-IL

Dir, HEL

ATTN: SLCHE-SS-ED (5 cys)

Cdr, USAOC&S

ATTN: ATSE-CG (Mr. Senn)
 ATSL-DTM-WS (2 cys)

USER EVALUATION SHEET/CHANGE OF ADDRESS

This laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers below will aid us in our efforts.

1. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

2. How, specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

3. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

4. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

BRL Report Number _____ Division Symbol _____

Check here if desire to be removed from distribution list. _____

Check here for address change. _____

Current address: Organization _____
Address _____

-----FOLD AND TAPE CLOSED-----

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T(NEI)
Aberdeen Proving Ground, MD 21005-5066

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE \$300

BUSINESS REPLY LABEL

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T(NEI)
Aberdeen Proving Ground, MD 21005-9989