

MRL-TN-549

AR-005-679



DEPARTMENT OF DEFENCE

DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION

MATERIALS RESEARCH LABORATORY

MELBOURNE, VICTORIA

TECHNICAL NOTE

MRL-TN-549

AD-A208 878


STRESS INTENSITY CALIBRATION OF A RING SPECIMEN
USING A FINITE ELEMENT TECHNIQUE

G. Clark and T.V. Rose

SDTICD
ELECTE
JUN 15 1989
H

Approved for Public Release

DSTO 
MELBOURNE



89 6 15 039

**DEPARTMENT OF DEFENCE
MATERIALS RESEARCH LABORATORY**

**TECHNICAL NOTE
MRL-TN-549**

**STRESS INTENSITY CALIBRATION OF A RING SPECIMEN
USING A FINITE ELEMENT TECHNIQUE**

G. Clark and T.V. Rose

ABSTRACT

A finite element technique has been used to determine the stress intensity at the tip of a bore crack in a cylindrical fracture specimen. This technical note describes the detailed input for the computer programs which perform the stress analyses. Much of the preparatory work involves generating a suitable mesh of elements which represents the elastic properties of the specimen. The constraints which are imposed on the mesh geometry are described.

Approved for Public Release

© Commonwealth of Australia

POSTAL ADDRESS: Director, Materials Research Laboratory
P.O. Box 50, Ascot Vale, Victoria 3032, Australia

STRESS INTENSITY CALIBRATION OF A RING SPECIMEN
USING A FINITE ELEMENT TECHNIQUE

G. Clark and T.V. Rose

1. INTRODUCTION



Materials Research Laboratories are currently investigating the effect of residual stresses resulting from autofrettage on the growth of fatigue cracks originating at craze cracks on the bore surface of large-calibre gun barrels. This investigation makes use of ring specimens 25.4 mm thick, cut from 76 mm gun* barrel forgings; the rings are compressed across a diameter, and a fatigue crack grows from a starter notch in the bore surface immediately above the lower loading point. The stress-intensity at the tip of such a crack is known for rings having a diameter ratio of 0.5 [1,2]; in this case however, it was necessary to use specimens with a diameter ratio of 0.555, and this factor was believed to have a significant effect on the stress intensity calibration of the cracked specimen.

To obtain the stress-intensity calibration for the MRL specimen geometry, the specimen was modelled mathematically and subjected to a Finite-Element (FE) stress analysis. The computer programs used for this work were made available by ARL and are known collectively as DISMAL (DISplacement Method anALysis). This report describes the use of DISMAL for the ring specimen geometry.

2. DISMAL

The DISMAL programs for structural analysis were developed at the University of Sydney by Dr R.H. Keays [4]. Dr Keays later worked at ARL and modified the programs for operation on the ARL DEC PDP-10. Facilities for inserting a special crack tip element were added later [3] in order to provide better representation of the stress gradient near a crack tip. Full details on the general use of DISMAL are given in reference 4.

* Weapon for Australian Army Fire Support Vehicle



2.1 Mesh Generation

To analyse a specific geometry, it is first necessary to represent the structure as a network (or mesh) of elements. The ring specimen was modelled using a two-dimensional mesh consisting of quadrilaterals (QUAD4 elements), triangles (TRIM3) and one special element at the crack tip. The symmetry of the specimen permitted the use of a mesh representing only half of the ring, as shown in Fig. 1.

To generate the mesh, it is necessary to draw out the specimen on a scale sufficient for accurate identification of the element corners (or nodes), including features such as the fatigue crack and load-application points. The special element is then defined and consists of 10 nodes making a semicircle centred on the crack tip. The node points are separated by 20° and are placed at a radius 'r' where 'r' is half the crack length or half the remaining ligament, whichever is smaller. These nodes are numbered 1 to 10 clockwise and are linked consecutively. Two further semicircles of 10 nodes are positioned at radii $1.15r$ and $1.30r$, and serve to transmit the displacements from the body of the structure to the special element; these are numbered 11 to 30 (clockwise, increasing radius). These nodes are linked to form two bands of quadrilaterals around the special element.

This procedure for designating the corners of quadrilaterals (and triangles where these are more suitable) is continued until the whole structure is represented. The semicircular arrangement of points 1 to 30 is not, in general, continued, although the following guide lines are followed.

(a) The area enclosed by each element should gradually increase with distance from the crack tip until a workable element size (typically 0.5% of the total area) is achieved.

(b) The numbering system used should ensure that the difference between the largest and smallest node numbers defining an element is minimised in order to reduce computing time. An acceptable band width was obtained with a node difference of 15.

(c) The smallest allowable included angle is 40° for quadrilaterals and 15° for triangular elements.

(d) Loads should be introduced via a series of elements of gradually increasing size.

2.2 Input to Programs - File "DATA"

A file "DATA" is constructed, containing all the information required to characterize the mesh and loading conditions. The format (including order) of this information is rigidly defined in the programs and any deviation from this format can produce results which contain errors. Appendix 1 is the DATA file for a ring specimen which contains a crack 0.2 of the wall thickness in length. The major features requiring care during construction of this file are described below.

(a) The program title must be the first line of data; a FORTRAN format of 18A4 is used, read with right justification, e.g. RING _555_A/W0.2.

(b) Units used in the program form the second line, in 2A3, 2X, 2A3 format, e.g. M M _ _ _ _ _ NEWTON.

(c) MASK is the third line, and suppresses the unused degrees of freedom for each node. The format is MASK _ _ _ XYZ $R_x R_y R_z$ where XYZ represents displacement in the x, y and z directions, and R_x , R_y , R_z allow rotations about the three axes; a code 1 inhibits movement and 0 allows displacement, e.g. MASK _ _ _ 000111 allows movement of the nodes but no rotations.

An error was discovered in the existing program prohibiting the use of a two-dimensional mask i.e. 001111, and it was therefore necessary to insert the 'z' direction restriction after each node number.

(d) The fourth line defines the total number of points in the structure (and hence the number of lines following). Format is POINTS, 12X, I4.

(e) The following lines consist of information about each node in the mesh; number, degree of freedom and position (in a rectangular coordinate system). The format is I5, 2X, 6I1, 3F10.2, and nodes are inserted in ascending numerical order (in fact, the program re-numbers the nodes in input order, so it is necessary to take care with input to avoid the band-width problem outlined earlier).

In the example in Appendix 1, it should be noted that symmetry of the specimen requires the use of a y-direction restriction on those points along the symmetry axis and common to both halves of the specimen. It is also necessary to fix one point on the mesh in space to avoid translational movement of the whole specimen; in this case, point 377 (on the symmetry axis) was chosen.

(f) Following the last node description are two lines which define the material's elastic properties. The format is

```
MATERIAL, 17X, TITLE OR COMMENT (UP TO 17 CHARACTERS)
E15.0, F5.3, E15.0, 2E10.0
```

where the second line contains Young's Modulus, Poisson's Ratio, Shear modulus, maximum allowable stress in tension or compression, and maximum allowable shear stress. Default for the maximum allowable stresses is zero.

(g) The next section defines the special crack tip element; two lines are used, the first having the format 4A4, A2, 1X, I4, 4A4, A2

```
SPECIAL_ELEMENTS _ _ _ _ _ 1 _ _ CRACK_TIP
```

The second line is a mask used to define the degrees of freedom for each node point, in format I2, 60I1, the first term being the number of nodes in the element, the others being masks of a similar form to those used earlier. Only masks of 000111 or 000000 can be used; no z-direction constraint is allowed. The third line (I2, 10I5) defines the similarity and corner points of the special element; a second special element (identical in size and orientation) may be inserted by making SIM=01 for the second special element. Note that points are defined in an anti-clockwise direction.

(h) Printing of the element stiffness matrices and of detailed stresses may be switched off by the next two lines:

```
PRINT_ELSTIF_OFF
PRINT_STRESS_OFF
```

(i) The quadrilateral element control line and element definitions follow, in the format

```
4A4, A2, 1X, I4, 2X, 4A4, A2
I2, 4I5, F10.4, E10.1, F5.3, E10.1
```

where the first line contains

```
QUADRI _ _ _ _ _ QUAD4 _ _ _ 307
```

The second 4A4, A2 is available for comments which will appear in the output text, and the second line contains (in order) similarity, the four node numbers (anticlockwise), thickness (assumed to be unchanged if left blank), Young's Modulus, Poisson's Ratio, and Shear Modulus (the last three defaulting to the values in the previous MATERIAL statement). The second format is repeated for each element of the specified type.

(j) Triangular element control line and definitions follow a similar format (with 3I5 instead of 4I5). Thickness may be left blank, defaulting to the previously-defined value.

(k) If the structure has been fully defined, the line END _ _ STRUCTURE is inserted.

(l) Any number of load cases may now be inserted, in the format

```
LOADS, 14X, I4, 2X, 4A4, A2
I5, 6F10.02
```

where the first line contains the number of loads in the load case, and the load case name, and the second line(s) contain the number of the node(s) at which load is applied, the forces in x, y, z directions, and moments M_x , M_y , M_z .

(m) The line END _ _ LOADS terminates the data file.

2.3 Input to Programs - File "CDATA"

A second input file is required to define the properties of the crack tip special element. The file contains

Number of nodes in the special element
 Young's modulus, Poisson's ratio, thickness
 and radius of the element
 Angular separate of nodes (in radians)
 Integration step size
 The number of terms in the stress function
 Global coordinates of local axes $X_i Y_i Z_i$ ($i=1,2,3$).

Further details of these parameters are given in reference 5, and an example of file CDATA is given in Appendix 2.

3. DATA CHECKING AND INPUT

Two programs are used to check the input data. The first, DIPLLOT creates a plot of the mesh as described in DATA, and this plot may be inspected for continuity and geometric anomalies. An example of the dialogue required to run DIPLLOT is given in reference 4.

The second program INPUTS performs some checking in preparation for determination of the stiffness matrix. If there are no errors a communication file DTALK.TMP is created on disk. If no such file is produced, information on the errors in DATA is given in file PRINT1.LST.

If all is in order, the programs which make up DISMAL are run as a BATCH job (too much core is required for running the programs individually from MONITOR). The batch control program for execution of DISMAL is contained in Appendix 3.

4. RESULTS AND DISCUSSION

The crack tip stress intensity is given in the output file PRINT3.LST. For this particular geometry, the symmetry condition used to reduce the number of elements implies that the load applied to the half-ring is half of that which would be applied to the full ring.

Meshes representing crack lengths between 0.1 and 0.9 of the ring wall thickness (W) were processed. The values of stress intensity (K) obtained for a load P are given in Table I, in the form of the dimensionless parameter Y where B is the ring thickness and

$$K = \frac{PY}{B\sqrt{W}}$$

For ease of use, a polynomial was fitted to this data, giving the relation

$$Y = 9.8054(a/W)^{0.5} - 25.0044(a/W) + 54.6356(a/W)^{1.5} - 78.330(a/W)^2 + 62.0963(a/W)^{2.5} - 21.7418(a/W)^3$$

This polynomial was used [6] to determine the relationship between fatigue crack growth rate and crack tip stress intensity in ring specimens.

5. CONCLUSION

A finite element technique has been used to determine the stress intensity at the tip of a bore crack in a ring specimen loaded in compression across the diameter; various crack lengths were considered, and the results have been presented in a polynomial form.

Table I Results of Analysis

Crack Length	$Y = KB\sqrt{W} / P$
0.1 W	1.717
0.2 W	2.073
0.3 W	2.273
0.4 W	2.376
0.5 W	2.433
0.6 W	2.400
0.7 W	2.312
0.8 W	2.150
0.9 W	1.865

REFERENCES

1. Jones, A.T., "A Radially Cracked Cylindrical Fracture Toughness Specimen", Engineering Fracture Mechanics, 6 435-446 (1974).
2. Grandt, A.F., Jr, "Evaluation of a Cracked Ring Specimen for Fatigue Testing under Constant Range in Stress Intensity Factor", Proc. Internat. Conf. Fracture Mechanics and Technology, Hong Kong, March 21-25, 1977.
3. Jones, R. and Callinan, R.J., "A Special Crack Tip Element for Three-Dimensional Crack Problems", Structures Report 374, Aeronautical Research Laboratories, Melbourne (November 1978).
4. Callinan, R.J., "Users Guide to DISMAL - A General Purpose Structural Analysis Program", Structures and Materials Tech. Memorandum 227, Aeronautical Research Laboratories, Melbourne (January 1975).
5. Callinan, R.J., "Programs for Calculating Stress Intensity Factors in Structures having Cracked Sheet Elements", Structures Tech. Memorandum 244, Aeronautical Research Laboratories, Melbourne (1976).
6. Clark, G., "Experimental Determination of Stress-Intensity in a Cracked Cylindrical Specimen", Report MRL-R-774, Materials Research Laboratories, Melbourne (1980).




Figure 1. Finite Element Mesh for half ring containing a bore crack 0.2 of the wall thickness in length.




Figure 2. Crack tip region of mesh shown in Fig. 1. Crack tip is at "a".

DATA

(APPENDIX__1)

RING 0.555 R A/W=0.2 with modified points

MM NEWTONS

MASK 000111

POINTS		377	
1	1	108.000	0.000
2	1	108.482	2.736
3	1	109.872	5.142
4	1	112.000	6.928
5	1	114.611	7.878
6	1	117.389	7.878
7	1	120.000	6.928
8	1	122.128	5.142
9	1	123.518	2.736
10	11	124.000	0.000
11	1	106.000	0.000
12	1	106.603	3.420
13	1	108.340	6.428
14	1	111.000	8.660
15	1	114.264	9.848
16	1	117.736	9.848
17	1	121.000	8.660
18	1	123.660	6.428
19	1	125.397	3.420
20	11	126.000	0.000
21	1	104.000	0.000
22	1	104.724	4.104
23	1	106.807	7.713
24	1	110.000	10.392
25	1	113.914	11.818
26	1	118.084	11.818
27	1	122.000	10.392
28	1	125.193	7.713
29	1	127.276	4.104
30	11	128.000	0.000
31	1	100.000	0.000
32	1	99.870	5.000
33	1	103.600	10.400
34	1	108.000	14.000
35	1	113.200	16.000
36	1	118.800	16.000
37	1	124.000	14.000
38	1	128.400	10.400
39	1	131.200	5.600
40	11	132.000	0.000
41	1	98.870	15.000
42	1	104.800	19.200
43	1	112.000	22.000
44	1	120.000	22.000
45	1	127.200	19.200
46	1	132.800	14.400
47	1	136.800	7.600
48	11	138.000	0.000
49	1	96.820	25.000
50	1	102.000	28.000
51	1	110.800	30.000
52	1	121.000	30.000

53	1	131.200	26.000
54	1	138.800	19.600
55	1	144.000	10.400
56	11	146.000	0.000
57	1	93.670	35.000
58	1	108.800	40.000
59	1	123.200	40.000
60	1	136.400	34.800
61	1	146.800	26.000
62	1	154.000	14.000
63	11	156.000	0.000
64	1	89.300	45.000
65	1	97.600	49.600
66	1	106.600	52.000
67	1	116.000	52.800
68	1	125.200	52.000
69	1	134.400	49.600
70	1	142.400	45.600
71	1	150.000	40.000
72	1	156.000	34.000
73	1	161.600	26.000
74	1	165.200	18.000
75	1	168.000	9.200
76	11	168.800	0.000
77	11	180.000	0.000
78	1	179.720	10.000
79	1	178.890	20.000
80	1	177.480	30.000
81	1	175.500	40.000
82	1	166.000	42.000
83	1	158.400	50.000
84	1	148.800	56.800
85	1	139.200	62.000
86	1	127.600	64.800
87	1	172.920	50.000
88	1	169.710	60.000
89	1	156.000	68.800
90	1	144.000	75.200
91	1	165.830	70.000
92	1	161.250	80.000
93	1	150.000	80.000
94	1	158.670	85.000
95	1	86.600	50.000
96	1	95.260	55.000
97	1	103.920	60.000
98	1	112.580	65.000
99	1	121.240	70.000
100	1	129.900	75.000
101	1	138.560	80.000
102	1	147.220	85.000
103	1	155.880	90.000
104	1	61.920	57.360
105	1	90.110	63.070
106	1	98.300	68.830
107	1	106.490	74.560
108	1	114.680	80.300

109	1	122.870	86.040
110	1	131.060	91.770
111	1	139.260	97.510
112	1	147.450	103.240
113	1	76.600	64.280
114	1	84.260	70.710
115	1	91.930	77.130
116	1	99.590	83.560
117	1	107.250	89.990
118	1	114.910	96.420
119	1	122.570	102.850
120	1	130.230	109.270
121	1	137.890	115.700
122	1	70.710	70.710
123	1	77.780	77.780
124	1	84.850	84.850
125	1	91.920	91.920
126	1	98.990	98.990
127	1	106.060	106.070
128	1	113.140	113.140
129	1	120.210	120.210
130	1	127.280	127.280
131	1	64.280	76.600
132	1	70.710	84.260
133	1	77.130	91.930
134	1	83.560	99.590
135	1	89.990	107.250
136	1	96.420	114.910
137	1	102.850	122.570
138	1	109.270	130.230
139	1	115.700	137.890
140	1	57.360	81.920
141	1	63.090	90.110
142	1	68.830	98.300
143	1	74.560	106.490
144	1	80.300	114.680
145	1	86.040	122.870
146	1	91.770	131.060
147	1	97.510	139.260
148	1	103.240	147.450
149	1	50.000	86.600
150	1	55.000	95.260
151	1	60.000	103.920
152	1	65.000	112.580
153	1	70.000	121.240
154	1	75.000	129.900
155	1	80.000	138.560
156	1	85.000	147.220
157	1	90.000	155.880
158	1	42.260	90.630
159	1	46.490	99.690
160	1	50.710	108.760
161	1	54.940	117.820
162	1	59.170	126.880
163	1	63.390	135.950
164	1	67.620	145.010

5	1	71.850	154.070
6	1	76.070	163.140
7	1	34.200	93.970
8	1	37.620	103.370
9	1	41.040	112.760
0	1	44.460	122.160
1	1	47.880	131.560
2	1	51.300	140.950
3	1	54.720	150.350
4	1	58.140	159.750
5	1	61.560	169.140
6	1	25.880	96.590
7	1	28.470	106.250
8	1	31.060	115.910
9	1	33.650	125.570
0	1	36.230	135.230
1	1	38.820	144.890
2	1	41.410	154.550
3	1	44.000	164.210
4	1	46.590	173.870
5	1	17.360	98.480
6	1	19.100	108.330
7	1	20.840	118.180
8	1	22.570	128.030
9	1	24.310	137.870
0	1	26.050	147.720
1	1	27.780	157.570
2	1	29.520	167.420
3	1	31.260	177.270
4	1	8.720	99.620
5	1	9.590	109.580
6	1	10.460	119.540
7	1	11.330	129.510
8	1	12.200	139.470
9	1	13.070	149.430
0	1	13.940	159.390
1	1	14.820	169.350
2	1	15.690	179.320
3	1	0.000	100.000
4	1	0.000	110.000
5	1	0.000	120.000
6	1	0.000	130.000
7	1	0.000	140.000
8	1	0.000	150.000
9	1	0.000	160.000
0	1	0.000	170.000
1	1	0.000	180.000
2	1	-8.720	99.620
3	1	-9.590	109.580
4	1	-10.460	119.540
5	1	-11.330	129.510
6	1	-12.200	139.470
7	1	-13.070	149.430
8	1	-13.940	159.390
9	1	-14.820	169.350
0	1	-15.690	179.320

221	1	-17.360	98.480
222	1	-19.100	108.330
223	1	-20.840	118.180
224	1	-22.570	128.030
225	1	-24.310	137.870
226	1	-26.050	147.720
227	1	-27.780	157.570
228	1	-29.520	167.420
229	1	-31.260	177.270
230	1	-25.880	96.590
231	1	-28.470	106.250
232	1	-31.060	115.910
233	1	-33.650	125.570
234	1	-36.230	135.230
235	1	-38.820	144.890
236	1	-41.410	154.550
237	1	-44.000	164.210
238	1	-46.590	173.870
239	1	-34.200	93.970
240	1	-37.620	103.370
241	1	-41.040	112.780
242	1	-44.460	122.180
243	1	-47.880	131.580
244	1	-51.300	140.980
245	1	-54.720	150.380
246	1	-58.140	159.780
247	1	-61.560	169.180
248	1	-42.260	90.630
249	1	-46.490	99.690
250	1	-50.710	108.760
251	1	-54.940	117.820
252	1	-59.170	126.880
253	1	-63.390	135.950
254	1	-67.620	145.010
255	1	-71.850	154.070
256	1	-76.070	163.140
257	1	-50.000	86.600
258	1	-55.000	95.260
259	1	-60.000	103.920
260	1	-65.000	112.580
261	1	-70.000	121.240
262	1	-75.000	129.900
263	1	-80.000	138.560
264	1	-85.000	147.220
265	1	-90.000	155.880
266	1	-57.360	81.920
267	1	-63.090	90.110
268	1	-68.830	98.300
269	1	-74.560	106.490
270	1	-80.300	114.680
271	1	-86.040	122.870
272	1	-91.770	131.060
273	1	-97.510	139.260
274	1	-103.240	147.450
275	1	-64.280	76.600
276	1	-70.710	84.260

277	1	-77.130	91.930
278	1	-83.560	99.590
279	1	-89.990	107.250
280	1	-96.420	114.910
281	1	-102.850	122.570
282	1	-109.270	130.230
283	1	-115.700	137.890
284	1	-70.710	70.710
285	1	-77.780	77.780
286	1	-64.850	84.850
287	1	-91.920	91.920
288	1	-98.990	98.990
289	1	-106.070	106.070
290	1	-113.140	113.140
291	1	-120.210	120.210
292	1	-127.280	127.280
293	1	-76.600	64.280
294	1	-84.260	70.710
295	1	-91.930	77.130
296	1	-99.590	83.560
297	1	-107.250	89.990
298	1	-114.910	96.420
299	1	-122.570	102.850
300	1	-130.230	109.270
301	1	-137.890	115.700
302	1	-81.920	57.360
303	1	-90.110	63.090
304	1	-98.300	68.830
305	1	-106.490	74.560
306	1	-114.680	80.300
307	1	-122.870	86.040
308	1	-131.060	91.770
309	1	-139.260	97.510
310	1	-147.450	103.240
311	1	-86.600	50.000
312	1	-95.260	55.000
313	1	-103.920	60.000
314	1	-112.580	65.000
315	1	-121.240	70.000
316	1	-129.900	75.000
317	1	-138.560	80.000
318	1	-147.220	85.000
319	1	-155.880	90.000
320	1	-90.630	42.260
321	1	-99.690	46.490
322	1	-108.760	50.710
323	1	-117.820	54.940
324	1	-126.880	59.170
325	1	-135.950	63.390
326	1	-145.010	67.620
327	1	-154.070	71.850
328	1	-163.140	76.070
329	1	-93.970	34.200
330	1	-103.370	37.620
331	1	-112.760	41.040
332	1	-122.160	44.460

33	1	-131.560	47.880
34	1	-140.950	51.300
35	1	-150.350	54.720
36	1	-159.750	58.140
37	1	-169.140	61.560
38	1	-96.590	25.880
39	1	-106.250	28.470
40	1	-115.910	31.060
41	1	-125.570	33.650
42	1	-135.230	36.230
43	1	-144.890	38.820
44	1	-154.550	41.410
45	1	-164.210	44.000
46	1	-173.870	46.590
47	1	-98.480	17.360
48	1	-108.330	19.100
49	1	-118.180	20.840
50	1	-128.030	22.570
51	1	-137.870	24.310
52	1	-147.720	26.050
53	1	-157.570	27.780
54	1	-167.420	29.520
55	1	-177.270	31.260
56	1	-99.620	8.720
57	1	-109.580	9.590
58	1	-119.540	10.460
59	1	-129.510	11.330
60	1	-139.470	12.200
61	1	-149.430	13.070
62	1	-159.390	13.940
63	1	-169.350	14.820
64	1	-174.000	16.000
65	1	-179.320	15.690
66	11	-100.000	0.000
67	11	-110.000	0.000
68	11	-120.000	0.000
69	11	-130.000	0.000
70	11	-140.000	0.000
71	11	-150.000	0.000
72	11	-160.000	0.000
73	11	-170.000	0.000
74	11	-175.000	0.000
75	1	-175.000	11.000
76	1	-179.830	7.850
77	111	-180.000	0.000
TERIAL		76MM RING(ST	
9000.		.32	79166.
ECIAL ELEMENTS		1	CRACK TIP
00011100011100011100011100011100011			
10	9	8	7 6 5 4
INT ELSTIF OFF			
INT STRESS OFF			
IAURIL	QUAD4	307	
11	1	2	12 1.00
12	2	3	13
13	3	4	14

13	3	4	14
14	4	5	15
5	6	16	15
6	7	17	16
7	8	18	17
8	9	19	18
9	10	20	19
21	11	12	22
22	12	13	23
23	13	14	24
14	15	25	24
15	16	26	25
16	17	27	26
17	18	28	27
18	19	29	28
19	20	30	29
31	21	22	32
32	22	23	33
33	23	24	34
24	25	35	34
25	26	36	35
26	27	37	36
27	28	38	37
28	29	39	38
29	30	40	39
33	34	42	41
34	35	43	42
35	36	44	43
36	37	45	44
37	38	46	45
38	39	47	46
39	40	48	47
41	42	50	49
42	43	51	50
43	44	52	51
44	45	53	52
45	46	54	53
46	47	55	54
47	48	56	55
50	51	58	57
51	52	59	58
52	53	60	59
53	54	61	60
54	55	62	61
55	56	63	62
64	65	96	95
65	66	97	96
66	67	98	97
67	68	86	98
68	69	85	96
69	70	84	85
70	71	83	84
71	72	82	83
72	73	80	82
73	74	79	80
74	75	78	79

82	87	88	83
83	88	89	84
84	89	90	85
85	90	100	86
90	93	102	101
92	94	93	89
93	94	103	102
95	96	105	104
96	97	106	105
97	98	107	106
98	99	108	107
99	100	109	108
100	101	110	109
101	102	111	110
102	103	112	111
104	105	114	113
105	106	115	114
106	107	116	115
107	108	117	116
108	109	118	117
109	110	119	118
110	111	120	119
111	112	121	120
113	114	123	122
114	115	124	123
115	116	125	124
116	117	126	125
117	118	127	126
118	119	128	127
119	120	129	128
120	121	130	129
122	123	132	131
123	124	133	132
124	125	134	133
125	126	135	134
126	127	136	135
127	128	137	136
128	129	138	137
129	130	139	138
131	132	141	140
132	133	142	141
133	134	143	142
134	135	144	143
135	136	145	144
136	137	146	145
137	138	147	146
138	139	148	147
140	141	150	149
141	142	151	150
142	143	152	151
143	144	153	152
144	145	154	153
145	146	155	154
146	147	156	155
147	148	157	156
149	150	159	158

150	151	160	159
151	152	161	160
152	153	162	161
153	154	163	162
154	155	164	163
155	156	165	164
156	157	166	165
158	159	168	167
159	160	169	168
160	161	170	169
161	162	171	170
162	163	172	171
163	164	173	172
164	165	174	173
165	166	175	174
167	168	177	176
168	169	178	177
169	170	179	178
170	171	180	179
171	172	181	180
172	173	182	181
173	174	183	182
174	175	184	183
176	177	186	185
177	178	187	186
178	179	188	187
179	180	189	188
180	181	190	189
181	182	191	190
182	183	192	191
183	184	193	192
185	186	195	194
186	187	196	195
187	188	197	196
188	189	198	197
189	190	199	198
190	191	200	199
191	192	201	200
192	193	202	201
194	195	204	203
195	196	205	204
196	197	206	205
197	198	207	206
198	199	208	207
199	200	209	208
200	201	210	209
201	202	211	210
203	204	213	212
204	205	214	213
205	206	215	214
206	207	216	215
207	208	217	216
208	209	218	217
209	210	219	218
210	211	220	219
212	213	222	221

213	214	223	222
214	215	224	223
215	216	225	224
216	217	226	225
217	218	227	226
218	219	228	227
219	220	229	228
221	222	231	230
222	223	232	231
223	224	233	232
224	225	234	233
225	226	235	234
226	227	236	235
227	228	237	236
228	229	238	237
230	231	240	239
231	232	241	240
232	233	242	241
233	234	243	242
234	235	244	243
235	236	245	244
236	237	246	245
237	238	247	246
239	240	249	248
240	241	250	249
241	242	251	250
242	243	252	251
243	244	253	252
244	245	254	253
245	246	255	254
246	247	256	255
248	249	258	257
249	250	259	258
250	251	260	259
251	252	261	260
252	253	262	261
253	254	263	262
254	255	264	263
255	256	265	264
257	258	267	266
258	259	268	267
259	260	269	268
260	261	270	269
261	262	271	270
262	263	272	271
263	264	273	272
264	265	274	273
266	267	276	275
267	268	277	276
268	269	278	277
269	270	279	278
270	271	280	279
271	272	281	280
272	273	282	281
273	274	283	282
275	276	285	284

276	277	286	285
277	278	287	286
278	279	288	287
279	280	289	288
280	281	290	289
281	282	291	290
282	283	292	291
284	285	294	293
285	286	295	294
286	287	296	295
287	288	297	296
288	289	298	297
289	290	299	298
290	291	300	299
291	292	301	300
293	294	303	302
294	295	304	303
295	296	305	304
296	297	306	305
297	298	307	306
298	299	308	307
299	300	309	308
300	301	310	309
302	303	312	311
303	304	313	312
304	305	314	313
305	306	315	314
306	307	316	315
307	308	317	316
308	309	318	317
309	310	319	318
311	312	321	320
312	313	322	321
313	314	323	322
314	315	324	323
315	316	325	324
316	317	326	325
317	318	327	326
318	319	328	327
320	321	330	329
321	322	331	330
322	323	332	331
323	324	333	332
324	325	334	333
325	326	335	334
326	327	336	335
327	328	337	336
329	330	339	338
330	331	340	339
331	332	341	340
332	333	342	341
333	334	343	342
334	335	344	343
335	336	345	344
336	337	346	345
338	339	348	347

339	340	349	348
340	341	350	349
341	342	351	350
342	343	352	351
343	344	353	352
344	345	354	353
345	346	355	354
347	348	357	356
348	349	358	357
349	350	359	358
350	351	360	359
351	352	361	360
352	353	362	361
353	354	363	362
354	355	365	364
356	357	367	366
357	358	368	367
358	359	369	368
359	360	370	369
360	361	371	370
361	362	372	371
362	363	373	372
363	375	374	373
364	365	376	375
375	376	377	374

1ANGLES	TRIM3	32
---------	-------	----

363	364	375
363	354	364
32	33	41
49	50	57
57	65	64
58	65	57
66	65	58
58	67	66
59	67	58
68	67	59
59	69	68
60	69	59
70	69	60
60	71	70
61	71	60
72	71	61
61	73	72
62	73	61
74	73	62
62	75	74
63	75	62
76	75	63
77	75	76
77	78	75
81	82	80
87	82	81
91	89	88
89	91	92
89	93	90
100	90	101

	99	86	100
	98	86	99
D STRUCTURE			
ADS		1	.1
1		100.0	
ADS		1	.77
77	-100.0		
ADS		1	11
11		100.0	
ADS		1	.21
21		100.0	
ADS		1	31
31		100.0	
D LOADS			

CDAIA

(APPENDIX_2)

10
209000.,0.32,1.,8.0
+.0.,.34906.,.69813,1.04719,1.3962,1.74532,2.09439,2.44345,2.79252,3.141590.
0.01
9
0.,0.,0.
1.,0.,0.
0.,1.,0.

BLOKK.CTL

(APPENDIX_3)

*514720
.R PIP
*DSK:DATA=DATA(3600,3613)
*DSK:/X=(3600,3613)ELSTIF.EXE
*DSK:/X=(3600,3613)STRESS.EXE
*DSK:CDAIA=(3600,3613)CDAIA
*DSK:/X=(3600,3613)ASSOLX.EXE,INPUTX.EXE
*DSK:/X=(3600,3613)CRACK3.EXE
.CHKPNT A1
A1:;.RU CRACK3
.CHKPNT A2
A2:;.RU INPUTX
.CHKPNT A3
A3:;.RU ELSTIF
.CHKPNT A4
A4:;.RU ASSOLX
.CHKPNT A5
A5:;.RU STRESS
.R PRINT
*DATA,CDAIA,PRINT1.LST/P(50),PRINT3.LST/P(400)
.R PRINT
*HELL
.DEL *.*

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

DOCUMENT CONTROL DATA SHEET

REPORT NO.
MRL-TN-549AR NO.
AR-005-679REPORT SECURITY CLASSIFICATION
Unclassified

TITLE

Stress intensity calibration of a ring specimen using a
finite element technique

AUTHOR(S)

G. Clark and
T.V. Rose

CORPORATE AUTHOR

Materials Research Laboratory
Defence Science & Technology Organisation
PO Box 50
Ascot Vale Victoria 3032REPORT DATE
January 1989TASK NO.
-SPONSOR
-FILE NO.
G6/4/8-3708REFERENCES
6PAGES
27

CLASSIFICATION/LIMITATION REVIEW DATE

CLASSIFICATION/RELEASE AUTHORITY
Chief, Materials Division MRL

SECONDARY DISTRIBUTION

Approved for public release

ANNOUNCEMENT

Announcement of this report is unlimited

KEYWORDS

Finite elements
Crack propagationStress analysis
Computer programsCalibrating
Elastic properties

SUBJECT GROUPS 0041K

ABSTRACT

A finite element technique has been used to determine the stress intensity at the tip of a bore crack in a cylindrical fracture specimen. This technical note describes the detailed input for the computer programs which perform the stress analyses. Much of the preparatory work involves generating a suitable mesh of elements which represents the elastic properties of the specimen. The constraints which are imposed on the mesh geometry are described.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED