

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

AD-A217 321

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1990	3. REPORT TYPE AND DATES COVERED presentation/paper	
4. TITLE AND SUBTITLE DEVELOPMENT OF A NEW FIELD STRENGTH MODEL FOR PROPHEX			5. FUNDING NUMBERS PE: 0602701A WU: DN088 607 PN: MP48	
6. AUTHOR(S) D. B. Sailors, J. R. Gnessin, and D. L. Lucas			8. PERFORMING ORGANIZATION REPORT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Ocean Systems Center San Diego, CA 92152-5000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Communications-Electronics Command Ft. Monmouth, NJ 07703			11. SUPPLEMENTARY NOTES	
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A new field strength model was developed for PROPHEX which was a significant departure from prior versions. Until recently, the model was based on that developed by the Deutsche Bundespost (Damboldt, T., NATO AGARD Conference Proc. - No. 173, 1975). In the new model, the Deutsche Bundespost model was replaced for paths shorter than 7000 km by a model relying on propagation via the regular E-layer and the F2-layer. The routine finds a lower order mode for the E-layer, F2-layer, and a mixed E-layer and F2-layer. Only one E-layer hop is considered in the mixed mode. The MUF model used is the NIMMUF-85 model (Sailors et al., NOSC TR 1121, July 1986). The E-layer MUF is calculated as in IONOCAP. The ionospheric absorption equation is the one used in IONOCAP with the near specular reflection losses calculated for E-layer modes at low frequencies. The over-the-MUF losses are calculated using the Phillips (Wheeler, J.L., Radio Sci., 1, 1303-1308, 1966) method for values of frequency/MUF ratio up to about 1.5 MHz depending on ground distance and with values greater being considered in the "scatter" region. The losses above these values are estimated as in IONOCAP. The value of the absorption index I at night has a value which is a function of solar activity (Wakii, J. Radio Res. Labs, Japan, 18, 191-208, May 1971). All the losses calculated are a function of geomagnetic latitude, length of path, time of day and season since the excess system loss tables of IONOCAP are used in the module along with the distribution of the MUFs. Using CCIR Data Base C, the new model's bias and rms error for frequencies less than the MUF are 1.1dB high and 13.5dB, respectively, and for frequencies above the MUF the bias and rms error were 2.7dB low and 15.8dB, respectively. The most pronounced improvement seems to be in the over-the-MUF loss which shows a much lower average residual from the previous method of about one-fifth and an rms residual of less than one-half. Published in <i>National Radio Science</i> , January 1990.				
14. SUBJECT TERMS propagation high frequency communication			15. NUMBER OF PAGES	
numerical modeling frequency management			16. PRICE CODE	
oblique sounds			17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	
18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT UNLIMITED

DTIC
ELECTE
JAN 30 1990
S B E D

