

4

TECHNICAL REPORT BRL-TR-3085

BRL

AD-A221 035

**FREE-FIELD STAGNATION PRESSURE AND
IMPULSE FROM A HIGH EXPLOSIVE DETONATION
IN A MODEL UNDERGROUND STORAGE FACILITY**

STEPHEN J. ZARDAS

APRIL 1990

NTIC
SERIAL
MAY 03 1990
S E D

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

**BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

90 05 02 061

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1990		3. REPORT TYPE AND DATES COVERED BRL Technical Report, from Oct 88 to Jan 89
4. TITLE AND SUBTITLE Free-Field Stagnation Pressure and Impulse From a High Explosive Detonation in a Model Underground Storage Facility			5. FUNDING NUMBERS PR: 4A66 580 5M87	
6. AUTHOR(S) Stephen J. Zardas				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Ballistic Research Laboratory ATTN: SLCBR-TB-B Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER BRL-TR-3085	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) DOD Explosives Safety Board 2461 Eisenhower Ave. Alexandria, VA 22331-0600			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES The assistance of Mr. Charles N. Kingery in providing project guidance, and Messrs Muller, Sunderland, Bernhardt and Peterson in conducting the model tests is gratefully acknowledged.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Results are presented from high-explosive (PETN) model tests conducted to determine free-field stagnation pressures and impulses produced by simulated underground chamber/tunnel explosions. The model consisted of a 1:50 scale, smooth, chamber/tunnel configuration with a converging area change. Internal side-on pressures and external side-on and stagnation pressures were measured as a function of chamber-charge loading density and external test-bed type (i.e., sand or plywood). Results of the tests indicate that the ratio of stagnation pressure to side-on pressure is dependent on terrain at the tunnel exit.				
14. SUBJECT TERMS Airblast/Overpressure; Munition Storage; Blast Waves; Stagnation Pressure; Underground Storage; Stagnation Impulse.			15. NUMBER OF PAGES 70	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

UNCLASSIFIED

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (NTIS only).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

CONTENTS

Page

LIST OF FIGURES	v
LIST OF TABLES	v
1 INTRODUCTION	1
1.1 Background.	1
1.2 Objectives.	1
2 TEST PROCEDURES	1
2.1 Test model.	1
2.2 Instrumentation.	8
3 RESULTS AND DISCUSSION	8
4 SUMMARY, CONCLUSIONS, AND RECOMMENDATIONS	14
5 REFERENCES	18
APPENDIX A: PRESSURE-TIME AND IMPULSE-TIME RECORDS	19
DISTRIBUTION LIST	59

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Chamber/tunnel configuration	3
2. View of model chamber/tunnel	4
3. Transducer mounted in ground baffle along a blast line	5
4. View of test site showing 0- and 45-degree blast lines	6
5. Centering device for detonating cord	7
6. Schematic of data acquisition-reduction system	9
7. Sand disturbance at model exit, shot 2	10
8. Sand disturbance at model exit, shot 3	11
9. Post-shot photograph of shot 4	15
10. Pressure ratio versus distance ratio on 0-degree line outside tunnel	16
A-1. Shot 1, chamber-loading density 0.681 kg/m ³ , sand base	21
A-2. Shot 2, chamber-loading density 0.681 kg/m ³ , sand base	30
A-3. Shot 3, chamber-loading density 1.46 kg/m ³ , sand base	39
A-4. Shot 4, chamber-loading density 1.46 kg/m ³ , plywood base	48
A-5. Shot 5, chamber-loading density 1.46 kg/m ³ , plywood base	57

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Gage Locations.	2
2. Shot Matrix.	2
3. Overpressure Comparison.	12
4. Comparison of Side-on and Stagnation Impulses.	13

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

1.1 Background. The Department of Defense Explosive Safety Board (DDESB) has a need for the characterization of airblast hazards for use in determining quantity-distance (Q-D) standards for ordnance. This research effort addresses the approximate Q-D standards to be applied when munitions, stored underground, explode. A previous effort by BRL¹ in this area characterized the external side-on blast pressures from such explosions. However, it was noted that external stagnation pressures along the tunnel axis may considerably exceed the side-on pressures due to the high velocity of the jet flow exiting the tunnel.

Also, small-scale, shock-tube tests² showed that external stagnation pressures could be much higher than comparable side-on pressures. These high stagnation pressures, if produced by accidental detonation of underground storage facilities, could result in Q-D standards that are less than required.

1.2 Objectives. The objective of this effort, sponsored by DDESB, is to conduct scale-model tunnel tests to determine stagnation pressures relative to side-on pressures in the free field.

2. TEST PROCEDURES

A smooth-walled steel pipe chamber/tunnel model of 1:50 scale was operated with detonating cord as described in the following sections.

2.1 Test model. The test model used is shown in Figure 1. Pressure transducers were mounted in the chamber wall to record the reflected and quasi-static pressure in the chamber. A transducer was also placed near the exit end of the tunnel to record the side-on exit pressure. Transducers were also mounted in lead bricks along blast radials located at 0° and 45° from the tunnel exit to record both side-on and stagnation pressures. Figure 2 is a photograph of the model. Figure 3 shows the transducers mounted in ground baffles along the blast line. Ground distances for the transducer stations were chosen to record equal pressures on both blast lines at corresponding stations and are presented in Table 1. A photograph of the test site is shown in Figure 4. The detonating cord was cut in lengths, bundled, and placed in a cardboard tube, Figure 5, then centered in the chamber to give the desired loading density, as shown in Table 2.

This corresponds to a distributed storage of munitions in the chamber of an underground storage facility. Detonation was initiated at the closed-chamber end by a Type 2023 detonator. In tests 1 and 2 the charges were 0.0634 kg of PETN, and in tests 3, 4, and 5, the charge was 0.136 kg of PETN.

TABLE 1. Gage Locations.

Station	<u>Distance from tunnel exit to gage, m</u>	
	Shots 1 & 2	Shots 3, 4, & 5 ^a
0-1	1.00	1.2
0-2	1.53	2.43
0-3	2.61	4.17
0-4	4.89	7.80
45-1	0.80	0.90
45-2	1.06	1.68
45-3	1.81	2.88
45-4	3.38	5.39

^a45-degree blast line not used in shots 4 and 5.

Table 2. Shot Matrix.

Shot No.	Charge ^a weight, kg	Chamber-loading density, kg/m ³	Test base
1	0.0634	0.681	Sand
2	0.0634	0.681	Sand
3	0.136	1.46	Sand
4	0.136	1.46	Plywood
5	0.136	1.46	Plywood

^a Explosive used was 0.0106 kg/m PETN detonating cord.


CHAMBER/TUNNEL PARAMETERS

TUNNEL AREA/CHAMBER AREA 0.16

CHAMBER VOLUME 0.0932 m³

TUNNEL VOLUME 0.0208 m³

TOTAL VOLUME 0.114 m³



* FOUR STATIONS ON EACH LINE
COVERING RANGES WHERE HEAVY
DAMAGE TO INHABITED BUILDINGS
WILL OCCUR

Figure 1. Chamber/tunnel configuration.




Figure 2. View of model chamber/tunnel.




Figure 3. Transducer mounted in ground baffle along a blast line.



Figure 4. View of test site showing 0- and 45-degree blast lines.




Figure 5. Centering device for detonating cord.

2.2 Instrumentation: The data acquisition-reduction system is shown in Figure 6.

3. RESULTS AND DISCUSSION

Figures 7 and 8 show post shot photographs of the disturbance of the sand test-bed surface from shots 2 and 3. There was some cratering near the exit and enough soot from the explosion to mark a path along the 0-degree line. The 45-degree line was essentially free from soot.

Appendix A presents pressure-time records from the chamber, tunnel, and each station of the blast lines. At station C-1, in the chamber, the records show that large blast reflections are produced at charge detonation. Then the pressure builds to some average quasi-static value and decays by exhausting into the tunnel and out the exit.

Blast wave propagation can be seen by comparing the records from each station on each blast line. Large, double-peaked waveforms are seen along the 0-degree line, but not on the 45-degree line. Whether or not the peaks catch up determines the maximum pressure at a given station.

The test model configuration was not varied during the shots; however, to maintain the predicted pressure levels of 68.95 kPa at station 1, 24.13 kPa at station 2, 11.72 kPa at station 3, and 5.00 kPa at station 4, the transducers were moved based on charge weight. Locations of chamber and tunnel transducers are shown in Figure 1.

Table 3 compares the peak side-on and stagnation pressures from the tests. In some instances multiple values of pressure were obtained, which are listed to show the extra peaks. Also, the experimental environment in the chamber was quite severe and few data were obtained there. Table 4 compares the external side-on and stagnation impulses.

Initially, it was expected, from the tests in the small-scale shock tube,² that the peak stagnation overpressures for shots 1 and 2 would be approximately 7 to 8 times the peak side-on overpressures at comparable gage locations along the 0-degree axis, and for shot 3, approximately 11 to 12 times greater. As shown in Table 3, stagnation overpressures were much lower than expected for shots 1 and 2 and even lower for shot 3.




Figure 6. Schematic of data acquisition-reduction system.



Figure 7. Sand disturbance at model exit, shot 2.



Figure 8. Sand disturbance at model exit, shot 3.

TABLE 3. Overpressure Comparison.

Pressure, kPa										
Station	Shot 1		Shot 2		Shot 3		Shot 4		Shot 5	
	Side-on	Stagnation	Side-on	Stagnation	Side-on	Stagnation	Side-on	Stagnation	Side-on	Stagnation
C-1	700	-	1,400	-	-	-	-	-	-	-
T-1	650	-	750	-	990	-	900	-	1,150	-
0-1	58	130/230	100	114/114	85	62	75	75/395	83	75/390
0-2	33	37	33	36	19/24	18	19/31	40/150	27/40	22/131
0-3	12	24	12	17	9.7	11	10/15	20/24	10/11	20/28
0-4	4.3	4	4.3	5.7	3.3	4.3	3.9	4.1	4.5	4.9
45-1	75	163	66	140	66	120	--	Not measured	--	--
45-2	33	44	31	47	27	33	--	Not measured	--	--
45-3	16	-	17	-	9.7	8.8	--	Not measured	--	--
45-4	5.8	11	5.5	11	3.3	5.0	--	Not measured	--	--

TABLE 4. Comparison of Side-on and Stagnation Impulses.

Impulse, kPa-msec											
Station	Shot 1		Shot 2		Shot 3		Shot 4		Shot 5		
	Side-on	Stagnation	Side-on	Stagnation	Side-on	Stagnation	Side-on	Stagnation	Side-on	Stagnation	
0-1	38	255	45	118	57	59	75	7,200	84	6,300	
0-2	39	52	39	78	36	58	74	1,640	77	1,150	
0-3	17	20	24	30	19	22	67	165	78	90	
0-4	5.6	5.6	4.8	6.3	7.7	7.8	15	16	17	18	
45-1	14	35	12	27	18	32			-- Not measured --		
45-2	11	13	11	13	17	22			-- Not measured --		
45-3	6.6	-	6.0	-	14	7.7			-- Not measured --		
45-4	3.8	4.5	3.0	3.9	7.3	8.5			-- Not measured --		

All possible variables and results of the tests were examined to determine the cause of this apparent anomaly. This examination indicated that the cause could be the type of material used in the model test bed. In the shock-tube tests plywood was used, whereas sand was used in the model tests. As shown in Figures 7 and 8, the sand at the exit of the model was somewhat disturbed in shots 1 and 2, and more noticeably disturbed in shot 3. From this, it was assumed that the shock wave disturbed the sand, which, in turn, interfered with the following high-speed jet flow from the tunnel.

A plywood sheet was placed, as shown in Figure 9, at the tunnel exit for shots 4 and 5. Also, 25.4-mm-diameter copper tubing, used in tests 1, 2, and 3 to deflect sand from the stagnation pick-up tubes, was not used in shots 4 and 5. As shown in Table 3, these measures proved fruitful: stagnation pressures from shots 4 and 5 were approximately four to five times the side-on pressures at stations 0-1 and 0-2. Also, stagnation pressure impulses were much greater than side-on values at stations 0-1, 0-2, and 0-3 for shots 4 and 5 as shown on Table 4 and Figures A-4 and A-5.

The free-field blast pressure can be predicted using a method described in Reference 1. In Figure 10, the solid line is the predicted value for the conditions of these tests and is plotted as the ratio of free-field blast pressure to tunnel-exit pressure ($\Delta P/P_w$) versus the ratio of radial distance to tunnel diameter (R/D_T). The measured data for the five shots are generally higher than predicted and are comparable with the results of Reference 1 which states that, under these conditions, a variation in free-field pressure of a factor of two may be expected.

4. SUMMARY, CONCLUSIONS, AND RECOMMENDATIONS

Results of tests to determine the free-field stagnation overpressures from explosions in a model storage chamber have been presented. Pressure-time records were obtained for stagnation and side-on overpressures on 0- and 45-degree radials as measured from the longitudinal axis of the tunnel, taken as 0 degrees. For shots 1 and 2, the measured stagnation pressures were somewhat lower than expected, and much lower for shot 3. Analysis indicated that the shock wave at the tunnel exit disturbed the sand test bed to the extent that the sand, in turn, interfered with the following high-speed flow. In shots 4 and 5 plywood was used at the tunnel exit and resultant stagnation overpressures were more nearly as expected.





Figure 9. Post-shot photograph of shot 4.



From these minimum number of tests, it appears that the stagnation-to-side-on overpressure ratio is terrain dependent. However, the affect on stagnation pressure of removing the copper tubing sand deflectors is not known.

It is suggested that studies be continued to more adequately define the effect of sand and plywood and to determine the effects of different types of terrain features.

5. REFERENCES

1. Culter, G. A., G. Bulmash, and C. N. Kingery. "Simulation Techniques for the Prediction of Blast from Underground Munitions Storage Facilities." BRL-MR-3659, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, April 1988.
2. Kingery, C. N., and E. J. Gion. "Jet-Flow from Shock Tubes." BRL-TR-3015, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1989.

APPENDIX A:

PRESSURE-TIME AND IMPULSE-TIME RECORDS

INTENTIONALLY LEFT BLANK.





Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.






Figure A-1. Shot 1. chamber-loading density 0.681 kg/m^3 . sand base.



STATION 45-3 ST CURVE NOT AVAILABLE.

Figure A-1. Shot 1, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-1. Shot 1. chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-2. Shot 2. chamber-loading density 0.681 kg/m^3 , sand base.





Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.






Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.

Test: DDESB UNDERGROUND STOR
Exp: 2
Station: 45-2 SO



Test: DDESB UNDERGROUND STOR
Exp: 2
Station: 45-2 ST





Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.



STATION 45-3 ST CURVE IS NOT AVAILABLE.

Figure A-2. Shot 2, chamber-loading density 0.681 kg/m³, sand base.





Figure A-2. Shot 2, chamber-loading density 0.681 kg/m^3 , sand base.

STATION C-1 CURVE IS NOT AVAILABLE.




Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3. chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.





Figure A-3. Shot 3, chamber-loading density 1.46 kg/m^3 , sand base.

STATION C-1 CURVE IS NOT AVAILABLE.




Figure A-4. Shot 4, chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-4. Shot 4. chamber-loading density 1.46 kg/m^3 . plywood base.





Figure A-4. Shot 4, chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-4. Shot 4, chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-4. Shot 4, chamber-loading density 1.46 kg/m^3 , plywood base.

STATION C-1 CURVE IS NOT AVAILABLE.




Figure A-5. Shot 5, chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-5. Shot 5. chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-5. Shot 5, chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-5. Shot 5. chamber-loading density 1.46 kg/m^3 , plywood base.





Figure A-5. Shot 5, chamber-loading density 1.46 kg/m^3 , plywood base.

INTENTIONALLY LEFT BLANK.

No of Copies	Organization
1	Office of the Secretary of Defense OUSD(A) Director, Live Fire Testing ATTN: James F. O'Bryon Washington, DC 20301-3110
(Unclass., unlimited) 12	Administrator
(Unclass., limited) 2	Defense Technical Info Center
(Classified) 2	ATTN: DTIC-LDA Cameron Station Alexandria, VA 22304-6145
1	HQDA (SARD-TR) WASH DC 20310-0001
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001
1	Commander US Army Laboratory Command ATTN: AMSLC-DL Adelphi, MD 20783-1145
2	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-MSI Picatinny Arsenal, NJ 07806-5000
2	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000
1	Director Benet Weapons Laboratory Armament RD&E Center US Army AMCCOM ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-5000
1	Commander US Army Aviation Systems Command ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798

No of Copies	Organization
1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099
1	Commander US Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander US Army Tank-Automotive Command ATTN: AMSTA-TSL (Technical Library) Warren, MI 48397-5000
1	Director US Army TRADOC Analysis Command ATTN: ATAA-SL White Sands Missile Range, NM 88002-5502
(Class. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
(Unclass. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000 <u>Aberdeen Proving Ground</u>
2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	Cdr, USATECOM ATTN: AMSTE-TO-F
3	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI
1	Dir, VLAMO ATTN: AMSLC-VL-D

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Office Secretary of Defense ADUSDRE (R/AT) (ET) ATTN: Mr. J. Persh, Staff Specialist Materials and Structures Washington, DC 20301	1	HQDA (DAEN-ECE-T, Mr. R. L. Wright) WASH DC 20310
1	Under Secretary of Defense for Research and Engineering Department of Defense Washington, DC 20301	1	HQDA (DAEN-MCC-D, Mr. L. Foley) WASH DC 20310
1	Director of Defense Research and Engineering Washington, DC 20301	1	HQDA (DAEN-RDL, Mr. Simonini) WASH DC 20310
1	Assistant Secretary of Defense (Atomic Energy) ATTN: Document Control Washington, DC 20301	1	HQDA (DAEN-RDZ-A, Dr. Choromokos) WASH DC 20310
1	Assistant Secretary of Defense (MRA&L) ATTN: EO&SP Washington, DC 20301	1	HQDA (DALO-SMA, COL W. F. Paris II) WASH DC 20310
1	Director Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209	1	HQDA (DAPE-HRS) WASH DC 20310
1	Director Defense Intelligence Agency ATTN: DT-1B, Dr. J. Vorona Washington, DC 20301	3	Director Institute for Defense Analyses ATTN: Dr. H. Menkes Dr. J. Bengston Tech Info Ofc 1801 Beauregard St. Alexandria, VA 22311
2	Chairman Joint Chiefs of Staff ATTN: J-3, Operations J-5, Plans & Policy (R&D Division) Washington, DC 20301	1	Director US Army Ballistic Missile Defense Systems Command Advanced Technology Center ATTN: M. Whitfield P. O. Box 1500, West Station Huntsville, AL 35807
4	Director Defense Nuclear Agency ATTN: SPTD, Mr. T. E. Kennedy DDST (E), Dr. E. Sevin OALG, Mr. T. P. Jeffers LEEE, Mr. J. Eddy Washington, DC 20305	2	Director US Army Engineer Waterways Experimental Station ATTN: WESNP K. Davis P. O. Box 631 Vicksburg, MS 39180-0631
1	Chairman Department of Defense Explosives Safety Board 2461 Eisenhower Avenue Alexandria, VA 22331	1	Commander US Army Materiel Command ATTN: AMCSF 5001 Eisenhower Avenue Alexandria, VA 22333-0001

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Commander HQ AMCCOM ATTN: AMSMC-IS Rock Island, IL 61299-6000	1	Director US Army Missile and Space Intelligence Center ATTN: AIAMS-YDL Redstone Arsenal, AL 35898-5500
1	Commander US Army Armament, Munitions and Chemical Command ATTN: AMSMC-IMP-L Rock Island, IL 61299-7300	1	Commander US Army Natick Research and Development Laboratories ATTN: AMDNA-D, Dr. D. Seiling Natick, MA 01760
1	Commander Pine Bluff Arsenal Pine Bluff, AR 71601	1	US Army Engineer Division ATTN: Mr. Char P. O. Box 1600 Huntsville, AL 35807
1	Commander US Army Rock Island Arsenal Rock Island, IL 61299	1	Commandant US Army Engineer School ATTN: ATSE-CD Fort Leonard Wood, MO 65473-6620
1	Commanding General US Army Armament Command ATTN: AMSAR-SA Rock Island Arsenal Rock Island, IL 61201	1	Commander Dugway Proving Ground ATTN: STEDP-TO-H, Mr. Miller Dugway, UT 84022
1	Commander US Army Aviation Systems Command ATTN: AMSAV-ES 4300 Goodfellow Blvd. St. Louis, MO 63120-1798	1	Commander Naval Weapons Center ATTN: Code 62C2, Mr. G. Ostermann China Lake, CA 93555-6001
2	Director Lewis Directorate US Army Air Mobility Research and Development Laboratory Lewis Research Center ATTN: Mail Stop 77-5 21000 Brookpark Road Cleveland, OH 441351	1	Commander US Army Materials Technology Laboratory ATTN: SLCMT-ATL Watertown, MA 02172-0001
1	Commander, USACECOM R&D Technical Library ATTN: ASQNC-ELC-I-T, Myer Center Fort Monmouth, NJ 07703-5301	1	Air Force Armament Laboratory ATTN: AFATL/DOIL (Technical Information Center) Eglin AFB, FL 32542-5438
1	Commander US Army Harry Diamond Laboratories ATTN: SLCHD-TI 2800 Powder Mill Road Adelphi, MD 20783-1197	2	Commander Naval Surface Warfare Center White Oak Laboratory ATTN: R-15, Mr. M. M. Swisdak Mr. W. D. Smith III Silver Spring, MD 20902-5000
1	Commander US Army Foreign Science and Technology Center ATTN: Research & Data Branch Federal Office Building 220-7th Street, NE Charlottesville, VA 22901	1	Commander US Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709-2211

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander Naval Weapons Evaluation Facility ATTN: Document Control Kirtland AFB, NM 87117	3	AFML (LNN, Dr. T. Nicholas; MAS; MBC, Mr. D. Schmidt) Wright-Patterson AFB, OH 45433
1	Commander Naval Research Laboratory ATTN: Code 2027, Tech Lib Washington, DC 20375	1	Headquarters Department of Energy Office of Military Application Washington, DC 20545
1	Air Force Systems Command ATTN: IFGF Andrews AFB Washington, DC 20334	1	Mr. Richard W. Watson Director, Pittsburgh Mining & Safety Research Center Bureau of Mine, Dept. of the Interior 4800 Forbes Avenue Pittsburgh, PA 15213
3	Commander US Army Belvoir Research and Development Center ATTN: STRBE-NN Fort Belvoir, VA 22060-5606	12	Director Lawrence Livermore Laboratory Technical Information Division P. O. Box 808 Livermore, CA 94550
1	Assistant Secretary of the Navy (Research and Development) Navy Development Washington, DC 20350	1	Director Los Alamos Scientific Laboratory ATTN: Dr. J. Taylor P. O. Box 1663 Los Alamos, NM 875441
2	Director Sandia National Laboratories ATTN: Info Dist Div Dr. W. A. von Riesemann (Div 6442) Albuquerque, NM 87115	1	Aeronautical Research Associates of Princeton, Inc. ATTN: Dr. C. Donaldson 50 Washington Road P. O. Box 2229 Princeton, NJ 08540
1	Applied Research Associates, Inc. ATTN: Mr. John Keefer 30 Diamond St. P. O. Box 548 Aberdeen, MD 21001	1	Director National Aeronautics and Space Administration George C. Marshall Space Flight Center Huntsville, AL 35812
1	Agbabian Associates ATTN: Dr. D. P. Reddy 250 N. Nash Street El Segundo, CA 90245	1	Director National Aeronautics and Space Administration Scientific and Technical Information Facility P. O. Box 8757 Baltimore/Washington International Airport MD 21240
1	Ammann and Whitney ATTN: Mr. N. Dobbs Suite 1700 Two World Trade Center New York, NY 10048	1	National Academy of Science ATTN: Mr. D. G. Groves 2101 Constitution Avenue, NW Washington, DC 20418
1	Black and Veatch, Engineers-Architects ATTN: Mr. H. D. Laverentz 1500 Meadow Lake Parkway Kansas City, MO 64114		

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
10	Central Intelligence Agency OIR/DB/Standard GE47 HQ Washington, DC 20505	1	Physics International 2700 Merced Street San Leandro, CA 94577
1	DNA Information and Analysis Center Kaman Tempo ATTN: DASOAC 816 State Street P. O. Drawer QQ Santa Barbara, CA 93102	1	R&D Associates ATTN: G. P. Ganong P. O. Box 9377 Albuquerque, NM 87119
1	Science Applications, Inc. Division 164, MST-3-2 1710 Goodridge Drive McLean, VA 22102	2	The Boeing Company Aerospace Division ATTN: Dr. Peter Grafton Dr. D. Strome Mail Stop 8C-68 P. O. Box 3707 Seattle, WA 98124
2	Battelle Memorial Institute ATTN: Dr. L. E. Hulbert Mr. J. E. Backofen, Jr. 505 King Avenue Columbus, OH 43201	1	General American Transportation Corp. General American Research Div. ATTN: Dr. J. C. Shang 7449 N. Natchez Avenue Niles, IL 60648
1	Georgia Institute of Technology ATTN: Dr. S. Atluri 225 North Avenue, NW Atlanta, GA 30332	1	Lovelace Research Institute ATTN: Dr. E. R. Fletcher P. O. Box 5890 Albuquerque, NM 87115
1	IIT Research Institute ATTN: Mrs. H. Napadensky 10 West 35 Street Chicago, IL 60616		<u>Aberdeen Proving Ground</u>
2	AVCO Corporation Structures and Mechanics Dept. ATTN: Dr. William Broding Dr. J. Gilmore 201 Lowell Street Wilmington, MA 01887	1	Cdr, USATECOM ATTN: AMSTE-SI-F
1	Aerospace Corporation P. O. Box 92957 Los Angeles, CA 90009	1	Cdr, US Army Toxic and Hazardous Materials Agency ATTN: AMXTH-TE
1	Dr. Wilfred E. Baker Wilfred Baker Engineering P. O. Box 6477 San Antonio, TX 78209		
1	J. G. Engineering Research Associates 3831 Menlo Drive Baltimore, MD 21215		
1	McDonnell Douglas Aeronautics Western Division ATTN: Dr. Lea Cohen 5301 Bosla Avenue Huntington Beach, CA 92647		

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number BRL-TR-3085 Date of Report APRIL 1990

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Name

Organization

Address

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD
ADDRESS

Name

Organization

Address

City, State, Zip Code

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

-----FOLD HERE-----

DEPARTMENT OF THE ARMY

Director

U.S. Army Ballistic Research Laboratory

ATTN: SLCBR-DD-T

Aberdeen Proving Ground, MD 21005-5066

OFFICIAL BUSINESS



**NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES**

BUSINESS REPLY MAIL

FIRST CLASS PERMIT No 0001, APG, MD

POSTAGE WILL BE PAID BY ADDRESSEE

Director

U.S. Army Ballistic Research Laboratory

ATTN: SLCBR-DD-T

Aberdeen Proving Ground, MD 21005-9989

-----FOLD HERE-----