

NAVAL POSTGRADUATE SCHOOL

Monterey, California

AD-A223 296



THESIS

FURTHER STUDIES OF TURBULENCE STRUCTURE
RESULTING FROM INTERACTIONS BETWEEN
EMBEDDED VORTICES AND WALL JETS
AT HIGH BLOWING RATIOS

by

William D. Doner

December 1989

Thesis Co-Advisors: Chelakara S. Subramanian
Phillip M. Ligrani

Approved for public release; distribution is unlimited

DTIC
ELECTE
JUN 27 1990
S B D

90 06 27 06L

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
4. PERFORMING ORGANIZATION REPORT NUMBER(S)			7a. NAME OF MONITORING ORGANIZATION Naval Postgraduate School		
6a. NAME OF PERFORMING ORGANIZATION Naval Postgraduate School		6b. OFFICE SYMBOL (If applicable) Code 69		7b. ADDRESS (City, State, and ZIP Code) Monterey, California 93943-5000	
6c. ADDRESS (City, State, and ZIP Code) Monterey, California 93943-5000		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
8a. NAME OF FUNDING/SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)		10. SOURCE OF FUNDING NUMBERS	
8c. ADDRESS (City, State, and ZIP Code)		PROGRAM ELEMENT NO		TASK NO	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) FURTHER STUDIES OF TURBULENCE STRUCTURE RESULTING FROM INTERACTIONS BETWEEN EMBEDDED VORTICES AND WALL JETS AT HIGH BLOWING RATIOS					
12. PERSONAL AUTHOR(S) Doner, William D.					
13a. TYPE OF REPORT Master's Thesis		13b. TIME COVERED FROM _____ TO _____		15. PAGE COUNT 292	
14. DATE OF REPORT (Year, Month, Day) 1989, December					
16. SUPPLEMENTARY NOTATION The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Turbulence Structure; Embedded Vortices and Wall Jets		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
Interactions of wall jets and vortices embedded in turbulent layers commonly occur near gas turbine blades and endwalls where film cooling is employed. These interactions frequently result in undesirable heat transfer effects at blade and endwall surfaces. In this study, a crossed hot-wire probe is used to measure the turbulence structure resulting from this type of interaction. The vortex is generated using a half delta-wing vortex generator mounted at 12 degrees with respect to a 10 m/s mean velocity flow over a flat plate. A single injection hole, 0.95 cm in diameter, inclined 30 degrees to the horizontal, is positioned 59.3 cm downstream of the vortex generator. The vortex generator is positioned so that vortex upwash or downwash could be located over the injection hole. Streamwise					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Prof. Chelakara S. Subramanian			22b. TELEPHONE (Include Area Code) (408) 646-2588		22c. OFFICE SYMBOL Code 69Su

DD Form 1473, JUN 86

Previous editions are obsolete

S/N 0102-LF-014-6603

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

#19 - ABSTRACT - (CONTINUED)

development of the turbulent boundary layer was investigated for the following cases: (1) boundary layer with jet only ($m = 1.5$), and (2) boundary layer with vortex only. Measurement of interaction between the boundary layer, vortex upwash, and the wall jet was made at one station with various blowing ratios.

At low blowing ratios ($m = 0.5$ and 1.5) the vortex dominates the flow. Significant alterations to the turbulent structure are seen in the Reynolds stress components, vorticity distributions and mean velocities. At higher blowing ratios ($m = 2.5$ and 3.5) the jet dominates the flow, the vortex is blown away from the wall, and its turbulence effects are dispersed over a larger area.



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

Approved for public release; distribution is unlimited

Further Studies of Turbulence Structure Resulting from
Interactions Between Embedded Vortices and Wall Jets
at High Blowing Ratios

by

William D. Doner
Lieutenant, United States Navy
B.S.CEM, Oregon State University, 1980

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN MECHANICAL ENGINEERING


from the

NAVAL POSTGRADUATE SCHOOL
December 1989


Author:


William D. Doner

Approved by:


Chelakara S. Subramanian, Thesis Co-Advisor


Phillip M. Ligrani, Thesis Co-Advisor


Anthony J. Healey, Chairman
Department of Mechanical Engineering

ABSTRACT

Interactions of wall jets and vortices embedded in turbulent layers commonly occur near gas turbine blades and endwalls where film cooling is employed. These interactions frequently result in undesirable heat transfer effects at blade and endwall surfaces. In this study, a crossed hot-wire probe is used to measure the turbulence structure resulting from this type of interaction.

The vortex is generated using a half delta-wing vortex generator mounted at 12 degrees with respect to a 10 m/s mean velocity flow over a flat plate. A single injection hole, 0.95 cm in diameter, inclined 30 degrees to the horizontal, is positioned 59.3 cm downstream of the vortex generator. The vortex generator is positioned so that vortex upwash or downwash could be located over the injection hole. Streamwise development of the turbulent boundary layer was investigated for the following cases: (1) boundary layer with jet only ($m = 1.5$), and (2) boundary layer with vortex only. Measurement of interaction between the boundary layer, vortex upwash, and the wall jet was made at one station with various blowing ratios.

At low blowing ratios ($m = 0.5$ and 1.5) the vortex dominates the flow. Significant alterations to the turbulent structure are seen in the Reynolds stress components,

vorticity distributions and mean velocities. At higher blowing ratios ($m = 2.5$ and 3.5) the jet dominates the flow, the vortex is blown away from the wall, and its turbulence effects are dispersed over a larger area. *See eq. (2.5) - 5*

TABLE OF CONTENTS

I.	INTRODUCTION -----	1
	A. BACKGROUND -----	1
	B. OBJECTIVES -----	3
	C. EXPERIMENTAL APPROACH -----	4
	D. THESIS OUTLINE -----	5
II.	EXPERIMENTAL APPARATUS -----	6
	A. WIND TUNNEL AND TEST SECTION -----	6
	B. VORTEX GENERATOR -----	7
	C. INJECTION SYSTEM -----	7
III.	HOT-WIRE ANEMOMETER AND DATA ACQUISITION SYSTEM -----	8
	A. CROSSED HOT-WIRE SYSTEM -----	8
	B. DATA ACQUISITION SYSTEM -----	9
	C. CALIBRATION -----	11
	D. MICROCOMPUTER -----	14
IV.	EXPERIMENTAL RESULTS -----	19
	A. CALCULATIONS -----	19
	B. SURVEY CONDITIONS AND PARAMETERS -----	20
	C. BASELINE DATA -----	20
	D. BOUNDARY LAYER/VORTEX/WALL JET INTERACTIONS -----	26
V.	SUMMARY AND CONCLUSIONS -----	29
	APPENDIX A: SOFTWARE DIRECTORY -----	31
	APPENDIX B: DATA FILE DIRECTORY -----	33

APPENDIX C: FIGURES -----	34
LIST OF REFERENCES -----	263
BIBLIOGRAPHY -----	265
INITIAL DISTRIBUTION LIST -----	266

LIST OF TABLES

1. SUMMARY OF SURVEY CONDITIONS AND PARAMETERS -----	21
2. LOCATION OF CORE CENTER AND SIZE IN BOUNDARY LAYER WITH VORTEX ONLY -----	25
3. CORE RADIUS, CIRCULATION AND STREAMWISE VORTICITY OF BOUNDARY LAYER WITH VORTEX UPWASH ABOVE JET ---	28

LIST OF FIGURES

1.	Test Section Schematic -----	34
2.	Vortex Generator -----	35
3.	Vortex Generator Downwash Placement -----	36
4.	Vortex Generator Upwash Placement -----	37
5.	Data Acquisition System -----	38
6.	$\bar{u}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	39
7.	$\bar{v}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	40
8.	$\bar{w}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	41
9.	$\overline{u'^2}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	42
10.	$\overline{v'^2}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	43
11.	$\overline{w'^2}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	44
12.	$\overline{u'v'}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	45
13.	$\overline{u'w'}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	46
14.	$\overline{u'^3}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	47
15.	$\overline{v'^3}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	48
16.	$\overline{w'^3}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	49
17.	$\overline{u'^2v'}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$) -----	50

18.	$\overline{u'v'^2}$ (Boundary Layer, Station A', m = 1.5, $\Delta = 0.25$) -----	51
19.	$\overline{u'^2w'}$ (Boundary Layer, Station A', m = 1.5, $\Delta = 0.25$) -----	52
20.	$\overline{u'w'^2}$ (Boundary Layer, Station A', m = 1.5, $\Delta = 0.25$) -----	53
21.	Streamwise Vorticity (Boundary Layer, Station A', m = 1.5, $\Delta = 0.25$) -----	54
22.	$\overline{u}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	55
23.	$\overline{v}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	56
24.	$\overline{w}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	57
25.	$\overline{u'^2}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	58
26.	$\overline{v'^2}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	59
27.	$\overline{w'^2}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	60
28.	$\overline{u'v'}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	61
29.	$\overline{u'w'}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	62
30.	$\overline{u'^3}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	63
31.	$\overline{v'^3}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	64
32.	$\overline{w'^3}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	65
33.	$\overline{u'^2v'}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	66
34.	$\overline{u'v'^2}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	67

35.	$\overline{u'^2 w'}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	68
36.	$\overline{u' w'^2}$ (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	69
37.	Streamwise Vorticity (Boundary Layer, Station A'', m = 1.5, $\Delta = 0.25$) -----	70
38.	$\overline{u}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	71
39.	$\overline{v}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	72
40.	$\overline{w}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	73
41.	$\overline{u'^2}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	74
42.	$\overline{v'^2}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	75
43.	$\overline{w'^2}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	76
44.	$\overline{u' v'}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	77
45.	$\overline{u' w'}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	78
46.	$\overline{u'^3}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	79
47.	$\overline{v'^3}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	80
48.	$\overline{w'^3}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	81
49.	$\overline{u'^2 v'}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	82
50.	$\overline{u' v'^2}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	83
51.	$\overline{u'^2 w'}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	84

52.	$\overline{u'w'^2}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	85
53.	Streamwise Vorticity (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$) -----	86
54.	$\overline{u}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	87
55.	$\overline{v}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	88
56.	$\overline{w}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	89
57.	$\overline{u'^2}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	90
58.	$\overline{v'^2}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	91
59.	$\overline{w'^2}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	92
60.	$\overline{u'v'}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	93
61.	$\overline{u'w'}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	94
62.	$\overline{u'^3}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	95
63.	$\overline{v'^3}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	96
64.	$\overline{w'^3}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	97
65.	$\overline{u'^2v'}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	98
66.	$\overline{u'v'^2}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	99
67.	$\overline{u'^2w'}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	100
68.	$\overline{u'w'^2}$ (Boundary Layer, Station C, m = 1.5, $\Delta = 0.25$) -----	101

69.	Streamwise Vorticity (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$) -----	102
70.	$\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	103
71.	$\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	104
72.	$\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $\Delta = 0.25$) -----	105
73.	$\bar{u}^{'2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	106
74.	$\bar{v}^{'2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	107
75.	$\bar{w}^{'2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	108
76.	$\bar{u}^{'v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	109
77.	$\bar{u}^{'w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	110
78.	$\bar{u}^{'3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	111
79.	$\bar{v}^{'3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	112
80.	$\bar{w}^{'3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	113
81.	$\bar{u}^{'2v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	114
82.	$\bar{u}^{'v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	115
83.	$\bar{u}^{'2w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	116
84.	$\bar{u}^{'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	117
85.	Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$) -----	118

86.	$\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	119
87.	$\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	120
88.	$\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	121
89.	$\overline{u'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	122
90.	$\overline{v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	123
91.	$\overline{w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	124
92.	$\overline{u'v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	125
93.	$\overline{u'w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	126
94.	$\overline{u'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	127
95.	$\overline{v'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	128
96.	$\overline{w'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	129
97.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	130
98.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	131
99.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	132
100.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	133
101.	Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', m = 0, $\Delta = 0.25$) -----	134
102.	$\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, m = 0, $\Delta = 0.10$) -----	135

103.	$\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	136
104.	$\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	137
105.	$\overline{u'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	138
106.	$\overline{v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	139
107.	$\overline{w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	140
108.	$\overline{u'v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	141
109.	$\overline{u'w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	142
110.	$\overline{u'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	143
111.	$\overline{v'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	144
112.	$\overline{w'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	145
113.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	146
114.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	147
115.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	148
116.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	149
117.	Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$) -----	150
118.	$\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	151
119.	$\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	152

120.	$\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	153
121.	$\overline{u'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	154
122.	$\overline{v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	155
123.	$\overline{w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	156
124.	$\overline{u'v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	157
125.	$\overline{u'w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	158
126.	$\overline{u'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	159
127.	$\overline{v'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	160
128.	$\overline{w'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	161
129.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	162
130.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	163
131.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	164
132.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	165
133.	Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$) -----	166
134.	$\bar{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	167
135.	$\bar{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	168
136.	$\bar{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	169

137.	$\overline{u'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	170
138.	$\overline{v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	171
139.	$\overline{w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	172
140.	$\overline{u'v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	173
141.	$\overline{u'w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	174
142.	$\overline{u'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	175
143.	$\overline{v'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	176
144.	$\overline{w'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	177
145.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	178
146.	$\overline{u'v'^2}$ (Boundary layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	179
147.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	180
148.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	181
149.	Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$) -----	182
150.	$\overline{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	183
151.	$\overline{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	184
152.	$\overline{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	185
153.	$\overline{u'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	186

154.	$\overline{v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	187
155.	$\overline{w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	188
156.	$\overline{u'v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	189
157.	$\overline{u'w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	190
158.	$\overline{u'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	191
159.	$\overline{v'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	192
160.	$\overline{w'^3}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	193
161.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	194
162.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	195
163.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	196
164.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	197
165.	Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$) -----	198
166.	$\overline{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	199
167.	$\overline{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	200
168.	$\overline{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	201
169.	$\overline{u'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	202
170.	$\overline{v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	203

171.	$\overline{w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	204
172.	$\overline{u'v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	205
173.	$\overline{u'w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	206
174.	$\overline{u'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	207
175.	$\overline{v'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	208
176.	$\overline{w'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	209
177.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	210
178.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	211
179.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	212
180.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	213
181.	Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$) -----	214
182.	$\overline{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	215
183.	$\overline{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	216
184.	$\overline{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	217
185.	$\overline{u'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	218
186.	$\overline{v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	219
187.	$\overline{w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	220

188.	$\overline{u'v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	221
189.	$\overline{u'w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	222
190.	$\overline{u'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	223
191.	$\overline{v'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	224
192.	$\overline{w'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	225
193.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	226
194.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	227
195.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	228
196.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	229
197.	Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$) -----	230
198.	$\overline{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	231
199.	$\overline{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	232
200.	$\overline{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	233
201.	$\overline{u'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	234
202.	$\overline{v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	235
203.	$\overline{w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	236
204.	$\overline{u'v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	237

205.	$\overline{u'w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	238
206.	$\overline{u'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	239
207.	$\overline{v'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	240
208.	$\overline{w'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	241
209.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	242
210.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	243
211.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	244
212.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	245
213.	Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$) -----	246
214.	$\overline{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	247
215.	$\overline{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	248
216.	$\overline{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	249
217.	$\overline{u'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	250
218.	$\overline{v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	251
219.	$\overline{w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	252
220.	$\overline{u'v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	253
221.	$\overline{u'w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	254

222.	$\overline{u'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	255
223.	$\overline{v'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	256
224.	$\overline{w'^3}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	257
225.	$\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	258
226.	$\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	259
227.	$\overline{u'^2w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	260
228.	$\overline{u'w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	261
229.	Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$) -----	262

LIST OF SYMBOLS

SYMBOL	MEANING
B, K, n	hot-wire calibration constants
C	temperature drift correction factor
C_d	discharge coefficient
d	injection hole diameter
E	anemometer voltage
E_{corr}	anemometer voltage corrected for temperature drift
E_{oc}	no-flow voltage extrapolated from velocity calibration
$E_{o(measured)}$	measured no-flow voltage
m	blowing ratio
OHR	overheat ratio
T	turbulence intensity, temperature
T_∞	freestream temperature
T_{cal}	freestream temperature when hot-wire probe is calibrated
U_{eff}	effective cooling velocity
U_o, U_∞	local freestream, freestream velocity
U_{inj}	injectant velocity
U, V, W	instantaneous velocities in x, y and z directions respectively
$\bar{u}, \bar{v}, \bar{w}$	mean velocity components in x, y and z directions respectively
u', v', w'	fluctuating components in x, y and z directions respectively

v^*	friction velocity
$\vec{V}$	secondary flow vector
x	streamwise distance measured from boundary layer trip
x'	streamwise distance measured from downstream edge of injection hole
y	vertical distance
Y_{cen}	vertical location of vortex center
Y_{core}	average vortex core radius in vertical direction
z	spanwise distance measured from centerline
Z_{cen}	spanwise location of vortex center
Z_{core}	average vortex core radius in spanwise direction
α	temperature coefficient of resistance
Γ, Cr	circulation
Δ	node spacing
δ	boundary layer thickness, yaw angle
μ	viscosity
ρ_{inj}	injectant density
ρ_∞	freestream density
σ	total normal stress
σ'	Reynolds normal stress
τ	total shear stress
τ'	Reynolds shear stress
ν	kinematic viscosity
ψ	effective wire angle
ω_x	streamwise vorticity

ACKNOWLEDGMENTS

This work would not have been possible without the support of my thesis advisors, Professor Phillip Ligrani and Professor Chelakara Subramanian. Professor Ligrani's direction, patience, and encouragement were an inspiration. Professor Subramanian provided indispensable expertise in the laboratory and in the development and modification of software. I would like to thank Lt James Green USN, for his concise explanations to numerous technical questions. And lastly, I would like to thank my wife, Connie, and my children for their support and understanding during the many hours spent away from home conducting this research.

I. INTRODUCTION

A. BACKGROUND

In a film cooled gas turbine engine, significant disturbances to the cooling film result from the interaction between the injectant and the embedded vortices in the gas stream. These disturbances result in local hot-spots that would otherwise be protected by the cooling film. Measurement of these interactions is necessary in order to understand the turbulence structure. This will eventually lead to a means to minimize the negative effects, allowing the development of better designs and more efficient engines.

A study of embedded vortices and wall jet interactions was conducted by Green [Ref. 1]. He measured the turbulence structure resulting from the interactions when the vortex downwash passes over a single film cooling hole. He concluded that embedded vortices significantly distort the injectant turbulence characteristics, thereby altering its turbulent transport properties. The present study is a continuation of Green's work. In addition to vortex downwash measurements, measurements at different blowing ratios are presented when the vortex upwash passes above the injection hole.

To the best knowledge of the author, Green's work [Ref. 1] is the only attempt to measure the turbulence structure of vortex/wall jet interactions. Several researchers have measured the turbulence structure of embedded vortices without wall jets. Of these, Shabaka, Mehta and Bradshaw [Ref. 3] studied the characteristics of a single vortex embedded in a turbulent boundary layer. They concluded that the vortex changes the properties of the outer region of the boundary layer. Cutler and Bradshaw [Ref. 4] studied the interaction of vortex pairs with common flow downward in a turbulent boundary layer. Mehta and Bradshaw [Ref. 5] studied interaction of vortex pairs with common flow upward. The two studies show that turbulence structure changes cannot be explained using current turbulence models, and that secondary longitudinal vortices exist having opposite rotational direction to the principle vortices.

Eibeck and Eaton [Ref. 6] studied the heat transfer and fluid dynamic behavior of a turbulent boundary layer with an embedded vortex. Mean velocity profiles in the log-law region are similar to those in two-dimensional turbulent boundary layers. However, as for the Shabaka et al. [Ref. 3] study, the region outside of the boundary layer log-law region was observed to be significantly distorted by the vortices.

Westphal, Pauley, and Eaton [Ref. 7] made measurements of a single vortex interacting with a turbulent boundary

layer. They obtained mean and turbulent velocity results similar to Shabaka et al. [Ref. 3]. They observed that the skin friction increased under the vortex downwash and decreased under the vortex upwash.

The interaction of vortices and wall jets has also been studied by Skow and Peake [Ref. 8], Heffernan [Ref. 9], Schwartz [Ref. 10], Iwanski, et al. [Ref. 11], Visser, et al. [Ref. 12], Ligrani and Schwartz [Ref. 13], and Ligrani and Williams [Ref. 14]. Most of these studies emphasize heat transfer perturbations or vortex control, and none present detailed turbulence measurements.

B. OBJECTIVES

The purpose of the present study is to obtain further information on the turbulence structure resulting from the interactions between an embedded vortex and a single wall jet. A vortex is created using a vortex generator delta wing placed at a 12 degree angle with streamwise flow. The vortex is positioned so that either the downwash or the upwash is located over the injection hole. Information on the streamwise development of the turbulent structure is obtained from measurements at four streamwise locations, A' ($x'/d = 5.9$), A'' ($x'/d = 19.2$), B ($x'/d = 30.1$), and C ($x'/d = 70.3$).

Blowing ratio m , is defined as the ratio of injectant mass flux to freestream mass flux. For the upwash studies,

blowing ratios of 0 (no blowing), 0.5, 1.5, 2.5, and 3.5 are used in order to study the effect of varying blowing ratio. For downwash studies, data are obtained for blowing ratios of 0 and 1.5 in order to compare with previous data.

C. EXPERIMENTAL APPROACH

First, data showing the streamwise development of the turbulent boundary layer with injection at a blowing ratio of 1.5 and no vortex are presented. Next, baseline measurements of the turbulence structure with no injectant and the vortex downwash over the injection hole are given. These measurements provide confirmation of the operation of the experimental apparatus. Lastly, data are presented to illustrate the interactions between vortices and wall jets. These results are given for one streamwise station with the vortex upwash located over the injection site for a range of blowing ratios.

A free stream velocity of 10 m/s is used for all measurements. The boundary layer is tripped 1.08 m upstream of the wall jet as shown in Figure 1. For downwash measurements, the leading edge of the vortex generator is placed 0.487 m downstream of the boundary layer trip, 0.011 m off the tunnel centerline, and at an angle of 12 degrees with respect to tunnel centerline (Figures 2 and 3). For upwash studies the vortex generator is moved to 0.047 m off tunnel centerline using the same streamwise location and

angle (Figures 2 and 4). The jet issues from a 0.952 cm diameter hole located at the centerline of the tunnel and inclined 30 degrees with respect to the horizontal test surface. The ratio of boundary layer displacement thickness to injection hole diameter is equal to 0.28 at the injection site.

A crossed hot-wire probe is used to measure mean and instantaneous velocity components in spanwise normal planes. Measurements are taken at four different streamwise locations.

D. THESIS OUTLINE

Chapter I gives introduction and motivation for research. Chapter II describes the wind tunnel, injection system, vortex generator and other equipment. Chapter III gives an overview of the hot-wire anemometer, data acquisition, micro-computer and probe traversing system. Results of experiments are given in Chapter IV and conclusions are in Chapter V. A software directory is given in Appendix A. A Data Directory is contained in Appendix B. Appendix C contains all the figures and plots generated by this study.

II. EXPERIMENTAL APPARATUS

A. WIND TUNNEL AND TEST SECTION

Experiments were conducted using the same wind tunnel described by Green [Ref. 1: pp. 6-8]. A detailed description of this wind tunnel will not be repeated here. The wind tunnel was manufactured by Aerolab and is located in the laboratories of the Mechanical Engineering Department of the Naval Postgraduate School. The freestream turbulence intensity is about 0.20 percent, for freestream velocities of 10 m/s. The boundary layer is tripped to become fully turbulent at the entrance to the test section with a 1.5 mm high strip of tape. A schematic of the test section is shown in Figure 1.

The right handed coordinate system is also shown in Figure 1. Its origin is located on the floor of the test section where the turbulence trip intersects the spanwise centerline. The positive x direction is measured downstream from the trip. The positive y direction is measured upward from the test surface. The positive z direction is measured to the right of centerline as looking downstream. The four downstream locations of data collection (labeled A', A'', B and C) are also shown in Figure 1. Location of injection holes, Kiel probe, and thermocouple are also shown. Further

information concerning the wind tunnel and testing may be found in [Ref. 2: pp. 38-40].

B. VORTEX GENERATOR

A half delta wing is used to generate the single longitudinal vortex. Figures 2 and 3 show the placement of the delta wing on the test surface so that the vortex downwash passes over the injection hole. Figure 4 shows the position of the delta wing so that the vortex upwash passes over the injection hole. This generator is the same one employed by Green [Ref. 1].

C. INJECTION SYSTEM

The air injection system is also described by Green [Ref. 1: pp. 6-8] with the exception of the air supply. In the present study, the Ingersol-Rand air compressor used in Green's work, is replaced by a 1.5 hp, 2.5 psig, 30 scfm EG&G ROTRON regenerative blower. The discharge of the blower flows into an aluminum plenum measuring 18 in x 18 in x 18 in. The outlet of this plenum is connected to the globe valve and rotometer, and other apparatus described by Green.

III. HOT-WIRE ANEMOMETER AND DATA ACQUISITION SYSTEM

The same data acquisition system and same type of crossed hot wire anemometer probe are used in this study as described by Green [Ref. 1:pp. 9-20] and Subramanian et al. [Ref. 15]. A schematic of the system employed to obtain the measurements is shown in Figure 5. A brief description follows.

A. CROSSED HOT-WIRE SYSTEM

1. Crossed Hot-wire Probe

The crossed hot-wire probe, Type 55 P51, is made by DANTEC Electronics Inc. The 5 μm wires are made of 90% platinum and 10% rhodium. They are mounted perpendicular to each other with about 1 mm separating them. Each wire is about 1 mm long with a "cold" resistance of about 4.1 ohms at room temperature. An operating overheat ratio of 1.8 is used for all experiments. The probe and holder are supported by a vertical stem which are mounted on a traversing device that moves the probe in the y-z plane. The probe can also be rotated about the stem (y axis) for yaw calibration.

2. Hot-wire Anemometer and Signal Conditioner

Two DANTEC 55M10 constant temperature bridges are used to operate the crossed hot-wires (one for each wire).

The probe and connecting cable "cold" wire resistances are measured on the decade counter by balancing the bridge. The operating resistance is then set to 1.8 times the cold wire resistance.

A DANTEC 56N20 two channel signal conditioner is used to low pass filter using a 10 kHz cut off frequency and to amplify signals from the bridges. The operating range of the high speed analog-to-digital converter is optimized by using a gain of 2 without any DC offset. The low pass filter is used to eliminate noise. The high pass setting on the signal conditioner is set to "DC" in order to include the DC component and low frequency velocity variations of the signal.

B. DATA ACQUISITION SYSTEM

1. Low Speed Data Acquisition

For low speed data acquisition and analog-to-digital conversion, a Hewlett-Packard 3497A control unit is used. Readings obtained by the low speed data acquisition system include ones from a Kiel probe and electronic manometer, freestream and injection thermocouples, and hot-wire anemometer voltage signals during probe calibration. A sample size of 50 is taken with a 5 Hz sampling frequency. Temperature and pressure data are read by the low speed data acquisition system during probe calibration as well as during turbulence measurements.

2. High Speed Analog-to-digital Converter

A Hewlett-packard 6944A Multiprogrammer with a buffered 69759A A/D card is used to convert analog turbulence signals from the signal conditioner to digital signals. The buffer feature allows digitized data to be stored while the computer is performing other tasks. Continuous data acquisition is accomplished as long as the computer reads the data out of the buffer faster than it is being written.

The sampling rate and the number of samples collected at each data point are set so that converged time-averaged velocity values are obtained. A sampling frequency of 5000 Hz per channel and a sample size of 20,000 samples per channel are employed. This combination results in four seconds of real sample time per channel at each data point. Increasing the sample size dramatically increases computer run time. Lowering the sampling frequency results in less resolution of small time scale turbulence effects.

The high speed analog-to-digital converter card reads analog inputs and converts them to 12-bit binary numbers. The card is configured to measure analog inputs ranging from -10.240 V to +10.235 V. This 20.475 V input range is divided into 4096 increments of 0.005 V size.

C. CALIBRATION

The instantaneous velocities U and V (and W) are calculated using Equation (1). A different form of this equation is determined for the signal from each wire giving a system of two equations which are solved for two unknown velocities.

$$U_{eff} = U \cos \psi + V \sin \psi = K(E^2 - E_{oc}^2)^{1/n} \quad (1)$$

Coefficients K, ψ , and n are constants determined from the sensor calibration. E_{oc} is the effective bridge voltage at zero velocity extrapolated from the forced convection calibration. The effective wire angle is denoted ψ . Calibration is a three step process including: velocity and yaw calibration in the uw plane, and velocity calibration in the uv plane.

1. Velocity Calibration in the uw Plane

By rearranging Equation (1) and defining a coefficient, B:

$$B = (\cos \psi / K)^n \quad (2)$$

a relationship between E and U is obtained, given by:

$$E^2 = E_{oc}^2 + B U^n \quad (3)$$

Based on Collis and Williams [Ref. 16], n is set equal to 0.45. From the flow velocity, U , and bridge voltages, E , a least squares fit can be used to find B and E_{oc}^2 .

2. Yaw Calibration

The value of K can be determined from Equation (2) if the effective wire angle ψ is known. Yaw calibration involves moving the probe through a series of known angles in the x - z plane ($V = 0$) with the probe exposed to a constant flow velocity. At a yaw angle, δ , Equation (1) then becomes:

$$U \cos(\psi + \delta) = K(E_\delta^2 - E_{oc}^2)^{1/n} \quad (4)$$

where E_δ is the bridge voltage at yaw angle δ . From Equation (1) with zero yaw angle:

$$K = \frac{U \cos \psi}{(E^2 - E_{oc}^2)^{1/n}} \quad (5)$$

where E equals the bridge voltage when yaw angle is equal to zero. Replacing K in Equation (4) with Equation (5) and rearranging then gives:

$$\tan \psi = (\cos \delta - [(E_\delta^2 - E_{oc}^2)/(E^2 - E_{oc}^2)]^{1/n})/\sin \delta \quad (6)$$

Effective wire angles are subsequently determined directly from Equation (6) after the probe is yawed through six different values of δ . The final ψ for each wire is then the average of the six ψ 's calculated at the six yaw angles.

3. Velocity Calibration in the uv Plane

For the uv plane measurements, the wire constants from the uw plane calibrations are corrected for possible probe pitching when the probe was rotated from uw to uv plane. This is done as follows. The velocity calibration explained in Section III.C.1 is repeated with the probe in the uv plane. The zero flow voltage E_{oc} , and the power law index, n , are assumed to be the same as determined from the uw plane calibration. Then, from a linear least square fit of

$$[E^2 - E_{oc}^2] \text{ vs } U^{0.45}$$

the slope of the line, B_{uv} is obtained. Then, the wire angle in the uv plane ψ_{uv} is found from

$$\cos \psi_{uv} = k/B_{uv}$$

where k is given by Equation (5) for the uw plane.

D. MICROCOMPUTER

A Hewlett-Packard Series 9000 computer is the central brain of the system. The computer is equipped with interfaces connected to the HP 6944A multiprogrammer with a high speed analog-to-digital converter and a buffer, the low speed data acquisition system, and the traverse motor controller. The computer reads data from the buffer in the multiprogrammer, performs on line data reduction and controls the position of the probe. Reduced data are stored on a 3.5" disk for future use.

1. Data Reduction

At each node, 20,000 samples per channel are collected. With 228 nodes and two channels, over 9.1 million samples are collected per survey.

a. Hot-wire Temperature Drift Correction

The freestream air temperature does not remain constant during the 12 hours required to complete one survey. Since the calibration constants depend on the "cold" wire resistance at the freestream air temperature during calibration, hot-wire calibration will change due to this freestream temperature drift. To correct for these variations the measured bridge voltage, E , is corrected using:

$$E_{\text{corr}} = E(1 + C) \quad (7)$$

where C is given by:

$$C = \alpha(T_{\alpha} - T_{cal})/[2(OHR - 1)] \quad (8)$$

where α is the temperature coefficient of resistance and is equal to $0.0034/C$ for the wire material, OHR is the overheat ratio, T_{α} is the freestream temperature and T_{cal} is the freestream temperature at time of calibration.

b. Look-up Table

In order to save computer time and speed up data reduction, a look-up table is constructed. The look-up table contains one effective velocity for each of the 4096 binary values assigned to voltages by the high speed analog-to-digital converter. This means that Equation (1), which requires time-consuming exponential calculations, is used only 4096 times to calculate effective velocities from voltages rather than 9.1 million times. When the table is used, the computer simply reads a binary value from the high speed analog-to-digital converter, finds this value in the look-up table then reads the corresponding effective velocity. The look-up table includes the hot wire system gains as well as the temperature drift corrections. The look-up table contains two effective velocity arrays, one for each of the crossed wires. With the effective velocities known for each wire, the instantaneous velocities, U and V, can be calculated from Equation (1).

c. Turbulence Statistics

Because computer memory limits array size to 2000 elements, data collection is done in ten loops in order to achieve the 20,000 samples per wire per data point.

Turbulence statistics are calculated and averaged for each loop. The averages from the ten loops are then averaged.

Turbulent statistics are calculated using the following equations. By replacing the subscript v with w and upper case V with W, the following equations can also be used for the uw plane calculations.

$$\bar{u} = S_u$$

$$\bar{v} = S_v$$

$$\overline{u'^2} = S_{uu} - S_u S_u$$

$$\overline{v'^2} = S_{vv} - S_v S_v$$

$$\overline{u'v'} = S_{uv} - S_u S_v \quad (9)$$

$$\overline{(u')^2 v'} = S_{uuv} - S_v (S_u S_u - (u')^2) - 2 S_u \overline{u'v'}$$

$$\overline{u' (v')^2} = S_{uvv} - S_u (S_v S_v - (v')^2) - 2 S_v \overline{u'v'}$$

$$\overline{u'^3} = S_{uuu} - S_u (S_u S_u + 3 (u')^2)$$

$$\overline{v'^3} = S_{vvv} - S_v (S_v S_v + 3 (v')^2)$$

where:

$$\begin{aligned}
 S_u &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} U \\
 S_v &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} V \\
 S_{uu} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} UU \\
 S_{vv} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} VV \\
 S_{u'v'} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} UV \\
 S_{uuv} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} UUV \\
 S_{uvv} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} UVV \\
 S_{uuu} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} UUU \\
 S_{vvv} &= \frac{1}{20,000} \sum_{loop=1}^{10} \sum_{sample=1}^{2000} VVV
 \end{aligned} \tag{10}$$

In these equations, U and V are instantaneous velocities.

2. Probe Traversing

The microcomputer controls the position of the probe through a MODULYNX MITAS controller (type PMS085-C2AR) which drives two D.C. motors, which move the probe in the y and z directions. For all but two surveys, the probe is traversed through a 3.0 inch x 4.5 inch plane. The area of these surveys are covered with a 12 node by 19 node matrix with vertical and horizontal node spacing of 0.25 inches. The additional two surveys are conducted using 304 nodes with a 16 node x 19 node matrix and a spacing of 0.10 inches, which gives a 1.5 inch x 1.8 inch plane.

IV. EXPERIMENTAL RESULTS

A. CALCULATIONS

All calculations are performed using the same software as Green [Ref. 1]. A directory of this software is presented in Appendix A. All results are displayed in graphical form.

1. Normalization of Results

Freestream velocity is used to normalize Reynolds stress tensor components, average velocities and triple products. To normalize data from each column of nodes, the freestream velocity is measured at the top of each column. This accounts for small variations in freestream velocity over the 12 hour period required to complete a 228 node survey. The location of this freestream velocity measurement is well outside the boundary layer and the regions influenced by the vortices.

2. Streamwise Vorticity

Streamwise vorticity is estimated using the center-finite-difference method at each node. Green [Ref. 1:p. 22] provides additional details.

3. Circulation

Circulation is estimated using the method described by Schwartz [Ref. 10: pp. 17-18]. Circulation is calculated by multiplying the vorticity at each node by the area around

that node and then summing this product over all nodes that exceed the threshold. The threshold level is established so that background "noise" from estimation of velocity derivatives does not influence the estimation of circulation. These calculations are described in detail by Green [Ref. 1:p. 22]. Circulation is denoted C_r in the listings on each vorticity plot.

4. Vortex Core Size

Vortex core size is estimated using the two methods described by Green [Ref. 1:p. 23]. The resulting Y_{core} and Z_{core} values from these methods are also listed on the vorticity plots.

B. SURVEY CONDITIONS AND PARAMETERS

Table 1, below, gives the conditions of each survey conducted. Discussion of results will proceed in the same order as presented in Table 1.

C. BASELINE DATA

1. Streamwise Development of Boundary Layer with Injection Only

Figures 6-69 show the streamwise development of the boundary layer with injection from a single hole at a blowing ratio of 1.5. The location of the four streamwise measurement locations and the coordinate system are shown in Figure 1. The interaction of the jet with the boundary

TABLE 1

SUMMARY OF SURVEY CONDITIONS AND PARAMETERS

Run # Date.Time	Probe Loc.	Probe Orient.	Node Spacing	Blowing Ratio	Vortex Gen.	Figure Num.
61789.1949	A'	uv	0.25	1.5	NONE	6-21
61889.0745	A'	uw	0.25	1.5	NONE	
61689.1711	A''	uv	0.25	1.5	NONE	22-37
61789.0647	A''	uw	0.25	1.5	NONE	
61589.0844	B	uv	0.25	1.5	NONE	38-53
61589.2121	B	uw	0.25	1.5	NONE	
61889.1951	C	uv	0.25	1.5	NONE	54-69
61989.0755	C	uw	0.25	1.5	NONE	
60789.2054	A'	uv	0.25	0	DW	70-85
60889.0854	A'	uw	0.25	0	DW	
60689.1107	A''	uv	0.25	0	DW	86-101
60789.0704	A''	uw	0.25	0	DW	
61089.0743	B	uv	0.10	0	DW	102-117
61289.0813	B	uw	0.10	0	DW	
60889.2049	C	uv	0.25	0	DW	118-133
60989.1219	C	uw	0.25	0	DW	
72189.0931	B	uv	0.25	0	UW	134-149
72289.0831	B	uw	0.25	0	UW	
71089.1212	B	uv	0.10	1.5	DW	150-165
71189.1220	B	uw	0.10	1.5	DW	
60189.1156	B	uv	0.25	0.5	UW	166-181
60289.0927	B	uw	0.25	0.5	UW	
60389.0655	B	uv	0.25	1.5	UW	182-197
60389.1901	B	uw	0.25	1.5	UW	
60489.0652	B	uv	0.25	2.5	UW	198-213
60489.1856	B	uw	0.25	2.5	UW	
60589.0715	B	uv	0.25	3.5	UW	214-229
60589.1918	B	uw	0.25	3.5	UW	

NOTES:

1. Freestream velocity $U_\infty = 10$ m/s
2. Probe locations (x'/d): $A' = 5.9$, $A'' = 19.2$, $B = 30.1$, and $C = 70.3$
3. Downwash Vortex Generator: 12 degrees with leading edge at $x = 48.7$ cm and $z = 1.0$ cm
4. Upwash Vortex Generator: 12 degrees with leading edge at $x = 48.7$ cm and $z = 4.7$ cm

layer is the strongest at the measuring location closest to the injection site (station A').

Mean velocities, the three normal Reynolds stress components and two Reynolds shear stress components are distorted significantly by the jet. Normal stresses show completely different character compared to shear stresses as injectant is convected downstream. In this regard, normal stresses show maximum values near the center of the injection jet. Mean velocities, shear stresses and longitudinal vorticity distributions provide evidence that boundary layer fluid wraps around the jet to form a structure similar to a vortex pair. Because of the secondary flows within this structure, distributions of $\overline{u'v'}$ and $\overline{u'w'}$ at $x'/d = 5.9$ show quite complicated variations. Some of the contours in the proximity of the jet are dome shaped. This pattern is centered along the jet axis ($z = 0$) and seen in the plots of $\overline{v'^3}$, $\overline{u'^2v'}$, and $\overline{u'v'^2}$.

The vortex-like structure on the $+z$ side rotates clockwise as looking downstream ($+x$ direction), and the matching vortex on the $-z$ side rotates in a counter-clockwise direction. The effect of this vortex pair is to convect low-velocity fluid away from the wall at $z = 0$ and to convect high-velocity freestream fluid towards the wall at z locations of 1.5 to 3.0 cm and -1.5 to -3.0 cm. As expected, this vortex pair structure grows in size and decreases in intensity as it progresses downstream. Both

vortices have a region of large positive $\overline{u'^3}$, with a region of large negative $\overline{u'^3}$ between them near the wall.

Contours of $\overline{u'v'}$ at $x'/d = 5.9$ show double positive peaks which exist above a region of negative $\overline{u'v'}$. The values of these peaks are about $0.004U_e^2$ or $0.003U_e^2$. Because of these peaks, the shear stress distribution shows a shape which is flattened in the spanwise direction. Shear stress levels beneath the double peak (near the wall) are also lower than in the surrounding undisturbed boundary layer. In a turbulent boundary layer with a two-dimensional mean flow field, positive shear stresses do not exist. In this situation, a typical minimum value of $\overline{u'v'}$ is $-0.0028U_e^2$.

Positive $\overline{u'v'}$ shear stress regions are not noticeable for x'/d of 19.2, 30.1 and 70.3. At these streamwise stations, negative shear stresses extend in the vertical direction away from the wall. Shear stress levels are also quite small along the axis of the jet because of minimal turbulence production.

Distributions of $\overline{u'w'}$ are very interesting since there are high stress levels around the jet, and strong gradients of positive and negative stresses, especially for $x'/d = 5.9$. Symmetric contours are evident about the jet centerplane, especially for the last three streamwise stations. At the first three streamwise stations, a pair of positive shear stress regions and a pair of negative shear stress regions are evident. For $x'/d > 5.9$ the inner pair

grows vertically as absolute values of shear stress diminish. The outer pair is then pushed in the spanwise direction as this occurs. Interestingly, the general characteristics of $\overline{u'w'}$ development show some similarity to the development of mean streamwise vorticity.

In the clockwise vortex, the spanwise shear, $\overline{u'w'}$, shows large negative values while the triple products $\overline{w'^3}$ and $\overline{u'^2w'}$ show large positive values. In the counter-clockwise vortex, $\overline{u'w'}$ is positive and $\overline{w'^3}$ and $\overline{u'^2w'}$ are negative. Very little disturbance to the boundary layer is noted at spanwise locations for z less than about -4.0 cm.

2. Streamwise Development of the Boundary Layer with a Single Embedded Vortex and No Film Injection

Data showing the effects of the interactions between a vortex and the boundary layer are shown in Figures 70-149. Figures 70-133 show streamwise development when the vortex downwash passes over the injection hole (see Figure 3). Figures 102-117 are present results of a detail survey at station B when a node spacing of 0.10 inches is employed to provide greater degree of spatial resolution of the measured quantities. Figures 134-149 present data obtained when the vortex upwash passes over the injection hole.

As expected, data in Figures 70-133 show that the vortex center moves to the left ($-z$ direction) and upward ($+y$ direction) as the flow progresses downstream. The vortex core size remains approximately constant.

Circulation decreases as the vortex energy is dissipated. Table 2 lists the location of the core center, the average core size and the circulation for each measurement station.

TABLE 2
LOCATION OF CORE CENTER AND SIZE IN BOUNDARY LAYER
WITH VORTEX ONLY

STATION	CORE CENTER z(cm), y(cm)	AVERAGE CORE SIZE (cm)	CIRCULATION (s ⁻¹)
A'	-1.9, 2.5	0.74	0.10230
A''	-2.5, 2.5	0.71	0.09574
B	-2.9, 2.8	NA	NA
C	-4.4, 3.1	0.77	0.08121

NOTES:

1. Average core radius using 40% of $\omega_{x,max}$ criterion
2. Station B core size and circulation not calculated

The three primary regions of the vortex are the core, downwash region and upwash region. Boundary layer thinning in the downwash region results as high velocity fluid is convected toward the wall. The boundary layer is thickened in the vortex upwash region as slower moving fluid is convected away from the wall.

At station A', the normal Reynolds stress components $\overline{u'^2}$, $\overline{v'^2}$, and $\overline{w'^2}$ show large gradients in the vortex core. Two regions of large positive Reynolds shear stress, $\overline{u'w'}$, are separated by a region of large negative Reynolds shear stress. The triple products show large gradients not only

at the vortex core, but also, near the wall in the downwash region.

Data for station B from the survey with 0.10 inch node spacing provides additional information on the detailed structure of the flow. Here, the triple products show severe gradients in the vortex core that are not apparent in the surveys when a 0.25 inch node spacing is used.

Data in Figures 134-149 for position B show flow properties for a different spanwise vortex location. These results are similar to ones obtained when the vortex downwash passes over the injection hole, except the vortex center shifts 3.6 cm to the right when compared to the downwash case.

D. BOUNDARY LAYER/VORTEX/WALL JET INTERACTIONS

Data showing the interactions between the vortex and wall jet are presented for station B which is equivalent to x'/d of 30.1. Figures 150-165 show results of a survey (node spacing of 0.10 inches) conducted when the vortex downwash passes above the injection location. Figures 166-229 then give data showing the effects of blowing ratio when the vortex upwash passes over the injection location.

1. Vortex Downwash Passes Over the Injection Hole, $m = 1.5$

In Figures 150-165, it is apparent that the vortex center moves away from the wall because of the walljet. The size of the core of this primary vortex is about the same as

with no blowing. A weak secondary vortex also develops which is seen in Figure 165. This region of negative vorticity is centered at $y = 0.87$ cm and $z = -6.25$ cm and corresponds to an area of high streamwise velocity.

Results in Figures 150-165 also show large gradients of $\overline{u'v'}$ and all triple products in or near the vortex core which are not apparent in the surveys where a 0.25 inch node spacing is used. These regions of high Reynolds shear stress tend to become enlarged because of the jet. The jet also causes dome-shaped regions near the wall, centered at $z = -3.0$ cm, in plots of $\overline{u}$, $\overline{u'v'}$, $\overline{u'w'}$, $\overline{u'^2w'}$ and $\overline{u'^3}$

2. Vortex Upwash Passes Over the Injection Hole,
 $m = 0.5, 1.5, 2.5$ and 3.5

Figures 166-229 show the effects of varying blowing ratio on the boundary layer when the vortex upwash passes over the injection site. Table 3 gives circulation and core radius values for the different blowing ratios. From these data, it is evident that circulation increases as blowing ratio increases. A region of negative vorticity develops near the wall at low blowing ratios. As blowing ratio increases, this negative vorticity region increases in size and intensity. The region moves upward as blowing ratio increases and more fluid is convected away from the wall.

Data for blowing ratios of 0.5 and 1.5 show qualitative behavior typical of vortices uninfluenced by wall jets. Large gradients of the Reynolds shear stresses and most

TABLE 3

CORE RADIUS, CIRCULATION AND STREAMWISE VORTICITY
OF BOUNDARY LAYER WITH VORTEX UPWASH ABOVE JET

BLOWING RATIO	CORE RADIUS (cm)	CIRCULATION (m ² /s)	STREAMWISE VORTICITY (s ⁻¹)
0.5	0.77	0.10175	503.8
1.5	0.75	0.10622	550.1
2.5	0.91	0.13010	461.2
3.5	1.02	0.14247	437.0

triple products exist near the core. With blowing ratios of 0.5 and 1.5, contour plots of $\overline{u'^2}$, $\overline{v'^2}$, $\overline{w'^2}$, $\overline{u'v'}$, and $\overline{u'w'}$ also show dome-shaped variations near $z = -1.25$ cm. Similar behavior is evident in regard to the triple products. The dome-shaped regions are characterized by large positive values near the wall. As blowing ratio increases, spatial extents and magnitudes of properties of these regions then increase.

With blowing ratios of 2.5 and 3.5, data indicate that the jet is more influential than the vortex in regard to local flow behavior. Because of the walljet, the vortex is pushed away from the wall and contour plots show mushroom-shaped variations. The vortex core grows in size and is displaced upward. Severe gradients of $\overline{u'v'}$, $\overline{u'w'}$ and triple products develop in the core, which separate negative and positive regions.

V. SUMMARY AND CONCLUSIONS

The turbulent structure as a result of the interaction of an embedded vortex and a single wall jet was investigated. Measurements of the streamwise development of the boundary layer as influenced by a jet only and by a vortex only were conducted to verify and clarify earlier work. The effects of a jet on the boundary layer with an embedded vortex with the upwash passing over the jet were also investigated. The vortex was generated using a 12 degree delta wing mounted on the test section floor. Blowing ratios varied from 0.5 to 3.5. Freestream velocity was 10 m/s, as provided in a zero pressure gradient.

The vortex significantly alters the turbulence structure of the wall jet and vice versa. At blowing ratios of 1.5 and less, the injectant is distorted and convected away from the injection hole by vortex secondary flows. At blowing ratios above 1.5, the jet dominates the flow causing the vortex to be displaced away from the wall. Because of the jet, Reynolds shear stress components, $\overline{u'v'}$ and $\overline{u'w'}$ show severe gradients near the vortex core. When the vortex upwash passes over the injection location, a region of negative vorticity develops because of the jet, which grows in intensity and is displaced away from the wall as the blowing ratio increases.

Mean velocities, and the three normal Reynolds stress components are distorted significantly by a 1.5 blowing ratio when no vortex is present. Normal stresses show completely different character compared to shear stresses as injectant is convected downstream. In this regard, normal stresses show maximum values near the center of the injection jet. Mean velocities, shear stresses and longitudinal vorticity distributions provide evidence that boundary layer fluid wraps around the jet to form a structure similar to a vortex pair. Because of the secondary flows within this structure, distributions of $\overline{u'v'}$ and $\overline{u'w'}$ at $x'/d = 5.9$ show quite complicated variations.

APPENDIX A

SOFTWARE DIRECTORY

Calibration, data acquisition and plotting programs are written in the HP-BASIC language. Program names and descriptions follow.

<u>Program Name</u>	<u>Description</u>
HWCAL300	Performs velocity and yaw calibration for the crossed wire probe. Calibration constants for measurements in uv and uw planes are written to files Cal#UV and Cal#UW respectively. In these file names, # is an integer automatically assigned to index the calibration files.
SETCOND	Calculates blowing ratio, discharge coefficient and freestream velocity before each experiment. User must input total freestream pressure, pressure drop across injection holes, number of injection holes in use and injectant flow rate.
HOTWIREUV	Data acquisition program for measurements in the uv plane. Measures actual system gain and offset. Then constructs look-up table using probe calibration constants read from file Cal#UV. The program includes commands to automatically move the probe through the desired number of nodes at the <u>desired node spacing</u> . <u>Calculates $\bar{u}$, u'^2, v'^2, $u'v'$, v'^3, u'^2v' and $u'v'^2$ at each node.</u> The results are written to a data file named by the user. This file is referred to as the uv data file.
HOTWIREUW	Data acquisition program for measurements in the uw plane. Reads probe calibration constants from file Cal#UW and writes results to the uw data file.
AVG	Reads from <u>uv and uw data files</u> and normalizes $\bar{u}$, u'^2 and u'^3 at each node with respect to $\bar{u}_{bar}$, $\bar{u}_{bar}^2$ or $\bar{u}_{bar}^3$ measured at

the top of each column of nodes. Averages normalized quantities from uv and uw data files. Results are plotted in contour format.

Baruv	Reads data from uv data file and plots contours of u and v normalized with respect to ubar measured at the top of each column of nodes.
Baruw	Reads data from uw data file and plots contours of u and w normalized with respect to ubar measured at the top of each column of nodes.
2UV	Reads data from uv data file and plots contours of $\overline{v'^2}$ and $u'v'$ normalized with respect to $\overline{ubar^2}$ measured at the top of each column of nodes.
2UW	Reads data from uw data file and plots contours of $\overline{w'^2}$ and $u'w'$ normalized with respect to $\overline{ubar^2}$ measured at the top of each column of nodes.
3UV	Reads data from uv data file and plots contours of $\overline{v'^3}$, u'^2w' , and $u'v'^2$ normalized with respect to $\overline{ubar^3}$ measured at the top of each column of nodes.
3UW	Reads data from uw data file and plots contours of $\overline{w'^3}$, u'^2w' , and $u'w'^2$ normalized with respect to $\overline{ubar^3}$ measured at the top of each column of nodes.

APPENDIX B

DATA DIRECTORY

Run # Date.Time	Probe Loc.	Probe Orient.	Node Spacing	Blowing Ratio	Vortex Gen.	Figure Num.
61789.1949	A'	uv	0.25	1.5	NONE	6-21
61889.0745	A'	uw	0.25	1.5	NONE	
61689.1711	A''	uv	0.25	1.5	NONE	22-37
61789.0647	A''	uw	0.25	1.5	NONE	
61589.0844	B	uv	0.25	1.5	NONE	38-53
61589.2121	B	uw	0.25	1.5	NONE	
61889.1951	C	uv	0.25	1.5	NONE	54-69
61989.0755	C	uw	0.25	1.5	NONE	
60789.2054	A'	uv	0.25	0	DW	70-85
60889.0854	A'	uw	0.25	0	DW	
60689.1107	A''	uv	0.25	0	DW	86-101
60789.0704	A''	uw	0.25	0	DW	
61089.0743	B	uv	0.10	0	DW	102-117
61289.0813	B	uw	0.10	0	DW	
60889.2049	C	uv	0.25	0	DW	118-133
60989.1219	C	uw	0.25	0	DW	
72189.0931	B	uv	0.25	0	UW	134-149
72289.0831	B	uw	0.25	0	UW	
71089.1212	B	uv	0.10	1.5	DW	150-165
71189.1220	B	uw	0.10	1.5	DW	
60189.1156	B	uv	0.25	0.5	UW	166-181
60289.0927	B	uw	0.25	0.5	UW	
60389.0655	B	uv	0.25	1.5	UW	182-197
60389.1901	B	uw	0.25	1.5	UW	
60489.0652	B	uv	0.25	2.5	UW	198-213
60489.1856	B	uw	0.25	2.5	UW	
60589.0715	B	uv	0.25	3.5	UW	214-229
60589.1918	B	uw	0.25	3.5	UW	

NOTES:

1. Freestream velocity $U_\infty \approx 10$ m/s
2. Probe locations (x'/d): $A' = 5.9$, $A'' = 19.2$, $B = 30.1$, and $C = 70.3$
3. Downwash Vortex Generator: 12 degrees with leading edge at $x = 48.7$ cm and $z = 1.0$ cm
4. Upwash Vortex Generator: 12 degrees with leading edge at $x = 48.7$ cm and $z = 4.7$ cm

APPENDIX C

FIGURES




Figure 1. Test Section Schematic




Figure 2. Vortex Generator




Figure 3. Vortex Generator Downwash Placement





Figure 4. Vortex Generator Upwash Placement



$\bar{u} / U_e$ RANGES		$U_e = 10.0$ m/s	
0	> .697 < .730	5	> .904 < .946
1	> .730 < .78	6	> .946 < .987
2	> .78 < .821	7	> .987 < 1.03
3	> .821 < .863	8	> 1.03 < 1.07
4	> .863 < .904	9	> 1.071 < 1.11

Figure 6. $\bar{u}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)




Figure 7. $\bar{v}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)




Figure 8. $\bar{w}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)

RUNS #61789. 1949 and 61889. 0745





Figure 9. $\overline{u'^2}$ (Boundary Layer, Station A',
m = 1.5, $\Delta = 0.25$)

v'^2 / Ue^2

BOUNDARY $m=1.5$ STA A'

RUN #61789.1949



v'^2 / Ue^2 RANGES


	v'^2 / Ue^2 RANGES	$Ue = 10.0$ m/s	
0	1.1×10^{-6} to 5.61×10^{-6}	5	1.1×10^{-6} to 0.00797
1	5.61×10^{-6} to 0.0016	6	1.1×10^{-6} to 0.00956
2	0.0016 to 0.00319	7	1.1×10^{-6} to 0.0111
3	0.00319 to 0.00478	8	1.1×10^{-6} to 0.0127
4	0.00478 to 0.00637	9	1.1×10^{-6} to 0.0143

Figure 10. $\overline{v'^2}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)

w'^2 / Ue^2

BOUNDARY $m=1.5$ STA A'

RUN #61889.0745



w'^2 / Ue^2 RANGES		$Ue=10.0$ m/s	
0	> .00148 < 7.1E-6	5	> .00597 < .00746
1	> 7.1E-6 < .0015	6	> .00746 < .00895
2	> .0015 < .00299	7	> .00895 < .0104
3	> .00299 < .00448	8	> .0104 < .0119
4	> .00448 < .00597	9	> .0119 < .0134

Figure 11. $\overline{w'^2}$ (Boundary Layer, Station A',
 $m = 1.5, \Delta = 0.25$)

$u'v' / Ue^2$

BOUNDARY $m=1.5$ STA A'

RUN #61789.1949




Figure 12. $u'v'$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)

$u'w' / Ue^2$
 BOUNDARY $m=1.5$ STA A'
 RUN #61889.0745





Figure 13. $\overline{u'w'}$ (Boundary Layer, Station A',
 $m = 1.5$, $\Delta = 0.25$)

u'^3 / Ue^3

BOUNDARY $m=1.5$ STA A'

RUNS #61789.1949 and 61889.0745




u'^3 / Ue^3 RANGES		Ue=10.0 m/s	
0	1>-.000191 <-.0.62E-5	5	1>.000334 <.000439
1	1>-.0.62E-5 <1.00E-5	6	1>.000439 <.000544
2	1>1.00E-5 <.000124	7	1>.000544 <.000649
3	1>.000124 <.000229	8	1>.000649 <.000754
4	1>.000229 <.000334	9	1>.000754 <.000859

Figure 14. u'^3 (Boundary Layer, Station A',
 $m = 1.5$, $\Delta = 0.25$)

V'^3 / Ue^3

BOUNDARY $m=1.5$ STA A'

RUN #61789.1949



V'^3 / Ue^3 RANGES

	$Ue=10.0$ m/s
0 1 > -.000256 < -.000160	5 1 > .000183 < .00027
1 1 > -.000160 < -.000080	6 1 > .00027 < .000350
2 1 > -.000080 < -.000040	7 1 > .000350 < .000446
3 1 > -.000040 < -.000020	8 1 > .000446 < .000533
4 1 > -.000020 < -.000010	9 1 > .000533 < .000621

Figure 15. V'^3 (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)

w'^3 / Ue^3

BOUNDARY $m=1.5$ STA A'

RUN #61889.0745





Figure 16. w'^3 (Boundary Layer, Station A',
 $m = 1.5$, $\Delta = 0.25$)

$(u'^2)v' / Ue^3$
BOUNDARY $m=1.5$ STA A'

RUN #61789.1949



$(u'^2)v' / Ue^3$ RANGES


0	>-.000536	<-.000441
1	>-.000441	<-.000346
2	>-.000346	<-.000251
3	>-.000251	<-.000156
4	>-.000156	<-.000061
5	>-.000061	<-.000016
6	>.000016	<.000061
7	>.000061	<.000116
8	>.000116	<.000171

$Ue=10.0$ m/s

Figure 17. u'^2v' (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)

$u'(v'^2) / Ue^3$
BOUNDARY $m=1.5$ STA A'

RUN #61789.1949



$u'(v'^2) / Ue^3$ RANGES


0	>-.000373	<-.000304	5	>-2.96E-5	< 3.9E-5
1	>-.000304	<-.000236	6	> 3.9E-5	< .000108
2	>-.000236	<-.000167	7	> .000108	< .000176
3	>-.000167	<-.9.83E-5	8	> .000176	< .000245
4	>-9.83E-5	<-2.96E-5	9	> .000245	< .000314

$Ue=10.0$ m/s

Figure 18. $\overline{u'v'^2}$ (Boundary Layer, Station A',
 $m = 1.5$, $\Delta \approx 0.25$)

$(u'^2)w' / Ue^3$
BOUNDARY $m=1.5$ STA A'

RUN #61889.0745



$(u'^2)w' / Ue^3$ RANGES

0	>-.000478	<-.000382
1	>-.000382	<-.000286
2	>-.000286	<-.000191
3	>-.000191	<-.000095
4	>-.000095	<.000000

$Ue=10.0$ m/s


5	>1.09E-6	<9.69E-5
6	>9.69E-5	<.000193
7	>.000193	<.000288
8	>.000288	<.000384
9	>.000384	<.000480

Figure 19. $\overline{u'^2 w'}$ (Boundary Layer, Station A',
 $m = 1.5$, $\Delta = 0.25$)

$u'(w'^2) / Ue^3$

BOUNDARY $m=1.5$ STA A'

RUN #61889.0745




$Ue=10.0$ m/s

$u'(w'^2) / Ue^3$ RANGES

0	>-.000285	<-.000223
1	>-.000223	<-.000161
2	>-.000161	<-.0001
3	>-.0001	<-.00005
4	>-.00005	<.00001
5	>.00001	<.00005
6	>.00005	<.0001
7	>.0001	<.0002
8	>.0002	<.0005
9	>.0005	<.001

Figure 20. $\overline{u'w'^2}$ (Boundary Layer, Station A', $m = 1.5$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 0 DEGREES
 RUN# 61789.1949 & 61889.0745 PROBE POSITION: A'
 BLOWING RATIO= 1.5 FREESTREAM VELOCITY(U)= 10 m/s



Cr= .02917 m²/s Wxmax=283.0 1/s
 Zcen= .64 cm Ycen=1.19 cm Cr/(Uc*d)= .20472
 Zcore= .95 cm Ycore=4.45 cm (calc. from secondary flow vectors)
 Zcore= .59 cm Ycore= .49 cm (calc. from 40% of Wxmax)

Figure 21. Streamwise Vorticity (Boundary Layer, Station A', m = 1.5, Δ = 0.25)

$\bar{u} / U_e$
 BOUNDARY $m=1.5$ STA A"
 RUNS #61689.1711 and 61789.0617





Figure 22. $\bar{u}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

$\bar{v} / U_e$
BOUNDARY $m=1.5$ STA A"

RUN #61689.1711



$\bar{v} / U_e$ RANGES		$U_e = 10.0$ m/s	
0	1) $-.0438$ < $-.0387$	5	1) $.0219$ < $.035$
1	1) $-.0307$ < $-.0175$	6	1) $.035$ < $.0482$
2	1) $-.0175$ < $-.0044$	7	1) $.0482$ < $.0613$
3	1) $-.0044$ < $.00874$	8	1) $.0613$ < $.0744$
4	1) $.00874$ < $.0219$	9	1) $.0744$ < $.0876$

Figure 23. $\bar{v} / U_e$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)




Figure 24. $\bar{w}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

$$u'^2 / Ue^2$$

BOUNDARY $m=1.5$ STA A"

RUNS #61689.1711 and 61789.0617





Figure 25. u'^2 (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

v'^2 / Ue^2

BOUNDARY $m=1.5$ STA A"

RUN #61689.1711



v'^2 / Ue^2 RANGES


	v'^2 / Ue^2 RANGES	$Ue=10.0$ m/s
0	1 > -.00035 < 5.62E-6	5 > .00143 < .00179
1	1 > 5.62E-6 < .000362	6 > .00179 < .00214
2	2 > .000362 < .000718	7 > .00214 < .0025
3	3 > .000718 < .00107	8 > .0025 < .00285
4	4 > .00107 < .00143	9 > .00285 < .00321

Figure 26. $\overline{v'^2}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

w'^2 / Ue^2

BOUNDARY $m=1.5$ STA A''

RUN #61789.0617




w'^2 / Ue^2 RANGES		$Ue=10.0$ m/s	
0	>-.000536 < 5.35E-6	5	>.00217 < .00271
1	> 5.35E-6 < .000546	6	>.00271 < .00325
2	>.000546 < .00109	7	>.00325 < .00379
3	>.00109 < .00163	8	>.00379 < .00433
4	>.00163 < .00217	9	>.00433 < .00488

Figure 27. $\overline{w'^2}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

$u'v' / Ue^2$

BOUNDARY $m=1.5$ STA A"

RUN #61689.1711



$u'v' / Ue^2$ RANGES


	$u'v' / Ue^2$ RANGES	$Ue = 10.0$ m/s	
0	$1 > -0.00211 < -0.00189$	5	$1 > -0.00095 < -0.00072$
1	$1 > -0.00189 < -0.00166$	6	$1 > -0.00072 < -0.00055$
2	$1 > -0.00166 < -0.00144$	7	$1 > -0.00055 < -0.000327$
3	$1 > -0.00144 < -0.00122$	8	$1 > -0.000327 < -0.000104$
4	$1 > -0.00122 < -0.00095$	9	$1 > -0.000104 < 0.000110$

Figure 28. $\overline{u'v'}$ (Boundary layer, Station A'', $m = 1.5$, $\Delta = 0.25$)

$u'w' / Ue^2$

BOUNDARY $m=1.5$ STA A"

RUN #61789.0617




$u'w' / Ue^2$ RANGES		$Ue=10.0$ m/s			
0	>-.00199	<-.00163	5	>-.000179	<.000182
1	>-.00163	<-.00126	6	>.000182	<.000544
2	>-.00126	<-.000903	7	>.000544	<.000906
3	>-.000903	<-.000541	8	>.000906	<.00127
4	>-.000541	<-.000179	9	>.00127	<.00163

Figure 29. $u'w'$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

u'^3 / Ue^3

BOUNDARY $m=1.5$ STA A"

RUNS #61689.1711 and 61789.0617



u'^3 / Ue^3 RANGES


	$Ue=10.0$ m/s
0 : >-.000134 <-.000112	5 : >-2.52E-5 <-3.42E-6
1 : >-.000112 <-9.04E-5	6 : >-3.42E-6 < 1.03E-5
2 : >-9.04E-5 <-6.87E-5	7 : > 1.03E-5 < 4.01E-5
3 : >-6.87E-5 <-4.69E-5	8 : > 4.01E-5 < 6.10E-5
4 : >-4.69E-5 <-2.52E-5	9 : > 6.10E-5 < 8.36E-5

Figure 30. u'^3 (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

V'^3 / Ue^3

BOUNDARY $m=1.5$ STA A"

RUN #61689.1711



V'^3 / Ue^3 RANGES		$Ue=10.0$ m/s	
0	>-2.09E-5 <-1.1E-5	5	> 2.00E-5 < 3.00E-5
1	>-1.1E-5 <-1.01E-6	6	> 3.00E-5 < 4.07E-5
2	>-1.01E-6 < 0.94E-6	7	> 4.07E-5 < 5.07E-5
3	> 0.94E-6 < 1.09E-5	8	> 5.07E-5 < 6.06E-5
4	> 1.09E-5 < 2.00E-5	9	> 6.06E-5 < 7.06E-5

Figure 31. V'^3 (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

BOUNDARY m=1.5 STA A"

RUN #61789.0617





Figure 32. $\overline{w'^3}$ (Boundary Layer, Station A'',
m = 1.5, $\Delta = 0.25$)

$(u'^2)v' / Ue^3$

BOUNDARY $m=1.5$ SAT A"

RUN #61689.1711



$(u'^2)v' / Ue^3$ RANGES


0	> 1.20E-5	< 6.1E-6	5	> 2.06E-5	< 2.73E-5
1	> 6.1E-6	< 5.73E-7	6	> 2.73E-5	< 3.4E-5
2	> 5.73E-7	< 7.25E-6	7	> 3.4E-5	< 4.06E-5
3	> 7.25E-6	< 1.39E-5	8	> 4.06E-5	< 4.73E-5
4	> 1.39E-5	< 2.06E-5	9	> 4.73E-5	< 5.4E-5

$Ue = 10.0$ m/s

Figure 33. $\overline{u'^2v'}$ (Boundary Layer, Station A'', $m = 1.5$, $\Delta = 0.25$)

$u'(v'^2) / Ue^3$
BOUNDARY $m=1.5$ STA A"

RUN #61689.1711



$u'(v'^2) / Ue^3$ RANGES		$Ue=10.0$ m/s	
0	$> -3.46E-5$	5	$> -1.37E-5$
1	$> -3.84E-5$	6	$> -9.46E-6$
2	$> -2.62E-5$	7	$> -5.27E-6$
3	$> -2.2E-5$	8	$> -1.08E-6$
4	$> -1.78E-5$	9	$> -1.11E-6$
			$> 7.31E-6$

Figure 34. $\overline{u'v'^2}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$
 BOUNDARY $m=1.5$ STA A"

RUN #61789.0617





Figure 35. $\overline{u'^2 w'}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

$u'(w'^2) / Ue^3$

BOUNDARY $m=1.5$ STA A"

RUN #61789.0617



$Ue=10.0$ m/s

$u'(w'^2) / Ue^3$ RANGES

0	>-3.98E-5	<-3.14E-5	5	> 2.64E-6	< 1.11E-5
1	>-3.14E-5	<-2.29E-5	6	> 1.11E-5	< 1.97E-5
2	>-2.29E-5	<-1.44E-5	7	> 1.97E-5	< 2.82E-5
3	>-1.44E-5	<-5.88E-6	8	> 2.82E-5	< 3.67E-5
4	>-5.88E-6	< 2.64E-6	9	> 3.67E-5	< 4.52E-5

Figure 36. $\overline{u'w'^2}$ (Boundary Layer, Station A'',
 $m = 1.5$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 0 DEGREES
 RUN# 61689.1711 & 61789.0617 PROBE POSITION: A''
 BLOWING RATIO= 1.5 FREESTREAM VELOCITY(U)= 10 m/s




Figure 37. Streamwise Vorticity (Boundary Layer, Station A'', $m = 1.5$, $\Delta = 0.25$)




Figure 38. $\bar{u}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)




Figure 39. $\bar{v}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

wbar / Ue
 BOUNDARY m=1.5 STA B
 RUN #61589.2121





Figure 40. $\bar{w}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

$$u'^2 / Ue^2$$

BOUNDARY $m=1.5$ STA B

RUNS #61589.0844 and 61589.2121




u'^2 / Ue^2 RANGES		$Ue=10.0$ m/s	
0	> .000707 < 8.43E-6	5	> .00287 < .00359
1	> 8.43E-6 < .000724	6	> .00359 < .0043
2	> .000724 < .00144	7	> .0043 < .00502
3	> .00144 < .00216	8	> .00502 < .00573
4	> .00216 < .00287	9	> .00573 < .00645

Figure 41. u'^2 (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

v'^2 / Ue^2

BOUNDARY $m=1.5$ STA B

RUN #61589.0844



v'^2 / Ue^2 RANGES		$Ue=10.0$ m/s	
0	>-.00026 < 6.18E-6	5	>.00107 < .00134
1	> 6.18E-6 < .000272	6	>.00134 < .0016
2	>.000272 < .000538	7	>.0016 < .00187
3	>.000538 < .000804	8	>.00187 < .00213
4	>.000804 < .00107	9	>.00213 < .0024

Figure 42. $\overline{v'^2}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

RUN #61589.2121





Figure 43. $\overline{w'^2}$ (Boundary Layer, Station B,
 $m = 1.5, \Delta = 0.25$)

$u'v' / Ue^2$
 BOUNDARY $m=1.5$ STA B
 RUN #61589.0844




$u'v' / Ue^2$ RANGES $Ue=10.0$ m/s
 0 1 >-.00219 <-.00197 5 1 >-.00109 <-.00071
 1 1 >-.00197 <-.00175 6 1 >-.000871 <-.000651
 2 1 >-.00175 <-.00153 7 1 >-.000651 <-.000432
 3 1 >-.00153 <-.00131 8 1 >-.000432 <-.000212
 4 1 >-.00131 <-.00109 9 1 >-.000212 < 6.91E-6

Figure 44. $u'v'$ (Boundary Layer, Station B,
 $m = 1.5$, $\Delta = 0.25$)

$u'w' / Ue^2$

BOUNDARY $m=1.5$ STA B

RUN #61589.2121



$Ue = 10.0 \text{ m/s}$

$u'w' / Ue^2$ RANGES		$Ue = 10.0 \text{ m/s}$	
0	>-.00158 <-.00132	5	>-.000264 <-1.0E-6
1	>-.00132 <-.00105	6	>-1.0E-6 <.000261
2	>-.00105 <-.00079	7	>.000261 <.000523
3	>-.00079 <-.000527	8	>.000523 <.000788
4	>-.000527 <-.000264	9	>.000788 <.00105

Figure 45. $u'w'$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

u'^3 / Ue^3
BOUNDARY $m=1.5$ STA B

RUNS #61589.0844 and 61589.2121





Figure 46. u'^3 (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

V'^3 / Ue^3

BOUNDARY $m=1.5$ STA B

RUN #61589.0844



V'^3 / Ue^3 RANGES

0 : > -1.17E-5	< -6.01E-6	5 : > 1.69E-5	< 2.26E-5
1 : > -6.01E-6	< -2.94E-7	6 : > 2.26E-5	< 2.83E-5
2 : > -2.94E-7	< 5.42E-6	7 : > 2.83E-5	< 3.4E-5
3 : > 5.42E-6	< 1.11E-5	8 : > 3.4E-5	< 3.97E-5
4 : > 1.11E-5	< 1.69E-5	9 : > 3.97E-5	< 4.55E-5

$Ue = 10.0$ m/s

Figure 47. V'^3 (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

w'^3 / Ue^3

BOUNDARY $m=1.5$ STA B

RUN #61589.2121





Figure 48. w'^3 (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

$(u'^2)^{1/2} v' / Ue^{1/3}$

BOUNDARY $m=1.5$ STA B

RUN #61589.0844



$(u'^2)^{1/2} v' / Ue^{1/3}$ RANGES

0	> -1.22E-5	< -4.6E-6	5	> 2.56E-5	< 3.32E-5
1	> -4.6E-6	< 2.96E-6	6	> 3.32E-5	< 4.08E-5
2	> 2.96E-6	< 1.05E-5	7	> 4.08E-5	< 4.83E-5
3	> 1.05E-5	< 1.81E-5	8	> 4.83E-5	< 5.59E-5
4	> 1.81E-5	< 2.56E-5	9	> 5.59E-5	< 6.34E-5


$Ue=10.0$ m/s

Figure 49. $\overline{u'^2 v'}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

$$u'(v'^2) / Ue^3$$

BOUNDARY m=1.5 STA B

RUN #61589.0844




u'(v'^2) / Ue^3 RANGES		Ue=10.0 m/s			
0	>-4.27E-5	<-3.8E-5	5	>-1.93E-5	<-1.47E-5
1	>-3.8E-5	<-3.33E-5	6	>-1.47E-5	<-1.E-5
2	>-3.33E-5	<-2.87E-5	7	>-1.E-5	<-5.34E-6
3	>-2.87E-5	<-2.4E-5	8	>-5.34E-6	<-6.79E-7
4	>-2.4E-5	<-1.93E-5	9	>-6.79E-7	< 3.99E-8

Figure 50. $\overline{u'v'^2}$ (Boundary Layer, Station B, m = 1.5, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$

BOUNDARY $m=1.5$ STA B

RUN #61589.2121



$Ue=10.0 \text{ m/s}$

$(u'^2)w' / Ue^3 \text{ RANGES}$

0	>-4.94E-5	<-4.06E-5	5	>-5.58E-6	< 3.18E-6
1	>-4.06E-5	<-3.19E-5	6	> 3.18E-6	< 1.19E-5
2	>-3.19E-5	<-2.31E-5	7	> 1.19E-5	< 2.07E-5
3	>-2.31E-5	<-1.43E-5	8	> 2.07E-5	< 2.95E-5
4	>-1.43E-5	<-5.58E-6	9	> 2.95E-5	< 3.82E-5

Figure 51. $\overline{u'^2 w'}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

$$u'(w'^2) / Ue^3$$

BOUNDARY m=1.5 STA B

RUN #61589.2121




Figure 52. $\overline{u'w'^2}$ (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 0 DEGREES
 RUN# 61589.0844 & 61589.2121 PROBE POSITION: B
 BLOWING RATIO= 1.5 FREESTREAM VELOCITY(U)= 10 m/s




Figure 53. Streamwise Vorticity (Boundary Layer, Station B, $m = 1.5$, $\Delta = 0.25$)





Figure 54. $\bar{u}$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

vbar / Ue
 BOUNDARY m=1.5 STA C
 RUN #61889.1951



vbar / Ue RANGES		Ue=10.0 m/s	
0	>-.0211 <-.0161	5	>.00402 <.00906
1	>-.0161 <-.0111	6	>.00906 <.0141
2	>-.0111 <-.00604	7	>.0141 <.0191
3	>-.00604 <-.00101	8	>.0191 <.0242
4	>-.00101 <.00402	9	>.0242 <.0292

Figure 55. $\bar{v}$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)





Figure 56. $\bar{w}$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

u'^2 / Ue^2

BOUNDARY $m=1.5$ STA C

RUNS #61889.1951 and 61989.0755



u'^2 / Ue^2 RANGES

Run	u'^2 / Ue^2 Range	Ue (m/s)
0	1.0×10^{-6} to 9.4×10^{-6}	5.1
1	9.4×10^{-6} to 0.00009	6.1
2	0.00009 to 0.00137	7.1
3	0.00137 to 0.00205	8.1
4	0.00205 to 0.00273	9.1
5	0.00273 to 0.00341	
6	0.00341 to 0.00408	
7	0.00408 to 0.00476	
8	0.00476 to 0.00544	
9	0.00544 to 0.00612	

Figure 57. $\overline{u'^2}$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

v'^2 / Ue^2
 BOUNDARY $m=1.5$ STA C
 RUN #61889.1951




Figure 58. v'^2 (Boundary Layer, Station C,
 $m = 1.5$, $\Delta = 0.25$)

w'^2 / Ue^2
 BOUNDARY $m=1.5$ STA C
 RUN #61989.0755




Figure 59. $\overline{w'^2}$ (Boundary Layer, Station C,
 $m = 1.5, \Delta = 0.25$)

$u'v' / Ue^2$
 BOUNDARY $m=1.5$ STA C
 RUN #61889.1951




Figure 60. $\overline{u'v'}$ (Boundary Layer, Station C,
 $m = 1.5, \Delta = 0.25$)

$u'w' / Ue^2$
 BOUNDARY $m=1.5$ STA C
 RUN #61989.0755





Figure 61. $\overline{u'w'}$ (Boundary Layer, Station C,
 $m = 1.5, \Delta = 0.25$)

u'^3 / Ue^3

BOUNDARY $m=1.5$ STA C

RUNS #61889.1951 and 61989.0755



u'^3 / Ue^3 RANGES

$Ue=10.0$ m/s

0	>-.000147	<-.000126	5	>-4.19E-5	<-2.09E-5
1	>-.000126	<-.000105	6	>-2.09E-5	< 6.17E-8
2	>-.000105	<-.0.39E-5	7	> 6.17E-8	< 2.1E-5
3	>-0.39E-5	<-0.29E-5	8	> 2.1E-5	< 4.2E-5
4	>-0.29E-5	<-4.19E-5	9	> 4.204E-5	< 6.3E-5

Figure 62. u'^3 (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

V'^3 / Ue^3

BOUNDARY $m=1.5$ STA C

RUN #61889.1951





Figure 63. V'^3 (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

w'^3 / Ue^3
 BOUNDARY $m=1.5$ STA C
 RUN #61989.0755




w'^3 / Ue^3 RANGES $Ue=10.0$ m/s

0	$>-3.52E-5$	$<-2.88E-5$	5	$>-2.34E-6$	$<4.22E-6$
1	$>-2.88E-5$	$<-2.2E-5$	6	$>4.22E-6$	$<1.08E-5$
2	$>-2.2E-5$	$<-1.55E-5$	7	$>1.08E-5$	$<1.73E-5$
3	$>-1.55E-5$	$<-8.91E-6$	8	$>1.73E-5$	$<2.38E-5$
4	$>-8.91E-6$	$<-2.34E-6$	9	$>2.38E-5$	$<3.05E-5$

Figure 64. w'^3 (Boundary Layer, Station C,
 $m = 1.5$, $\Delta = 0.25$)

$(u'^2)v' / Ue^3$
BOUNDARY $m=1.5$ STA C

RUN #61889.1951




$(u'^2)v' / Ue^3$ RANGES		$Ue=10.0$ m/s			
0	> -5.27E-6	< -7.00E-9	5	> 2.1E-5	< 2.63E-5
1	> -7.00E-9	< 5.26E-6	6	> 2.63E-5	< 3.16E-5
2	> 5.26E-6	< 1.05E-5	7	> 3.16E-5	< 3.68E-5
3	> 1.05E-5	< 1.58E-5	8	> 3.68E-5	< 4.21E-5
4	> 1.58E-5	< 2.1E-5	9	> 4.21E-5	< 4.74E-5

Figure 65. $\overline{u'^2v'}$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

$$u'(v'^2) / Ue^3$$

BOUNDARY m=1.5 STA C

RUN #61889.1951




$u'(v'^2) / Ue^3$ RANGES		$Ue=10.0$ m/s	
0	$>-3.42E-5$ $<-3.06E-5$	5	$>-1.63E-5$ $<-1.20E-5$
1	$>-3.06E-5$ $<-2.7E-5$	6	$>-1.20E-5$ $<-9.22E-6$
2	$>-2.7E-5$ $<-2.35E-5$	7	$>-9.22E-6$ $<-5.66E-6$
3	$>-2.35E-5$ $<-1.99E-5$	8	$>-5.66E-6$ $<-2.89E-6$
4	$>-1.99E-5$ $<-1.63E-5$	9	$>-2.89E-6$ $< 1.47E-6$

Figure 66. $\overline{u'v'^2}$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

BOUNDARY m=1.5 STA C

RUN #61989.0755




(u' ^ 2)w' / Uo ^ 3 RANGES	Uo=10.0 m/s
0 1>-5.26E-5 <-4.44E-5	5 1>-1.17E-5 <-3.52E-6
1 1>-4.44E-5 <-3.63E-5	6 1>-3.52E-6 < 4.67E-6
2 1>-3.63E-5 <-2.81E-5	7 1> 4.67E-6 < 1.20E-5
3 1>-2.81E-5 <-1.99E-5	8 1> 1.20E-5 < 2.1E-5
4 1>-1.99E-5 <-1.17E-5	9 1> 2.1E-5 < 2.92E-5

Figure 67. $u'^2 w'$ (Boundary Layer, Station C,
 $m = 1.5, \Delta = 0.25$)

$u'(w'^2) / Ue^3$

BOUNDARY $m=1.5$ STA C

RUN #61989.0755



$u'(w'^2) / Ue^3$ RANGES

Ue=10.0 m/s
0 1 > -4.45E-5 < -3.74E-5
1 1 > -3.74E-5 < -3.02E-5
2 1 > -3.02E-5 < -2.31E-5
3 1 > -2.31E-5 < -1.6E-5
4 1 > -1.6E-5 < -0.92E-6
5 1 > -0.92E-6 < -1.0E-6
6 1 > -1.0E-6 < 5.31E-6
7 1 > 5.31E-6 < 1.24E-5
8 1 > 1.24E-5 < 1.95E-5
9 1 > 1.95E-5 < 2.66E-5

Figure 68. $u'w'^2$ (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 0 DEGREES
 RUN# 61889.1951 & 61989.0755 PROBE POSITION: C
 BLOWING RATIO= 1.5 FREESTREAM VELOCITY(U)= 10 m/s




Figure 69. Streamwise Vorticity (Boundary Layer, Station C, $m = 1.5$, $\Delta = 0.25$)




Figure 70. $\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)




Figure 71. $\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)




Figure 72. $\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $\Delta = 0.25$)




Figure 73. u'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

$$v'^2 / Ue^2$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A'

RUN #60789.2054




Figure 74. v'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)





Figure 75. w'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

$$u'v' / Ue^2$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A'

RUN #60789.2054



$u'v' / Ue^2$ RANGES		$Ue=10.0$ m/s	
0	>-.00163 <-.00143	5	>-.000625 <-.000424
1	>-.00143 <-.00123	6	>-.000424 <-.000224
2	>-.00123 <-.00103	7	>-.000224 <-2.35E-5
3	>-.00103 <-.000825	8	>-2.35E-5 <.000177
4	>-.000825 <-.000625	9	>.000177 <.000377

Figure 76. $u'v'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)





Figure 77. $u'w'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

$$u'^3 / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A'

RUNS #60789.2054 and 60889.0854



u'^3 / Ue^3 RANGES		$Ue = 10.0$ m/s	
0	>-.000220 <-.0002	5	>-.0.05E-5 <-.07E-5
1	>-.0002 <-.000172	6	>-.0.07E-5 <-.20E-5
2	>-.000172 <-.000144	7	>-.0.20E-5 <-.94E-6
3	>-.000144 <-.000116	8	>-.0.94E-6 <.29E-5
4	>-.000116 <-.05E-5	9	>.29E-5 <.00E-5

Figure 78. u'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)




Figure 79. v'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)




Figure 80. w'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

$$(u'^2)v' / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A'

RUN #60789.2054





Figure 81. u'^2v' (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

$$u'(v'^2) / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A'

RUN #60789.2054



$u'(v'^2) / Ue^3$ RANGES

0	>-4.99E-5	<-4.44E-5
1	>-4.44E-5	<-3.89E-5
2	>-3.89E-5	<-3.34E-5
3	>-3.34E-5	<-2.79E-5
4	>-2.79E-5	<-2.25E-5
5	>-2.25E-5	<-1.7E-5
6	>-1.7E-5	<-1.15E-5
7	>-1.15E-5	<-5.99E-6
8	>-5.99E-6	<-5.03E-7
9	>-5.03E-7	< 4.88E-6


$Ue=10.0$ m/s

Figure 82. $u'v'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

$$(u'^2)w' / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A'

RUN #60889.0854



$(u'^2)w' / Ue^3$ RANGES $Ue=10.0$ m/s

0	>-4.78E-5	<-3.43E-5	5	> 1.97E-5	< 3.32E-5
1	>-3.43E-5	<-2.08E-5	6	> 3.32E-5	< 4.68E-5
2	>-2.08E-5	<-7.3E-6	7	> 4.68E-5	< 6.03E-5
3	>-7.3E-6	< 6.22E-6	8	> 6.03E-5	< 7.38E-5
4	> 6.22E-6	< 1.97E-5	9	> 7.38E-5	< 8.73E-5

Figure 83. u'^2w' (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)




Figure 84. $\overline{u'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A', $m = 0$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 60789.2054 & 60889.0854 PROBE POSITION: A'
 BLOWING RATIO= 0 FREESTREAM VELOCITY(U)= 10 m/s




Figure 85. Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station A', m = 0, Δ = 0.25)




Figure 86. $\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 87. $\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 88. w (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 89. u'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 90. v'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)





Figure 91. w'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)

$u'v' / Ue^2$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A''

RUN #60689.1107



$u'v' / Ue^2$ RANGES

	$Ue=10.0$ m/s
0 : >-.00169 <-.00147	5 : >-.000984 <-.000364
1 : >-.00147 <-.00124	6 : >-.000364 <-.000143
2 : >-.00124 <-.00102	7 : >-.000143 < 7.7E-5
3 : >-.00102 <-.000804	8 : > 7.7E-5 < .000297
4 : >-.000804 <-.000584	9 : > .000297 < .000510

Figure 92. $u'v'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)





Figure 93. $u'w'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)

$$u'^3 / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A''

RUNS #60689.1107 and 60789.0704



u'^3 / Ue^3 RANGES		Ue=10.0 m/s	
0	1 > -.000222 < -.000194	5	1 > -0.50E-5 < -5.87E-5
1	1 > -.000194 < -.000167	6	1 > -5.07E-5 < -3.15E-5
2	1 > -.000167 < -.00014	7	1 > -3.15E-5 < -4.37E-6
3	1 > -.00014 < -.000113	8	1 > -4.37E-6 < 2.20E-5
4	1 > -.000113 < -0.50E-5	9	1 > 2.20E-5 < 4.99E-5

Figure 94. u'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 95. v'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 96. w'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)

$$(u'^2)^{1/2} v' / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A''

RUN #60689.1107




Figure 97. $\overline{u'^2 v'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)





Figure 98. $u'v'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)

$$(u'^2)w' / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION A"

RUN #60789.0704



$(u'^2)w' / Ue^3$ RANGES		$Ue=10.0$ m/s	
0	$>-4.02E-5$	5	$> 3.17E-5$
1	$>-2.58E-5$	6	$> 4.6E-5$
2	$>-1.14E-5$	7	$> 6.04E-5$
3	$> 2.93E-6$	8	$> 7.48E-5$
4	$> 1.73E-5$	9	$> 8.91E-5$

Figure 99. $\overline{u'^2 w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)




Figure 100. $\overline{u'w'^2}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 60689.1107 & 60789.0704 PROBE POSITION: A''
 BLOWING RATIO= 0 FREESTREAM VELOCITY(U)= 10 m/s




Figure 101. Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station A'', $m = 0$, $\Delta = 0.25$)





Figure 102. $\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

vbar / Ue

DETAIL SURVEY 12 DEGREE VG m=0 STATION B


RUN #61089.0743



vbar / Ue RANGES		Ue=10.0 m/s	
0	>-.227 <-.184	5	>-.0154 <.0268
1	>-.184 <-.142	6	>.0268 <.0691
2	>-.142 <-.0999	7	>.0691 <.111
3	>-.0999 <-.0577	8	>.111 <.154
4	>-.0577 <-.0154	9	>.154 <.196

Figure 103. $\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, m = 0, $\Delta = 0.10$)

wbar / Ue
 DETAIL SURVEY 12 DEGREE VG m=0 STATION B
 RUN #61289.0813



wbar / Ue RANGES		Ue=10.0 m/s	
0	>-.292 <-.247	5	>-.0662 <-.021
1	>-.247 <-.202	6	>-.021 <.0242
2	>-.202 <-.157	7	>.0242 <.0694
3	>-.157 <-.111	8	>.0694 <.115
4	>-.111 <-.0662	9	>.115 <.16

Figure 104. w (Boundary Layer w/vortex, Downwash @ Centerline, Station B, m = 0, Δ = 0.10)




Figure 105. u'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

v'^2 / Ue^2

DETAIL SURVEY 12 DEGREE VG $m=0$ STATION B

RUN #61089.0743




Figure 106. v'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

w'^2 / Ue^2

DETAIL SURVEY 12 DEGREE VG $m=0$ STATION B

RUN #61289.0813




Figure 107. w'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)




Figure 108. $u'v'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

$u'w' / Ue^2$

DETAIL SURVEY 12 DEGREE VG $m=0$ STATION B

RUN #61289.0813




Figure 109. $u'w'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)





Figure 110. u'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

v'^3 / Ue^3

DETAIL SURVEY 12 DEGREE VG $m=0$ STATION B

RUN #61089.0743



v'^3 / Ue^3 RANGES		$Ue=10.0$ m/s	
0	>-.000753 <-.000625	5	>-.00011 <1.86E-5
1	>-.000625 <-.000496	6	>1.86E-5 <.000147
2	>-.000496 <-.000367	7	>.000147 <.000276
3	>-.000367 <-.000239	8	>.000276 <.000405
4	>-.000239 <-.00011	9	>.000405 <.000533

Figure 111. v'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)




Figure 112. w'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

$(u'^2)v' / Ue^3$
 DETAIL SURVEY 12 DEGREE VG $m=0$ STATION B
 RUN #61089.0743





Figure 113. u'^2v' (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

$$u'(v'^2) / Ue^3$$

DETAIL SURVEY 12 DEGREE VG m=0 STATION B


RUN #61089.0743



$u'(v'^2) / Ue^{1/3}$ RANGES		$Ue=10.0$ m/s			
0	$0 \rightarrow -.000149$	$<-.000133$	5	$5 \rightarrow -7.00E-5$	$<-5.51E-5$
1	$1 \rightarrow -.000133$	$<-.000110$	6	$6 \rightarrow -5.51E-5$	$<-3.95E-5$
2	$2 \rightarrow -.000110$	$<-.000102$	7	$7 \rightarrow -3.95E-5$	$<-2.30E-5$
3	$3 \rightarrow -.000102$	$<-0.64E-5$	8	$8 \rightarrow -2.30E-5$	$<-0.10E-6$
4	$4 \rightarrow -0.64E-5$	$<-7.00E-5$	9	$9 \rightarrow -0.10E-6$	$<7.47E-6$

Figure 114. $u'v'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

$(u'^2)w' / Ue^3$
 DETAIL SURVEY 12 DEGREE VG $m=0$ STATION B
 RUN #61289.0813



$(u'^2)w' / Ue^3$ RANGES

0	1	2	3	4	5	6	7	8	9
-9.5E-5	-7.7E-5	-5.9E-5	-4.1E-5	-2.3E-5	-5.0E-6	-1.29E-5	1.29E-5	3.09E-5	4.89E-5
					$Ue=10.0$ m/s				

Figure 115. $\overline{u'^2 w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)




Figure 116. $u'w'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 0$, $\Delta = 0.10$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 61289.0743 & 61289.0813 PROBE POSITION: B
 BLOWING RATIO= 0 FREESTREAM VELOCITY(U)= 10 m/s




Figure 117. Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station B, m = 0, $\Delta = 0.10$)




Figure 118. $\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 119. $\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, m = 0, $\Delta = 0.25$)




Figure 120. $\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 121. u'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 122. v'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 123. w'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 124. $u'v'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 125. $u'w'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)




Figure 126. u'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)

$$v'^3 / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION C

RUN #60889.2049





Figure 127. v'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)

w'^3 / Ue^3

12 DEGREE VORTEX GENERATOR $m=0$ STATION C

RUN #60989.1219



w'^3 / Ue^3 RANGES		$Ue=10.0$ m/s	
0	$1 > -6.00E-5$	5	$1 > -1.56E-6$
1	$1 > -4.89E-5$	6	$1 > 1.03E-5$
2	$1 > -3.71E-5$	7	$1 > 2.21E-5$
3	$1 > -2.52E-5$	8	$1 > 3.4E-5$
4	$1 > -1.34E-5$	9	$1 > 4.58E-5$
			$1 > 5.76E-5$

Figure 128. w'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)





Figure 129. $u'^2 v'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)

$$u'(v'^2) / Ue^3$$

12 DEGREE VORTEX GENERATOR m=0 STATION C

RUN #60889.2049



u'(v'^2) / Ue^3 RANGES


Ue=10.0 m/s
0 1 > -7.18E-5 < -6.39E-5
1 1 > -6.39E-5 < -5.6E-5
2 1 > -5.6E-5 < -4.82E-5
3 1 > -4.82E-5 < -4.03E-5
4 1 > -4.03E-5 < -3.24E-5
5 1 > -3.24E-5 < -2.45E-5
6 1 > -2.45E-5 < -1.67E-5
7 1 > -1.67E-5 < -8.0E-6
8 1 > -8.0E-6 < -9.31E-7
9 1 > -9.31E-7 < 6.94E-6

Figure 130. $u'v'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, m = 0, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$

12 DEGREE VORTEX GENERATOR $m=0$ STATION C

RUN #60989.1219



$Ue=10.0 \text{ m/s}$

$(u'^2)w' / Ue^3 \text{ RANGES}$

5	>	4.17E-6	<	1.53E-5
6	>	1.53E-5	<	2.64E-5
7	>	2.64E-5	<	3.74E-5
8	>	3.74E-5	<	4.85E-5
9	>	4.85E-5	<	5.96E-5


0	>	-5.13E-5	<	-4.82E-5
1	>	-4.82E-5	<	-2.91E-5
2	>	-2.91E-5	<	-1.0E-5
3	>	-1.0E-5	<	-6.91E-6
4	>	-6.91E-6	<	4.17E-6

Figure 131. $\overline{u'^2 w'}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)

$$u'(w'^2) / Ue^3$$

12 DEGREE VORTEX GENERATOR $m=0$ STATION C

RUN #60989.1219



$u'(w'^2) / Ue^3$ RANGES

Contour Value	Range
0	$-0.000100 < -0.000100$
1	$-0.000100 < -0.000100$
2	$-0.000100 < -0.000100$
3	$-0.000100 < -0.000100$
4	$-0.000100 < -0.000100$
5	$-0.000100 < -0.000100$
6	$-0.000100 < -0.000100$
7	$-0.000100 < -0.000100$
8	$-0.000100 < -0.000100$
9	$-0.000100 < -0.000100$

$Ue = 10.0 \text{ m/s}$

Figure 132. $u'w'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station C, $m = 0$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 60889.2049 & 60989.1219 PROBE POSITION: C
 BLOWING RATIO= 0 FREESTREAM VELOCITY(U)= 10 m/s




Figure 133. Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station C, m = 0, $\Delta = 0.25$)

$\bar{u} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0$ STATION B
 RUNS #72189.0931 and 72289.0831





Figure 134. $\bar{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$)

$\bar{v} / U_e$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72189.0931



$U_e = 10.0 \text{ m/s}$

$\bar{v} / U_e$ RANGES

0 : >-.158 <-.122	5 : >.0103 <.0535
1 : >-.122 <-.0873	6 : >.0535 <.0886
2 : >-.0873 <-.0521	7 : >.0886 <.124
3 : >-.0521 <-.0169	8 : >.124 <.159
4 : >-.0169 <.0103	9 : >.159 <.194

Figure 135. $\bar{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$)

$\bar{w} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0$ STATION B
 RUN #72289.0831




Figure 136. $\bar{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$)

u'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @CL m=0 STATION B

RUNS #72189.0031 and 72289.0031




Figure 137. u'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

v'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72189.0931




Figure 138. v'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

w'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72289.0831




Figure 139. w'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

$u'v' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0$ STATION B

RUN #72189.0931





Figure 140. $u'v'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$)

$u'w' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0$ STATION B

RUN #72289.0831



$u'w' / Ue^2$ RANGES $Ue=10.0$ m/s

0	>-.00146	<-.00123	5	>-.00020	<-.4.39E-5
1	>-.00123	<-.00099	6	>-.4.39E-5	<.000193
2	>-.00099	<-.000753	7	>.000193	<.000429
3	>-.000753	<-.000517	8	>.000429	<.000666
4	>-.000517	<-.00028	9	>.000666	<.000902

Figure 141. $u'w'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0$, $\Delta = 0.25$)

u'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUNS #72189.0931 and 72289.0831




Figure 142. u'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

$$v'^3 / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72189.0931





Figure 143. v'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, Δ = 0.25)

w'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72289.0831



w'^3 / Ue^3 RANGES

0 : >-.000175	<-.000131	Ue=10.0 m/s	5 : > 4.49E-5	< 8.88E-5
1 : >-.000131	<-.00008E-5		6 : > 8.88E-5	< .000133
2 : >-.00008E-5	<-.00004.29E-5		7 : > .000133	< .000177
3 : >-.00004.29E-5	< 1.04E-5		8 : > .000177	< .000221
4 : > 1.04E-6	< 4.49E-5		9 : > .000221	< .000264

Figure 144. w'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

$(u'^2)v' / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B
 RUN #72189.0931





Figure 145. $\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

$u'(v'^2) / Ue^3$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72189.0931



$u'(v'^2) / Ue^3$ RANGES

0	> -0.000109	< -9.74E-5	5	> -5.00E-5	< -3.92E-5
1	> -9.74E-5	< -8.58E-5	6	> -3.92E-5	< -2.75E-5
2	> -8.58E-5	< -7.41E-5	7	> -2.75E-5	< -1.59E-5
3	> -7.41E-5	< -6.25E-5	8	> -1.59E-5	< -4.23E-6
4	> -6.25E-5	< -5.00E-5	9	> -4.23E-6	< 7.41E-6

Ue=10.0 m/s

Figure 146. $u'v'^2$ (Boundary layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B
 RUN #72289.0831




Figure 147. u'^2w' (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

$$u'(w'^2) / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0 STATION B

RUN #72289.0831




Figure 148. $|u'w'|^2$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 72189.0931 & 72289.0831 PROBE POSITION: B
 BLOWING RATIO= 0 FREESTREAM VELOCITY(U)= 10 m/s




Figure 149. Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0, Δ = 0.25)





Figure 150. $\bar{u}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$\bar{v} / U_e$

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B


RUN #71089.1212



$\bar{v} / U_e$ RANGES		$U_e = 10.0 \text{ m/s}$	
0 : >-.143	<-.100	5 : >.0331	<.0602
1 : >-.100	<-.0724	6 : >.0602	<.103
2 : >-.0724	<-.0372	7 : >.103	<.130
3 : >-.0372	<-.00209	8 : >.130	<.174
4 : >-.00209	<.0331	9 : >.174	<.209

Figure 151. $\bar{v}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$\bar{w} / U_e$
 DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B
 RUN #71189.122



$\bar{w} / U_e$ RANGES		$U_e = 10.0 \text{ m/s}$	
0	:>-.217 <-.178	5	:>-.0182 <.0216
1	:>-.178 <-.138	6	:>.0216 <.0814
2	:>-.138 <-.0979	7	:>.0814 <.101
3	:>-.0979 <-.0581	8	:>.101 <.141
4	:>-.0581 <-.0182	9	:>.141 <.181

Figure 152. $\bar{w}$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

u'^2 / Ue^2

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUNS #71089.1212 and 71189.122





Figure 153. u'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

v'^2 / Ue^2

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUN #71089.1212



v'^2 / Ue^2 RANGES $Ue=10.0$ m/s

0 1 > .0011 < .00227	5 1 > .00553 < .00686
1 1 > .00227 < .00155	6 1 > .00686 < .00818
2 1 > .00155 < .00288	7 1 > .00818 < .00951
3 1 > .00288 < .0042	8 1 > .00951 < .0108
4 1 > .0042 < .00553	9 1 > .0108 < .0122

Figure 154. v'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

w'^2 / Ue^2

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUN #71189.122




Figure 155. w'^2 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$u'v' / Ue^2$

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUN #71089.1212





Figure 156. $u'v'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$u'w' / Ue^2$

DETAIL SURVEY 12 DEGREE VG m=1.5 STATION B

RUN #71189.122




$u'w' / Ue^2$ RANGES		$Ue=10.0$ m/s	
0	>-.00203 <-.00230	5	>-.00055 <-.00055
1	>-.00230 <-.00192	6	>-.00055 <.000362
2	>-.00192 <-.00146	7	>.000362 <.000019
3	>-.00146 <-.00101	8	>.000019 <.00120
4	>-.00101 <-.00055	9	>.00120 <.00173

Figure 157. $u'w'$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, m = 1.5, $\Delta = 0.10$)

u'^3 / Ue^3

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUNS #71089.1212 and 71189.122



u'^3 / Ue^3 RANGES		$Ue=10.0$ m/s	
0	>-.000400 <-.000352	5	>-.000127 <-.12E-5
1	>-.000352 <-.000296	6	>-.12E-5 <-.151E-5
2	>-.000296 <-.00024	7	>-.151E-5 < 4.11E-5
3	>-.00024 <-.000103	8	> 4.11E-5 < 9.72E-5
4	>-.000103 <-.000127	9	> 9.724E-5 < .000153

Figure 158. u'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

v'^3 / Ue^3

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUN #71089.1212




Figure 159. v'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

w'^3 / Ue^3

DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B

RUN #71189.122




Figure 160. w'^3 (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$(u'^2)v' / Ue^3$
 DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B
 RUN #71089.1212





Figure 161. u'^2v' (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$u'(v'^2) / Ue^3$
 DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B
 RUN #71089.1212



$u'(v'^2) / Ue^3$ RANGES $Ue=10.0$ m/s
 0 > -0.0013 < -0.00109 5 $> -2.13E-5$ $< 4.94E-7$
 1 > -0.00109 $< -8.67E-5$ 6 $> 4.94E-7$ $< 2.23E-5$
 2 $> -8.67E-5$ $< -6.49E-5$ 7 $> 2.23E-5$ $< 4.41E-5$
 3 $> -6.49E-5$ $< -4.31E-5$ 8 $> 4.41E-5$ $< 6.59E-5$
 4 $> -4.31E-5$ $< -2.13E-5$ 9 $> 6.59E-5$ $< 8.77E-5$

Figure 162. $u'v'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$(u'^2)w' / Ue^3$
 DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B
 RUN #71189.122




Figure 163. u'^2w' (Boundary Layer w/vortex, Downwash @
 Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$u'(w'^2) / Ue^3$
 DETAIL SURVEY 12 DEGREE VG $m=1.5$ STATION B
 RUN #71189.122




Figure 164. $u'w'^2$ (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)




Figure 165. Streamwise Vorticity (Boundary Layer w/vortex, Downwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.10$)

$\bar{u} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B
 RUNS #60189.1156 and 60289.0927




Figure 166. $\bar{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

vbar / Ue

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0.5 STATION B

RUN #60189.1156




Figure 167. $\bar{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

wbar / Ue

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0.5 STATION B

RUN #60289.0927





Figure 168. $\bar{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

$$u'^2 / Ue^2$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0.5 STATION B

RUNS #60189.1156 and 60289.0927




u'^2 / Ue^2 RANGES		Ue=10.0 m/s	
0	> .00068 < 8.32E-6	5	> .00276 < .00345
1	> 8.32E-6 < .000697	6	> .00345 < .00414
2	> .000697 < .00139	7	> .00414 < .00483
3	> .00139 < .00207	8	> .00483 < .00552
4	> .00207 < .00278	9	> .00552 < .00621

Figure 169. u'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0.5, $\Delta = 0.25$)

v'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUN #60189.1156




v'^2 / Ue^2 RANGES		$Ue=10.0$ m/s	
0 1 > .000736	< 6.02E-6	5 1 > .00297	< .00371
1 1 > 6.02E-6	< .000748	6 1 > .00371	< .00446
2 1 > .000748	< .00149	7 1 > .00446	< .0052
3 1 > .00149	< .00223	8 1 > .0052	< .00594
4 1 > .00223	< .00297	9 1 > .00594	< .00668

Figure 170. v'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

w'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUN #60289.0927



w'^2 / Ue^2 RANGES $Ue=10.0$ m/s

0	>-.000479	< 6.13E-6	5	>.00195	< .00243
1	> 6.13E-6	< .000491	6	>.00243	< .00292
2	>.000491	< .000976	7	>.00292	< .0034
3	>.000976	< .00146	8	>.0034	< .00389
4	>.00146	< .00195	9	>.00389	< .00437

Figure 171. w'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

$u'v' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUN #60189.1156




Figure 172. $u'v'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

$u'w' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUN #60289.0927




Figure 173. $u'w'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

u'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUNS #60189.1156 and 60289.0927




Figure 174. u'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

v'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUN #60189.1156




Figure 175. v'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

w'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B

RUN #60289.0927




Figure 176. w'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

$(u'^2)v' / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B
 RUN #60189.1156





Figure 177. $\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

$$u'(v'^2) / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0.5 STATION B

RUN #60189.1156



$u'(v'^2) / U_0 \wedge 3$ RANGES		$U_0=10.0$ m/s			
0	>-9.69E-5	<-8.64E-5	5	>-4.45E-5	<-3.41E-5
1	>-8.64E-5	<-7.59E-5	6	>-3.41E-5	<-2.36E-5
2	>-7.59E-5	<-6.55E-5	7	>-2.36E-5	<-1.31E-5
3	>-6.55E-5	<-5.5E-5	8	>-1.31E-5	<-2.64E-6
4	>-5.5E-5	<-4.45E-5	9	>-2.64E-6	< 7.03E-6

Figure 178. $\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0.5, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=0.5$ STATION B
 RUN #60289.0927





Figure 179. $\overline{u'^2 w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 0.5$, $\Delta = 0.25$)

$u'(w'^2) / Ue^3$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=0.5 STATION B

RUN #60289.0927



$u'(w'^2) / Ue^3$ RANGES

0 : > -7.53E-5	< -6.27E-5	Ue=10.0 m/s
1 : > -6.27E-5	< -5.01E-5	5 : > -1.23E-5
2 : > -5.01E-5	< -3.75E-5	6 : > 3.45E-7
3 : > -3.75E-5	< -2.49E-5	7 : > 1.29E-5
4 : > -2.49E-5	< -1.23E-5	8 : > 2.55E-5
		9 : > 3.01E-5
		10 : > 5.07E-5

Figure 180. $u'w'^2$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0.5, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx)
 RUN# 60189.1156 & 60289.0927
 BLOWING RATIO= .5
 VORT. GEN. ANGLE= 12 DEGREES
 PROBE POSITION: B
 FREESTREAM VELOCITY(U)= 10 m/s




Figure 181. Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 0.5, Δ = 0.25)

$\bar{u} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=1.5$ STATION B
 RUNS #60389.0655 and 60389.1901





Figure 182. $\bar{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

$\bar{v} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=1.5$ STATION B
 RUN #60389.0655



vbar / Ue RANGES		Ue=10.0 m/s			
0	>-.194	<-.155	5	>.00224	<.0415
1	>-.155	<-.116	6	>.0415	<.0800
2	>-.116	<-.0763	7	>.0800	<.12
3	>-.0763	<-.037	8	>.12	<.159
4	>-.037	<.00224	9	>.159	<.199

Figure 183. $\bar{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

wbar / Ue

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.1901




Figure 184. $\bar{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

u'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=1.5$ STATION B

RUNS #60389.0655 and 60389.1901




Figure 185. u'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

v'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.0655




Figure 186. $\overline{v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

w'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.1901




Figure 187. w'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

$u'v' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.0655




Figure 188. $u'v'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

$u'w' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=1.5$ STATION B

RUN #60389.1901




Figure 189. $u'w'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

u'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=1.5$ STATION B

RUNS #60389.0655 and 60389.1901




Figure 190. u'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

V'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.0655




Figure 191. V'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

w'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=1.5$ STATION B

RUN #60389.1901




Figure 192. w'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

$$(u'^2)v' / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.0655




Figure 193. $\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

$u'(v'^2) / Ue^3$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.0655




Figure 194. $\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B
 RUN #60389.1901




Figure 195. $\overline{u'^2 w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

$u'(w'^2) / Ue^3$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=1.5 STATION B

RUN #60389.1901




Figure 196. $u'w'^2$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 1.5, $\Delta = 0.25$)

STREAMWISE VORTICITY (ω_x)
 RUN# 60389.0655 & 60389.1901
 BLOWING RATIO= 1.5
 VORT. GEN. ANGLE= 12 DEGREES
 PROBE POSITION: B
 FREESTREAM VELOCITY(U)= 10 m/s




Figure 197. Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 1.5$, $\Delta = 0.25$)

$\bar{u} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=2.5$ STATION B
 RUNS #60489.0652 and 60489.1856




Figure 198. $\bar{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

$\bar{v} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=2.5$ STATION B
 RUN #60489.0652




Figure 199. $\bar{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

$\bar{w} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=2.5$ STATION B
 RUN #60489.1856




Figure 200. $\bar{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

u'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=2.5$ STATION B

RUNS #60489.0652 and 60489.1856




Figure 201. u'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

v'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=2.5$ STATION B

RUN #60489.0652




Figure 202. v'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

w'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=2.5$ STATION B

RUN #60489.1856





Figure 203. w'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

$u'v' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.0652



$u'v' / Ue^2$ RANGES

Range	Value
0	$0.00317 < -0.00262$
1	$0.00262 < -0.00208$
2	$0.00208 < -0.00153$
3	$0.00153 < -0.000989$
4	$0.000989 < -0.000446$

$Ue = 10.0 \text{ m/s}$

Range	Value
5	$0.000446 < 9.84E-5$
6	$9.84E-5 < 0.000642$
7	$0.000642 < 0.00119$
8	$0.00119 < 0.00173$
9	$0.00173 < 0.00227$

Figure 204. $u'v'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

$u'w' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.1856




Figure 205. $\overline{u'w'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

u'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUNS #60489.0652 and 60489.1856




Figure 206. u'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

v'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.0652





Figure 207. v'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

w'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.1856



w'^3 / Ue^3 RANGES

Range	Value
0	1.0×10^{-5} to 1.0×10^{-4}
1	1.0×10^{-4} to 1.0×10^{-3}
2	1.0×10^{-3} to 1.0×10^{-2}
3	1.0×10^{-2} to 1.0×10^{-1}
4	1.0×10^{-1} to 1.0×10^0

Ue=10.0 m/s

Range	Value
5	1.0×10^{-5} to 1.0×10^{-4}
6	1.0×10^{-4} to 1.0×10^{-3}
7	1.0×10^{-3} to 1.0×10^{-2}
8	1.0×10^{-2} to 1.0×10^{-1}
9	1.0×10^{-1} to 1.0×10^0

Figure 208. w'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

$$(u'^2)v' / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.0652




Figure 209. u'^2v' (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

$u'(v'^2) / Ue^3$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.0652




Figure 210. $\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

$(u'^2)w' / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B
 RUN #60489.1856





Figure 211. u'^2w' (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

$u'(w'^2) / Ue^3$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=2.5 STATION B

RUN #60489.1856



$u'(w'^2) / Ue^3$ RANGES

0 : > -8.54E-5	< -6.78E-5	5 : > 2.36E-6	< 1.99E-5
1 : > -6.78E-5	< -5.03E-5	6 : > 1.99E-5	< 3.75E-5
2 : > -5.03E-5	< -3.27E-5	7 : > 3.75E-5	< 5.5E-5
3 : > -3.27E-5	< -1.52E-5	8 : > 5.5E-5	< 7.26E-5
4 : > -1.52E-5	< 2.38E-6	9 : > 7.26E-5	< 9.01E-5

Ue=10.0 m/s

Figure 212. $\overline{u'w'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 2.5, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 60489.0652 & 60489.1856 PROBE POSITION: B
 BLOWING RATIO= 2.5 FREESTREAM VELOCITY(U)= 10 m/s




Figure 213. Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 2.5$, $\Delta = 0.25$)

$\bar{u} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B
 RUNS #60589.0715 and 60589.1918




Figure 214. $\bar{u}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

$\bar{v} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B
 RUN #60589.0715




Figure 215. $\bar{v}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

$\bar{w} / U_e$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B
 RUN #60509.1918




Figure 216. $\bar{w}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

u'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B

RUNS #60589.0715 and 60589.1918




Figure 217. u'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

v'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B

RUN #60589.0715




Figure 218. v'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

w'^2 / Ue^2

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B

RUN #60589.1918




Figure 219. w'^2 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

$u'v' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B

RUN #60589.0715




Figure 220. $u'v'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

$u'w' / Ue^2$

12 DEGREE VORTEX GENERATOR UPWASH @ CL $m=3.5$ STATION B

RUN #60589.1918





Figure 221. $u'w'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

$$u'^3 / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B

RUNS #60589.0715 and 60589.1918



u'^3 / Ue^3 RANGES		$Ue=10.0$ m/s	
0	:>-.000317 <-.000189	5	:>.000323 <.000451
1	:>-.000189 <-6.14E-5	6	:>.000451 <.000579
2	:>-6.14E-5 < 6.66E-5	7	:>.000579 <.000707
3	:> 6.66E-5 <.000195	8	:>.000707 <.000835
4	:>.000195 <.000323	9	:>.000835 <.000963

Figure 222. u'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 3.5, $\Delta = 0.25$)

v'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B

RUN #60589.0715




Figure 223. v'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 3.5, $\Delta = 0.25$)

w'^3 / Ue^3

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B

RUN #60589.1918





Figure 224. w'^3 (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 3.5, $\Delta = 0.25$)

$$(u'^2)v' / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B

RUN #60589.0715



(u'^2)v' / Ue^3 RANGES

Ue=10.0 m/s
0 : >-.000306 <-.000292
1 : >-.000292 <-.000197
2 : >-.000197 <-.000103
3 : >-.000103 <-0.47E-6
4 : >-0.47E-6 < 0.6E-5
5 : > 0.6E-5 < .000181
6 : > .000181 < .000275
7 : > .000275 < .00037
8 : > .00037 < .000464
9 : > .000464 < .000559

Figure 225. $\overline{u'^2v'}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 3.5, $\Delta = 0.25$)

$u'(v'^2) / Ue^3$
 12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B
 RUN #60589.0715




Figure 226. $\overline{u'v'^2}$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 3.5, $\Delta = 0.25$)

$$(u'^2)w' / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B

RUN #60589.1918





Figure 227. $\overline{u'^2}w'$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, m = 3.5, $\Delta = 0.25$)

$$u'(w'^2) / Ue^3$$

12 DEGREE VORTEX GENERATOR UPWASH @ CL m=3.5 STATION B

RUN #60589.1918



$Ue = 10.0 \text{ m/s}$

$u'(w'^2) / Ue^3 \text{ RANGES}$

0	>-.000179	<-.000134	5	> 4.99E-5	< 9.57E-5
1	>-.000134	<-.000089	6	> 9.57E-5	< .000142
2	>-.000089	<-.000044	7	> .000142	< .000187
3	>-.000044	<-.000000	8	> .000187	< .000233
4	>-.000000	<.000000	9	> .000233	< .000279

Figure 228. $u'w'^2$ (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

STREAMWISE VORTICITY (Wx) VORT. GEN. ANGLE= 12 DEGREES
 RUN# 60589.0715 & 60589.1918 PROBE POSITION: B
 BLOWING RATIO= 3.5 FREESTREAM VELOCITY(U)= 10 m/s




Figure 229. Streamwise Vorticity (Boundary Layer w/vortex, Upwash @ Centerline, Station B, $m = 3.5$, $\Delta = 0.25$)

LIST OF REFERENCES

1. Green, J.G., Turbulence Structure Interaction Between an Embedded Vortex and Wall Jet, Master's Thesis, Naval Postgraduate School, Monterey, California, June 1989.
2. Joseph, S.L., The Effects of an Embedded Vortex on a Film Cooled Turbulent Boundary Layer, Master's Thesis, Naval Postgraduate School, Monterey, California, December 1986.
3. Shabaka, I.M.M.A., Mehta, R.D., and Bradshaw, P., "Longitudinal Vortices Embedded in Turbulent Boundary Layers. Part I. Single Vortex," Journal of Fluids Mechanics, Vol. 155, pp. 37-57, 1985.
4. Cutler, A.D., and Bradshaw, P., "The Interaction Between a Strong Longitudinal Vortex and a Turbulent Boundary Layer," AIAA paper No. AIAA-86-1071, 1986.
5. Mehta, R.D., and Bradshaw, P., "Longitudinal Vortices Embedded in Turbulent Boundary Layers, Part 2. Vortex Pair with Common Flow Upwards," Journal of Fluid Mechanics, Vol. 188, pp. 529-546, 1988.
6. Eibeck, P.A., and Eaton, J.K., "An Experimental Investigation of the Heat Transfer Effects of a Longitudinal Vortex Embedded in a Turbulent Boundary Layer," Stanford University Thermosciences Division Report MD-48, 1985.
7. Westphal, R.V., Pauley, W.R., and Eaton, J.K., "Interaction Between a Vortex and a Turbulent Boundary Layer, Part I: Mean Flow Evolution and Turbulence Properties," NASA Technical Memorandum 88361, 1987.
8. Skow, A.M., and Peake, D.J., "Control of the Forebody Vortex Orientation by Asymmetric Air Injection: (Part A) Application to Enhanced Departure/Spin Recovery of Fighter Aircraft and (Part B) Details of the Flow Structure, Von Karman Institute Special Course on Aerodynamic Characteristics of Controls Report No.711," March 1983.
9. Heffernan, K.G., Trailing Vortex Attenuation Devices, Master's Thesis, Naval Postgraduate School, Monterey, California, June 1985.

10. Schwartz, G.E., Control of Embedded Vortices Using Wall Jets, Master's Thesis, Naval Postgraduate School, Monterey, California, September 1988.
11. Iwanski K., Ng, T., and Nelson, R., "An Experimental Investigation of Delta Wing Vortex Flow With and Without External Jet Blowing," paper presented at the 27th Aerospace Sciences Meeting, Reno, Nevada, January 1989.
12. Visser, K., Nelson, R., and Ng, T., "A Flow Visualization and Aerodynamic Force Data Evaluation of Spanwise Blowing on Full and Half Span Delta Wings," paper presented at the 27th Aerospace Sciences Meeting, Reno, Nevada, January 1989.
13. Ligrani, P.M., and Schwartz, G.E., "Control of Embedded Vortices Using Wall Jets," submitted for Physics of Fluids, 1989.
14. Ligrani, P.M., and Williams, W.W., "Effects of an Embedded Vortex on Injectant from a Single Film Cooling Hole in a Turbulent Boundary Layer," to appear in ASME Transactions Journal of Turbomachinery, 1989.
15. Subramanian, C.S., Green, J.G., and Ligrani, P.M., "Cross-Wire Data Acquisition and Turbulence Data Processing using HP 9836S series 200 Computer." Technical Report #NPS ME#1.89 for the Naval Postgraduate School, Monterey, California, February 1989.
16. Collis, D.C., and Williams, M.J., "Two-Dimensional Convection from Heated Wires at Low Reynolds Numbers," Journal of Fluid Mechanics, Vol. 6, pp. 357-370, 1959.

BIBLIOGRAPHY

- Bradshaw, P., An Introduction to Turbulence and Its Measurement, Pergamon Press, Inc., 1971.
- Craig, D.W., Effect of Vortex Circulation on Injectant from a Single Film Cooling Hole and a Row of Film Cooling Holes in a Turbulent Boundary Layer, Part I: Injection Beneath the Bortex Downwash, Master's Thesis, Naval Postgraduate School, Monterey, California, June 1989.
- Goldstein, R.J., Fluid Mechanics Measurements, Hemisphere Publishing Corp., 1983.
- Hinze, J.O., Turbulence, 2nd Edition, McGraw-Hill, 1975.
- Librani, P.M., Ortiz, A., Joseph, S.L. and Evans, D.L., "Effects of Embedded Vortices of Film Cooled Boundary Layers," ASME Transactions Journal of Turbomachinery, Vol. 111, No. 1, pp. 71-77, 1989.
- Perry, A.E., Hot-Wire Anemometry, Oxford University Press, 1982.
- Schlichting H., Boundary-Layer Theory, 7th Edition, McGraw-Hill, 1979.
- Subramanian, C.S., Ligrani, P.M., Green, J.G., Doner, W., and Pisut, K., Development and Structure of a Film Cooling Jet in a Turbulent Boundary Layer with Heat Transfer, Transport Phenomena and Dynamics in Rotating Machinery, Hemisphere Publishing Co., 1990.
- White, F.M., Fluid Mechanics, 2nd Edition, McGraw-Hill, 1979.

INITIAL DISTRIBUTION LIST

	No. Copies
1. Defense Technical Information Center Cameron Station Alexandria, Virginia 22304-6145	2
2. Library, Code 0142 Naval Postgraduate School Monterey, California 93943-5002	2
3. Department Chairman, Code 69 Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943-5000	1
4. Professor Phillip M. Ligrani, Code 69Li Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943-5000	8
5. Professor Chelakara S. Subramanian, Code 69Su Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943-5000	5
6. LT William D. Doner, USN 15227 SE Oatfield Road Milwaukie, Oregon 97267	2
7. Naval Engineering Circular Office Code 34 Naval Postgraduate School Monterey, California 93943-5000	1