

TIP: FILE COPY

REPORT NO. NADC-86089-60

ODH
①

AD-A223 363



FLAMMABILITY PERFORMANCE OF FABRICS USED FOR CLOTHING AND SEAT KIT COVERS

Tara Larson and Mike Markushewski
Aircraft and Crew Systems Technology Directorate
NAVAL AIR DEVELOPMENT CENTER
Warminster, PA 19974-5000

DECEMBER 1985

FINAL REPORT

Approved for Public Release; Distribution is Unlimited

20030206125

Prepared for
NAVAL AIR SYSTEMS COMMAND
Department of the Navy
Washington, DC 20381

90-08 '22-188

NOTICES

REPORT NUMBERING SYSTEM - The numbering of technical project reports issued by the Naval Air Development Center is arranged for specific identification purposes. Each number consists of the Center acronym, the calendar year in which the number was assigned, the sequence number of the report within the specific calendar year, and the official 2-digit correspondence code of the Command Office or the Functional Directorate responsible for the report. For example, Report No. NADC-86015-20 indicates the fifteenth Center report for the year 1986, and prepared by the Systems Directorate. The numerical codes are as follows:

CODE	OFFICE OR DIRECTORATE
00	Commander, Naval Air Development Center
01	Technical Director, Naval Air Development Center
02	Comptroller
10	Directorate Command Projects
20	Systems Directorate
30	Sensors & Avionics Technology Directorate
40	Communications and Navigation Technology Directorate
50	Software Computer Directorate
60	Aircraft & Crew Systems Technology Directorate
70	Planning Assessment Resources
80	Engineering Support Group

PRODUCT ENDORSEMENT - The discussion or instructions concerning commercial products herein do not constitute an endorsement by the Government nor do they convey or imply the license or right to use such products.

APPROVED BY: 

DATE: 29 December 1986

TEST. GALT
APT. W. C. C. C.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified		1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION AVAILABILITY OF REPORT Approved for Public Release; Distribution is Unlimited	
1c. DECLASSIFICATION/DOWNGRADING SCHEDULE			
4. PERFORMING ORGANIZATION REPORT NUMBER NADO-86089-60		5. MONITORING ORGANIZATION REPORT NUMBER N/A	
6a. NAME OF PERFORMING ORGANIZATION Naval Air Development Center	6b. OFFICE SYMBOL (if applicable) 6031	7a. NAME OF MONITORING ORGANIZATION N/A	
6c. ADDRESS (City, State, and ZIP Code) Warminster, PA 18974		7b. ADDRESS (City, State, and ZIP Code) N/A	
8a. NAME OF FUNDING SPONSORING ORGANIZATION Naval Air Systems Command	8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code) Washington, D.C. 20361		10. SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO	PROJECT NO
		TASK NO	WORK UNIT ACCESSION NO
11. TITLE (Include Security Classification) FLAMMABILITY PERFORMANCE OF FABRICS USED FOR CLOTHING AND SEAT KIT COVERS			
12. PERSONAL AUTHOR(S) Tara Larson and Mike Markushewski			
13a. TYPE OF REPORT Final	13b. TIME COVERED FROM TO	14. DATE OF REPORT (Year, Month, Day)	15. PAGE COUNT
16. SUPPLEMENTARY NOTES			
17. COSAT CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB GROUP	
		Flammability Clothing, protective - clothing, Nomex Fabrics, Seat Kits, Knit, Nylon, Cotton, Leather, Fibers	
19. ABSTRACT (Continue on reverse if necessary and identify by block number)			
An important characteristic of the clothing worn by naval airmen is protection from fire and flame be provided. This protection factor is dependent upon the type of material used and any layering that may occur by wearing more than one piece of equipment at a time. In this report, the flammability of the fabrics used for aviator clothing and ejection seat kit covers in the Naval aviation community are examined according to type of material used. They are then categorized by the degree of protection that is provided against flammability.			
20. DISTRIBUTION AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED, LIMITED ☒ SAME AS RPT ☐ DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION	
22a. NAME OF RESPONSIBLE INDIVIDUAL Tara Larson		22b. TELEPHONE (Include Area Code) 215-441-3763	22c. OFFICE SYMBOL 6031

DISCUSSION

The following summary and chart present the current fabrics in use by the fleet in clothing and seat kits, and describes the flammability characteristics of these fabrics. Information ranking each of these fabrics against each other, according to flammability, could not be found at this time. Therefore, the chart is arranged into three categories which have decreasing flammability performance.

Category I contains groups which are variations of Nomex, the variation usually being in weight (oz./yd²) and type of weave or knit. Nomex requires very high temperatures to initiate burning, will char without melting, self extinguishes itself upon removal from the heat source and is also durable with good abrasion resistant characteristics.

Category II is comprised of the items made from leather. Leather is flame resistant, shrinks when in contact with the heat source and is self extinguishing.

Category III contains the nylon and cotton fabrics currently in use on some of the clothing items. All of these fabrics are flammable and cannot withstand high temperatures. Nylon will melt upon contact with the heat source and self extinguish upon removal. Cotton will burn without melting, producing ash and will continue to burn after the source of flame has been removed.

When evaluating the flammability protection of a fabric to be used for clothing, the protection provided to the body must include consideration of the heat and time factor values before the ignition of the fabric. Burns will result if the skin temperature is held above 150°F for one second (Hilado p. 27). In a study conducted by Alice Stoll and Maria Chianta, both the tolerance time to absorbed thermal energy, and the protection provided to the skin by specific fabrics, were evaluated. From this study, the benefit of multiple layers of protective fabric was shown and a ranking of the tested fire resistant fabrics was established. The listing of fabrics primarily contains variations of Nomex and indicates better protection being provided by the samples of greater weight (oz./yd²). From this table a comparison with the fabrics tested and the fabrics in use can be made to some extent, but more importantly it supports the practice of providing as many pieces of Nomex clothing as possible to allow for layering. The layers increase the thickness of the Nomex which provides greater protection against the potential flaming of the garments and the rate of heat flux to the skin.

In the clothing area, the newer pieces that have been introduced, or are being introduced, to the fleet are all made of at least one layer of Nomex. Some garments made of the more flammable fabrics of nylon and cotton are still being used by the fleet. Using Nomex fabrics for these garments would allow for layering of the fabric providing even greater and better protection from fire to the aircrew member. In cooler temperatures, the members of the fleet usually wear a layer of the thermal, Nomex underwear providing at least one layer of fireproof fabric between themselves and the heat source. But, during warm weather the Flyers Coverall may be the only layer of Nomex worn by some crewmen since both the survival vest and torso harness are still fabricated of nylon.

New fabrics and finishes are being developed in the area of flammability to improve upon fabric performance and protection. The fabrics presently in the system are the best that could be found for the purpose at the time of procurement. Currently, new fabrics with better flame resistance, and new finishes which would provide flame resistance to fabrics which are otherwise flammable, are being investigated for potential use in the system. Nomex provides good protection especially when layered, but it now appears that there may be better products available depending upon the types of weaves, knits, weights and colors required.

NADC-86089-60

The recommendation at this time is to facilitate replacement of the more flammable clothing with the less flammable counterpart to insure that all aircrewmembers are wearing as many layers of flame resistant clothing as possible. It is also suggested that more meaningful tests be performed on the fabrics that are being developed for use in environments requiring nonflammable fabrics. These tests should be designed to quantify the protection levels, i.e. time to ignite, time to blister and burn intensity rather than the conventional tests which measure effects on the fabrics such as flame time, glow time and char length. These tests would allow for comparison of fabrics against each other, demonstrate the level of protection provided and direct researchers in developing new and better fabrics and finishes in this field.

- after flame time: time the specimen continues to burn after the flame is shut off.
- after glow time: time the specimen continues to glow after it has ceased to flame.
- char length: distance from the end of the specimen, which was exposed to the flame, to the end of center of charred area.

Accession For
NTIS GRA&I
DTIC TAB
Unannounced
Justification

☒ ☐ ☐

A-1



FABRIC	ITEM	FLAMMABILITY
1. Aramid (Nomex)		
A. MIL C 85637, Laminated, Fire Resistant, Waterproof and Moisture Vapor Permeable	62 P Anti Exposure Coverall	After flame time, seconds 2 Char length, inches 5 This fabric is produced through lamination of fabrics B and C with Goretex. These layers provide the flame protection.
B 1) MIL C 83429A Aramid (Nomex), woven 2) MIL C 43603, Type II Aramid (Nomex), knitted cloth (Fabrics are the same except for type of weave) 3) MIL C 83283 Aramid (Nomex) knitted cloth	1) 62 P Anti Exposure Coverall, outer shell b. Outside cover, personal life preserver c. CWU 27 P (large green), CWU 27 P (Blue) Summer Flyer's Coveralls 2) CWU 33 P Anti Exposure Coverall, outer shell 3) CWU 17 P Intermediate Flyer's Coveralls	Flaming time, seconds 2 Glow time, seconds 25 Char length, inches 3.5 Nomex properties include: - High temperature required for degradation - Fibers char without melting or dripping, do not char at less than 675°F (357°C) - Any burning will be self extinguishing when the high temperature is removed - Remains protective after exposure to high amounts of thermal energy. - Good abrasion characteristics.
C) MIL C 85636, AS) Aramid (Nomex), Jersey knit	62 P Anti Exposure Coverall, inner shell backing material	After flame time, seconds 1.0 After glow time, seconds 25.0 Char length, inches 5.0 Nomex flammability properties same as B
D. MIL C 81814 Aramid (Nomex) (Different weight and flammability requirements than section II)	1) CWU 36 P Summer Flyer's Jacket 2) CWU 18 P Extreme Cold Weather Trousers 3) CWU 17 P, CWU 45 P, Cold Weather Flyer's Jackets 4) Winter Flyer's Hood 5) CSU 15 P Anti G Garmet	After flame time, seconds 1 After glow time, seconds 14 Char length, inches 3.5 Nomex flammability properties same as B
E. MIL C 81813A Aramid (Nomex), Quilted Batting	1) CWU 36 P Lining, Summer Flyer's Coverall 2) CWU 18 P Lining Extreme Cold Weather Trousers 3) CWU 17 P & CWU 45 P Cold Weather Flyer's Jacket's Lining	Flame time, seconds 2 Glow time, seconds 25 Char length, inches 5.0 No melting will not char at a temperature less than 875°F (357°C)

FABRIC	ITEM	FLAMMABILITY
F. MIL-C-85038, Type I Aramid (Nomex) Waffle Type, (thermal circular knit	CWU 43 P, CWU 44 P, Cckt Weather Underwear.	The spec does not contain a flammability require- ment, but because this is a Nomex Cloth, it can be assumed to meet the same criteria defined in section B.
G 1) MIL-C-72196 Aramid (Nomex) 2) Nomex "Honeycomb" (no number)	1) Seat Cushion Cover for the following Survival kits a. RSKK 1 b. RSKK 8 c. RSKK 9 d. RSKK 3 e. SKU 3/A 2) Seat Cushion Cover a. SKU 4/A b. SKU 6/A	See section B.
H 1) MIL-R-6001, Type II Flame resistant, Grade A Latex Foam Rubber 2) DYNAR modified polyurethane, open cell foam. 3) Safescreat urethane foam	1) Foam Core used in seat cushions of the following survival kits: a. RSKK 1 b. RSKK 8 c. RSKK 6 d. RSKK 9 e. RSKK 3 2) Foam core used in seat cushions of the following survival kits: a. SKU 4/A b. SKU 6/A	1) Shall support a flame not longer than 50 seconds after removal from the flame 2) Unstable over 180°F (82.2°C). Urethane foams: flammable.

FABRIC	ITEM	FLAMMABILITY
II. Leather		
1) KKL L 254 Non-treated water resistant leather	1)a GS FGP 2 Fire Resistant Flyer's Gloves b. HAU 8 P Lined Gloves c Edge roll on hammerhead fixed wing aircraft, Type A or B Class 1, A	Leather is not flame proof but it is flame resistant and does provide protection, shrinks and is self extinguishing, does not melt
2) KKL L 162 Non-treated leather	2) Type G 1 Intermediate Flyer's Jacket	
3) Water Resista Leather	3)a Flyer's Boot b Aircrew Safety Boot	
III Nylon and Cotton		
1) MIL C 508 Type I Nylon, oxford cloth	1)a Winter Flyer's Suit b Lining, Type G 1, intermediate Flyer's Jacket c MK 2A Cutaway, Anti G Coverall d SV 28 Survival vest	None of these fabrics has a flammability requirement included in the spec. Nylon cannot withstand extremely high temperatures and will melt. It will self extinguish after removal from source of flame. If not solution dyed the dye may continue to burn off
2) MIL C 18002, Type I Nylon base polytetrafluorene coating	2)a OD 10CW 16 P Quick Ejecting Anti Exposure Coverall b Anti Exposure Mittens c Anti Exposure Hood d Life Preserver	It should be kept in mind that all of these pieces are worn over other garments that are usually non flammable.
3) MIL C 43191, Wind resistant between cotton and nylon	3) Cover, small arms protective body armor	
4) Nylon Webbing	4) MBU 11/P Torso Harness	
K.1) Cotton Vantile	1)a CWU 21/P Anti Exposure Coverall b CWU 53 P Anti Exposure Coverall	1) No flammability requirements
2) MIL C 18087, Cotton	2)a CWU 23 P Linner underwear b Winter Flyer's suit inner shell	2) Flame time, seconds 20 Glow time, seconds 20 Char length, inches 5.5
		Cotton cannot withstand high temperatures, will burn without melting, continues to burn after has been removed.

NAO-86089-60

BIBLIOGRAPHY

1. Behnke, Wallace P., Aramid Fibers for Protective Clothing, p. 146-167, Proceedings of the 1978 Symposium on Textile Flammability, R. Bruce LeBlanc, editor, LeBlanc Research Corporation, East Greenwich, RI, 1978.
2. Haddo, Carlos J., Flammability Handbook for Plastics, Technomic Publishing Co., Inc., Stanford, CT, 1969.
3. National Material Advisory Board, Fire Safety Aspects of Polymeric Materials, Vol 6, Aircraft: Civil and Military, National Academy of Sciences, Washington, DC, 1977.
4. Stoll, A. M., and M. A. Chianta, 1969. Method and Rating System for Evaluation of Thermal Protection. Aerospace Med. 40:1232-1238.
5. Stoll, A. M., M. A. Chianta, and J. R. Piargallini, 1979. Thermal Conduction Effects in Human Skin. Aviation, Space and Environmental Med. August, p. 778-787.

DISTRIBUTION LIST (CONTINUED)

	No of Copies
Commanding Officer Naval Submarine Medical Research Laboratory P.O. Box 900 Naval Base Groton, CT 06340	(1)
Commander Naval Safety Center Naval Air Station Norfolk, VA 23511 (1 for Code 055) (1 for Code 40)	(2)
Chief of Naval Material Department of the Navy Washington, DC 20360 (1 for MAT 04F) (1 for MAT 08T24D)	(2)
Director Naval Research Laboratory Code 6100 CDW Washington, DC 20375	(1)
Commander Naval Supply Systems Command COP 09B Department of the Navy Washington, DC 20376	(1)
Commanding Officer Naval Medical Research Institute National Naval Medical Center Heat Stress Division Bethesda, MD 20814	(1)
Naval Air Systems Command Technical Library and Project Rm. 278 Jefferson Plaza II Department of the Navy Washington, DC 20361	(1)
United States Navy Naval Research Laboratory Library Code 1433 Washington, DC 20375	(1)
NAVAIROCEVCEN (3 for 8131) (3 for 80D1) (3 for 80B1)	(9)

DISTRIBUTION LIST
Report No. NADC-86089-60

NAVY

	No. of Copies
Commander.	(8)
Naval Air Systems Command	
Naval Air Systems Command Headquarters	
Washington, DC 20361	
(2 for AIR 00D4)	
(1 for AIR 310H)	
(1 for AIR 531)	
(1 for AIR 5311)	
(1 for AIR 5311D)	
(1 for AIR 53433A)	
(1 for AIR 53432)	
 Officer in Charge.	 (1)
Navy Clothing & Textile Research Facility	
Code 20	
ATTN: Richard Wojtaszek	
21 Strathmore Road	
Natick, MA 01760	
 Commander.	 (2)
Naval Air Test Center	
Aircrew Systems Branch	
Patuxent River, MD 20670	
 Chief of Naval Research	 (1)
(Code 440)	
800 North Quincy St.	
Arlington, VA 22217	
 Commander.	 (3)
Naval Supply Systems Command	
Naval Supply Systems Command Headquarters	
Washington, DC 20376	
(1 for Sup 04X)	
(1 for Code 91)	
(1 for Sup 0431F)	
 Chief of Naval Operations.	 (1)
(OP-987H)	
Navy Department	
Washington, DC 20350	
 Commander.	 (1)
Naval Sea Systems Command	
Code 0342	
Naval Sea Systems Command Headquarters	
Washington, DC 20362	