

DTIC FILE COPY

AD _____

2

AD-A223 390

MODELING OF THE NON-AUDITORY RESPONSE TO BLAST OVERPRESSURE

Computer Model of Complex Waves Within
an Enclosure and Their Biological Effects

ANNUAL/FINAL REPORT

William Roush
James H. Stuhmiller

JANUARY 1990

Supported by

U.S. ARMY MEDICAL RESEARCH AND DEVELOPMENT COMMAND
Fort Detrick, Frederick, Maryland 21701-5012

Contract No. DAMD17-85-C-5238

JAYCOR
11011 Torreyana Road
San Diego, California 92121-1190

1990
Cy

Approved for public release; distribution unlimited

The findings in this report are not to be construed as an
official Department of the Army position unless so
designated by other authorized documents.

90 07 2 030

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION <u>Unclassified</u>			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; distribution unlimited		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S)			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION JAYCOR Applied Sci. & Engr. Technol.		6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION Director Walter Reed Army Institute of Research		
6c. ADDRESS (City, State, and ZIP Code) 11011 Torreyana Rd. San Diego, CA 92121-1190			7b. ADDRESS (City, State, and ZIP Code) ATTN: SGRD-UWZ-C, Kenneth T. Dodd, Ph.D. Bldg. 40 Washington, DC 20307-5100		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION U.S. Army Medical Research & Development Command		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER DAMD17-85-C-5238		
8c. ADDRESS (City, State, and ZIP Code) Fort Detrick Frederick, MD 21701-5012			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO. 62787A	PROJECT NO. 62787A878	TASK NO. AB
11. TITLE (Include Security Classification) (U) Modeling of the Non-Auditory Response to Blast Overpressure					
12. PERSONAL AUTHOR(S) William Roush and James H. Stuhmiller					
13a. TYPE OF REPORT Annual/Final	13b. TIME COVERED FROM 8/25/85 TO 7/31/89	14. DATE OF REPORT (Year, Month, Day) 1990 January	15. PAGE COUNT 36		
16. SUPPLEMENTARY NOTATION Computer Model of Complex Waves Within an Enclosure and Their Biological Effects					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) RA 3		
FIELD	GROUP	SUB-GROUP			
26	14				
23	04				
19. ABSTRACT (Continue on reverse if necessary and identify by block number) The repeated passage of pressure waves past a given point, following an explosion in an enclosure, results in the long and complicated pressure time histories called "complex waves." The waves are not only complex because of their temporal variation, but their effect on biological structures depends on the <i>direction</i> of each wave component. The ability to estimate injury under these circumstances represents one of the greatest challenges of biomechanical modeling. A mathematical model for the reflections of blast waves within an enclosure has been constructed based on the concept of mirror-like reflections of the wave front at each solid surface. The model accounts for the position and orientation of each surface and allows for the presence of openings, such as doors and windows. A simplified model for the venting of explosion product gases is also included. The pressure loading time histories are combined with simplified models of the structural response of various organ systems that are known to be injured by air blast. The combined models not only allow estimates of potential injury due to explosions within enclosures, but also provide a means of judging the accuracy of the blast calculations in terms of the requirements of injury prediction.					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Mary Frances Bostian			22b. TELEPHONE (Include Area Code) 301-663-7325		22c. OFFICE SYMBOL SGRD-RMI-S

Computer Model of Complex Waves Within an Enclosure and Their Biological Effects

19. ABSTRACT *(Continued from front)*

The blast field predictions are compared with measurements made inside an Armored Personnel Carrier and inside a field bunker. Many qualitative features are captured but the agreement does not extend to individual details. A comparison of the peak overpressures and the total pressure impulse shows that in most cases agreement is within 20-30%, but there are certain cases for which the disagreement is much greater.

The measured and calculated pressure histories are used in the simplified biological response models and a comparison made of the critical parameter of injury. For the tympanic membrane and the upper respiratory tract, the critical stress calculated using the mathematical model differ from that calculated using the measured data by an amount not significantly greater than the variation of stress as a correlate of injury. For the lung, however, the variations are much larger and suggest that a more accurate prediction scheme may be required.

MODELING OF THE NON-AUDITORY RESPONSE TO BLAST OVERPRESSURE

Computer Model of Complex Waves Within an Enclosure and Their Biological Effects

JANUARY 1990

Supported by

U.S. ARMY MEDICAL RESEARCH
AND DEVELOPMENT COMMAND

Fort Detrick

Frederick, Maryland 21701-5012

Contract No. DAMD17-85-C-5238

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special

A-1



COMPUTER MODEL OF COMPLEX WAVES WITHIN AN ENCLOSURE AND THEIR BIOLOGICAL EFFECTS

William Roush
James H. Stuhmiller
Applied Science and Engineering Technology
JAYCOR

ABSTRACT

The repeated passage of pressure waves past a given point, following an explosion in an enclosure, results in the long and complicated pressure time histories called "complex waves." The waves are not only complex because of their temporal variation, but their effect on biological structures depends on the *direction* of each wave component. The ability to estimate injury under these circumstances represents one of the greatest challenges of biomechanical modeling.

A mathematical model for the reflections of blast waves within an enclosure has been constructed based on the concept of mirror-like reflections of the wave front at each solid surface. The model accounts for the position and orientation of each surface and allows for the presence of openings, such as doors and windows. A simplified model for the venting of explosion product gases is also included. *Keywords: Non-Automatic Responses to Blast Overpressure,*

The pressure loading time histories are combined with simplified models of the structural response of various organ systems that are known to be injured by air blast. The combined models not only allow estimates of potential injury due to explosions within enclosures, but also provide a means of judging the accuracy of the blast calculations in terms of the requirements of injury prediction.

The blast field predictions are compared with measurements made inside an Armored Personnel Carrier and inside a field bunker. Many qualitative features are captured but the agreement does not extend to individual details. A comparison of the peak overpressures and the total pressure impulse shows that in most cases agreement is within 20-30%, but there are certain cases for which the disagreement is much greater.

The measured and calculated pressure histories are used in the simplified biological response models and a comparison made of the critical parameter of injury. For the tympanic membrane and the upper respiratory tract, the critical stress calculated using the mathematical model differ from that calculated using the measured data by an amount not significantly greater than the variation of stress as a correlate of injury. For the lung, however, the variations are much larger and suggest that a more accurate prediction scheme may be required.

Computer modeling explosions, Pressure waves, Blast injury, Weapons Effects
(Biological Complex Wave Model)

A - (JG)

CONTENTS

	<u>Page</u>
ABSTRACT	
1. INTRODUCTION	1-1
2. COMPLEX WAVE MODEL	2-1
3. ORGAN RESPONSE MODEL	3-1
4. COMPARISON OF COMPLEX WAVE MODEL WITH DATA	4-1
5. COMPARISON OF ORGAN RESPONSE MODEL WITH FIELD DATA	5-1
REFERENCES	R-1

ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
1. Primary images (P_i)	2-2
2. Secondary images (S_{ij})	2-3
3. Tertiary images (T_{ijk})	2-4
4. Third order reflection	2-6
5. APC specification and sensor location	4-2
6. Bunker specification and sensor location	4-3
7. 57 gm C-4 blast "S" free field sensor	4-4
8. 2/13/87 blast Lambdroid face-on sensor	4-5
9. Peak pressure	4-6
10. Total impulse	4-7
11. 57 gm C-4 blast "S" free field sensor	5-2
12. 2/13/87 blast Lambdroid face-on sensor	5-3
13. Tympanic stress	5-4
14. URT stress	5-5
15. Work done on lung	5-6

TABLE

<u>Table</u>	<u>Page</u>
1. Parameter Values for the Three Organ Systems	3-2

1. INTRODUCTION

The repeated passage of pressure waves past a given point, following an explosion in an enclosure, results in the long and complicated pressure time histories called "complex waves." The waves are not only complex because of their temporal variation, but their effect on biological structures depends on the *direction* of each wave component. The ability to estimate injury under these circumstances represents one of the greatest challenges of biomechanical modeling.

A mathematical model for the reflections of blast waves within an enclosure has been constructed based on the concept of mirror-like reflections of the wave front at each solid surface. The model accounts for the position and orientation of each surface and allows for the presence of openings, such as doors and windows. A simplified model for the venting of explosion product gases is also included.

The pressure loading time histories are combined with simplified models of the structural response of various organ systems that are known to be injured by air blast. The combined models not only allow estimates of potential injury due to explosions within enclosures, but also provide a means of judging the accuracy of the blast calculations in terms of the requirements of injury prediction.

The blast field predictions are compared with measurements made inside an Armored Personnel Carrier and inside a field bunker. Many qualitative features are captured but the agreement does not extend to individual details. A comparison of the peak overpressures and the total pressure impulse shows that in most cases agreement is within 20-30%, but there are certain cases for which the disagreement is much greater.

The measured and calculated pressure histories are used in the simplified biological response models and a comparison made of the critical parameter of injury. For the tympanic membrane and the upper respiratory tract, the critical stress calculated using the mathematical model differ from that calculated using the measured data by an amount not significantly greater than the variation of stress as a correlate of injury. For the lung, however, the variations are much larger and suggest that a more accurate prediction scheme may be required.

2. COMPLEX WAVE MODEL

The first step in COMPLX is to use the method of images^(3,4) to generate a distribution of changes which produces the same wave pattern within the enclosure.

This algorithm produces reflected images of the blast source, creating N primary images (Fig. 1), where N is the number of enclosure walls. The primary images are reflected by the walls of the enclosure, creating $N(N - 1)$ secondary images (Fig. 2). Images do not reflect off the wall that created them. The secondary images reflect into the walls of the enclosure creating $N(N - 1)^2$ tertiary images (Fig. 3). This is an infinite process, producing reflecting images at increasing distances from the original source. The model carries out the process until the images reach a specific distance from the source. Images beyond this distance do not contribute to the pressure-time history during an interval equal to the maximum distance divided by the speed of sound.

First, the position of each image is computed as a function of the position of its source within the enclosure. The equations used for computing image positions are:

$$X_i = X_s - (2 D_{\text{surf}} X_{\text{norml}})$$

$$Y_i = Y_s - (2 D_{\text{surf}} Y_{\text{norml}})$$

$$Z_i = Z_s - (2 D_{\text{surf}} Z_{\text{norml}})$$

where:

X_i = X coordinate of Image

Y_i = Y coordinate of Image

Z_i = Z coordinate of Image

X_s = X coordinate of Image source

Y_s = Y coordinate of Image source

Z_s = Z coordinate of Image source

X_{norml} = X component of the reflecting wall's unit vector

Y_{norml} = Y component of the reflecting wall's unit vector

Z_{norml} = Z component of the reflecting wall's unit vector

D_{surf} = distance from the image source to the reflecting wall.




Figure 1. Primary images (P_i). i = reflecting wall.




Figure 2. Secondary images (S_{ij}). i = primary image source;
 j = reflecting wall.




Figure 3. Tertiary images (T_{ijk}). ij = secondary image source;
 k = reflecting wall.

Next, the pressure-time history is computed as the sum of all blast waves that can be viewed at the sensor location of interest. The model computes the path from the sensor back to the original blast via each image and its source. For example, a tertiary image's path would involve the reflection of the blast off three walls (Fig. 4). COMPLX checks each path to determine if it can be "viewed" from the sensor, that is, that the path is not obstructed by any object and that the path intersects the reflecting wall. COMPLX creates a list of all paths that are in view of the sensor.

The pressure-time history is the sum of the individual blast waves, each of which is considered to be a Friedlander wave. The characteristics of the blast waves are calculated using the normalized blast parameters quoted in Chapter 6 of Baker.⁽⁵⁾

$$\text{Pressure-time history: } P(t) = \sum_{i=1}^k P_i(t) \quad 0 \leq t \leq T_{\max}$$

where:

$T_{\max}$ is given by the maximum specified distance an image can be from the blast divided by the speed of sound.

i = blast wave index

k = number of blast waves seen by sensor

$$\text{Friedlander wave: } P(t) = P_s (1 - t_a/t_d) e^{[-b(t_a/t_d)]}$$

where:

$P(t)$ = pressure at time t

P_s = peak pressure

t_a = time measured from wave arrival

t_d = positive duration of wave

b = exponential parameter of Friedlander wave

The parameters P_s , t_a , t_d , and b can be determined from Baker tables when the normalized distance from the sensor is known.

$$D_i = d/D_{\text{not}}$$




Figure 4. Third order reflection. The distance, d_5 , between the sensor (1) and the tertiary image, T_{412} , is equal to the path of the blast wave, d_4, d_3, d_2, d_1 .
 $(d_5 = d_4 + d_3 + d_2 + d_1)$

where:

D_i = normalized distance from source

d = distance of blast wave path

$$D_{not} = (E/P_o)^{1/3}$$

E = energy released by charge

P_o = ambient pressure

The blast parameters t and t_d are determined from the relations:

$$t = T_a T_o$$

$$t_d = T_s T_o$$

where:

T_a = normalized time of arrival

T_s = normalized positive duration

$$T_o = D_{not}/a$$

a = ambient speed of sound

The peak pressure, P_s , is determined both by the distance to and strength of the blast and the orientation of the incident wave to the sensor.

$$\text{for } -\frac{\pi}{2} \leq \theta \leq \frac{\pi}{2}$$

$$P_s = [P_r \cos(\theta) + P_i \sin(\theta)] P_o R$$

$$\text{for } \theta > \left| \frac{\pi}{2} \right|$$

$$P_s = P_i [1 + 0.25 \cos(\theta)] P_o R$$

where:

θ = angle between the individual blast waves and the orientation of an object at the given location

P_s = normalized reflected pressure

P_i = normalized incident pressure

P_o = ambient pressure

R = reflectivity factor

The parameter R is the product of the reflectivities of each wall the wave encounters before reaching the sensor.

COMPLX adds the pressurization of the enclosure due to expanding gases of the blast to the pressure-time history. This corresponds to the "Quasi-Static Overpressure Response"⁽³⁾ and "fill"⁽⁴⁾. The pressurization is the result of competition between heating of the ambient gases in the enclosure by the explosive and the loss of energy from the flow leaking out of the enclosure. The deviation for computing the pressurization of the enclosure follows as:

Equation of state for the entire enclosure:

$$pV = NRT$$

$$E = E_o + NC_v(T - T_o)$$

The explosion violently produces gas which adds mass and energy to the enclosure. Both factors increase the pressure of the enclosure:

$$\frac{dp}{p} = \frac{dE}{E} \quad (1)$$

The explosion adds an amount of energy, E , when the explosion gases completely mix with the ambient gases,

$$E(t) = E_o + \Delta E \frac{V_E(t)}{V_R}$$

If the mixing proceeds at particle speed, u_e , behind the blast, then

$$\frac{V_E(t)}{V_R} = \frac{4/3 \pi (u_e t)^3}{4/3 \pi R_R^3} = \left(\frac{u_e t}{R_R} \right)^3 = \left(\frac{t}{T_e} \right)^3$$

where the volume, V , of the enclosure is represented by the equivalent sphere and T_e is the time for the expanding gases to fill the enclosure,

$$\frac{1}{E_o} \left(\frac{dE}{dt} \right)_e = \frac{\Delta E}{E_o} \frac{3}{T_e} \left(\frac{t}{T_e} \right)^2 \quad \text{for } t \leq T_e \quad (2)$$

If there is a place for the gases to leak to the ambient, then the flow will take energy out of the enclosure at a rate

$$\left(\frac{dE}{dt} \right)_{out} = \frac{-E}{V} u_{out} A_{out}$$

The flow is driven by the energy difference between the outside and the inside,

$$u_{out} = k \Delta p$$

so that

$$\frac{1}{E} \left(\frac{dE}{dt} \right)_{out} = - \left(\frac{k p_c A_{out}}{V} \right) \frac{\Delta p}{p_o} = \frac{1}{T_o} \left(\frac{\Delta p}{p_o} \right) \quad (3)$$

T_o depends on the effectiveness of the leak, where:

$T_o = 0$ for a closed enclosure

$T_o = \infty$ for a free field.

Combining Eqs. (1), (2), and (3) gives

$$\frac{d}{dt} \left(\frac{\Delta p}{p_o} \right) + \frac{1}{T_o} \left(\frac{\Delta p}{p_o} \right) = \begin{cases} 3/T_e \left(\frac{\Delta E}{E_o} \right) \left(\frac{t}{T_e} \right)^2, & t/T_e \leq 1 \\ 0, & t/T_e > 1 \end{cases} \quad (4)$$

Eq. (4) can be written in terms of dimensionless variables.

$$\left(\frac{\Delta p}{p_o} \right) = \left(\frac{\Delta E}{E_o} \right) f(t/t_e) \quad (5)$$

where

$$r = t/t_e$$

to yield

$$\bar{p}' + \theta \bar{p} = \begin{cases} 3r^2 & , \quad r \leq 1 \\ 0 & , \quad 1 < r \end{cases} \quad (6)$$

where

$$\theta = \frac{T_e}{T_o} \quad .$$

The solution is then

$$\bar{p}(r) = \begin{cases} 3/\theta^3 [(\theta r)^2 - 2(\theta r) + 2 - 2e^{-(\theta r)}] & , \quad r \leq 1 \\ 3/\theta^3 [\theta^2 - 2\theta + 2 - 2\exp^{-\theta}] e^{-\theta(r-1)} & , \quad 1 < r \end{cases} \quad (7)$$

Using the equations of state, the equation for the expansion pressure becomes

$$p_e(t) = E_e/V_r f(\epsilon)$$

where:

E_e = energy of explosive

V_r = volume of enclosure

The final step in computing the load pressure-time history is to add the pressurization of the enclosure,

$$p(t) = p(t) + p_e(t)$$

3. ORGAN RESPONSE MODEL

COMPLX uses the load pressure-time history determined in the previous section as the driving force for the Generalizable Model.⁽²⁾ The Generalizable Model⁽²⁾ uses the damped harmonic oscillator equation for computing the structural dynamics of the body due to a blast wave. Therefore the equation of motion for the body becomes:

$$m \frac{d^2 x}{dt^2} + \left(\frac{2m}{t_c} \right) \frac{dx}{dt} + kx = p(t)$$

where:

m = mass/area

t_c = characteristic damping time

k = spring constant/area

x = displacement

By solving for the displacement, x , and the velocity, dx/dt , COMPLX can compute the delivered stress to a particular organ. The model uses the displacement to compute the stress delivered to the tympanic and larynx membranes and the velocity to compute the stress delivered to the lung.

For the tympanic and larynx membranes, the stress is computed from:

$$\sigma_{\text{tissue}} = f k x$$

For the lung, the tissue stress is assumed to be proportional to the parenchymal pressure at the pleural surface, which is given by:

$$p_p = \frac{2m}{t_c} \frac{dx}{dt}$$

When the maximum tissue stress within an organ exceeds a critical value, injury is predicted to occur. Table 1 gives the parameter values for the organ systems.

Table 1. Parameter Values for the Three Organ Systems

Organ	m (kgm/m ²)	t_c (ms)	k (kPa/mm)	f	σ_{crit} (MPa)
Tympanic membrane	0.2	10	7.9	133	7.5-15
Upper respiratory tract	10	100	4	5	1
Lung	15	10	0	--	--

4. COMPARISON OF COMPLEX WAVE MODEL WITH DATA

We compare the predictions of COMPLX with two sets of complex blast environment data. The first set was measured inside an APC (Fig. 5). The second was measured inside a field bunker (Fig. 6). The digitized field data is plotted as a pressure-time history curve for comparison with the same curve produced by the model.

Since the exact conditions of the test are not known, the comparisons are only approximate but are intended to give the reader an idea of COMPLX's ability to predict the characteristics of a complex wave. In the following sequence of plots, for both the APC and the bunker data, the parameters of the model are set up such that:

1. Sensor positions and orientations are identical to those of the field blast.
2. The orientation function is the same as described in the second section of this report.
3. The walls have 100 percent reflectivity.
4. The enclosure is not pressurized.

The APC data was measured from a series of blasts in which the explosive charge weights were varied. The specific charge weights were 57 gm, 113 gm, 227 gm, and 454 gm. The pressure sensors (Fig. 5) used to measure the data were kept in the same location for the entire blast series. The N and S pressure sensors faced upwards while the Lambdroid's four sensors faced towards the blast, away from the blast, and perpendicular to the blast. The charges were all detonated in the center of the APC. Comparison plots have been made with all the APC data. Figure 7 is an example from this set.

The bunker data was measured from a series of blasts in which the sensor's position (Fig. 6) was varied. In addition, for each sensor position a different charge weight was detonated, 227 gm and 454 gm. The sensor configuration (Fig. 6) for this series of blasts was a free field pointing upward, Lambdroid with a sensor pointing towards the blast, a sheep with a skin sensor pointing towards the blast, and another sheep with an esophagus sensor. Comparison plots have been made with all Bunker data. Figure 8 is an example from this set.

We have taken peak pressure and total impulse from each of the comparison data sets and plotted field data versus model calculation (Figs. 9 & 10). This creates a scatter plot such that those points which lie on the 45 degree line are of equivalent values for field data and model calculation. The points that don't lie on the 45 degree line are off by a percentage difference. Scatter plots are a good means of visualizing the correlation of a large data set.







Figure 5. APC specification and sensor location.




Blast 2/13/87
227 gm C-4




Blast 2/18/87
227 gm C-4

Blast 2/20/87
454 gm C-4



Blast 3/2/87
227 gm C-4

Blast 3/3/87
454 gm C-4



Blast 3/5/87
227 gm C-4

Blast 3/6/87
454 gm C-4


I I-Beam

○ Lambdroid


● Sensor Probe

⦿ Sheep

Figure 6. Bunker specification and sensor location.




Field Data




Model

Figure 7. 57 gm C-4 blast "S" free field sensor.



Field Data



Model

Figure 8. 2/13/87 blast Lambdroid face-on sensor.




Figure 9. Peak pressure.





Figure 10. Total impulse.


5. COMPARISON OF ORGAN RESPONSE USING CALCULATED AND MEASURED PRESSURES

Both the predicted and measured pressure-time history curves are used as input to the Generalizable Model⁽²⁾ to produce a sequence of three plots. The first plot graphs the maximum tympanic membrane stress as a function of time. The second plot graphs the maximum larynx stress as a function of time. The third plot graphs the lung's overpressure as a function of time. These quantities are used in the prediction of blast injury.

Figures 11 and 12 are the predicted organ response where the driving forces are plotted in Figures 8 and 9, respectively. Scatter plots have been made for the maximum tympanic stress (Fig. 13), the maximum URT stress (Fig. 14), and the work done on the lung (Fig. 15). A case-by-case description may be found in a supplementary report.




Field Data




Model

Figure 11. 57 gm C-4 blast "S" free field sensor.



Field Data



Model

Figure 12. 2/13/87 blast Lambdroid face-on sensor.




Figure 13. Tympanic stress.




Figure 14. URT stress.




Figure 15. Work done on lung.

REFERENCES

1. Richmond, R. D., J. T. Yelverton, W. Hicks, and Y. Y. Phillips, "Biological Effects of Complex Blast Waves from Explosions Inside an Enclosure," Los Alamos Natl. Lab. and WRAIR Results Report (draft) for WRAIR, February 1987.
2. Stuhmiller, J. H., Y. Y. Phillips, and K. T. Dodd, "Considerations in Developing a Mechanistically-Based Model of Blast-Induced Injury to Air-Containing Organs," presented 9-10 June 1986 at Aberdeen Proving Ground, Maryland, Proceedings of the Third Workshop on Launch Blast Overpressure, U. S. Army Ballistic Research Lab. Special Publication BRL-SP-66, June 1987.
3. Heaps, C. W., "Weapon Blast Scaling: Free Field and In Enclosures," presented 9-10 June 1986 at Aberdeen Proving Ground, Maryland, Proceedings of the Third Workshop on Launch Blast Overpressure, U. S. Army Ballistic Research Lab. Special Publication BRL-SP-66, June 1987.
4. Britt, J. R. and J. L. Drake, "Penetration of Short Duration Airblast into Protective Structures," The Shock and Vibration Bulletin, Bulletin 54, The Shock and Vibration Laboratory, Washington, D.C., June 1987.
5. Baker, W. E., Explosions in Air, University of Texas Press, Austin, 1973.

DISTRIBUTION LIST

4 copies	Director Walter Reed Army Institute of Research ATTN: SGRD-UWZ-C Washington, DC 20307-5100
1 copy	Commander US Army Medical Research and Development Command ATTN: SGRD-RMI-S Fort Detrick, Frederick, MD 21701-5012
2 copies	Defense Technical Information Center (DTIC) ATTN: DTIC-DDAC Cameron Station Alexandria, VA 22304-6145
1 copy	Dean School of Medicine Uniformed Services University of the Health Sciences 4301 Jones Bridge Road Bethesda, MD 20814-4799
1 copy	Commandant Academy of Health Sciences, US Army ATTN: AHS-CDM Fort Sam Houston, TX 78234-6100