

AD

AD-E402 078

Technical Report ARAED-CR-90008

AD-A225 625

RE-EXAMINE LIQUID PROPELLANT NITROMETHANE
HAZARD CLASSIFICATION PARAMETERS AND ADDRESS
THE HAZARDS CLASSIFICATION OF VARIOUS SLURRY MIXTURES

William Herrera
William Toliver
Southwest Research Institute
San Antonio, TX 78228-0510

W. O. Seals
ARDEC
Project Engineering

DTIC
ELECTE
AUG 10 1990
D
60 E

August 1990



US ARMY
ARMAMENT MUNITIONS
& CHEMICAL COMMAND
ARMAMENT RDE CENTER


U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND
ENGINEERING CENTER

Armament Engineering Directorate
Picatinny Arsenal, New Jersey

Approved for public release; distribution unlimited.

90 08 10 51

DISCLAIMER NOTICE



**THIS DOCUMENT IS BEST
QUALITY AVAILABLE. THE COPY
FURNISHED TO DTIC CONTAINED
A SIGNIFICANT NUMBER OF
PAGES WHICH DO NOT
REPRODUCE LEGIBLY.**

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement by or approval of the U.S. Government.

Destroy this report when no longer needed by any method that will prevent disclosure of contents or reconstruction of the document. Do not return to the originator.

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION AVAILABILITY OF REPORT Approved for public release; Distribution is unlimited		
2b. DECLASSIFICATION DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER 01-2512			5. MONITORING ORGANIZATION REPORT NUMBER Contractor Report ARDEC-CR-90008		
6a. NAME OF PERFORMING ORGANIZATION Southwest Research Institute		6b. OFFICE SYMBOL		7a. NAME OF MONITORING ORGANIZATION ARDEC.AED	
6c. ADDRESS (CITY, STATE, AND ZIP CODE) San Antonio, TX 78228-0510			7b. ADDRESS (CITY, STATE, AND ZIP CODE) Energetics and Warheads Div.(SMCAR-AEE) Picatinny Arsenal, NJ 07806-5000		
8a. NAME OF FUNDING SPONSORING ORGANIZATION ARDEC, IMD STINFO Branch		8b. OFFICE SYMBOL SMCAR-IMI-I		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER DAAA21-88-R-0084	
8c. ADDRESS (CITY, STATE, AND ZIP CODE) Picatinny Arsenal, NJ 07806-5000			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
11. TITLE (INCLUDE SECURITY CLASSIFICATION) RE-EXAMINE LIQUID PROPELLANT NITROMETHANE HAZARD CLASSIFICATION PARAMETERS AND ADDRESS THE HAZARDS CLASSIFICATION OF VARIOUS SLURRY MIXTURES					
12. PERSONAL AUTHOR(S) W.R. Herrera and W.L. Toliver, Southwest Research Institute; W. Seals, ARDEC Project Engineer					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM 3/27/89 TO 1/31/90		14. DATE OF REPORT (YEAR, MONTH, DAY) August 1990	
15. PAGE COUNT 33					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (CONTINUE ON REVERSE IF NECESSARY AND IDENTIFY BY BLOCK NUMBER)		
FIELD	GROUP	SUB-GROUP	Nitromethane/ Storage group C Texas system		
			Regulation 385-100 Flammable liquid TB 700-2		
19. ABSTRACT (CONTINUE ON REVERSE IF NECESSARY AND IDENTIFY BY BLOCK NUMBER) Nitromethane is a potential candidate for the main energetic material in the U.S. Army Tactical Explosive System (TEXS). Storage of nitromethane in a general purpose warehouse is advantageous. The goal of this program was to examine the regulation concerning hazard classification, transportation, and storage of liquid propellant nitromethane. Agencies reviewed included United Nations, U.S. Department of Defense, U.S. Department of Transportation, and the Occupational Safety and Health Administration of the Department of Labor. At present the United Nations, the U.S. Department of Transportation, and the Occupational Safety and Health Administration classify nitromethane as a flammable liquid. The Department of Defense classifies nitromethane as a mass detonating explosive. The Department of Defense classification does not permit storage in general warehouses. To store nitromethane in a general purpose warehouse, the nitromethane would have to be reclassified or the user would have to obtain a waiver. Waivers are difficult to obtain and are only valid for limited time periods.					
20. DISTRIBUTION AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS				21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL I. HAZNEDARI				22b. TELEPHONE (INCLUDE AREA CODE) 724-3316	
				22c. OFFICE SYMBOL SMCAR-IMI-I	

CONTENTS

Introduction	1
Classification Analysis	3
United Nations	3
Department of Defense	4
Department of Transportation	5
Occupational Safety and Health Administration	6
DOD Waiver Requirements	8
Liquid Blasting Agents and Nitromethane Hazard Classification Meeting	9
Conclusion	15
Bibliography	16
Appendix A - United Nations Procedure For Assignment of Hazard Divisions	17
Distribution List	23

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
A-1	



INTRODUCTION

Southwest Research Institute (SwRI) was contracted under DOD Contract DAAA21-88-R-0021, Delivery Order 004 to perform the following tasks:

- 1) (3.1) Establish all the requirements necessary for an item to be stored in the general purpose warehouse.
- 2) (3.2) Determine if nitromethane can be stored in a general purpose warehouse. If nitromethane cannot be stored in the general purpose warehouse, can a waiver be obtained? If a waiver can be obtained, establish what are the conditions that have to be met for storage and who is the cognizant person (names, office symbol, location, and telephone number) that can grant the waiver.
- 3) (3.3) Determine what is required and if the Army can change the U.S. Department of Defense (DOD) hazard classification of nitromethane to permit storage in the general purpose warehouse, and what procedure and cognizant person (name, office symbol, location and telephone number) will be responsible to grant the change.
- 4) (3.4) Coordinate and conduct a meeting with all the key players for the DOD and U.S. Department of Transportation (DOT) necessary to attain a unified classification of nitromethane and detail an approach that is required to unify the DOD and DOT classification of nitromethane.
- 5) (3.5) Address the classification of stearic acid-coated atomized aluminum powder, aluminum slurry, and an aluminum perchlorate solution with respect to the tests, interpretation of test data, and classification of each energetic liquid material. Detailed analyses and all testing to date will have to be provided by the government so this assessment can be made. These topics will be discussed at the meeting with the DOD and DOT personnel.
- 6) Prepare and present a formal plan for unification of the DOD and DOT classification of nitromethane.

Nitromethane is being considered as a potential candidate for the main energetic material in the Tactical Explosive System (TEXS). A major tactical advantage would be attained if the nitromethane can be stored in Army general purpose warehousing. The program tasks address the requirements necessary for an item to be stored in general purpose warehousing.

The U.S. Department of Defense (DOD) is concerned with classification, storage, and transportation of nitromethane. The U.S. Department of Defense classifies nitromethane as a Group IV, Mass Detonating Liquid Propellant. The DOD classification does not permit nitromethane to be stored in general purpose warehousing. With special storage provisions, nitromethane can be placed in the strong oxidizer category.

The U.S. Department of Transportation (DOT) and the United Nations (UN) are responsible for classification and transportation of nitromethane. The United Nations, U.S. Department of Transportation and Occupational Safety and Health Administration classify nitromethane as a flammable liquid with quantity limitations in packing and transport. This variation in classification is of concern because of the discrepancies in the procedures for transporting and handling of nitromethane and there are other propellant slurry mixtures that are under consideration for TEXS application and their classification will have to be addressed. The Occupational Safety and Health Administration (OSHA) regulates the storage of nitromethane.

In addition, other propellant mixtures/slurries are under consideration for TEXS application. A standardization of procedures for classifying these substances needs to be addressed.

This report presents the results of analysis of these four agencies' policies concerning the transportation, hazard classification or storage of nitromethane. Section 2.0 gives a detailed discussion of the requirements concerning nitromethane by agency. Notes and special provisions are explained in detail. In addition, Section 3.0 discusses the Department of Defense waiver requirements on hazardous substances. Section 4.0 is a synopsis of the minutes of Hazardous Classification meeting held at SwRI. That meeting addressed the concerns, remediations and recommendation of some of the principally involved agencies.

CLASSIFICATION ANALYSIS

The nitromethane hazard classification, transportation, and storage protocols are presented in the following sections.

United Nations

United Nations classifies nitromethane as a flammable liquid, Class 3 hazard with special provision 26. Packing is Group II, Method M.¹ Clarifications to these classifications and provisions are:

- Class 3 hazards are flammable liquids which give off a flammable vapor at temperatures of not more than 60.5°C—closed-cup test or 65.6°C—open cup test.²
- Special provision 26 states that this substance has some dangerous explosive properties.³ These properties are not defined.
- Packing Group II is based on inflammability and initial boiling point with Packing Group II having a flashpoint less than 23°C—closed cup and a initial boiling point greater than 35°C. Nitromethane closed cup flashpoint is 95°F or 35°C with a boiling point of 101.2°C.⁴ Packing Group III is for flammable liquids with a flashpoint greater than 23°C and less than or equal to 60.5°C. Nitromethane is listed in Group II because the presence of added substances or impurities cause movement from Group III to II.
- Method M indicates that special recommendations for the transport of the goods by multimodal tank-container. Nitromethane transport in multimodal tanks is forbidden by *Recommendations in the Transport of Dangerous Goods*.⁵ Tanks, with a capacity of not less than 450 liters fitted with service and structural equipment necessary for transport of dangerous liquids, are tank containers.⁶

1. *Recommendations on the Transport of Dangerous Goods*, Chapter 2, p. 45

2. *Recommendations on the Transport of Dangerous Goods*, p. 5

3. *Recommendations on the Transport of Dangerous Goods*, p. 152

4. Rudolf Meyer, *Explosives*, 3rd Edition, p. 246

5. *Recommendations on the Transport of Dangerous Goods*, Table 12.2, p. 324

6. *Recommendations on the Transport of Dangerous Goods*, p. 227

Nitromethane may be shipped in limited quantities which eliminates labeling requirements.⁷ Packing in 1-liter metal containers or 1/2 liter in glass or plastic containers is the limit for Class 3, Group II substances.

The United Nations identification number for nitromethane is UN 1261 which is the same as the Department of Transportation.

United Nations hazardous material classification procedures use UN manual ST/SG/AC.10/14, *Recommendations on the Transport of Dangerous Goods, Tests and Criteria*. Flow charts showing the United Nations hazard classification procedures are found in Appendix A.

Department of Defense

The Department of Defense classifies nitromethane⁸ as a liquid propellant, mass detonating explosive, Hazard Group IV⁵. Nitromethane falls into compatibility Storage Group F⁴. The following are clarifications:

- Note 4 states nitromethane is chemically compatible with compatibility Storage Group C liquid propellants, but require separate storage due to difference in hazards.
- Note 5 states technical grade or better nitromethane in unit quantities of 55 gallons or less in DOT 17E or C drums may require storage as Hazard Group II provided:
 - a) Drums are stacked only one tier high.
 - b) Drums are protected from direct sun rays
 - c) Maximum storage life of 2 years unless storage life tests show product meets purchase specification at that time. Repeat test at 1-year intervals thereafter.
- The hazards from materials in Hazard Group IV are the same as for mass-detonating explosives. Army Material Command Regulation 385-100 determines quantity-distance requirements.⁹
- Materials in Hazard Group II are strong oxidizers. Army Material Command Regulation 385-100 specifies quantity-distance criteria.¹⁰

DOD classifies hazards by using the procedures given in Army Technical Bulletin 700-2. Results of these tests determine parameters such as sensitivity to impact, friction, and flashpoint. The parameters from these test require correlation with DOT classification parameters to determine DOT

7. *Recommendation on the Transport of Dangerous Goods*, Table 15-1, p. 385

8. Army Material Command Regulation 385-100, Table 15-1, p. 15-7

9. Army Material Command Regulation 385-100, Section 15-6(d), Table 15-6, p. 15-3

10. Army Material Command Regulation 385-100, Section 15-6(b), Table 15-3, p. 15-3

hazard classes. The DOT classification determine labeling and packing requirements for transport. Appendix A shows a flowchart of the DOD administration procedures for hazard classification.

Department of Transportation

The Department of Transportation is responsible for the proper classification and regulation of transportation of hazardous substances. Presented are the analysis of the Department of Transportation requirements.

The Department of Transportation classifies nitromethane as a flammable liquid with the following notes:¹¹

- Nitromethane identification number is UN 1261. The UN prefix means it is suitable for international shipment.
- Column 5a lists a packing exception number 173.118. Exception number 173.118 is:
 - a) limited quantities become excepted from DOT labeling requirements when packed 1) in metal containers not over 1 quart, packed in strong outside containers, 2) or packed in containers not over 1 pint or 16 ounces by weight each, packed in strong outside containers, 3) or packed in inside containers with a rated capacity of 1 gallon or less, packed in strong outside containers.¹²
 - b) a flammable liquid that does not meet the definition of another hazard class and has a flashpoint of 73°F or higher is not subject to the specification packaging requirements of this part when in packaging of 110 gallons or less.¹³
- Column 5b lists a packing specific requirement 173.149a. Nitromethane requires packing as specified in section 173.119b. Forbidden are shipments in cargo tanks, tank cars, portable tanks or any containers greater than 110 gallon capacity.¹⁴ Section 173.119b covers packing requirements for flammable liquids with a flashpoint of 20°F to 73°F.¹⁵ This section is inconsistent with the flashpoint of nitromethane.
- 1 quart maximum net quantity in one package is the limit for shipping aboard passenger carrying airliners per column 6a.

11. Code of Federal Regulations, Title 49, Part 172, Table 172.101, p. 142

12. Code of Federal Regulations, Title 49, Part 173.118(a), p. 471

13. Code of Federal Regulations, Title 49, Part 173.118(b), p. 472

14. Code of Federal Regulations, Title 49, Part 173.149a, p. 493

15. Code of Federal Regulations, Title 49, Part 173.119b, p. 475

- 10 gallon maximum net quantity in one package is the limit for cargo aircraft per column 6b.
- Columns 7a and 7b related to water shipments show notes 1 and 2. Notes 1 and 2 stowage on deck or underdeck.¹⁶ Recommended is underdeck stowage.
- DOT has scattered various classification criteria (such as flashpoints for flammable liquids) through out 49 CFR parts 171, 172 and 173. Most of the test use national standards such as American National Standards Institute (ANSI), or American Society for Testing Methods (ASTM), etc. In some cases they require use of test equipment such as a commercial no. 8 blasting cap or Bureau of Explosives' Impact Apparatus.

DOT documentation relates to classification and transportation of hazardous materials. DOT hazard classification procedures are the same as those used by the United Nations. DOT documentation does not address storage.

Occupational Safety and Health Administration

OSHA regulates storage of flammable liquids in industrial/commercial environments.¹⁷ The Army Material Command invokes OSHA requirements as the minimum standard.¹⁸ Addressed in this report are OSHA requirements about container storage because nitromethane transportation is in 55-gallon, DOT-approved drums. Nitromethane transportation and storage in the TEXS context will be in DOT-approved, 55-gallon drums. The following items are a synopsis of the OSHA regulations on flammable liquid storage in containers:

The definition of flammable liquids are liquids with a flashpoint less than 100° F. These are Class I liquids subdivided into three classes discussed below.¹⁹ The three class subdivisions are:

- Class IA-liquids with flashpoint below 73°F and boiling point below 100°F.
- Class IB-liquids with flashpoint below 73°F and boiling point above 100°F.
- Class IC-liquids with flashpoint above 73°F and below 100°F.

OSHA classifies nitromethane as a Class IC flammable liquid using the above criteria.

Flammable or combustible liquids require storage in a tank or in a container that follow paragraph (d)(2). The requirements of paragraph (d)(2) are:

16. Code of Federal Regulations, Title 49, Part 172.101, p. 77

17. Code of Federal Regulations, Title 29, Part 1910.106 p. 217

18. Army Material Command Regulation 385-100, Section 1-2, p. 1-1

19. Code of Federal Regulations, Title 29, Part 1910.106, Section (19), p. 219

- Any can, barrel, or drum is a container.²⁰
- Section (d) says this paragraph applies only to the storage of flammable or combustible liquids in drums or other containers not exceeding 60 gallons individual capacity. This also applies to portable tanks not exceeding 660 gallons individual capacity.²¹
- Section (2) states that:
 - Use only approved containers and portable tanks. Metal containers and portable tanks meeting the requirements of Chapter I, Title 49 of the CFR (that is, DOT approved).
 - Each portable tank require one or more devices installed in the top with enough venting capacity to limit internal pressure under fire exposure conditions.
 - Table H-12²² list the following container sizes for various types of containers which for a Class IC flammable liquid are:

Glass or approved plastic	1 gallon
Metal (other than DOT drums)	5 gallon
Safety cans	5 gallon
Metal drums (DOT approved)	60 gallon
Approved portable tanks	660 gallons

20. Code of Federal Regulations, Title 29, Part 1910.106, p. 220

21. Code of Federal Regulations, Title 29, Part 1910.106, Section (d), p. 230

22. Code of Federal Regulations, Title 29, Part 1910.106, p. 231

DOD WAIVER REQUIREMENTS

A waiver is granted only after determination that compliance with applicable safety standards is not possible, and that essential work on critical Army material requires performance or other necessary and compelling reasons exist. Waivers and exemptions granted for specific situations and limited as indicated in pertinent correspondence do not cover similar operations, locations, or conditions. Waivers are issued for 1 year or less, and no waiver remains in effect for longer than 5 years. Waivers granted for 1 year require review 1 year from the date of initial request by the installation commander to ensure that the circumstances have not changed. Results of this review and a progress report on milestones completed are forwarded through command channels to the Commander, AMC, ATTN: DRCSF-E. When the time to correct the deviation exceeds 5 years, a request for an exemption is appropriate. Positive steps to program and budget for correction are necessary for granting of waivers.

Facilities in existence or in an advanced state of planning before the issuance of today's standards may not require waivers or exemptions in the following situations provided the current hazard is not greater than that assumed for original use:

- 1) The facility does not follow present DOD standards as required by Chapter 17 of this regulation; however, the facility is built in accordance with regulations in effect at the time. This also applies to construction plans developed before the effective date of this regulation, can demonstrate that redesign or modification is not feasible, or it is not feasible to reduce quantities of hazardous material.
- 2) Facilities not following present standards unique to this regulation and the facility and operations have been reviewed and approved by HQ, AMC, ATTN: DRCSF.

Upon local determination that a waiver of mandatory provisions of the regulation is necessary, installations and activities will forward requests through command channels to the Commander, AMC, ATTN: DRCSF. Expiring waivers are not renewed unless there is evidence that all practicable means for following approved standards are exhausted. All requests for exemptions will be forwarded to the Commander, AMC, ATTN: DRCSF-E.²³

23. Army Material Command Regulation 385-100, Section 1-6, p. 1-3

LIQUID BLASTING AGENTS AND NITROMETHANE HAZARD CLASSIFICATION MEETING

A meeting hosted by SwRI was held on October 19, 1989 to discuss hazard classification for liquid blasting agents and nitromethane. A list of attendees is presented in Table 1.

TABLE 1. LIST OF ATTENDEES

Name	Affiliation/Address	Phone Number
Robert E. Lyle	Southwest Research Institute	512/522-2170
William R. Herrera	Southwest Research Institute	512/522-3622
William L. Toliver	Southwest Research Institute	512/522-3191
Donna Kessler	AMC Field Safety Activity Attn: AMXOS-SE Charlestown, IN 47111-9669	812/284-7825 AV 366-7825
Earle Smith	HQ: AFISC/SEWV Norton AFB, CA 92409	714/382-3137 AV 876-3137
Edward Klinghoffer	Naval Sea Systems Command Washington, DC 20362	202/692-2080 AV 222-2080
William L. Smith	U.S. Army, PM-MCD	201/724-7933 AV 880-7933
William O. Seals	U.S. Army, ARDEC	201/724-5378 AV 880-5378
Jim Elliott	U.S. Army, ARDEC Attn: SMCAR-SF	201/724-3047 AV 880-3047
Ranen K. Chatterjee	U.S. Army Attn: SMCAR-FSM-M	201/724-6112
Leon Manole	U.S. Army Attn: AMSMC-QAR-R(D)	201/724-5549 AV 880-5549

Mr. Leon Manole of U.S. Army gave a presentation on the Tactical Explosive System (TEXS) to explain its mission and purpose. Mr. Manole briefly introduced the candidate systems and gave a generic discussion of the merits of each. Mr. Manole talked about the Department of Defense classification scheme for liquid propellants and gave the criteria for Hazard Class IV and Hazard Class II. Mr. Manole also discussed the UN and DOT hazard classification criteria.

Mr. William Herrera of SwRI discussed that SwRI will test and evaluate candidate TEXS materials in an unbiased way. The government personnel will be invited to attend testing or review any information from the material testing that SwRI will perform.

The meeting was then turned over to Mr. William Seals of U.S. Army who presented test methods and classification information regarding the liquid propellant program for guns. Particular emphasis was placed on how an interim classification was obtained on these materials. The interim classification was used to allow transport of the gun propellant materials during the research phases. The tests performed for these liquid propellants were:

Interim Classification Tests	Supplemental Tests
Thermal test	JANNAF thermal stability
Card gap	Adiabatic compression
Impact	Critical diameter
Ignition and unconfined burning	Flashpoint minimum pressure for vapor phase ignition
Detonation	Electrostatic sensitivity

Mr. Seals stated that the first two tests are particularly important for liquid propellants. Some of these tests are not mandatory for liquids, but could be imposed, with the first two tests the most serious candidates to be made mandatory. Nitromethane was used as the baseline material for the liquid propellant program because it could be sensitive to adiabatic compression ignition which can cause an explosion or detonation.

Open discussion during this session included the following points:

- DOD is trying to decide which hazard class liquid propellants should be classified. The class candidates are 1.1 through 1.5 which are basically aimed at solid materials.
- Nitromethane should be tested for thermal stability over all temperature ranges to include those below freezing. Nitromethane should also be tested with varying volumes including the test specified 8 cubic inches.
- Jim Elliot of the U.S. Army stated that it seems pertinent to use binary agents in which each binary component is not classified as explosive until the binary agents are mixed at the point of use.
- It was stated that liquid propellants will present a hazard concern during the manufacturing process.

- DOD logistics personnel do not want liquid propellants declassified to lessor hazard classes because it will cause complications in the storage of these materials.

Mr. Seals displayed various viewgraphs showing test apparatus details used in small-scale testing of liquid propellant materials and pointed out specific concerns with testing liquids versus solids with these apparatus. Mr. Manole pointed out there are no available commercial no. 8 blasting caps that meet the specifications. No. 8 caps sold commercially now contain more explosive material and are dimensioned larger than the specification allows. Mr. Manole had to have a commercial firm specially produce no. 8 caps that meet the current specification to perform tests on the TEXS candidates. This manufacturing process took approximately 6 months.

Mr. Herrera presented the next session concerning the criteria for evaluation of liquid blasting agents. Numerous viewgraphs were presented with most paralleling those shown by Mr. Seals in the prior session. Mr. Herrera pointed out what kind of tests can be performed on liquid materials and gave some cautions on this testing. The cautions are:

- Be very careful to test the liquid material without involving effects of the test apparatus itself.
- There are material concerns with liquid materials that are not addressed with the current testing methods regarding solid materials. The test chamber material may have to be coated with a polyethylene liner, for example.
- Have to be particularly careful not to introduce contaminants from the containers.

Another open discussion occurred with the following points discussed:

- DOD has a requirement to transport the TEXS material by the U.S. Air Force Military Airlift Command (MAC). Air Force Regulation 71-4 will be the governing regulation for transport but MAC generally follows the DOT guidelines for hazardous material transport.
- It was pointed out again that there is a lack of adequate test criteria for liquid agents verses solid agents.
- Individual components of the binary agents are safe but when mixed they are now a hazard classified as a mass detonating explosive, Class 1.1.
- A question arose about what happens when binary agents are mixed and placed in the TEXS pipe but not used. Mr. Manole stated that the agents will not be removed from the pipe with the intention of reuse but will be destroyed by explosion or burning when taken out.
- A question arose if nitromethane could be ruled out now because it is not a binary agent.

- Mr. Seals pointed out that small scale testing could be used to preliminarily rank the three TEXS candidates but large scale testing will eventually have to be performed, particularly a critical mass test.

Mr. Herrera led the next session with the topic of generic formulations of the binary candidates. Particular attention was paid to the oxidizer agent of these formulations. Sodium perchlorate is generally used mixed with water to form an aqueous solution of approximately 35 to 50% water. Aqueous sodium perchlorate solutions are considered by the UN and the DOT to be flammable liquids because they may contribute oxygen to a fire if there is a problem. The oxidizing agents cannot be stored with reactive agents and certain metals as a reaction could occur.

Mr. Manole pointed out that the Army stores chemicals such as lye, Draino, soaps, etc., in general purpose warehousing with some of these chemicals being relatively hazardous.

Mr. Herrera presented viewgraphs of the United Nations hazard classification flowcharts for explosives and pointed out that the first question to be answered would be "Is the substance manufactured with the view to producing a practical explosive or pyrotechnic effect?" A no answer leads to certain test sequences. A yes answer leads to more stringent test sequences. Individual components of the binary agent (oxidizer/fuel) are not produced with the intent of producing an explosive or pyrotechnics and therefore can be answered with a no. The binary agents are only intended to be explosive when mixed. Nitromethane is not a binary agent and will be intended to be used as a explosive in the TEXS context and therefore will have to follow the yes path. The consensus of all government meeting attendees was that it would be a valid approach to follow the UN/DOT classification methodology as presented in the flow diagrams.

Another open discussion was pursued to discuss these issues. Those discussed are:

- The DOD Explosives Safety Board will have a meeting October 24 and 25 to discuss the issue of liquid propellant/explosive/blasting agents. It was asked if Mr. Manole could arrange to attend this meeting and Mr. Herrera also. Mr. Manole stated that he would have to have the permission of the PM office but he would try. Mr. Herrera stated he could attend. Mr. Bill Smith of the U.S. Army stated that an outside contractor would have to be invited by the board. Mr. Bill Smith is to check with the board and notify Mr. Herrera by Monday afternoon if he is to attend.
- Mr. Manole stated that the ARDEC Safety Board initially gave the binary candidates an explosive classification until further discussions with the DOD safety community (the reason for this meeting).
- The group looked into DOD classification parameters for sodium perchlorate and determined per AMC 385-100 that there is not a separate classification for sodium perchlorate but just for perchlorates in general. Perchlorates are classified as Class 1.4D if in original container (385-100, page 19-14) and Class 1.3D if not in original container. Class D includes items such as TNT, picric acid, or pentolite. Page 19-19 of 385-100 has perchlorates classified as Group L which includes items such as ammonium nitrate or solid peroxides.

- Mr. Manole stated that the binary agents would be stored in original packaging of DOT specified metal drums. If the safety community desired they would agree to store and transport in stronger drums with increased wall thickness, etc.
- It was stated that there are two ways to approach reclassification. The first would be to ask DOT to change the regulations as specified in Title 49, Code of Federal Regulations which the DOT is usually reluctant to do. The other method is to ask DOT to grant an exemption to these materials which is the usual procedure.
- Mr. Elliott suggested that the PM should state, by letter, that TEXS components are binary with the oxidizer being an aqueous agent which is not addressed in 385-100. Specific labeling and packing requirements should be met. He felt this method would not be challenged.
- Mr. Manole stated that the PM is willing to do any test the safety community desires to be able to qualify the TEXS components for storage in general purpose warehouse.

Mr. William Toliver of SwRI presented the next session. This session was coverage of UN, DOT and DOD hazard classification of nitromethane. Mr. Toliver stated that the UN and DOT procedures are identical. Nitromethane is classified as flammable liquid by both. The UN hazard classification procedure flow diagrams were shown again and it was pointed out that nitromethane is intended to be an explosive substance in the TEXS context and would have to take the YES branch leading to more stringent testing.

Mr. Toliver then presented the DOD classifications for nitromethane which is Hazard Class IV, liquid propellants except that it can be classified in Hazard Class II in the following circumstances:

- Technical grade or better nitromethane in unit quantities of 55 gallons or less stored in DOT 17E or C drums.
- Drums are stored one tier high
- Drums are protected from direct sun rays
- Maximum storage life of 2 years unless storage life tests indicate product meets purchase specification at that time. Such tests are to be repeated at 1-year intervals thereafter.

Mr. Toliver stated that the most important difference between Hazard Group IV and II is the quantity/distance relationships, Hazard Group II having less distance requirements than IV.

Mr. Manole gave some generic facts regarding manufacture, storage, and transportation of nitromethane.

The final session of the meeting was an open discussion of nitromethane. The following items were brought up:

- Mr. Herrera gave short brief on how nitromethane could be tested for the varying effects of nitroparaffin sensitivities.
- Mr. Manole says nitromethane can be made to almost any sensitivity by altering the types and amounts of nitroparaffins.
- Mr. Manole stated that the true tests of an explosive is the substances ability to sustain a detonation wave front throughout the entire medium.
- If a nitromethane specification were to be written for use in TEXS, all nitroparaffins would have to be studies and chacterized for their safety (carcinogenic effects) and performance effects on the nitromethane. The allowable tolerances in the specfication of these nitroparafin would reflect this study.
- Mr. Earle Smith of Norton AFB again stated that the Air Force would prefer the use of the binary candidates.

At the end of this session, Mr. Herrera asked Mr. Manole how to inform the DOT of the results of this meeting. Mr. Manole stated that he would ask the PM office for a decision on the requirements for a briefing to DOT in Washington, D.C.

CONCLUSIONS

Nitromethane is classified as a flammable liquid by the United Nations, Department of Transportation and the Occupational Safety and Health Administration. This classification requires transportation in containers less than 110 gallons. OSHA requires nitromethane storage in DOT-approved containers less than 60 gallons or portable tanks with less than 660 gallon capacity.

DOD classifies nitromethane as a liquid propellant mass detonating substance which invokes quantity/distance requirements. With special storage provisions nitromethane becomes downgraded to less hazardous classes with shorter quantity/distance relationships. This is advantageous to reduce the amount of square footage required for storage. To store nitromethane in general purpose warehousing the Army will have to re-examine the current classification or grant a waiver. Waivers are difficult to obtain and granted on a site by site basis. Waivers are for limited periods not exceeding 5 years. Evaluation is required on a yearly basis. The waiver approach does not seem feasible.

Two alternatives may be preferable to obtaining a DOD waiver. Based on experimental findings, the reclassification of nitromethane to a less hazardous group will allow less stringent storage and handling requirements. The possibility also exists to convert nitromethane to a binary system, whereby each of the constituents is classified within a less hazardous grouping, and hazardous characteristics are only in evidence at the end use application. This approach would also be feasible for other candidate propellant slurry/mixtures. Further study will be necessary to optimize either of the alternatives.

BIBLIOGRAPHY

Code of Federal Regulations, Department of Labor, Title 29, Chapter XVII, Occupational Safety and Health Administration

Code of Federal Regulations, Department of Transportation, Title 49

Department of the Army, Army Material Command, AMC Regulation 385-100, *Safety Manual*

Department of Defense, Department of the Army, Technical Bulletin 700-2, *Explosives Hazard Classification Procedures*


Meyer, Rudolf. *Explosives*. 3rd ed. New York: VCH, 1987

United Nations. *Recommendations on the Transport of Dangerous Goods*, ST/SG/AC.10/1/rev. 4


United Nations. *Recommendations on the Transport of Dangerous Goods, Tests and Criteria*, ST/SG/AC.10/11/rev. 4

APPENDIX A


UNITED NATIONS PROCEDURE FOR ASSIGNMENT OF HAZARD DIVISION



UNITED NATIONS HAZARDOUS SUBSTANCE ACCEPTANCE PROCEDURE



DOD ADMINISTRATIVE PROCEDURE FOR HAZARD CLASSIFICATION



DISTRIBUTION LIST

Administrator
Defense Technical Info Center
ATTN: Accessions Division (12)
Cameron Station
Alexandria, VA 22304-6145

HQDA (SARD-TR)
Washington, D.C. 20310-0001

Commander
U.S. Army Materiel Command
ATTN: AMCDRA-ST
5001 Eisenhower Avenue
Alexandria, VA 22333-0001

Commander
U.S. Army Laboratory Command
ATTN: AMSLC-DL
Adelphi, MD 20783-1145

Director
Benet Weapons Laboratory
Armament RD&E Center
U.S. Army AMCCOM
ATTN: SMCAR-CCB-TL
Watervliet, NY 12189-4050

Commander
U.S. Army Armament, Munitions and Chemical Command
ATTN: SMCAR-ESP-L
Rock Island, IL 61299-5000

Commander
U.S. Army Aviation Systems Command
ATTN: AMSAV-DACL
4300 Goodfellow Blvd.
St. Louis, MO 63120-1798

Director
U.S. Army Aviation Research and Technology Activity
Ames Research Center
Moffett Field, CA 94035-1099

Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-CS-R (DOC)
Redstone Arsenal, AL 35898-5010

Commander
U.S. Army Tank-Automotive Command
ATTN: AMSTA-TSL (Technical Library)
Warren, MI 48397-5000

Director
U.S. Army TRADOC Analysis Command
ATTN: ATAA-SL
White Sands Missile Range, NM 88002-5502

Commandant
U.S. Army Infantry School
ATTN: ATSH-CD-CSO-OR
Fort Benning, GA 31905-5660

Air Force Armament Laboratory
ATTN: AFATL/DLODL
Eglin AFB, FL 32542-5000

Director
USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen
Aberdeen Proving Ground, MD 21005-5066

Commander
USATECOM
ATTN: AMSTE-TD
Aberdeen Proving Ground, MD 21005-5066

Commander
CRDEC
AMCCOM
ATTN: SMCCR-RSP-A
Aberdeen Proving Ground, MD 21010-5423

Commander
CRDEC
AMCCOM
ATTN: SMCCR-MSI
SMCCR-MU
Aberdeen Proving Ground, MD 21010-5423

Director
VLAMO
ATTN: AMSLC-VL-D
Aberdeen Proving Ground, MD 21005-5066

Director
Defense Advanced Research Projects Agency
ATTN: J. Lupo
J. Richardson
1400 Wilson Boulevard
Arlington, VA 22209

HQDA
ATTN: SARD-ZT, G. Singley
SARD-TT, I. Szkrybalo
SARD-TC, C. Church
D. Zimmerman
Washington, D.C. 20310

HQ
U.S. Army Materiel Command
ATTN: AMCICP-AD, B. Dunetz
5001 Eisenhower Avenue
Alexandria, VA 22333-0001

Commander
Armament RD&E Center
U.S. Army AMCCOM
ATTN: SMCAR-IMI-I (5)
SMCAR-AEE-B, D. Downs
SMCAR-AEE-BR, B. Brodman
W. Seals
A. Beardell
SMCAR-AEE-W, N. Slagg
SMCAR-AEE, A. Bracuti
J. Lannon
M. Gupta
J. Salo
D. Chieu
SMCAR-FSS-D, L. Frauen
SMCAR-FSA-S, H. Liberman
SMCAR-FSS-DA, J. Feneck
R. Kopmann
J. Irizarry
SMCAR-CCS-C, T. Hung
SMCAR-SFS
Picatinny Arsenal, NJ 07806-5000

Director
Benet Weapons Laboratory
Armament RD&E Center
U.S. Army AMCCOM
ATTN: SMCAR-CCB, L. Johnson
SMCAR-CCB-S, F. Heiser
SMCAR-CCB-DS, E. Conroy
A. Graham
Watervliet, NY 12189-4050

Commander
Materials Technology Laboratory
U.S. Army Laboratory Command
ATTN: SLCMT-MCM-SB, M. Levy
Watertown, MA 02172-0001

Commander
USACECOM R&D Technical Library
ATTN: ASQNC-ELC-I-T, Myer Center
Ft. Monmouth, NJ 07703-5000

Commander
U.S. Army Harry Diamond Laboratories
ATTN: SLCHD-TA-L
2800 Powder Mill Road
Adelphi, MD 20783-1145

Commander
U.S. Army Belvoir Research and Development Center
ATTN: STRBE-WC
Technical Library (Vault) B-315
Fort Belvoir, VA 22060-5606

Commander
U.S. Army Research Office
ATTN: Technical Library
P.O. Box 12211
Research Triangle Park, NC 27709-2211

Commandant
U.S. Army Field Artillery School
ATTN: ATSF-CMW
ATSF-TSM-CN, J. Spicer
Fort Sill, OK 73503

Commandant
U.S. Army Armor Center
ATTN: ATSB-CD-MLD
Fort Knox, KY 40121

Commander
Naval Surface Weapons Center
ATTN: D.A. Wilson (Code G31)
Dahlgren, VA 22448-5000

Commander
Naval Surface Weapons Center
ATTN: J. East (Code G33)
Dahlgren, VA 22448-5000

Commander
U.S. Naval Surface Weapons Center
ATTN: O. Dengrel
K. Thorsted
Silver Spring, MD 20902-5000

Commander (Code 3247)
Naval Weapons Center
Gun Systems Branch
China Lake, CA 93555-6000

Superintendent
Naval Postgraduate School
Department of Mechanical Engineering
ATTN: Code 1424, Library
Monterey, CA 93943

AFOSR/NA (L. Caveny)
Building 410
Bolling AFB
Washington, DC 20332

Commandant
USAFAS
ATTN: ATSF-TSM-CN
Fort Sill, OK 73503-5600

Director
Jet Propulsion Laboratory
ATTN: Technical Library
4800 Oak Grove Drive
Pasadena, CA 91109

Director
National Aeronautics and Space Administration
ATTN: MS-603, Technical Library
MS-86, Dr. Povinelli
21000 Brookpark Road
Lewis Research Center
Cleveland, OH 44135

Director
National Aeronautics and Space Administration
Manned Spacecraft Center
Houston, TX 77058

Central Intelligence Agency
Office of Central Reference
Dissemination Branch
Room GE-47 HQS
Washington, DC 20502

Central Intelligence Agency
ATTN: Joseph E. Backofen
HQ Room 5F22
Washington, DC 20502

Calspan Corporation
ATTN: Technical Library
P.O. Box 400
Buffalo, NY 14225

General Electric Ordnance System Division
ATTN: J. Mandzy, OP43-220
R.E. Mayer
H. West
W. Pasko
R. Pate
I. Magoon
J. Scudiere
Minh Luu
100 Plastics Avenue
Pittsfield, MA 01201-3698

General Electric Company
Armament Systems Department
ATTN: D. Maher
Burlington, VT 05401

Honeywell, Inc.
ATTN: R.E. Tompkins
MN38-330
10400 Yellow Circle Drive
Minnetonka, MN 55343

IITRI
ATTN: Library
10 West 35th Street
Chicago, IL 60616

Olin Chemicals Research
ATTN: David Gavin
P.O. Box 586
Cheshire, CT 06410-0586

Paul Gough Associates
ATTN: Paul Gough
1048 South Street
Portsmouth, NH 03801-5423

Safety Consulting Engineer
ATTN: Mr. C. James Dahn
5240 Pearl Street
Rosemont, IL 60018

Sandia National Laboratories
ATTN: R. R. Rychnovsky, Div 8152
S. Griffiths, Div 8244
R. Carling, Div 8152
P.O. Box 969
Livermore, CA 94551-0969

Science Applications, Inc.
ATTN: R. Edelman
23146 Cumorah Crest
Woodland Hills, CA 91364

Science Applications International Corporation
ATTN: Dr. F.T. Phillips
Dr. Fred Su
10210 Campus Point Drive
San Diego, CA 92121

Science Applications International Corporation
ATTN: Norman Banks
4900 Waters Edge Drive
Suite 255
Raleigh, NC 27606

Sundstrand Aviation Operations
ATTN: Mr. Owen Briles
P.O. Box 7202
Rockford, IL 61125

Veritay Technology, Inc.
ATTN: E.B. Fisher
4845 Millersport Highway
P.O. Box 305
East Amherst, NY 14051-0305

Director
The Johns Hopkins University
Applied Physics Laboratory
Johns Hopkins Road
Laurel, MD 20707

Director
CPIA
The Johns Hopkins University
ATTN: T. Christian
Technical Library
Johns Hopkins Road
Laurel, MD 20707

University of Illinois at Chicago
ATTN: Professor Sohail Murad
Department of Chemical Engineering
Box 4348
Chicago, IL 60680

University of Maryland at College Park
ATTN: Professor Franz Kasler
Department of Chemistry
College Park, MD 20742

University of Missouri at Columbia
ATTN: Professor R. Thompson
Department of Chemistry
Columbia, MO 65211

University of Michigan
ATTN: Professor Gerard M. Faeth
Department of Aerospace Engineering
Ann Arbor, MI 48109-3796

Director
Ballistic Research Laboratory
ATTN: AMXBR-OD-ST
Aberdeen Proving Ground, MD 21005-5423

Commander
U.S. Army Armament, Munitions and Chemical Command
ATTN: AMSMC-GCL (D)
Picatinny Arsenal, NJ 07806-5000

University of Missouri at Columbia
ATTN: Professor F.K. Ross Research Reactor
Columbia, MO 65211

University of Missouri at Kansas City
Department of Physics
ATTN: Professor R.D. Murphy
1110 East 48th Street
Kansas City, MO 64110-2499

Pennsylvania State University
Department of Mechanical Engineering
ATTN: Professor K. Kuc
University Park, PA 16802

Princeton Combustion Research Laboratories, Inc.
ATTN: N.A. Messina
M. Summerfield
4275 U.S. Highway One North
Monmouth Junction, NJ 08852

University of Arkansas
Department of Chemical Engineering
ATTN J. Havens
227 Engineering Building
Fayetteville, AR 72701

University of Delaware
Department of Chemistry
ATTN: MR. James Cronin
Professor Thomas Brill
MR. Peter Spohn
Newark, DE 19711

University of Texas at Austin
Bureau of Engineering Research
ATTN: BRC EME133, Room 1.100
H. Fair
10100 Burnet Road
Austin, TX 78758

Olin Corporation
ATTN: Victor A. Corso
DR. Ronald L Dotson
24 Science Park
New Haven, CT 06511