

2

TECHNICAL REPORT BRL-TR-3158

BRL

DTIC FILE COPY

THE SHAPED CHARGE CONCEPT
PART II. THE HISTORY OF SHAPED CHARGES

WILLIAM P. WALTERS

SEPTEMBER 1990

DTIC
ELECTE
SEP 28 1990
S B D
Co

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

AD-A226 772

90 09 27 078

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 1990		3. REPORT TYPE AND DATES COVERED Final June 1989 - June 1990
4. TITLE AND SUBTITLE The Shaped Charge Concept, Part II. The History of Shaped Charges			5. FUNDING NUMBERS PR: 1L162618AH80 44024-022-65	
6. AUTHOR(S) William P. Walters				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066			10. SPONSORING / MONITORING AGENCY REPORT NUMBER BRL-TR-3158	
11. SUPPLEMENTARY NOTES Part I - BRL Report No. BRL-TR-3142, August 1990				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This article is the second of a three part series on hollow charges and shaped charges. This part depicts the history of shaped charges from their early beginning through the post World War II era. 				
14. SUBJECT TERMS Shaped Charges, Penetration, Jets, Hypervelocity Impact, Warheads			15. NUMBER OF PAGES 29	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

UNCLASSIFIED

INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

	ACKNOWLEDGMENT	v
1.	INTRODUCTION	1
2.	HISTORY	1
3.	REFERENCES	15
	DISTRIBUTION	21



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENT

This manuscript was prepared while the author was a Visiting Research Scholar at the Center for Composite Materials, University of Delaware. The University of Delaware is gratefully acknowledged as being an excellent host during my tenure from June 1989 to June 1990.

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

The term "shaped charge" is applied to explosive charges with lined or unlined cavities. The cavity is formed in the end of the explosive charge opposite the point of detonation. The term "shaped charge," however, has a more general meaning, e.g., in Cook (1958). The shaped charge is sometimes referred to as the hollow charge (in the U.K. and the U.S.), the cumulative charge (in the USSR), or the Hohlladung (in Germany).

2. HISTORY

The history of shaped charge conception and development is wrought with controversy. In 1792, the mining engineer, Franz von Baader (1792), allegedly noted that one can focus the energy of an explosive blast on a small area by forming a hollow in the charge. Lenz (1965) stated that Baader, in 1799 (not 1792!), observed that if depressions or shapes were cut in an explosive and placed face down on a steel plate, the detonation would cause these shapes to appear on the plate. This is known as explosive engraving. D. R. Kennedy (1983) presents additional information on the life of von Baader and his version of the history of the shaped charge effect. Other historical accounts are given in Berkholtz (1988) and in Walters and Zukas (1989).

The original von Baader (1792) paper, however, primarily discussed bore hole drilling and loading, confinement effects on propellants, the positioning of a small air cavity between the explosive powder and the tamping (at best, a standoff distance effect), and rock fragmentation. His original paper did not discuss explosive engraving or hollow cavity charges. However, this is a moot point since von Baader used black powder in his experiments which is not capable of detonation or shock formation. Actual shaped charge devices were made possible by the discovery of blasting caps (detonators) by Alfred Nobel (Mohaupt 1966; E. I. du Pont 1980) in 1867. The explosive reaction initiated by these blasting caps could propagate through a column of explosive without the use of confinement. This was termed "detonation" or "brisant explosion." Thus, the first demonstration of the hollow cavity effect for high explosives was achieved by von Foerster (sometimes spelled Forsier, the correct spelling being Forster with an umlaut over the "o" which may be written as "oe") in 1883 (von Foerster 1883, 1884). A translation of some of Lieutenant von Foerster's work is given in Wisser (1886). Quoting from von Foerster (Wisser 1886):

"If a coin be placed between a gun cotton cartridge and a wrought-iron plate, the figures and letters in relief on the coin will appear in the iron as depressions after the explosion; if, instead of the coin, a green leaf be inserted, the entire skeleton of the leaf will appear

on the iron plate after the explosion. The more prominent, as well as the finer veins, protect the underlying iron, the more delicate parts of the leaf, lying between the veins, cannot afford the same protection; hence, the depression under the latter is the greater."

Again, this is a form of explosive engraving. Kennedy (1983), Freiwald (1941), Schardin (1954), and Berkholtz (1988) provide further detail on the discoveries of von Foerster and conclude that he was the true discoverer of the modern hollow charge.

Also, Gustov Bloem (1886) of Dusseldorf patented a shell for detonating caps which resembles a shaped charge with a hemispherical liner.

The hollow cavity (i.e., unlined shaped charge) was rediscovered by Charles E. Munroe of the Naval Torpedo Station, Newport, Rhode Island. Munroe's discoveries date from 1888 and are well documented (Munroe 1888a, 1888b, 1888c, 1894, 1900). The hollow charge or cavity effect is known in the U.S. and U.K. as the Munroe Effect.

Munroe (1888c) detonated blocks of explosive in contact with steel plates. The explosive charge had the initials U.S.N. (United States Navy) inscribed on the charge opposite the point of initiation. These initials were reproduced on the steel plate. Munroe further observed that when a cavity was formed in a block of explosive, opposite the point of initiation, the penetration, or depth of the crater produced in the target, increased. In other words, a deeper cavity could be formed in a steel block using a smaller mass of explosive! In Munroe's own words:

"We have offered as an hypothesis to explain this phenomenon that, where spaces exist between the gun cotton and the iron, portions of the undetonated gun cotton, or of the products of the explosion, the indentions are produced by the impact of these moving particles. We have devised many experiments to test this theory, and all have tended to confirm it. Among others we have bored deeper and deeper holes in the gun cotton, until we have completely perforated it, and the indentations made in the iron plates have increased with the depth of the hole in the gun cotton disk until, when the hole was bored completely through the gun cotton, we succeeded in completely perforating the iron plate." (Munroe 1888c; Clark 1948)

The increase in penetration results from the focusing of the explosive gases (detonation products) by the hollow cavity.

One of the first lined shaped charges (or perhaps the first shaped charge if we discount Bloem [1886]) was devised by Munroe (1894) and Clark (1948). This device consisted of a tin can with sticks of dynamite tied around and on top of it, with the open end of the tin can pointing downward. It was used to punch a hole through the top of a steel safe.

Early German reference to the hollow cavity effect, after von Foerster and Bloem, occurred in 1911-1912 patents in the U.K. and Germany by WASAG (Westfälische Anhaltische Sprengstoff Actien Gesellschaft) (1910, 1911). The WASAG patents clearly demonstrated the hollow cavity effect and the lined shaped charge effect. Also, M. Neumann (1911) and E. Neumann (1914) (who are often confused in the literature) demonstrated the hollow cavity effect. M. Neumann (1911) shows a greater penetration into a steel plate from a cylinder of explosive with a hollow, conical cavity (247 grams of Trinitrotoluol) than from a solid cylinder (310 grams of Trinitrotoluol).

This clearly illustrates what is known in the U.S. and Britain as the "Munroe Effect" and in Germany as the "Neumann Effect." The depth of the crater in the target can be further increased by displacing the hollow charge some optimal distance from the target, i.e., increasing the standoff distance, especially for a lined cavity charge. This situation was depicted graphically in Figure 4 of Part 1.

This effect was also illustrated in 1941 in Germany when a hollow cavity charge and a lined cavity charge detonated at a certain standoff distance above an armor plate were compared (OTIB 1941). The target plate was ship armor steel and the explosive mixture was 50% TNT and 50% cyclonite. The hollow cavity was a hemisphere with a cylindrical extension at its base equal to one-half of the diameter of the cavity (D). The liner was made of iron. The explosive contour was of the same geometry as the cavity and the explosive thickness was 0.15 times the cavity diameter. For the (unlined) hollow charge the penetration $P = 0.4D$ at zero standoff. For the lined cavity, $P = 0.7D$ at zero standoff, and $P = 1.2D$ for standoffs between 0.5 and 1.5D. For the iron-lined charge, D represents the inside diameter of the liner.

These formulae (OTIB 1941) are not accurate but are valid only for this particular experiment. They are not universal laws, but do illustrate the relative increase in performance in going from unlined to lined charges with a non-zero standoff distance.

Kennedy (1983) describes similar studies dated from 1913 to the early 1930s, concerned with the hollow cavity effect in mining and detonation devices.

Others, notably Baum et al. (1949) and Rollings et al. (1971), attribute the hollow cavity effect to

M. Sukharevskii (also transliterated as Sukhreski and Sucharewski), see Murphy (1983), for example. Indeed, Sukharevskii (1925) was the first known Soviet to investigate the shaped charge effect (in 1925-1926). He observed an increase in the explosive effect by a factor of 3 to 5. He also noted that the dimensions of the perforation achieved by hollow charges were proportional to the dimensions of the hollow cavity of the charge. Berkholtz (1988) and Schardin (1954) provide further detail on the life and results of Sukharevskii.

The first Italian paper on the shaped charge effect was by C. Lodati (1932). Apparently Schardin (1954) reviewed this work and reported that Lodati did not contribute anything new to the field.

Early British development of the hollow cavity charge was reported in Kline (1945). Eather and Griffiths (1983) of the U.K. provided a history of the U.K. contributions to the field of shaped charges which includes the achievements of Evans, Ubbelohde, Taylor, Tuck, Mott, Hill, Pack, and others. A. Marshall (1920) provides an early history of the unlined cavity charge and attributes its discovery to Munroe.

In the U.S., the contributions of Watson (1925) on percussion fuzes and Wood (1936) on self-forging fragments (also called explosively-formed penetrators, Misznay-Schardin devices, ballistic discs, or P-charge projectiles) were significant.

The Watson percussion fuzes, patented in 1925, used a parabola-shaped booster charge with a metal-lined hemispherical cavity, or "arched shield," to intensify the effect of the booster charge. Watson (1925) stated that the lined cavity effect required only one-fifth to one-sixth as much explosive as an unlined booster and the lined cavity charge would function over a "considerable air gap." This fuze is, in effect, a detonator using the shaped charge principle.

R. W. Wood (1936) of the Johns Hopkins University described what is known today as an "explosively formed penetrator." Wood's studies originated during his investigation of the death of a young woman who, on opening the door of a house furnace, was killed by a small particle of metal which flew out of the fire and penetrated her breast bone. The small particle of metal was from the coned end of a detonator which was apparently delivered with the coal from the mine. His paper also discussed the plastic flow of metals, deflagration, and detonation. Eichelberger (1954) credited Wood for recognizing the enhancement obtained by metal lined hollow charges.

Also, Payman and Woodhead (1937) of the U.K. reported observations of jets from the cavity in the ends of detonators. They attributed this jetting process to the "Munroe Effect."

The lined cavity shaped charge research accelerated tremendously between 1935 and 1950, due primarily to World War II and the application of shaped charges to the bazooka, panzerfaust, and other devices. The history of shaped charge development during this time frame is somewhat ambiguous in that the British, Germans, and U.S. all have made significant claims to the early development of modern lined cavity charges.

The discoverers of the modern lined cavity effect were Franz Rudolf Thomanek for Germany and Henry Hans Mohaupt, a Swiss, for the U.S.. Thomanek and Mohaupt independently perfected the hollow charge concept and developed the first effective lined cavity shaped charge penetrators.

Thomanek's early work dates from late 1935 to 1939 (Freiwald 1935; Schardin 1954; Brandmayer and Thomanek 1943; Thomanek 1942, 1959, 1960, 1978; and Thomanek and von Hutten 1935). The Thomanek and von Hutten patent applications (approximately 1935) pertain to hollow charges, armor piercing shells, the shell nose design, high explosive mixtures and additives, techniques for casting high explosives, impact fuze systems, explosive initiation systems, shoulder-fired weapons, and small caliber, hand-held weapons. Unfortunately, this document is not dated by year, but the translator's note states, "(Partly before 1935?)."

Thomanek (1960) claims discovery of the hollow charge lining effect on 4 February 1938. Thomanek and von Hutten (1935) describe the tests and work conducted by Thomanek and his co-worker, Brandmayer.

Thomanek (1942) presents a detailed account of the hollow and lined cavity charge work he conducted from 1935 to 1941 in support of compensation he eventually received from the Reich. He credits Foerster with the first hollow charge work in 1883 and notes the contributions of WASAG and E. Neumann.

Thomanek reports that in 1935-36 an armor-piercing projectile with a hollow shaped charge was developed by the Army Weapons Office and patented by Captain Wimmer. The anti-tank rifle was demonstrated by Thomanek in the presence of Hitler in late 1935. Standoff effects, liner geometry, and liner materials were studied extensively from 1937 to the end of World War II (Walters and Zukas 1989; Thomanek 1942).

Thomanek and colleagues suspected that overlapping shock waves from the jetting of a hollow charge formed a new, more intense shock wave from the superposition of two primary shock waves. Thus, tests were performed with a glass-lined, evacuated cavity to determine the optimal air cavity pressure. In 1938, Thomanek and Schardin observed that glass lined shaped charges revealed superior performance due to the

glass liner and not due to the evacuated cavity. Further studies concluded that iron and copper liners were especially suitable for increasing penetration (Schardin 1954).

Thomanek (1942) listed some of his most significant accomplishments during World War II as the development of: a casting device for hollow charges (patent applied for 10 August 1940); acute angle cone and liner with wall thickness for armor-piercing projectiles (patent applied for 9 September 1940); diaphragm-like liner for hollow charges (6 November 1940); and a hollow charge for rifle anti-tank land mines (29 May 1941).

Other German developments included steel liners (0.5- to 1.0-mm-thick) that were found to be superior to gray-iron casting (June 1940) and hollow charges with conical liners (up to 1.5-mm-thick and with angles between 20° and 45°) which would perforate 15-mm armor plate at the proper standoff (25-30 mm). The charges used were cast. An increase of the diameter of the blast hole was made possible by the use of a bell-shaped, hollow charge which would also permit fewer irregularities than with the acute cone. The diameter was 1 cm (of the charge). The idea of firing a hollow charge shell from the shoulder was first conceived in 1937 (i.e., a rifle grenade).

Schardin (1954) noted that an exceptional degree of precision was required to guarantee the homogeneity of the jet from a shaped charge liner, especially the rotational symmetry of the liner wall thickness.

Schardin also reported on the early simulation of jet formation resulting from the impact of two streams of water. Also, experiments were conducted where a closed, conical glass container filled with air was plunged, apex first, into a tank of water. An explosive charge was detonated in the water below the apex of the glass cone. The resulting shock wave in water collapsed the glass liner and formed a jet of water similar to a hollow charge. The jet of water had a higher velocity than the water fountain formed from a simple underwater detonation without the glass liner.

The jet formed from a spinning shaped charge was also studied. It was observed that some jets formed from spinning shaped charges were tube-like in their structure, i.e., hollow. Water jets formed from impinging jet streams with rotating and tapered nozzles were shown to simulate this tube formation or hollow jets. It was also noted that jets from spinning shaped charges with hemispherical liners were less susceptible to spin effects (angular dispersion) than jets from conical shaped charge liners (Schardin 1954).

Schardin also reported on jet velocities of 90 km/sec resulting from symmetrically rotated shaped charges with beryllium liners. These charges were fired into a vacuum and were primarily in the gaseous phase.

L. Simon (1947) provides further detail on the German shaped charge studies during World War II and on the organization of the German military/industrial complex.

Mohaupt independently developed and introduced the shaped charge concept to the U.S.. Mohaupt's early work is given in Mohaupt (1966, 1941a, 1941b, 1947). Mohaupt's patent claimed a date of 9 November 1939 (Mohaupt, Mohaupt, and Kauders 1941a) .

Mohaupt, using lined cavity charges, designed practical military devices ranging from rifle grenades to mortars to 100-mm diameter artillery projectiles. These devices were test-fired at the Swiss Army Proving Ground at Thun, at Mohaupt's Laboratory, and at the French Naval Artillery Proving Ground at Gavre. These results were also demonstrated to the U.K. who then began development programs of their own, citing the U.K. WASAG patent as prior art (WASAG 1911). Following the early results of World War II, the French Government authorized the release of Mohaupt's information to the U.S. and in late 1940, tests were conducted at Aberdeen Proving Ground, Maryland, using several aspects of lined cavity shaped charges (Mohaupt 1966). The U.S. Ordnance Department had previously rejected a shaped charge munition presented by Nevil M. Hopkins, an American inventor. The Ordnance Department, however, used Hopkins' claim and the WASAG patent to lower Mohaupt's requested price of \$25,000. The U.S. accepted the program, classified it, and thus excluded Dr. Mohaupt from the effort but produced the 2.36-inch HEAT machine gun grenade and the 75-mm and 105-mm HEAT artillery projectiles in 1941. Later, the machine gun grenade was modified to include a rocket motor and a shoulder launcher and became the bazooka. The bazooka was first used by the U.K. in North Africa in 1941. Other HEAT rounds were fired from tank mounted howitzers (Kennedy 1983, Mohaupt 1966). Berkholz (1988), Green et al. (1955), and Watson (1950) provide additional detail on Mohaupt, Hopkins, and the use of HEAT rounds in World War II. Gray et al. (1947) also filed a U.S. patent (in 1941) on a shaped charge device during the same period as Mohaupt.

The anti-tank rocket weapons of World War II were pioneered by Dr. Robert H. Goddard who offered the Ordnance Department a series of tube launchers designed to fire rocket projectiles in 1918. Goddard died before receiving credit for his pioneering work, although the bazooka, adopted 24 years later, closely resembled his 1918 model. Dr. Hickman, a student of Robert Goddard, provided continuity to the studies that produced the anti-tank rocket weapon of World War II (Green et al. 1955). Incidentally, Leslie Skinner, formerly of Aberdeen Proving Ground, has been called the "Father of the Bazooka." The Bazooka derived its name from a homemade trombone popularized by radio comedian Bob Burns (Weston 1985).

Kennedy (1983), Berkholz (1988), and Walters and Zukas (1989) provide additional detail on bazookas as well as on the work of Thomanek and Mohaupt.

The German development of shaped charge warheads during the World War II period is discussed in Kennedy (1983, 1985), L. Simon (1947), Cave et al. (1945), Birkhoff (1947), Schumann (1945), OTIB (1941), Schardin (1954), Kline (1945), Thomanek (1942, 1960, 1978), and Thomanek and von Hutern (1935). Simon (1947) and Cave et al. (1945) entered Germany near the end of World War II to study and recover German technology. Simon (1947) reported on flash x-ray photographs in Germany including collapse studies of conical and hemispherical liners. Various other liner geometries were studied including helmet-shaped liners, bottle-shaped liners, and ellipsoidal liners. The effect of varying the cone angle, the wall thickness, and the standoff distance was studied for various shaped charges. Also, the effect of tapering the liner with respect to thickness was studied. The Germans concluded that 60/40 cyclotol (a RDX-TNT mixture) was the optimum explosive fill for shaped charges and aluminized explosives provided no additional advantage. According to Simon, the liner materials studied were steel, sintered iron, copper, aluminum, and zinc. It was realized that copper was the best liner material, but due to the shortage of copper in Germany, zinc liners were used instead.

Schumann (1941) reports on studies relating to standoff distance effects, explosive lenses, wave-shaping, and hemispherical liners. Schumann concluded that the hemisphere was an effective shaped charge liner geometry (actually a hemisphere with a cylindrical extension on its equator).

Wagner (1944) discussed the SHL (Schwere Hohlladung or heavy shaped charge). The SHL 500 was a 65-cm diameter shaped charge used against light ships. The SHL 1000 was apparently an improvement to the SHL 500. The largest SHL of this series was called the Beethoven and had a diameter of 180 cm with 5,000 kg of high explosive. The Beethoven was designed for use against ships and ground fortifications. During the Normandy invasion, the Beethoven destroyed two battleships and four large transport ships. The Beethoven was the forerunner of the MISTEL I and MISTEL II, which are discussed under shaped charge applications.

Wagner also discussed the development and production of other armor piercing, shaped charge projectiles

The hollow charge, or unlined shaped charge was first deployed on May 10, 1940 by the Germans on the Belgian fort of Eben Emael. The Germans, using 77 men, 10 gliders (carrying about 77,000 deutschmarks) and 56 hollow charges, defeated 780 men defending the world's strongest fort. The fort fell in somewhat more than a day, but the decisive struggle took only 20 minutes (Mrázek 1970). The hollow

charges were of two sizes, a 110-pound and a 25-pound charge. The hollow charges knocked out the steel cupolas (six-inches-thick) and observation turrets which led to the early demise of the Belgian defenses (Berkholtz 1988; Mrazek 1970).

The Germans were also instrumental in transferring hollow charge research to the Japanese. There is no evidence of hollow charge research in Japan before May 1942. At that time two German officers of the Army Weapons Office, Colonel Paul Niemueller and Major Walter Merkel, provided Japan with data and samples of the German 30- and 40-mm hollow charge rifle grenade. The Japanese officials involved were Lt. Col. Yoshitaka, the Japanese liaison officer for the Germans, and Col. A. Kobayashi, an explosives expert at the Second Army Arsenal in Tokyo (OTIR 1946). Other notable Japanese researchers were Futagami, Naruse, Nasu, Nagaoka, Nakiyama, and Lt. Gen. Kan. The hollow charges were presented as highly secret and valuable project and the Germans and Japanese continued to exchange shaped charge data until the cessation of hostilities in 1945.

The Japanese instigated a research and development program of their own and additional shaped charge designs were received from Germany. These designs included the panzerfaust and a large German hollow charge called the "MISTERIE?" (This is undoubtedly the MISTEL which evolved from the Beethoven charge discussed earlier). From the MISTEL, the Japanese developed the large SAKURA Bombs I and II for kamikaze attacks against warships which are discussed in Part 3.

In addition to the captured U.S. and British ammunition, and the information received from Germany, the Japanese did considerable independent research on shaped charges (OTIR 1946). This research included: gas flow and gas velocity from an unlined hollow charge; the jet velocity from a lined hollow charge; penetration versus standoff distance studies; hollow charge liner geometries varying from conical to hemispherical caps; various liner materials including mild steel, copper, aluminum, zinc, asbestos, molded bakelite, tin, and paper; recovery of jet particles in sand; and dynamic (missile) effects. The Japanese preferred laminated liners (three to seven sheets) over a single, homogeneous liner of the same thickness. The Japanese also concluded that a hole in the apex of a conical or hemispherical liner was desirable. Also, the size of this hole was critical, an optimal value for the apex hole diameter being one-tenth of the warhead charge diameter. (The wall thickness was taken as one twenty-fifth of the charge diameter and the liner diameter was taken to be four-fifths of the charge diameter for both conical and hemispherical liners). The optimal cone apex angle was determined to be between 35 to 50 degrees. Other tests used 94-mm-diameter, soft steel, hemispherical liners with a 2.5-mm wall thickness. The optimal open apex diameter was concluded to be three-sixteenths of the charge diameter for this warhead.

Tapered liners were designed based on the 30- and 40-mm German rifle grenades. They used 19° conical steel liners tapered from 0.5 mm at the apex to 1.0 mm at the base. Other projectiles used constant wall thickness, laminated liners. The Japanese also developed torpedos, 18 inches and 12 inches in diameter using a tapered wall, 45° conical steel shaped charge liner with an open apex (OTIR 1946).

Other studies related to detonation physics and methods of focusing the gas flow, calculation of the target hole volume and penetration, penetration of concrete targets, and the recovery of jet particles by reducing the explosive power (mixing dynamite with starch to reduce the "strength" of the dynamite) and capturing the jet in sand (OTIR 1946).

The explosive charges used in research were spherical and formed from the arcs of two circles. Thus, the cross section of the charge looked like a new moon or quarter moon, etc., depending on the two radii used. Cylindrical, tapered, and boattailed explosive geometries were also studied as well as the effect of the high explosive head height and the length-to-diameter ratio of the charge. In fact, the height of the charge was varied from 0.5 of a charge diameter to 6 charge diameters. A charge height of 1.5 to 2 charge diameters was concluded to be optimal for a 80-mm diameter charge with a 64-mm diameter soft iron, hemispherical liner and with a 2.5-mm-thick wall (OTIR 1946).

Futagami (OTIR 1946) tested two-dimensional charges, i.e., a flat, disc-shaped charge confined between two lead plates. Tests of this nature were used to evaluate various liner materials, cone apex angles, liner wall thickness effects, and the effect of the diameter of the open apex region. All of the effects, including standoff distance studies, were also investigated with "three-dimensional" shaped charges. Futagami also studied bimetallic liners of soft iron and copper (the iron was in contact with the high explosive). As mentioned earlier, various liner materials were studied, including paper (of course, as stated in OTIR [1946], "...the paper shell is tore in pieces and flies away."). The Japanese also noted that any cavity existing between the liner and the explosive reduces the penetrating capability of the warhead.

The Japanese anti-tank shells, although not as effective as those developed by the Germans or the Allies, were used effectively on the Burma front. Other Japanese innovations (Kennedy 1983) included the suicidal "Lunge" mine which was, in fact, a shaped charge with a wooden handle used as an anti-tank weapon.

Some of the research conducted in the U.K. in the early forties is reported in Monro (1943). Monro describes the research of Evans, Ubbelohde, Lennard-Jones, Devonshire, and Andrew. The U.K. studied cadmium liners (which probably produce molten jets) and steel liners (where the jet is probably not liquid). Other topics, as pursued by the Germans, Japanese, and U.S. were also investigated. Monro reports on

U.S. weapons tests and on the evaluation of captured German shaped charges with aluminum, hemispherical liners and on Italian shaped charges using mild steel, parabolic liners. Tuck's (1943) work was also significant in the early forties.

The research and development in the U.S. in the 1940s is documented in Kennedy (1983), Birkhoff (1947), Cook (1958), and DM-1 (1947). DM-1 (1947) is an interesting history of weapons and demolition devices developed during World War II. Several topics are covered ranging from pocket knives to flame throwers to Bangalore Torpedos to shaped charges. A Bangalore Torpedo is a long, light steel tube loaded with explosives. It is essentially a pipe bomb. This device was invented during World War II by Major R. L. McClintock of the Queen Victoria's own Madras Sappers and Miners near Bangalore in Mysore, India (DM-1 1947). The Bangalore Torpedo was used to remove barbed wire entanglements, clear mine fields, and to insert into holes in fortifications made by shaped charge devices.

Shaped charge development, based on the early work of Mohaupt, was continued in the U.S. by the Du Pont Company, the Hunter Manufacturing Company, Croydon, Pennsylvania (for the M2 shaped charge), the Doblins Manufacturing Company, the Hercules Powder Company, the Atlas Powder Company, and the Coming Glass Company (for glass conical liners). This work was directed by the Board of Engineer Equipment or Engineer Board (EB). Research was conducted by Du Pont and the Eastern Laboratory at Gibbstown, New Jersey. Demolition charges such as the M1, M2, M2A3, M3, M3A, and others were tested at Aberdeen Proving Ground in 1942 and developed by the corporations cited above. A chronology of demolition shaped charge development from 1942 to 1946 is given in DM-1 (1947). Also, specifications for the M2A3 and the M3 shaped charge are given in DM-1 1947. The M3 weighs 40 pounds, 30 of which are high explosive and contains a welded steel cone that penetrates 60 inches of concrete. The M3 charge is 12.5 inches high and 9 inches in diameter. The M2A3 contains a glass, conical-shaped charge liner, it weighs 15 pounds with 11.5 pounds of explosive and can penetrate 30 inches of concrete. The M2A3 has approximately the same penetrating power as the M1, and further details are given in Part 3 where demolition charges are discussed.

In addition to the fundamental studies performed in 1941 at the Eastern Laboratory, E. I. Du Pont de Nemours and Company (Du Pont), parallel studies were undertaken by the Eastern Laboratory and Division 8, National Defense Research Committee, Bruceton, PA. The sponsor was the Office of Scientific Research and Development. The chief scientists at the National Defense Research Committee were G. B. Kistiakowsky, D. P. MacDougall, S. J. Jacobs, and G. H. Messerly (Cook 1958).

At the same time, E. M. Pugh organized a group at the Carnegie Institute of Technology. Following the war, the Carnegie Institute took over the National Defense Research Committee facilities at Bruceton.

The Carnegie Group (C.I.T.) employed some outstanding researchers which contributed much of the current shaped charge knowledge. The leaders at Carnegie were R.V. Heine-Geldern, N. Rostoker, Emerson Pugh, and his student, Robert Eichelberger (a former Director of BRL).

In addition to the work at C.I.T., important post-war contributions to shaped charge research were made by L. Zernow and associates at BRL. Other laboratories making important contributions during this time period were the Naval Ordnance Laboratory, Maryland (Solem and August), the Naval Ordnance Test Station, California (Throner, Weinland, Kennedy, Pearson, and Rinehart), Picatinny Arsenal, New Jersey (Dunkle), the Stanford Research Institute, California (Poulter), and others. Additional developments in shaped charge technology, especially on the West Coast, are presented in Kennedy (1983).

Excellent bibliographical and historical information is provided in Birkhoff (1947), Parker (1950), and NRDC (1945). Ayton et al. (1955) is somewhat more recent. This bibliography contains references, with informative abstracts, to all pertinent literature found in books, periodicals, and reports on the subject of shaped charges, particularly their military applications. The time frame covered is basically 1930 - 1954, although some earlier background material has been covered.

The shaped charge principle was clarified and understood as a result of the pioneering flash x-ray photographs taken in the U.S. by Seely and Clark (1943), Clark and Rodas (1945) and in the U.K. by Tuck (1943). Schumann and Schardin obtained similar flash radiographs in Germany in 1941 (Birkhoff 1947; Schumann 1945; Schardin and Thomer 1941). Birkhoff (1947) and Schumann (1945) discuss the "angry priority controversy" over the first flash radiograph. X-ray photographs (or flash radiographs) are necessary since ordinary photographs are uninformative due to the smoke and flame associated with the detonation. See also Clark (1949).

Schardin and Thomer (1941) published excellent flash radiographs of collapsing shaped charges with hemispherical liners. These x-ray photographs clearly depict the collapse of the hemispherical liner (as it "turns inside out from the pole") and illustrates the "pinch-off effect" as the equatorial region of the liner collapses on the jet. The liner was truncated from the equator to remove this "pinch-off." These phenomenon were rediscovered some 30 years later.

The Roentgenblitz or flash x-ray is made possible by the very brief discharge of a high voltage x-ray tube. The basic apparatus was developed by Dr. Slack of Westinghouse Electric Company (Simon 1947).

Also, Linschitz and Paul (1943) experimentally studied conical lined shaped charges in different stages of collapse. Hand tamped nitroguanidine of various densities was used as the explosive fill to achieve a

partial collapse of the liner. The conical liner was recovered in water after a partial deformation, the degree of liner deformation (or collapse) corresponding to the density of the explosive fill. The results showed excellent agreement with the flash x-ray photographs.

Based on the analysis of the flash x-ray data and the partial collapse studies (Linschitz and Paul 1943), analytical models of the collapse of a lined conical shaped charge were developed and verified by Birkhoff (1947, 1943), Birkhoff et al. (1948), Evans (1950), Tuck (1943) and Pugh et al. (1952).

A bibliography and account of the weaponization of the shaped charge and similar principles are given in Backofen (1980a, 1980b, 1980c) and Backofen and Williams (1981a, 1981b, 1981c). Backofen's bibliography is extensive, especially regarding foreign sources. Earlier, World War II time frame results and bibliographical information are given in DM-1 (1947), Parker (1950), NRDC (1945), Ayton et al. (1955), Hill et al. (1944), and NDRC (1946). The time line charts given in Walters and Zukas (1989) highlight the major events in shaped charge advancement.

Shaped charge theory continued to develop during the 1950s, boosted by the Korean War (Cook 1958; Kennedy 1983; Berkholz 1988; Walters 1986; Walters and Zukas 1989; Thomanek 1959, 1960; Kolsky et al. 1949; Kolsky 1949; Evans and Ubbelohde 1950a, 1950b; Pugh et al. 1951; and Koski et al. 1952). During this time period, tremendous progress was made toward the understanding of the phenomena associated with shaped charge jets. Improved flash x-ray techniques were employed to observe the jet process and analytical models were improved. Efforts were made to improve existing shaped charge liners; to use detonation wave shapers; to provide spin compensation via fluted liners; to provide shaped charge follow-through mechanisms; and to enhance the overall system performance. Moses (1957) filed a U.S. patent on wave shaping and follow-through concepts for a shaped charge munition. Also, slugs from shaped charge firings were recovered and metallographic analyses were performed by Desphande and Singh (1959) and Singh et al. (1959). Jet temperature effects were examined by Robinson (1957) and the effect of environmental pressure and temperature on shaped charge jet formation and performance was studied by Reed and Carr (1950). Birkhoff (1947) discussed many of the problems still being studied today and additional information is given in Walters and Zukas (1989).

Starting in the 1950s and 1960s, significant shaped charge developments were made possible by the perfecting of experimental techniques such as high speed photography and flash radiography. Other improvements resulted from the transition from TNT to more energetic explosives, i.e., from TNT to Comp B to Octol and then to pressed explosives, notably LX-14. Also, alternate modes of initiation (other than point-initiation) and wave-shaping techniques have provided warhead design improvements. Other advances stemmed from the development of large computer codes to simulate the collapse, formation, and

growth of the jet from a shaped charge liner. Numerical techniques and the advantages and limitations of various computer codes for wave propagation and penetration studies are discussed in detail in Walters and Zukas (1989). These codes provide, for the most part, excellent descriptions of the formation of the jet.

Currently, shaped charge research continues in order to devise a successful countermeasure to the advanced armors currently fielded and/or contemplated, see e.g., Kennedy (1985). Studies which originated in the 1950s still continue; notably, torpedo applications of shaped charge rounds, anti-aircraft rounds, fragmentation rounds, multi-staged or tandem warheads, long standoff rounds, non-conical liners, and non-copper liners. Also, metallurgical and chemical aspects of the liner material as well as methods of liner fabrication remain important.

3. REFERENCES

- Ayton, M. W., J. R. Gibson, C. G. Gurtowski, and B. Bledisoe. "Shaped Charges, An Annotated Bibliography." The Library of Congress, Technical Information Division, Washington D.C., May 1955.
- Backofen, J. E. "Shaped Charges Versus Armor." Armor, July-August 1980a.
- Backofen, J. E. "Shaped Charges Versus Armor, Part II." Armor, September-October 1980b.
- Backofen, J. E. "Shaped Charges Versus Armor, Part III." Armor, November-December 1980c.
- Backofen, J. E., and L. W. Williams. "Antitank Mines." Armor, July-August 1981a.
- Backofen, J. E., and L. W. Williams. "Antitank Mines - Part II." Armor, September-October 1981b.
- Backofen, J. E., and L. W. Williams. "Antitank Mines - Part III." Armor, November-December 1981c.
- Baum, F. A., R. P. Stanykovich, and B. I. Skekter. Physics of an Explosion. AD 400151, Research Information Service, New York, p. 546, 1949.
- Berkholtz, N. E. "Evolution of the Shaped Charge." Unpublished paper presented at the 38th Annual Bomb and Warhead Technical Meeting, Albuquerque, New Mexico, 18-19 March 1988.
- Birkhoff, G., "Mathematical Jet Theory of Lined Hollow Charges." BRL Report No. 370, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 18 June 1943.
- Birkhoff, G. "Hollow Charge Anti-Tank (HEAT) Projectiles." BRL Report No. 623, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, 10 February 1947.
- Birkhoff, G., D. MacDougall, E. Pugh, and G. Taylor. "Explosive with Lined Cavities." J. Appl. Phys., Vol. 19, No. 6, June 1948.
- Bloem, G. "Shell for Detonating Caps." U.S. Patent 342,423, Dusseldorf, Prussia, Germany, 25 May 1886.
- Brandmayer, C., and F. R. Thomanek. "High Explosive Charge." Hungarian Patent 134,378, Berlin, Germany, assigned 9 December 1943.
- Cave, J. W., J. L. Bergman, and A. Haley. "Report of Investigation of the Proving Ground at Hillersleben, Germany." APG Misc. Report No. 063, Aberdeen Proving Ground, Maryland, 6 June 1945.
- Clark, G. B. "Secrets of the Shaped Charge." Ordinance, Vol. XXXIII, No. 169, pp. 49-51, July-August 1948.
- Clark, J. C. "Flash Radiography Applied to Ordnance Problems." J. Appl. Phys., Vol. 20, pp. 363-370, April 1949.
- Clark, J. C., and W. M. Rodas. "High Speed Radiographic Studies of Controlled Fragmentation." BRL Report No. 585, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, 16 June 1945.
- Cook, M. A. The Science Of High Explosives. American Chemical Society Monograph Series, New York: Reinhold Publishing Corporation, 1958.

- Deshpande, R. C., and S. Singh. "Studies of Slugs from Explosives with Lined Cavities: 11." Transactions of the Metallurgical Society of AIME. Vol. 215, p. 497, June 1959.
- DM-1. "History of the Development of Demolitions and Obstacles, I. Demolition Explosives and Equipment." War Department Corps of Engineers, AD-B959585, 9 September 1947.
- du Pont, E. I., de Nemours and Co. The Blaster's Handbook. 16th Edition, Wilmington, Delaware, 1980.
- Eather, R., and N. Griffiths. "A U.K. Note on the History of Shaped Charges." Royal Armament Research and Development Establishment Report, August 1983. Presented at MBB Schrobenhausen, West Germany, September 1983.
- Eichelberger, R. J. "Re-Examination of the Theories of Jet Formation and Target Penetration by Lined Cavity Charges." Doctoral Dissertation, Carnegie Institute of Technology, Pittsburgh, Pennsylvania, 1954.
- Evans, W. M. "The Hollow Charge Effect." Bulletin of the Institution of Mining and Metallurgy, No. 520, March 1950.
- Evans, W. M., and A. R. Ubbelohde. "Formation of Munroe Jets and Their Action on Massive Targets." Research Supplement, Vol. 3-7, London, 1950a.
- Evans, W. M., and A. R. Ubbelohde. "Some Kinematic Properties of Munroe Jets." Research Supplement, Vol. 3-8, London, 1950b.
- Freiwald, H. "The History of Hollow Charge Effect of High Explosive Charges." With forward by Hubert Schardin, for German Academy of Aviation Research, Berlin, Germany, 15 September 1941.
- Gray, J. C., W. E. Thibodeau, J. H. Church, and G. J. Kessenich. "Projectile." U. S. Patent No. 2,426,997, 9 September, Application 10 March 1941, (1947).
- Green, C. M., H. C. Thomson, and P. C. Roots. United States Army in World War II. The Technical Services. The Ordnance Department: Planning Munitions for War. Office of the Chief of Military History, Department of the Army, Washington, D.C., 1955.
- Hill, R., N. Mou, and D. Pack. A.R.D. Theoretical Research Report No. 2/44, January 1944, and 13/44, March 1944.
- Kennedy, D. R. "The History of the Shaped Charge Effect, The First 100 Years." A paper presented at MBB Schrobenhausen, West Germany, September 1983.
- Kennedy, D. R. "The Infantryman VS. the MBT." National Defense, ADPA, pp. 27-34, March 1985.
- Kline, H. W. "The Cavity Charge, Its Theory and Applications to the Opening of Explosive Filled Ordnance, Etc." U.S.N.R. Ordnance Investigation Laboratory, Naval Powder Factory, Indian Head, Maryland, 15 August 1945.
- Kolsky, H. "A Study of the Mechanisms of Munroe Charges, Part II - Charges with Hemispherical Liners." Research Supplement, Vol. 2-2, pp. 96-98, London, 1949.
- Kolsky, H., C. I. Snow, and A. C. Shearman. "A Study of the Mechanisms of Monroe Charges, Part I - Charges with Conical Liners." Research Supplement, Vol 2-2, pp. 89-95, London, 1949.
- Koski, W. S., F. A. Lucy, R. G. Shreffler, and F. J. Willig. "Fast Jets From Collapsing Cylinders." J. Appl. Phys. Vol. 23, No. 12, pp. 1300-1305, December 1952.
- Lenz, R. R. Explosives and Bomb Disposal Guide. Springfield: Charles C. Thomas, 1965.

- Linschitz, H., and M. A. Paul. "Experimental Studies of Cone Collapse and Jet Formation. Part I: Recovery of Cones From Low-Powered Charges." Division 8, National Defense Research Committee of the Office of Scientific Research And Development, OSRD Report No. 2070, 29 November 1943.
- Lodati, C. "An Explanation of the Explosive Behavior of Hollow Blocks of Compressed TNT." Giornale di Chim. ind. ed. appl., Vol. 14, pp. 130, 1932.
- Marshall, A. "The Detonation of Hollow Charges." J. of the Society of the Chemical Industry, Vol. 39, No. 3, p. 35T, 16 February 1920.
- Mohaupt, B., H. Mohaupt, and E. Kauders. "An Improved Explosive Projectile." Patent, Commonwealth of Australia, assigned to Berthold Mohaupt, Henry Mohaupt, and Erick Kauders of France, (date claimed for patent 9 November 1939), August 1941a.
- Mohaupt, H. H. "Projectile." U.S. Patent No. 2,419,414, assigned April 22, 1947. Originally filed 3 October 1941b.
- Mohaupt, H. H. "Projectile." U.S. Patent No. 2,974,595, assigned 1961. Originally filed 11 September 1947.
- Mohaupt, H. "Shaped Charges and Warheads." Aerospace Ordnance Handbook, edited by F. Pollard and J. Arnold, Chapter 11, New Jersey: Prentice-Hall, Inc., 1966.
- Monro, E. A. "Shaped Charges: A Review Covering the Period 26 August 1942 to 28 February 1943." Advisory Council on Scientific Research and Technical Development, Shaped Charges Sub-Committee, A. C. 3827, SC 19, 14 April 1943.
- Moses, S. A. "Projectile for Shaped Charges." U.S. Patent 2,809,585, application 16 November 1949, patented 15 October 1957.
- Mrazek, J. E. The Fall of Eben Emael Prelude to Dunkerque. Published by author, 1970.
- Munroe, C. E. "On Certain Phenomena Produced by the Detonation of Gun Cotton." Newport Natural History Society, Proceedings 1883-1888, Report No. 6, 1888a.
- Munroe, C. E. "Wave-Like Effects Produced by the Detonation of Gun Cotton." American Journal of Science, Vol. 36, pp. 48-50, 1888b.
- Munroe, C. E. "Modern Explosives." Scribner's Magazine, Vol. 111, New York, pp. 563-576, January-June 1888c.
- Munroe, C. E. Executive Document No. 20, 53rd Congress, 1st Session, Washington, D.C., 1894.
- Munroe, C. E. "The Applications of Explosives." Popular Science Monthly, Vol. 56, in 2 parts, pp. 300-455, 1900.
- Murphy, M. J. "Shaped Charge Penetration in Concrete: A Unified Approach." Doctor of Engineering Dissertation, University of California-Davis. Also Lawrence Livermore National Laboratory Report, UCRL-53393, January 1983.
- National Defense Research Council. "Protection Against Shaped Charges." Carnegie Institute of Technology, NDRC Report No. A-384 and OSRD Report No. 6384, February 1946.

- National Defense Research Council. "Annotated Bibliography of NDRC Technical Reports and Memorandums of Division 2, Including Pertinent Division 8 Reports." NDRC Memorandum No. A-106M, OSRD Report No. 4830B, 1 May 1945.
- Neumann, E. "New Hollow Bodies of High Explosive Substances." Zeitschrift für das Gesamte Schiess- und Sprengstoffwesen, Darmstadt, Germany, pp. 183-187, 15 May 1914.
- Neumann, M. "Einiges über brisante Sprengstoffe." Zeitschrift für Angewandte Chemie, Wittenburg, Germany, pp. 2233-2240, 24 November 1911.
- OTIB, "Results of Blasting Tests for Hollow Charges With and Without Liners." Performed in the Ballistic Institute of the Academy for Aerial Warfare, Germany, Ordnance Technical Intelligence Bulletin No. 1476, 1941.
- OTIR, "Ordnance Technical Intelligence Report Number 11." Office of the Chief Ordnance Officer GHQ, AFPAC, Tokyo, Japan, AD 94384, approximately 1946.
- Parker, D. K. "Hollow Charges: A Bibliography." Technical Information Section, Development and Proof Services, APG Misc. Report No. 120, Aberdeen Proving Ground, Maryland, June 1950.
- Payman, W., and D. W. Woodhead. "Explosion Waves and Shock Waves, V. - The Shock Wave and Explosion Products from Detonating High Explosives." Proceedings of the Royal Society, A, Vol. 163, 1937.
- Pugh, E. M., R. Eichelberger, and N. Rostoker. "Theory of Jet Formation by Charges with Lined Conical Cavities." J. Appl. Phys., Vol. 23, No. 5, May 1952.
- Pugh, E. M., R. V. Heine-Geldern, S. Foner, and E. C. Mutschler. "Kerr Cell Photography of High Speed Phenomena." J. Appl. Phys., Vol. 22, No. 4, pp. 487-493, April 1951.
- Reed, J. E., and F. F. Carr. "Effect of Temperature, Pressure, Standoff Upon Perfo-Jet Penetration." Oil and Gas Journal, Vol. 49, p. 69, 3 August 1950.
- Robinson, R. L. "Temperature Effect on Formations During Jet Perforating." J. of Petroleum Technology, Vol. 9, pp. 12-14, May 1957.
- Rollings, R. R., G. B. Clark, and H. N. Kalia. "Penetration in Granite by Shaped Charge Liners of Various Metals." Report No. RMERC-TR-70-13, University of Missouri, Rolla, April 1971.
- Schardin, H. "Development of the Shaped Charge." Wehrtechnische Hefte, 51 (4), 1954.
- Schardin, H., and G. Thomer. "Untersuchung des Hohlkörperproblems mit Hilfe der Roentgenblitz-Methode (Investigation of the Hollow Charge Problems with Help of the Flash X-ray Method)." Ballistisches Institut der Luftkriegsakademie Gatow, Prof No. 9, OTIB 1628, 20 November 1941.
- Schumann, E. "The Scientific Basis of the Hollow Charge Effect." Publication BIOS/Gp. 2/HEC 5919, Halstead Exploiting Center, England, approximately 1945.
- Schumann, E. "Wirkungssteigerung Beim Hohlsprenkörper (Improvement of the Effect of Hollow Charges)." Ordnance Technical Intelligence Bulletin, OTIB 1249-17, 26 February 1941.
- Seely, L. B., and J. C. Clark. "High Speed Radiographic Studies of Controlled Fragmentation." BRL Report No. 368, U. S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, 16 June 1943.
- Simon, L. E., German Research in World War II. New York: John Wiley and Sons, 1947.

- Singh, S., A. Soundraraj, and R. C. Deshpande. "Studies of Slugs from Explosives with Lined Cavities: 1." Transactions of the Metallurgical Society of AIME, Vol. 215, p. 166, February 1959.
- Sukharevskii, M. Technica i Snabschenie Krasnoi Armii. No. 170, pp. 13-18, 1925. Also Woina i Technica. No. 253, pp. 18-24, 1926 (1925).
- Tuck, J. L. "Note on the Theory of the Munroe Effect." U.K. Report, A. C. 3596 (Phys. Ex. 393-WA-638-24, 27 February 1943).
- Thomanek, F. R. "Substantiating Material in Support of Evaluation of Compensation in Favor of Explosive-Experimental Company and Diploma - Engineer, F. R. Thomanek." OTIB 1468, Ordnance Technical Intelligence Bulletin No. 411, 1942.
- Thomanek, F. R. "Die Erste Hohlladungswaffe - The First Hollow Charge Weapon." Explosivstoffe, No. 1, pp. 9-11, 1959.
- Thomanek, F. R. "The Development of the Lined Hollow Charge." Feltman Research Laboratories, Picatinny Arsenal, Dover, New Jersey, Technical Notes No. FRL-TN-27, March 1961, a translation from Explosivstoffe. Vol. 8, No. 8, August 1960.
- Thomanek, F. R. "Meine Hohlladungs - Aktivitäten." For periods 1932-935, 1938-1945, 1957-1969 and from 1975 to date, 10 March 1978.
- Thomanek, F. R., and H. von Hutern. "Patent Applications by Franz Rudolf Thomanek and Hellmuth von Hutern." Ordnance Technical Intelligence Bulletin 1249-19, (not dated but contains statement "Partly before 1935?").
- von Baader, F. "Versuch einer Theorie der Sprengarbeit." Bergmannische Journal, von Kohler and Hoffman, March 1792.
- von Foerster, M. Versuche mit Komprimierter Schiessbaumwolle. Berlin: Miuller and Son, 1883.
- von Foerster, M. "Experiments with Compressed Gun Cotton." Van Nostrand's Engineering Magazine, Vol. 31, pp. 113-119, July - December 1884.
- Wagner, "Documents Connected with the Development of Hollow Charge Ammunition." Memorandum for H. D. L. Saur by Wagner and other papers, OTIB 1249, Misc-2, November 1944.
- Walters, W. P. "Explosive Loading of Metals and Related Topics." BRL-SP-56, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, May 1986.
- Walters, W. P., and J. A. Zukas. Fundamentals of Shaped Charges. New York: John Wiley and Sons, 1989.
- WASAG. "Verfahren zur Herstellung von Sprengkorpem." Westfälich - Anhaltische Sprengstoffe Actien Gesellschaft, German patent DRP - Anmeldung W 36269, 14 December 1910. In Zeitschrift für das Gesamte Schiess und Sprengstoffwesen, Vol. 6, p. 358, 1911.
- WASAG. "Improvement in Explosive Charges or Bodies." Patent No. 28,030 (U.K.) to Westfälich - Anhaltische Sprengstoffe Actien Gesellschaft, Berlin, 13 December 1911.
- Watson, C. P. "Percussion Fuzes." 1925 U. S. Patents 1,524,011 and 1,534,012 filed 22 September 1921, and 27 August 1923, both issued on 14 April 1925.
- Watson, M. S. U.S. Army in World War II. The War Department. Chief of Staff. Prewar Plans and Preparations. Historical Division, Department of the Army, Washington, D.C., 1950.

Weston, L. "APG's Contribution to World War II Was Highly Significant." APG News, p. 5B,
22 May 1985.

Wisser, J. P. Compressed Gun Cotton for Military Use. Translated from the German of Max von Foerster
with an introduction on Modern Gun Cotton, Its Manufacture, Properties, and Analysis. New York:
D. Van Nostrand, 1886.

Wood, R. W. "Optical and Physical Effects of High Explosives." Proceedings of the Royal Society,
London, Vol. 157A, pp. 249-261, 1936.

No of Copies	Organization
1	Office of the Secretary of Defense OUSD(A) Director, Live Fire Testing ATTN: James F. O'Bryon Washington, DC 20301-3110
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145
1	HQDA (SARD-TR) WASH DC 20310-0001
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001
1	Commander US Army Laboratory Command ATTN: AMSLC-DL Adelphi, MD 20783-1145
2	Commander US Army, ARDEC ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000
2	Commander US Army, ARDEC ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000
1	Director Benet Weapons Laboratory US Army, ARDEC ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-5000
1	Commander US Army Aviation Systems Command ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798

No of Copies	Organization
1	Director US Army Aviation Research and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center Moffett Field, CA 94035-1000
1	Commander US Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander US Army Tank-Automotive Command ATTN: AMSTA-TSL (Technical Library) Warren, MI 48397-5000
1	Director US Army TRADOC Analysis Command ATTN: ATAA-SL White Sands Missile Range, NM 88002-5502
(Class. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
(Unclass. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000 <u>Aberdeen Proving Ground</u>
2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	Cdr, USATECOM ATTN: AMSTE-TD
3	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI
1	Dir, VLAMO ATTN: AMSLC-VL-D

No. of
Copies Organization

- 1 Commander
MICOM Research, Development
and Engineering Center
ATTN: Library
Redstone Arsenal, AL 35898
- 1 Commander
US Army Research Office
P.O. Box 12211
Research Triangle Park, NC 27709-2211
- 1 Commander
US Army Foreign Science and
Technology Center
ATTN: AIAST-IS
220 Seventh Street, NE
Charlottesville, VA 22901-5396
- 1 Commander
Det S, USAOG
USAINSCOM
ATTN: IAGPC-S
Ft. Meade, MD 20755
- 9 Commander
Naval Surface Warfare Center
ATTN: Code DG-50
DX-21, Lib Br
T. Spivok
W. Reed, R10A
R. Phinney
C. Smith
E. Johnson
W. Bullock
C. Dickerson
White Oak, MD 20910
- 1 Commander
Naval Surface Warfare Center
ATTN: Code 730, Lib
Silver Springs, MD 20910
- 2 Commander
Naval Weapons Center
ATTN: Code 4057
Code 45, Tech Lib
China Lake, CA 93555
- 1 AFATL/DLJR (J. Foster)
Eglin AFB, FL 32542

No. of
Copies Organization

- 1 Commander
Air Force Wright Aeronautical Laboratory
A.F. Systems Command
ATTN: Dr. Lee Kennard, ASD/PMRRC
USAF Wright Patterson AFB, OH 45443
- 1 Director
US Army Missile & Space Intelligence
Center
ATTN: AIAMS-YDL
Redstone Arsenal, AL 35898-5000
- 1 Commander, USACECOM
R&D Technical Library
ATTN: ASQNC-ELC-I-T, Myer Center
Fort Monmouth, NJ 07703-5301
- 10 Central Intelligence Agency
Office of Central Reference
Dissemination Branch
Room GE-47 HQS
Washington, D.C. 20502
- 1 Commander
Naval EOD Technology Center
ATTN: C. Cherry
Code 6052A
Indian Head, MD 20640
- 1 Director
Lawrence Livermore Laboratory
ATTN: Technical Library
P.O. Box 808
Livermore, CA 94550
- 1 Battelle-Columbus Laboratories
ATTN: Technical Library
505 King Avenue
Columbus, OH 43201
- 6 Sandia Laboratories
ATTN: Dr. J. Asay
Dr. R. Longcope
Dr. R. Sandoval
Dr. M. Forrestal
Dr. M. Vigil
Dr. A. Robinson
P.O. Box 5800
Albuquerque, NM 87185

<u>No. of Copies</u>	<u>Organization</u>
4	University of California Los Alamos Scientific Lab ATTN: Dr. J. Walsh Dr. R. Karpp Dr. C. Mautz Technical Library P.O. Box 1663 Los Alamos, NM 87545
2	University of Illinois Dept of Aeronautical and Astronautical Engineering ATTN: Prof. A. R. Zak Prof S. M. Yen Campus Police Building 101 N. Mathews Urbana, IL 61801
1	University of Dayton Research Institute ATTN: Dr. S. J. Bless P.O. Box 283 Dayton, OH 45409
3	University of Delaware Department of Mechanical Engineering ATTN: Prof. J. Vinson Prof. D. Wilkins Prof. J. Gillespie Newark, DE 19716
1	Southwest Research Institute ATTN: A. Wenzel 6220 Culebra Road P.O. Drawer 28510 San Antonio, TX 78284
1	Battelle Edgewood Operations ATTN: R. Jameson 2113 Emmorton Park Road Suite 200 Edgewood, MD 21040
1	Defense Technology International, Inc. ATTN: D.E. Ayer The Stark House 22 Concord Street Nashua, NH 03060

<u>No. of Copies</u>	<u>Organization</u>
1	Sundstrand Advanced Technology Group ATTN: P.J. Murray 4747 Harrison Ave. P.O. Box 7002 Rockford, IL 61125-7002
2	E.I. DuPont De Nemours & Company ATTN: B. Scott L. Minor Chestnut Run - CR 702 Wilmington, DE 19898
1	Owens-Corning Fiberglas Corporation Technical Center ATTN: D.R. Hartman 2790 Columbus Road, Rt. 16 Granville, OH 43023-1200
1	Dyna East Corporation ATTN: P.C. Chou 3201 Arch Street Philadelphia, PA 19104-2588
1	Aerojet Electro Systems Company ATTN: Warhead Systems, Dr. J. Carleone 1100 W. Hollyvale St. P.O. Box 296 Azusa, CA 91702
1	Physics International Company Tactical Systems Group Eastern Division P.O. Box 1004 Wadsworth, OH 44281-0904
3	Honeywell, Inc. Government and Aeronautical Products Division ATTN: G. Johnson J. Houston N. Berkholz 600 Second Street, NE Hopkins, NM 55343
1	S-Cubed ATTN: Dr. R. Sedgwick P.O. Box 1620 La Jolla, CA 92038-1620

No. of
Copies Organization

- 1 General Dynamics
Pomona Division
ATTN: R. Strike, MZ4-40
P.O. Box 2507
Pomona, CA 91769
- 2 California Research and Technology
ATTN: Dr. Ronald E. Brown
Mr. Mark Majerus
11875 Dublin Blvd.
Suite B-130
Dublin, CA 94568
- 1 Nuclear Metals Inc.
ATTN: M. Walz
2229 Main Street
Concord, MA 01742
- 1 SRI International
ATTN: Dr. L. Seaman
333 Ravenswood Avenue
Menlo Park, CA 94025
- 1 Northrop Corporation
Electro-Mechanical Division
ATTN: Donald L. Hall
500 East Orangethorpe Avenue
Anaheim, CA 92801
- 2 Boeing Aerospace Co.
Shock Physics & Applied Math
Engineering Technology
ATTN: J. Shrader, R. Helzer
P.O. Box 3999
Seattle, WA 98124
- 1 McDonnell Douglas Astronautics Company
ATTN: Bruce L. Cooper
5301 Bolsa Avenue
Huntington Beach, CA 92647
- 1 D.R. Kennedy and Associates Inc.
ATTN: Donald Kennedy
P.O. Box 4003
Mountain View, CA 94040

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number BRL-TR-3158 Date of Report SEPTEMBER 1990
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS

Name

Organization

Address

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD ADDRESS

Name

Organization

Address

City, State, Zip Code

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

-----FOLD HERE-----

DEPARTMENT OF THE ARMY

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066
OFFICIAL BUSINESS



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT No 0001, APG, MD

POSTAGE WILL BE PAID BY ADDRESSEE

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-9989



-----FOLD HERE-----