

AD-A231 705

SECOND INTERNATIONAL WORKSHOP
ON POWER TRANSDUCERS FOR SONICS
AND ULTRASONICS.

DEUXIEMES JOURNEES D'ETUDES SUR
LES TRANSDUCTEURS SONORES ET
ULTRASONORES DE PUISSANCE.

June 12th & 13th 1990

12 et 13 Juin 1990

Toulon FRANCE

Organised by / Organisées par
Laboratoire d'Acoustique de l'Institut Supérieur
d'Electronique du Nord



Workshop sponsors / Partenaires des journées d'études

Direction des Recherches, Etudes et Techniques (DRET)

Thomson Sintra ASM

Schlumberger Etudes et Productions

CNRS

Toulon Var Technologies (TVT)

DTIC
S E E R G T
B D
1990



Best Available Copy

PROCEEDINGS
TEXTE DES CONFERENCES

Edited by / Edité par :
M. Daux, B. Hamonic, O.B. Wilson, J.N. Decarpligny.

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

91 2 04 93

Session 5

11h30 - 12h10

MAGNETO-HYDRODYNAMIC and THERMOACOUSTIC MECHANISMS FOR GENERATION OF SOUND IN SEAWATER

MECANISMES MAGNETO-HYDRODYNAMIQUES ET THERMOACOUSTIQUES POUR LA GENERATION DE SONS SOUS MARINS

Steve L. GARRETT, Naval Postgraduate School, Monterey, CA, USA
Tom GABRIELSON, Naval Air Development Center, Warminster, PA, USA

12h10 - 12h40

A LOW FREQUENCY TOW-POWERED SOUND SOURCE

UNE SOURCE BASSE FREQUENCE ACTIONNEE PAR REMORQUAGE

Joe BLUE, A.L. VAN BUREN, Naval Research Laboratory, USRD, Orlando, FL, USA
LT Paul A. SEMPER, Navy Nuclear Power School, Orlando, FL, USA

13h00 - 15h00

LUNCH

DEJEUNER

15h00 - 16h20

SESSION 6: *LOW FREQUENCY ELECTRONIC SYSTEMS*
LES DISPOSITIFS ELECTRONIQUES BASSE FREQUENCE

Chairman: Jean-Noël DECARPIGNY
ISEN-RECHERCHE, Lille, France

15h00 - 15h40

ELECTRONIC NEEDS FOR HIGH POWER TRANSDUCERS

LES BESOINS RELATIFS A L'ELECTRONIQUE POUR LES TRANSDUCTEUR DE FORTE PUISSANCE

George G. DIXON, Stephen R. LEYLAND,
Marconi Command and Control Systems, New Parks, Leicester, England

15h40 - 16h20

ELECTRONIC SYSTEMS MODELING

MODELISATION DES SYSTEMES ELECTRONIQUES

Jean-Marc CAPRON, ISEN-RECHERCHE, Lille, France
Serge FAURE, GERDSM, DCAN, Toulon, France

16h20 - 16h50

BREAK

PAUSE

16h50 - 17h30

SESSION 7

Chairman: Naval Research Laboratory

16h50 - 17h30

CALIBRATION

CALIBRATION

E. J. VAN BUREN, Naval Research Laboratory

17h30 - 18h10

MEASUREMENTS

METHODS OF TRANSDUCER

Christie GERDING

18h10 - 18h50

SESSION 8

Summary Thomsen

Résumé

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 1990	3. REPORT TYPE AND DATES COVERED Proceedings of Meeting		
4. TITLE AND SUBTITLE A low-frequency, tow-powered sound source		5. FUNDING NUMBERS Work Unit #59-0593-0-0 Assn #DN880-326		
6. AUTHOR(S) J. E. Blue and A. L. Van Buren				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Underwater Sound Reference Detachment Naval Research Laboratory P.O. Box 568337 Orlando, FL 32856-8337		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Technology 800 N. Quincy St. Arlington, VA 22217-5000		10. SPONSORING/MONITORING AGENCY REPORT NUMBER		
11. SUPPLEMENTARY NOTES This article appeared in the Proceedings of the Second International Workshop on Power Transducers for Sonics and Ultrasonics held 12-13 June 1990 in France				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) This paper discusses resonant cavities and their potential sound pressure output when they are modulated hydrodynamically. Rough calculations show that in the frequency range of 10 to 100 Hz source levels in excess of 200 dB re 1 micropascal should be achievable. Experimental data from three suboptimum devices showed source levels of 182 dB at 16.6 and 50 Hz and 168 dB at 34.5 Hz. It is expected that with appropriate designs one can achieve greater than 200 dB from 10 to 100 Hz with fairly small, lightweight devices. Further, with innovative designs one should be able to obtain frequency diversity and perhaps broad bandwidth with a single device.				
14. SUBJECT TERMS Sound Sources Transducers Projectors		Tow-Powered Low-Frequency Sources Sonar		15. NUMBER OF PAGES 22
				16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet *optical scanning requirements*.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

2

CONFIDENTIAL

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

A low-frequency, tow-powered sound source

J.E. Blue, A.L. Van Buren

Naval Research Laboratory, Underwater Sound Reference Detachment,

P. O. Box 568337, Orlando, Florida, USA 32856-8337

and LT Paul A. Semper

Navy Nuclear Power School, Orlando, Florida, USA

DTIC
ELECTE
FEB 07 1991
S B D

This paper discusses resonant cavities and their potential sound pressure output when they are modulated hydrodynamically. Rough calculations show that in the frequency range of 10 to 100 Hz source levels in excess of 200 dB re 1 μ Pa should be achievable. Experimental data from three suboptimum devices showed source levels of 182 dB at 16.6 and 50 Hz and 168 dB at 34.5 Hz. It is expected that with appropriate designs one can achieve greater than 200 dB from 10 to 100 Hz with fairly

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

small, lightweight devices. Further, with innovative designs one should be able to obtain frequency diversity and perhaps broad bandwidth with a single device.

I. INTRODUCTION

Sound generation is known to be inefficient when the radiating device is small compared to a wavelength of the frequency one wishes to generate. Production of high sound pressure levels at low frequency from devices small compared to a wavelength requires large amounts of acoustic power. For example, to produce 200 dB re 1 μ Pa at 10 Hz requires 1 kW of acoustic power and a volume displacement of 10^4 cm^3 . With efficiencies of the order of 1% for many low-frequency devices, the power amplifier requirement would be about 100 kW. If one could develop a suitable tow-powered source to derive power primarily from a ship's propulsion system, the power might be available without having to provide extra generating equipment on-board the vessel. A vessel such as the U.S. Naval Ship Stalwart (TAGOS-1) has a power plant that delivers 3,200 brake horsepower or about 2 MW of power. This vessel would be capable of towing such a device with about 5% of its power going to sound generation. A highly resonant device might do even better. Here we will consider resonant air cavity devices and give some results from theory and experiment.

II. SOME CONSIDERATIONS FOR PULSATING SPHERES AND RESONANT BUBBLES

From the previous paper in this meeting by Timme, Young, and Blue, let us examine Fig. 1. At 10 Hz a spherical source driven uniformly over its area would require 1 kW of acoustic power in the water to achieve a sound pressure level of 200 dB re 1 μ Pa. The question now is whether or not that source level

is a
modu
sourc
N
this

reson

reduc

are s

neces

shows

of th

A
bubbl

bubbl

rms ch

the re

Figs.

in Fig

pulsat

pressu

mainta

resona

0.088

III. S

We

Research

the res

sources

resonan

is achievable by causing the flow past a 10-Hz resonant bubble to sinusoidally modulate the pressure field in the fluid surrounding the bubble. A candidate source design that we examined previously¹ is shown schematically in Fig. 2. In this case we attached a rubber membrane to a rigid hemisphere to produce the resonant bubble or air cavity. The use of a rigid hemisphere was intended to reduce multi-pole excitation of the resonant cavity. Our objective and approach are shown in Fig. 3. Let us now examine the size and volume displacement necessary to produce a 200-dB source level from a resonant bubble. Figure 4 shows Minnaert's equation² for a resonant gas bubble in water. The relationship of the sound pressure produced in the water to the volume displacement of the bubble is given in Fig. 5 for the case of an omnidirectional source. Assume the bubble pulsates linearly with a change of $\pm 5\%$ in its resonant radius; i.e., the rms change in the resonant radius is 3.5%. From this assumption we calculate the rms volume displacement δV_0 as shown in Fig. 6. Combining equations in Figs. 4, 5, and 6 we obtain the acoustic pressure referenced to 1 meter as shown in Fig. 7. Here we see that a 10-Hz resonant bubble at a depth of 9.8 m pulsating at 3.5% rms of the resonant radius ($r_0 = 0.46$ m) will give a sound pressure level of 203 dB re $1 \mu\text{Pa}$ at 1 m. To obtain 200 dB at 100 Hz maintaining the 3.5% rms displacement criteria one would have to place the resonant bubble at a depth of 62.3 m. Its radius at that depth would be 0.088 m.

III. SOME RESULTS FROM SUB-OPTIMUM DEVICES

We have tested three different prototype tow-powered sources at the Naval Research Laboratory. None of the prototypes is close to being optimum, however, the results do show that producing fairly high sound pressure levels from such sources is not that difficult. Figure 8 shows the concept for a 16.6-Hz resonant source. The salient features here are the flow modulator, plastic

shroud, and rigid hemisphere. For this device and for a 50-Hz resonant device that we built, the stiffness and loss in the membrane as well as the design of the flow modulators were factors in making the device suboptimum. Figures 9 and 10 show results from these two devices. Source levels of ~ 182 dB were obtained at a tow speed of 1.85 km/hr (1 knot) for both of these devices. Lack of linearity with tow speed causes us some concern. Figure 11 shows the devices were omnidirectional. No measurements of harmonic distortion were made. Figure 12 shows another concept for a tow-powered source that was tested. This device was modeled by LT Semper for his Master's thesis³ in mechanical engineering at the University of Central Florida. This device corrects a deficiency of the first devices by providing a variable speed motor to control the modulation frequency instead of depending on tuning the flow modulator to rotate at the proper resonant rate. We will not go into detail about the modeling but it involves the elastic moduli of the elastomeric membrane, adds the radiation mass in an ad hoc manner, and calculates the peak modulation pressure as a function of tow speed. Figure 13 shows the calculated source levels as a function of the peak modulation pressure. Since the model used is a linear one, we expect the linear response shown here. For a peak modulation pressure of 0.1 psi theory predicts a sound pressure level of 168 dB at 34.5 Hz. Figure 14 shows the experimental results which agree well at resonance with the theory after selection of appropriate parameters to put into the theory.

IV. DISCUSSION

The results presented here were meant to stimulate thought on tow- or flow-powered devices. We have shown with very crude devices that source levels of 170 to 190 dB are easily obtainable. Our belief is that source levels greater

that
devi
freq

REFE

1. I

s

2. k

3. P

T

1


than 200 dB can be obtained from 10 to 100 Hz with rather small, lightweight devices and that with innovative design we can develop devices that have frequency diversity and maybe even fairly broad bandwidth.



REFERENCES

1. H.C. Schau, A.L. Van Buren, and F.J. Rodosta, "Low-frequency, tow-powered sound source," J. Acoust. Soc. Am. 74, 583(A) (1983).
2. M. Minnaert, Phil. Mag. n16 235 (1933).
3. Paul A. Semper, "Mathematical Modeling of a Low-Frequency Cylindrical Sound Transducer," Master's thesis, University of Central Florida, Orlando, FL, 1990.

FIGURE CAPTIONS

- Fig. 1 Source level and acoustic power radiated from a harmonically pulsating sphere with $ka \ll 1$.
- Fig. 2 Tow-powered, low-frequency sound source.
- Fig. 3 Objective and approach in creating a tow-powered, low-frequency sound source.
- Fig. 4 Minnaert's equation for a resonant bubble in water.
- Fig. 5 Sound pressure referenced back to 1 m from an omnidirectional source with volume displacement δV .
- Fig. 6 Volume displacement for a resonant bubble with 3.5% rms oscillation about r_0 .
- Fig. 7 Sound pressure level re $1\mu\text{Pa}$ for a 10-Hz resonant bubble at 9.8-m depth pulsating 3.5% r_0 rms ($r_0 = 0.46\text{m}$).
- Fig. 8 Flow modulator.
- Fig. 9 Sound pressure level vs tow speed.
- Fig. 10 Sound pressure level vs tow speed
- Fig. 11 Directivity of 16.6 and 50 Hz sources.
- Fig. 12 Tow-powered sound source.
- Fig. 13 Effects of the magnitude of forcing.
- Fig. 14 Sound pressure level vs frequency.





83

OBJECTIVE

Produce a robust, inexpensive sound source capable of high (>200 dB) sound pressure levels at low (<100 Hz) frequency and whose primary source of power is derived from being towed through the water.

APPROACH

Investigate theoretically and experimentally a new sound source concept involving a resonant air cavity excited by a modulated flow field.

$$f_o r_o = \sqrt{\frac{3\gamma P_h}{4\pi^2 \rho}}$$

f_o = resonant frequency

r_o = radius at resonance

γ = adiabatic constant

P_h = hydrostatic pressure

ρ = density

$$f_o r_o = 3.26 \sqrt{\frac{h + 9.8}{9.8}}$$

h = water depth in meters

r_o in meters

$$|p|_{1m} = \frac{\omega^2 \rho}{4\pi} \delta V$$

ω = angular frequency

ρ = density

δV = volume displacement

Volume of resonant bubble

$$V_o = \frac{4}{3} \pi r_o^3$$

$$(\delta V)_{3.5\%} = \frac{4}{3} \pi \left[(1.035)^3 - 1 \right] r_o^3$$

$$= 0.457 r_o^3$$

$$|p|_{1m} = \frac{4.95 \times 10^4}{f_o} \left(\frac{h + 9.8}{9.8} \right)^{3/2}$$



$$\text{SPL} = 213.9 - 20 \log f_o + 30 \log \left(\frac{h + 9.8}{9.8} \right) \text{ dB re } 1 \mu\text{Pa}$$


$$\text{For } f_o = 10 \text{ Hz and } h = 9.8 \text{ m}$$


$$\text{SPL} = 203 \text{ dB}$$


FLOW MODULATOR


1 RF S = 20 Hz
20 SLOTS;











200

