

AD-A239 927



25

TECHNION RESEARCH AND DEVELOPMENT FOUNDATION LTD.

APPLICATION OF MIXED STRATEGIES FOR  
IMPROVED MISSILE GUIDANCE

Grant No. AFOSR 89-0528

Interim Scientific Report

covering the period of

15.10.90 - 15.6.91


DTIC  
SELECTE  
AUG 27, 1991  
S B D

Principal Investigator:

Professor Josef Shinar  
Faculty of Aerospace Engineering  
Technion - Israel Institute of Technology  
Haifa 32000, Israel.

**DISTRIBUTION STATEMENT A**  
Approved for public release;  
Distribution Unlimited

91 8 26 043

91-08901  


# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> JUNE 1991	<b>3. REPORT TYPE AND DATES COVERED</b> INTERIM SCIENTIFIC, 15.10.90-15.6.91	
<b>4. TITLE AND SUBTITLE</b> APPLICATION OF MIXED STRATEGIES FOR IMPROVED MISSILE GUIDANCE			<b>5. FUNDING NUMBERS</b> G AFOSR-89-0528	
<b>6. AUTHOR(S)</b> DR JOSEPH SHINAR				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> TECHNION RESEARCH AND DEVELOPMENT FOUNDATION LTD. TECHNION CITY HAIFA 32000 ISRAEL			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> GUIDANCE AND CONTROL BRANCH ARMAMENT DIRECTORATE WL/MNAG, EGLIN AFB, FL 32542			<b>10. SPONSORING/MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b>				
<b>12a. DISTRIBUTION/AVAILABILITY STATEMENT</b> APPROVE FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> THE MAIN TASK IN THE REPORTED PERIOD HAS BEEN THE PREPARATION OF THE TOOLS FOR A NONDIMENSIONAL SENSITIVITY ANALYSIS. THIS SENSITIVITY ANALYSIS WILL ALLOW TO GENERALIZE THE RESULTS OBTAINED SO FAR IN PREVIOUS PHASES OF OUR RESEARCH AND TO PERFORM A PARAMETRIC INVESTIGATION.				
<b>14. SUBJECT TERMS</b> MISSILE GUIDANCE, MIXED STRATEGIES			<b>15. NUMBER OF PAGES</b> 7(+2)	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL	

## GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

**Block 1. Agency Use Only (Leave blank).**

**Block 2. Report Date.** Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

**Block 3. Type of Report and Dates Covered.** State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

**Block 4. Title and Subtitle.** A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

**Block 5. Funding Numbers.** To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

**Block 6. Author(s).** Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

**Block 7. Performing Organization Name(s) and Address(es).** Self-explanatory.

**Block 8. Performing Organization Report Number.** Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

**Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es).** Self-explanatory.

**Block 10. Sponsoring/Monitoring Agency Report Number.** (If known)

**Block 11. Supplementary Notes.** Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supercedes or supplements the older report.

**Block 12a. Distribution/Availability Statement.** Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

**Block 12b. Distribution Code.**

OOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

**Block 13. Abstract.** Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

**Block 14. Subject Terms.** Keywords or phrases identifying major subjects in the report.

**Block 15. Number of Pages.** Enter the total number of pages.


**Block 16. Price Code.** Enter appropriate price code (NTIS only).

**Blocks 17. - 19. Security Classifications.** Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

**Block 20. Limitation of Abstract.** This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

TABLE OF CONTENTS

SUMMARY	1
INTRODUCTION	2
NON-DIMENSIONAL ANALYSIS	2
IMPLEMENTATION ISSUES	6
CONCLUDING REMARKS	6
REFERENCES	7



<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/ _____	
<b>Availability Codes</b>	
Dist	Avail and/or Special
A-1	

APPLICATION OF MIXED STRATEGIES FOR  
IMPROVED MISSILE GUIDANCE

Grant No. AFOSR 89-0528

**SUMMARY**

The main task in the reported period has been the preparation of the tools for a non-dimensional sensitivity analysis. This sensitivity analysis will allow to generalize the results obtained so far in previous phases of our research and to perform a parametric investigation.

## INTRODUCTION

The work on the task of non-dimensional sensitivity analysis started in November 1990 in parallel with the preparation of the report on the last year's activities. The progress of the work has been slower than expected for two separate reasons: the need to introduce and train new research personnel and the perturbations caused by the Gulf War.

At present, we are in the last phases of preparing and validating the computational tools for the parametric investigation.

This Interim Report describes two topics:

- a. The principles of the planned non-dimensional sensitivity analysis.
- b. The practical steps taken in preparing and validating the computational tools for the practical investigation.

## NON-DIMENSIONAL ANALYSIS

In order to generalize the numerical results of any study, it is a common practice to express them in a proper non-dimensional form. In order to do so the following steps have to be taken: Scaling of **all** variables of the problem, based on a judicious selection of scaling parameters of some physical significance. Definition of the "similarity parameters" of the problem.

The present investigation effort has been guided by some well-known results of "linearized missile guidance" analysis and their extension as reported in Refs. 1 and 2.

Since the study involves point-mass models only the last two of the three basic dimensions (mass, distance and time) have to be scaled. In our dynamic model the missile is assumed to have a first-order transfer function with the time-constant  $\tau_p$ . The value of this time-constant is selected therefore as the unit of "normalized" time.

$$\bar{t} = t/(t)_{\text{ref}} \quad (1)$$

$$(t)_{\text{ref}} = \tau_p \quad (2)$$

The unit of "normalized" distance was selected, based on the fact that the study is concerned with maneuvering targets, as a product for maximum lateral acceleration of the evader  $(a_E)_{\text{max}}$  and  $\tau_p^2$ . (In the "classical" linear guidance analysis, miss distances due to target maneuver are proportional to this factor.)

$$\bar{x} = x/x_{(\text{ref})} \quad (3)$$

$$(x)_{\text{ref}} = \tau_p^2 (a_E)_{\text{max}} \quad (4)$$

Using the above defined scaling transformation keeps the following non-dimensional variables unchanged:

- a. The pursuer-evader speed ratio ( $\beta$ )

$$\beta \triangleq \frac{V_P}{V_E} = \frac{\bar{V}_P}{\bar{V}_E} \quad (5)$$

- b. The pursuer-evader maximum maneuver ratio ( $\mu$ )

$$\mu \triangleq \frac{(a_P)_{\text{max}}}{(a_E)_{\text{max}}} = \frac{(\bar{a}_P)_{\text{max}}}{(\bar{a}_E)_{\text{max}}} \quad (6)$$

- c. The normalized time of flight ( $\theta_f$ )

$$\theta_f \triangleq \frac{t_f}{(t)_{\text{ref}}} = \frac{R_o}{V_c} \frac{1}{\tau_p} = \frac{\bar{R}_o}{\bar{V}_c} \quad (7)$$

- d. The "dynamic similarity parameter" (Refs. 1,2) defined by

$$\gamma^* \triangleq \frac{(V_E)_{\text{max}}}{V_E} \tau_p = \frac{(\bar{a}_E)_{\text{max}}}{\bar{V}_E} \quad (8)$$

Using the time scale change given by (1) all frequencies are normalized

$$\bar{\omega} = \omega(t_{\text{ref}}) = \omega\tau_p \quad (9)$$

This scaling equally refers to the actually assumed periodical random phase maneuvers and electronic jinking as well as to the shaping filters modelling these stochastic processes. The spectral density of the white noise, used as the input of the shaping filter has to be also rescaled according to the units of the considered disturbance.

In our previous investigation three types of disturbances were considered:

1. The "glint" noise of the radar receiver, modelled as measurement noise.
2. The periodical random phase target maneuvers.
3. The "electronic jinking".

The last two were considered as "process noises". As a consequence, another important similarity parameter has to be identified: the ratio of the two process noises, (in other words the "normalized jinking" parameter)

$$(\bar{W})_{\text{max}} \triangleq (W)_{\text{max}} / \tau_p^2 (a_E)_{\text{max}} \quad (10)$$

Moreover, the "glint", which is proportional to the physical size of the target aircraft, must be scaled as all the other variables. Since the dimension of the glint spectral density  $\phi_{gl}$  is  $[m^2 \text{sec}]$ , the normalized spectral density should be

$$\bar{\phi}_{gl} = \phi_{gl} / \tau_p^2 (a_E)_{\text{max}} \quad (11)$$

Keeping all the above defined similarity parameters constant should lead, according to the theory, to the same normalized miss distance

$$\bar{M} \triangleq R(t_f) / \tau_p^2 (a_E)_{\text{max}} \quad (12)$$

against the same evader strategy.

In order to guarantee the same operational efficiency, i.e. the same single shot kill probability, the lethality range of the missile's warhead has to be kept proportional to the expected miss distance. This can be done if the non-

dimensional warhead lethality parameter, defined as

$$R_{\ell}^* \triangleq R_{\ell} / \tau_p^2 (a_E)_{\max} \quad (13)$$

is kept constant.

In summary, we have a set of seven non-dimensional similarity parameters  $\beta$ ,  $\mu$ ,  $\gamma^*$ ,  $\theta_f$ ,  $(\bar{W})_{\max}$ ,  $\bar{\phi}_{gl}$ ,  $R_{\ell}^*$ , as a basis of a parametric sensitivity analysis. In theory, for the same set of these parameters similar non-dimensional results, expressing a large family of dimensional results, are to be expected.

The number of parameters being quite large it seems to be useful to keep some of them constant and to carry out the parametric sensitivity analysis by varying only a few.

For the planned sensitivity analysis the following parameters are going to be kept constant:

$$\text{the speed ratio } \beta = V_p / V_e$$

$$\text{the dynamic similarity parameter } \gamma^* = \frac{\tau_p (a_E)_{\max}}{V_E}$$

$$\text{the normalized flight time } \theta_f = \frac{R_o}{V_c} \frac{1}{\tau_p}$$

The remaining parameters  $\mu$ ,  $(\bar{W})_{\max}$ ,  $\bar{\phi}_{gl}$ ,  $R_{\ell}^*$ , belong to two different groups. For a given scaling transformation, based on  $\tau_p$  and  $(a_E)_{\max}$ ,  $\mu$  and  $R_{\ell}^*$  can be considered as design parameters of the missile, while  $(\bar{W})_{\max}$  and  $\bar{\phi}_{gl}$  are related to the evading aircraft. The last two both depend on the physical dimension of the aircraft and have to be varied together accordingly. They signify the relationship between disturbance created by the evader's maneuverability and the disturbance due to ECM or glint respectively.

Another important distinction between the two pairs of these parameters is that the first two ( $\mu$  and  $R_{\ell}^*$ ) do not interact with the estimation process and therefore no change in the "optimal estimation" is expected with their variations. However, if the ratio of the different disturbances is changed it

most certainly will require a modification of the estimator.

In this way the sensitivity analysis will be separated in two parts:

- a. sensitivity of the guidance performance,
- b. sensitivity of the estimation quality.

This separation will also allow to obtain the correlation between the estimation error and the miss distance.

### IMPLEMENTATION ISSUES

There are two options to carry out the above outlined non-dimensional parametric investigation. The first one is to use the existing computer code which is written in dimensional form, by carefully adapting the input in a way that the required similarity is preserved. The second option is to rewrite the computer code in non-dimensional variables.

In both cases careful validation tests has to be carried out in order to gain confidence in the method of the analysis and the results. Validation for each case is via comparison to some existing dimensional data.

Presently we are engaged in work using the first option and have already discovered already several problems to be addressed. In parallel with the above effort a new non-dimensional computer code is being generated.

### CONCLUDING REMARKS

In this interim report the analytical basis of a non-dimensional parametric sensitivity analysis is outlined and the two options to carry out the task are indicated. Presently, work is being done parallel for both options.

## REFERENCES

1. Shinar, J. and Rotsztein, Y., "Non-Dimensional Similarity Parameters in Pursuit-Evasion Problems", TAE Report No. 336, April 1978.
2. Forte, I., Steinberg, A. and Shinar, J., "On the Effects of Nonlinear Kinematics in Optimal Evasion", Optimal Control Application and Methods, Vol. 4, No. 2, 1983, pp. 139-152.