



2

ing instructions regarding this data source
this burden estimate or in any other aspect of this
operation Operations and Reports, 1215 Jefferson
0704-0188, Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)

2.

08/06/91

POP Test (05/91)

DATES COVERED

4. TITLE AND SUBTITLE

Performance Oriented Packaging Testing of Mk 43 Mod 0
and Mk 43 Mod 1 Drums for Packing Group II Solid
Hazardous Materials

5. FUNDING NUMBERS

6. AUTHOR(S)

Dennis Kotun

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Weapons Station Earle
Test and Evaluation Division (Code 403)
Colts Neck, NJ 07722-5000

8. PERFORMING ORGANIZATION
REPORT NUMBER

DODPOPHM/USA/DODO/
NADTR91010

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Weapons Support Center
Crane, IN 47522-5000

10. SPONSORING / MONITORING
AGENCY REPORT NUMBER

Same as above

11. SUPPLEMENTARY NOTES

N/A

12a. DISTRIBUTION / AVAILABILITY STATEMENT

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

Qualification tests were performed to determine whether the in-service Mk 43 Mod 0 Drum could be utilized to contain properly dunnaged solid type hazardous materials weighing up to a gross weight of 167.8 kg (370 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the United Nations Recommendations on the Transportation of Dangerous Goods and the Department of Transportation's Title 49 CFR and the Final Rulings published in the Federal Register, Vol. 55 on 21 Dec 90. The drum has conformed to the POP performance requirements; i.e., the drum successfully retained its contents throughout the specified tests.

In addition, due to their similarities in size and weight, this test is considered representative of qualification testing for the Mk 43 Mod 1 Drum as per the variation in the Federal Register (21 Feb 91) and page 52724, para 178.601h of the Final Rulings specified in the Department of Transportation's Performance Oriented Packaging Standards in the Federal Register, Vol. 55.

14. SUBJECT TERMS

POP Test of Mk 43 Mod 0 and Mk 43 Mod 1 Drums

15. NUMBER OF PAGES

5

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION
OF THIS PAGE

UL

19. SECURITY CLASSIFICATION
OF ABSTRACT

UL

20. LIMITATION OF ABSTRACT

UL

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank)

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must be at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers, may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit
	Accession No

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If author or coauthor, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. If known.

Block 11. Supplemental Notes. Enter information not included elsewhere such as Prepared in cooperation with Trans of To be published. When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (NTIS only).

Blocks 17 - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

DODPOPHM/USA/DOD/NADTR91010

PERFORMANCE ORIENTED PACKAGING TESTING
OF
DRUMS, MK 43 MOD 0 AND MK 43 MOD 1,
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

Author:
Dennis M. Kotun
Mechanical Engineering Technician



Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

6 August 1991

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Weapons Support Center
Code PM-4
Crane, Indiana 47522-5000

Accession For	
DTIC GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or
A-1	Special

01 8 09 028

91-07435



INTRODUCTION

The Mk 43 Mod 0 Drum tested, contained a simulated load of 317 pounds of sand representing the worst case of loading. Overall weight of the drum was 370 pounds. This Performance Oriented Packaging (POP) test was performed to ascertain whether this standard container (Packing Group II) would meet the requirements as specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9. A base level vibration test was also conducted in accordance with the final rulings specified in the Department of Transportation's Performance Oriented Packaging Standards in the Federal Register Volume 55. This vibration test was previously conducted by WPNSTA Earle as documented in Test Report 40-013-90.

The objectives of these tests were to minimize the risk of personnel or environmental exposure to the hazards associated with the contents in the advent of a transportation or handling accident.

In addition, due to their similarities in size and weight, this test is considered representative of qualification testing for the Mk 43 Mod 1 Drum as per the variation in the Federal Register (21 February 1991) and page 52724, paragraph 178.601h of the Final Rulings specified in the Department of Transportation's Performance Oriented Packaging Standards in the Federal Register, Volume 55.

TESTS PERFORMED

1. Stacking Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.6. Three drums were used for this test. Each drum was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a height of 3 meters (including the test sample). A weight of 1,110 pounds was stacked on each sample drum. The test was performed for 24 hours. After the allowed time, the weight was removed and the drums examined.

2. Drop Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.3. Six drums were used as required. The drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drums for each orientation):

- a. Horizontally.
- b. Diagonally on the edge between the cover assembly and the top ring of the drum.

This test was performed at an ambient temperature of $+70 \pm 20$ °F.

PASS/FAIL (UN CRITERIA)

1. Stacking Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.6.3 of ST/SG/AC.10/1 and states the following: "... no test sample should leak. No test sample should show any deterioration which could adversely affect transport safety or any distortion liable to reduce its strength or cause instability in stacks of packages."

2. Drop Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.3.5 of ST/SG/AC.10/1 and states the following: "Where a packaging for solids undergoes a drop test and its upper face strikes the target, the test sample passes the test if the entire contents are retained by an inner packaging or inner receptacle; e.g., a plastic bag, even if the closure is no longer sift-proof. A slight discharge from the closure(s) upon impact should not be considered to be a failure of the packaging provided that no further leakage occurs."

TEST RESULTS

1. Stacking Test

Satisfactory.

2. Drop Test

Satisfactory.

DISCUSSION

1. Stacking Test

Each drum was visibly checked after the 24-hour period was over. There was no leakage, distortion, or deterioration to any of the drums as a result of this test.

2. Drop Test

After each drop, the containers were inspected for any damage which would be a cause for rejection. The inspection after the horizontal drops indicated there was a 6-inch flat indentation at the point of impact on both the top and bottom rims, but no leakage was found. No leakage was found after the diagonal drops, although two 1-inch raised bulges on the drum's lid were present, 8 inches bilaterally apart from the point of impact. The drums remained intact and functional upon completion of the tests.

REFERENCE MATERIAL

A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6

B. Title 49 CFR 107, et al., Performance Oriented Packaging Standard; Changes to Classification, Hazard Communication, Packaging and Handling Requirements Based on UN Standards and Agency Initiative; Final Rule, Federal Register, Vol. 55, No. 246 of December 21, 1990.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Headquarters, Military Traffic Management Command (2 copies)
ATTN: MT-SS, James Gibson
5611 Columbia Pike
Falls Church, VA 22041-5050

TEST DATA SHEET

DATA SHEET:	
Container: Mk 43 Mod 0 Drum	
Type: 1A2	Container P/N or NSN: NSN 1320-01-114-2028
Specification Number: ADL 5166058-A000	Material: Steel
Gross Weight: 167.8 kg (370 pounds)	Dimensions: 24" H x 24" dia
Closure (Method/Type): Removable Cover	Empty Weight: 24.3 kg (53.5 pounds)
Additional Description: Mod 1 Drawing 5166058	
PRODUCT: See table	
Name: See table	NSN(s): See table
United Nations Number: See table	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container: See table	Flash Point: N/A
Net Weight: See table	
TEST PRODUCT: Simulated Weights of Sand	
Name: Sand	Physical State: Solid
Consistency: N/A	
Density/Specific Gravity: N/A	
Test Pressure (Liquids Only): N/A	
Amount Per Container: N/A	Net Weight: 143.6 kg (317 pounds)

TABLE 1

Mk 43 Mods 0, 1 Drum

NALC	NSN	Type	Packing Drawing	UN Code	UN Number	#/ Cntr	Weight (lb)
N/A	1390-01-035-1842	Shipping Container	ADL- 5166058	1.2G	0314	1	203

**MK 43 MOD 0 AND MK 43 MOD 1
DRUMS
POP MARKING**

UN 1A2/Y168/S/*/USA/DOD/NAD**

**** YEAR LAST PACKED OR MANUFACTURED**