

AD-A240 857



2

TECHNICAL REPORT BRL-TR-3260

BRL

DTIC
S ELECTE
SEP 30 1991
D

APPLICATIONS OF FOURIER TRANSFORM
INFRARED PHOTOACOUSTIC SPECTROSCOPY
TO SOLID PROPELLANT CHARACTERIZATION

ROSE ANN PESCE-RODRIGUEZ
ROBERT A. FIFER

AUGUST 1991

91-11830



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

UNCLASSIFIED

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE August 1991	3. REPORT TYPE AND DATES COVERED Final, July 1988 - October 1990	
4. TITLE AND SUBTITLE Applications of Fourier Transform Infrared Photoacoustic Spectroscopy to Solid Propellant Characterization			5. FUNDING NUMBERS 1L161102AH43	
6. AUTHOR(S) Rose Ann Pesce-Rodriguez and Robert A. Fifer				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) US Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066			10. SPONSORING / MONITORING AGENCY REPORT NUMBER BRL-TR-3260	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Fourier transform infrared photoacoustic spectroscopy (FT-IR-PAS) has been used to examine surfaces of composite solid propellants. Depletion of crystalline energetic material from extruded surfaces and of plasticizer from aged surfaces has been documented. In addition, a method has been developed to determine the mass per unit area of graphite on coated propellant surfaces.				
14. SUBJECT TERMS fourier transform; infrared spectroscopy; solid propellants; plasticizer depletion; graphite analysis			15. NUMBER OF PAGES 20	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

UNCLASSIFIED

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	ACKNOWLEDGMENTS	v
1.	INTRODUCTION	1
2.	EXPERIMENTAL	2
3.	RESULTS AND DISCUSSION	2
3.1	Depletion of RDX at Extruded Surfaces	2
3.2	Plasticizer Loss From Aged Surfaces	4
3.3	Graphite Surface Coating Analysis	4
3.4	Additional Applications	9
4.	CONCLUSIONS	9
5.	REFERENCES	11
	DISTRIBUTION LIST	13

Accession For	
NTIS CRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Availability or Special
A-1	

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

We thank Mr. Steve Kessel and Dr. Bernie Strauss of the U.S. Army Armament Research, Development, and Engineering Center, Picatinny Arsenal, NJ, for providing the graphite-coated samples used in this investigation.

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

Observations by members of the propellant community have generated interest in the examination of solid propellant surface composition (Rocchio, private communication 1988). Such observations include occasional lot-to-lot differences in performance tests (e.g., flamespreading) for propellants with identical formulations or between aged and unaged propellant. Along with the interest in surface composition comes the need for experimental techniques capable of detecting surface variations resulting from such phenomena as extrusion "wiping" effects, plasticizer evaporation and diffusion, and nonhomogeneous application of the graphite commonly used to coat propellant grains. Although all of these phenomena are potentially important, none has yet been characterized or correlated with ballistic behavior, primarily because of the absence of suitable experimental surface characterization techniques. Conventional chemical analysis techniques require the accurate removal of micrometer-thick layers from the sample surfaces. Removal of such thin layers from the surface of brittle propellants is not readily accomplished without concomitant surface modification.

In this investigation, the above-mentioned phenomena were examined by Fourier transform infrared (FT-IR) photoacoustic spectroscopy (PAS), a nondestructive technique for near-surface analysis (McClelland 1983; Grahm, Grim, and Fateley 1985). There are two main advantages of FT-IR-PAS; first, depth profiling can be performed by obtaining spectra at varying interferometer mirror velocities; and second, sample preparation is usually not required (Michaelian 1989; Urban and Koenig 1986; Yang, Bresee, and Fateley 1987). The ability to analyze samples with virtually no preparation proved to be extremely useful for the analysis of these composite propellant samples. The only requirement for this study was that samples fit in the sample holder. Because our interest was the composition at extruded surfaces, it was important to perform the analysis with minimal sampling handling. With FT-IR-PAS, sample handling is minimized, and complications that are introduced by analysis with more traditional methods are avoided. Results demonstrating the applicability of FT-IR-PAS to characterization of solid propellants are described in this report.

2. EXPERIMENTAL


Spectra were obtained on a Mattson Polaris FT-IR spectrometer using software provided by the manufacturer. Detection of the photoacoustic signal was achieved with a helium-purged MTEC Model 100 photoacoustic cell. Each spectrum was the average of 32 scans with a resolution of 8 cm^{-1} . Spectra were obtained with a moving mirror velocity of 0.316 cm/s and were ratioed against a carbon black (Norit-A) background.

The composite propellant samples used in this investigation were cylindrical in shape with a length and diameter of 1.4 and 1.1 cm, respectively, and are commonly referred to as "grains." The formulation was composed of crystalline energetic material (cyclo-1,3,5-trimethylene-2,4,6-trinitramine, RDX), non-energetic binder (cellulose acetate butyrate [CAB]), energetic binder (nitrocellulose [NC]), antioxidant (ethyl centralite [EC]), and either of two plasticizers. One is an azide plasticizer, hereafter referred to as "P," whose complete structure is proprietary information. The other is a mixture of two dinitro plasticizers, hereafter referred to as "A/B," whose structures are also proprietary information. Grain exteriors commonly have a thin graphite coating which provides lubrication when packing into artillery shells and protects against static electrical charges that might otherwise result in unintentional ignition.


3. RESULTS AND DISCUSSION

3.1 Depletion of RDX at Extruded Surfaces. Photoacoustic spectra of a typical sample are given in Figure 1. Bands assigned to RDX (R), cellulose acetate butyrate (C), nitrocellulose (N), and plasticizer (P) are appropriately labeled in spectrum A. Spectra B, C, and D are labeled to draw attention to specific bands.


Comparison of spectra A and B indicates a reduced level of RDX at the extruded surface, as evidenced by the decreased relative intensity of RDX bands. This reduction is attributed to the wiping action of the extrusion process which covers RDX particles with polymeric binder at the propellant surface. This finding supports conclusions based on scanning electron microscopy of extruded propellant surfaces (Lieb, private communication).




(A) Bulk Surface (cleaved)



(B) Side Surface Without Graphite Coating



(C) Side Surface With Graphite Coating



(D) Uncoated Side Surface After Accelerated Aging

LEGEND: R = RDX, C = Cellulose Acetate Butyrate, N = Nitrocellulose, P = Plasticizer


Figure 1. FT-IR-PA Spectra of Propellant Grains.

3.2 Plasticizer Loss From Aged Surfaces. Spectrum 1D illustrates the applicability of FT-IR-PAS to the examination of propellant aging. This spectrum was obtained from the extruded surface of a propellant grain that had been heated at 80° C for 26 hours. Loss of plasticizer "P" is demonstrated by the large decrease in absorbance of the plasticizer's azide band at 1,900 cm^{-1} . The same phenomenon has been observed for composite propellants formulated with several other plasticizers. Depletion of plasticizer has been observed at room temperature as well as at elevated temperatures. Spectral conditions are reproducible over long time periods, making both long term ambient and short term accelerated aging studies possible.


An example of depletion of "A/B" plasticizer is given in Figure 2. Although the infrared spectra of the two dinitro plasticizers are very similar they can be distinguished by bands appearing between 1,200 and 1,100 cm^{-1} . In propellant spectra, these bands are obscured by CAB bands but can be observed by performing digital subtraction (i.e., propellant spectrum minus CAB spectrum). The spectra in Figure 2 illustrate the loss of "A/B" plasticizer on heating.

3.3 Graphite Surface Coating Analysis. An interesting application of FT-IR-PA spectroscopy to the characterization of solid propellants is the analysis of their graphite coating. A method has been developed to determine the mass of graphite on a given surface area. Such information is useful in understanding lot-to-lot variations in propellant ignition and flamespreading. For cases where quantitative measurements are not necessary, relative graphite "thicknesses" can be readily obtained by simply comparing the baseline absorbance of FT-IR-PA. As illustrated in Figure 1C, the spectral baseline of coated propellant surfaces occurs at a higher photoacoustic absorbance value than that of uncoated surfaces (see Figure 1A).


This observation is explained by considering that graphite, a black body absorber, gives a relatively flat spectrum when its single-beam spectrum is ratioed against the carbon black background spectrum. For coated grains, the FT-IR-PA spectrum includes both the flat graphite spectrum and the spectrum of the propellant layer below the graphite. It was found that the baseline "absorbance" value was proportional to the mass of graphite on the propellant surface. With this information, a method was developed to determine the graphite mass per unit area.



(A) Untreated Propellant Spectrum



(B) Untreated Propellant Spectrum Minus CAB Spectrum



(C) Heat-Treated Propellant Spectrum Minus CAB Spectrum


LEGEND: C = Cellulose Acetate Butyrate; A and B Are the Two Dinitro Plasticizers.

Figure 2. FT-IR-PA Spectra of Propellant Grains Plasticized With "A/B" Plasticizer.


The method requires the construction of a calibration curve whose slope is the ratio of photoacoustic baseline "absorbance" to graphite mass and whose intercept is the baseline "absorbance" for an uncoated sample. Determination of the calibration curve slope is not straightforward, as standards for such a determination are not available. For this reason, the slope was determined indirectly by following the decrease in baseline "absorbance" as graphite was removed from a coated propellant surface. Graphite removal was achieved by gently wiping the coated surface against a piece of preweighed filter paper. Quantitation of transferred graphite was obtained from the difference in filter paper mass after transferral. Measurements were made to ± 0.001 mg with a Perkin Elmer AD2Z Autobalance. The graphite removal procedure was repeated no less than four times on the same coated slab and discontinued before the underlying layer of propellant was exposed. Confirmation that only graphite was removed from the slab was obtained by examination of the FT-IR-PA spectrum of the filter paper after transferral.

Figure 3A gives typical results of the above procedure, i.e., the relationship between photoacoustic absorbance and graphite mass removed from the propellant surface. Only a small fraction of the graphite was removed from the sample surface to generate the data in Figure 3A. Removal of additional graphite would risk concomitant removal of propellant in the layer below. The slope of the calibration curve is then calculated by multiplying the slope of the line in Figure 3A by -1, which then gives the relationship between photoacoustic absorbance and increasing mass of graphite on the propellant surface. For completion of the calibration curve, a baseline absorbance measurement for uncoated propellant is made and taken as the Y intercept. The resultant calibration curve is given in Figure 3B. With this calibration curve and samples with known surface area, routine analysis of coated grains may be performed. Values obtained from the analysis have units of mass of graphite per unit area.

Using this method, propellant grains coated with a set of ten graphite samples, varying in particle size and crystallinity, were analyzed. Exposure of reproducible surface areas was ensured by placing a circular brass mask over the propellant sample. The mask was contoured to the cylindrical shape of the grain to minimize the cell volume and prevent loss of the acoustic signal. Slopes of calibration curves were determined from at least three samples with each type of graphite. Measurements of mass of graphite on a given surface area were obtained from at least six samples with the same type of graphite. Results of the analysis are given in Table 1.



(A) PA Absorbance vs. Mass of Graphite Removed From Propellant Grain Surface



(B) PA Absorbance vs. Mass of Graphite Remaining on Propellant Grain Surface

Figure 3. Experimental Data and Calibration Curve for Graphite Coating Analysis.

Table 1. Summary of Graphite Glaze Analysis

Graphite Source and Number	Graphite Type (% ash)	Graphite Particle Size (μm)	PA Absorbance at $2,000\text{ cm}^{-1}$	Calibration Curve Slope	Graphite Mass per Unit Area (mg/cm^2)
Dixon 200-10	natural (2)	2.5	19.1	9.8	5.2
Dixon 200-39	synthetic (0.5)	2.5	18.3	14.7	3.3
Dixon 200-19	amorphous (19.4)	2.5	16.2	9.9	4.2
Dixon 400-10	natural flake (2.9)	2.5	17.5	11.9	3.9
Asbury Mills 041-C	natural (3.2)	4.0	18.0	11.9	3.9
Asbury Mills M150	amorphous (17.2)	4.3	19.8	9.3	5.5
Asbury Mills M450	synthetic (0.5)	4.3	18.5	12.8	3.9
Dixon 041-B	natural (?)	7.5	16.0	12.2	3.3
Dixon 041-A	natural (?)	18.0	16.3	8.8	4.7
Dixon 155	natural flake (4.3)	18.0	17.1	13.4	3.3

Calculated values for mass of graphite per unit area fall within a small range of values (i.e., 3.3 to 5.5 mg/cm^2). Values for calibration curve slopes can be divided into at least two groups, i.e., those with slopes 8.8 to 9.9 and those with slopes of 11.9 to 14.7. Although the relationship between the calibration curve slope and graphite type has not yet been determined, it does make sense that the former group includes two samples with high ash content (Dixon 200-19 and Asbury Mills M150 have 19.4 and 14.7% ash, respectively). Ash is typically composed of silica, alumina, iron oxide, calcium oxide, potassium oxide, sodium oxide, sulfur trioxide, and sulfuric anhydride, none of which absorb radiation at $2,000\text{ cm}^{-1}$. Removal of graphite with a high ash content will result in a smaller change in absorptivity than will the removal of graphite with little or no ash. The two other samples in the 8.8 to 9.9 slope group, Dixon 200-10 and Dixon 041-A, have less than 5% ash. It is not clear why their calibration curve slopes are lower than other samples with low ash content.

3.4 Additional Applications. As part of a study of condensed phase processes during solid propellant combustion (Schroeder 1990), we are using FT-IR-PAS to examine samples that have been ignited and subsequently extinguished. For example, for RDX/CAB propellants, we observe that the extinguished surface is essentially a foamy layer of binder (cellulose acetate butyrate). The foam is believed to have formed by the flow of gaseous RDX decomposition products through molten binder. Substantially reduced levels of RDX and plasticizer were observed for this layer. Material below the foamy layer was found to have a composition similar to that of unburned propellant.

In another study, FT-IR-PAS was used to analyze the bulk composition, rather than the surface composition, of two explosive samples composed of RDX, stearic acid, magnesium oxide, and graphite. Although the formulations were believed to be identical, ballistic properties of the two samples varied greatly. Photoacoustic spectra indicated not only differences in the stearic acid level but also the presence of residual cyclohexanone solvent in one of the samples. As is typical for most investigations of solid composite propellants by FT-IR-PAS, the analysis provided qualitative and semi-quantitative results relatively quickly and required no sample preparation.

4. CONCLUSIONS

The applications of FT-IR-PAS described above illustrate how well suited the technique is for characterization of composite propellant surfaces. The ability to detect variations in surface composition caused by plasticizer evaporation, extruder "wiping" effects, and nonhomogeneous application of graphite, provides a useful tool for understanding surface-related inconsistencies in ballistic behavior. Because so little sample preparation is required, FT-IR-PAS has the potential to be incorporated into both quality control/quality assurance monitoring and developmental studies of solid propellants.

INTENTIONALLY LEFT BLANK.

5. REFERENCES

- Fifer, R. A., R. A. Pesce-Rodriguez, C. J. Selawski, and C. S. Miser. "Infrared Techniques for the Determination of CAB and NC in Solid Propellants." 1990 JANNAF Propellant Development Characterization Subcommittee Meeting, CPIA Pub, in press.
- Grahm, J. A., W. M. Grim, and W. G. Fateley. "Fourier Transform Infrared Spectroscopy." Fourier Transform Infrared Spectroscopy, edited by J. R. Ferraro and L. J. Basile. New York: Academic Press, vol. 4, chap. 9, p. 345, 1985.
- Lieb, R. Private communication. U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, September 1989.
- McClelland, J. F. Analytical Chemistry. Vol. 55, 89A, 1983.
- Michaelian, K. H. Applied Spectroscopy. Vol. 43, p. 185, 1989.
- Rocchio, J. Private communication. U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1988.
- Schroeder, M. A., R. A. Fifer, M. S. Miller, and R. A. Pesce-Rodriguez. "Condensed-Phase Processes During Solid Propellant Combustion I. Preliminary Chemical and Microscope Examination of Extinguished Propellant Samples," BRL-MR-3845, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1990.
- Urban, M. W., and J. L. Koenig. Applied Spectroscopy. Vol. 40, p. 994, 1986.
- Yang, C. Q., R. R. Bresee, and W.G. Fateley. Applied Spectroscopy. Vol. 41, p. 889, 1987.

INTENTIONALLY LEFT BLANK.

No. of Copies	Organization	No. of Copies	Organization
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander U.S. Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander U.S. Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001	1	Commander U.S. Army Tank-Automotive Command ATTN: ASQNC-TAC-DIT (Technical Information Center) Warren, MI 48397-5000
1	Commander U.S. Army Laboratory Command ATTN: AMSLC-DL 2800 Powder Mill Road Adelphi, MD 20783-1145	1	Director U.S. Army TRADOC Analysis Command ATTN: ATRC-WSR White Sands Missile Range, NM 88002-5502
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000	1	Commandant U.S. Army Field Artillery School ATTN: ATSF-CSI Ft. Sill, OK 73503-5000
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	(Class. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
1	Director Benet Weapons Laboratory U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050	(Unclass. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
(Unclass. only) 1	Commander U.S. Army Armament, Munitions and Chemical Command ATTN: AMSMC-IMF-L Rock Island, IL 61299-5000	1	Air Force Armament Laboratory ATTN: WL/MNOI Eglin AFB, FL 32542-5000 <u>Aberdeen Proving Ground</u>
1	Director U.S. Army Aviation Research and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center Moffett Field, CA 94035-1000	2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
		1	Cdr, USATECOM ATTN: AMSTE-TC
		3	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI
		1	Dir, VLAMO ATTN: AMSLC-VL-D
		10	Dir, BRL ATTN: SLCBR-DD-T

<u>No. of Copies</u>	<u>Organization</u>
1	HQDA (SARD-TR, C.H. Church) WASH DC 20310-0103
4	Commander US Army Research Office ATTN: R. Ghirardelli D. Mann R. Singleton R. Shaw P.O. Box 12211 Research Triangle Park, NC 27709-2211
2	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-B, D.S. Downs SMCAR-AEE, J.A. Lannon Picatinny Arsenal, NJ 07806-5000
1	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-BR, L. Harris Picatinny Arsenal, NJ 07806-5000
2	Commander US Army Missile Command ATTN: AMSMI-RD-PR-E, A.R. Maykut AMSMI-RD-PR-P, R. Betts Redstone Arsenal, AL 35898-5249
1	Office of Naval Research Department of the Navy ATTN: R.S. Miller, Code 432 800 N. Quincy Street Arlington, VA 22217
1	Commander Naval Air Systems Command ATTN: J. Ramnarace, AIR-54111C Washington, DC 20360
1	Commander Naval Surface Warfare Center ATTN: J.L. East, Jr., G-23 Dahlgren, VA 22448-5000

<u>No. of Copies</u>	<u>Organization</u>
2	Commander Naval Surface Warfare Center ATTN: R. Bernecker, R-13 G.B. Wilmot, R-16 Silver Spring, MD 20903-5000
5	Commander Naval Research Laboratory ATTN: M.C. Lin J. McDonald E. Oran J. Shnur R.J. Doyle, Code 6110 Washington, DC 20375
1	Commanding Officer Naval Underwater Systems Center Weapons Dept. ATTN: R.S. Lazar/Code 36301 Newport, RI 02840
2	Commander Naval Weapons Center ATTN: T. Boggs, Code 388 T. Parr, Code 3895 China Lake, CA 93555-6001
1	Superintendent Naval Postgraduate School Dept. of Aeronautics ATTN: D.W. Netzer Monterey, CA 93940
3	AL/LSCF ATTN: R. Corley R. Geisler J. Levine Edwards AFB, CA 93523-5000
1	AL/MKPB ATTN: B. Goshgarian Edwards AFB, CA 93523-5000
1	AFOSR ATTN: J.M. Tishkoff Bolling Air Force Base Washington, DC 20332
1	OSD/SDIO/IST ATTN: L. Cavery Pentagon Washington, DC 20301-7100

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commandant USAFAS ATTN: ATSF-TSM-CN Fort Sill, OK 73503-5600	1	Atlantic Research Corp. ATTN: R.H.W. Waesche 7511 Wellington Road Gainesville, VA 22065
1	F.J. Seiler ATTN: S.A. Shackelford USAF Academy, CO 80840-6528	1	AVCO Everett Research Laboratory Division ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149
1	University of Dayton Research Institute ATTN: D. Campbell AL/PAP Edwards AFB, CA 93523	1	Battelle ATTN: TACTEC Library, J. Huggins 505 King Avenue Columbus, OH 43201-2693
1	NASA Langley Research Center Langley Station ATTN: G.B. Northam/MS 168 Hampton, VA 23365	1	Cohen Professional Services ATTN: N.S. Cohen 141 Channing Street Redlands, CA 92373
4	National Bureau of Standards ATTN: J. Hastie M. Jacox T. Kashiwagi H. Semerjian US Department of Commerce Washington, DC 20234	1	Exxon Research & Eng. Co. ATTN: A. Dean Route 22E Annandale, NJ 08801
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, GA 95813	1	Ford Aerospace and Communications Corp. DIVAD Division Div. Hq., Irvine ATTN: D. Williams Main Street & Ford Road Newport Beach, CA 92663
1	Applied Combustion Technology, Inc. ATTN: A.M. Varney P.O. Box 607885 Orlando, FL 32860	1	General Applied Science Laboratories, Inc. 77 Raynor Avenue Ronkonkama, NY 11779-6649
2	Applied Mechanics Reviews The American Society of Mechanical Engineers ATTN: R.E. White A.B. Wenzel 345 E. 47th Street New York, NY 10017	1	General Electric Ordnance Systems ATTN: J. Mandzy 100 Plastics Avenue Pittsfield, MA 01203
1	Atlantic Research Corp. ATTN: M.K. King 5390 Cherokee Avenue Alexandria, VA 22314	1	General Motors Rsch Labs Physical Chemistry Department ATTN: T. Sloane Warren, MI 48090-9055

<u>No. of Copies</u>	<u>Organization</u>
2	Hercules, Inc. Allegheny Ballistics Lab. ATTN: W.B. Walkup E.A. Yount P.O. Box 210 Rocket Center, WV 26726
1	Alliant Techsystems, Inc. Marine Systems Group ATTN: D.E. Broden/ MS MN50-2000 600 2nd Street NE Hopkins, MN 55343
1	Alliant Techsystems, Inc. ATTN: R.E. Tompkins MN38-3300 5700 Smetana Drive Minnetonka, MN 55343
1	IBM Corporation ATTN: A.C. Tam Research Division 5600 Cottle Road San Jose, CA 95193
1	IIT Research Institute ATTN: R.F. Remaly 10 West 35th Street Chicago, IL 60616
2	Director Lawrence Livermore National Laboratory ATTN: C. Westbrook M. Costantino P.O. Box 808 Livermore, CA 94550
1	Lockheed Missiles & Space Co. ATTN: George Lo 3251 Hanover Street Dept. 52-35/B204/2 Palo Alto, CA 94304
1	Director Los Alamos National Lab ATTN: B. Nichols, T7, MS-B284 P.O. Box 1663 Los Alamos, NM 87545

<u>No. of Copies</u>	<u>Organization</u>
1	National Science Foundation ATTN: A.B. Harvey Washington, DC 20550
1	Olin Ordnance ATTN: V. McDonald, Library P.O. Box 222 St. Marks, FL 32355-0222
1	Paul Gough Associates, Inc. ATTN: P.S. Gough 1048 South Street Portsmouth, NH 03801-5423
2	Princeton Combustion Research Laboratories, Inc. ATTN: M. Summerfield N.A. Messina 475 US Highway One Monmouth Junction, NJ 08852
1	Hughes Aircraft Company ATTN: T.E. Ward 8433 Fallbrook Avenue Canoga Park, CA 91303
1	Rockwell International Corp. Rocketdyne Division ATTN: J.E. Flanagan/HB02 6633 Canoga Avenue Canoga Park, CA 91304
4	Director Sandia National Laboratories Division 8354 ATTN: R. Cattolica S. Johnston P. Mattern D. Stephenson Livermore, CA 94550
1	Science Applications, Inc. ATTN: R.B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364
3	SRI International ATTN: G. Smith D. Crosley D. Golden 333 Ravenswood Avenue Menlo Park, CA 94025

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Stevens Institute of Tech. Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030	1	Brigham Young University Dept. of Chemical Engineering ATTN: M.W. Beckstead Provo, UT 84058
1	Sverdrup Technology, Inc. LERC Group ATTN: R.J. Locke, MS SVR-2 2001 Aerospace Parkway Brook Park, OH 44142	1	California Institute of Tech. Jet Propulsion Laboratory ATTN: L. Strand/MS 512/102 4800 Oak Grove Drive Pasadena, CA 91109
1	Sverdrup Technology, Inc. ATTN: J. Deur 2001 Aerospace Parkway Brook Park, OH 44142	1	California Institute of Technology ATTN: F.E.C. Culick/ MC 301-46 204 Karman Lab. Pasadena, CA 91125
1	Thiokol Corporation Elkton Division ATTN: S.F. Palopoli P.O. Box 241 Elkton, MD 21921	1	University of California Los Alamos Scientific Lab. P.O. Box 1663, Mail Stop B216 Los Alamos, NM 87545
3	Thiokol Corporation Wasatch Division ATTN: S.J. Bennett P.O. Box 524 Brigham City, UT 84302	1	University of California, Berkeley Chemistry Department ATTN: C. Bradley Moore 211 Lewis Hall Berkeley, CA 94720
1	United Technologies Research Center ATTN: A.C. Eckbreth East Hartford, CT 06108	1	University of California, San Diego ATTN: F.A. Williams AMES, B010 La Jolla, CA 92093
3	United Technologies Corp. Chemical Systems Division ATTN: R.S. Brown T.D. Myers (2 copies) P.O. Box 49028 San Jose, CA 95161-9028	2	University of California, Santa Barbara Quantum Institute ATTN: K. Schofield M. Steinberg Santa Barbara, CA 93106
1	Universal Propulsion Company ATTN: H.J. McSpadden Black Canyon Stage 1 Box 1140 Phoenix, AZ 85029	1	University of Colorado at Boulder Engineering Center ATTN: J. Daily Campus Box 427 Boulder, CO 80309-0427
1	Veritay Technology, Inc. ATTN: E.B. Fisher 4845 Millersport Highway P.O. Box 305 East Amherst, NY 14051-0305		

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	University of Southern California Dept. of Chemistry ATTN: S. Benson C. Wittig Los Angeles, CA 90007
1	Cornell University Department of Chemistry ATTN: T.A. Cool Baker Laboratory Ithaca, NY 14853
1	University of Delaware ATTN: T. Brill Chemistry Department Newark, DE 19711
1	University of Florida Dept. of Chemistry ATTN: J. Winefordner Gainesville, FL 32611
3	Georgia Institute of Technology School of Aerospace Engineering ATTN: E. Price W.C. Strahle B.T. Zinn Atlanta, GA 30332
1	University of Illinois Dept. of Mech. Eng. ATTN: H. Krier 144MEB, 1206 W. Green St. Urbana, IL 61801
1	Johns Hopkins University/APL Chemical Propulsion Information Agency ATTN: T.W. Christian Johns Hopkins Road Laurel, MD 20707
1	University of Michigan Gas Dynamics Lab Aerospace Engineering Bldg. ATTN: G.M. Faeth Ann Arbor, MI 48109-2140

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	University of Minnesota Dept. of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455
3	Pennsylvania State University Applied Research Laboratory ATTN: K.K. Kuo H. Palmer M. Micci University Park, PA 16802
1	Pennsylvania State University Dept. of Mechanical Engineering ATTN: V. Yang University Park, PA 16802
1	Polytechnic Institute of NY Graduate Center ATTN: S. Lederman Route 110 Farmingdale, NY 11735
2	Princeton University Forrestal Campus Library ATTN: K. Brezinsky I. Glassman P.O. Box 710 Princeton, NJ 08540
1	Purdue University School of Aeronautics and Astronautics ATTN: J.R. Osborn Grissom Hall West Lafayette, IN 47906
1	Purdue University Department of Chemistry ATTN: E. Grant West Lafayette, IN 47906
2	Purdue University School of Mechanical Engineering ATTN: N.M. Laurendeau S.N.B. Murthy TSPC Chaffee Hall West Lafayette, IN 47906

<u>No. of Copies</u>	<u>Organization</u>
1	Rensselaer Polytechnic Inst. Dept. of Chemical Engineering ATTN: A. Fortijn Troy, NY 12181
1	Stanford University Dept. of Mechanical Engineering ATTN: R. Hanson Stanford, CA 94305
1	University of Texas Dept. of Chemistry ATTN: W. Gardiner Austin, TX 78712
1	University of Utah Dept. of Chemical Engineering ATTN: G. Flandro Salt Lake City, UT 84112
1	Virginia Polytechnic Institute and State University ATTN: J.A. Schetz Blacksburg, VA 24061
1	Freedman Associates ATTN: E. Freedman 2411 Diana Road Baltimore, MD 21209-1525

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers below will aid us in our efforts.

1. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.)

2. How, specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.)

3. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate.

4. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.)

BRL Report Number BRL-TR-3260 Division Symbol

Check here if desire to be removed from distribution list.

Check here for address change.

Current address: Organization _____
Address _____

DEPARTMENT OF THE ARMY
Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

OFFICIAL BUSINESS



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT No 0001, APG, MD

Postage will be paid by addressee

Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

