

AD-A242 356



TR-0300


AD

Reports Control Symbol
OSD - 1366

ON THE INTERRELATION OF TEMPERATURE, PRESSURE,
AIR DENSITY, AND HUMIDITY

August 1991

Bruce T. Miers



Approved for public release; distribution
unlimited.

US ARMY
LABORATORY COMMAND

ATMOSPHERIC SCIENCES LABORATORY
White Sands Missile Range, NM 88002-5501

91-15542



91 1113 006

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Destruction Notice

When this document is no longer needed, destroy it by any method that will prevent disclosure of its contents or reconstruction of the document.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE August 1991	3. REPORT TYPE AND DATES COVERED Final		
4. TITLE AND SUBTITLE ON THE INTERRELATION OF TEMPERATURE, PRESSURE, AIR DENSITY, AND HUMIDITY		5. FUNDING NUMBERS AH71-A 612784. H71.11.11		
6. AUTHOR(S) Bruce T. Miers				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Atmospheric Sciences Laboratory White Sands Missile Range, NM 88002-5501		8. PERFORMING ORGANIZATION REPORT NUMBER ASL-TR-0300		
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Laboratory Command Adelphi, MD 20783-1145		10. SPONSORING / MONITORING AGENCY REPORT NUMBER		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) During military operations in Southwest Asia (SWA), Headquarters, U.S. Armament, Munitions and Chemical Command (AMCCOM), Picatinny Arsenal, New Jersey (AMSMC-QAN-P(D)), requested a usable compilation of meteorological equations on the interrelation of temperature, pressure, air density, and humidity. The Predictive Technology Branch of AMCCOM was appointed by the Director, Command Group, Mid-East Operations, as the coordinator for all activities involving the identification of weapon and ammunition limitations for AMCCOM materials deployed in SWA. These equations were to be used to help define the exposure environment of munitions and materials in SWA. From the equations developed in the report and the supplied computer program, most vapor pressure, humidity, air density, and altimetry computations can be accomplished. Results compare favorably with values in meteorological handbooks.				
14. SUBJECT TERMS Temperature, Vapor pressure, Air density, Relative humidity, Absolute humidity, Density altitude, Pressure humidity			15. NUMBER OF PAGES 23	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet *optical scanning requirements*.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.


Block 16. Price Code. Enter appropriate price code (NTIS only).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

CONTENTS

1. INTRODUCTION	5
2. ESTIMATION OF HUMIDITY PARAMETERS	5
3. ESTIMATION OF THE WET BULB FROM THE DRY BULB AND THE DEW POINT	7
4. ESTIMATION OF ABSOLUTE HUMIDITY, RELATIVE HUMIDITY, AND AIR DENSITY ..	7
5. COMPUTATION OF PRESSURE AND DENSITY ALTITUDES	9
6. SUMMARY	10
LITERATURE CITED	11
APPENDIX. "C" PROGRAM	13
DISTRIBUTION	23



1. INTRODUCTION

Recent (1990-1991) military operations in Southwest Asia resulted in the placement of materials and munitions into the most oppressive combinations of heat and humidity in the world. The Persian Gulf is a shallow body of water less than 200 m deep that attains remarkably high temperatures in summer. The average water temperature in July and August is 31.1 °C (88 °F). One of the highest dew points ever recorded was 33.9 °C (93 °F) at Sharjah, Saudi Arabia, which is near Dubai on the southern end of the Persian Gulf. At the northern end of the Persian Gulf exists the most extreme high temperature, high humidity environment on record. On 24 July 1953 at 1400 (LST), the temperature was 48.3 °C (119 °F) and the dew point was 29.4 °C (85 °F), which yields a relative humidity of 34 percent.

This hostile environment could adversely affect the storage life and operability of military equipment. Among the requests from the field for information on environmental conditions, there have been a substantial number regarding the interrelation of temperature, pressure, air density, and relative humidity. This report discusses the basic equations that relate these variables along with simpler approximations that provide the accuracy required for most meteorological operations. A computer code that computes these meteorological parameters is included for completeness. This computer code is not intended to be used for voluminous data input; however, modifications could be made so that all data could be input in one routine and then output the desired results. These equations and codes were supplied to AMSMC-QAN-P(D) to satisfy an immediate need and were not intended for field use.

2. ESTIMATION OF HUMIDITY PARAMETERS

For most meteorological applications, the moisture content of the atmosphere is conveniently measured by means of dry (T) and wet (T_w) bulb temperatures. However, the computation of other measures of humidity such as the dew point (T_d), vapor pressure (e), and relative humidity (RH) can be somewhat complex. Semiempirical equations (Goff and Gratch, 1945) are often used, but for many applications simpler and less accurate equations are sufficient. World Meteorological Organization Publication 8, TP.3 (WMO, 1969) gives the universal psychrometric formula for computation of humidity parameters as the Regnault equation (equation (1)).

$$e = e_w - Ap(T - T_w) \quad (1)$$

where e is the vapor pressure, p is air pressure, e_w is the saturation vapor pressure at T_w (wet bulb), T is the dry bulb temperature, and A is the psychrometric coefficient. The saturation vapor pressure is the source of the computational problem. The difficulty lies in the departures from the ideal gas law and the variation of latent heat with temperature. Several papers in the literature give empirical approximations for the saturation vapor pressure (Murray, 1967, and Tabata, 1973, for example). Saturation vapor pressure can be expressed as a function of absolute temperature by the Clausius-Clapeyron equation (equation (2)).

$$\frac{1}{e_s} \frac{de_s}{dT} = \frac{EL}{RT^2} \quad (2)$$

where e_s is the saturation vapor pressure, T is the absolute temperature, L is the latent heat of vaporization of water, R is the gas constant for dry air, and E is the ratio of molecular weight of water vapor to that of dry air. Integration of this equation is difficult because L is not constant, but varies with temperature. If it is assumed that L is a linear function of T then, according to Abbott and Tabony (1985), the saturation vapor pressure can be expressed as in equation (3).

$$e_s = \exp(55.17 - 6803 T^{-1} - 5.07 \ln T) \quad (3)$$

where T is temperature. From Buck (1981), a form for recovering T from the vapor pressure over water is given in equation (4).

$$T = \frac{CZ}{(B - Z)} \quad (4)$$

where $Z = \ln(e_w/a)$ and $a = 6.1121$, $B = 17.368$, and $C = 238.88$ (over ice: $a = 6.1115$, $B = 22.452$, and $C = 272.55$). Equations (3) and (4) appear to be adequate for most meteorological purposes. Wexler (1976) optimized these equations, and equation (5) is a most accurate formulation for e_w , with uncertainty being only a few parts per million (ppm).

$$\begin{aligned} e_w = 0.01 \exp[& -2991.2729\theta^{-2} - 6017.0128\theta^{-1} + 18.87643854 \\ & - 0.028354721\theta + 0.17838301 \times 10^{-4} \theta^2 - 0.84150417 \times 10^{-9} \theta^3 \\ & + 0.44412543 \times 10^{-12} \theta^4 + 2.858487 \ln \theta] \end{aligned} \quad (5)$$

where θ is absolute temperature in kelvins. Equation (5) also provides the best available estimate for vapor pressure over supercooled water and can be used for water values below 0 °C. Supercooled conditions are often encountered with cooled mirror hygrometers in which a mirror surface can maintain a layer of water at -15 °C. The equation for saturation vapor pressure over ice is not given in the text but is included in the computer code (see appendix for the "C" program) for completeness. The interested reader is referred to the paper by Wexler (1976) for the exact formulation.

Sometimes an enhancement factor is added to the vapor pressure computation to compensate for the difference in saturation vapor pressure over "pure" water to the saturation vapor pressure over ambient moist air. Hyland (1975) estimated this uncertainty at 1000 mbar to increase from 0.01 percent at 50 °C to 0.06 percent at -50 °C. For vapor pressure and temperature ranges encountered in

Southwest Asia, this enhancement factor is considered superfluous. The interested reader is referred to a paper by Buck (1981) if the factor is considered important. For most meteorological purposes the accuracy required of e_w is that equivalent to an error of 0.1 °C in temperature. Equation (5) easily satisfies this requirement.

3. ESTIMATION OF THE WET BULB FROM THE DRY BULB AND THE DEW POINT

The precision to which the temperature (T) and the dew point (T_d) are reported in the WMO synoptic code messages was increased in 1982 from 1 °C to 0.1 °C. This change made it possible to compute humidity parameters directly from the messages rather than through internal reporting of the wet bulb (T_w). The advantage is increased automation; but the recovery of T_w from T and T_d is required, and this procedure is not straightforward. Estimating T_w from T and T_d is more complex than obtaining T_d from T and T_w . Equation (1) is expressed in terms of the depression of the wet bulb rather than the dew point, and so can only be solved for T_d by using an iterative procedure. A simpler method is to take advantage of the fact that T_w lies between T and T_d . At low temperatures T_w is not much less than T, but at high temperatures T_w is closer to T_d . Hence, the ratio of the wet bulb depression to the dew-point depression always lies between zero and unity and increases with temperature. Abbott and Tabony (1985) give a convenient linear representation of this property in equation (6).

$$\frac{T - T_w}{T - T_d} = 0.34 + 0.006 (T + T_d) \quad (6)$$

For values of T from -10 °C to +50 °C and dew-point depressions up to 15 °C, errors in T_w from using equation (6) are always less than 0.3 °C. For increased accuracy an iterative approximation method is used in the supplied computer program.

4. ESTIMATION OF ABSOLUTE HUMIDITY, RELATIVE HUMIDITY, AND AIR DENSITY

Calculation of these values begins with a determination of e_s , which requires a knowledge not only of T and T_w but also of e_w at the wet bulb temperature. This can be obtained by replacing T by T_w in equation (3) to yield equation (7).

$$e_w = 6.1070 \exp \frac{17.38 T_w}{239.0 + T_w} \quad (7)$$

Since $e_s = e_{w(T_d)}$, the Regnault equation may be written as

$$e_{w(T_d)} = e_{w(T_w)} - Ap(T - T_w) \quad (8)$$

The ventilation coefficient A is usually taken to be 0.00079 (0.000720 if the wet bulb is frozen). Accurate values of p should be used. Abbot and Tabony (1985) show errors of about 20 percent in e, 2 percent in relative humidity, and 2 °C in T_d if a pressure of 1000 mbar is used when in reality the pressure was 950

mbar. The correct pressure to apply is the site pressure, uncorrected for altitude. The dew point can be calculated from the transposed Magnus (1844) equation for evaporation over water (equation (9)).

$$T_d = \frac{(239.0 K)}{(17.38 - K)} \quad (9)$$

where $K = \ln e - \ln 6.1070$.

The saturation vapor pressure at the dry bulb is then computed so that the relative humidity (RH) may be calculated from equation (10).

$$RH = \frac{e_{s,T_d}}{e_{s,T}} \times 100 \quad (10)$$

where e_s is the saturation vapor pressures at T and T_d .

Absolute humidity (AH) is the mass of water vapor per unit volume of atmosphere. The equation of state for water vapor can be written as

$$\rho_{ws} = \frac{(e_s m_w)}{(RT_s)} \quad (11)$$

where ρ_{ws} is the absolute humidity (grams per cubic meter) and the subscript refers to saturation conditions over water. e_s and T_s are the vapor pressure and temperature at saturation and m_w is the mass or weight of the water vapor. Equation (12) is a convenient computational method for determining absolute humidity.

$$AH = \frac{1322.8314}{T} \exp [25.22 \times (1.0 - (273.15/T_d)) + 5.31 \times \ln (273.15/T_d)] \quad (12)$$

where T and T_d are air temperature (K) and dew-point temperature (K), respectively. AH is expressed in grams per cubic meter.

Specific humidity (q) is defined as the weight of water vapor contained in a unit weight of air. Units of q are usually expressed in grams per gram or grams per kilogram. A simple expression for q is given by equation (13).

$$q = \frac{w}{1 + w} \quad \text{where: } w = \frac{0.622 e}{p - e} \quad (13)$$

where e is the vapor pressure at T and p is air pressure (mbar). Units are grams per gram.

The virtual temperature (T_v) is defined as the temperature of dry air having the same total pressure and density as the moist air. An expression for T_v is given by equation (14). p and e have the same meaning as in equation (13).

$$T_v = T(1 + 0.61w) \quad \text{where: } w = \frac{0.622 e}{p - e} \quad (14)$$

Once T_v is known the air density can be calculated from equation (15) (List, 1958).

$$\rho = 0.34838 \frac{p}{T_v} \quad (15)$$

where ρ is air density in kilograms per cubic meter, p is site pressure in millibars, and T_v is virtual temperature in kelvins.

5. COMPUTATION OF PRESSURE AND DENSITY ALTITUDES

Pressure altitude (PA) is the height above sea level in the standard atmosphere at which the altimeter setting (A) exists. The PA (in meters) can be computed by using equation (16).

$$PA = \frac{T_s}{a} [1 - (A/P_s)^{(1/n)}] + H_e \quad (16)$$

where T_s is the standard sea level temperature (288.16 K), a is the standard lapse rate (0.0065 °C/m), A is the site altimeter reading (inches mercury [Hg]), P_s is the standard sea-level pressure (29.921 inches Hg), n is a constant with a value of 5.2561, and H_e is the site elevation in meters above sea level. Restated, pressure altitude is the distance measured from the 29.921 inches hg pressure level, which is the standard datum plane.

Density altitude (DA) is the altitude above sea level characterized by a known air density. Density altitude bears the same relation to pressure altitude as true altitude does to indicated altitude. DA may be computed by using equation (17).

$$DA = 145,366 [1 - 17.326 (P_m/T_v)^{0.235}] \quad (17)$$

The units of DA are in feet; and A, He, P_s, and n are defined as above for pressure altitude and P_m is defined as

$$P_m = [A^{1/n} - He(P_s)^{1/n} (\frac{a}{T_s})]^n$$

6. SUMMARY

In determining the various measures of humidity, the greatest difficulty lies in evaluating the saturation vapor pressure. This difficulty is related to departures from the ideal gas law and the variation of latent heat with temperature. These departures make the Clausius-Clapeyron equation difficult to integrate analytically. Semiempirical equations by Goff and Gratch (1946) are available for extremely accurate computations of saturation vapor pressure, but for most meteorological purposes this accuracy is superfluous. Equations given in this report are simpler approximations providing the accuracy required for most meteorological applications. A simple iteration routine has been supplied for determining the wet bulb temperature from the temperature and dew point. From the equations and the supplied computer program, most vapor pressure, humidity, air density, and altimetry computations can be accomplished. Results compare favorably with values in meteorological handbooks.

LITERATURE CITED

- Abbott, P. F., and R. C. Tabony, 1935, The estimation of humidity parameters, Meteorological Magazine, 11:49-56.
- Buck, A. L., 1981, New Equations for Computing Vapor Pressure and Enhancement Factor, J Appl Meteorol, 20:1527-1532.
- Goff, J. A., and S. Gratch, 1946, Low-pressure properties of water from -160 to 212 F, Trans Amer Soc Heat Vent Eng, 52:95-121.
- Goff, J. A., and S. Gratch, 1945, Thermodynamic properties of moist air, Trans Amer Soc Heat Vent Eng, 51:125-157.
- Hyland, R. W., 1975, A correlation of the second interaction virial coefficients and enhancement factors for moist air, J Res Natl Bur Standards, 79A:551-560.
- List, R. J., 1958, Smithsonian Meteorological Tables, 6th Revised Edition, Washington D.C., The Smithsonian Institution.
- Magnus, G., 1844, 'Versuche über die Spannkrafte des Wasserdampfes,' Ann Phy Chem (Poggendorff), 66:225.
- Murray, F. W., 1967, On the computation of saturation vapor pressure, J Appl Meteorol, 6:203-204.
- Tabata, S., 1973, A simple but accurate formula for the saturation vapor pressure over liquid water, J Appl Meteorol, 12:1410-1411.
- Wexler, A., 1976, Vapor pressure formulation for water in the range 0 to 100 C - A Revision, J Res Natl Bur Standards, 80A:775.
- WMO, 1969, Guide to Meteorological Instruments and Observing Practices, WMO-No. 8. TP.3, Third Edition, Secretariat of the World Meteorological Organization, Geneva, Switzerland.

APPENDIX
"C" PROGRAM

/*

File: SVP.C
Program: Saturation Vapor Pressure.
Author: Kevin K. Lewis, 1991.
Purpose: SVP computes the saturation vapor pressure of a set of input data. See the provided documentation for a full explanation.

SVP was written for the Weather Data Integration Branch of the Battle Weather Data Division of the Atmospheric Sciences Laboratory.

SVP.C was compiled using Borland's Turbo C++ compiler. It was not compiled using any C++ options, so it should compile with any Borland compiler and run properly.

SVP.C should easily port to any system with an ANSI C compatible compiler.

*/

```
#include <stdio.h>
#include <math.h>

void Svp( double *T, double *Tw, double *P );
double Ew( double T );
void Air_Density( double T, double P );
void Temp();
void Wet_T( double T, double Td, double P );
double Dew_Point( double T, double P );
void Density_Altitude( double *T );
void Pressure_Altitude();
int Get_Data( double *data, char param, char *t );
double Convert_Temp( double temp, char type, char need );
double Convert_Pressure( double p, char type, char need );
double Convert_Height( double h, char type, char need );
char Getchar();

/* Define the variables. */
double K, ewp, Td, Tw, R, rho;
char numstr[50], ch;

void main()
```

```

(
double T, Tv, P;
puts( ' ');
puts( ' *** Saturation Vapor Pressure *** ');
puts( ' ');
puts( '\nInstructions:\n' );
puts( 'When prompted, follow your input by a letter corresponding to the units of' );
puts( 'the input values. For example, 20 degrees Celsius is entered as 20c (capital' );
puts( 'or lower case 'C'). 293 Kelvin as 293K, 68 degrees Fahrenheit as 68F, 29.92' );
puts( 'inches of mercury as 29.92I, 1013 millibars as 1013m, 1000 feet as 1000F.' );
puts( 'and 300 meters as 300M. Output units are given with the computed value.' );

do (

    Svp( &T, &Tv, &P );

    Air_Density( Tv, P );

    do (
        printf( '\nWould you like to compute the Density Altitude (y/n)? ' );
        ch=Getchar();
        if( ch!='y' && ch!='Y' && ch!='n' && ch!='N' ) (
            putchar( '\a' );
            ch=0;
        )
    ) while( !ch );
    if( ch=='y' || ch=='Y' )
        Density_Altitude( &T );

    do (
        printf( '\nWould you like to compute the Pressure Altitude (y/n)? ' );
        ch=Getchar();
        if( ch!='y' && ch!='Y' && ch!='n' && ch!='N' ) (
            putchar( '\a' );
            ch=0;
        )
    ) while( !ch );
    if( ch=='y' || ch=='Y' )
        Pressure_Altitude();

/*
... We are done with all the computations. Find out if the user has some
other stuff to do.
*/

do (
    printf( '\n\nWould you like to compute additional values (y/n)? ' );
    ch=Getchar();
    if( ch!='y' && ch!='Y' && ch!='n' && ch!='N' ) (
        putchar( '\a' );
        ch=0;
    )
) while( !ch );
) while( ch=='y' || ch=='Y' );

}

```

```

void Svp( double *T, double *Tw, double *P )

{
    double AH, RH, q, w, e;
    /* Get the dry bulb temperature. */
    puts( '\n' );
    do {
        printf( 'Input the dry bulb temperature T followed by K, C, or F: ' );
    } while( Get_Data( T, 'T', &ch ) == -1 );
    *T = Convert_Temp( *T, ch, 'K' );

    /* Get the pressure. */
    do {
        printf( 'Input the pressure P followed by I or M (default=1013.25mb): ' );
    } while( Get_Data( P, 'P', &ch ) == -1 );
    *P = Convert_Pressure( *P, ch, 'M' );

    do {
        printf( '\nDo you have the dew point temperature (y/n)? ' );
        ch = Getchar();
        if( ch != 'y' && ch != 'Y' && ch != 'n' && ch != 'N' ) {
            putchar( '\a' );
            ch = 0;
        }
    } while( !ch );
    putchar( 10 );
    if( ch == 'y' || ch == 'Y' ) {
        do {
            printf( 'Input the dew point temperature Td followed by K, C, or F: ' );
        } while( Get_Data( &Td, 'T', &ch ) == -1 );
        Td = Convert_Temp( Td, ch, 'K' );
        e = Ew( Td );
        Wet_T( *T, Td, *P );
    }
    else {
        do {
            printf( 'Input the wet bulb temperature Tw followed by K, C, or F: ' );
        } while( Get_Data( &Tw, 'T', &ch ) == -1 );
        Tw = Convert_Temp( Tw, ch, 'K' );
        Td = Dew_Point( *T, *P );
        printf( '\nThe Dew Point Temperature is \t\tZ10.4f [Kelvin]\n', Td );
        printf( '\t\tZ10.4f [Celsius]\n', Convert_Temp( Td, 'K', 'C' ) );
        printf( '\t\tZ10.4f [Fahrenheit]\n', Convert_Temp( Td, 'K', 'F' ) );
        e = Ew( Td );
    }
}

/* Compute 'ewp' */
ewp = Ew( *T );
printf( '\nThe Saturation Vapor Pressure e(T) is \tZ10.4f [millibars]\n', ewp );

printf( '\nThe Saturation Vapor Pressure e(Td) is \tZ10.4f [millibars]\n', e );

```

```

/* Compute the relative humidity. */
RH=e/ewp*100;
printf( "The Relative Humidity is \t\tZ10.4f%%\n", RH );

/* Compute the absolute humidity. */
AH=( 1322.8314/(T) ) *exp( 25.22*( 1.0 - ( 273.15/Td ) ) + 5.31*log( 273.15/Td ) );
printf( "\nThe Absolute Humidity is \t\tZ10.4f [grams per cubic meter]\n", AH );

/* Compute the virtual temperature. */
w=0.622*ewp/( P - ewp );
q=w/( 1.0 + w );
printf( "The Specific Humidity is \t\tZ10.4f [grams per gram]\n", q );
Tv=T*( 1.0 + 0.61*w );
printf( "The Virtual Temperature is \t\tZ10.4f [Kelvin]\n", Tv );
}

double Ew( double T ) /* T must be in K, and P must be in mB. */
(
    double satvp;
/*
    The second equation is used for saturation vapor pressure over ice. If you
    wish to use this equation, remove the comment markers on the indicated lines.
*/
/* Remove this line.
    if( T<273.15 )
        Remove this line. */

    satvp=0.01*exp( -2991.2729/( T*T ) - 6017.0128/T + 18.87643854 -
        0.028354721*T + 0.17838301e-4*T*T - 0.84150417e-9*T*T*T +
        0.44412543e-12*T*T*T*T + 2.858487*log( T ) );

/* Remove this line.
    else
        satvp=0.01*exp( -5865.3696/T + 22.241033 + 0.013749042*T -
            0.34031775e-4*T*T + 0.26967687e-7*T*T*T + 0.6918651*log( T ) );
    Remove this line. */

    return satvp;
}

/* Compute the air density. */
void Air_Density( double Tv, double P )
(
    double rho;
    rho=0.34838*P/Tv;
    printf( "\nThe Air Density is \t\t\tZ10.4f [kilograms per cubic meter]\n", rho );
)

```

```

/* Compute the dew point. */
double Dew_Point( double T, double P )

{
    double A=0.000799, es, e, K;
    T -= 273.16; Tw -= 273.16; /* convert to deg C */
    es=6.107*exp( 17.38*Tw/( 239.0 + Tw ) );
    e = es - A*P*( T - Tw );
    K = log( e ) - log( 6.1070 );
    /* printf( "\ne, es, K, P, T, Tw = %7.3f, %7.3f, %7.3f, %8.3f, %7.3f, %7.3f\n",
        e, es, K, P, T, Tw ); */
    return ( 239.0*K )/( 17.38 - K ) + 273.16;
}

void Wet_T( double T, double Td, double P )

{
    int times=0;
    double tw0, F, Fp, dif;
    double A, a, b, c;
    T=Convert_Temp( T, 'K', 'C' );
    Td=Convert_Temp( Td, 'K', 'C' );
    tw0=0.5*( T + Td );
    do {
        if( tw0>=0.0 ) {
            A=0.000799;
            a=17.38;
            b=239.0;
        }
        else {
            A=0.00072;
            a=22.44;
            b=272.4;
        }
        c=6.107*exp( a*Td/( b + Td ) ) + A*P*T;
        F = 6.107*exp( a*tw0/( b + tw0 ) ) + A*P*tw0 - c;
        Fp = 6.107*a*b/( ( b + tw0 )*( b + tw0 ) )*exp( a*tw0/( b + tw0 ) ) + A*P;
        dif=F/Fp;
        do {
            dif=0.5*dif;
        } while( fabs(dif/tw0)>=0.5 );
        tw0 = tw0 - dif;
        if( times++>20 ) {
            puts( "\nWarning: possible error in computing wet bulb temperature--20 iterations done." );
            break;
        }
    } while( fabs( dif )>=0.001 ); /* If it's accurate enough; stop. */
    printf( "\nThe wet bulb temperature is %t\tX10.4f [Celsius]\n", tw0 );
    printf( "          \t\tX10.4f [Celsius]\n", Convert_Temp( tw0, 'C', 'X' ) );
    printf( "          \t\tX10.4f [Fahrenheit]\n", Convert_Temp( tw0, 'C', 'F' ) );
    Tw=tw0;
}

```

```

}

```

```

void Density_Altitude( double *T )

```

```

{
    double r=.006, a=.0065, n=5.2561, Ps=29.921, Ts=288.16;
    double Alt, He, rho_h, Pm, Tv;
    char numstr[50];
    printf( "\nInput T followed by K, C, or F (default is original input=X7.2fK): ", *T );
    if( Get_Data( T, 'T', &ch )!=-1 )
        *T=Convert_Temp( *T, ch, 'K' );
    Tv = -0.288 + ( 9.0/5.0 )*( *T )*( 1.0 + 1.60779*r )/( 1.0 + r );
    do {
        printf( "Input Site Pressure Uncorrected followed by I or M: " );
    } while( Get_Data( &Alt, 'P', &ch )!=-1 );
    Alt=Convert_Pressure( Alt, ch, 'I' );
    do {
        printf( "Input site elevation followed by M or F: " );
    } while( Get_Data( &He, 'H', &ch )!=-1 );
    He=Convert_Height( He, ch, 'M' );
    Pm=pow( pow( Alt, 1.0/n ) - He*pow( Ps, 1.0/n )*( a/Ts ), n );
    rho_h=145366.0*( 1.0 - pow( 17.326*( Pm/Tv ), 0.235 ) );
    printf( "The Density Altitude is \t\tX10.4f [feet]\n", rho_h );
    printf( " \t\tX10.4f [meters]\n", Convert_Height( rho_h, 'F', 'M' ) );
}

```

```

void Pressure_Altitude()

```

```

{
    double PA, Ts, a, A, Ps, n, He;
    Ts=288.16;
    a=0.0065;
    puts( "\n" );
    do {
        printf( "Input the Altimeter Value followed by I or M: " );
    } while( Get_Data( &A, 'P', &ch )!=-1 );
    A=Convert_Pressure( A, ch, 'I' );
    do {
        printf( "Input the site elevation followed by M or F: " );
    } while( Get_Data( &He, 'H', &ch )!=-1 );
    He=Convert_Height( He, ch, 'M' );
    Ps=29.921;
    n=5.2561;
    PA=( Ts/a )*( 1.0 - pow( A/Ps, 1.0/n ) ) + He;
    printf( "The Pressure Altitude is \t\tX10.4f [meters]\n", PA );
    printf( " \t\tX10.4f [feet]\n", Convert_Height( PA, 'M', 'F' ) );
}

```

```

int Get_Data( double *data, char param, char *type )
{
    int len;
    double tmp;
    char t[50];
    gets( t );
    if( strcmp( t, "" )==0 ) {
        if( param=='P' ) {
            *data=1013.25;
            *type='M';
            return 0;
        }
        else
            return -1;
    }
    len=strlen( t );
    *type=t[len-1];
    switch( param ) {
        case 'T':
            if( *type!='C' && *type!='c' && *type!='K' && *type!='k' && *type!='F' && *type!='f' )
                return -1;
            break;
        case 'P':
            if( *type!='M' && *type!='m' && *type!='I' && *type!='i' )
                return -1;
            break;
        case 'H':
            if( *type!='M' && *type!='m' && *type!='F' && *type!='f' )
                return -1;
            break;
    }
    t[len-1]='\0';
    *data=atof( t );
    tmp=Convert_Temp( *data, *type, 'C' );
    if( param=='T' ) {
        if( tmp<-100.0 || tmp>100.0 ) {
            puts( "Temperature is out of range. Enter a new temperature, -100°C<T<100°C" );
            return -1;
        }
    }
    return 0;
}

```

```

double Convert_Temp( double temp, char type, char need )

```

```

(
switch( need ) (
    case 'K':
        switch( type ) (
            case 'k':
            case 'K':
                return temp;
            case 'f':
            case 'F':
                return 5.0/9.0*( temp - 32.0 ) + 273.15;
            case 'c':
            case 'C':
                return temp + 273.15;
        )
    case 'C':
        switch( type ) (
            case 'k':
            case 'K':
                return temp - 273.15;
            case 'f':
            case 'F':
                return 5.0/9.0*( temp - 32.0 );
            case 'c':
            case 'C':
                return temp;
        )
    case 'F':
        switch( type ) (
            case 'k':
            case 'K':
                return 9.0/5.0*( temp - 273.15 ) + 32.0;
            case 'c':
            case 'C':
                return 9.0/5.0*temp + 32.0;
            case 'f':
            case 'F':
                return temp;
        )
    )
return -1;
)

```

```
double Convert_Pressure( double p, char type, char need )
```

```
{
    switch( need ) {
        case 'I':
            switch( type ) {
                case 'i':
                case 'I':
                    return p;
                case 'm':
                case 'M':
                    return p/33.86;
            }
        case 'M':
            switch( type ) {
                case 'i':
                case 'I':
                    return 33.86*p;
                case 'm':
                case 'M':
                    return p;
            }
    }
    return -1;
}
```

```
double Convert_Height( double h, char type, char need )
```

```
{
    switch( need ) {
        case 'M':
            switch( type ) {
                case 'f':
                case 'F':
                    return h*0.3048;
                case 'm':
                case 'M':
                    return h;
            }
        case 'F':
            switch( type ) {
                case 'f':
                case 'F':
                    return h;
                case 'm':
                case 'M':
                    return h*3.280839895;
            }
    }
    return -1;
}
```

```
}
```

```
char Getchar()
```

```
{
```

```
    char c;
```

```
    c=getchar();
```

```
    fflush( stdin );
```

```
    return c;
```

```
}
```

DISTRIBUTION LIST FOR PUBLIC RELEASE

Commandant
U.S. Army Chemical School
ATTN: ATZN-CM-CC (S. Barnes)
Fort McClellan, AL 36205-5020

Commander
U.S. Army Aviation Center
ATTN: ATZQ-D-MA
Mr. Oliver N. Heath
Fort Rucker, AL 36362

Commander
U.S. Army Aviation Center
ATTN: ATZQ-D-MS (Mr. Donald Wagner)
Fort Rucker, AL 36362

NASA/Marshall Space Flight Center
Deputy Director
Space Science Laboratory
Atmospheric Sciences Division
ATTN: E501 (Dr. George H. Fichtl)
Huntsville, AL 35802

NASA/Marshall Space Flight Center
Atmospheric Sciences Division
ATTN: Code ED-41
Huntsville, AL 35812

Deputy Commander
U.S. Army Strategic Defense Command
ATTN: CSSD-SL-L
Dr. Julius Q. Lilly
P.O. Box 1500
Huntsville, AL 35807-3801

Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-AC-AD
Donald R. Peterson
Redstone Arsenal, AL 35898-5242

Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-AS-SS
Huey F. Anderson
Redstone Arsenal, AL 35898-5253

Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-AS-SS
B. Williams
Redstone Arsenal, AL 35898-5253

Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-DE-SE
Gordon Lill, Jr.
Redstone Arsenal, AL 35898-5245

Commander
U.S. Army Missile Command
Redstone Scientific Information
Center
ATTN: AMSMI-RD-CS-R/Documents
Redstone, Arsenal, AL 35898-5253

Commander
U.S. Army Intelligence Center
and Fort Huachuca
ATTN: ATSI-CDC-C (Mr. Colanto)
Fort Huachuca, AZ 85613-7000

Northrup Corporation
Electronics Systems Division
ATTN: Dr. Richard D. Tooley
2301 West 120th Street, Box 5032
Hawthorne, CA 90251-5032

Commander - Code 3331
Naval Weapons Center
ATTN: Dr. Alexis Shlanta
China Lake, CA 93555

Commander
Pacific Missile Test Center
Geophysics Division
ATTN: Code 3250-3 (R. de Violini)
Point Mugu, CA 93042-5000

Commander
Pacific Missile Test Center
Geophysics Division
ATTN: Code 3250 (Terry E. Battalino)
Point Mugu, CA 93042-5000

Lockheed Missiles & Space Co., Inc.
Kenneth R. Hardy
Org/91-01 B/255
3251 Hanover Street
Palo Alto, CA 94304

Commander
Naval Ocean Systems Center
ATTN: Code 54 (Dr. Juergen Richter)
San Diego, CA 92152-5000

Meteorologist in Charge
Kwajalein Missile Range
P.O. Box 67
APO San Francisco, CA 96555

U.S. Department of Commerce
Mountain Administration Support
Center
Library, R-51 Technical Reports
325 S. Broadway
Boulder, CO 80303

Dr. Hans J. Liebe
NTIA/ITS S 3
325 S. Broadway
Boulder, CO 80303

NCAR Library Serials
National Center for Atmos Rsch
P.O. Box 3000
Boulder, CO 80307-3000

Bureau of Reclamation
ATTN: D: 1200
P.O. Box 25007
Denver, CO 80225

HQDA
ODCSOPS
ATTN: DAMO-FDZ
Washington, D.C. 20310-0460

Mil Asst for Env Sci Ofc of
The Undersecretary of Defense
for Rsch & Engr/R&AT/E&LS
Pentagon - Room 3D129
Washington, D.C. 20301-3080

Director
Naval Research Laboratory
ATTN: Code 4110
Dr. Lothar H. Ruhnke
Washington, D.C. 20375-5000

HQDA
DEAN-RMD/Dr. Gomez
Washington, D.C. 20314

Director
Division of Atmospheric Science
National Science Foundation
ATTN: Dr. Eugene W. Bierly
1800 G. Street, N.W.
Washington, D.C. 20550

Commander
Space & Naval Warfare System Command
ATTN: PMW-145-1G (LT Painter)
Washington, D.C. 20362-5100

Commandant
U.S. Army Infantry
ATTN: ATSH-CD-CS-OR
Dr. E. Dutoit
Fort Benning, GA 30905-5090

USAFETAC/DNE
Scott AFB, IL 62225

Air Weather Service
Technical Library - FL4414
Scott AFB, IL 62225-5458

HQAWS/DOZ
Scott AFB, IL 62225-5008

USAFETAC/DNE
ATTN: Mr. Charles Glauber
Scott AFB, IL 62225-5008

Commander
U.S. Army Combined Arms Combat
ATTN: ATZL-CAW (LTC A. Kyle)
Fort Leavenworth, KS 66027-5300

Commander
U.S. Army Combined Arms Combat
ATTN: ATZL-CDB-A (Mr. Annett)
Fort Leavenworth, KS 66027-5300

Commander
U.S. Army Space Institute
ATTN: ATZI-SI (Maj Koepsell)
Fort Leavenworth, KS 66027-5300

Commander
U.S. Army Space Institute
ATTN: ATZL-SI-D
Fort Leavenworth, KS 66027-7300

OL-AA PL/LYP
ATTN: Mr. Chisholm
Hanscom AFB, MA 01731-5000

OL-AA PL/LY
ATTN: Dr. Robert A. McClatchey
Hanscom AFB, MA 01731-5000

Raytheon Company
Dr. Charles M. Sonnenschein
Equipment Division
528 Boston Post Road
Sudbury, MA 01776
Mail Stop 1K9

Director
U.S. Army Materiel Systems
Analysis Activity
ATTN: AMXSY-MP (H. Cohen)
APG, MD 21005-5071

Commander
U.S. Army Chemical Rsch,
Dev & Engr Center
ATTN: SMCCR-OPA (Ronald Pennsyle)
APG, MD 21010-5423

Commander
U.S. Army Chemical Rsch,
Dev & Engr Center
ATTN: SMCCR-TDT (Mr. Joseph Vervier)
APG, MD 21010-5423

Commander
U.S. Army Chemical Rsch,
Dev & Engr Center
ATTN: SMCCR-MUC (Mr. A. Van De Wal)
APG, MD 21010-5423

Director
U.S. Army Materiel Systems
Analysis Activity
ATTN: AMXSY-GC (Mr. Fred Campbell)
APG, MD 21005-5071

Director
U.S. Army Materiel Systems
Analysis Activity
ATTN: AMXSY-CR (Robert N. Marchetti)
APG, MD 21005-5071

Director
U.S. Army Materiel Systems
Analysis Activity
ATTN: AMXSY-CS (Mr. Brad W. Bradley)
APG, MD 21005-5071

Commander
U.S. Army Laboratory Command
ATTN: AMSLC-CG
2800 Powder Mill Road
Adelphi, MD 20783-1145

Commander
Headquarters
U.S. Army Laboratory Command
ATTN: AMSLC-CT
2800 Powder Mill Road
Adelphi, MD 20783-1145

Commander
Harry Diamond Laboratories
ATTN: SLCIS-CO
2800 Powder Mill Road
Adelphi, MD 20783-1197

Director
Harry Diamond Laboratories
ATTN: SLCHD-RT-AC
Dr. Z.G. Sztankay
Adelphi, MD 20783-1197

Air Force Systems Command/WER
Andrews AFB, MD 20334-5000

National Security Agency
ATTN: W21 (Dr. Longbothum)
9800 Savage Road
Ft George G. Meade, MD 20755-6000

Officer in Charge
Naval Surface Weapons Center
White Oak Library
Technical Library
Silver Springs, MD 20910-1090

The Environmental Research
Institute of MI
ATTN: IRIA Library
P.O. Box 8618
Ann Arbor, MI 48107-8618

Commander
U.S. Army Research Office
ATTN: DRXRO-GS (Dr. W.A. Flood)
P.O. Box 12211
Research Triangle Park, NC 27709

Dr. Jerry Davis
North Carolina State University
Department of Marine, Earth, &
Atmospheric Sciences
P.O. Box 8208
Raleigh, NC 27650-8208

Commander
U.S. Army Cold Regions Research
& Engineering Laboratory
ATTN: CRREL-RG (Mr. Robert Redfield)
Hanover, NH 03755-1290

Commander
U.S. Army Cold Regions Research
& Engineering Laboratory
ATTN: CECRL-RD (Dr. K.F. Sterrett)
Hanover, NH 03755-1290

Commanding Officer
U.S. Army Armament R&D Command
ATTN: DRDAR-TSS, Bldg 59
Dover, NJ 07801

U.S. Army Communications-Electronics
Command Center for EW/RSTA
ATTN: AMSEL-RD-EW-SP
Fort Monmouth, NJ 07703-5303

Commander
U.S. Army Communications-Electronics
Command
ATTN: AMSEL-EW-D (File Copy)
Fort Monmouth, NJ 07703-5303

Headquarters
U.S. Army Communications-Electronics
Command
ATTN: AMSEL-EW-MD
Fort Monmouth, NJ 07703-5303

Commander
U.S. Army Satellite Comm Agency
ATTN: DRCPM-SC-3
Fort Monmouth, NJ 07703-5303

Director
EW/RSTA Center
ATTN: AMSEL-EW-DR
Fort Monmouth, NJ 07703-5303

USACECOM
Center for EW/RSTA
ATTN: AMSEL-RD-EW-SP
Fort Monmouth, NJ 07703-5303

6585th TG (AFSC)
ATTN: RX (CPT Stein)
Holloman AFB, NM 88330

Department of the Air Force
OL/A 2nd Weather Squadron (MAC)
Holloman AFB, NM 88330-5000

PL/WE
Kirtland AFB, NM 87118-6008

Director
U.S. Army TRADOC Analysis Command
ATTN: ATRC-WSS-R
White Sands Missile Range, NM 88002

Rome Laboratory
ATTN: Technical Library RL/DOVL
Griffiss AFB, NY 13441-5700

Department of the Air Force
7th Squadron
APO, NY 09403

AWS
USAREUR/AEAWX
APO, NY 09403-5000

AF Wright Aeronautical Laboratories
Avionics Laboratory
ATTN: AFWAL/AARI (Dr. V. Chimelis)
Wright-Patterson AFB, OH 45433

Commander
U.S. Army Field Artillery School
ATTN: ATSF-F-FD (Mr. Gullion)
Fort Sill, OK 73503-5600

Commandant
U.S. Army Field Artillery School
ATTN: ATSF-TSM-TA
Mr. Charles Taylor
Fort Sill, OK 73503-5600

Commander
Naval Air Development Center
ATTN: Al Salik (Code 5012)
Warminster, PA 18974

Commander
U.S. Army Dugway Proving Ground
ATTN: STEDP-MT-DA-M
Mr. Paul Carlson
Dugway, UT 84022

Commander
U.S. Army Dugway Proving Ground
ATTN: STEDP-MT-DA-L
Dugway, UT 84022

Commander
U.S. Army Dugway Proving Ground
ATTN: STEDP-MT-M (Mr. Bowers)
Dugway, UT 84022-5000

Defense Technical Information Center
ATTN: DTIC-FDAC
Cameron Station
Alexandria, VA 22314

Commanding Officer
U.S. Army Foreign Science &
Technology Center
ATTN: CM
220 7th Street, NE
Charlottesville, VA 22901-5396

Naval Surface Weapons Center
Code G63
Dahlgren, VA 22448-5000

Commander
U.S. Army OEC
ATTN: CSTE-EFS
Park Center IV
4501 Ford Ave
Alexandria, VA 22302-1458

Commander and Director
U.S. Army Corps of Engineers
Engineer Topographics Laboratory
ATTN: ETL-GS-LB
Fort Belvoir, VA 22060

Department of the Air Force
HQ 5 Weather Wing (MAC)
ATTN: 5 WW/DN
Langley AFB, VA 23665-5000

Commander and Director
U.S. Army Corps of Engineers
Engineer Topographics Laboratory
ATTN: CEETL-ZD
Fort Belvoir, VA 22060-5546

Commander
Logistics Center
ATTN: ATCL-CE
Fort Lee, VA 23801-6000

Commander
USATRADOCC
ATTN: ATCD-FA
Fort Monroe, VA 23651-5170

Science and Technology
101 Research Drive
Hampton, VA 23666-1340

Commander
U.S. Army Nuclear & Cml Agency
ATTN: MONA-ZB Bldg 2073
Springfield, VA 22150-3198