

AD-A242 604



TION PAGE

Form Approved
OMB No. 0704-0188

Page 1 of 1 of 1 response. Including the time for reviewing instructions, searching existing data sources, gathering of information, and collection of information. Send comments regarding this burden estimate or any other aspect of this Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

2

1. REPORT DATE 11/06 /91		3. REPORT TYPE AND DATES COVERED POP Test (07/91)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Container, Shipping and Storage, CNU-405/E for Packing Group II Solid Hazardous Material		5. FUNDING NUMBERS	
6. AUTHOR(S) James M. Dwyer, Mechanical Engineering Tech		8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/ NADTR91021 Rev. A	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Weapons Station Earle Test and Evaluation Branch (Code 5023) Colts Neck, NJ 07722-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER Same as above	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Commander, Pacific Missile Test Center ATTN: Monacchio (Code 2042) Point Mugu, CA 93042		11. SUPPLEMENTARY NOTES N/A	
12a. DISTRIBUTION / AVAILABILITY STATEMENT DTIC S ELECTE NOV 19 1991 C D		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Qualification tests were performed to determine whether the in-service CNU-405/E Shipping and Storage Container could be utilized to contain properly dunnaged solid type hazardous materials weighing up to a gross weight of 70.24 kg (155 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the United Nations Recommendations on the Transportation of Dangerous Goods and the Department of Transportation's Title 49 CFR and the Final Rulings published in the Federal Register, Vol. 55 on 21 Dec 90. The container has conformed to the POP performance requirements; i.e., the container successfully retained its contents throughout the specified tests.			
14. SUBJECT TERMS POP Test of CNU-405/E Shipping and Storage Container		15. NUMBER OF PAGES 6	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		16. PRICE CODE	
18. SECURITY CLASSIFICATION OF THIS PAGE UL		19. SECURITY CLASSIFICATION OF ABSTRACT UL	
20. LIMITATION OF ABSTRACT UL			

91-15856



91 1118 089

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines to meet optical scanning requirements.**

Block 1. Agency Use Only (Leave Blank)

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of ..., To be published in When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denote public availability or limitation. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR)

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - DOD - Leave blank

DOE - DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports

NASA - NASA - Leave blank

NTIS - NTIS - Leave blank.

Block 13. Abstract. Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (NTIS only).

Blocks 17. - 19. Security Classifications.

Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

DODPOPHM/USA/DOD/NADTR91021 REVISION A

Superseding
DODPOPHM/USA/DOD/NADTR91021
21 August 1991

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
CONTAINER, SHIPPING AND STORAGE, CNU-405/E
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
James M. Dwyer
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

6 November 1991

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Pacific Missile Test Center
Code 2042
Point Mugu, California 93042

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTRODUCTION

The CNU-405/E Shipping and Storage Container tested, contained inert 25 mm cartridges weighing 63 kg (116.6 pounds), and an additional 7.2 kg (16 pounds) of lead. Weight of the loaded container was 70 kg (155 pounds). This Performance Oriented Packaging (POP) test was performed to ascertain whether this standard container (Packing Group II) would meet the requirements as specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9. A base level vibration test was also conducted in accordance with the final rulings specified in the Department of Transportation's Performance Oriented Packaging Standards in the Federal Register Volume 55. Due to unavailability, only two containers were used which is less than the number required by the UN recommendation. This has been approved by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

The objectives of these tests were to minimize the risk of personnel or environmental exposure to the hazards associated with the contents in the advent of a transportation or handling accident.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with paragraph 178.608 of the Performance Oriented Packaging Standards, Final Ruling, published in the Federal Register, Vol. 55, No. 246, December 21, 1990. One sample container was placed on the repetitive shock platform. The container was restrained during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour at a frequency of 3.2 Hz.

2. Stacking Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.6. One container was used for this test. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a height of 3 meters (including the test sample). A weight of 562 kg (1,240 pounds) was stacked on the sample container. The test was performed for 24 hours. After the allowed time, the weight was removed and the containers examined.

3. Drop Test

This test was performed in accordance with ST/SG/AC.10/1, chapter 9, paragraph 9.7.3. One container was used throughout the test. Five drops were performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom
- b. Flat top
- c. Flat on long side
- d. Flat on short side
- e. One corner

All tests were performed at an ambient temperature of $+70 \pm 20$ °F.

PASS/FAIL (UN CRITERIA)

1. Base Level Vibration Test (HM-181 CRITERIA)

The criteria for passing the base level vibration test is outlined in paragraph 178.608 of the Title 49 CFR Final Ruling and states the following: "immediately following the period of vibration, each package shall be removed from the platform, turned on its side and observed for any evidence of leakage. Rupture or leakage from any of the packages constitutes failure of the test."

2. Stacking Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.6.3 of ST/SG/AC.10/1 and states the following: "... no test sample should leak. No test sample should show any deterioration which could adversely affect transport safety or any distortion liable to reduce its strength or cause instability in stacks of packages "

3. Drop Test (UN CRITERIA)

The criteria for passing the drop test is outlined in paragraph 9.7.3.5 of ST/SG/AC.10/1 and states the following: "Where a packaging for solids undergoes a drop test and its upper face strikes the target, the test sample passes the test if the entire contents are retained by an inner packaging or inner receptacle; e.g., a plastic bag, even if the closure is no longer sift-proof. A slight discharge from the closure(s) upon impact should not be considered to be a failure of the packaging provided that no further leakage occurs."

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

Immediately after the vibration test was completed, each container was removed from the platform, turned on its side and observed for any evidence of leakage. There was no leakage to the containers as a result of this test.

2. Stacking Test

Each container was visibly checked after the 24-hour period was over. There was no leakage, distortion, or deterioration to any of the containers as a result of this test.

3. Drop Test

After each drop, the containers were inspected for any damage which would be a cause for rejection. Final inspection indicated damage was minimal with only minor denting noted. The containers remained intact and functional upon completion of the tests.

REFERENCE MATERIAL

A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6

B. Title 49 CFR 107, et al., Performance Oriented Packaging Standard; Changes to Classification, Hazard Communication, Packaging and Handling Requirements Based on UN Standards and Agency Initiative; Final Rule, Federal Register, Vol. 55, No. 246 of December 21, 1990.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)

ATTN: DTIC/FDA

Bldg. 5, Cameron Station

Alexandria, VA 22304-6145

Headquarters, Military Traffic Management Command (2 copies)

ATTN: MT-SS, James Gibson

5611 Columbia Pike

Falls Church, VA 22041-5050

Commanding Officer

Naval Weapons Support Center

ATTN: D. Colglazier (Code 50254)

Crane, IN 47522-5000

Commanding General

Marine Corps Research, Development, and Acquisition Command

ATTN: AM

Washington, DC 20380-0001

TEST DATA SHEET

DATA SHEET:	
Container: CNU-405/E Shipping and Storage Container	
Type: 4A2	Container P/N or NSN: 8140-01-201-8596
Specification Number: NAVAIRSYSCOM Drawing 986AS106	Material: Steel
Gross Weight: 70.24 kg (155 pounds)	Dimensions: 18.54" L x 10.51" W x 14.59" H
Closure (Method/Type): Removable Lid	Tare Weight: 10.17 kg (22.45 pounds)
Additional Description: Also as part of test 16 pounds lead	
PRODUCT:	
Name: See table	NSN(s): See table
United Nations Number: See table	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container:	Flash Point: N/A
Net Weight: See table	
TEST PRODUCT:	
Name: 25 mm Cartridge	Physical State: Solid
Consistency: N/A	
Density/Specific Gravity: N/A	
Test Pressure (Liquids Only): N/A	
Amount Per Container: N/A	Net Weight: 52.85 kg (116.55 pounds)

TABLE 1
CNU-405/E Shipping and Storage Container

NALC	NSN	Type	Packing Drawing	UN Code	UN Number	#/ Cntr	Weight (kg)
A974	1305-01-209-5915	25 mm M791	5167214	1.4C	0339	55	44.7
A975	1305-01-212-8360	25 mm M792	5167214	1.2E (04)	0321	55	44.7
A976	1305-01-212-5066	25 mm M793	5167214	1.4C	0417	55	44.7
A978	1305-01-210-6802	25 mm PGU-23	1829AS100	1.4C	0339	100	67.2
A978	1305-01-250-0101	25 mm PGU-23	12013674	1.4C	0339	80	57.7
A979	1305-01-251-2582	25 mm PGU-20	12013674	1.4C	0339	80	57.7
A979	1305-01-251-3623	25 mm PGU-20	1829AS100	1.4C	0339	100	67.2
A980	1305-01-136-3624	25 mm PGU-22	1829AS100	1.2E	0321	100	70.2
A981	1305-01-213-2581	25 mm Mk 210	5167214	1.2E	0321	55	44.7
A981	1305-01-271-7782	25 mm Mk 210/2	5167214	1.2E	0321	55	44.7
A982	1305-01-199-6737	25 mm PGU-25	1829AS100	1.2E	0321	100	70.2
A982	1305-01-250-0100	25 mm PGU-25	12013674	1.2E	0321	80	57.7
A982	1305-01-270-2318	25 mm PGU-25A/U	1829AS100	1.2E	0321	100	70.2

CNU-405/E
SHIPPING AND STORAGE CONTAINER
POP MARKING

UN 4A2/Y70/S//USA/DOD/NAD**

**** YEAR LAST PACKED OR MANUFACTURED**

Encl (2)