

AD-A245 537



This estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and reviewing the collection of information, Send comments regarding this burden estimate or any other aspect of this burden, including this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Road, to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

2. REPORT DATE
01/923. REPORT TYPE AND DATES COVERED
POP Test (11/91)4. TITLE AND SUBTITLE
Performance Oriented Packaging Testing of Wood Box,
Shipping and Storage, PPP-B-601, for PHOENIX Rocket
Motor for Packing Group II Solid Hazardous Materials

5. FUNDING NUMBERS

6. AUTHOR(S)

James M. Dwyer

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Weapons Station Earle
Test and Evaluation Branch (Code 5023)
Colts Neck, NJ 07722-50008. PERFORMING ORGANIZATION
REPORT NUMBERDODPOPHM/USA/DOD/
NADTR91030

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Commander, Naval Air Systems Command
(AIR-41821B)
Department of the Navy
Washington, DC 20361-805010. SPONSORING / MONITORING
AGENCY REPORT NUMBER

Same as above

11. SUPPLEMENTARY NOTES

N/A

12a. DISTRIBUTION / AVAILABILITY STATEMENT

This document has been approved
for public release and sale; its
distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

Qualification tests were performed to determine whether the in-service PPP-B-601 Shipping and Storage Wood Box for PHOENIX Rocket Motor could be utilized to contain properly dunnaged solid type hazardous materials weighing up to a gross weight of 322 kg (710 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the United Nations Recommendations on the Transportation of Dangerous Goods, ST/SG/AC.10/1 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178. The wood box has conformed to the POP performance requirements; i.e., the wood box successfully retained its contents throughout the specified tests.

DTIC

ELECTE

FEB 05 1992

92-02706



14. SUBJECT TERMS

POP Test of PPP-B-601 Shipping and Storage Wood Box
for PHOENIX Rocket Motor

15. NUMBER OF PAGES

5

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT
UNCLASSIFIED18. SECURITY CLASSIFICATION
OF THIS PAGE
UL19. SECURITY CLASSIFICATION
OF ABSTRACT
UL20. LIMITATION OF ABSTRACT
UL

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with; Trans. of; To be published in. When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

DODPOPHM/USA/DOD/NADTR91030

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
WOOD BOX, SHIPPING AND STORAGE, PPP-B-601
FOR PHOENIX ROCKET MOTOR
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
James M. Dwyer
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

January 1992

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Air Systems Command
(Code AIR-41821B)
Washington, DC 20361-8050

Accession For	
NTIS	CRA&I ☒
DTIC	TAB ☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Specnl
A-1	



INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the PPP-B-601 Shipping and Storage Wood Box (Packing Group II) meets the requirements specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 1 October 1991. The box contents consisted of one inert rocket motor section weighing 211 kg (465 pounds), and an additional 16 kg (35 pounds) of sand. Gross weight of the loaded box was 322 kg (710 pounds). Due to unavailability only one box was available for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test shall be performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The box shall be placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the boxes shall be restricted during vibration in all but the vertical direction. The frequency of the platform shall be increased until the box leaves the platform 1/16 of an inch at some instant during each cycle. Test time shall be 1 hour.

2. Stacking Test

This test shall be performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The box shall be subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a height of 3 meters (including the test box). A weight of 1,361 kg (3,000 pounds) shall be stacked on the test box. The test shall be performed for 24 hours. The weight shall then be removed and the container examined.

3. Drop Test

This test shall be performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Five drops shall be performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom.
- b. Flat top.
- c. Flat on long side.
- d. Flat on short side.
- e. One corner.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): "A packaging passes the vibration test if there is no rupture or leakage from any of the packages."

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): "No test sample may leak. In composite packagings or combination packagings, there must be no leakage of the filling substance from the inner receptacle, or inner packaging. No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength or cause instability in stacks of packages."

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested--

(1) For removable head drums for solids, the entire contents are retained by an inner packaging (e.g., a plastic bag) even if the closure on the top head of the drum is no longer sift-proof;

(2) For a composite or combination packaging, there is no damage to the outer packaging likely to adversely affect safety during transport, and there is no leakage of the filling substance from the inner packaging;

(3) For a drum, jerrican or bag, any discharge from a closure is slight and ceases immediately after impact with no further leakage;

(4) For packagings for explosives, no rupture of the packaging occurs.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

Immediately after the vibration test was completed, the box was removed from the platform, turned on its side and observed for evidence of leakage. No leakage was observed.

2. Stacking Test

The box was visibly checked after the 24-hour period was over. No leakage, distortion, or deterioration was observed.

3. Drop Test

After each drop, the box was inspected for evidence of leakage. No leakage was observed.

REFERENCE MATERIAL

A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6.

B. Code of Federal Regulations, Title 49 CFR, Parts 107 through 178.

C. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Defense General Supply Center (1 copy)
ATTN: DDRV-TMPA, D. Gray
Richmond, VA 23219

Hercules
ATTN: Jim Sherrard
1101 Johnson Drive
McGregor, TX 76657

Naval Air Systems Command
ATTN: C. Moran (Code AIR-41821B)
Washington, DC 20361-8050

TEST DATA SHEET

DATA SHEET:	
Container: PPP-B-601 Shipping and Storage Wood Box for PHOENIX Rkt Mtr	
Type: 4D	Container P/N or NSN:
Specification Number: PPP-B-601	Material: Wood
Gross Weight: 322 kg (710 pounds)	Dimensions: 74" L x 25-3/4" W x 29-1/2" H
Closure (Method/Type): 16 clips and banding	Tare Weight: 95 kg (210 pounds)
Additional Description: Banding (3/4" strap), 3 places	
PRODUCT:	
Name: See table	NSN(s): See table
United Nations Number: See table	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container:	Flash Point: N/A
Net Weight: See table	
TEST PRODUCT:	
Name: Rocket Motor and 35 pounds of sand	Physical State: Solid
Consistency: N/A	
Density/Specific Gravity: N/A	
Test Pressure (Liquids Only): N/A	
Amount Per Container: N/A	Net Weight: 227 kg (500 pounds)

TABLE 1
PPP-B-601 Shipping and Storage Wood Box for PHOENIX Rocket Motor

NALC	NSN	Type	Packing Drawing	UN Code	UN Number	#/ Cntr	Weight (lb)
V885	1337-01-135-6910	Rocket Motor	RK392A00041	1.3C	0186	1	465
V887	1337-01-272-2172	Rocket Motor	RK392A00041	1.3C	0186	1	465

NOTE: The container is qualified for a maximum net weight of 500 pounds.

**PPP-B-601 SHIPPING AND STORAGE
WOOD BOX FOR
PHOENIX ROCKET MOTOR
POP MARKING**

UN 4D/Y322/S//USA/DOD/NAD**

**** YEAR LAST PACKED OR MANUFACTURED**