

1. The first group of respondents (Group 1) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

2. The second group of respondents (Group 2) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

3. The third group of respondents (Group 3) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

4. The fourth group of respondents (Group 4) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

5. The fifth group of respondents (Group 5) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

6. The sixth group of respondents (Group 6) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

7. The seventh group of respondents (Group 7) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

8. The eighth group of respondents (Group 8) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

9. The ninth group of respondents (Group 9) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

10. The tenth group of respondents (Group 10) consisted of 100 individuals who were randomly selected from the general population of the United States. This group was used to determine the overall prevalence of the disease in the population.

2


Prepared by:


K. J. Libbert

Reviewed by:


R. F. Sanders

Reviewed by:


R. F. Karcher

Approved by:


D. N. Montgomery

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 27 Jan 92	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of the M2A1 Ammunition Box for Packing Group II Solid Hazardous Mtrl.			5. FUNDING NUMBERS	
6. AUTHOR(S) Kerry J. Libbert				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Crane Division Naval Surface Warfare Center Code 5053 Crane, IN 47522			8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92101	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Crane Division Naval Surface Warfare Center Code 5042 Crane, IN 47522			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Unlimited Distribution			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The M2A1 Ammunition Box (Drawing 19200-7553296) was tested for conformance to Performance Oriented Packaging criteria established by the United Nations Recommendations on the Transport of Dangerous Goods. The box was tested with a gross weight of 33 pounds (15.0 kilograms) and met all requirements.				
14. SUBJECT TERMS M2A1 Ammunition Box Performance Oriented Packaging, Hazardous Materials			15. NUMBER OF PAGES 7	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

INTRODUCTION

The M2A1 Ammunition Box was tested to ascertain whether the container would meet the requirements of Performance Oriented Packaging (POP) as specified by the United Nations Recommendations on the Transport of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9. A base level vibration test was also conducted in accordance with the rulings specified by the Department of Transportation Performance Oriented Packaging Standards, 49 CFR Part 106 et al. Federal Register/Vol. 56, No. 245/Friday, December 20, 1991/Rules and Regulations. The objectives were to evaluate the adequacy of the container in protecting Packing Group II solid hazardous materials.

The M2A1 box is made of steel and has a hinged lid with a handle on top. The box is shown in Figure 1.

TESTS PERFORMED

1. Drop Test

This test was performed in accordance with ST/SG/AC.10/1, Chapter 9, Paragraph 9.7.3. Five containers were used during the test series, one for each drop. The drop height was 1.2 meters and the drop sequence was as follows:

- a. Flat on Bottom
- b. Flat on Top
- c. Flat on Long Side
- d. Flat on Short Side
- e. On a Corner

The test was performed at ambient temperature ($70^{\circ} + 20^{\circ}\text{F}$). The contents of the container should be retained within its packaging and exhibit no damage liable to affect safety during transport.

2. Stacking Test

This test was performed in accordance with ST/SG/AC.10/1, Chapter 9, Paragraph 9.7.6. Three different containers were used, each with a stack weight of 830 pounds. The test was performed for 24 hours. After the allowed time, the weight was removed and the container examined. Any leakage, deterioration, or distortion which could adversely affect transport or reduce its strength or cause instability in stacks of packages is cause for rejection.

3. Base Level Vibration Test

This test was performed in accordance with the Federal Register/Vol 55, No. 246/Friday, December 21, 1990/Final Rule. Three sample containers were loaded with steel weights and closed as for shipment. Each container was placed on a vibrating



platform that had a vertical double-amplitude (peak-to-peak displacement) of one inch. The packages were constrained horizontally to prevent them from falling off the platform, but were free to move vertically, bounce and rotate. The test was performed for one hour at a frequency that caused each point of the container bottom to be raised from the platform to such a degree that a 1.6mm thick metal strip could be passed between the bottom of any package and the platform.

PASS/FAIL (UN CRITERIA)

The criteria for passing the drop test is outlined in Paragraph 9.7.3.5 of ST/SG/AC.10/1 and states the following: "Where a packaging for solids undergoes a drop test and its upper face strikes the target, the test sample passes the test if the entire contents are retained by an inner packaging or inner receptacle (e.g., a plastic bag), even if the closure is no longer sift-proof".

The criteria for passing the stacking test is outlined in Paragraph 9.7.6.3 of ST/SG/AC.10/1 and states the following: "No test sample should show any deterioration which could adversely affect transport safety or any distortion liable to reduce its strength or cause instability in stacks of packages".

PASS/FAIL (FEDERAL REGISTER CRITERIA)

The criteria for passing the Base Level Vibration Test is outlined in the Federal Register/Vol. 56, No. 245/Friday, December 20, 1991/Rules and Regulations and states the following: "Immediately following the period of vibration, each package shall be removed from the platform, turned on its side and observed for any evidence of leakage. A packaging passes the vibration test if there is no rupture or leakage from any of the packages. No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength."

TEST RESULTS

1. Drop Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Base Level Vibration Test

Satisfactory.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Date	
App. Authority	
Date	
Dist	
A-1	

DISCUSSION

1. Drop Test

After each drop the container was inspected for any damage which would be cause for rejection. Final inspection revealed minor damage to the boxes, but no spillage of contents.

2. Stacking Test

Three containers were individually tested. Each container was visibly inspected after the 24-hour period was over. There was no leakage, distortion, or deterioration to the container as a result of this test.

3. Base Level Vibration Test

Immediately following the vibration test, each container was removed from the platform, turned on its side and observed for any evidence of leakage. All latches remained fastened and there was no evidence of leakage of contents.

REFERENCE MATERIAL

United Nation's "Recommendations on the Transport of Dangerous Goods", ST/SG/AC.10/1, Revision 6

Department of Transportation Performance Oriented Packaging Standards, 49 CFR Part 106 et al. Federal Register/Vol. 56, No. 245/Friday, December 20, 1991/Rules and Regulations

DISTRIBUTION LIST

Commander
Crane Division
Naval Surface Warfare Center
Code 5053 and Code 5042
Crane, IN 47522-5000

Commanding Officer
Naval Weapons Station Earle
Code 403 and Code C11
Colts Neck, NJ 07722-5000

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDAC (Virginia Guidi)
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Headquarters, Military Traffic Management Command (2 copies)
ATTN: MTMC/MT-SS (James Gibson)
5611 Columbia Pike
Falls Church, VA 22041-5050

Defense General Supply Center
DDRV-TMPA (Dave Gay)
Richmond, VA 23297-5000

DATA SHEET

CONTAINER:

M2A1 Ammunition Box

Type: 4A1

UN Code: See Table I

Specification Number:
Drawing 19200-7553296

Material:
Steel

Gross Weight:
15.0 kg
(33.0 pounds)

Dimensions:
.30m L x .15m W x .19m H
(12.00" L x 6.09" W x 7.50" H)

Closure (Method/type):
Latch (1 ea.)

Tare Weight:
2.4 kg
(5.2 pounds)

Additional Description: Box was constructed in accordance
with drawing 19200-7553296.

PRODUCTS:

See Table I

Proper Shipping Name: See Table II

United Nations Number: See Table I

United Nations Packing Group: II

Physical State: Solid

Amount Per Container: See Table I

Net Weight: Varies

TEST PRODUCT:

Name: Steel rods

Physical State: Solid

Size: .11m L x .02m Dia
(4.50" L x 1.00" Dia)

Quantity: 27

Dunnage: Foam polyethylene, PPP-C-1752

Gross Weight: 15.0 kg (33.0 lbs.)

TABLE I

DODIC OR NALC	NSN	ITEM	TYPE	PACKING DRAWING	HAZ. CL.	UN NO.	# CNTR.	PER WT	GROSS (KG)
2W89	1370-01-239-9544	MJU-8A/B	FLARE	2816235	1.3G	0093	21	9.0	
3W92	1370-01-251-5792	MK137-0	SIGNAL	6537416			12	4.5	
LW60	1370-01-032-7028	MK46-1C	FLARE	2816235	1.3G	0093	21	9.0	
LW62	1370-01-041-2629	MJU-8/B	FLARE	2816235	1.3G	0093	21	9.0	
L161	1370-01-252-0318	MK131-0	SIGNAL	6263403			10	6.3	
L273	1370-01-177-4072	MK99-3	SIGNAL	6118534	1.4G	0191	5	6.0	
L451	1370-01-252-0317	MK132-0	SIGNAL	6263400			10	6.1	
M862	1377-00-806-4886	S-75	SQUIB	2128480	1.4S	0454	500	4.0	
M996	1375-01-069-6671	MK87-0	CHARGE		1.1D	0048	5	11.0	
M997	1375-01-068-3984	MK88-0	CHARGE	5206288	1.4D	0410	5	8.5	
MW86	1375-01-020-8907	MK48-0	DEVICE	3192610	1.4S	0367	2	4.9	
N250	1390-00-451-8695	MK342-1	FUZE	2513109	1.4S	0349	8	8.2	
N259	1390-00-563-7712	MK393-0	FUZE	2513109	1.2D	0409	8	7.7	
N457	1390-01-146-7620	MK417-0	FUZE	2513109	1.2D	0409	8	10.4	
N458	1390-00-488-3993	MK404-0	FUZE	2513109	1.2D	0409	8		
N618	1390-01-043-1683	MK407-1	FUZE	2513109	1.2D	0409	8	10.4	
N670	1390-01-178-8609	MK418-0	FUZE	2513109	1.2D	0409	8	10.0	

TABLE II

UN SERIAL NUMBER	PROPER SHIPPING NAME
0048	CHARGES, DEMOLITION
0093	FLARES, AERIAL
0191	SIGNAL DEVICES, HAND
0349	ARTICLES, EXPLOSIVE, N.O.S.
0367	FUZES, DETONATING
0409	FUZES, DETONATING
0410	FUZES, DETONATING
0454	IGNITERS