

AD-A248 895



PAGE

Form Approved
OMB No 0704-0188

2

Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 04/92	3. REPORT TYPE AND DATES COVERED POP Test (01/92)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Container, Shipping and Storage, Mk 461 Mod 1 for Packing Group II Solid Hazardous Materials		5. FUNDING NUMBER DTIC ELECTE S D D APR 22 1992	
6. AUTHOR(S) Lewis Coutts		8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92001	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Weapons Station Earle Test and Evaluation Branch (Code 5023) Colts Neck, NJ 07722-5000		10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Commander, Naval Sea Systems Command (Code PMS-422) Washington, DC 20362-5101		10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A			
12a. DISTRIBUTION/AVAILABILITY STATEMENT This document has been approved for public release and sale; its distribution is unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Qualification tests were performed to determine whether the in-service Mk 461 Mod 1 Shipping and Storage Container could be utilized to contain properly dunnaged solid type hazardous materials weighing up to a gross weight of 67 kg (148 pounds). The tests were conducted in accordance with Performance Oriented Packaging (POP) requirements specified by the United Nations Recommendations on the Transportation of Dangerous Goods, ST/SG/AC.10/1 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178. The container has conformed to the POP performance requirements; i.e., the container successfully retained its contents throughout the specified tests.			
14. SUBJECT TERMS POP Test of Mk 461 Mod 1 Shipping and Storage Container		15. NUMBER OF PAGES 7	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		16. PRICE CODE	
18. SECURITY CLASSIFICATION OF THIS PAGE UL		19. SECURITY CLASSIFICATION OF ABSTRACT UL	
		20. LIMITATION OF ABSTRACT UL	



92 4 20 168

**Best
Available
Copy**

DODPOPHM/USA/DOD/NADTR92001

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
CONTAINER, SHIPPING AND STORAGE, MK 461 MOD 1
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
Lewis Coutts
Mechanical Engineer

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

April 1992

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Commander, Naval Sea Systems Command
(Code PMS-422)
Washington, DC 20362-5101

Accession For	
NTIS CRA&I	
DTIC TAB	
Unannounced	
Justification	
By	
Distribution	
Availability	
Dist	Avail
A-1	Spec



INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 461 Mod 1 Shipping and Storage Container (Packing Group II) meets the requirements specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 1 October 1991. The container contents consisted of one inert SM2 Block IIIB Guidance Section weighing 52 kg (115 pounds). Gross weight of the loaded container was 67 kg (148 pounds).

Due to unavailability only two containers were used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990. The containers were identified as #1 and #2.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The container #1 was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container leaves the platform $1/16$ of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The container #1 was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a height of 3 meters (including the test container). A weight of 268 kg (592 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then be removed and the container examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Five drops were performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom using container #1.
- b. Flat top using container #1.

- c. Flat on long side using container #1.
- d. Flat on short side using container #1.
- e. One corner using container #2.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 3.5 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The container was visibly checked after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the tested container was inspected. The guidance section was completely retained by the container.

REFERENCE MATERIAL

A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6.

B. Code of Federal Regulations, Title 49 CFR, Parts 107-178.

C. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Defense General Supply Center (1 copy)
ATTN: DDRV-TMPA, D. Gray
Richmond, VA 23219

TEST DATA SHEET

DATA SHEET:	
Container: Mk 461 Mod 1 Shipping and Storage Container	
Type: 4H1	Container P/N or NSN: N/A
Specification Number: DL 6213011	Material: Polystyrene Bead Foam
Gross Weight: 67 kg (148 pounds)	Dimensions: 52.4" L x 24" W x 24" H
Closure (Method/Type): PPP-T-97 Tape	Tare Weight: 15 kg (33 pounds)
Additional Description:	
PRODUCT:	
Name: See table	NSN(s): See table
United Nations Number: See table	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container:	Flash Point: N/A
Net Weight: See table	
TEST PRODUCT:	
Name: SM2 Blk IIIB Guidance Section	Physical State: Solid
Consistency: N/A	
Density/Specific Gravity: N/A	
Test Pressure (Liquids Only): N/A	
Amount Per Container: N/A	Net Weight: 52 kg (115 pounds)

TABLE 1
Products Approved for Shipping in the
Mk 461 Mod 1 Shipping and Storage Container

NALC	NSN	Type	Packing Drawing	UN Code	UN Number	#/ Cntr	Weight (lb)
N/A	N/A	SM2 Blk IIIB Guidance Sect	6213011	N/A	N/A	1	115

N/A = Not Assigned

MK 461 MOD 1
SHIPPING AND STORAGE CONTAINER
POP MARKING

UN 4H1/Y88/S//USA/DOD/NAD**

**** YEAR LAST PACKED OR MANUFACTURED**