

AD-A250 034



2

TECHNICAL REPORT BRL-TR-3329

BRL

SHOCK TUBE STUDY OF THE REACTION OF
TRIETHANOL AMMONIUM NITRATE WITH N_2O

RICHARD A. BEYER

APRIL 1992

DTIC
SELECTE
MAY 15 1992
S B D

92-12917



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE April 1992	3. REPORT TYPE AND DATES COVERED Final, Sep 89 - Dec 90		
4. TITLE AND SUBTITLE Shock Tube Study of the Reaction of Triethanol Ammonium Nitrate With N ₂ O		5. FUNDING NUMBERS PR: 1L161102AH43		
6. AUTHOR(S) Richard A. Beyer				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066		10. SPONSORING / MONITORING AGENCY REPORT NUMBER BRL-TR-3329		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) The ignition of triethanol ammonium nitrate in O ₂ and N ₂ O has been studied in a shock tube over the temperature range from 1,300 K to 1,950 K. The ignition threshold for TEAN in 5% N ₂ O is above 1,300 K. The reactions can be described by Arrhenius kinetics with activation energies of 17.0 kcal/mol and 20.7 kcal/mol, respectively.				
14. SUBJECT TERMS liquid propellants, LP1846, shock tube, triethanol ammonium nitrate (TEAN), kinetics		15. NUMBER OF PAGES 21		
		16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES	v
1. INTRODUCTION	1
2. EXPERIMENTAL	1
3. OBSERVATIONS	2
4. ANALYSIS	4
5. DISCUSSION	5
6. CONCLUSION	6
7. REFERENCES	13
DISTRIBUTION LIST	15

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Schematic Diagram of the Test End of the Shock Tube	7
2. Eight Consecutive Line Images at 50 μ s Intervals From the End of the Shock Tube During Ignition of TEAN in N_2O/Ar	8
3. Signal From PbSe Detector at 4.49 μ m (N_2O emission) During Passage of Shocks for Calculated Reflected Shock Temperatures of (a) 1,665 K and (b) 2,390 K	9
4. Light Signals Detected at 389 nm for TEAN Heated in N_2O/Ar and Pure Ar	10
5. Light Detected at 389 nm for TEAN Heated in O_2/Ar	10
6. Arrhenius Plot of Ignition Delay vs. Inverse Temperature for TEAN Heated in N_2O/Ar	11
7. Arrhenius Plot of Ignition Delay Vs. Inverse Temperature for TEAN in O_2/Ar	11

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

Liquid propellants based on aqueous solutions of hydroxyl ammonium nitrate (HAN) and various fuels have been the subject of extensive studies (Decker et al. 1987). Of particular interest are the propellants designated LP1845 and LP1846, where the fuel is triethanol ammonium nitrate (TEAN). In our earlier work (Beyer 1990) we have shown that nitrous oxide, known to be a major product of the thermal decomposition of HAN, reacts with (ignites) TEAN powder. In this study, we further characterize this reaction at lower pressures, and attempt to produce an overall kinetics rate constant for this complex reaction.

2. EXPERIMENTAL

The shock tube used in these studies is stainless steel with a 98-mm inside diameter. The driver section is 1.2 m long; the driven (test) section is 6.3 m long. For typical conditions of the present measurements, a 0.001-in (25.4- μ m) thick Mylar polyester diaphragm was used. The initial pressures were 18 psi (120 kpa) in the driver section and from 5 to 20 torr (0.6 to 2.6 kpa) in the test section. The test gas was either 5% oxidizer in argon or pure argon. The driver gas was 30% air with the balance helium to maximize the test time. Under typical conditions, the passage of the initial shock raises the test gas to a temperature of about 750–1,000 K with a corresponding pressure increase. The reflected shock typically doubles the temperature of the gas and also raises the pressure. These present measurements were carried out over a range of reflected shock temperatures from 1,300 K to 1,900 K. Pressure in the reflected shock was near one half an atmosphere. The pressures were lower than those of the earlier studies in an attempt to increase the ignition delay time to where the temperature dependence could be more easily determined.

The layout of the test end of the shock tube is shown in Figure 1. A variety of instrumentation was used. Pressure transducers were placed at a minimum of two points to characterize the shock wave propagation. From the calculated shock velocity, a frozen-chemistry thermochemical equilibrium code (Gordon and McBride 1971) was used to calculate the pressure and temperature behind the shock waves. Ignition time was detected through a window in the end wall by a photomultiplier tube with a 389-nm filter, where strong CN radical emission from the onset of combustion is favored over other sources of light in the tube. A PbSe infrared detector with appropriate wavelength filters was used to study the emission from the nitrous oxide. In some experiments, carbon dioxide emission from mixtures of 5%

carbon dioxide in argon were also studied to compare signal loss for a molecule not expected to dissociate as rapidly as the nitrous oxide. The field of view for the infrared studies was a narrow region near pressure gauge No. 1 in Figure 1 (viewed from the side). A limited number of observations were also made with a Fairchild model 1200C line camera to verify that the ignition was taking place as predicted. In our present setup, we were able to record a line image with 200-point spatial resolution each 50 μ s. All signals were recorded with a 4-channel transient digitizer and analyzed with an i487-based ("PC-clone") desktop computer.

The sample of TEAN to be ignited (typically < 20 mg) was ground to a fine powder and placed on a 1-in-diameter disk with feathered edges mounted in the center of the tube about 210 mm from the end wall. TEAN is fairly hygroscopic. Samples were kept in a desiccator prior to use, and further outgassed in the evacuated shock tube for about 1 hour on humid days and when it was thought possible that water may have been added during transfer to the shock tube. No attempt was made to analyze the percent hydration of the samples. During a shock experiment, the incident shock wave sweeps the powder off the disk and disperses it in the region between the disk and the end wall. It is assumed that the smallest particles, which are the earliest to ignite, move with the gas velocity behind the shock wave. The incident shock is not sufficiently hot in these experiments to ignite the sample and its chemical effect is ignored. The reflected shock returns from the end wall, heats the particles, which then ignite after a measured delay time in the stagnant gas. The smallest particles are calculated to be on the order of 100 mm from the end wall when they encounter the reflected shock. The pressure and shock transit time between pressure gauges are measured directly. The pressure rise associated with the shocks is calculated from the code (Gordon and McBride 1971); as long as the calculated and measured pressures are in reasonable agreement, the experimental behavior is assumed to be ideal and the calculated numbers are used to determine the time of interaction of the reflected shock and the smallest TEAN particles.

3. OBSERVATIONS

A series of line images from the line camera is shown in Figure 2. These images were recorded under somewhat stronger shock conditions than typical data in order to raise the temperature and provide sufficiently strong signals for the camera to record. As can be seen in the figure, there is a small amount of early light at approximately 25 mm (12 arb units) from the end wall, followed by ever greater amounts of light as the larger particles to the right ignite and burn. In subsequent images, the amount of light grows even greater to the right for about a millisecond. Because of experimental difficulty and variability,

the camera pixel units were not calibrated; rather, the predicted point of ignition was marked with a light source and compared to the observation. The total field of view of the camera was on the order of 4 inches (100 mm). The apparent signal peak at the end wall has not been addressed in detail; it may be due to impurities.

An important issue raised in our earlier study was on the thermal stability of the nitrous oxide. Before pursuing these ignition measurements further, a study of this stability was made using the infrared detector and a 4.49- μm bandpass filter. Without the filter, the emission followed the pressure trace very well (but with a much slower rise time). A typical trace of good behavior observed with the filter is shown in Figure 3a. The incident and reflected shocks pass the point of observation at 0 and 200 μs , respectively. The relatively slow rise (compared to the pressure, which is instantaneous on this time scale) is assumed to be instrumental. As can be seen, the N_2O emission was probably not affected by thermal decomposition before the ignition time; this held true as long as we stayed below about 1,900 K. An example of a hotter shock and presumed loss of N_2O due to thermal decomposition is shown in Figure 3b. Under some conditions the 4.49- μm signal was not as steady as expected based on temperature and the pressure records. Under these conditions, measurements were made with a mixture of CO_2 in argon and a 4.29- μm filter. The same unsteady behavior and limited test time were observed, leading to the conclusion that the temperature variations were flow-related; shock tube conditions, especially pressure ratios, were adjusted accordingly to minimize these changes.

The ignition was determined from the light detected through the 389-nm filter, which is assumed to be dominated by CN emission. There are clearly other sources of light at this wavelength under the conditions of these experiments. However, as long as our tube was kept reasonably clean, in order to limit the amount of black body emission from background particles, the ignition discrimination was reasonably good. Figure 4 shows the light signals detected with samples of TEAN shocked under nearly identical conditions ~ 1,600 K and 0.5 atm. As can be seen in the figure, the light rises much earlier with the N_2O present. In Figure 4, the two signals are not on the same scale; the quantity of light with an oxidizer present (e.g., N_2O in this case) is always much greater. For comparison, measurements were also made with oxygen/argon mixtures. The ignition characteristics were somewhat different, as shown in Figure 5. Of particular note is the indication of a distinctive slope break, which was frequently, but not always, present in the oxygen shots. This phenomenon will be discussed in more detail later. The oxygen shots were also different in that there was almost always total consumption of the TEAN powder, compared to the nitrous oxide shots where a considerable residue of the larger particles always remained. Although

it was not carefully quantified, the ignition threshold for TEAN in 5% N₂O/Ar under the conditions of these experiments was about 1,325 K.

4. ANALYSIS

As mentioned earlier, the shock wave calculations are assumed to describe the experimental conditions. In order to measure an ignition delay time, the time that the particles enter the hot flow must be known. The assumptions are made that the smallest solid particles move with the gas velocity behind the incident shock, and that these same small particles heat up on a time scale short compared with the delay time (i.e., instantaneously) and that they are the first to ignite. The ignition delay time of these smallest particles is thus calculated from the results of the shock wave calculations which are based on the velocity, which is determined from the pressure gauge timing measurements, and the initial test section pressure. Thus, time zero for the heating of the particles is the calculated time for the smallest particles to enter the reflected shock region.

In order to deduce a "first light" time from the photomultiplier signals, the derivative of the signal is taken. For most of the N₂O signals, this technique yields the same result as careful inspection of the light signal. However, for the O₂ observations, there is frequently, but not always, a second sharp break in the derivative.

It is reasonable to first assume that the kinetics are described by an Arrhenius form,

$$\text{Rate} = [\text{oxidizer}]Ae^{-E_a/RT} ,$$

where [oxidizer] is the concentration of N₂O or O₂. In our measurements, the fraction of the gas which is oxidizer is always 5%, so this concentration is proportional to the pressure/temperature ratio in the reflected shock region. Since the observed delay time is proportional to the inverse of the rate, we can rewrite this expression as:

$$\frac{\text{Delay} * \text{Pressure}}{\text{Temperature}} = A' e^{E_a/RT} .$$

Graphically, if we plot the natural log of the product of the delay time with the (calculated) pressure divided by the (calculated) temperature vs $1,000/\text{temperature}$, the slope is E_a/R where E_a is the activation energy of the reaction and R is the gas constant. Figure 6 shows such a plot for the ignition of TEAN by N_2O/Ar . Although the number of data is not large, the behavior is reasonable. Since there are two breaks in the oxygen data, both were plotted and analyzed (Figure 7). In order to determine the activation energy more accurately, the data were fit to the full Arrhenius form using the well known but undocumented FITTER program of A. J. Kotlar. The activation energy from these N_2O data is 20.7 ± 1.1 kcal/mol where the uncertainty is one standard deviation. The activation energy for the oxygen data analyses are 16.4 ± 1.2 kcal/mol and 17.6 ± 6.4 kcal/mol for the first and second breaks, respectively. These are essentially the same within their statistical uncertainties (standard deviations) and have been combined as one data set to give a value of 17.0 ± 3.3 kcal/mol for the reaction with oxygen. It is of some note that the magnitude of the delays is not greatly different for the two oxidizers studied here.

5. DISCUSSION

The interpretation of the numbers measured here is interesting. When the TEAN is heated in the shock tube, it possibly can burn as solid; melt and burn as a liquid; or melt, thermally decompose, and burn as a gas. The melting point of TEAN is near 80°C with decomposition taking place at much higher temperatures—nearer 280°C . There was not a readily available apparatus for the measurement of the heat of fusion prior to the preparation of this report. A search of some previous contract work done by the Navy (Skahan 1987) yielded values of 149 J/g (7.55 kcal/mol) for pure TEAN and 292 J/g (14.8 kcal/mol) for 80% TEAN, with the balance assumed by the present author to be water of hydration of this hygroscopic material. As mentioned in Section 2, reasonable efforts were made to keep the TEAN dry, but no analysis was made. The measured values of 20.7 kcal/mol and 17.0 kcal/mol are strongly suggestive that, at least with oxygen, and possibly with nitrous oxide, we are measuring the melting kinetics and that the ignition reactions take place very rapidly after melting. If one concludes that the melting is the rate limiting step of this reaction, then the variability of these measured numbers may well be due to variations in the water content of samples used.

A second possibly important observation is that the oxygen consumes the sample completely whereas the nitrous oxide leaves many of the larger sized particles unaffected on the end and side walls of the shock tube. If both were rate limited by the melting of the sample, one might reasonably expect similar consumption of the sample in both cases. Thus, the difference in activation energy may in fact be real

and suggests that the nitrous oxide does not react as rapidly with the liquid TEAN as does oxygen. This might be significant in that in the liquid propellant combustion, the TEAN never exists as an isolated solid, since it is above its melting point before significant reaction takes place.

6. CONCLUSION

Measurements have been made of the activation energy for the reaction of TEAN with oxygen and nitrous oxide in argon. The magnitude of the numbers measured and other observations suggest that oxygen reacts rapidly with the TEAN after melting, while the nitrous oxide reaction may have a rate limiting step other than simple melting.




Figure 1. Schematic Diagram of the Test End of the Shock Tube.






Figure 2. Eight Consecutive Line Images at 50- μ s Intervals From the End of the Shock Tube During Ignition of TEAN in $N_2/O_2/Ar$.



a. 1,665 K



b. 2,390 K

Figure 3. Signal From PbSe Infrared Detector at 4.49 μm (N₂O Emission) During Passage of Shocks for Calculated Reflected Shock Temperatures.




Figure 4. Light Signals Detected at 389 nm for TEAN Heated in N₂O/Ar and Pure Ar.




Figure 5. Light Detected at 389 nm for TEAN Heated in O₂/Ar.




Figure 6. Arrhenius Plot of Ignition Delay vs. Inverse Temperature for TEAN Heated in N_2O/Ar .




Figure 7. Arrhenius Plot of Ignition Delay vs. Inverse Temperature for TEAN in O_2/Ar .

INTENTIONALLY LEFT BLANK.

7. REFERENCES

- Beyer, R. A. "Shock Tube Studies of the Ignition of Triethanol Ammonium Nitrate in Nitrous Oxide: Preliminary Results." BRL-TR-3120, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 1990.
- Decker, M. M., N. Klein, E. Friedman, C. Leveritt, and J. Wojciechowski. "HAN-Based Liquid Gun Propellants: Physical Properties." BRL-TR-2864, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, 1987.
- Gordon, S., and B. J. McBride. "A Computer Program for Computation of Complex Chemical Equilibrium Composition," NASA SP-273, 1971.
- Skahan, P. B. "Liquid Propellant Engineering Data Package: Final Report." A compendium of unpublished measurements made under contract at NOS and NSWC, Indian Head, MD, provided by J. Wojciechowski of BRL, numbers quoted extracted from Figures 39 and 41, 1987.

INTENTIONALLY LEFT BLANK.

No. of
Copies Organization

2 Administrator
Defense Technical Info Center
ATTN: DTIC-DDA
Cameron Station
Alexandria, VA 22304-6145

1 Commander
U.S. Army Materiel Command
ATTN: AMCAM
5001 Eisenhower Ave.
Alexandria, VA 22333-0001

1 Commander
U.S. Army Laboratory Command
ATTN: AMSLC-DL
2800 Powder Mill Rd.
Adelphi, MD 20783-1145

2 Commander
U.S. Army Armament Research,
Development, and Engineering Center
ATTN: SMCAR-IMI-I
Picatinny Arsenal, NJ 07806-5000

2 Commander
U.S. Army Armament Research,
Development, and Engineering Center
ATTN: SMCAR-TDC
Picatinny Arsenal, NJ 07806-5000

1 Director
Benet Weapons Laboratory
U.S. Army Armament Research,
Development, and Engineering Center
ATTN: SMCAR-CCB-TL
Watervliet, NY 12189-4050

(Unclass. only)1 Commander
U.S. Army Armament, Munitions,
and Chemical Command
ATTN: AMSMC-IMF-L
Rock Island, IL 61299-5000

1 Director
U.S. Army Aviation Research
and Technology Activity
ATTN: SAVRT-R (Library)
M/S 219-3
Ames Research Center
Moffett Field, CA 94035-1000

1 Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-CS-R (DOC)
Redstone Arsenal, AL 35898-5010

No. of
Copies Organization

1 Commander
U.S. Army Tank-Automotive Command
ATTN: ASQNC-TAC-DIT (Technical
Information Center)
Warren, MI 48397-5000

1 Director
U.S. Army TRADOC Analysis Command
ATTN: ATRC-WSR
White Sands Missile Range, NM 88002-5502

1 Commandant
U.S. Army Field Artillery School
ATTN: ATSF-CSI
Ft. Sill, OK 73503-5000

2 Commandant
U.S. Army Infantry School
ATTN: ATZB-SC, System Safety
Fort Benning, GA 31903-5000

(Class. only)1 Commandant
U.S. Army Infantry School
ATTN: ATSH-CD (Security Mgr.)
Fort Benning, GA 31905-5660

(Unclass. only)1 Commandant
U.S. Army Infantry School
ATTN: ATSH-CD-CSO-OR
Fort Benning, GA 31905-5660

1 WL/MNME
Eglin AFB, FL 32542-5000

Aberdeen Proving Ground

2 Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen

1 Cdr, USATECOM
ATTN: AMSTE-TC

3 Cdr, CRDEC, AMCCOM
ATTN: SMCCR-RSP-A
SMCCR-MU
SMCCR-MSI

1 Dir, VLAMO
ATTN: AMSLC-VL-D

10 Dir, USABRL
ATTN: SLCBR-DD-T

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	HQDA (SARD-TC, C.H. Church) WASH DC 20310-0103	2	Commander Naval Surface Warfare Center ATTN: R. Bernecker, R-13 G.B. Wilmot, R-16 Silver Spring, MD 20903-5000
4	Commander US Army Research Office ATTN: R. Ghirardelli D. Mann R. Singleton R. Shaw P.O. Box 12211 Research Triangle Park, NC 27709-2211	5	Commander Naval Research Laboratory ATTN: M.C. Lin J. McDonald E. Oran J. Shnur R.J. Doyle, Code 6110 Washington, DC 20375
2	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-B, D.S. Downs SMCAR-AEE, J.A. Lannon Picatinny Arsenal, NJ 07806-5000	1	Commanding Officer Naval Underwater Systems Center Weapons Dept. ATTN: R.S. Lazar/Code 36301 Newport, RI 02840
1	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-BR, L. Harris Picatinny Arsenal, NJ 07806-5000	2	Commander Naval Weapons Center ATTN: T. Boggs, Code 388 T. Parr, Code 3895 China Lake, CA 93555-6001
2	Commander US Army Missile Command ATTN: AMSMI-RD-PR-E, A.R. Maykut AMSMI-RD-PR-P, R. Betts Redstone Arsenal, AL 35898-5249	1	Superintendent Naval Postgraduate School Dept. of Aeronautics ATTN: D.W. Netzer Monterey, CA 93940
1	Office of Naval Research Department of the Navy ATTN: R.S. Miller, Code 432 800 N. Quincy Street Arlington, VA 22217	3	AL/LSCF ATTN: R. Corley R. Geisler J. Levine Edwards AFB, CA 93523-5000
1	Commander Naval Air Systems Command ATTN: J. Ramnarace, AIR-54111C Washington, DC 20360	1	AFOSR ATTN: J.M. Tishkoff Bolling Air Force Base Washington, DC 20332
1	Commander Naval Surface Warfare Center ATTN: J.L. East, Jr., G-23 Dahlgren, VA 22448-5000	1	OSD/SDIO/IST ATTN: L. Caveny Pentagon Washington, DC 20301-7100

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commandant USAFAS ATTN: ATSF-TSM-CN Fort Sill, OK 73503-5600	1	AVCO Everett Research Laboratory Division ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149
1	F.J. Seiler ATTN: S.A. Shackelford USAF Academy, CO 80840-6528	1	Battelle ATTN: TACTEC Library, J. Huggins 505 King Avenue Columbus, OH 43201-2693
1	University of Dayton Research Institute ATTN: D. Campbell AL/PAP Edwards AFB, CA 93523	1	Cohen Professional Services ATTN: N.S. Cohen 141 Channing Street Redlands, CA 92373
1	NASA Langley Research Center Langley Station ATTN: G.B. Northam/MS 168 Hampton, VA 23365	1	Exxon Research & Eng. Co. ATTN: A. Dean Route 22E Annandale, NJ 08801
4	National Bureau of Standards ATTN: J. Hastie M. Jacox T. Kashiwagi H. Semerjian US Department of Commerce Washington, DC 20234	1	General Applied Science Laboratories, Inc. 77 Raynor Avenue Ronkonkoma, NY 11779-6649
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, GA 95813	1	General Electric Ordnance Systems ATTN: J. Mandzy 100 Plastics Avenue Pittsfield, MA 01203
1	Applied Combustion Technology, Inc. ATTN: A.M. Varney P.O. Box 607885 Orlando, FL 32860	1	General Motors Rsch Labs Physical Chemistry Department ATTN: T. Sloane Warren, MI 48090-9055
2	Applied Mechanics Reviews The American Society of Mechanical Engineers ATTN: R.E. White A.B. Wenzel 345 E. 47th Street New York, NY 10017	2	Hercules, Inc. Allegheny Ballistics Lab. ATTN: W.B. Walkup E.A. Yount P.O. Box 210 Rocket Center, WV 26726
1	Atlantic Research Corp. ATTN: R.H.W. Waesche 7511 Wellington Road Gainesville, VA 22065	1	Alliant Techsystems, Inc. Marine Systems Group ATTN: D.E. Broden/ MS MN50-2000 600 2nd Street NE Hopkins, MN 55343

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Alliant Techsystems, Inc. ATTN: R.E. Tompkins MN38-3300 5700 Smetana Drive Minnetonka, MN 55343	2	Princeton Combustion Research Laboratories, Inc. ATTN: M. Summerfield N.A. Messina 475 US Highway One Monmouth Junction, NJ 08852
1	IBM Corporation ATTN: A.C. Tam Research Division 5600 Cottle Road San Jose, CA 95193	1	Hughes Aircraft Company ATTN: T.E. Ward 8433 Fallbrook Avenue Canoga Park, CA 91303
1	IIT Research Institute ATTN: R.F. Remaly 10 West 35th Street Chicago, IL 60616	1	Rockwell International Corp. Rocketdyne Division ATTN: J.E. Flanagan/HB02 6633 Canoga Avenue Canoga Park, CA 91304
2	Director Lawrence Livermore National Laboratory ATTN: C. Westbrook M. Costantino P.O. Box 808 Livermore, CA 94550	4	Director Sandia National Laboratories Division 8354 ATTN: R. Cattolica S. Johnston P. Mattern D. Stephenson Livermore, CA 94550
1	Lockheed Missiles & Space Co. ATTN: George Lo 3251 Hanover Street Dept. 52-35/B204/2 Palo Alto, CA 94304	1	Science Applications, Inc. ATTN: R.B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364
1	Director Los Alamos National Lab ATTN: B. Nichols, T7, MS-B284 P.O. Box 1663 Los Alamos, NM 87545	3	SRI International ATTN: G. Smith D. Crosley D. Golden 333 Ravenswood Avenue Menlo Park, CA 94025
1	National Science Foundation ATTN: A.B. Harvey Washington, DC 20550	1	Stevens Institute of Tech. Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030
1	Olin Ordnance ATTN: V. McDonald, Library P.O. Box 222 St. Marks, FL 32355-0222	1	Sverdrup Technology, Inc. LERC Group ATTN: R.J. Locke, MS SVR-2 2001 Aerospace Parkway Brook Park, OH 44142
1	Paul Gough Associates, Inc. ATTN: P.S. Gough 1048 South Street Portsmouth, NH 03801-5423		

<u>No. of Copies</u>	<u>Organization</u>
1	Sverdrup Technology, Inc. ATTN: J. Deur 2001 Aerospace Parkway Brook Park, OH 44142
1	Thiokol Corporation Elkton Division ATTN: S.F. Palopoli P.O. Box 241 Elkton, MD 21921
3	Thiokol Corporation Wasatch Division ATTN: S.J. Bennett P.O. Box 524 Brigham City, UT 84302
1	United Technologies Research Center ATTN: A.C. Eckbreth East Hartford, CT 06108
3	United Technologies Corp. Chemical Systems Division ATTN: R.S. Brown T.D. Myers (2 copies) P.O. Box 49028 San Jose, CA 95161-9028
1	Universal Propulsion Company ATTN: H. J. McSpadden 25401 North Central Ave. Phoenix, AZ 85027-7837
1	Veritay Technology, Inc. ATTN: E.B. Fisher 4845 Millersport Highway P.O. Box 305 East Amherst, NY 14051-0305
1	Brigham Young University Dept. of Chemical Engineering ATTN: M.W. Beckstead Provo, UT 84058
1	California Institute of Tech. Jet Propulsion Laboratory ATTN: L. Strand/MS 512/102 4800 Oak Grove Drive Pasadena, CA 91109

<u>No. of Copies</u>	<u>Organization</u>
1	California Institute of Technology ATTN: F.E.C. Culick/ MC 301-46 204 Karman Lab. Pasadena, CA 91125
1	University of California Los Alamos Scientific Lab. P.O. Box 1663, Mail Stop B216 Los Alamos, NM 87545
1	University of California, Berkeley Chemistry Department ATTN: C. Bradley Moore 211 Lewis Hall Berkeley, CA 94720
1	University of California, San Diego ATTN: F.A. Williams AMES, B010 La Jolla, CA 92093
2	University of California, Santa Barbara Quantum Institute ATTN: K. Schofield M. Steinberg Santa Barbara, CA 93106
1	University of Colorado at Boulder Engineering Center ATTN: J. Daily Campus Box 427 Boulder, CO 80309-0427
2	University of Southern California Dept. of Chemistry ATTN: S. Benson C. Wittig Los Angeles, CA 90007
1	Cornell University Department of Chemistry ATTN: T.A. Cool Baker Laboratory Ithaca, NY 14853

<u>No. of Copies</u>	<u>Organization</u>
1	University of Delaware ATTN: T. Brill Chemistry Department Newark, DE 19711
1	University of Florida Dept. of Chemistry ATTN: J. Winefordner Gainesville, FL 32611
3	Georgia Institute of Technology School of Aerospace Engineering ATTN: E. Price W.C. Strickland B.T. Zinn Atlanta, GA 30332
1	University of Illinois Dept. of Mech. Eng. ATTN: H. Krier 144MEB, 1206 W. Green St. Urbana, IL 61801
1	Johns Hopkins University/APL Chemical Propulsion Information Agency ATTN: T.W. Christian Johns Hopkins Road Laurel, MD 20707
1	University of Michigan Gas Dynamics Lab Aerospace Engineering Bldg. ATTN: G.M. Faeth Ann Arbor, MI 48109-2140
1	University of Minnesota Dept. of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455
3	Pennsylvania State University Applied Research Laboratory ATTN: K.K. Kuo H. Palmer M. Micci University Park, PA 16802

<u>No. of Copies</u>	<u>Organization</u>
1	Pennsylvania State University Dept. of Mechanical Engineering ATTN: V. Yang University Park, PA 16802
1	Polytechnic Institute of NY Graduate Center ATTN: S. Lederman Route 110 Farmingdale, NY 11735
2	Princeton University Forrestal Campus Library ATTN: K. Brezinsky I. Glassman P.O. Box 710 Princeton, NJ 08540
1	Purdue University School of Aeronautics and Astronautics ATTN: J.R. Osborn Grissom Hall West Lafayette, IN 47906
1	Purdue University Department of Chemistry ATTN: E. Grant West Lafayette, IN 47906
2	Purdue University School of Mechanical Engineering ATTN: N.M. Laurendeau S.N.B. Murthy TSPC Chaffee Hall West Lafayette, IN 47906
1	Rensselaer Polytechnic Inst. Dept. of Chemical Engineering ATTN: A. Fortijn Troy, NY 12181
1	Stanford University Dept. of Mechanical Engineering ATTN: R. Hanson Stanford, CA 94305

No. of
Copies Organization

- 1 University of Texas
 Dept. of Chemistry
 ATTN: W. Gardiner
 Austin, TX 78712

- 1 University of Utah
 Dept. of Chemical Engineering
 ATTN: G. Flandro
 Salt Lake City, UT 84112

- 1 Virginia Polytechnic
 Institute and
 State University
 ATTN: J.A. Schetz
 Blacksburg, VA 24061

- 1 Freedman Associates
 ATTN: E. Freedman
 2411 Diana Road
 Baltimore, MD 21209-1525

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers below will aid us in our efforts.

1. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

2. How, specifically, is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

3. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate.

4. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

BRL Report Number BRL-TR-3329 Division Symbol

Check here if desire to be removed from distribution list. _____

Check here for address change. _____

Current address: Organization _____
 Address _____

DEPARTMENT OF THE ARMY
Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066

OFFICIAL BUSINESS**BUSINESS REPLY MAIL**

FIRST CLASS PERMIT No 0001, APG, MD

Postage will be paid by addressee.

**Director
U.S. Army Ballistic Research Laboratory
ATTN: SLCBR-DD-T
Aberdeen Proving Ground, MD 21005-5066**

**NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES**