

AD-A251 027



②

TECHNICAL REPORT BRL-TR-3344

BRLHYPERVELOCITY FIRINGS FROM
A 7-INCH HARP GUNJOSEPH W. COLBURN
CARL R. RUTH
FREDERICK W. ROBBINS
ALBERT W. HORSTDTIC
ELECTE
MAY 29 1992
S B D


MAY 1992

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

92-14122



NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY <i>(Leave blank)</i>	2. REPORT DATE May 1992	3. REPORT TYPE AND DATES COVERED Final Aug 90 - Sep 91		
4. TITLE AND SUBTITLE Hypervelocity Firings From A 7-Inch HARP Gun		5. FUNDING NUMBERS PR: 11.162618AH80		
6. AUTHOR(S) Joseph W. Colburn, Carl R. Ruth, Frederick W. Robbins and Albert W. Horst				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) USA Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066		10. SPONSORING/MONITORING AGENCY REPORT NUMBER BRL-TR-3344		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for Public Release - Distribution is Unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT <i>(Maximum 200 words)</i> Numerous approaches are being pursued to launch projectiles of various types to hypervelocities. While much recent activity has focused on the development of electric guns, research is also being conducted employing conventional chemical propulsion, both to provide a detailed understanding of the hydrodynamics of conventional hypervelocity launchers and to provide baseline data against which the various emerging propulsion concepts can be evaluated. Over the past several years, firings were conducted at the Ballistic Research Laboratory using long 120-mm gun tubes to provide velocities in the 2.5-2.7 km/s range. This report documents more recent, limited firings using a 7-inch HARP gun, launching 5-kg projectiles to a velocity exceeding 2.8 km/s. Simulations of these firings were made using the XNOVAKTC (XKTC) interior ballistic code, and a comparison of theoretical and experimental data is provided.				
14. SUBJECT TERMS Interior Ballistics, Modeling, Hypervelocity, Hypervelocity Guns			15. NUMBER OF PAGES 40	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

	Page
LIST OF FIGURES.....	v
ACKNOWLEDGMENTS.....	vii
1. INTRODUCTION.....	1
2. EXPERIMENTAL.....	1
2.1 Gun Hardware.....	1
2.2 Instrumentation.....	2
2.3 Propelling Charge.....	2
2.4 Projectiles.....	3
3. GUN FIRINGS.....	4
3.1 Round One.....	4
3.2 Round Two.....	5
3.3 Comparison.....	7
3.4 Instrumentation Performance.....	7
3.4.1 Pressure.....	7
3.4.2 Interferometer.....	7
3.4.3 Cameras.....	8
4. MODELING.....	8
4.1 Background.....	8
4.2 Round One.....	9
4.3 Round Two.....	11
5. CONCLUSIONS.....	12
6. REFERENCES.....	12
APPENDIX: Input for XKTC Simulation of 7-Inch HARP Gun Firings....	13
DISTRIBUTION LIST.....	21



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	Seven-Inch HARP Gun at BRL's Range 18.....	2
2.	Seven-Inch HARP Gun Diagram (SN 1098).....	2
3.	Charge Components & Diagram.....	3
4.	Projectile for Round One (4.987 kg).....	4
5.	Projectile for Round Two (4.988 kg).....	4
6.	Round One, Experimental Pressure Data.....	5
7.	Round Two, Experimental Pressure Data.....	6
8.	Round Two, Velocity Waterfall Plot.....	6
9.	Round One, Calculated Pressure Data.....	9
10.	Round One, Calculated Base Pressure Data.....	10
11.	Round Two, Calculated Pressure Data.....	11

INTENTIONALLY LEFT BLANK

ACKNOWLEDGMENTS

The authors would like to thank Mr. James Bowen, Mr. John "Davey" Hewitt, Mr. Dennis Meier, and Mr. James Tuerk of BRL's Range 18 for their outstanding efforts in performing the firings discussed in this report. The authors would also like to thank Mr. Fred Brandon, and Mr. Todd Rosenberger for their assistance in preparing this report.

INTENTIONALLY LEFT BLANK

1. INTRODUCTION

The quest to achieve higher projectile velocities is currently of worldwide interest among the ballistics community. While terminal ballisticians debate the relative merits of velocity and mass on target, the interior ballisticians continue to pursue both conventional and novel approaches to providing launch velocities of 2.5 km/s and greater. A considerable investment is being made to develop practical electric guns, including electrothermal-chemical and electromagnetic launchers of various types. Large light gas guns and even inbore ramjet propulsion are being considered for providing very high launch velocities. However, conventional chemical propulsion appears to offer a limited but certainly achievable capability in this area. Current efforts at the Ballistic Research Laboratory include a modest study of solid propellant hypervelocity guns, aimed at providing a detailed understanding of the hydrodynamics of this environment as well as baseline data on the performance available from a conventional approach. Such a launcher may or may not offer a practical capability for tactical or strategic applications, but may indeed offer a readily available laboratory device for facilitating large-scale terminal ballistics studies at very high velocities, as well as serving as a basis of comparison to measure the progress of the more novel propulsion approaches.

The most direct methods for increasing projectile velocity in a solid propellant gun are to decrease the projectile mass, increase the length of the weapon, increase the maximum chamber pressure, and increase the energy in the propulsion charge. Any or all of these techniques may be used to produce a hypervelocity launch system. In parallel to the quest for higher velocities is the development of techniques to accurately model the performance of these guns. Most modern interior ballistic computer codes perform very well through the inventory of fielded ammunition, but when the ratio of the propulsion charge mass to the projectile mass (Charge to Mass ratio or C/M) exceeds one (1) (the value approached by most modern kinetic energy ammunition), the mechanism for transfer of energy from the burning propellant to the base of the projectile ceases to be as simple as assumed by most codes (Robbins 1986).

2. EXPERIMENTAL

2.1 Gun Hardware. At BRL, seven-inch smoothbore gun systems originally modified for use in the High Altitude Research Program (HARP) are frequently used to accelerate large masses to current ordnance velocities, or light masses to the hypervelocity regime (Bull and Murphy 1988; Evans 1966; Boyer and MacAllister 1966). These guns feature projectile travels of up to 15.25 m (600 in), maximum chamber pressures of 483 MPa (70 kpsi) and chamber volumes of 0.037 m³




Figure 1. Seven-Inch HARP Gun at BRL's Range 18.

(2271 in³) or more. For our tests a gun of this type was mounted in a M174 recoil on a M1 towed howitzer mount. The tube was supported just forward of the joint by a rigid mount equipped with rollers (see Figures 1 and 2). This prevented excessive tube droop and restricted tube whip during the gun firing without interfering with the recoil cycle. New inspection criteria for this series of gun condemned this tube (SN 1098) and breech soon after these experimental firings were completed.




Figure 2. Seven-Inch HARP Gun Diagram (SN 1098).

2.2 Instrumentation The gun was instrumented with ten (10) piezoelectric pressure transducers (Kistler Model 6211) at nine (9) different axial locations along the tube. Transducer locations are identified in Figure 2. The transducer mounting holes were machined directly into the tube wall. Two microwave interferometers (15 GHz & 10.525 GHz) were utilized to record the motion of the projectile while in the gun tube. Two 35-mm smear cameras were used to record projectile velocity and integrity after muzzle exit. High speed film cameras and standard video cameras were utilized to record various portions of each firing.

2.3 Propelling Charge The high ratio of chamber length to chamber diameter in this gun system made the design of the ignition system critical to safe operation. Previous firings of this weapon at C/M's of up to one (1) utilized an artillery type black powder and nitrocellulose "snake" running up the center of the charge to transmit the ignition pulse to the propellant bed uniformly. Experience with 120-mm hypervelocity gun systems indicated that it would be simpler and safer to




Figure 3. Charge Components & Diagram.

utilize partially cut stick propellant technology (Ruth and Horst 1991; Ruth, Robbins, and Horst 1991). The multiperforated propellant sticks have nearly the same progressivity as multi-perforated granular propellants, but since the sticks present natural flow channels to the igniter gasses, it is safe to ignite this very long charge with just a breech mounted ignition system. The charge configuration for round one is shown in Figure 3. It consisted of an M52 electric igniter, an M82 percussion primer, a 209 g (0.461 lb) class 1 black powder basepad, and 31.8 kg (70.1 lb) of JA2 stick propellant. Round two utilized 30.4 kg (67.0 lb) of the JA2 stick propellant. The JA2 was divided up into three bundles. Details of the charge configurations are presented in Table 1. XNOVAKTC, an interior ballistic computer code described later in the paper, was utilized to determine which of the lots of JA2 stick propellant on hand would yield the highest muzzle velocity with a maximum pressure of 448MPa (65 kpsi).

Table 1. Charge Component Data.

ROUND NUMBER	PROPELLANT TYPE	MASS OF BUNDLE 1	MASS OF BUNDLE 2	MASS OF BUNDLE 3	TOTAL CHARGE MASS	BASE PAD MASS
1	JA2. 19 perf, partially-cut cylindrical stick	12.864 kg	12.873 kg	6.061 kg	31.798 kg	209 g
2		14.462 kg	14.378 kg	1.584 kg	30.424 kg	

2.4 Projectiles Figure 4 shows a diagram of the 4.987 kg (10.994 lb) slug projectile utilized for the first firing. Polypropolux, a high strength, low cost plastic, was chosen as the base material for this projectile because of successful test firings in a 120-mm hypervelocity system. Since the measurement of projectile velocity was a critical part of the program, the projectile had to have a material capable of reflecting microwave energy on its front face. This requirement was satisfied with a 0.003175 m (0.125 in) thick aluminum plate attached to the front of the projectile. This projectile survived launch, but analysis of radar data led us to believe that obturation was lost early in the firing.




Figure 4. Projectile for Round One, 4.987 kg.





Figure 5. Projectile for Round Two, 4.988 kg.

Figure 5 is a diagram of the 4.988 kg (10.996 lb) projectile design used for the second round. The forward and rear diameters are the same as the round one projectile, but the interference fit section at the rear of the projectile presents a larger obturating surface. The rear face of the projectile was reinforced with a .00635 m (0.25 in) thick aluminum plate to provide greater protection from the propelling gasses. To maintain the same projectile mass and allow for the much wider obturator band and the additional aluminum plate, the length of the projectile was reduced. Other changes resulting from the change in projectile design are highlighted in the description of the gun firings.

3. GUN FIRINGS

3.1 Round One To maintain similitude with previously completed computer simulations, the projectile needed to be seated 1.473 m (58.0 in) from the rear face of the tube (1.397 m (55.0 in) from the forward face of the spindle). The projectile was inserted into the chamber by hand then forced into position using a hydraulic jack. Since this system did not allow precise control of the projectile motion, the projectile was finally seated at a position 1.492 m (58.75 in) from the rear face of the tube. The calculations presented in this paper were performed after the firings and reflect the true experimental seating distance. Table 2 summarizes the gun parameters for both rounds. Before loading the propulsion charge the chamber was swabbed with Keivan, a water based jelling agent traditionally used as a thickener in the food industry, which was intended to provide a cooling layer to reduce chamber erosion due to the hot burning JA2 propellant. Figure 6 shows the pressure time histories for round one.

Table 2. Gun Firing & Simulation Data.									
ROUND NUMBER	CHARGE MASS (kg)	PROJECTILE MASS (kg)	C/M	CHAMBER VOLUME (m ³)	P1 (MAX) (MPa)	P2 (MAX) (MPa)	P3 (MAX) (MPa)	P4 (MAX) (MPa)	MUZZLE VELOCITY (m/s)
1	31.798	4.987	6.38	0.04962	428	362	306	297	---
1-XKTC	31.798	4.987	6.38	0.04962	418	376	324	320	2815
2	30.424	4.988	6.1	0.04382	432	365	316	---	2818
2-XKTC	30.424	4.988	6.1	0.04382	413	---	304	---	2880



3.2 Round Two An increase in the force required to seat the projectile, due to the projectile design changes made prior to round two, limited the seating distance to 1.295 m (51 in). This significantly decreased the chamber volume and required a reduction in the propulsion charge mass. Before the propulsion charge was loaded for round two the gun tube was purged with helium and sealed with a plastic diaphragm. It was hoped that this procedure would have two positive effects. The first was to reduce the resistive force encountered by the projectile by decreasing the density of the gas in the tube. Interior ballistic simulations show that a helium filled tube yields a significant increase in muzzle velocity. The greatest benefit would have been gained by evacuating the tube, but the difference between helium and vacuum is not that large, and the experimental




Figure 7. Round 2, Experimental Pressure Data.




Figure 8. Round 2, Velocity Waterfall Plot.

technique for evacuating the tube is much more cumbersome than a simple gas purge. The other benefit of the helium purge was to eliminate any reactive gasses from in front of the projectile. Then if obturation failed, the fuel rich gasses would not encounter an oxidizer rich atmosphere. This technique reduces the effect of blow-by on inbore radar signals. Figure 7 shows the pressure time history for round two and Figure 8 shows the waterfall plot (velocity spectrum at discrete time steps described in the interferometry section).

3.3 Comparison Even though there were slight differences in charge mass and chamber volume (as detailed in Tables 1 and 2), the peak chamber pressures were virtually identical for both rounds. Despite the length of the charge and the simple base ignition system, pressure wave levels were minimal throughout the interior ballistic cycle. This is credited to the low axial gas flow resistance of the stick charge.

3.4 Instrumentation Performance

3.4.1 Pressure. All of the pressure transducers in the gun chamber appeared to perform well during the first firing. The downbore gages (beyond P4) only worked for a short time. This was believed to be caused by a flexural resonance phenomenon which causes high frequency, high amplitude radial strain waves in relatively thin tube walls during the passage of a hypervelocity projectile (Simkins 1987). Efforts are currently underway to attempt to isolate the transducers from this effect. During the second firing most of the chamber transducers functioned properly, but the performance of downbore gages was marginal at best. It should be noted that P3 was exposed to the initial chamber pressurization for round one; however, because of changes in the projectile for the second round, the projectile was not seated as far into the gun, and covered P3 until after the projectile moved 0.05 m (1.97 in).

3.4.2 Interferometry. On the first round the inbore 15 GHz radar signal attenuated after just a few centimeters of projectile travel. The 10.525 GHz radar, used in the downrange mode during the first round, failed to track any signal due to masking by the enormous cloud of ionized gas which followed the projectile out of the muzzle. On the second round the 15 GHz signal once again disappeared soon after the onset of projectile motion. For this round the 10.525 GHz radar was used in the inbore mode, and transmitted signal throughout the interior ballistic cycle. Figure 8 was generated by performing Fast Fourier Transforms (FFT's) on the raw interferometer data at one-millisecond intervals. No attempt was made to generate a velocity-time history from the interferometer data.

3.4.3 Cameras. All framing, video and smear cameras performed well during these firings.

4. MODELING

4.1 Background. Previous efforts to model large-caliber hypervelocity firings in a 120-mm gun (Ruth and Horst 1991; Ruth, Robbins, and Horst 1991) underscored the necessity of employing a two-phase flow interior ballistic code to simulate the hydrodynamics (particularly the pressure gradient) associated with the very high charge-to-mass ratios employed. Lumped-parameter codes continue to be useful, even at hypervelocities, for defining overall performance potential for a given gun envelope; however, limitations in the physics of the codes (again, primarily the simplified pressure gradient) typically require compromises in the input data to provide a match to observed peak pressures and velocities, leading to significant disparities in details of the inbore trajectory between theory and experiment.


In an attempt to model the 7-inch HARP firings conducted in this study, calculations were performed using the XKTC interior ballistic code (Gough 1990). XKTC is then latest version in a successful series of improvements to the NOVA code (Gough 1980), embodying the features of codes known as XNOVA (more efficient computational techniques), NOVATC (traveling charge option), XNOVAK (finite rate chemistry), and XNOVAT (numerous features for tank ammunition, including case combustion and projectile afterbody intrusion).


The basis for the NOVA family is a one-dimensional (with area change), two-phase, unsteady flow representation of the interior ballistic cycle. The balance equations describe the evolution of macroscopic flow properties accompanying changes in mass, momentum, and energy arising out of interactions associated with combustion, interphase drag, and heat transfer. The state variables are to be thought of as averages of local microproperties, with intractable details of the microflow related to the macroscopic variables by means of empirical correlations. Functioning of the igniter is specified as a predetermined mass injection rate as a function of space and time. Flamespread then follows from axial convection, with the propellant responding as an inert material until a surface temperature ignition criterion is met; regression then ensues based on a conventional aP^n burning rate law, unless the finite rate chemistry option is invoked (not used in this study). The governing equations are solved by the method of finite differences with an explicit allowance for discontinuities in the state variables at internal boundaries defined by the ends of the propellant increments.

4.2 Round One. Prior to the actual firings, a nominal XKTC input data base (see Appendix) was assembled based on the physical dimensions and properties of the system components, an assumed projectile seating distance, and other data (e.g., propellant burning rate, bore resistance profile) developed for and modified from previous hypervelocity firings (Robbins, Ruth, and Horst, not yet published). Simulations were performed using these data to identify the best available propellant lot and to estimate a charge weight that would provide maximum performance at a peak chamber pressure at about 414 MPa (60 kpsi), a recommended safe limit for our tube.

After the first firing, the data base was altered to reflect actual component masses and loading data (e.g., projectile seating distance). The first simulation performed using these data provided an adequate match to overall performance data (e.g., peak chamber pressure) but a somewhat disappointing representation of details of the pressure-time curves as well as the times at which the projectile passed the downbore pressure gages.

One of the essential features of a multiphase flow interior ballistic code is treatment of interactions between the solid and gas phases, such as the interphase drag. This drag force is usually calculated in such codes by reference to empirically based correlations for fixed and fluidized beds of particles of approximately the correct shape at appropriate Reynolds numbers. For the






partially cut stick propellant employed in the subject firings, while it is clear that the propellant initially offers the geometric characteristics of a bundle of stick propellant and later transforms to a (largely fluidized) bed of what is essentially granular propellant, the timing of this event is unknown. The XKTC code makes the assumption that this transformation begins to occur when motion of the projectile has provided sufficient additional chamber volume for the separated propellant pieces to rotate. Owing to the limitations and uncertainties of this assumption, additional simulations were performed varying the time period over which this transition occurs.

The final parameters selected (also listed in the Appendix) resulted in the pressure-time curves shown in Figure 9, providing a good match to the shape of the experimental curves and the times at which the projectile passed the first three downbore pressure gages, with the predicted pressure within 10 MPa of the measured value. No verification of the predicted muzzle velocity was possible as this measurement failed.

Figure 10 displays a simulated projectile base pressure-time curve, along with values for the maximum pressures recorded by the first three downbore gages. We note that while good agreement is seen for the first two locations, the measured value for the third falls far below the simulated base pressure at that position. Given the damage to downbore gages beyond the third

position (possibly from tube flexural resonance), data recorded at this third position was also considered suspect. A quick check on the plausibility of these data was performed by constructing a simple model of the base pressure curve based on the early portion of the calculated curve "spliced" to experimental data from all three downbore gages. A comparison of predicted velocities based on this crude model and the XKTC simulation itself (which provided a good fit to the experimental pressures measured at the first two downbore gages but not the third) revealed a difference of some 600 m/s, the profile including the data from the third downbore gage predicting a velocity a velocity of 2479 m/s, far below both theory and experiment as presented in Table 2. It was thus concluded that the experimental pressure measured by the third downbore gage should be discounted.

4.3 Round Two. As mentioned in an earlier section of this report, changes were introduced in the configuration of the projectile for the second firing, and an XKTC calculation was performed reflecting these changes to select a charge mass for the test. The input data are again recorded in the Appendix, and the pressure-time curves resulting from the simulation are presented in Figure 11. The simulation, however, assumed pure helium in the tube ahead of the projectile, a situation that was not likely at the time of the firing, and did not fully account for the influence of the change in projectile configuration on the bore resistance. These factors likely account for some disparity



between the prediction and the measured values (which this time includes a successful measurement of the projectile velocity), as presented in Table 2. Further, the quality of virtually all recorded downbore pressure curves precluded their use as anything but event markers in evaluating the accuracy of the simulation.

5. CONCLUSIONS

Significant masses can be propelled to velocities in excess of 2.5 km/s utilizing a conventional mode of solid propulsion. While the high charge to mass ratio leads to significant pressure gradients ultimately limiting achievable velocities (Heiser 1980), firings conducted under this program verify the practicality of such launchers for use in laboratory applications and perhaps even suggest the potential for certain weapon applications as well. Further, the XKTC multiphase flow interior ballistic code appears to offer a useful capability for charge design for such launchers.

6. REFERENCES

- Boyer, E.D. and L.C. MacAllister. "Seven-Inch HARP Gun-Launched Vertical Probe System: Initial Development." BRL-MR-1770, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1966.
- Bull, G.V. and C.H. Murphy Jr.. Paris Kanonen - the Paris Guns (Wilhelmsgeschütze) and Project HARP. Herford, U.K., Mittler, 1988.
- Evans, J.W. "Development of Gun Probe Payloads and a 1750 MC/S Telemetry System." BRL-MR-1749, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, May 1966.
- Gough, P.S. "The NOVA Code: A User's Manual. Volume I. Description and Use." IHCR 80-8, Naval Ordnance Station, Indian Head, MD, December 1980.
- Gough, P.S. "The XNOVAKTC Code." BRL-CR-627, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, February 1990.
- Heiser, R. "Gasdynamic Limits of Maximum Attainable Muzzle Velocities for Conventional Guns." The Proceedings of the Fifth International Ballistics Symposium, April 1980.
- Robbins, F.W. "Studies Supporting Development of a Modified Gradient Equation for Lumped Parameter Interior Ballistic Codes." Proceedings of the 23rd JANNAF Combustion Meeting, CPIA Publication 457, vol. II, pp. 165-175, October 1986.
- Ruth, C.R. and A.W. Horst Jr.. "Detailed Characterization of Hypervelocity Firings in a Long 120-mm Gun." BRL-TR-3190, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, March 1991.
- Ruth, C.R., F.W. Robbins, and A.W. Horst Jr.. "Experimental Hypervelocity Firings Using Stick and Granular Propellant Configurations." BRL-MR-3921, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1991.
- Simkins, T.E. "Resonance of Flexural Waves in Gun Tubes." ARDEC Technical Report ARCCB-TR-87008, Benet Weapons Laboratory, Watervliet, NY, July 1987.

APPENDIX

INPUT FOR XKTC SIMULATION OF 7-INCH HARP GUN FIRINGS

INTENTIONALLY LEFT BLANK

ROUND ONE, PRELIMINARY SIMULATION

175 MM MOD GUN 1098 HARP

TTFFTT 160 00 1

55 -3 0 3500

10.0 604.0 0.0001 2.0 0.05 0.01 0.0001 0.0001

1000 100 1100 100 1500 100

8 9 6 5 0 0 1 2 0 0 0 8 0

529. 14.7 28.896 1.4

529.0

JA2 19PF LOT 792-39 1.0 55.75 70.1 .05763

-9 .587 0.036 1.5 19. 1

.1 0.01 8.0 7.0 1.0 1.0

40000. 1.0 41754. .5

6000. .0010154 .8608 100000. .00048009 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

9967547. 30.93 1.221 23.00

0. .008 .012 .015 .05 .0510 .052 .0525 .0725

0.0 .99 1.00 12.0 12.1 21.3

0.0 0.0 0.0 0.0 0.0 0.0

75. 75. 0.0 0.0 0.0 0.0

00. 00. 0.0 0.0 0.0 0.0

0. 0. 0.0 0.0 0. 0.

0. 0. 0.0 0.0 0. 0.

0. 0. 0. 0. 0. 0.

0. 0. 0. 0. 0. 0.

0.0 0.0 0.0 0.0 0.0 0.0

0.0 0.0 0.0 0.0 0.0 0.0

0.0 4.240 41.2 4.240 49.15 3.806 85.00 3.79

88.6 3.655 114.65 3.65 120. 3.65 659.1 3.65

0.0 200. 28. 300. 38. 1000. 45. 300.

615. 300.

1.4 14.7 550. 28.9

0.05 0.43 10. 1.25

7.77 0.0228 .7 55.75 10.994 44.0 0.000

0.0 37. 50. 85. 137. 197. 654.25 50.

INTENTIONALLY LEFT BLANK

ROUND ONE, FINAL SIMULATION

175 MM MOD GUN 1098 HARP

TTFFTTT 160 00 1

56 -3 0 3500

10.0 604.0 0.0001 2.0 0.05 0.01 0.0001 0.0001

1000 100 1100 100 1500 100

8 9 6 5 0 0 3 2 0 0 0 8 0 0 0 0

529. 14.7 28.896 1.4

529.0

JA2 19PF LOT 792-39 1.0 22.0 28.362 .05763

-9 .587 0.036 1.5 19. 1

.1 0.0 10.0 9.0 2.0 1.0

40000. 1.0 41754. .5

6000. .0010459 .8608 100000. .00049449 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

JA2 19PF LOT 792-39 22.0 43.0 28.380 .05763

-9 .587 0.036 1.5 19. 1

.1 0.01 8.0 6.0 2.0 2.0

40000. 1.0 41754. .5

6000. .0010459 .8608 100000. .00049449 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

JA2 19PF LOT 792-39 43.0 55.75 13.361 .05763

-9 .587 0.036 1.5 19. 1

.1 0.01 7.0 5.0 2.0 2.0

40000. 1.0 41754. .5

6000. .0010459 .8608 100000. .00049449 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

9967547. 30.93 1.221 23.00

0. .008 .012 .015 .05 .0510 .052 .0525 .0725

0.0 .99 1.00 12.0 12.1 21.3

0.0 0.0 0.0 0.0 0.0 0.0

75. 75. 0.0 0.0 0.0 0.0

00. 00. 0.0 0.0 0.0 0.0

0. 0. 0.0 0.0 0. 0.

0. 0. 0.0 0.0 0. 0.

0. 0. 0. 0. 0. 0.

0. 0. 0. 0. 0. 0.

0.0 0.0 0.0 0.0 0.0 0.0

0.0 0.0 0.0 0.0 0.0 0.0

0.0 4.240 41.2 4.240 49.15 3.806 85.00 3.79

88.6 3.655 114.65 3.65 120. 3.65 659.1 3.65

0.0 500. 28. 500. 38. 3000. 45. 500.

615. 500.

1.4 14.7 550. 28.9

0.1 0.43 10. 1.25

7.77 0.0228 .7

55.75 10.994 44.0 0.000

0.0 37. 50. 85. 137. 197. 654.25 50.

INTENTIONALLY LEFT BLANK

ROUND TWO, PRELIMINARY SIMULATION

175 MM MOD GUN 1098 HARP

TTFFTTT 1 6 0 00 1

56 -3 0 3500

10.0 611.0 0.0001 2.0 0.05 0.01 0.0001 0.0001

1000 100 1100 100 1500 100

8 9 6 5 0 0 3 2 0 0 0 8 0 0 0 0

529. 14.7 28.896 1.4

529.0

JA2 19PF LOT 792-39 1.0 22.5 31.884 .05763

-9 .587 0.036 1.5 19. 1

.1 0.0 10.0 8.0 2.0 2.0

40000. 1.0 41754. .5

6000. .0010459 .8608 100000. .00049449 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

JA2 19PF LOT 792-39 22.5 44.0 31.698 .05763

-9 .587 0.036 1.5 19. 1

.1 0.01 8.0 6.0 2.0 2.0

40000. 1.0 41754. .5

6000. .0010459 .8608 100000. .00049449 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

JA2 19PF LOT 792-39 44.0 48.00 3.492 .05763

-9 .587 0.036 1.5 19. 1

.1 0.01 7.0 5.0 2.0 2.0

40000. 1.0 41754. .5

6000. .0010459 .8608 100000. .00049449 .9469 0.0 800.

.0277 .0001345 .6

20372433. 24.8226 1.2268 26.98

9967547. 30.93 1.221 23.00

0. .008 .012 .015 .05 .0510 .052 .0525 .0725

0.0 .99 1.00 12.0 12.1 21.3

0.0 0.0 0.0 0.0 0.0 0.0

75. 75. 0.0 0.0 0.0 0.0

00. 00. 0.0 0.0 0.0 0.0

0. 0. 0.0 0.0 0. 0.

0. 0. 0.0 0.0 0. 0.

0. 0. 0. 0. 0. 0.

0. 0. 0. 0. 0. 0.

0.0 0.0 0.0 0.0 0.0 0.0

0.0 0.0 0.0 0.0 0.0 0.0

0.0 4.240 41.2 4.240 49.15 3.806 85.00 3.79

88.6 3.655 114.65 3.65 120. 3.65 659.1 3.65

0.0 200. 28. 300. 45. 3000. 45. 300.

615. 300.

14.7 550. 4.0

0.05 0.43 7. 6.0

7.77 0.0228 .7

48.00 10.994 44.0 0.000

0.0 50. 137. 197. 397. 597. 654.25 50.

INTENTIONALLY LEFT BLANK

**No. of
Copies Organization**

- 2 Administrator
Defense Technical Info Center
ATTN: DTIC-DDA
Cameron Station
Alexandria, VA 22304-6145
- 1 Commander
U.S. Army Materiel Command
ATTN: AMCAM
5001 Eisenhower Ave.
Alexandria, VA 22333-0001
- 1 Commander
U.S. Army Laboratory Command
ATTN: AMSLC-DL
2800 Powder Mill Rd.
Adelphi, MD 20783-1145
- 2 Commander
U.S. Army Armament Research,
Development, and Engineering Center
ATTN: SMCAR-IMI-I
Picatinny Arsenal, NJ 07806-5000
- 2 Commander
U.S. Army Armament Research,
Development, and Engineering Center
ATTN: SMCAR-TDC
Picatinny Arsenal, NJ 07806-5000
- 1 Director
Benet Weapons Laboratory
U.S. Army Armament Research,
Development, and Engineering Center
ATTN: SMCAR-CCB-TL
Watervliet, NY 12189-4050
- (Unclass. only) 1 Commander
U.S. Army Rock Island Arsenal
ATTN: SMCRI-TL/Technical Library
Rock Island, IL 61299-5000
- 1 Director
U.S. Army Aviation Research
and Technology Activity
ATTN: SAVRT-R (Library)
M/S 219-3
Ames Research Center
Moffett Field, CA 94035-1000
- 1 Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-CS-R (DOC)
Redstone Arsenal, AL 35898-5010

**No. of
Copies Organization**

- 1 Commander
U.S. Army Tank-Automotive Command
ATTN: ASQNC-TAC-DIT (Technical
Information Center)
Warren, MI 48397-5000
- 1 Director
U.S. Army TRADOC Analysis Command
ATTN: ATRC-WSR
White Sands Missile Range, NM 88002-5502
- 1 Commandant
U.S. Army Field Artillery School
ATTN: ATSF-CSI
Ft. Sill, OK 73503-5000
- 2 Commandant
U.S. Army Infantry School
ATTN: ATZB-SC, System Safety
Fort Benning, GA 31903-5000
- (Class. only) 1 Commandant
U.S. Army Infantry School
ATTN: ATSH-CD (Security Mgr.)
Fort Benning, GA 31905-5660
- (Unclass. only) 1 Commandant
U.S. Army Infantry School
ATTN: ATSH-CD-CSO-OR
Fort Benning, GA 31905-5660
- 1 WLMNOI
Eglin AFB, FL 32542-5000
- Aberdeen Proving Ground
- 2 Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen
- 1 Cdr, USATECOM
ATTN: AMSTE-TC
- 3 Cdr, CRDEC, AMCCOM
ATTN: SMCCR-RSP-A
SMCCR-MU
SMCCR-MSI
- 1 Dir, VLAMO
ATTN: AMSLC-VL-D
- 10 Dir, USABRL
ATTN: SLCBR-DD-T

<u>No. of Copies</u>	<u>Organization</u>
1	Commander U.S. Army Concepts Analysis Agency ATTN: D. Hardison 8120 Woodmont Avenue Bethesda, MD 20014
1	C.I.A. 01R/DB/Standard Washington, DC 20505
1	U.S. Army Ballistic Missile Defense Systems Command Advanced Technology Center P.O. Box 1500 Huntsville, AL 35807-3801
1	Chairman DOD Explosives Safety Board Room 856-C Hoffman Bldg. 1 2461 Eisenhower Avenue Alexandria, VA 22331-0600
1	Commander U.S. Army Materiel Command ATTN: AMCDE-DW 5001 Eisenhower Avenue Alexandria, VA 22333-5001
1	Department of the Army Office of the Product Manager 155mm Howitzer, M109A6, Paladin ATTN: SFAE-AR-HIP-IP, Mr. R. De Kleine Picatinny Arsenal, NJ 07806-5000
2	Commander Production Base Modernization Agency U.S. Army Armament Research, Development, and Engineering Center ATTN: AMSMC-PBM, A. Siklosi AMSMC-PBM-E, L. Laibson Picatinny Arsenal, NJ 07806-5000
3	PEO-Armaments Project Manager Tank Main Armament System ATTN: AMCPM-TMA/K. Russell AMCPM-TMA-105 AMCPM-TMA-120/C. Roller Picatinny Arsenal, NJ 07806-5000

<u>No. of Copies</u>	<u>Organization</u>
15	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE SMCAR-AEE-B, A. Beardell D. Downs S. Einstein S. Westley S. Bernstein J. Rutkowski B. Brodman P. O'Reilly R. Cirincione A. Grabowsky P. Hui J. O'Reilly N. DeVries SMCAR-AES, S. Kaplowitz Picatinny Arsenal, NJ 07806-5000
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCD, D. Spring SMCAR-CCH-V, C. Mandala Picatinny Arsenal, NJ 07806-5000
1	Commander U.S. Army Armament Research, Development and Engineering Center ATTN: SMCAR-HFM, E. Barriores Picatinny Arsenal, NJ 07806-5000
1	Commander U.S. Army Armament Research, Development and Engineering Center ATTN: SMCAR-FSA-T, M. Salsbury Picatinny Arsenal, NJ 07806-5000
1	Commander U.S. Army Armament Research, Development and Engineering Center ATTN: SMCAR-FF-C, MAJ Lundberg Picatinny Arsenal, NJ 07806-5000
1	Commander U.S. Army Armament Research, Development and Engineering Center ATTN: SMCAR-FF-E, A. Graf Picatinny Arsenal, NJ 07806-5000

<u>No. of Copies</u>	<u>Organization</u>
1	Commander, USACECOM R&D Technical Library ATTN: ASQNC-ELC-IS-L-R, Meyer Center Fort Monmouth, NJ 07703-5301
1	Commander U.S. Army Harry Diamond Laboratory ATTN: SLCHD-TA-L 2800 Powder Mill Rd. Adelphi, MD 20783-1145
1	Commandant U.S. Army Aviation School ATTN: Aviation Agency Fort Rucker, AL 36360
2	Program Manager U.S. Tank-Automotive Command ATTN: AMCPM-ABMS, T. Dean (2cps) Warren, MI 48092-2498
1	Project Manager U.S. Tank-Automotive Command Fighting Vehicle Systems ATTN: SFAE-ASM-BV Warren, MI 48092-2498
1	Project Manager, Abrams Tank System ATTN: SFAE-ASM-AB Warren, MI 48397-5000
1	Director HQ, TRAC RPD ATTN: ATCD-MA Fort Monroe, VA 23651-5143
2	Director U.S. Army Materials Technology Laboratory ATTN: SLCMT-ATL (2 cps) Watertown, MA 02172-0001
1	Commander U.S. Army Research Office ATTN: Technical Library P.O. Box 12211 Research Triangle Park, NC 27709-2211
1	Commander U.S. Army Belvoir Research and Development Center ATTN: STRBE-WC Fort Belvoir, VA 22060-5006

<u>No. of Copies</u>	<u>Organization</u>
1	Director U.S. Army TRAC-Ft. Lee ATTN: ATHC-L, Mr. Cameron Fort Lee VA 23801-6140
1	Commandant U.S. Army Command and General Staff College Fort Leavenworth, KS 66027
1	Commandant U.S. Army Special Warfare School ATTN: Rev and Trng Lit Div Fort Bragg, NC 28307
3	Commander Radford Army Ammunition Plant ATTN: SMCAR-QA/HI LIB (3 cps) Radford, VA 24141-0298
1	Commander U.S. Army Foreign Science and Technology Center ATTN: AMXST-MC-3 220 Seventh Street, NE Charlottesville, VA 22901-5396
2	Commander Naval Sea Systems Command ATTN: SEA 62R SEA 64 Washington, DC 20362-5101
1	Commander Naval Air Systems Command ATTN: AIR-954-Tech Library Washington, DC 20360
1	Naval Research Laboratory Technical Library Washington, DC 20375
2	Commandant U.S. Army Field Artillery Center and School ATTN: ATSF-CO-MW, E.Dublsky (2 cps) Ft. Sill, OK 73503-5600
1	Office of Naval Research ATTN: Code 473, R.S. Miller 800 N. Quincy Street Arlington, VA 22217-9999

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
3	Commandant U.S. Army Armor School ATTN: ATZK-CD-MS, M. Falkovitch (3 cps) Armor Agency Fort Knox, KY 40121-5215	4	Commander Indian Head Division Naval Surface Warfare Center ATTN: Code 610, T.C. Smith D. Brooks K. Rice Technical Library Indian Head, MD 20640-5035
2	Commander U.S. Naval Surface Warfare Center ATTN: J.P. Consaga C. Goltmer Indian Head, MD 20640-5000	1	AL/TSTL (Technical Library) ATTN: J. Lamb Edwards AFB, CA 93523-5000
4	Commander Naval Surface Warfare Center ATTN: Code 730 Code R-13, K. Kim R. Bernecker H. Sandusky Silver Spring, MD 20903-5000	1	AFATL/DLYV Eglin AFB, FL 32542-5000
2	Commanding Officer Naval Underwater Systems Center ATTN: Code 5B331, R.S. Lazar Technical Library Newport, RI 02840	1	AFATL/DLXP Eglin AFB, FL 32542-5000
5	Commander Naval Surface Warfare Center ATTN: Code G33, J. East W. Burrell J. Johndrow Code G23, D. McClure Code DX-21 Tech Library Dahlgren, VA 22448-5000	1	AFATL/DLJE Eglin AFB, FL 32542-5000
3	Commander Naval Weapons Center ATTN: Code 388, C.F. Price Code 3895, T. Parr Information Science Division China Lake, CA 93555-6001	3	AAI Corporation ATTN: J. Hebert J. Frankle D. Cleveland P.O. Box 126 Hunt Valley, MD 21030-0126
1	OSD/SDIC/IST ATTN: L.H. Caveny Pentagon Washington, DC 20301-7100	2	Aerojet Solid Propulsion Co. ATTN: P. Micheli L. Torreyson Sacramento, CA 96813
		3	AL/LSCF ATTN: J. Levine L. Quinn T. Edwards Edwards AFB, CA 93523-5000
		1	AVCO Everett Research Laboratory ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149-5936

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	General Electric Company Tactical System Department ATTN: J. Mandzy 100 Plastics Ave. Pittsfield, MA 01201-3698	1	Paul Gough Associates, Inc. ATTN: P.S. Gough 1048 South St. Portsmouth, NH 03801-5423
1	IITRI ATTN: M.J. Klein 10 W. 35th Street Chicago, IL 60616-3799	1	Physics International Company ATTN: Library/H. Wayne Wampler 2700 Merced Street San Leandro, CA 984577-5602
1	Hercules, Inc. Allegheny Ballistics Laboratory ATTN: William B. Walkup P.O. Box 210 Rocket Center, WV 26726	1	Princeton Combustion Research Laboratory, Inc. ATTN: M. Summerfield 475 US Highway One Monmouth Junction, NJ
1	Hercules, Inc. Radford Army Ammunition Plant ATTN: E. Hibshman Radford, VA 24141-0299	2	Rockwell International Rocketdyne Division ATTN: BA08, J.E. Flanagan J. Gray 6633 Canoga Avenue Canoga Park, CA 91303-2703
1	Hercules, Inc. Hercules Plaza ATTN: B.M. Riggleman Wilmington, DE 19894	1	Thiokol Corporation Huntsville Division ATTN: Tech Library Huntsville, AL 35807
3	Lawrence Livermore National Laboratory ATTN: L-355, A. Buckingham M. Finger L-324, M. Constantino P.O. Box 808 Livermore, CA 94550-0622	1	Sverdrup Technology, Inc. ATTN: Dr. John Deur 2001 Aerospace Parkway Brook Park, OH 44142
1	Olin Corporation Badger Army Ammunition Plant ATTN: F.E. Wolf Baraboo, WI 53913	2	Thiokol Corporation Elkton Division ATTN: R. Biddle Tech Library P.O. Box 241 Elkton, MD 21921-0241
3	Olin Corporation ATTN: E.J. Kirschke A.F. Gonzalez D.W. Worthington P.O. Box 222 St. Marks, FL 32355-0222	1	Science Applications International Corp. ATTN: M. Palmer 2109 Airpark Rd. Albuquerque, NM 87106
1	Olin Ordinance ATTN: H.A. McElroy 10101 9th Street, North St. Petersburg, FL 33716	1	Veritay Technology, Inc. ATTN: E. Fisher 4845 Millersport Hwy. East Amherst, NY 14501-0305

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Universal Propulsion Company ATTN: H.J. McSpadden 25401 North Central Ave. Phoenix, AZ 85027-7837	1	Institute of Gas Technology ATTN: D. Gidaspo 3424 S. State Street Chicago, IL 60616-3896
1	Battelle ATTN: TACTEC Library, J.N. Huggins 505 King Avenue Columbus, OH 43201-2693	1	Johns Hopkins University Applied Physics Laboratory Chemical Propulsion Information Agency ATTN: T. Christian Johns Hopkins Road Laurel, MD 20707-0690
1	Brigham Young University Department of Chemical Engineering ATTN: M. Beckstead Provo, UT 84601	1	Massachusetts Institute of Technology Department of Mechanical Engineering ATTN: T. Toong 77 Massachusetts Avenue Cambridge, MA 02139-4307
1	California Institute of Technology 204 Karman Lab Main Stop 301-46 ATTN: F.E.C. Culick 1201 E. California Street Pasadena, CA 91109	1	Pennsylvania State University Department of Mechanical Engineering ATTN: V. Yang University Park, PA 16802-7501
1	California Institute of Technology Jet Propulsion Laboratory ATTN: L.D. Strand, MS 512/102 4800 Oak Grove Drive Pasadena, CA 91109-8099	1	Pennsylvania State University Department of Mechanical Engineering ATTN: K. Kuo University Park, PA 16802-7501
1	University of Illinois Department of Mechanical/Industry Engineering ATTN: H. Krier 144 MEB; 1206 N. Green St. Urbana, IL 61801-2978	1	Pennsylvania State University Assistant Professor Department of Mechanical Engineering ATTN: Dr. Stefan T. Thynell 219 Hallowell Building University Park, PA 16802-7501
1	University of Massachusetts Department of Mechanical Engineering ATTN: K. Jakus Amherst, MA 01002-0014	1	Pennsylvania State University Director, Gas Dynamics Laboratory Department of Mechanical Engineering ATTN: Dr. Gary S. Settles 303 Mechanical Engineering Building University Park, PA 16802-7501
1	University of Minnesota Department of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55414-3368	1	SRI International Propulsion Sciences Division ATTN: Tech Library 333 Ravenwood Avenue Menlo Park, CA 94025-3493
3	Georgia Institute of Technology School of Aerospace Engineering ATTN: B.T. Zim E. Price W.C. Strehle Atlanta, GA 30332	1	Rensselaer Polytechnic Institute Department of Mathematics Troy, NY 12181

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Director Los Alamos Scientific Lab ATTN: T3/D. Butler M. Division/B. Craig P.O. Box 1663 Los Alamos, NM 87544	1	Alliant Techsystems, Inc. ATTN: R.E. Tompkins MN38-3300 5700 Smetana Dr. Minnetonka, MN 55343
1	General Applied Sciences Lab ATTN: J. Erdos 77 Raynor Ave. Ronkonkoma, NY 11779-6649	1	Alliant Techsystems, Inc. ATTN: J. Kennedy 7225 Northland Drive Brooklyn Park, MN 55428
1	Battelle PNL ATTN: Mr. Mark Garnich P.O. Box 999 Richland, WA 99352	1	Science Applications, Inc. ATTN: R.B. Edelman 23146 Cumorah Crest Drive Woodland Hills, CA 91364-3710
1	Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlevy III Castle Point Station Hoboken, NJ 07030-5907	1	Battelle Columbus Laboratories ATTN: Mr. Victor Levin 505 King Ave. Columbus, OH 43201-2693
3	Institute for Advanced Technology Stonelake Office Complex 4030-2W Braker Lane ATTN: H. Fair T. Kiehne D. Berry Austin, TX 78759	1	Allegheny Ballistics Laboratory Propulsion Technology Department Hercules Aerospace Company ATTN: Mr. Thomas F. Farabaugh P.O. Box 210 Rocket Center, WV 26726
1	Rutgers University Department of Mechanical and Aerospace Engineering ATTN: S. Terzian University Heights Campus New Brunswick, NJ 08903	1	MBR Research Inc. ATTN: Dr. Moshe Ben-Reuven 601 Ewing St., Suite C-22 Princeton, NJ 08540 <u>Aberdeen Proving Ground</u>
1	University of Southern California Mechanical Engineering Department ATTN: OHE200, M. Gerstein Los Angeles, CA 90689-5199	1	Cdr, CSTA ATTN: STECS-PO, Hendricksen
2	University of Utah Department of Chemical Engineering ATTN: A. Baer Salt Lake City, UT 84112-1194		
1	Washington State University Department of Mechanical Engineering ATTN: C.T. Crowe Pullman, WA 99163-5201		

No. of
Copies Organization

1 L'Ingenieur en Chef de l'Armement CHARTIER
Centre Technique Armes et Munitions
Etablissement Technique de Bourges
Carrefour de Zero-Nord - Route de Guerry
BP 712 18015 Bourges Cedex
France