

## REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 2704-0188

AD-A252 342



1. DATE

NA

3. REPORT TYPE AND DATES COVERED

01 AUG 89 to 31 OCT 91

Final

4. TITLE AND SUBTITLE

RANDOM DESIGN AND PROBABILISTIC ANALYSIS OF INTERCONNECTION  
NETWORKS (U)

5. FUNDING NUMBERS

AFOSR-89-0471  
61102F 2304/8A

6. AUTHOR(S)

Professor Masson

7. PERFORMING ORGANIZATION NAME(S)

Johns Hopkins Univ.  
Math Sciences  
Baltimore MD 212188. PERFORMING ORGANIZATION  
REPORT NUMBER

AFOSR-TR-

92 0544

9. SPONSORING AGENCY NAME(S)

AFOSR/NM

Bolling AFB DC 20332-6443

10. SPONSORING MONITORING  
AGENCY REPORT NUMBER

AFOSR-89-0471

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION STATEMENT (if applicable)

Approved for public release;  
distribution unlimited.

12b. DISTRIBUTION CODE

UL

13. ABSTRACT

New designs for both nonblocking and rearrangeable broadcast switching networks have been developed. Analysis to determine/evaluation of broadcast networks based on the trade-off between rearrangeability and cost has been performed.

DTIC  
ELECTE  
JUN 22 1992  
S A D

14. SUBJECT TERMS

15. NUMBER OF PAGES

3

16. PRICE CODE

17. SECURITY CLASSIFICATION  
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION  
OF ABSTRACT

UNCLASSIFIED

19. SECURITY CLASSIFICATION  
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UL

FINAL REPORT  
to  
Air Force Office of Scientific Research

Random Design and Probabilistic Analysis  
of  
Interconnection Networks  
Grant AFOSR 89-0471

92

92-15704



FINAL REPORT  
to  
Air Force Office of Scientific Research

Random Design and Probabilistic Analysis  
of  
Interconnection Networks  
Grant AFOSR 89-0471

Gerald M. Masson  
Department of Computer Science  
  
Edward R. Scheinerman  
Department of Mathematical Sciences  
  
Johns Hopkins University  
Baltimore, Maryland 21218

COPY  
MAILED

|                    |                                     |
|--------------------|-------------------------------------|
| Accession For      |                                     |
| NTIS GRA&I         | <input checked="" type="checkbox"/> |
| DTIC TAB           | <input type="checkbox"/>            |
| Unannounced        | <input type="checkbox"/>            |
| Justification      |                                     |
| By                 |                                     |
| Distribution       |                                     |
| Availability Codes |                                     |
| Dist               | Availability Codes                  |
| A-1                |                                     |

Overview of Research Accomplishments

For a *broadcast connection* through a multi-stage network, an input port can be simultaneously connected to more than one output port (but an output port can be connected to at most one input port at a time). In this research supported by AFOSR grant 89-0471, new designs for both *nonblocking* and *rearrangeable* broadcast switching networks for realizing broadcast connections are presented.

In the nonblocking broadcast network category, we obtain the results that lead to the currently best known explicit constructions of nonblocking broadcast networks with a constant number of stages relative to both crosspoint and control algorithm complexity. In three-stage versions of our designs, comprised of  $r$  switches of size  $n \times m$  in the input stage,  $m$  switches of size  $r \times r$  in the middle stage, and  $r$  switches of size  $m \times n$  in the output stage, we prove that if  $n \geq \min(n-1)(x + r^{1/x})$ , where  $1 \leq x \leq \min\{n-1, r\}$ , the resulting  $v(m, n, r)$  network is nonblocking for broadcast assignments. This condition represents an improvement on the minimum number of middle switches from  $O(nr)$  to  $O(n \frac{\log r}{\log \log r})$  relative to previously known results. The results can be generalized to  $(2k+1)$ -stage networks for  $k > 1$ . Moreover, a linear control algorithm is designed for satisfying broadcast connection requests. The sequential and parallel hardware implementations of

this control algorithm are also described and analyzed. In the parallel implementation, connection requests can be satisfied in  $O(\frac{(\log r)^2}{\log \log r})$  gate propagations for a  $v(m, n, r)$  network. This work provides a class of nonblocking broadcast networks for real-time parallel/distributed computing and telecommunication applications which require high-speed network path routings.

In the rearrangeable broadcast network category, we present analytical results which permit the rearrangeability of broadcast networks to be evaluated on the basis of fundamental parameters associated with the network structure so that the trade-off between the network rearrangeability and the network cost can be determined. These results permit our broadcast networks to be designed for which the average number of rearrangements for satisfying a connection request in an  $N \times N$  network can be reduced to  $O(1)$  in comparison with  $O(N)$  in other existing designs while holding the asymptotic crosspoint growth to  $O(N \log N)$ . Our analytically derived results are supported by simulation data. This work provides a class of low-cost broadcast networks for broadcasting and conferencing applications wherein only a limited degree of rearrangeability can be tolerated.

This research is described in detail in the following six papers.