

FL-TR-92-2114

AD-A253 919



2

**GEOPHYSICAL INVESTIGATIONS AT
PAHUTE MESA, NEVADA**

John F. Ferguson


**University of Texas at Dallas
Center for Lithospheric Studies
PO Box 830688
Richardson, TX 75083-0688**

**DTIC
ELECTE
JUL 16 1992
S B D**

30 April 1992

**Final Report
17 February 1989-21 November 1991**

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED



**PHILLIPS LABORATORY
AIR FORCE SYSTEMS COMMAND
HANSCOM AIR FORCE BASE, MASSACHUSETTS 01731-5000**

92-18848




92 7 15 042


SPONSORED BY
Defense Advanced Research Projects Agency
Nuclear Monitoring Research Office
ARPA ORDER NO. 5307

MONITORED BY
Phillips Laboratory
Contract No. F19628-89-K-0006

The views and conclusions contained in this document are those of the authors and should not be interpreted as representing the official policies, either expressed or implied, of the Defense Advanced Research Projects Agency or the U.S. Government.

This technical report has been reviewed and is approved for publication.


JAMES F. LEWKOWICZ
Contract Manager
Solid Earth Geophysics Branch
Earth Sciences Division


JAMES F. LEWKOWICZ
Branch Chief
Solid Earth Geophysics Branch
Earth Sciences Division


DONALD H. ECKHARDT, Director
Earth Sciences Division

This report has been reviewed by the ESD Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS).

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.

If your address has changed, or if you wish to be removed from the mailing list, or if the addressee is no longer employed by your organization, please notify PL/IMA, Hanscom AFB, MA 01731-5000. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document requires that it be returned.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this section of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 30 April 1992	3. REPORT TYPE AND DATES COVERED Final Report 2/17/89 - 11/21/91		
4. TITLE AND SUBTITLE Geophysical Investigations at Pahute Mesa, Nevada		5. FUNDING NUMBERS PE 62714E PR 9A10 - TDA WU AB Contract F19628-89-K-0006		
6. AUTHOR(S) John F. Ferguson				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Texas at Dallas Center for Lithospheric Studies PO Box 830688 Richardson, TX 75083-0688		8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Phillips Laboratory Hanscom AFB, MA 01731-5000 Contract Manager: James Lewkowicz/GPEH		10. SPONSORING/MONITORING AGENCY REPORT NUMBER PL-TR-92-2114		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; Distribution unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Part I of this study has concentrated on the assembly of a data base of geological and geophysical data for a transect at Pahute Mesa, Nevada. Existing data, in the form of well logs, gravity observations and seismic travel times, have been supplemented by new gravity and seismic data especially for the construction of a geophysical model of the shallow crust. The transect is modeled as an extensional basin, with up to 5 km of structural relief and volcanic fill. Major faulting is on the east side. The second part of this study has applied the new GPS technology to geotectonic monitoring of nuclear explosions at Pahute Mesa, Nevada. Significant deformation is observed to be caused by the test BULLION. New rapid survey methods have been successfully applied to perform studies, which would have been otherwise prohibitively time consuming.				
14. SUBJECT TERMS Pahute Mesa, Nevada; geologic structure; gravity modeling; ray tracing; Global Positioning System; deformation; nuclear explosions			15. NUMBER OF PAGES 72	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

Contents

Part I: A Geophysical-Geological Transect at Pahute Mesa, Nevada	1
Introduction	2
Gravity Data	6
Seismic Data	9
Geophysical Modeling	14
Conclusions	19
References	20
Figures	23
Part II: Geodetic Experiments on Nevada Test Site Events Using the Global Positioning System	29
Introduction	30
Explosion Mechanics	31
Previous Geodetic Studies	34
GPS Methodology	36
Structural Setting	42
Results of the BULLION Survey	44
The BEXAR Survey	48
Conclusions	50
References	51
Figures	53

DTIC QUALITY INSPECTED 2

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	1

A Geophysical-Geological Transect at Pahute Mesa, Nevada

John F. Ferguson¹ and Allen H. Cogbill²

Final Technical Report: Part I

**¹ The University of Texas at Dallas
Richardson, TX**

**² Los Alamos National Laboratory
Los Alamos, NM**

Introduction

The Pahute Mesa, Nevada, nuclear test site is situated atop a complex of volcanic centers. The youngest such caldera is the Silent Canyon caldera, about 14 Ma. It has long been recognized that a considerable thickness of volcanically derived material underlies this site (Orkild et al., 1968), but the details are obscured by a blanket of more recent tuffs from the Timber Mountain caldera, to the south. The structural development at Pahute Mesa has been controlled, over about the past 20 Ma, by successive, local volcanic activity and regional, basin and range extension (Byers et al., 1989; Warren, et al., 1985).

Spence (1974) recognized the presence of a major high velocity structure under the volcanic complex, that extends into the upper mantle. These results were based on travel time anomalies for teleseismic P-waves from nuclear explosions at Pahute Mesa. The existence of some kind of deep high velocity anomaly has been confirmed in several studies since. Minster et al. (1981) used a much larger teleseismic data set and attempted to map structural variation in the crust and mantle beneath both Pahute Mesa and Yucca Flat. Taylor (1983) used regional propagation paths and teleseismic travel time residuals to build a similar, block-type model. In these later models the

structure was parameterized by relatively thick layers (≥ 5 km), which were subdivided laterally into blocks of 10 km size or greater. The high velocity body begins at a depth in excess of 5 km; at shallower depths Pahute Mesa is characterized by low seismic velocities. Velocities up to 5% greater than expected for this region are to be found to depths greater than 100 km, in a zone which extends to the north and northeast of Pahute Mesa.

Although the resolution of these methods is quite low from a geologic standpoint, the existence and definition of spatially and azimuthally dependent anomalies in travel time and amplitude is very well established. The block type models mentioned above, as well as studies by Cormier (1987) and Lynnes and Lay (1988), have attempted to explain these anomalies using upper mantle structure. Cormier found that Taylor's (1983) velocity anomaly reproduced the amplitude anomaly very well in a qualitative sense, but only reduced the log-amplitude variance by 25%. A major limitation of the travel time residual models is a lack of adequate detail in the shallow (< 5 km) subsurface. This region is the scene of very large geophysical variations, involving low density and velocity volcanic materials filling a basin in a high-density, high-velocity basement comprised of Paleozoic sediments and Mesozoic intrusives. Amplitude anomalies at

Yucca Flat have been explained by Ferguson (1988) and McLaughlin et al. (1987) by using shallow crustal variation alone. While the structure at these two sites is very different, the shallow crustal structure at Pahute Mesa may be responsible for at least a portion of the amplitude anomaly in a manner not previously considered. The ability to predict seismic amplitude variations due to local structure is vital to the ability to accurately predict explosion yields in the context of a limited test ban treaty.

Local recordings of seismic signals from nuclear tests have also been studied. The principal focus of these studies has been the seismic source function (Stump and Johnson, 1984; Barker et al., 1991), but it has been necessary to develop one-dimensional velocity and density models for the computation of seismic Green's functions. A very good average velocity model, valid at very shallow (< 1 km) depths is to be found in Leonard and Johnson (1987), and a comparison of several one-dimensional models is made in Barker et al. (1991).

The availability of subsurface geologic and geophysical data is considerable and unique for a volcanic center. This data was developed to support the nuclear test activities and is restricted to depths less than the usual depths for

test emplacement (i. e., about 600 m). Some older data extends to depths of a 1 km, but this is extremely limited. Recently, an increased effort has been made to synthesize the results of this subsurface exploration, starting with Warren et al. (1985). In the current study this data base will be extensively utilized to constrain the geophysical modeling. Figure 1 is an interpreted geologic cross-section for the transect shown on Figure 2.

The results considered here attempt to bridge the gap between the borehole data and the deep crust and upper mantle. A laterally variable model is constructed along a transect across Pahute Mesa, Rainier Mesa and extending to Yucca Flat. The geophysical constraints are provided by Bouguer gravity data and local P-wave travel times.

Gravity Data

The gravity map presented in Figure 2 is compiled from approximately 1500 gravity stations collected by the USGS, mostly in the 1960's (Healey, 1968) and about 250 more stations collected by the University of Texas at Dallas and Los Alamos National Laboratory (UTD/LANL) in 1985. The older data are sparsely sampled and predate both the existing road network and topographic maps. The elevations were usually controlled by altimeter. The accuracy of these older data may be only a few mGal.

The 1985 survey was conducted along roads spanning Pahute Mesa both east to west and north to south. Stations were spaced every 300 m, with position control provided by a Zeiss Elta-4 electronic distance meter. Two LaCoste & Romberg Model G gravity meters were employed. These data are conservatively estimated to be good to within 0.5 mGal.

Terrain corrections were calculated for the UTD/LANL gravity data using a special procedure in conjunction with hand-digitized elevation data from 1:24,000 topographic maps. Depending upon the local terrain, each 20 ft, 40 ft or 100 ft contour was digitized at arc intervals of 25 to 50 m.

The resulting irregularly distributed elevation data were then used in the following procedure. A multiquadric surface (Hardy, 1971) was fit to all data within 1500 m of

each station. The number of data used in each case varied between about 350 and 1300. The terrain effect was integrated using a modification of Hammer's (1939) method. A total of 21 annular zones were defined, with radii from 5 to 1260 m. Within each zone, 24 approximately square compartments were specified. In each compartment the mean elevation was estimated from 20 pseudo-random samples of the multiquadric surface.

Additional terrain corrections out to a distance of 166.7 km were computed using a modified version of Plouff's (1977) program and the 30 arc-second regional topographic grid of mean elevations. Corrections for tides and meter drift were applied and a reduction density of 2000 kg/m^3 used. This relatively low density is justified by the resulting reduced correlation between gravity and topography.

The UTD/LANL data were merged with the older USGS data and points, which were determined to be outliers, were edited. The USGS data were already terrain-corrected; thus, new terrain corrections were not computed, but the USGS gravity data were reduced using the 2000 kg/m^3 density. Contours of the Bouguer gravity anomaly are shown in Figure 2. Differences in anomaly amplitude observed in this map as compared to earlier publications (e.g., Healey, 1968)

are primarily due to the use of the lower reduction density, as opposed to the standard 2670 kg/m^3 . The entire data set is described and included in the compilation of Harris et al. (1989).

Seismic Data

The seismic data used in this study are from a variety of sources. Travel time and waveform data from local recordings of nuclear explosions were gathered from the literature and were also acquired specifically for this study. We conducted a wide-angle seismic survey in 1986, using high explosive sources, in order to obtain information in the caldera margin area.

A joint program for the execution of a wide-angle seismic experiment was developed by the University of Texas at Dallas and Los Alamos National Laboratory in 1986. The Pahute Mesa geologic structure is laterally discontinuous, with several high impedance contrast layers, due to welded tuff and lavas (Orkild et al., 1968), and a high attenuation, with Q perhaps as low as 50 (Johnson, 1988). These facts discourage attempts to perform conventional reflection or refraction surveys. In Big Burn Valley, immediately southeast of Pahute Mesa, older volcanic rocks (Belted Range tuff) are exposed. These rocks are physically distinct from those which fill the Silent Canyon caldera. A shot point in Big Burn Valley permits the Silent Canyon structure to be "undershot", with seismic energy injected directly into layers corresponding to the deeper structure. Snyder and Carr (1984) and Hoffman and Mooney (1984)

present the results of a similar survey at the Crater Flat caldera located 30 km to the south of Pahute Mesa. The success of the Crater Flat model indicated that a similar approach at Pahute Mesa might be fruitful. It is also difficult to obtain permission to drill shot holes on Pahute Mesa itself, due to the prevalence of archeological sites. The 1986 Pahute Mesa Seismic Experiment (PMSE86) was designed around these considerations.

A single shot point location was established in Big Burn Valley, and a line of recording stations was established along available roads trending northwest, roughly normal to the strike of the caldera margin and mapped faults. The line passes close to several important boreholes, particularly the deep holes PM-1 and Uel9w-1, which penetrate caldera margin structures. The survey geometry is shown in Figure 3. The recording line is 12.5 km long, with a 3.5 km near-offset from the shot point necessitated by topography. Twenty four- channel spreads of 1.5 km aperture and 67 m geophone group interval were deployed. Each channel recorded a string of 4.5 Hz vertical component geophones spaced 3 to 6 m apart. Fifteen bit, floating point records were made at a 2 ms sample rate.

Each spread recorded a shot from the Big Burn Valley shot point location, as well as a shot from each end with a

12 liter Dinoseis (ARCO trademark) gas exploder source. The explosive charges ranged from 13.6 to 680 kg, for near offsets ranging from 3.5 to 14.5 km. To provide redundancy, the spreads were overlapped by 50% for successive shots. The Dinoseis shots, equivalent to about a kilogram of explosive and vertically stacked over .4 to 8 shots, were not generally observable out to 1.5 km offset in the low Q, near-surface layers. These local shots were useful in establishing near-surface velocities for elevation static corrections on the recording line and near the shot point. The P-wave travel times for a total of 685 explosive records and 449 Dinoseis records were picked.

The nuclear tests Kernville (15 February 1988) and Alamo (7 July 1988) were recorded in order to provide ray paths with reverse propagation to PMSE86. Kernville, located just off the northwest end of the PMSE86 line, was almost perfectly sited to provide reverse coverage (Figure 3). Four event-triggered, 3-component recordings were made at stations KVA, KVC, KVF and KVG, using either accelerometers or seismometers. A fifth station failed to trigger and deployment of series of planned stations to the southeast was thwarted by scheduling difficulties. Alamo was located near the middle of the PMSE86 line (Figure 5) and was recorded at 3 stations in Big Burn Valley (ALA, ALC and ALD)

and 1 on Rainier Mesa (ALE). Station ALB failed to record during the experiment. All the recordings of Alamo were 3-component seismometer records.

Waveform data for the nuclear events Scotch (23 May 1967), Boxcar (26 April 1968) and Almendro (6 June 1973) can be found in Perret (1976, 1983). These data are also presented in Barker et al. (1991). Additional travel times for Almendro were found in an Environmental Research Corporation report (Anon., 1974). Recordings of Farm (16 December 1978) are discussed in Stump and Johnson (1984) and travel times were provided by Brian Stump (personal communication).

Elevation static corrections were applied to reduce the receivers to a datum elevation of 1.9 km (the elevation of the PMSE86 shot point). Such corrections ranged up to several tenths of a second and may have velocity uncertainties of up to 50%, but the corrections seem to be reasonable as applied. Timing uncertainties in some of the nuclear explosion data are considerable and are of a similar magnitude in some cases. The travel times are range from 1-4 seconds, so that the travel time uncertainty is between about 3 and 10 percent.

The travel time data for PMSE86 were smoothed by the fitting of straight line segments by an outlier-resistant

procedure (Velleman and Hoaglin, 1981). This reduced the number of travel time observations for PMSE86 to 11, which compares favorably to the 17 travel time observations from the 6 nuclear tests. Although these data are sparse, it should be noted that the shallow structure within the caldera is well constrained by boreholes. The seismic travel times, along with the gravity data, therefore provide important control on the deeper and laterally discontinuous structure at the caldera boundary.

Geophysical Modeling

The cross-section presented in this paper is controlled by the gravity observations, seismic wave travel times, and the subsurface geologic and geophysical data presented in the previous section. The interpretation of these data is based on forward modeling to match the observations from a common model parameterization, for rock type and associated mass density and compressional wave velocity. The cross section is very detailed in areas where well control is good and more generalized elsewhere.

The initial model was determined exclusively by geologic considerations and has been refined on the basis of the geophysical constraints. From 10-25 km on the cross section, well control is quite good down to 0.6 km depth and exists to about 1.5 km depth. Below 1.5 km, lithologies and properties are inferred from indirect geophysical measurements. The forward modeling, using known properties in the shallow (< 1.5 km) subsurface, is assumed to properly account for and "strip off" the shallow structure. Deeper horizons are then adjusted to produce a model fitting the geophysical data adequately. Where well control was nonexistent, some shallow areas were also adjusted. Such adjustments occurred primarily from 25-37 km on the cross-section.

The geologic cross-section was constructed from polygonal cross-section layers, with uniform, somewhat generalized lithologies. These lithologies were lumped together and identified on the basis of age, rock type and physical properties. A density function, either a constant or a linear function of depth, was assigned to each lithology. These smoothed density averages were usually determined from borehole gravity or density logs. With this type of parameterization, it is straightforward to calculate the gravity effect using the method of Murthy et al. (1979), for polygonal prisms of uniform cross section and infinite strike length. This assumption of two-dimensionality is acceptable for the chosen transect (Figure 2).

A regional gravity anomaly was estimated by low-pass filtering the gravity data in a 10 by 10 degree region centered on Pahute Mesa. The filter high cut was between 150 and 75 km wavelength. The low-pass-filtered regional grid was interpolated and subtracted from the observed Bouguer gravity values in a corridor 2 km wide containing the cross section. The residual Bouguer gravity data were modeled using relative densities above sea level and absolute densities below sea level. The use of data from a narrow zone along the assumed structural strike direction

facilitates an understanding of the lack of two-dimensionality in the structure as evidenced by the scatter in Figure 4 of the observed values.

The seismic travel times for the model were originally calculated using the two-dimensional ray tracing method of Cerveny et al. (1977). Such modeling was rather unwieldy due to the differences in the model parameterizations required by the gravity and ray tracing computer codes. At each modeling iteration, we adjusted the model structure and tested against both the gravity and seismic observations. This process necessitated a 2 time-consuming reparameterizations of the model at each iteration. Other difficulties common to wide-offset raytrace modeling included critically refracted rays and the shooting of rays to emerge near specific points on the surface.

The calculation of travel times by finite difference solution of the eikonal equation developed by Vidale (1988) permitted a more flexible approach. The model parameterization was maintained on the polygonal basis with linear velocity versus depth functions in each polygon. To compute travel times for both critical and non-critical raypaths, the velocity distribution was rasterized to produce a dense grid of values for the finite difference code. Since only a single, easy-to-modify parameterization

is required, new models can be constructed and tested quickly. The travel times computed in this manner may not be as accurate as is possible using the ray tracing method (see Qin et al., 1992), but they are thought to be sufficiently accurate for this purpose.

Displays of the two-dimensional density and velocity distributions (Figures 4 and 5), as well as vertical profiles (Figure 6) permit a visual inspection of the model. Manual, iterative adjustment of the polygon vertices and the density and velocity functions produced a sequence of models converging to an acceptable model shown as Figures 4, 5 and 6. Because this was a forward modeling effort only, the uniqueness and resolution of the model cannot be evaluated, but we believe that it is a reasonable and parsimonious representative of the possible models.

The fit of the model to the gravity data is characterized by a median absolute deviation (MAD) of 1.2 mGal. Although this is larger than the accuracy of the gravity data themselves, it should be contrasted with the scatter in the data due to structural variation along strike (and extremely shallow structure which is unaccounted for in the model. Variation from these sources is on the order of 3-4 mGal. The maximum deviation of 11.5 mGal is clearly due to three-dimensional structural effects. The two-dimensional

model can be considered to represent the average structure in a 2 km-wide zone containing the cross-section. A less detailed model could be produced, which would fit the gravity data equally well, but would not reflect all the pertinent geologic information available.

The shot point and receiver locations are scattered in a much broader zone around the cross-section than the gravity data (Figure 3), but the travel times are somewhat less sensitive to the local variations. The velocity model that was fit is considerably less detailed than the density model. The travel times are fit with a MAD of 0.05 s, which is well within the uncertainties in the travel times, and the maximum deviation of 0.19 s is not unreasonable. Considerable latitude is possible in changes to this model, which will not significantly affect the fit to the observations.

Conclusions

The Bouguer gravity and sparse seismic travel time data have been useful in constructing a model of the 1-5 km deep structure under Pahute Mesa, Nevada. The use of known geologic structure for depths less than 1 km was essential in this process. The polygonal-basis modeling method used in this study has been very flexible. In the future, this forward modeling scheme will be incorporated with a nonlinear inversion method, for combined geophysical inversion of diverse geophysical data.

The new model indicates that the structure has more of the appearance of an asymmetrical graben than a classical caldera. This would be consistent with the hypothesis that the volcanic centers developed locally in a basin and range rift structure. Major structural relief on the pre-Tertiary surface, of 3-4 km, exists between Yucca Flat and Pahute Mesa. Most of this relief occurs in a zone between 25 and 30 km on the cross section (Figures 1, 4 and 5). This zone encompasses the Split Ridge, Scrugham Peak and Almendro faults. The proximity of explosion sources to similar fault-controlled structures at Yucca Flat, has been demonstrated to cause major seismic amplitude anomalies (Ferguson, 1988). The effect of the structure modeled here on seismic amplitudes needs further investigation.

References

- Anonymous, Observed seismic data Almendro event, Environmental Research Corp., Las Vegas, NV, NVO-1163-244, 1974.
- Barker, J. S., S. H. Hartzell, L. J. Burdick and D. V. Helmberger, Analysis of local seismic waveforms from underground nuclear explosions: forward modeling for effective source functions at Pahute Mesa, *J. Geophys. Res.*, 96, 10,129-10,143, 1991.
- Byers Jr., F. M., W. J. Carr and P. P. Orkild, Volcanic centers of southwestern Nevada: evolution of understanding, 1960-1988, *J. Geophys. Res.*, 94, 5908-5924, 1989.
- Carroll, R. D. and J. E. Magner, Velocity logging and seismic velocity of rocks in the Rainier Mesa area, Nevada Test Site, Nevada, USGS-OFR-88-380, 1988.
- Cerveny, V., I. A. Molotkov and I. Pesencik, *Ray Method in Seismology*, Univ. Karlova, Prague, 1977.
- Cormier, V. F., Focusing and defocusing of teleseismic P waves by known three-dimensional structure beneath Pahute Mesa, Nevada Test Site, *Bull. Seis. Soc. Am.*, 77, 1688-1703, 1987.
- Ferguson, J. F., R. N. Felch, C. L. V. Aiken, J. S. Oldow and H. Dockery, Models of the Bouguer gravity and geologic structure at Yucca Flat, Nevada, *Geophysics*, 53, 231-244, 1988.
- Ferguson, J. F., Body wave magnitude variation at Yucca Flat, Nevada, *Bull. Seis. Soc. Am.*, 78, 863-872, 1988.
- Hammer, S., Terrain corrections for gravimeter stations, *Geophysics*, 4, 184-194, 1939.
- Hardy, R. L., Multiquadric equations of topography and other irregular surfaces, *J. Geophys. Res.*, 76, 1905-1915, 1971.
- Harris, R. N., D. A. Ponce, D. L. Healey and H. W. Oliver, Principal facts for about 16,000 gravity stations in the Nevada Test Site and Vicinity, USGS-OFR-89-682-A,

1989.

Hartzell, S. H., L. J. Burdick and T. Lay, Effective source functions for Pahute Mesa nuclear tests, Woodward-Clyde Consultants, Pasadena, CA, WCCP-R-83-3, 1983.

Healey, D. L., Application of gravity data to geologic problems at Nevada Test Site, in Eckel, E. B., [editor], Nevada Test Site: Geol. Soc. Am. Memoir 110, 147-156, 1968.

Hoffman, L. R. and W. D. Mooney, A seismic study of Yucca Mountain and vicinity, southern Nevada; data report and preliminary results, USGS-OFR-83-588, 1984.

Leonard, M. A. and L. R. Johnson, Velocity structure of Silent Canyon caldera, Nevada Test Site, Bull. Seis. Soc. Am., 77, 597-613, 1987.

Lynnes, C. S. and T. Lay, Analysis of amplitude and travel-time anomalies for short period P-waves from NTS explosions, Geophys. J., 92, 431-443.

McLaughlin, K. L., L. M. Anderson and A. C. Lees, Effects of local geologic structure on Yucca Flats, Nevada Test Site, explosion waveforms: two-dimensional linear finite-difference simulations, Bull. Seis. Soc. Am., 77, 1211-1222, 1987.

Minster, J. B., J. M. Savino, W. L. Rodi, T. H. Jordan and J. F. Masso, Three-dimensional velocity structure of the crust and upper mantle beneath the Nevada Test Site, Systems, Science and Software, La Jolla, CA, SSS-R-81-5138, 1981.

Murthy, I. V. R. and D. B. Rao, Gravity anomalies of two-dimensional bodies of irregular cross-section with density contrast varying with depth, Geophysics, 44, 1525-1530, 1979.

Orkild, P. P., Byers Jr., F. M., D. L. Hoover and K. A. Sargent, Subsurface geology of Silent Canyon caldera, Nevada Test Site, Nevada, in Eckel, E. B., [editor], Nevada Test Site: Geol. Soc. Am. Memoir 110, 77-86, 1968.

Perret, W. R., Surface motion induced by nuclear explosions beneath Pahute Mesa, Part I, SLA-74-0348, 1976.

- Perret, W. R., Surface motion induced by nuclear explosions beneath Pahute Mesa, Part II, SLA-74-0348, 1983.
- Plouff, D., Preliminary documentation for a FORTRAN program to compute gravity terrain corrections based on topography digitized on a geographic grid, USGS-OFR-77-535, 1977.
- Qin, F., Y. Luo, K. B. Olsen, W. Cai, and G. T. Schuster, Finite-difference solution of the eikonal equation along expanding wavefronts, *Geophysics*, 57, 478-487.
- Reamer, S. K. and J. F. Ferguson, Regularized two-dimensional Fourier gravity inversion method with application to the Silent Canyon caldera, Nevada, *Geophysics*, 54, 486-496, 1989.
- Snyder, D. B. and W. J. Carr, Interpretation of gravity data in a complex volcano-tectonic setting, southwestern Nevada, *J. Geophys. Res.*, 89, 10,193-10,206, 1984.
- Spence, W., P-wave residual differences and inferences on an upper mantle source for the Silent Canyon volcanic center, southern Great Basin, Nevada, *Geophys. J. R. Astr. Soc.*, 38, 505-523, 1974.
- Stump, B. W. and L. R. Johnson, Near-field source characterization of contained nuclear explosions in tuff, *Bull. Seis. Soc. Am.*, 74, 1-26, 1984.
- Taylor, S. R., Three-dimensional crust and upper mantle structure at the Nevada Test Site, *J. Geophys. Res.*, 88, 2220-2232, 1983.
- Velleman, P. F. and D. C. Hoaglin, *Applications, Basics, and Computing of Exploratory Data Analysis*, Duxbury Press, Boston, MA, 1981.
- Vidale, J., Finite-difference calculation of travel times, *Bull. Seis. Soc. Am.*, 78, 2062-2076, 1988.
- Warren, R. G., F. M. Byers, Jr. and P. P. Orkild, Post-Silent Canyon caldera structural setting for Pahute Mesa, *Proc. 3rd Symp. on Containment of Underground Nuclear Explosions*, Volume 2, 3-30, 1985.




Figure 1. Generalized geologic cross section for the transect at Pahute Mesa, Nevada shown in Figure 2. Thc, Tma and Tmr are units from the Black Mountain and Timber Mountain volcanic centers. Pt and Ti are Paleozoic sedimentary and Tertiary intrusive rocks. The Pc is associated with the collapse of the Silent Canyon caldera.






Figure 2. Bouguer gravity (reduced at 2000 kg/m³) anomaly map for Pahute Mesa, Nevada. The contour interval is 2 mGal. The location of the geophysical transect is delimited by A to A'.



+ Observed
 --- Calculated


Maximum Absolute Error = 11.486
 Mean Error = -0.985
 Standard Deviation = 2.335
 Median Error = -1.132
 Median Absolute Deviation = 1.208



Density in gm/cm^3
 Depth Relative to 1.9 km Elevation


$1.50+0.740z$	$2.10+0.050z$
$1.55+0.175z$	$2.15+0.000z$
$1.66+0.400z$	$2.25+0.100z$
$1.70+0.000z$	$2.30+0.075z$
$1.80+0.000z$	$2.45+0.025z$
$1.95+0.100z$	$2.55+0.175z$
$2.04+0.000z$	$2.63+0.000z$
	$2.65+0.014z$

Figure 4. A profile of the observed gravity data, with 2 km of the transect in Figure 2 (+'s) and the anomaly calculated from the density distribution in the cross section below.



△ Alamo
 γ Almendro
 □ Boxcar
 ☆ Farm
 ○ Scotch
 * Kernville
 + PMSE86
 — Calculated

Maximum Absolute Error = 0.188
 Mean Error = 0.031
 Standard Deviation = 0.070
 Median Error = 0.012
 Median Absolute Deviation = 0.051



Velocity in km/s
 Depth Relative to 1.9 km Elevation

1.70+2.222 z	2.98+0.600 z
2.09+1.860 z	3.52+0.235 z
	5.50+0.050 z

Figure 5. The observed P-wave travel times for the shots and receivers in Figure 3 and the computed travel time curves for the velocity distribution in the cross section below.




Figure 6. Vertical profiles of velocity and density from the model in Figures 4 and 5. P- and S-wave velocity and density relations for Pahute Mesa, Nevada from the seismological literature are on the bottom row, along with logs from a deep well, ue20f, which is south of the western portion of the transect.

**Geodetic Experiments on Nevada Test Site Events Using the
Global Positioning System**

**J. F. Ferguson¹, D. G. Ziegler¹, C. L. V. Aiken¹
and A. H. Cogbill²**

Final Technical Report: Part II

**1 The University of Texas at Dallas
Richardson, TX**

**2 Los Alamos National Laboratory
Los Alamos, NM**

Introduction

Underground nuclear explosions produce considerable deformation in their vicinity. Patterns of dilatation due to cavity formation, fracturing and subsidence due to cavity collapse, as well as motion on pre-existing faults are regularly observed. Geodetic studies of this deformation have been made on several occasions in the past 30 years, including Dickey (1969; 1971), Savage et al. (1974) and Krier et al. (1987). In addition to strong motion seismograms, post-shot fracture mapping and aftershock seismicity, geodetic studies provide important constraints on the nature of explosion induced deformation, which may be due to tectonic release or block motion (Massey, 1981). In some respects, nuclear testing provides a natural laboratory for the study of fault mechanics.

This report will discuss two new surveys made for the events BULLION (13 June 1990) and BEXAR (4 April 1991). The locations of these events are shown in Figure 1. Geodetic measurements for these events were made using the new Global Positioning System (GPS) satellite navigation technology. These experiments were intended to demonstrate the efficacy and efficiency of rapid GPS survey methodology in Earth deformation studies.

Explosion Mechanics

The phenomena associated with a contained, underground explosion are summarized below. The scaled depth of burial is

$$d_s = d / W^{1/3},$$

where yield, W , is given in kilotons (kt). Houser (1969) states that for scale depths greater than about $60 \text{ m/kt}^{1/3}$, no excavated crater is formed and for $d_s > 90 \text{ m/kt}^{1/3}$, the explosion is effectively contained, for conditions at Yucca Flat, Nevada (overburden density of between 1800 and 2100 kg/m^3).

Immediately following the detonation, a spherical cavity is formed, with radius proportional to $W^{1/3}$. Mueller and Murphy (1971) provide the relationship,

$$r_c = 28.0 W^{0.29} d^{-0.11},$$

with depth and radius in meters. Intense fracturing occurs around the cavity, with an inner crushed zone tapering into a radial fracture pattern. Fracture opening is limited by the build-up of hoop stresses caused by the compression wave radiating from the explosion. Borg (1973) indicates that the radius of pervasive fracturing is between 2.7 to 3.5 r_c . Thrust faults may be formed in a conical zone (45° dip) above the cavity by the outgoing compressional wave. Evidence of this thrusting is found in moment tensor

solutions for several explosions (Massey, 1981).

The compression wave, when reflected from the free surface, produces a tensile failure at depth. A slab of material is separated and propelled in free fall, from whence it subsequently "slaps down". This spall phenomena extends to a radius of one or two depths of burial around the epicenter. There may be more than one spalled slab and the spall zone may not be cylindrically symmetric due to local structural weakness.

After the event, there may be a net doming over the shot point due to the dilation associated with the fracturing. This may be very short lived due to the instability of the cavity at depth. For explosions above a certain scale depth, approximately $300 \text{ m/kt}^{1/3}$ at Yucca Flat, Nevada, (Houser, 1969), the cavity will collapse and the void will migrate upward. If collapse extends to the surface, a collapse crater, with a volume similar to the original cavity, will remain. Collapse craters are the rule at Yucca Flat, in alluvium, but are rare at Pahute Mesa, with more competent volcanic rocks at the surface. In either event, there may be a resulting net subsidence over the shot point.

In addition to the tension cracks formed by the explosion, pre-existing, natural fractures, either joints or

faults, may be activated. New fracture patterns are often closely associated with existing fractures (Barosh, 1968 and Bucknam, 1969). Modest size blocks of rock may respond passively to the explosion (i. e. they are simply pushed around) or regional tectonic strain may be released (i. e. an earthquake is triggered). Considerable controversy has surrounded the tectonic release hypothesis and geodetic measurements may have some bearing on the resolution of the debate (Massey, 1981).

Dickey (1969) observed that explosions within $300 \text{ W}^{1/3}$ m of the Yucca fault would initiate fault displacement. Rupture seems to only occur within the spall zone (Weaver, personal communication). At Pahute Mesa the empirical relationship between fault length and yield or magnitude was investigated by McKeown and Dickey (1969). The SCOTCH test in 1969 had a body wave magnitude of 5.7 (PDE) and a yield of 155 kt, just above the current treaty limit of 150 kt. This event ruptured the U19as fault (later termed the Scotch fault) for about 1.5 km. This could be taken to an upper limit of rupture to be expected from the BULLION and BEXAR events. The post-shot fracture map for BULLION shows rupture on the West Greeley fault over a total distance of 2.7 km in several discontinuous segments, however the distance from the explosion hypocenter to the fault is only about 0.5 km.

Previous Geodetic Studies

Early applications of geodetic methods were to the large, megaton scale explosions BENHAM (Dickey, 1969), JORUM (Dickey, 1971) and HANDLEY (Savage et al., 1974) at Pahute Mesa, Nevada. In Dickey's work quadrilateral strain figures, one or two kilometers across were deployed within 18 km of the explosion epicenter using electronic distance measuring instruments. The horizontal components of strain were computed from displacements within these figures. Attempts were made to resolve the strain into contributions due to cavity expansion and dislocations on known faults. During BENHAM, a level line was run through the epicentral region, which demonstrated a general subsidence of up to 0.76 m, with differential motion on faults of up to 0.5 m.

During the JORUM experiment a 2 km line, located about 10 km southwest of the epicenter, was monitored continuously for 5 days, starting 5.5 hours after the test. Several steps in displacement were recorded, one of which seemed to be associated with an aftershock of magnitude 2.25.

The HANDLEY survey (Savage et al., 1974) was performed on a much larger scale. A network of seven stations and seventeen baselines was established, with a 30 km aperture enclosing the test location. All baselines were measured with a Geodolite. Atmospheric measurements were

simultaneously made from aircraft in order to correct for refraction effects. Five repeat surveys were made starting two weeks after the test, with the last made three years later. A relaxation of baseline lengths was observed within two years of the test. Initial changes of up to -247 mm, underwent some reductions and even reversals. Massey (1981) has used this as evidence against the tectonic release hypothesis, suggesting that the pre-shot fault configuration had long term stability.

A more recent examples of geodetic surveys are found in Krier et al. (1987). Two Yucca Flat explosions, KINIBITO and GLENCOE were surveyed prior to and after the tests. In both cases dense lines of stations were established perpendicular to the strike of nearby faults (generally north-south), north, south and east (the fault side) of the explosion epicenter. Horizontal displacements were determined by electronic distance meter and elevations were determined by leveling. Strike-slip motion on the faults was evident, as well as vertical displacements. A general radial, outward displacement was also observed. Differential compaction of alluvium, in a surface layer which thickens across the faults, was thought to be responsible for much of the vertical displacement.

GPS Methodology

The Global Positioning System is the latest and best of a series of satellite based navigation systems deployed by the Department of Defense. Details of the operation of the system may be found in Lambeck (1988) and Leick (1990). A good summary is contained in Dixon (1991) and an even briefer summary will be presented here. A constellation of satellites orbits the Earth at 20,000 km altitude, in six orbital planes. At least eight of the satellites will be visible to an observer on the surface at any time, although the incomplete constellation at the time of the surveys presented here did not provide this kind of 24 hour coverage. A GPS receiver contains a clock, as do all of the satellites. Positioning is achieved by synchronization of the clocks through signals broadcast by the satellites. The ranges to the satellites are determined by the travel times of the radio waves, since the satellite positions are known through ephemeris data broadcast by the satellites. These positions are accurate to tens of meters, however the coded military signals provide positions which are about ten times better, but neither are sufficient for geodetic purposes.

Highly accurate relative positions are achieved by comparing the signal phase between two receivers during post-processing of recorded tracking data (double difference

carrier phase processing). The linear equations which determine the position from the travel times are differenced between receivers and satellites (double difference) and the new equations solved for relative position from the phase differences. One or more receivers are set up at known, base locations and one or more receivers can rove between points to be determined. The use of phase differences results in an ambiguity in the roving receiver's position due to the unknown number of cycles or wavelengths present for each satellite. At any observation epoch, hundreds of wavefront intersection points will lie within a few meters of the true position, one of which is correct. The problem is to resolve this ambiguity through redundant measurements of some kind.

Once the correct solution is found, baselines can be measured to within centimeters and even millimeters over distances of thousands of kilometers. Elevations are less well determined, because satellites below the receiver are not visible, but even so, centimeter accuracy is possible. The GPS system actually has set new standards for survey performance, when compared to conventional optical methods. The previous highest grade of survey, termed first order first class, three new GPS based levels exist above, now called B, A and AA (FGCC, 1989). Advantages also accrue from the necessity for vertical rather than horizontal visibility

and the fact that measurement errors do not accumulate within a network of stations, each measurement being independent (although changes in the satellite configuration determine the precision). Errors due to ionospheric dispersion are correctable by the use of a dual frequency system. All satellites broadcast simultaneously on the L1 (1575.42 MHz) and L2 (1227.60 MHz) channels. Errors due to the lower, neutral atmosphere (troposphere) are probably not too important for the short (< 10 km) baselines involved in these experiments.

Several modes of data acquisition are possible. The most widely used to date has been the static mode. Recordings are made for extended periods of time, at the base and unknown locations, while both receivers remain stationary. For baselines of a few kilometers the recording time may be tens of minutes, but for long baselines of hundreds of kilometers the recording time may be hours. While this method is very effective, it is also very slow. In this study we endeavored to employ two more rapid techniques.

The kinematic method depends on the receiver maintaining continuous lock on the satellite signals, while it is moved from place to place. A brief pause (30 to 120 s) at each monument to be positioned is all that is required,

as the receiver position is continuously maintained in transit. The survey is initialized on a known, short baseline, often through a swapping of the antennas on the base and roving receivers. Another approach, used in this study, was to establish a station by the static method, which is then used as a known baseline to initialize the signal phase. Any station known to within 5 cm could be used for this purpose. It is difficult in practice to maintain lock on at least four satellites, due to the fact that the high frequency radio signals are easily blocked by topography, trees, buildings, vehicles and people (Balde et al., 1992).

The dual occupation, rapid static method (Mader, 1992; Ziegler, 1992) seems to be the most satisfactory of the techniques, in that occupation times are brief and continuous signal lock is not required. In this method each monument is visited twice, at least 45 minutes between visits, so that the satellite configuration will have changed. A systematic search of the so called ambiguity function, permits the resolution of the integer phase ambiguity at each station (Mader, 1992 and Talbot, 1991). The BULLION survey utilized both the kinematic and rapid static methods, although rapid static type data was acquired at all stations. The BEXAR survey was based entirely on the

rapid static method. Some static solutions were employed for base station ties to external monuments in both surveys.

Baselines were generally much less than 10 km and thus presented few difficulties with atmospheric related errors. Dual frequency receivers were used at all times, so that corrections for ionospheric dispersion could be made, if necessary. All solutions reported here are L1 only, except for the statically determined baseline between stations STAR and 20, in the BULLION survey. Errors involving deficiencies in the satellite configuration were reduced by a careful choice of the time window for data collection. The dilution of precision is monitored continuously in the receiver and whenever limits were exceeded, surveying was discontinued until the values improved. This would usually entail a wait of up to an hour or so, until the satellite configuration would again be satisfactory. During 1990 and 1991 the satellite constellation was incomplete, so that only a limited time window of 8 to 10 hours per day was available, often at night.

The monuments surveyed were temporarily established, especially for these projects, with the exception of a few permanent monuments of long standing. The permanent monuments are maintained by Holmes and Narver, Inc., for operations at NTS. Where possible a brass cap was bonded to

rock outcrop with silicone cement. In the BULLION survey, small wooden hubs, with a punched nail inset, were emplaced in soil covered areas. In the BEXAR survey, lengths of steel reinforcing rod were driven into soil covered areas and topped with a marked plastic cap. All of these monuments were apparently quite stable over the short period of two or three months between repeat surveys.

Structural Setting

Pahute Mesa, Nevada is located at the site of a complex volcanic center, with several collapse features buried under a blanket of younger tuffs from the Timber and Black Mountain volcanic centers (Orkild et al. 1968). These features are further dissected by Basin and Range extension along north-south trending faults, which creates an asymmetrical (deeper on the west) graben structure (Warren et al., 1985). East-west trending structures have been recognized at Pahute Mesa as well (Warren, personal communication). These appear to be related to the buried caldera structures and result in abrupt changes in the thickness of units within the fill and the truncation of north-south trending faults. Although these so called shear zones have been active until the most recent units were emplaced, they do not result in mappable fault traces, perhaps due to the unfavorable orientation of the current stress field.

While the north-south faults almost always localize deformation during the nuclear tests, there is evidence that the east-west trending shear zones respond as well. Fractures do not open along the shear zones, but compressional features do form. These have been termed pressure ridges and often form en echelon patterns along the

trend of the shear zones. Figure 2, adapted from Maldonado (1977), shows postshot fracture maps from FONTINA (m_b 6.3) and MUENSTER (m_b 6.2). The FONTINA test, located about 6 km west and 1 km north of BULLION, shows pressure ridges on the trend of the East Thirsty Canyon shear zone. MUENSTER is about 2.5 km due west of BEXAR and produced pressure ridges on the northwest-southeast trending Silent Canyon shear zone.

The BULLION test was located near the deepest portion of the volcanic fill and only half a kilometer west of a major Basin and Range fault, the West Greeley fault. Another, similar but more minor fault is located about the same distance to the west (Figure 3). Both faults dip to the west at a high angle. The BULLION working point was just below the water table at a depth of 687 m.

Nuclear tests in the vicinity of BULLION are displayed in Figure 4, with body wave magnitudes and names plotted. The West Greeley fault, just to the east of BULLION, has been activated by numerous tests in the past. The 825 kiloton test GREELEY ruptured 6 kilometers of the fault on 20 December 1966. This previous history of testing may have a substantial effect on motion during subsequent events.

Results of the BULLION Survey

The 31 stations shown in Figure 3, were occupied both pre- and post-BULLION in June and July of 1990. STAR and CROW are permanent monuments with conventionally surveyed locations. Stations 15 (not shown) and 24 were also occupied by accelerometers during the test. Vertical displacement profiles have been constructed along lines 1, 2 and 3.

A total of 32 stations were successfully positioned in the BULLION survey. In the before and after the event surveys we then have 64 total solutions, of these 40 were solved at least two times. These repeat measurements form the basis for an analysis of the reliability of the solutions. Final values for the displacement estimates were formed by taking simple averages of the repeated measurements. The absolute values of the maximum coordinate differences were used in the repeatability analysis. Rank order statistics were then applied to characterize the error distribution. The results are summarized in Table I. Vertical spread refers to the maximum absolute elevation error, horizontal spread refers to the vector magnitude of the horizontal coordinate maximum absolute differences and total spread is the vector magnitude of all three coordinate maximum, absolute differences.

The results in Table I indicate that the error

distribution is skewed to the high side. While 50% of the vertical and horizontal repetitions are less than 1.5 cm apart, 75% are less than 2.5 cm apart, but errors range up to 6 cm. It can be assumed, for the purposes of this study, that displacements in Figures 5 and 6 greater than about 3 or 4 cm represent a true geophysical signal. A similar analysis of the stations monumented with wooden hubs versus those stations with brass caps bonded to rock, indicates that the brass caps are somewhat more stable. If all stations had been founded on rock the error might have been reduced by about 1 or 2 cm. Due to the limited nature of the repeatability test and the fact that solutions were obtained by two different analysts (D. G. Z. and C. L. V. A.), with two different computer codes (the National Geodetic Survey's Omni and Trimble Navigation's Trimvec) and two different methods (kinematic and rapid static) variously applied at each station, it is best not to put too much stress on this analysis. It is apparent, however, that usable geophysical measurements were obtained.

Scaled, horizontal displacement vectors, due to the nuclear test BULLION are plotted in Figure 5. These horizontal components of motion are generally much larger than the observed vertical displacements. Although motion is observed that is consistent with right-lateral movement on

the West Greeley fault (500 m east of BULLION), the predominant transport in the northern part of the map is to the west. This motion is consistent with left-lateral motion on the East Thirsty Canyon shear zone. This conclusion is well supported by the data and is quite surprising. Transport toward ground zero is also somewhat unexpected and may be related to observed subsidence.

The vertical displacements due to the nuclear test BULLION have been profiled in Figure 6. The pattern shown on these profiles is rather complicated and not well represented by the sampling scheme employed. Line 1 is normal to the mapped structure, but parallel to the suspected East Thirsty Canyon shear zone. Lines 2 and 3 are both parallel, and very close, to mapped faults. Significant displacements are observed in both an absolute and a relative sense. In line 1 subsidence is observed between normal faults north of ground zero. Up and down motion, with a wavelength of approximately 1.5 kilometers, is observed on normal faults on the east and west of ground zero. Station 12 appears to be an outlier, distinct from the pattern. Stations 16 and 33, with more significantly anomalous behavior (vertical displacement of -43 cm at station 16 and horizontal displacement of 55 cm at station 33) were edited from these results. These two stations are located on the

steep hillside, adjacent to the West Greeley fault and seem to have been involved in a slumping phenomena.

The BEXAR Survey

The nuclear test BEXAR was executed on 4 April 1991, prior to the test in February and after the test in May, the network displayed in Figure 7 was surveyed. Most of the locations in this network were also occupied by accelerometers or seismometers during the test. The design of this survey was influenced by several perceived limitations in the BULLION survey. The overall aperture of the network is greater, about 10 km as opposed to 3 km. The stations are more randomly distributed, although a rough north-south and two east-west lines may be drawn through the stations. In compromise, the sample density is much less, even on the transect lines.

During the surveys two base stations were occupied at all times, so that a greater strength and redundancy results. It will be possible to perform a meaningful least squares network adjustment on these data. All stations were occupied at least twice, during each survey. All processing of these data will be by the ambiguity function method (Mader, 1992). No attempt was made to maintain signal lock for kinematic processing. The network was tied to a station located well outside of the expected deformation, about 20 km to the south. Three permanent monuments were included in the network.

The results of this survey are not yet available, but it is expected to be as successful as the BULLION survey and possibly more informative. The data will be examined for deformation along the Silent Canyon shear zone, as well as on the mapped north-south trending faults.

Conclusions

The utility of GPS positioning, in rapid static and kinematic modes has been demonstrated. It is possible to obtain data from networks of around 50 stations, with an aperture of 10 km, in several days of effort.

Significant displacement vectors were obtained in the BULLION survey. Horizontal motions of up to 20 cm and vertical motions of up to 10 cm were observed. Resolution was found to be on the order of a few cm. Deformation was observed along known faults and unexpectedly along the East Thirsty Canyon shear zone. The limited spacial coverage of these data have somewhat limited the interpretation, but the results do prove the effectiveness of the methods employed.

These surveys are the first earth deformation studies to employ the rapid static method. The results obtained have verified the confidence placed in the methods. The possibility of performing more rapid surveys, on both nuclear tests and in post-earthquake studies, is now open. It would be of particular interest to utilize the rapid survey methods to repeatedly survey certain monuments in the post-event phase to look for time dependent effects.

References

- Balde, M., C. Aiken, D. Ziegler, J. Hare, S. Cates and W. Gosnold, (1992), Pseudo-Kinematic GPS positioning of a gravity survey in North Dakota, Proc. 6th Int. Geod. Symp. on Satellite Positioning, Ohio State Univ., Columbus, OH.
- Barosh, P. J., (1968), Relationships of explosion-produced fracture patterns to geologic structure in Yucca Flat, Nevada Test Site, in *Nevada Test Site*, Eckel, E. B., ed., Geol. Soc. Am. Mem. 110, Boulder, CO.
- Borg, I. Y., (1973), Extent of pervasive fracturing around underground nuclear explosions, *Int. J. Rock Mech. Min. Sci.*, v 10, p 11-18.
- Bucknam, R. C., (1969), Geologic effects of the BENHAM underground nuclear explosion, *Bull. Seis. Soc. Am.*, v 59, p 2209-2219.
- Dickey, D. D., (1969), Strain associated with the BENHAM nuclear explosion, *Bull. Seis. Soc. Am.*, v 59, p 2209-2219.
- Dickey, D. D., (1971), Strain accompanying the JORUM underground nuclear explosion and its relation to geology, *Bull. Seis. Soc. Am.*, v 61, p 1571-1581.
- Dixon, T. H., (1991), An introduction to the Global Positioning System and some geological applications, *Rev. Geophys.*, v 29, p 249-276.
- Federal Geodetic Control Committee, (1989), Geometric geodetic accuracy standards and specifications for using GPS relative positioning technique, ver. 5.0, National Geodetic Information Center, Rockville, MD.
- Houser, F. N., (1969), Subsidence related to underground nuclear explosions, Nevada Test Site, *Bull. Seis. Soc. Am.*, v 59, p 2231-2251.
- Krier, D. J., F. N. App and L. Medina, (1987), Pre- and post-event elevation and horizontal surveys across the Yucca and Topgallant faults, Nevada Test Site, LA-CP-87-182, Los Alamos National Laboratory, Los Alamos, NM.
- Lambeck, K., (1988), *Geophysical Geodesy: The Slow Deformations of the Earth*, Oxford, Oxford, UK.

- Leick, A., (1990), *GPS Satellite Surveying*, Wiley, New York.
- Mader, G. L., (1992), Rapid static and kinematic Global Positioning System solutions using the ambiguity function technique, *J. Geophys. Res.*, v 97, p 3271-3283.
- Maldonado, F. (1977), Composite postshot fracture map of Pahute Mesa, Nevada Test Site, June 1973 through March 1976, USGS-474-243, U. S. Geological Survey, Denver, CO.
- Massey, R. P., (1981), Review of seismic source models for underground nuclear explosions, *Bull. Seis. Soc. Am.*, v 71, p 1249-1268.
- McKeown, F. A. and D. D. Dickey, (1969), Fault displacements and motion related to nuclear explosions, *Bull. Seis. Soc. Am.*, v 59, p 2253-2269.
- Mueller, R. A. and J. R. Murphy, (1971), Seismic characteristics of underground nuclear detonations: Part I seismic spectrum scaling, *Bull. Seis. Soc. Am.*, v 61, p 1675-1692.
- Orkild, P. P., F. M. Byers, Jr., D. L. Hoover, and K. A. Sargent, (1968), Subsurface geology of Silent Canyon caldera, in *Nevada Test Site*, Eckel, E. B., ed., Geol. Soc. Am. Mem. 110, Boulder, CO.
- Savage, J. C., W. T. Kinoshita and W. H. Prescott, (1974), Geodetic determination of strain at the Nevada Test Site following the HANDLEY event, *Bull. Seis. Soc. Am.*, v 64, p 115-129.
- Talbot, N. C., (1991), Sequential phase ambiguity resolution for real-time static differential GPS positioning, *Man. Geod.*, v 16, p274-282.
- Warren, R. G., F. M. Byers, Jr. and P. P. Orkild, (1985), Post-Silent Canyon caldera structural setting for Pahute Mesa, Proc. 3rd Symp. on Containment of Underground Nuclear Explosions, v 2, p 3-30.
- Ziegler, D., R. Hunt and C. Aiken, (1992), Rapid GPS positioning of a gravity survey in the South Georgia Basin, Georgia, using the ambiguity function technique, Proc. 6th Int. Geodetic. Symp. on Satellite Positioning, Ohio State Univ., Columbus, OH.

Table I

Spread	Minimum	1st Quartile	Median	3rd Quartile	Maximum
Vertical	0	3	10	21	41
Horizontal	4	9	14	25	59
Total	5	11	18	30	67

Units are millimeters

Total of 40 points

Table I. Rank order statistics for the maximum coordinate differences among the repeated stations of the BULLION survey.




Figure 1. Location of the nuclear tests BULLION and BEXAR. The outline of the Silent Canyon caldera and the major north-south trending faults are shown for reference.




Figure 2. Post-event fracture maps for the tests FONTINA on the right and MUENSTER on the left (after Maldonado, 1977).




Figure 3. The network of monuments established for the BULLION survey. Faults which have been mapped in the vicinity are also shown on the figure. Lines 1, 2 and 3 are used for vertical displacement profiles in Figure 6.




Figure 4. Locations of previously detonated explosions near BULLION. The body wave magnitude is shown as a rough measure of explosion size.




Figure 5. Horizontal displacements due to the explosion BULLION.
A 10 cm vector is displayed at the bottom for scale.




Figure 6. Vertical displacements due to the explosion BULLION on profile lines 1, 2 and 3, which are located on Figure 3.

DISTRIBUTION LIST

Prof. Thomas Ahrens
Seismological Lab, 252-21
Division of Geological & Planetary Sciences
California Institute of Technology
Pasadena, CA 91125

Prof. Keiiti Aki
Center for Earth Sciences
University of Southern California
University Park
Los Angeles, CA 90039-0741

Prof. Shelton Alexander
Geosciences Department
403 Deike Building
The Pennsylvania State University
University Park, PA 16802

Dr. Ralph Alewine, III
DARPA/NMRO
3701 North Fairfax Drive
Arlington, VA 22203-1714

Prof. Charles B. Archambeau
CIRES
University of Colorado
Boulder, CO 80309

Dr. Thomas C. Bache, Jr.
Science Applications Int'l Corp.
10260 Campus Point Drive
San Diego, CA 92121 (2 copies)

Prof. Muawia Barazangi
Institute for the Study of the Continent
Cornell University
Ithaca, NY 14853

Dr. Jeff Barker
Department of Geological Sciences
State University of New York
at Binghamton
Vestal, NY 13901

Dr. Douglas R. Baumgardt
ENSCO, Inc
5400 Port Royal Road
Springfield, VA 22151-2388

Dr. Susan Beck
Department of Geosciences
Building #77
University of Arizona
Tucson, AZ 85721

Dr. T.J. Bennett
S-CUBED
A Division of Maxwell Laboratories
11800 Sunrise Valley Drive, Suite 1212
Reston, VA 22091

Dr. Robert Blandford
AFTAC/TT, Center for Seismic Studies
1300 North 17th Street
Suite 1450
Arlington, VA 22209-2308

Dr. G.A. Bollinger
Department of Geological Sciences
Virginia Polytechnical Institute
21044 Derring Hall
Blacksburg, VA 24061

Dr. Stephen Bratt
Center for Seismic Studies
1300 North 17th Street
Suite 1450
Arlington, VA 22209-2308

Dr. Lawrence Burdick
Woodward-Clyde Consultants
566 El Dorado Street
Pasadena, CA 91109-3245

Dr. Robert Burrige
Schlumberger-Doll Research Center
Old Quarry Road
Ridgefield, CT 06877

Dr. Jerry Carter
Center for Seismic Studies
1300 North 17th Street
Suite 1450
Arlington, VA 22209-2308

Dr. Eric Chael
Division 9241
Sandia Laboratory
Albuquerque, NM 87185

Prof. Vernon F. Cormier
Department of Geology & Geophysics
U-45, Room 207
University of Connecticut
Storrs, CT 06268

Prof. Steven Day
Department of Geological Sciences
San Diego State University
San Diego, CA 92182

Marvin Denny
U.S. Department of Energy
Office of Arms Control
Washington, DC 20585

Dr. Cliff Frolich
Institute of Geophysics
8701 North Mopac
Austin, TX 78759

Dr. Zoltan Der
ENSCO, Inc.
5400 Port Royal Road
Springfield, VA 22151-2388

Dr. Holly Given
IGPP, A-025
Scripps Institute of Oceanography
University of California, San Diego
La Jolla, CA 92093

Prof. Adam Dziewonski
Hoffman Laboratory, Harvard University
Dept. of Earth Atmos. & Planetary Sciences
20 Oxford Street
Cambridge, MA 02138

Dr. Jeffrey W. Given
SAIC
10260 Campus Point Drive
San Diego, CA 92121

Prof. John Ebel
Department of Geology & Geophysics
Boston College
Chestnut Hill, MA 02167

Dr. Dale Glover
Defense Intelligence Agency
ATTN: ODT-1B
Washington, DC 20301

Eric Fielding
SNEE Hall
INSTOC
Cornell University
Ithaca, NY 14853

Dr. Indra Gupta
Teledyne Geotech
314 Montgomery Street
Alexandria, VA 22314

Dr. Mark D. Fisk
Mission Research Corporation
735 State Street
P.O. Drawer 719
Santa Barbara, CA 93102

Dan N. Hagedorn
Pacific Northwest Laboratories
Battelle Boulevard
Richland, WA 99352

Prof Stanley Flate
Applied Sciences Building
University of California, Santa Cruz
Santa Cruz, CA 95064

Dr. James Hannon
Lawrence Livermore National Laboratory
P.O. Box 808
L-205
Livermore, CA 94550

Dr. John Foley
NER-Geo Sciences
1100 Crown Colony Drive
Quincy, MA 02169

Dr. Roger Hansen
HQ AFTAC/TTR
Patrick AFB, FL 32925-6001

Prof. Donald Forsyth
Department of Geological Sciences
Brown University
Providence, RI 02912

Prof. David G. Harkrider
Seismological Laboratory
Division of Geological & Planetary Sciences
California Institute of Technology
Pasadena, CA 91125

Dr. Art Frankel
U.S. Geological Survey
922 National Center
Reston, VA 22092

Prof. Danny Harvey
CIRES
University of Colorado
Boulder, CO 80309

Prof. Donald V. Helmberger
Seismological Laboratory
Division of Geological & Planetary Sciences
California Institute of Technology
Pasadena, CA 91125

Prof. Eugene Herrin
Institute for the Study of Earth and Man
Geophysical Laboratory
Southern Methodist University
Dallas, TX 75275

Prof. Robert B. Herrmann
Department of Earth & Atmospheric Sciences
St. Louis University
St. Louis, MO 63156

Prof. Lane R. Johnson
Seismographic Station
University of California
Berkeley, CA 94720

Prof. Thomas H. Jordan
Department of Earth, Atmospheric &
Planetary Sciences
Massachusetts Institute of Technology
Cambridge, MA 02139

Prof. Alan Kafka
Department of Geology & Geophysics
Boston College
Chestnut Hill, MA 02167

Robert C. Kemerait
ENSCO, Inc.
445 Pineda Court
Melbourne, FL 32940

Dr. Max Koontz
U.S. Dept. of Energy/DP 5
Forrestal Building
1000 Independence Avenue
Washington, DC 20585

Dr. Richard LaCoss
MIT Lincoln Laboratory, M-200B
P.O. Box 73
Lexington, MA 02173-0073

Dr. Fred K. Lamb
University of Illinois at Urbana-Champaign
Department of Physics
1110 West Green Street
Urbana, IL 61801

Prof. Charles A. Langston
Geosciences Department
403 Deike Building
The Pennsylvania State University
University Park, PA 16802

Jim Lawson, Chief Geophysicist
Oklahoma Geological Survey
Oklahoma Geophysical Observatory
P.O. Box 8
Leonard, OK 74043-0008

Prof. Thorne Lay
Institute of Tectonics
Earth Science Board
University of California, Santa Cruz
Santa Cruz, CA 95064

Dr. William Leith
U.S. Geological Survey
Mail Stop 928
Reston, VA 22092

Mr. James F. Lewkowicz
Phillips Laboratory/GPEH
Hanscom AFB, MA 01731-5000(2 copies)

Mr. Alfred Lieberman
ACDA/VI-OA State Department Building
Room 5726
320-21st Street, NW
Washington, DC 20451

Prof. L. Timothy Long
School of Geophysical Sciences
Georgia Institute of Technology
Atlanta, GA 30332

Dr. Randolph Martin, III
New England Research, Inc.
76 Olcott Drive
White River Junction, VT 05001

Dr. Robert Masse
Denver Federal Building
Box 25046, Mail Stop 967
Denver, CO 80225

Dr. Gary McCartor
Department of Physics
Southern Methodist University
Dallas, TX 75275

Prof. Thomas V. McEvilly
Seismographic Station
University of California
Berkeley, CA 94720

Dr. Art McGarr
U.S. Geological Survey
Mail Stop 977
U.S. Geological Survey
Menlo Park, CA 94025

Dr. Keith L. McLaughlin
S-CUBED
A Division of Maxwell Laboratory
P.O. Box 1620
La Jolla, CA 92038-1620

Stephen Miller & Dr. Alexander Florence
SRI International
333 Ravenswood Avenue
Box AF 116
Menlo Park, CA 94025-3493

Prof. Bernard Minster
IGPP, A-025
Scripps Institute of Oceanography
University of California, San Diego
La Jolla, CA 92093

Prof. Brian J. Mitchell
Department of Earth & Atmospheric Sciences
St. Louis University
St. Louis, MO 63156

Mr. Jack Murphy
S-CUBED
A Division of Maxwell Laboratory
11800 Sunrise Valley Drive, Suite 1212
Reston, VA 22091 (2 Copies)

Dr. Keith K. Nakanishi
Lawrence Livermore National Laboratory
L-025
P.O. Box 808
Livermore, CA 94550

Dr. Carl Newton
Los Alamos National Laboratory
P.O. Box 1663
Mail Stop C335, Group ESS-3
Los Alamos, NM 87545

Dr. Bao Nguyen
HQ AFTAC/TTR
Patrick AFB, FL 32925-6001

Prof. John A. Orcutt
IGPP, A-025
Scripps Institute of Oceanography
University of California, San Diego
La Jolla, CA 92093

Prof. Jeffrey Park
Kline Geology Laboratory
P.O. Box 6666
New Haven, CT 06511-8130

Dr. Howard Patton
Lawrence Livermore National Laboratory
L-025
P.O. Box 808
Livermore, CA 94550

Dr. Frank Pilotte
HQ AFTAC/TT
Patrick AFB, FL 32925-6001

Dr. Jay J. Pulli
Radix Systems, Inc.
2 Taft Court, Suite 203
Rockville, MD 20850

Dr. Robert Reinke
ATTN: FCTVTD
Field Command
Defense Nuclear Agency
Kirtland AFB, NM 87115

Prof. Paul G. Richards
Lamont-Doherty Geological Observatory
of Columbia University
Palisades, NY 10964

Mr. Wilmer Rivers
Teledyne Geotech
314 Montgomery Street
Alexandria, VA 22314

Dr. George Rothe
HQ AFTAC/TTR
Patrick AFB, FL 32925-6001

Dr. Alan S. Ryall, Jr.
DARPA/NMRO
3701 North Fairfax Drive
Arlington, VA 22209-1714

Dr. Richard Sailor
TASC, Inc.
55 Walkers Brook Drive
Reading, MA 01867

Prof. Charles G. Sammis
Center for Earth Sciences
University of Southern California
University Park
Los Angeles, CA 90089-0741

Prof. Christopher H. Scholz
Lamont-Doherty Geological Observatory
of Columbia University
Palisades, CA 10964

Dr. Susan Schwartz
Institute of Tectonics
1156 High Street
Santa Cruz, CA 95064

Secretary of the Air Force
(SAFRD)
Washington, DC 20330

Office of the Secretary of Defense
DDR&E
Washington, DC 20330

Thomas J. Sereno, Jr.
Science Application Int'l Corp.
10260 Campus Point Drive
San Diego, CA 92121

Dr. Michael Shore
Defense Nuclear Agency/SPSS
6801 Telegraph Road
Alexandria, VA 22310

Dr. Matthew Sibol
Virginia Tech
Seismological Observatory
4044 Derring Hall
Blacksburg, VA 24061-0420

Prof. David G. Simpson
IRIS, Inc.
1616 North Fort Myer Drive
Suite 1440
Arlington, VA 22209

Donald L. Springer
Lawrence Livermore National Laboratory
L-025
P.O. Box 808
Livermore, CA 94550

Dr. Jeffrey Stevens
S-CUBED
A Division of Maxwell Laboratory
P.O. Box 1620
La Jolla, CA 92038-1620

Lt. Col. Jim Stobie
ATTN: AFOSR/NL
Bolling AFB
Washington, DC 20332-6448

Prof. Brian Stump
Institute for the Study of Earth & Man
Geophysical Laboratory
Southern Methodist University
Dallas, TX 75275

Prof. Jeremiah Sullivan
University of Illinois at Urbana-Champaign
Department of Physics
1110 West Green Street
Urbana, IL 61801

Prof. L. Sykes
Lamont-Doherty Geological Observatory
of Columbia University
Palisades, NY 10964

Dr. David Taylor
ENSCO, Inc.
445 Pineda Court
Melbourne, FL 32940

Dr. Steven R. Taylor
Los Alamos National Laboratory
P.O. Box 1663
Mail Stop C335
Los Alamos, NM 87545

Prof. Clifford Thurber
University of Wisconsin-Madison
Department of Geology & Geophysics
1215 West Dayton Street
Madison, WS 53706

Prof. M. Nafi Toksoz
Earth Resources Lab
Massachusetts Institute of Technology
42 Carleton Street
Cambridge, MA 02142

Dr. Larry Turnbull
CIA-OSWR/NED
Washington, DC 20505

DARPA/RMO/SECURITY OFFICE
3701 North Fairfax Drive
Arlington, VA 22203-1714

Dr. Gregory van der Vink
IRIS, Inc.
1616 North Fort Myer Drive
Suite 1440
Arlington, VA 22209

HQ DNA
ATTN: Technical Library
Washington, DC 20305

Dr. Karl Veith
EG&G
5211 Auth Road
Suite 240
Suitland, MD 20746

Defense Intelligence Agency
Directorate for Scientific & Technical Intelligence
ATTN: DTIB
Washington, DC 20340-6158

Prof. Terry C. Wallace
Department of Geosciences
Building #77
University of Arizona
Tucson, AZ 85721

Defense Technical Information Center
Cameron Station
Alexandria, VA 22314 (2 Copies)

Dr. Thomas Weaver
Los Alamos National Laboratory
P.O. Box 1663
Mail Stop C335
Los Alamos, NM 87545

TACTEC
Batelle Memorial Institute
505 King Avenue
Columbus, OH 43201 (Final Report)

Dr. William Wortman
Mission Research Corporation
8560 Cinderbed Road
Suite 700
Newington, VA 22122

Phillips Laboratory
ATTN: XPG
Hanscom AFB, MA 01731-5000

Prof. Francis T. Wu
Department of Geological Sciences
State University of New York
at Binghamton
Vestal, NY 13901

Phillips Laboratory
ATTN: GPE
Hanscom AFB, MA 01731-5000

AFTAC/CA
(STINFO)
Patrick AFB, FL 32925-6001

Phillips Laboratory
ATTN: TSML
Hanscom AFB, MA 01731-5000

DARPA/PM
3701 North Fairfax Drive
Arlington, VA 22203-1714

Phillips Laboratory
ATTN: SUL
Kirtland, NM 87117 (2 copies)

DARPA/RMO/RETRIEVAL
3701 North Fairfax Drive
Arlington, VA 22203-1714

Dr. Michel Bouchon
I.R.I.G.M.-B.P. 68
38402 St. Martin D'Heres
Cedex, FRANCE

Dr. Michel Campillo
Observatoire de Grenoble
I.R.I.G.M.-B.P. 53
38041 Grenoble, FRANCE

Dr. Jorg Schlittenhardt
Federal Institute for Geosciences & Nat'l Res.
Postfach 510153
D-3000 Hannover 51, GERMANY

Dr. Kin Yip Chun
Geophysics Division
Physics Department
University of Toronto
Ontario, CANADA

Dr. Johannes Schweitzer
Institute of Geophysics
Ruhr University/Bochum
P.O. Box 1102148
4360 Bochum 1, GERMANY

Prof. Hans-Peter Harjes
Institute for Geophysics
Ruhr University/Bochum
P.O. Box 102148
4630 Bochum 1, GERMANY

Prof. Eystein Husebye
NTNF/NORSAR
P.O. Box 51
N-2007 Kjeller, NORWAY

David Jepsen
Acting Head, Nuclear Monitoring Section
Bureau of Mineral Resources
Geology and Geophysics
G.P.O. Box 378, Canberra, AUSTRALIA

Ms. Eva Johannisson
Senior Research Officer
National Defense Research Inst.
P.O. Box 27322
S-102 54 Stockholm, SWEDEN

Dr. Peter Marshall
Procurement Executive
Ministry of Defense
Blacknest, Brimpton
Reading FG7-FRS, UNITED KINGDOM

Dr. Bernard Massinon, Dr. Pierre Mechler
Societe Radiomana
27 rue Claude Bernard
75005 Paris, FRANCE (2 Copies)

Dr. Svein Mykkeltveit
NTNF/NORSAR
P.O. Box 51
N-2007 Kjeller, NORWAY (3 Copies)

Prof. Keith Priestley
University of Cambridge
Bullard Labs, Dept. of Earth Sciences
Madingley Rise, Madingley Road
Cambridge CB3 0EZ, ENGLAND