

AD-A254 149

TION PAGE

Form Approved
OMB No 0704-0188

2

Washington Headquarters
22202-4302, and to the Office of Management

It is estimated to average 1 hour per response, including the time for reviewing instructions, obtaining the data needed, and completing and reviewing the collection of information. Send any aspect of this collection of information, including suggestions for reducing this burden, to Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 08/92		3. REPORT TYPE AND DATES COVERED POP Test (06/92)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Container, Shipping and Storage, Mk 708 Mod 0 for Packing Group II Solid Hazardous Materials				5. FUNDING NUMBERS DTIC ELECTE S A D AUG 13 1992	
6. AUTHOR(S) Victor D. Saul					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Weapons Station Earle Test and Evaluation Branch (Code 5023) Colts Neck, NJ 07722-5000				8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92012	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Commander, Naval Sea Systems Command (PMS-422) Department of the Navy Washington, DC 20361-8050				10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A		This document has been approved for public release and sale; its distribution is unlimited.			
12a. DISTRIBUTION/AVAILABILITY STATEMENT				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 708 Mod 0 Shipping and Storage Container (Packing Group II) meets the requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was an inert Mk 210 Mod 0 Vertical Launch Digital Autopilot Control (DAC) unit weighing 12 kg (25 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 1 kg (2 pounds) were added. Gross weight of the loaded container was 27 kg (60 pounds).					
14. SUBJECT TERMS POP Test of Mk 708 Mod 0 Shipping and Storage Container				15. NUMBER OF PAGES 7	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UL		19. SECURITY CLASSIFICATION OF ABSTRACT UL	
				20. LIMITATION OF ABSTRACT UL	

DODPOPHM/USA/DOD/NADTR92012

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
CONTAINER, SHIPPING AND STORAGE, MK 708 MOD 0
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
Victor D. Saul
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

August 1992

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Sea Systems Command
(Code PMS-422)
Department of the Navy
Washington, DC 20362-5101

DTIC QUALITY INSPECTED 5

Accession For	
NTIS CRA&I	J
DTIC TAB	
Unannounced	
Justification	
By	
Distribution /	
Availability /	
Dist	Avail and/or Spec
A-1	

92-22745



92 8 11 087

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 708 Mod 0 Shipping and Storage Container (Packing Group II) meets the requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was an inert Mk 210 Mod 0 Vertical Launch Digital Autopilot Control (DAC) unit weighing 12 kg (25 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 1 kg (2 pounds) were added. Gross weight of the loaded container was 27 kg (60 pounds).

Due to unavailability only one container was used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The container was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 141 kg (310 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then removed and the container examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Six drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drops for each orientation):

- a. Horizontally.
- b. Diagonally on the edge between the cover assembly and the top ring of the container.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 4.1 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the container was inspected. The contents were completely retained by the container.

REFERENCE MATERIAL

A. Code of Federal Regulations, Title 49 CFR, Parts 107-178.

B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Defense General Supply Center
ATTN: DDRV-TMPA, D. Gay
Richmond, VA 23219

Commander
Crane Division (Code 4053)
Naval Surface Warfare Center
Crane, IN 47522-5000

TEST DATA SHEET

POP MARKING:	
UN 1A2/Y28/S/**/USA/DOD/NAD	
**YEAR LAST PACKED OR MANUFACTURED	
DATA SHEET:	
Container: Mk 708 Mod 0 Shipping and Storage Container	
Type: 1A2	Container P/N or NSN: NSN 1420-01-298-7581
Drawing Number: 6116622	Material: Steel
Gross Weight: 27 kg (60 pounds)	Dimensions: 20" dia x 20" H
Closure (Method/Type): Locking Ring	Tare Weight: 15 kg (33 pounds)
Additional Description:	
PRODUCT:	
Name: See table 1	NSN(s): See table 1
United Nations Number: See table 1	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container:	Flash Point: N/A
Net Weight: See table 1	
TEST PRODUCT:	
Name: Digital Autopilot Control (DAC)	Physical State: Solid
Consistency: N/A	Density/Specific Gravity: N/A
Test Pressure (Liquids Only): N/A	
Amount Per Container: N/A	Net Weight: 12 kg (27 pounds)
Additional Description:	
The net weight includes the net maximum product weight plus an additional 1 kg (2 pounds).	

TABLE 1
Products Approved for Shipping in the
Mk 708 Mod 0 Shipping and Storage Container

NALC	NSN	Product Type	Packing Drawing	Haz Class/Div	UN Number	Units/Cntr	Total Net Weight (lb)	Total Gross Weight (lb)
5W85	4T 1420-01-298-7581	Vertical Launch DAC	6206160	1.4S	0349	1	25	58

DAC = Digital Autopilot Control