

REPORT DOCUMENTATION PA

AD-A257 399

18

Public reporting burden of this collection of information is estimated searching existing data sources, gathering and maintaining the data comments regarding this burden estimate or any other aspect of this Washington Headquarters Services, Directorate for Information Oper 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.



ing instructions, nation. Send this burden, to 04, Arlington, VA

21

1. AGENCY USE ONLY (Leave blank)

2. REPORT DATE

10/92

3. REPORT TYPE AND DATES COVERED

POP Test (09/92)

4. TITLE AND SUBTITLE

Performance Oriented Packaging Testing of Mk 117 Mod 0 JATO Shipping Container for Packing Group II Solid Hazardous Materials

5. FUNDING NUMBERS

DTIC
ELECTE
OCT 26 1992
S A D

6. AUTHOR(S)

J. Mike Dwyer

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Weapons Station Earle
Test and Evaluation Branch (Code 5023)
Colts Neck, NJ 07722-5000

8. PERFORMING ORGANIZATION
REPORT NUMBER

DODPOPHM/USA/DOD/NADTR92028

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Commander, Naval Surface Warfare Center
Indian Head Division (Code 5710R)
Indian Head, MD 20640-5035

10. SPONSORING/MONITORING
AGENCY REPORT NUMBER

Same as above

11. SUPPLEMENTARY NOTES

N/A

12a. DISTRIBUTION/AVAILABILITY STATEMENT
This document has been approved for public release and sale; its distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Mk 117 Mod 0 JATO Shipping Container meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was two inert rocket motors weighing 23 kg (50 pounds) each. This represents the current maximum commodity weight. Gross weight of the loaded container was 59 kg (130 pounds). The test results indicate that the container has conformed to the POP requirements.

92-27872



14. SUBJECT TERMS

POP Test of Mk 117 Mod 0 JATO Shipping Container

15. NUMBER OF PAGES

7

16. PRICE CODE

17. SECURITY CLASSIFICATION OF
REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION OF THIS PAGE

UL

19. SECURITY CLASSIFICATION OF ABSTRACT

UL

20. LIMITATION OF ABSTRACT

UL

DODPOPHM/USA/DOD/NADTR92028

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
MK 117 MOD 0 JATO SHIPPING CONTAINER
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
J. Mike Dwyer
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

October 1992

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Surface Warfare Center
Indian Head Division (Code 5710R)
Indian Head, MD 20640-5035

Accession For	
NTIS	CRA&I ☒
DTIC	TAB ☐
Unannounced	☐
Justification	
By	
Distribution /	
Availability	
Dist	Availability Special
A-1	

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 117 Mod 0 JATO Container meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 31 December 1991. The packaged commodity used for the test was two inert rocket motors weighing 23 kg (50 pounds) each. This represents the current maximum commodity weight. Gross weight of the loaded container was 59 kg (130 pounds).

Due to unavailability only two container were used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The container was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 762 kg (1,680 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then removed and the container examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Five drops were performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom using container #1.
- b. Flat top using container #1.

- c. Flat on long side using container #1.
- d. Flat on short side using container #1.
- e. One on the aft stbd corner using container #2.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 3.6 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the container was inspected. The contents were completely retained by the container.

REFERENCE MATERIAL

A. Code of Federal Regulations, Title 49 CFR, Parts 107-178.

B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

Defense General Supply Center
ATTN: DDRV-TMPA, D. Gay
Richmond, VA 23219

Commander
Naval Surface Warfare Center
ATTN: Crane Division (Code 4053)
Crane, IN 47522-5000

TEST DATA SHEET

POP MARKING:	
UN 4C1/Y59/S/**/USA/DOD/NAD	
**YEAR LAST PACKED OR MANUFACTURED	
Container: Mk 117 Mod 0 JATO Shipping Container	
Type: 4C1	Container P/N or NSN: P/N 1638AS122
Drawing Number: 1638AS122	Outer Packaging Material: Wood
Dimensions: 34-1/8" L x 16-1/8" W x 9-13/16" H	Gross Weight: 59 kg (130 pounds)
Closure (Method/Type): two 5/8" straps and six 7-D nails	Tare Weight: 14 kg (30 pounds)
Additional Description:	
PACKAGED COMMODITY:	
Name: See table 1	NSN(s): See table 1
United Nations Number: See table 1	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container: See table 1	Flash Point: N/A
Net Weight: See table 1	
PACKAGED COMMODITY USED FOR TEST:	
Name: Two Inert Rocket Motors	Physical State: Solid
Consistency: N/A	Density/Specific Gravity: N/A
Test Pressure (Liquids Only): N/A	Net Weight: 45 kg (100 pounds)
Additional Description:	

N/A = Not Applicable

TABLE 1
Commodities Approved for Shipping in the
Mk 117 Mod 0 JATO Shipping Container

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Drawing Number	Haz Class/Div	UN Number	Units/ Cntr	Total Net Weight (lb)	Total Gross Weight (lb)
H341	1340-01-177-2502	Mk 117 Mod 0 JATO Rocket Motor	1638AS123	1.3C	0186	2	100	130