

REI

AD-A258 769

Form Approved
OBM No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Service, Office of Management and Budget, Paperwork Project Director (0704-0188), Washington, DC 20503.

the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Service, Office of Management and Budget, Paperwork Project Director (0704-0188), Washington, DC 20503.

1. Agency Use Only (Leave blank).

2. Report Date.
October 1992Report Type and Dates Covered.
Final - Proceedings

4. Title and Subtitle.

Critical Frequencies in Scattering from Submerged Elastic Shells

5. Funding Numbers.

Contract

Program Element No. 0601153N

Project No. 03202

Task No. 340

Accession No. DN255011

Work Unit No. 12212B

6. Author(s).

Michael F. Werby, Hassan B. Ali, and Michael K. Broadhead

7. Performing Organization Name(s) and Address(es).

Naval Research Laboratory
Ocean Acoustics and Technology Directorate
Stennis Space Center, MS 39529-50048. Performing Organization
Report Number.

PR 92:037:221

9. Sponsoring/Monitoring Agency Name(s) and Address(es).

Naval Research Laboratory
Ocean Acoustics and Technology Directorate
Stennis Space Center, MS 39529-500410. Sponsoring/Monitoring Agency
Report Number.

PR 92:037:221

11. Supplementary Notes.

Published in Proceedings of Mastering the Oceans Through Technology, (OCEANS 92).

12a. Distribution/Availability Statement.

Approved for public release; distribution is unlimited.

12b. Distribution Code.

13. Abstract (Maximum 200 words).

In the process of scattering from submerged elastic shells, it is possible to excite many types of resonances. Among these are the lowest order symmetric and antisymmetric Lamb modes, and the waterborne waves, such as the pseudo-Stoneley resonances and the higher order symmetric and antisymmetric Lamb modes S_i and A_i ($i = 1, 2, 3, \dots$). the frequency at which these originate are referred to as critical frequencies. We establish simple rules to determine the frequencies at which the resonances originate as a function of shell thickness and material properties.

DTIC
ELECTE
DEC 09 1992
S E D

14. Subject Terms.

Acoustic scattering, shallow water, waveguide propagation

15. Number of Pages.

6

16. Price Code.

17. Security Classification
of Report.

Unclassified

18. Security Classification
of This Page.

Unclassified

19. Security Classification
of Abstract.


Unclassified

20. Limitation of Abstract.

SAR

OCEANS 92

MASTERING
THE OCEANS
THROUGH
TECHNOLOGY



92-31175



REPRINTED FROM:

Accession For	
NTIS	CRA&I ☒
DTIC	TAB ☐
Unannounced ☐	
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	20

October 26-29, 1992
Newport, Rhode Island

Mastering the Oceans Through Technology



Sponsored by the Oceanic Engineering Society of IEEE
Providence Section of IEEE
Central New England Engineering Council of IEEE
The New England Section of the Marine Technology Society
92CH3217-7

Critical Frequencies in Scattering from Submerged Elastic Shells

Michael F. Werby, Hassan B. Ali, and Michael K. Broadhead
Naval Research Laboratory, Stennis Space Center, MS 39529-5004

Abstract – In the process of scattering from submerged elastic shells, it is possible to excite many types of resonances. Among these are the lowest order symmetric and antisymmetric Lamb modes, and the waterborne waves, such as the pseudo-Stoneley resonances and the higher order symmetric and antisymmetric Lamb modes S_i and A_i ($i = 1, 2, 3, \dots$). The frequency at which these originate are referred to as critical frequencies. We establish simple rules to determine the frequencies at which the resonances originate as a function of shell thickness and material properties.

1. INTRODUCTION

The presence of resonances generated from acoustical signals impinging on submerged evacuated elastic shells has been known for some time. In particular, the presence of the symmetric or dilatational Lamb mode S_0 as well as the lowest order antisymmetric Lamb or Flexural mode A_0 are well known and frequently studied. Moreover, the existence of higher order symmetric S_i and antisymmetric A_i Lamb modes ($i > 0$) manifest themselves with increasing frequency [1]. In addition, newly studied phenomena such as pseudo-Stoneley resonances [2-4] and pure waterborne waves [5] have received attention recently. All but the last phenomena have analogues for the infinite flat plate case which is fluid loaded on one side and evacuated on the other.

It is usual to associate resonances with vibrations, and the presence of the Lamb resonances on spherical shells can be associated with symmetric or antisymmetric vibrations that at discrete frequencies form standing waves on the object surface. These standing waves radiate into the fluid and add coherently with the specularly scattered signal producing a characteristic signature. The nature and appearance of the resonances just described are a function of material characteristics and shell thickness in addition to frequency. For very thin shells the lowest order resonance has a large amplitude and is in a region where there is a large recoil effect leading to both a large monopole term as well as the dipole term associated with the recoil effect. The subsequent symmetric Lamb modes are characterized by a sharp minimum followed by a sharp rise and then a return to a normal slowly varying back scattered return signal (form function). Flexural or antisymmetric resonances do not arise until the flexural phase velocity equals the speed of sound in

the fluid [4, 6] (subsonic material waves are too heavily dampened to be observed); this value of frequency is referred to as coincidence frequency. At and a little below coincidence frequency another phenomenon enters the picture, namely sharply defined waterborne waves which have their analogue in flat plates, namely Stoneley waves. Thus, the resonances that arise from these waterborne waves are labeled pseudo-Stoneley resonances. They occur only in the frequency region about coincidence frequency and give rise to very sharp spikes superimposed on broadly overlapping flexural resonances. This effect can be very dramatic. Another dramatic effect arises from the S_1 symmetric resonance which is a separate topic presented by Werby and Gaunard [7, 8]. Interestingly the onset of all of the higher order Lamb resonances can be obtained from the simple expressions used to predict the critical frequencies for the flat plate case. We will demonstrate this effect by employing the residual partial wave analysis (the partial wave component minus the exact acoustical background for a shell). It is only possible to perform the correct partial wave analysis if one has the correct background for the elastic shell [9, 10].

2. ACOUSTIC SCATTERING FROM SUBMERGED ELASTIC SHELLS

2.1 The Form Functions for Aluminum and Steel for ka from 0 to 500

We illustrate in this section the form function for 5% thick Aluminum and Steel shells. Figure 1a-d represent backscatter from aluminum 1(a) from $ka = 0$ to 250, 1(b) the residual results (with background subtracted) from 0 to 250, 1(c) for aluminum from 250 to 500, and 1(d) the residual for aluminum from 250 to 500. Figure 2a-d represent backscatter from steel 2(a) from $ka = 0$ to 250, 2(b) the residual results from 0 to 250, 2(c) for steel from 250 to 500, and 2(d) the residual for steel from 250 to 500. It is clear that a great deal of detail is present in each of the plots. The low frequency large returns with the sharp spikes for both materials are due to a superposition of the pseudo-Stoneley resonances with the weaker broadly overlapping flexural resonances. The higher frequency resonances (about $ka = 250$ in both cases) are due to the onset of the S_1 Lamb mode. We have indicated in the plots the onset of each of the modes.




Figure 1. (a) Backscatter from 5% aluminum shell from $ka = 0$ to 250; (b) residual backscatter for case 1a; (c) backscatter from 5% aluminum shell from $ka = 250$ to 500; and (d) residual backscatter for case 1c.

2.2 Discussion of Pure Waterborne Waves

We have earlier discussed pseudo-Stoneley waves [3, 4]. There is another phenomenon that corresponds to waves that have a phase velocity that is about the speed of sound in water. They are not, however, sharply defined in partial wave space, nor are they associated with the flexural wave or coincidence frequency. They are associated with the density of the material, and the thickness (really just the mass of the target) and the frequency. Their importance increases with frequency and they do not manifest themselves as sharp resonances in the form function but rather wash out other resonances such as S_0 and A_0 resonances. Thus for light material and thin shells such as aluminum and at high frequency one does not observe sharp resonances due to this wash out effect. We will not discuss this effect here.

2.3 A Partial Wave Analysis

If one subtracts the correct background [9, 10] from the elastic response then by definition one is left with

the "pure" resonance response. Resonances excited on bodies of canonical shape usually correspond to circumferentially excited waves which for spheres have a unique wave number. To be sure, this fact can be obscured by, for example, broadly overlapping partial waves; but none the less plotting the residual partial wave components—which is here referred to as a partial wave analysis—can be very revealing. There are two ways to perform a partial wave analysis: one can fix the mode number N and plot the residual response with respect to ka . On the other hand one can fix ka and plot the partial wave function with respect to mode number N . The first of these approaches is the most commonly used.

Figure 3a–c illustrates the PWA for 5% thick aluminum shells out to a ka of 500 for modes 1, 2, and 10. We have listed the onset of the different Lamb modes in Table 1 and indicated with arrows in the plots here the critical frequencies for each case. The same has been done for steel in Figure 4a–c. It is clear that the simple expressions listed in Table 1 and the computed values agree with the onset of the higher order Lamb modes.




Figure 2. (a) Backscatter from 5% steel shell from $ka = 0$ to 250; (b) residual backscatter for case 1a; (c) backscatter from 5% steel shell from $ka = 250$ to 500; and (d) residual backscatter for case 1c.

TABLE I
CRITICAL FREQUENCIES FOR THE HIGHER ORDER LAMB
MODES $ka = \pi(v_L/v_w)n/h$ A WHEN n ODD S WHEN n EVEN,
 $ka = \pi(v_L/v_w)n/h$ S WHEN n ODD A WHEN n EVEN h
IS % THICKNESS OF SHELL.

ALUMINUM	STEEL
A ₁ 129.3	A ₁ 140.2
S ₁ 258.5	S ₁ 243.9
S ₂ 269.1	S ₂ 280.3
A ₂ 387.8	A ₂ 420.5
A ₃ 403.7	A ₃ 487.9
S ₃ 517.1	S ₃ 560.6
S ₄ 538.2	S ₄ 731.9

2.4 Phase Velocity Plots

We have included in this work the phase velocities for the steel shell illustrated in Figure 5. Here we include the pseudo-Stoneley resonance (Fig. 5a), the pure water-borne wave (Fig. 5b), the A_0 resonance (Fig. 5c), the S_1 resonance (Fig. 5d), the A_1 resonance (Fig. 5e), the S_1 resonance (Fig. 5f), the S_2 resonance (Fig. 5g), the A_2 resonance (Fig. 5h), and the A_3 resonance (Fig. 5i). Note that the onset of each of the higher order Lamb resonances conforms to the values listed in Table 1. Further note that the S_1 resonance has a phase velocity that in effect decreases at some point (early on) then increases and then decreases again.

3. CONCLUSION

This is only a preliminary study of a large ongoing study of Lamb resonances. It is encouraging that most effects are easily understood in terms of flat plate theory






Figure 3. Partial wave for aluminum: (a) mode 1, (b) mode 2, and (c) mode 10.






Figure 4. Partial wave for steel: (a) mode 1, (b) mode 2, and (c) mode 10.




Figure 5. Phase velocity for steel: (a) pseudo-Stoneley resonance, 5% steel; (b) waterborne wave; (c) A_0 resonance; (d) S_0 resonance; (e) A_1 resonance.

and that the critical frequencies can be predicted by such simple expressions. Further some of the more dramatic effects such as the pseudo-Stoneley resonances and those due to the S_1 resonance can be interpreted.

4. ACKNOWLEDGMENTS

This work was funded by Program Element 0601153N, Program Manager Dr. E. R. Franchi, NRL contribution number PR92:037:221.

5. REFERENCES

- [1] H. Überall, "Model and surface-wave resonances in acoustic-wave scattering from elastic objects and in elastic-wave scattering from cavities," in *Proceedings of the IUTAM Symposium: Modern Problems in Elastic Wave Propagation*, p. 239-263, Northwestern University, Evanston, IL, Sept. 12-15, 1977, edited by J. Miklowitz and J. D. Achenbach, Wiley Intersciences, New York, 1978.




Figure 5. Phase velocity for steel (cont.) (f) S_1 resonance; (g) S_2 resonance; (h) A_2 resonance; and (i) A_3 resonance.

- [2] M. Talmant, H. Überall, R. D. Miller, M. F. Werby, and J. W. Dickey, "Lamb waves and fluid borne waves on water-loaded, air-filled thin spherical shells," *J. Acoust. Soc. Am.*, 86:278-289, 1989.
- [3] G. Quentin and M. Talmant, "The plane plate model applied to scattering of ultrasonic waves from cylindrical shells," in *Proceedings of the Int. Conference on Elastic Wave Propagation*, M. F. McCarthy and M. A. Hayes, editors, Elsevier Publications B. V., North Holland, 1989.
- [4] M. F. Werby and H. B. Ali, "Time domain solution from the frequency domain: Application to resonance scattering from elastic bodies," *Computational Acoustics-Vol. 2*, D. Lee, A. Cakmak, and R. Vichnevetsky, editors, p. 133-158, Elsevier Publications B. V., North Holland, IMAC, 1990.
- [5] M. F. Werby and H. Überall, "The excitation of waterborne waves at the interface of evacuated elastic spherical shells and pseudo-Stoneley resonances," *Journal de Physique IV, Colloque C1*, supplément au Journal de Physique III, Vol. 2, Arcachon, France, 14-17 April 1992.
- [6] D. Ross, *Mechanics of Underwater Noise*, Pergaman Press, New York, 1976.
- [7] M. F. Werby, "Strong resonance features present in the acoustic signatures of submerged elastic structures," *Special Issue of Optical Engineering*, Journal on Automatic Target Recognition, in press.
- [8] M. F. Werby, "Recent developments in scattering from submerged elastic and rigid targets," in *Proceedings on Resonance Scattering Conference*, Catholic University of America, May 1989. *Acoustic Resonance Scattering*, edited by H. Überall (Gordon and Breach, New York, in press).
- [9] M. F. Werby, "The isolation of resonances and the ideal acoustical background for submerged elastic shells," *Acoustics Letters*, 15(4):65-69, 1991.
- [10] M. F. Werby, "The acoustical background for a submerged elastic shell," *J. Acoust. Soc. Am.*, 90(6):3279-3287, December 1991.