

AD-A259 098

SECURITY CLASSIFICATION OF THIS PAGE

REPORT 1

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Unlimited	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			5. MONITORING ORGANIZATION REPORT NUMBER DTIC ELECTC DEC 14 1992	
4. PERFORMING ORGANIZATION REPORT NUMBER(S) DOD POP HMTR/AYD 92-011			7a. NAME OF MONITORING ORGANIZATION	
6a. NAME OF PERFORMING ORGANIZATION Packaging Division, AED	6b. OFFICE SYMBOL (If applicable) SMCAR-AEP	7b. ADDRESS (City, State, and ZIP Code)		
6c. ADDRESS (City, State, and ZIP Code) U.S. Army, ARDEC Picatinny Arsenal, NJ 07806-5000		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	10. SOURCE OF FUNDING NUMBERS		
8c. ADDRESS (City, State, and ZIP Code)		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
		WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) Performance Oriented Packaging Report for Charge, Demolition, Shaped, 40 Pound, M3A1				
12. PERSONAL AUTHOR(S) Snizek, Frank				
13a. TYPE OF REPORT Final	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 92-11-02		15. PAGE COUNT
16. SUPPLEMENTARY NOTATION				
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	Performance Oriented Packaging, POP, Charge, Demolition, Shaped, 40 Pound, M3A1 Mil-B-2427 wood box	
19. ABSTRACT (Continue on reverse if necessary and identify by block number) This POP report is for the Charge, Demolition, Shaped, 40 Pound, M3A1 which is packaged 1 charge/Mil-B-2427 wood box. This report describes the results of testing conducted.				
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT ☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL STEVE RUFFINI			22b. TELEPHONE (Include Area Code) (201) 724-2515	22c. OFFICE SYMBOL SMCAR-AEP

I. REPORT NUMBER: DOD POP HMTR/AYD 92-011

II. TITLE: Performance Oriented Packaging Report for Charge, Demolition, Shaped, 40 lb, M3A1

AUTHOR: Frank M. Snizek

PERFORMING ACTIVITY: ARDEC

ADDRESS: Department of the Army
ARDEC, SMCAR-AEP
HQ, U.S. Army Armament, Munitions, and Chemical Command
Picatinny Arsenal, NJ 07806-5000

DATE: 2 Nov 92

Approved for public release; Distribution is unlimited

Accession for
NTIS 92-011
DOD 92-011
Unpublished
Justification

By
Distribution/
Availability Codes

Dist	Special
A-1	

92-31314



388

92 12 11 088

2000-01-01

1. DATA SHEET

CONTAINER

Type: Box
UN Code: 4C1
Nomenclature: Box, Packing, Ammunition, for Charge, Demolition,
Shaped, 40 lb, M3A1
Specification Number: Type II, Grade A, Class 2, Mil-B-2427
Drawing Number: 7549165
Material: Wood
Gross Weight: 65 pounds
Outside Dimensions: 20 1/2 x 11 5/8 x 13 1/8
Inside Dimensions: 16 7/8 x 10 1/8 x 10 15/16

PRODUCT

Name: Charge, Demolition, Shaped, 40 lb, M3A1
Drawing Number: 8858382
United Nations Number: 0048
Physical State: Solid
Amount per Container: 1

2. BACKGROUND, TESTS, AND RESULTS

Reference the following document:

- a. 49CFR, October 1, 1991 Edition

Instead of testing with the actual item, three wooden boxes built to the same specification but packed with a fiberboard box loaded with sand to a gross weight of 100 pounds were tested.

A Stacking Test was conducted on one container with a weight of 914 pounds for 72 hours in lieu of three containers for 24 hours.

A Loose Cargo Test was conducted on three containers for one hour. The packages were tested at a vibration table frequency such that the bottom of the packages were raised 1/4 inch from the platform, which exceeds the requirement of 1/16 inch.

A Four Foot Drop Test was conducted on one of the containers that was subjected to the Loose Cargo Test. One container was dropped five times at different orientations as follows: top, bottom, long side, short side, and a top corner at the closure. This exceeds the requirement of one drop per container.

Test results indicated no leakage or spillage of the contents from the containers following any of the tests conducted, meeting the requirements of the 49 CFR.