

AD-A262 777



2

PL-TR-92-2332

**A PROGRAM TO DETERMINE THE POINTING  
ANGLE TO A SPECULAR POINT**

M.E. Gardner  
T.J. Keneshea  
R.P. Pauliukonis

Visidyne, Inc.  
10 Corporate Place  
South Bedford Street  
Burlington, MA 01803

22 October 1992

Approved for public release, distribution unlimited.

**SDTIC**  
**ELECTE**  
**MAR 04 1993**  
**S E D**

**93-04579**




98 3 3 057



**PHILLIPS LABORATORY**  
**Directorate of Geophysics**  
**AIR FORCE MATERIEL COMMAND**  
**HANSCOM AIR FORCE BASE, MA 01731-5000**

This technical report has been reviewed and is approved for publication

  
FRANCIS X. ROBERT  
Contract Manager

  
STEPHAN D. PRICE  
Branch Chief

  
ROGER VAN TASSEL  
Division Director

This report has been reviewed by the ESC Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS).

Qualified requestors may obtain additional copies from the Defense Technical Information Center. All others should apply to the National Technical Information Service.

If your address has changed, or if you wish to be removed from the mailing list, or if the addressee is no longer employed by your organization, please notify PL/TSI, Hanscom AFB, MA 01731-5000. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document requires that it be returned.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Do not report to burden of this collection of information, estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Office, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 22 October 1992	3. REPORT TYPE AND DATES COVERED Scientific No. 2		
4. TITLE AND SUBTITLE A Program to Determine the Pointing Angle to a Specular Point			5. FUNDING NUMBERS PE632200 PRS321 TA06 WUAB Contract F19628-90-C-0187	
6. AUTHOR(S) M.E. Gardner T.S. Keneshea R.P. Pauliukonis				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Visidyne, Inc. 10 Corporate Place South Bedford Street Burlington, MA 01803			8. PERFORMING ORGANIZATION REPORT NUMBER VI-1982	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Phillips Laboratory Hanscom AFB, MA 01731-5000 Contract Manager, Frank Robert/GPOB			10. SPONSORING MONITORING AGENCY REPORT NUMBER PL-TR-92-2332	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  This report describes a method for determining the pointing angle to a specular point given attitude information to the IBSS SPAS.				
14. SUBJECT TERMS IBSS Specular Point Pointing Angle			15. NUMBER OF PAGES 12	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

## A program to determine the pointing angle to a specular point.

This report describes a method for determining the pointing angle to a specular point given the latitude, longitude, inclination, yaw and pitch of the IBSS SPAS. The formulas for the parameters of the sun are taken from *Astronomical Formulae for Calculators*.<sup>1</sup>

The following variables that refer to the SPAS are obtained from SPAS ephemeris data furnished by Mission Research Corporation.

- $O_x$  = X component of the position vector (km) ECI
- $O_y$  = Y component of the position vector (km) ECI
- $O_z$  = Z component of the position vector (km) ECI
- GEOCLAT = geocentric latitude (+90°)
- SPASLON = geocentric longitude (+E)
- $V_x$  = X component of velocity vector (km/sec)
- $V_y$  = Y component of velocity vector (km/sec)
- $V_z$  = Z component of velocity vector (km/sec)
- $H_{SPAS}$  = distance (km) to the SPAS from the center of the earth.

The calendar year, month and day associated with each of these quantities are also obtained from the SPAS ephemeris data.

YAW and PITCH are obtained from the SPAS attitude data furnished by Mission Research Corporation.

The SPAS longitude, as given in the ephemeris, is measured positive toward the east. The formulae in this analysis assume that the SPAS longitude is positive toward the west. Therefore, SPASLON is made equal to -SPASLON.

The components of the SPAS inclination vector, given the position and velocity vectors can be written as:

$$I_x = O_y * V_z - O_z * V_y$$

$$I_y = O_z * V_x - O_x * V_z$$

$$I_z = O_x * V_y - O_y * V_x$$

The inclination angle, INCL, of the SPAS is then

$$INCL = \cos^{-1} \left[ \frac{I_z}{[I_x^2 + I_y^2 + I_z^2]^{1/2}} \right]$$

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

<sup>1</sup> J. Meeus, *Astronomical Formulae for Calculators*, Willmann-Bell, Richmond, VA (1988).

The SPAS heading angle measured from true north, HEAD, is computed from:

$$HEAD = \tan^{-1} \left[ \frac{\cos(INCL)}{[\sin^2(INCL) - \sin^2(GEOCLAT)]^{1/2}} \right].$$

If the SPAS is traveling from north to south, determined by examining the latitudes, the supplement of the heading angle is used. The azimuth from true north and elevation measured from the local horizon of the SPAS line-of-sight are determined as follows:

$$AZIMUTH = YAW + HEAD$$

$$ELEVATION = PITCH.$$

The Julian date, JD, is computed from:

$$JD = INT(365.25 y) + INT(30.6001(m+1)) + DD.dd + 1720994.5 + B$$

where INT is the integer part of the value in parentheses and DD.dd is the decimal day, y is the year and m is the month at the time of the calculation.

$$B = 2 - A + \left| \frac{A}{4} \right|, \text{ and}$$

$$A = \left| \frac{Y}{100} \right|,$$

The time T, measured in Julian Centuries of 36525 ephemeris days from the epoch 1900 January 0.5 ET, is given by

$$T = \frac{JD - 2415020.0}{36525}.$$

Since T is expressed in centuries, an error in the 5th decimal place will cause an error of 0.4 days in the time. Therefore, it is essential that this calculation be done in double precision.

The geometric mean longitude of the sun, L, referred to as the mean equinox of the date, is given by:

$$L = 279.69668 + 36000.76892 T + 0.0003025 T^2.$$

The mean anomaly of the sun, M, is expressed as:

$$M = 358.47583 + 35999.04975 T - 0.000150 T^2 - 0.0000033 T^3.$$

The equation for the center of the sun, C, is determined from:

$$C = (1.919460 - 0.004789 T - 0.000014 T^2) \sin(M) + (0.0200943 - 0.000100 T) \sin(2M) + 0.000293 \sin(3M).$$

The true longitude of the sun,  $\theta$ , equals

$$\theta = L + C.$$

This longitude must be modified to obtain the apparent longitude of the sun, referred to as the true equinox of the date.  $\theta$  is corrected for nutation and aberration as follows:

$$\Omega = 259.18 - 1934.142 T$$

$$\theta_{APP} = \theta - 0.000569 - 0.00479 \sin(\Omega).$$

The obliquity of the ecliptic,  $\epsilon$ , is given by

$$\epsilon = 23.452294 - 0.0130125 T - 0.00000164 T^2 + (9.2100 + 0.00091 T) \cos(\Omega) / 3600.0.$$

The right ascension at the sun,  $\gamma$ , is given by the formula

$$\gamma = \frac{180}{15\pi} \tan^{-1} \left( \frac{\cos \epsilon \sin(\theta_{APP})}{\cos(\theta_{APP})} \right) \text{ (hours)}.$$

The declination of the sun,  $\delta$ , is given by

$$\sin(\delta) = \sin(\theta_{APP}) \sin(\epsilon).$$

The coordinates of the sun relative to the position of the satellite must be determined.

The sidereal time at Greenwich at 0 hr. UT expressed in decimal hours in the interval 0-24 hours is given by the formula:

$$TIME_S = 0.276919398 + 100.0021359 T.$$

The sidereal time at Greenwich at the time of the calculation,  $T_{S\_CAL}$  is therefore:

$$T_{S\_CAL} = 1.00273908 * TIME_{CAL} + TIME_S$$

where  $\text{TIME}_{\text{CAL}}$  is in decimal hours.

The local hour angle in degrees is

$$\text{LHA} = \text{T}_{\text{s,CAL}} - \text{SPASLON} - \gamma.$$

The angle A in Fig. 1, which is the compliment of the solar zenith angle, is given by:

$$A = \sin^{-1} [\sin (\text{GEOCLAT}) \sin (\delta) + \cos (\text{GEOCLAT}) \cos (\delta) \cos (\text{LHA})].$$




Figure 1. SUN-SPAS-EARTH Geometry.

The earth center angle between the SPAS and the sun, the solar zenith angle of the SPAS, is

$$\text{SUN}_{\text{ECA}} = 90^\circ - A.$$

The azimuth to the specular point, i.e., azimuth of sun, is defined as:

$$\text{AZ}_{\text{SPEC}} = \tan^{-1} \left[ \frac{\sin (\text{LHA})}{\cos (\text{LHA}) \sin (\text{GEOCLAT}) - \tan (\delta) \cos (\text{GEOCLAT})} \right] + 180^\circ.$$

Five specular point altitudes are assumed, specifically 40, 30, 20, 10 and 0 km. An iterative procedure is necessary to calculate the earth center angle between the SPAS and the specular point.

With B equal to  $SUN_{ECA}$ ,  $H_{SPECULAR}$  equal to one of the 5 specular point altitudes measured from the center of the earth, and B' initially equal to B the following parameters are computed:

$$X_1 = 2 B' - B$$

$$FN = \frac{H_{specular}}{H_{spas}} \sin(B') - \sin(X_1)$$

$$FN' = \frac{H_{specular}}{H_{spas}} \cos(B') - 2 \cos(X_1)$$

A new value for B' is then determined from:

$$B'_{n+1} = \left| B'_n - \frac{FN}{FN'} \right|$$

A check is made to see if (B-B') is less than 0.0001. If it is not  $X_1$ , FN and FN' are recomputed using the new B'. This process is repeated until  $(B_{n+1} - B'_n)$  becomes less than 0.0001. The earth center angle between the satellite and the specular point is then given by:

$$ECA_{SAT-SPEC} = B - B'$$

The formulae used in this iteration can result in a B' that is greater than  $360^\circ$ . Therefore, B' must be reduced by multiples of  $360^\circ$  until an angle less than  $360^\circ$  is reached.

Figure 2 illustrates the geometry described above.


The elevation to the specular point is given by:

$$ELEV_{SPEC} = -[90^\circ + SUN_{ECA} - 2 B']$$

If B' is greater than  $90^\circ$ , there is no specular point for the given input parameters.

The distance D in kilometers from the SPAS to the specular point is given by:

$$D^2 = H_{SPAS}^2 + H_{SPECULAR}^2 - 2 H_{SPAS} H_{SPECULAR} \cos(ECA_{SAT-SPEC})$$



$$\begin{aligned}
 ECA_{BAT-SPEC} &= 180 - X_1 - [90 + 90 \cdot B] \\
 &= B' - X_1 \\
 &= B - B'
 \end{aligned}$$

Figure 2. Specular Scattering Geometry

The latitude,  $LAT_{SPEC}$ , of the specular point is defined as:

$$LAT_{SPEC} = \sin^{-1} [\cos (ECA_{SAT-SPEC}) \sin (GEOCLAT) + \sin (ECA_{SAT-SPEC}) \cos (GEOCLAT) \cos (AZ_{SPEC})].$$

The longitude of the specular point is determined in the following manner. First the parameters  $A_1$  and  $A_2$  are computed from:

$$A_1 = \sin^{-1} \left[ \frac{\sin (ECA_{SAT-SPEC}) \sin (AZ_{SPEC})}{\cos (LAT_{SPEC})} \right]$$

$$A_2 = \frac{\cos (ECA_{SAT-SPEC}) - \sin (GEOCLAT) \sin (LAT_{SPEC})}{\cos (GEOCLAT) \cos (LAT_{SPEC})}.$$

$A_2$  is the cos of  $A_1$ , however only the sign of  $A_2$  is required to determine  $\lambda$ , the longitudinal difference  $LONG_{SPAS} - long_{SPEC}$ .

If  $A_1 \geq 0^\circ$  and  $A_2 < 0$ , then  $\lambda = \pi - A_1$

If  $A_1 < 0^\circ$  and  $A_2 < 0$ , then  $\lambda = -\pi - A_1$ .

If  $A_2 > 0$ , then  $\lambda = A_1$ .

The longitude of the specular point is then

$$LONG_{SPEC} = SPASLON - \lambda.$$

Since  $LONG_{SPEC}$  must be between 0 and  $360^\circ$ , the same modification must be made to it as was done for  $B'$  to insure that it stays within this range.

The pointing angle to the specular point is defined as:

$$P = \cos^{-1} [\cos (ELEV_{SPEC}) \cos (ELEVATION) \cos (AZIMUTH - AZ_{SPEC}) + \sin (ELEV_{SPEC}) \sin (ELEVATION)]$$

The results of a typical calculation are shown in Table 1. The first column contains the day of the year (0 - 365), the hours of the day, the minutes of the hour and the seconds of the minute. The time is given in GMT. The next column contains the mission elapsed time (sec). The third column which contains the elapsed time (sec) from the start of an event was included for plotting purposes. The last 5 columns contain the pointing angles from the SPAS position at the time shown in column 1 to a specular point seen at 40, 30, 20, 10 and 0 km. The number 9999.9 in one of these columns indicates that the SPAS cannot see a specular point at that altitude.

TABLE 1  
EXAMPLE OF OUTPUT

DAY HH:MM:SS	MISSION ELAPSED TIME (SEC)	ELAPSED TIME	HEIGHT OF THE SPECULAR POINT				
			40 KM	30 KM	20 KM	10 KM	0 KM
121/23:42:11.00	302937.00	66	14.95	15.01	15.08	15.14	15.20
121/23:42:12.00	302938.00	67	14.90	14.97	15.03	15.09	15.15
121/23:42:13.00	302939.00	68	14.85	14.92	14.98	15.04	15.11
121/23:42:14.00	302940.00	69	14.81	14.87	14.93	14.99	15.06
121/23:42:15.00	302941.00	70	14.76	14.82	14.88	14.95	15.01
121/23:42:16.00	302942.00	71	14.71	14.77	14.84	14.90	14.96
121/23:42:17.00	302943.00	72	14.66	14.73	14.79	14.85	14.92
121/23:42:18.00	302944.00	73	14.76	14.68	14.74	14.80	14.87
121/23:42:19.00	302945.00	74	14.57	14.63	14.69	14.76	14.82
121/23:42:21.00	302947.00	76	14.48	14.54	124.60	14.67	14.73
121/23:42:22.00	302948.00	77	14.43	14.49	14.56	14.62	14.68
121/23:42:23.00	302949.00	78	14.38	14.44	14.51	14.57	14.64
121/23:42:24.00	302950.00	79	14.33	14.40	14.46	14.52	14.59
121/23:42:25.00	302951.00	80	14.28	14.35	14.41	14.48	14.54
121/23:42:26.00	302952.00	81	14.24	14.30	14.36	14.43	14.49
121/23:42:27.00	302953.00	82	14.19	14.25	14.32	14.38	14.45
121/23:42:28.00	302954.00	83	14.15	14.21	14.28	14.34	14.41
121/23:42:29.00	302955.00	84	14.10	14.17	14.23	14.30	14.36
121/23:42:30.00	302956.00	85	14.06	14.12	14.19	14.25	14.32
121/23:42:31.00	302957.00	86	14.01	14.07	14.14	14.21	14.27
121/23:42:32.00	302958.00	87	13.96	14.03	14.09	14.16	14.22
121/23:42:33.00	302959.00	88	13.92	13.98	14.05	14.11	14.18
121/23:42:34.00	302960.00	89	13.87	13.94	14.00	14.07	14.13