

AD-A263 185



2

ARMY RESEARCH LABORATORY



Tomographic Analysis of Line-of-Sight Infrared Spectra of Low-Pressure Flames

Kevin L. McNesby
Robert A. Fifer

ARL-TR-108

April 1993

DTIC
ELECTE
APR 26 1993
S E D

93 4 23 011

93-08683



30pg

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1993		3. REPORT TYPE AND DATES COVERED Final, May 1992-Oct 1992
4. TITLE AND SUBTITLE Tomographic Analysis of Line-of-Sight Infrared Spectra of Low-Pressure Flames.			5. FUNDING NUMBERS PR: 1L161102AH43	
6. AUTHOR(S) Kevin L. McNesby and Robert A. Fifer				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-PC Aberdeen Proving Ground, MD 21005-5068			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-B (Tech Lib) Aberdeen Proving Ground, MD 21005-5066			10. SPONSORING / MONITORING AGENCY REPORT NUMBER ARL-TR-108	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Line-of-sight Fourier transform infrared absorption spectra through a 17-torr methane/nitrous oxide flame have been tomographically analyzed using Abel's equations. Relative absorbances for N ₂ O, CH ₄ , CO ₂ , NO, and CO have been mapped for various "slices" of the flame at different heights in the flame. Results indicate that the region of maximum NO and CO formation occurs prior to the luminous region of the flame. The technique is shown to be useful in obtaining data from systems for which line of sight data may be unusable.				
14. SUBJECT TERMS tomography; infrared spectroscopy; low-pressure flames			15. NUMBER OF PAGES 26	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES	v
1. INTRODUCTION	1
2. BACKGROUND	1
3. EXPERIMENTAL	3
4. RESULTS AND DISCUSSION	4
5. CONCLUSION	9
6. REFERENCES	17
DISTRIBUTION LIST	19

DTIC QUALITY INSPECTED 4

Accession For	
NTIS CRA&I	☒
DTIC TAB	☒
Unannounced	☐
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. By moving the line-of-sight path to different values of the lateral coordinate, x , different line-of-sight absorbances, $g(x)$, may be obtained	3
2. Photo of 17-torr methane/nitrous oxide flame used in these experiments. Note the curvature of the luminous region of the flame	5
3. Line-of-sight absorbance spectra at lowest vertical position (0.65-mm HAB) in the 17-torr $\text{CH}_4/\text{N}_2\text{O}$ flame, with the line-of-sight path going from the center to the shroud (edge) region of the flame	7
4. Tomographic reconstruction of localized absorbance (frequency vs. absorbance as a function of axial distance from the burner center) obtained from inversion of the spectra in Figure 3	8
5. Relative peak absorbances for NO, CO, N_2O , CO_2 , and CH_4 as a function of axial distance "r" from flame center 0.65 mm above the burner surface	10
6. Relative peak absorbance of N_2O as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface	11
7. Relative peak absorbance of CH_4 as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface	12
8. Relative peak absorbance of CO_2 as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface	13
9. Relative peak absorbance of CO as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface	14
10. Relative peak absorbance of NO as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface	15

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

Several techniques have been applied to the study of low-pressure flames (Penner, Wang, and Bahadori 1984; Limbaugh 1985). One of the least used is Fourier transform infrared spectroscopy (FTIR), even though a major advantage of using FTIR spectroscopy is that the technique is non-perturbing to the system under investigation (Thorne and Melius 1990). However, drawbacks inherent to FTIR experiments on combustng systems such as line-of-sight limitations (McNesby and Fifer 1991), lack of sensitivity, difficulty in quantifying species and temperature (Anderson and Griffiths 1977), detector nonlinearity (Solomon et al. 1986), and limitations imposed by spectrometer resolution and apodization (Anderson and Griffiths 1975) (if any) have discouraged many investigators. It is not surprising that mass spectrometry, even though it is an intrusive technique, has become a more widely used tool for flame diagnostics (Howard et al. 1992).

The most ubiquitous of the limitations for FTIR transmission spectroscopy of flames is that it is a line-of-sight technique. Recently, Best et al. (1991) published a paper reporting the first use of tomography coupled with FTIR spectroscopy for reconstruction of localized spectra of an axisymmetric flame from line-of-sight absorption measurements. Previously, nonmedical applications of computed tomography have been mainly single wavelength studies in emission and absorption of reacting flows (Emmerman et al. 1980; Best et al. 1991; Hughey and Santavicca 1982).

Although the body of literature on the subject is extensive (Barrett and Swindell 1981; Cormack 1963; Dasch 1992; Penner, Wang, and Bahadori 1984; Limbaugh 1985), tomographic analysis has not become a standard analytical tool in chemistry. In this report, we recount our own efforts at applying tomographic analysis to line-of-sight spectra of low-pressure flames. This work is an extension of our initial efforts reported previously at tomographic reconstruction of FTIR flame spectra (McNesby and Fifer 1992).

2. BACKGROUND

Computed tomography allows the reconstruction of a three-dimensional image of an object by the stacking of two-dimensional "slices" of that object (Shepp and Logan 1974). In computed tomography, obtaining the "slices" is accomplished by computer manipulation of a series of sets of evenly spaced parallel projections through an object. Each set of parallel projections is taken from a different angle or view of the object. When the object is axisymmetric, only one set of parallel projection data is necessary.

Reconstruction of the image of an axisymmetric object from a single set of parallel projections may be accomplished algebraically (the "onion peel" method) using Fourier transforms or by using Abel's equations (Hughey and Santavicca 1982). In the work reported here, Abel's equations are used to analyze FTIR transmission spectra (the raw data input to the reconstruction program are absorbance data) of low-pressure burner flames.

The line-of-sight absorbance at a given frequency for a single absorbing species through an optically thin, axisymmetric medium may be given by

$$g(x) = 2 \int_x^1 f(r) r dr / (r^2 - x^2)^{1/2} \quad (1)$$

where $g(x)$ is the line-of-sight absorbance (projection) through the medium at lateral position x and $f(r)$ is the product of the absorption coefficient times the pressure at radial position r within the axisymmetric medium (Hughey and Santavicca 1982) (see Figure 1). If more than one species absorbed, then $f(r)$ would be a sum of absorption coefficients times pressure. Equation 1 may be solved for $f(r)$ using the Abel transformation

$$f(r) = -1/\pi \int_r^1 g'(x) dx / (x^2 - r^2)^{1/2}$$

where $g'(x)$ denotes the derivative with respect to x of the function $g(x)$. In general, the greater the number of projections, or, in other words, the more parallel line-of-sight spectra obtained, the better the reconstruction (although oversampling may increase error (Dasch [1992])). However, errors in original data tend to be amplified by the transformation process (Hughey and Santavicca 1982), and reconstruction of regions of abrupt change such as at the edge of a flame where large temperature, species, and density gradients occur may be inaccurate (Hughey and Santavicca 1982). Several investigators have tried to determine the best method of overcoming these limitations (Hughey and Santavicca 1982; Dasch 1992).

The general method of solution when Abel's equations are used is to divide the data $g(x)$ into segments and then to fit each of these segments to a polynomial for which an analytical solution to Equation 2 may be obtained (Hughey and Santavicca 1982; Dasch 1992). The process of fitting the data to a function is equivalent to smoothing the data. Smoothing is usually necessary to minimize the noise amplification in the reconstruction mentioned above. Such smoothing or filtering is common to most methods of reconstruction from projection data (Hughey and Santavicca 1982; Dasch 1992).





Figure 1. By moving the line-of-sight path to different values of the lateral coordinate, x , different line-of-sight absorbances, $g(x)$, may be obtained.

3. EXPERIMENTAL

A stoichiometric methane/nitrous oxide ($\text{CH}_4/\text{N}_2\text{O}$) flame was used in all experiments reported here. Total flow rate was 1.8 standard litres per minute. The overall chemical reaction was



Gases were from Matheson Industries, Inc., and were used without further purification. Pressure within the burner chamber was maintained at 17 (+/-0.2) torr. No shroud gas was used in the experiments reported here. Once the flame had stabilized, the pressure within the chamber slowly increased as the chamber heated up. Over the course of an experiment (several hours), the pressure within the chamber typically rose a few hundred millitorr. The stainless steel frit upon which the flame was supported and through which the premixed gases flowed was 70 mm in diameter. Line-of-sight spectral data were collected for 200 scans at 8-cm^{-1} resolution for each projection on a Mattson Polaris FTIR spectrometer. The spectrometer and beam path external to the burner chamber were purged with dry nitrogen gas to

eliminate absorbance from atmospheric gases. The light beam from the interferometer was directed through a low-pressure housing which contained a McKenna Industries flat flame burner modified for low-pressure operation. Beam size was regulated by 0.75-mm circular apertures on interferometer and Hg-Cd-Te detector sides of the low-pressure housing. Combustion gas flow was controlled by an MKS Inc. Model 147B flow controller. Pressure was controlled using a hand-operated valve in the exhaust line between the vacuum chamber and the Leybold Inc. Model 100 vacuum pump. It was found that for the experiments reported here, hand regulation of the pressure was often better than that achieved using an exhaust line mounted butterfly valve slaved to the MKS capacitance manometer used to monitor pressure. No correction was applied to account for beam divergence or for beam walking in any of the spectra collected (Griffiths and de Haseth 1986). The rest of the experimental apparatus has been described in detail in a previous report (McNesby and Fifer 1992).

Reconstruction was accomplished using a nonderivative solution to Abel's equations employing a least squares fit of spline functions to the experimental data (Deutsch and Beniaminy 1983). For each "slice" of the flame investigated, 20 projections were obtained on one side of the burner axis, with the first projection taken through the burner axis. The beam through the burner flame was 1.3 mm in diameter (95% of the radiant power of the apertured interferometer beam was contained within this diameter). Projections were spatially separated by 2 mm (beam center to beam center). Because of space restrictions within the burner chamber, it was not possible to obtain a complete set of spectra for each side of the burner axis. So, prior to reconstruction, the projections through one side of the burner axis were reflected about the burner axis. A check of parallel projections taken at equal distances from opposite sides of the burner axis (where possible) gave spectra which were superimposable.

4. RESULTS AND DISCUSSION

The appearance of the 17-torr $\text{CH}_4/\text{N}_2\text{O}$ flame used in these experiments is shown in Figure 2. Note the curvature exhibited at the underside of the luminous region of the flame. This curvature indicates that the flame is approaching the "blow off" point (Thorne and Smith 1988), i.e., the pressure and flow rate combination are such that the burner frit will no longer support the flame. Also evident is a nonluminous zone approximately 4 mm in height immediately above the burner surface. Figure 3 shows a series of parallel line-of-sight absorbance spectra (evacuated chamber used as reference), separated by 4 mm, through the flame shown in Figure 2, at a height above the burner (HAB) surface of 0.65 mm. The constant CO_2 absorbance (centered at $2,349\text{ cm}^{-1}$) due to "cold" gases (i.e., not within the vertical cylinder proscribed by the burner diameter) outside the flame region is evident in each spectrum. Figure 4 shows the tomographic reconstruction using the spectra shown in Figure 3. This figure is dominated by the




Figure 2. The 17-torr methane/nitrous oxide flame used in these experiments. Note the curvature of the luminous region of the flame.

Following Page Intentionally Left Blank




Figure 3. Line-of-sight absorbance spectra at lowest vertical position in the 17-torr $\text{CH}_4/\text{N}_2\text{O}$ flame, with the line-of-sight path going from the center (bottom spectrum) to the shroud (edge) region (top spectrum) of the flame.

Reconstructed Spectrum 0.65 mm IAB

absorbance




Figure 4. Tomographic reconstruction of localized absorbance (frequency vs. absorbance as a function of axial distance from the burner center) obtained from inversion of the spectra in Figure 3.

asymmetric and symmetric stretches of N_2O (at $2,223\text{ cm}^{-1}$ and $1,285\text{ cm}^{-1}$, respectively) and by the CH stretch of methane (Herzberg 1950) ($3,020\text{ cm}^{-1}$). This figure shows that just above the burner surface there is a higher concentration (absorption coefficient times pressure) of methane and nitrous oxide at the edge of the burner than at the center of the burner. The luminous portion of the flame may affect the density of the fuel-oxidizer mixture in the nonluminous region by creating a temperature gradient within the nonluminous zone. The curvature of the luminous zone may be responsible for the varying concentration profile of methane and nitrous across the face of the burner at levels immediately above the burner surface. The spike in the reconstruction around $2,360\text{ cm}^{-1}$ is probably spurious and due to noise in the line-of-sight data. The error in all reconstructions, based on reconstructions of synthetic data (round off error used to simulate noise [Hughey and Santavicca 1982]), is believed to be approximately 10%.

Figure 5 shows relative peak absorbances (at one selected frequency for each species) for N_2O , CH_4 , CO_2 , CO, and NO as a function of distance from the burner center through a "slice" of the flame 0.65 mm above the burner surface. The actual spatial resolution can be no better than the diameter of the probe beam, in this case equal to 1.3 mm. Figures 6 through 10 show relative peak absorbances (at one selected frequency for each species) for N_2O , CH_4 , CO_2 , CO, and NO, respectively, at HAB surface from 0.65 mm to 13.05 mm as a function of distance from the burner center. The contour at the top of each figure is due to absorbance nearest the burner surface. Figures 9 and 10 show that for this flame, the region of highest CO and NO concentration, respectively, occurs approximately 3 mm above the burner surface in the nonluminous region of the flame. These results are in agreement with recently reported results on $\text{CH}_4/\text{N}_2\text{O}$ low-pressure flames obtained using mass spectrometry (Vandooren, Branch, and Van Tiggelen 1992), although the peak in NO concentration followed by a decrease in the burned gas region has not been reported previously.

Obtaining absolute species concentrations requires knowledge of local temperatures and the dependence of the absorption coefficient for each species upon temperature (Ouyang and Varghese 1990). Work is presently being performed in which tomographic reconstruction of infrared diode laser spectra of CO will be used to obtain local temperatures.

5. CONCLUSION

We have shown that tomographic reconstruction using line-of-sight transmission spectra of low-pressure flames can be of use in evaluating the chemistry occurring within low pressure flames. At

0.65 mm IAB 1.25 mm Beam Diameter

17 Torr CH₄/N₂O Flame




Figure 5. Relative peak absorbances for NO, CO, N₂O, CO₂, and CH₄ as a function of axial distance "r" from flame center 0.65 mm above the burner surface.

N₂O Absorbance 17 torr CH₄/N₂O Flame




Figure 6. Relative peak absorbance of N₂O as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface.

CH4 Absorbance 17 torr CH4/N2O Flame




Figure 7. Relative peak absorbance of CH₄ as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface.

CO₂ Absorbance 17 torr CH₄/N₂O Flame




Figure 8. Relative peak absorbance of CO₂ as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface.

CO Absorbance 17 torr CH₄/N₂O Flame




Figure 9. Relative peak absorbance of CO as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface.

NO Absorbance 17 torr CH₄/N₂O Flame




Figure 10. Relative peak absorbance of NO as a function of axial distance from flame center and HAB surface. Contour at top of figure is closest to burner surface.

present the technique is labor intensive, but with improved optics and array detectors, and improved signal-to-noise ratio, the technique may become routine. We are presently working on obtaining quantitative results by extending the technique to infrared diode laser spectroscopy, and using the information obtained as a calibration for tomographic reconstruction using FTIR line-of-sight spectra.

6. REFERENCES

- Anderson, R. J., and P. R. Griffiths. "Errors in Absorbance Measurements in Infrared Fourier Transform Spectrometry Because of Limited Instrument Resolution." Analytical Chemistry, vol. 47, p. 2339, 1975.
- Anderson, R. J., and P. R. Griffiths. "Determination of Rotational Temperatures of Diatomic Molecules From Absorption Spectra Measured at Moderate Resolution." Journal of Quantitative Spectroscopy and Radiative Transfer, vol. 17, pp. 393-401, 1977.
- Barrett, H. H., and W. Swindell. Radiological Imaging. New York: Academic Press, 1981.
- Best, P. E., P. L. Chien, R. M. Carangelo, P. R. Solomon, M. Danchak, and I. Ilovici. "Tomographic Reconstruction of FTIR Emission and Transmission Spectra in a Sooting Laminar Diffusion Flame: Species Concentrations and Temperatures." Combustion and Flame, vol. 85, pp. 309-318, 1991.
- Cornack, A. M. "Representation of a Function By its Line Integrals, With Some Radiological Implications." Journal of Applied Physics, vol. 34, pp. 2722-2727, 1963.
- Dasch, C. J. "One-Dimensional Tomography: A Comparison of Abel, Onion-Peeling, and Filtered Backprojection Methods." Applied Optics, vol. 31, pp. 1146-1152, 1992.
- Deutsch, M., and I. Beniaminy. "Inversion of Abel's Integral Equation for Experimental Data." Journal of Applied Physics, vol. 54, pp. 137-143, 1983.
- Emmerman, P. J., R. Goulard, R. J. Santoro, and H. G. Semerjian. "Multiangular Absorption Diagnostics of a Turbulent Argon-Methane Jet." Journal of Energy, vol. 4, pp. 70-77, 1980.
- Griffiths, P. R., and J. A. de Haseth. Fourier Transform Infrared Spectrometry. New York: Wiley and Sons, 1986.
- Herzberg, G. Infrared and Raman Spectra. New York: Van Nostrand, 1950.
- Howard, S. L., J. E. Newberry, R. C. Sausa, and A. W. Miziolek. "Triple Quadrupole Mass Spectrometry Diagnostics of Propellant-Like Flames." BRL-TR-3352, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1992.
- Hughey, B. J., and D. A. Santavicca. "A Comparison of Techniques for Reconstructing Axisymmetric Reacting Flow Fields from Absorption Measurements." Combustion and Science Technology, vol. 29, pp. 167-190, 1982.
- Limbaugh, C. C. "Infrared Methods for Gaseous Measurements." Optical Engineering, vol. 7, edited by J. Wormhoudt, 1985.
- McNesby, K. L., and R. A. Fifer. "Infrared Diode Laser and Fourier Transform Spectroscopy of a Low Pressure Premixed Gas Flame." 28th JANNAF Combustion Subcommittee Meeting, CPIA Publication 573, vol. 2, pp. 533-539, Columbia, MD, 1991.

- McNesby, K. L., and R. A. Fifer. "Tomographic Reconstruction of Infrared Spectra of Non-Homogeneous Media: Applications to a Flat Flame Burner." BRL-TR-3333, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, April 1992.
- Ouyang, X., and P. L. Varghese. "Selection of Spectral Lines for Combustion Diagnostics." Applied Optics, vol. 29, pp. 4884-4890, 1990.
- Penner, S. S., C. P. Wang, and M. Y. Bahadori. "Laser Diagnostics Applied to Combustion Systems." 20th Symposium (International) on Combustion, pp. 1149-1176, 1984.
- Shepp, L. A., and B. F. Logan. "Reconstructing Interior Head Tissue From X-Ray Transmissions." IEEE Transactions on Nuclear Science NS-21, pp. 228-237, 1974.
- Solomon, P. R., R. M. Carangelo, D. G. Hamblen, and P. E. Best. "Infrared Analysis of Particulates by FTIR Emission/Transmission Spectroscopy." Applied Spectroscopy, vol. 40, pp. 746-759, 1986.
- Thorne, L. R., and C. F. Melius. "The Structure of Hydrogen Cyanide-Nitrogen Dioxide Premixed Flames." 23rd Symposium (International) on Combustion, pp. 397-403, 1990.
- Thorne, L. R., and O. I. Smith. "The Structure of Cyanogen-NO₂ Premixed Flames." Delivered at the 25th JANNAF Combustion Meeting, Huntsville, Alabama, 1988 (also see paper by David Dayton this meeting).
- Vandooren, J., M. C. Branch, and P. J. Van Tiggelen. "Comparisons of the Structure of Stoichiometric CH₄-N₂O-Ar and CH₄-O₂-Ar Flames by Molecular Beam Sampling and Mass Spectrometric Analysis." Combustion and Flame, vol. 90, pp. 247-258, 1992.

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Camcron Station Alexandria, VA 22304-6145	1	Commander U.S. Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander U.S. Army Materiel Command ATTN: AMCAM 5001 Eisenhower Ave. Alexandria, VA 22333-0001	1	Commander U.S. Army Tank-Automotive Command ATTN: ASQNC-TAC-DIT (Technical Information Center) Warren, MI 48397-500C
1	Director U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-AD, Tech Publishing 2800 Powder Mill Rd. Adelphi, MD 20783-1145	1	Director U.S. Army TRADOC Analysis Command ATTN: ATRC-WSR White Sands Missile Range, NM 88002-5502
1	Director U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-AD, Records Management 2800 Powder Mill Rd. Adelphi, MD 20783-1145	1	Commandant U.S. Army Field Artillery School ATTN: ATSF-CSI Ft. Sill, OK 73503-5000
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000	(Class. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	(Unclass. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
1	Director Benet Weapons Laboratory U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050	1	WL/MNOI Eglin AFB, FL 32542-5000
(Unclass. only) 1	Commander U.S. Army Rock Island Arsenal ATTN: SMCRI-IMC-RT/Technical Library Rock Island, IL 61299-5000		<u>Aberdeen Proving Ground</u>
1	Director U.S. Army Aviation Research and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center Moffett Field, CA 94035-1000	2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
		1	Cdr, USATECOM ATTN: AMSTE-TC
		1	Dir, ERDEC ATTN: SCBRD-RT
		1	Cdr, CBDA ATTN: AMSCB-CI
		1	Dir, USARL ATTN: AMSRL-SL-I
		10	Dir, USARL ATTN: AMSRL-OP-CI-B (Tech Lib)

<u>No. of Copies</u>	<u>Organization</u>
1	HQDA (SARD-TC, C.H. Church) WASH DC 20310-0103
4	Commander US Army Research Office ATTN: R. Ghirardelli D. Mann R. Singleton R. Shaw P.O. Box 12211 Research Triangle Park, NC 27709-2211
2	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-B, D.S. Downs SMCAR-AEE, J.A. Lannon Picatinny Arsenal, NJ 07806-5000
1	Commander US Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE-BR, L. Harris Picatinny Arsenal, NJ 07806-5000
2	Commander US Army Missile Command ATTN: AMSMI-RD-PR-E, A.R. Maykut AMSMI-RD-PR-P, R. Betts Redstone Arsenal, AL 35898-5249
1	Office of Naval Research Department of the Navy ATTN: R.S. Miller, Code 432 800 N. Quincy Street Arlington, VA 22217
1	Commander Naval Air Systems Command ATTN: J. Ramnarace, AIR-54111C Washington, DC 20360
1	Commander Naval Surface Warfare Center ATTN: J.L. East, Jr., G-23 Dahlgren, VA 22448-5000
2	Commander Naval Surface Warfare Center ATTN: R. Bernecker, R-13 G.B. Wilmot, R-16 Silver Spring, MD 20903-5000

<u>No. of Copies</u>	<u>Organization</u>
5	Commander Naval Research Laboratory ATTN: M.C. Lin J. McDonald E. Oran J. Shnur R.J. Doyle, Code 6110 Washington, DC 20375
1	Commanding Officer Naval Underwater Systems Center Weapons Dept. ATTN: R.S. Lazar/Code 36301 Newport, RI 02840
2	Commander Naval Weapons Center ATTN: T. Boggs, Code 388 T. Parr, Code 3895 China Lake, CA 93555-6001
1	Superintendent Naval Postgraduate School Dept. of Aeronautics ATTN: D.W. Netzer Monterey, CA 93940
3	AL/LSCF ATTN: R. Corley R. Geisler J. Levine Edwards AFB, CA 93523-5000
1	AFOSR ATTN: J.M. Tishkoff Bolling Air Force Base Washington, DC 20332
1	OSD/SDIO/IST ATTN: L. Caveny Pentagon Washington, DC 20301-7100
1	Commandant USAFAS ATTN: ATSF-TSM-CN Fort Sill, OK 73503-5600
1	F.J. Seiler ATTN: S.A. Shackelford USAF Academy, CO 80840-6528

<u>No. of Copies</u>	<u>Organization</u>
1	University of Dayton Research Institute ATTN: D. Campbell AL/PAP Edwards AFB, CA 93523
1	NASA Langley Research Center Langley Station ATTN: G.B. Northam/MS 168 Hampton, VA 23365
4	National Bureau of Standards ATTN: J. Hastie M. Jacox T. Kashiwagi H. Semerjian US Department of Commerce Washington, DC 20234
1	Applied Combustion Technology, Inc. ATTN: A.M. Varney P.O. Box 607885 Orlando, FL 32860
2	Applied Mechanics Reviews The American Society of Mechanical Engineers ATTN: R.E. White A.B. Wenzel 345 E. 47th Street New York, NY 10017
1	Atlantic Research Corp. ATTN: R.H.W. Waesche 7511 Wellington Road Gainesville, VA 22065
1	AVCO Everett Research Laboratory Division ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149
1	Battelle ATTN: TACTEC Library, J. Huggins 505 King Avenue Columbus, OH 43201-2693
1	Cohen Professional Services ATTN: N.S. Cohen 141 Channing Street Redlands, CA 92373

<u>No. of Copies</u>	<u>Organization</u>
1	Exxon Research & Eng. Co. ATTN: A. Dean Route 22E Annandale, NJ 08801
1	General Applied Science Laboratories, Inc. 77 Raynor Avenue Ronkonkama, NY 11779-6649
1	General Electric Ordnance Systems ATTN: J. Mandzy 100 Plastics Avenue Pittsfield, MA 01203
1	General Motors Rsch Labs Physical Chemistry Department ATTN: T. Sloane Warren, MI 48090-9055
2	Hercules, Inc. Allegheny Ballistics Lab. ATTN: W.B. Walkup E.A. Yount P.O. Box 210 Rocket Center, WV 26726
1	Alliant Techsystems, Inc. Marine Systems Group ATTN: D.E. Broden/MS MN50-2000 600 2nd Street NE Hopkins, MN 55343
1	Alliant Techsystems, Inc. ATTN: R.E. Tompkins 7225 Northland Drive Brooklyn Park, MN 55428
1	IBM Corporation ATTN: A.C. Tam Research Division 5600 Cottle Road San Jose, CA 95193
1	IIT Research Institute ATTN: R.F. Remaly 10 West 35th Street Chicago, IL 60616

<u>No. of Copies</u>	<u>Organization</u>
2	Director Lawrence Livermore National Laboratory ATTN: C. Westbrook M. Constantino P.O. Box 808 Livermore, CA 94550
1	Lockheed Missiles & Space Co. ATTN: George Lo 3251 Hanover Street Dept. 52-35/B204/2 Palo Alto, CA 94304
1	Director Los Alamos National Lab ATTN: B. Nichols, T7, MS-B284 P.O. Box 1663 Los Alamos, NM 87545
1	National Science Foundation ATTN: A.B. Harvey Washington, DC 20550
1	Olin Ordnance ATTN: V. McDonald, Library P.O. Box 222 St. Marks, FL 32355-0222
1	Paul Gough Associates, Inc. ATTN: P.S. Gough 1048 South Street Portsmouth, NH 03801-5423
2	Princeton Combustion Research Laboratories, Inc. ATTN: N.A. Messina M. Summerfield Princeton Corporate Plaza Bldg. IV, Suite 119 11 Deerpark Drive Monmouth Junction, NJ 08852
1	Hughes Aircraft Company ATTN: T.E. Ward 8433 Fallbrook Avenue Canoga Park, CA 91303

<u>No. of Copies</u>	<u>Organization</u>
1	Rockwell International Corp. Rocketdyne Division ATTN: J.E. Flanagan/HB02 6633 Canoga Avenue Canoga Park, CA 91304
4	Director Sandia National Laboratories Division 8354 ATTN: R. Cattolica S. Johnston P. Mattern D. Stephenson Livermore, CA 94550
1	Science Applications, Inc. ATTN: R.B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364
3	SRI International ATTN: G. Smith D. Crosley D. Golden 333 Ravenswood Avenue Menlo Park, CA 94025
1	Stevens Institute of Tech. Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030
1	Sverdrup Technology, Inc. LERC Group ATTN: R.J. Locke, MS SVR-2 2001 Aerospace Parkway Brook Park, OH 44142
1	Sverdrup Technology, Inc. ATTN: J. Deur 2001 Aerospace Parkway Brook Park, OH 44142
1	Thiokol Corporation Elkton Division ATTN: S.F. Palopoli P.O. Box 241 Elkton, MD 21921

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
3	Thiokol Corporation Wasatch Division ATTN: S.J. Bennett P.O. Box 524 Brigham City, UT 84302	1	University of California, Berkeley Chemistry Department ATTN: C. Bradley Moore 211 Lewis Hall Berkeley, CA 94720
1	United Technologies Research Center ATTN: A.C. Eckbreth East Hartford, CT 06108	1	University of California, San Diego ATTN: F.A. Williams AMES, B010 La Jolla, CA 92093
1	United Technologies Corp. Chemical Systems Division ATTN: R.R. Miller P.O. Box 49028 San Jose, CA 95161-9028	2	University of California, Santa Barbara Quantum Institute ATTN: K. Schofield M. Steinberg Santa Barbara, CA 93106
1	Universal Propulsion Company ATTN: H.J. McSpadden 25401 North Central Avenue Phoenix, AZ 85027-7837	1	University of Colorado at Boulder Engineering Center ATTN: J. Daily Campus Box 427 Boulder, CO 80309-0427
1	Veritay Technology, Inc. ATTN: E.B. Fisher 4845 Millersport Highway P.O. Box 305 East Amherst, NY 14051-0305	2	University of Southern California Dept. of Chemistry ATTN: S. Benson C. Wittig Los Angeles, CA 90007
1	Brigham Young University Dept. of Chemical Engineering ATTN: M.W. Beckstead Provo, UT 84058	1	Cornell University Department of Chemistry ATTN: T.A. Cool Baker Laboratory Ithaca, NY 14853
1	California Institute of Tech. Jet Propulsion Laboratory ATTN: L. Strand/MS 125-224 4800 Oak Grove Drive Pasadena, CA 91109	1	University of Delaware ATTN: T. Brill Chemistry Department Newark, DE 19711
1	California Institute of Technology ATTN: F.E.C. Culick/MC 301-46 204 Karman Lab. Pasadena, CA 91125	1	University of Florida Dept. of Chemistry ATTN: J. Winefordner Gainesville, FL 32611
1	University of California Los Alamos Scientific Lab. P.O. Box 1663, Mail Stop B216 Los Alamos, NM 87545	3	Georgia Institute of Technology School of Aerospace Engineering ATTN: E. Price W.C. Strahle B.T. Zinn Atlanta, GA 30332

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	University of Illinois Dept. of Mech. Eng. ATTN: H. Krier 144MEB, 1206 W. Green St. Urbana, IL 61801	1	Purdue University School of Aeronautics and Astronautics ATTN: J.R. Osborn Grissom Hall West Lafayette, IN 47906
1	The Johns Hopkins University Chemical Propulsion Information Agency ATTN: T.W. Christian 10630 Little Patuxent Parkway, Suite 202 Columbia, MD 21044-3200	1	Purdue University Department of Chemistry ATTN: E. Grant West Lafayette, IN 47906
1	University of Michigan Gas Dynamics Lab Aerospace Engineering Bldg. ATTN: G.M. Faeth Ann Arbor, MI 48109-2140	2	Purdue University School of Mechanical Engineering ATTN: N.M. Laurendeau S.N.B. Murthy TSPC Chaffee Hall West Lafayette, IN 47906
1	University of Minnesota Dept. of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455	1	Rensselaer Polytechnic Inst. Dept. of Chemical Engineering ATTN: A. Fontijn Troy, NY 12181
3	Pennsylvania State University Applied Research Laboratory ATTN: K.K. Kuo H. Palmer M. Micci University Park, PA 16802	1	Stanford University Dept. of Mechanical Engineering ATTN: R. Hanson Stanford, CA 94305
1	Pennsylvania State University Dept. of Mechanical Engineering ATTN: V. Yang University Park, PA 16802	1	University of Texas Dept. of Chemistry ATTN: W. Gardiner Austin, TX 78712
1	Polytechnic Institute of NY Graduate Center ATTN: S. Lederman Route 110 Farmingdale, NY 11735	1	Virginia Polytechnic Institute and State University ATTN: J.A. Schetz Blacksburg, VA 24061
2	Princeton University Forrestal Campus Library ATTN: K. Brezinsky I. Glassman P.O. Box 710 Princeton, NJ 08540	1	Freedman Associates ATTN: E. Freedman 2411 Diana Road Baltimore, MD 21209-1525

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number ARL-TR-108 Date of Report April 1993

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL

FIRST CLASS PERMIT No 0001, APG, MD

Postage will be paid by addressee.

Director
U.S. Army Research Laboratory
ATTN: AMSRL-OP-CI-B (Tech Lib)
Aberdeen Proving Ground, MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

