

AD-A264 056

JMENTATION PAGE

Form Approved
OMB No 0704-0188

It is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and reviewing the collection of information, sending comments regarding this burden estimate or any other aspect of this collection of information, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 3-26-93		3. REPORT TYPE AND DATES COVERED Annual 1 Aug 90 - 30 Jul 91	
4. TITLE AND SUBTITLE Computing with neural maps: application to perceptual and cognitive function				5. FUNDING NUMBERS AFOSR 88-0275 G1102F 233/A8 2305/B3	
6. AUTHOR(S) Eric L. Schwartz				7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) New York University Medical Center 550 First Ave. New York 10016 N.Y.	
8. PERFORMING ORGANIZATION REPORT NUMBER AFOSR 88-0275 93 14				9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Dr John F. Tangney AFOSR/NL Building 410, Duncan Ave, Suite B115 Bolling Air Force Base DC 20332-0001	
10. SPONSORING/MONITORING AGENCY REPORT NUMBER DTIC ELECTE MAY 13 1993				11. SUPPLEMENTARY NOTES	
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				12b. DISTRIBUTION STATEMENT 93-10273 498	
13. ABSTRACT (Maximum 200 words) 93 5 1 03 2 Models for visual attention, based on the representation of an attentional space as a two dimensional map have led to a model of visual attention which has been successfully used in the application of a space-variant active vision system, described below. Also, it has been demonstrated that stereo fusion limits, such as Panum's fusional area, scale in a manner which is determined by the size of a cortical hypercolumn, and the local value of cortical magnification factor. This in turn supports the notion that stereo disparity is computed by a local correlational operator defined on the span of a single pair of ocular dominance columns. A generalized image warp technique has been developed, which we term the "protocolumn algorithm", which provides image level models of the mapping of ocular dominance and orientation column systems at the level at the level of primary visual cortex. Finally, many of the ideas developed in this project have reached fruition in the construction of a space-variant active vision system. An initial prototype system has been constructed under hardware support from DARPA, and a number of difficult algorithmic problems in motor control, attention, space-variant image processing, and space-variant pattern classification, have begun to be studied.					
14. SUBJECT TERMS Visual cortex, vision, pattern recognition, active vision				15. NUMBER OF PAGES 4	
16. PRICE CODE				17. SECURITY CLASSIFICATION OF REPORT (u)	
18. SECURITY CLASSIFICATION OF THIS PAGE (u)				19. SECURITY CLASSIFICATION OF ABSTRACT (u)	
20. LIMITATION OF ABSTRACT (u)					

NSN 7540-01-280-5500

3 1 MAR 1993

Standard Form 298 (Rev 2-89)
Prescribed by ANSI Std Z39-18
298-102

YEARLY REPORT: 1991-1992**AFOSR Life Sciences 88-0275****P.I.: Eric L. Schwartz***Dept. of Cognitive and Neural Systems**Boston University**111 Cummington Street**Boston MA 02215**eric@thing4.bu.edu***SUMMARY**

Models for visual attention, based on the representation of an attentional space as a two dimensional map have led to a model of visual attention which has been successfully used in the application of a space-variant active vision system, described below. Also, it has been demonstrated that stereo fusion limits, such as Panum's fusional area, scale in a manner which is determined by the size of a cortical hypercolumn, and the local value of cortical magnification factor. This in turn supports the notion that stereo disparity is computed by a local correlational operator defined on the span of a single pair of ocular dominance columns. A generalized image warp technique has been developed, which we term the "protocolumn algorithm", which provides image level models of the mapping of ocular dominance and orientation column systems at the level of primary visual cortex. Finally, many of the ideas developed in this project have reached fruition in the construction of a space-variant active vision system. An initial prototype system has been constructed under hardware support from DARPA, and a number of difficult algorithmic problems in motor control, attention, space-variant image processing, and space-variant pattern classification, have begun to be studied.

DTIC QUALITY INSPECTED 1

Accession For	
NTIS CRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

PUBLICATIONS

LIST OF PAPERS AND TECHNICAL REPORTS

- [1] Alan Rojer and Eric Schwartz. The hough transform as bayesian inference. Technical Report 564, Courant Institute of Mathematical Sciences, 251 Mercer Street, New York, N.Y., May 1991.
- [2] Eric L. Schwartz and Alan S. Rojer. Cortical hypercolumns and the topology of random orientation maps. Technical Report 593, Courant Institute of Mathematical Sciences, 251 Mercer Street, May 1991.
- [3] Eric L. Schwartz and Alan S. Rojer. A computational study of cortical hypercolumns and the topology of random orientation maps. *Society for Neuroscience Abstracts*, 18:742, 1992.
- [4] David Rosenbluth, Amar Munsiff, Tom Albright, and Eric Schwartz. Computer reconstruction from 2dg serial sections of the topographic map of macaque visual cortex. *Society for Neuroscience Abstracts*, 18:742, 1992.
- [5] Ben Bederson, Richard Wallace, and Eric Schwartz. A miniatureized active vision system. *Int. Conf. Pattern Recog*, page In press, 1992.
- [6] Ping Wen Ong, Ben Bederson, Richard Wallace, and Eric Schwartz. Space variant optical character recognition. *11th International Conference on Pattern Recognition*, page In press, 1992.
- [7] Alan S. Roier and Eric L. Schwartz. Biological basis for space-variant sensor design: Implications for vlsi. In *SPIE Program on Computer Vision and Intelligent Robots IX: Advances in Intelligent Machines*, 1992.
- [8] Alan S. Rojer and Eric L. Schwartz. Fusion of multiple fixations with a space-variant sensor: conditional optimality of maximum resolution blending. In *SPIE Computer Vision and Intelligent Robots IX: Symposium on Advances in Intelligent Machines*, 1992.
- [9] Alan Rojer and Eric L. Schwartz. A quotient space hough transform for space variant visual attention. In Gail Carpenter and Stephen Grossberg, editors, *Neural Networks for Vision and Image Processing*, pages 407–436. 1992.
- [10] E. Ruppin, E. Schwartz, and Y. Yeshurun. Efficient packing of massively connected multi processor networks: Implications for biological and artificial systems. *Biol. Cybernetics*, page (Submitted), 1992.
- [11] Pierre Landau. Computer simulation of cortical polymaps: a proto-column algorithm. *Neural Networks*, 5:187–206, 1992.
- [12] E. L. Schwartz and H. Yeshurun. Cortical hypercolumn size determines stereo fusion limits. *Bio. Cybernetics*, 1992.
- [13] Richard S. Wallace, Benjamin B. Bederson, and Eric L. Schwartz. Voice-bandwidth visual communication through logmaps. *I.E.E.E. Workshop on Applications of Computer Vision*, page In press, 1992.

- [14] Y. Yeshurun and E.L. Schwartz. Stereo disparity estimation by cepstral filtering. *Bio. Cybernetics (submitted)*, 1992.
- [15] Ben Bederson, Richard Wallace, and Eric Schwartz. Control and design of the spherical pointing motor. *Machine Vision and Applications*, page In press, 1993.
- [16] Richard Wallace, Ping-Wen Ong, Ben Bederson, and Eric Schwartz. Space variant image processing. *International Journal of Machine Vision*, page In press, 1993.