

AD-A264 846



DOCUMENTATION PAGE

Form Approved
OMB No 0704-0188

2

2a. SECURITY CLASSIFICATION (AUTHORITY) SELECTE MAY 25 1993			1b. RESTRICTIVE MARKINGS		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE			3. DISTRIBUTION/AVAILABILITY OF REPORT Unrestricted		
4. PERFORMING ORGANIZATION REPORT NUMBER(S) 447248 - 3			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION Dept. of E.E. City College of New York		6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION AFOSR/NE		
6c. ADDRESS (City, State, and ZIP Code) 138th St. & Convent Ave. New York, NY 10031.			7b. ADDRESS (City, State, and ZIP Code) Building 410 Bolling AFB, DC 20332-0448		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION AFOSR		8b. OFFICE SYMBOL (If applicable) NE	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER AFOSR 88-0260		
8c. ADDRESS (City, State, and ZIP Code) Bolling AFB DC 20332			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO 61102F	PROJECT NO 2305	TASK NO B4
11. TITLE (Include Security Classification) Massively Parallel Spatial Light Modulation-based Optical Signal Processing					
12. PERSONAL AUTHOR(S) Yao Li					
13a. TYPE OF REPORT FINAL		13b. TIME COVERED FROM 7/90 TO 9/92		14. DATE OF REPORT (Year, Month, Day) 93, March, 21	
15. PAGE COUNT					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Optical Computing Signal Processing and Interconnect		
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
A new optical parallel arithmetic processing scheme using a nonholographic optoelectronic content-addressable memory (CAM) was proposed. The design of a four-bit CAM-based optical carry look-ahead adder was studied. Compared with existing optoelectronic binary addition approaches, this nonholographic CAM scheme offers a number of practical advantages, such as faster processing speed and ease of optical implementation and alignment. For an addition of numbers longer than four bits, by incorporating the previous stage's carry, a number of four-bit CLA's can be cascaded. Experimental results were also demonstrated. One paper to the Optics Letters was published.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNC		
22a. NAME OF RESPONSIBLE INDIVIDUAL Dr. Alan E. Craig / NE			22b. TELEPHONE (Include Area Code) (202) 767-4931		22c. OFFICE SYMBOL NE

93-11593



SP1

Because of the lack of fast, accurate and large dynamic range analog-to-digital devices, optical implementation of the digital multiplication through analog convolution (DMAC) algorithm yields a slow digital multiplier. By replacing both the optical adder and A/D converter arrays by an optical combinatorial logic counter array, a new optical fast digital multiplication method was studied. Compared to the existing optical DMAC scheme, the new method promises both higher processing speed and accuracy. A comparison of this and some of the other optical and electronic fast digital multiplication schemes was also detailed. One paper to the Applied Optics was published.

Two new optical free-space collinear cross-over interconnect schemes were suggested. The first optical implementation uses mirrors and beam-splitters, while the second uses a Fresnel zone plate and lens combination. Both schemes allow for practical cascading to form multistage interconnect networks. The Fresnel zone plate based approach has an additional advantage, e.g. it can perform a 2D cross-over of 1D folded data so that the overall interconnect throughput is greatly increased. Design issues of such interconnects are addressed and proof-of-principle experiments were demonstrated. One paper to the Applied Optics is to be published in Apr. 1991.

Based on a electronically addressed spatial light modulator as an input device, a degenerate photorefractive optical phase conjugator, a new real-time coherent optical Wigner distribution and ambiguity function generation method for both 1D and 2D complex signals was proposed. As compared to all the existing Wigner methods, the new scheme allows for processing real-time phase-only as well as general complex signals. The new method can also be extended to perform ambiguity function evaluation of complex signals. Experimental results of the processor were presented. One paper to the Applied Optics was published.

A novel optical analog-to-digital (A/D) conversion scheme that uses a real-time theta modulation followed by a table look-up was investigated. As a fast theta modulator, a wide-band acousto-optic (A-O) deflector that performs a voltage to optical beam

deflection angle mapping, was used. Using a GaP A-O deflector, a proof-of-principle 6-bit A/D converter was experimentally demonstrated. Design issues and device fundamental limits were studied. One paper summarizing the study was published in Applied Optics.

The existing linear and rectangular processor distribution topologies for optical interconnects, although promising in many respects, can not solve problems such as clock skews, the lack of supporting elements for efficient optical implementation, etc. The use of a ring array processor distribution topology, however, can overcome these problems. One effort of studying the ring array topology was conducted with an aim of implementing various fast clock rate, high performance, compact optical networks for digital electronic multiprocessor computers. Practical design issues are addressed. A 36 node LED and Si PIN diode based ring interconnect network was experimentally fabricated and tested. A detailed research report was published in Applied Optics.

Based on our preliminary study of the ring array processor distribution topology, a compact reflective ring array interconnect was designed. The designed network can be reconfigured to perform the task of either a nearest neighbor interconnect or a plus-minus 2I interconnect. Our system study has shown that the design of the supporting optical imaging system for the proposed architecture is easier to be handled than that using a conventional rectangular array topology. Design principles for both the individual optical components and the entire optical system was carried out using the ZEMAX software. The network performance parameters, such as the diffraction- and aberration-related processing capabilities, the optical transmitter coupling efficiency, the optical free-space power distribution loss, the detector dynamic range requirement, and the power-dependent elemental-bit-rate, are analyzed. The report summarizing the study has been submitted to and accepted by the Applied Optics for publication.

NTIS ✓

By _____	
Distribution / _____	
Availability Codes	
Dist	Avail and/or Special
A-1	

Recently, we have also investigated the possibility of implementing an optical shared content addressable memory (S-CAM) processor based on simple and efficient optical switches and free-space optical components. Electronic version of a CAM is usually based on the use of a digital programmable logic array (PLA) which only allows sharing among parallel I/O's in the time domain. Many computation applications, however, do require parallel sharing of memory information among various processors. Free-space optics provides such inherent parallelism to implement the sharing. In this study, we took a specific application example of building an N-bit modified signed digit adder using the S-CAM method. We showed that using an electronics scheme without suffering a speed loss, N PLA's each of 1K AND-OR switches must be employed. When the same calculation was performed using an optical S-CAM, a single 1K AND-OR switch array together with an appropriate space multiplexing scheme is sufficient. We then studied optical architectures to implement such a S-CAM and suggested and analyzed an optical matrix-product-based processor. The conclusion of the analysis is that the power consumption and the diffraction related cross-talk are the two dominant factors limiting the capacity of the optical S-CAM. It is possible to implement an optical S-CAM with a capacity to process 64 simultaneous memory access operations each of 32-bit in length with a 10^{-15} cross-talk error rate and in a 50 MHz read-out rate. A smaller scaled S-CAM was experimentally constructed to perform addition and subtraction of 8-bit MSD numbers in parallel. The detailed information was summarized in a paper submitted to the Applied Optics.

Publications: (only those which have not been reported to AFOSR)

- * "Free-space optical collinear crossover interconnects" Y. Li and B. Ha, Applied Optics, 30 (1991) pp.3288-3293.

- * "Ring-array processor distribution topology for optical interconnects," Y. Li, B. Ha, T. Wang, S. Wang, A. Katz, X. J. Lu, and E. Kanterakis, Applied Optics, 31 (1992) pp. 5548-5558.
- * "Reflective optical ring array interconnects: an optical system design study," B. Ha and Y. Li, Applied Optics, 32 (1993) in print.
- * "Parallel MSD arithmetic using an opto-electronic shared content-addressable memory processor," Y. Li and B. Ha, submitted to Applied Optics for publication.