


AD-A266 345



AD

2


TECHNICAL r e p o r t

USA-BRDEC-TR // 2539

Simulating Bridge Crossings

by
Russell Hepler

Report Date
May 1993



Distribution unlimited; approved for public release.

93-14721



United States Army
Belvoir Research, Development and Engineering Center
Fort Belvoir, Virginia 22060-5606

Destroy this report when it is no longer needed.
Do not return it to the originator.

The citation in this report of trade names of commercially available products does not constitute official endorsement or approval of the use of such products. Product names are being used for identification purposes only.

The opinions expressed in this report are the authors own, and do not consistute official positions.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Service, Direction of Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget Paperwork Project (0704-0188) Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE May 1993	3. REPORT TYPE AND DATES COVERED Final May 1992 - December 1992		
4. TITLE AND SUBTITLE Simulating Bridge Crossings (U)			5. FUNDING NUMBERS	
6. AUTHOR(S) Russell Hepler				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Belvoir Research, Development & Engineering Center ATT: SATBE-JBA Fort Belvoir, VA 22060-5606			8. PERFORMING ORGANIZATION REPORT NUMBER 2539	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES POC: Russell Hepler, (703) 704-2147				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Distribution unlimited; approved for public release			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Study to determine the feasibility and advisability of alternate methods of durability testing of military bridges. Objective was to reduce bridge test costs by substituting simulated crossings for a portion of the field crossings test used to assess the bridge durability requirement of 5000 crossings. A viable test procedure was developed which uses hydraulic actuators that apply cyclic loads to bridge prototypes to simulate tank crossings. The simulation test method outlined in this paper provides the following: 1. Significant savings in cost and time over field crossings. 2. A method for using the hydraulic actuators to create stresses in the bridge prototypes equal to the stresses created by tank crossings. 3. A method of incorporating strain data found during field crossings to ensure that the loads applied during the simulation are representative of the loads that occur during field crossings. 4. A consistent test procedure that is not altered based on the bridge design being tested. This approach eliminates the errors that might be caused by subjective evaluations from engineers' analysis of bridge designs.				
14. SUBJECT TERMS Bridge, Fatigue, Aluminum, Testing, Cost Savings, Simulation, Durability, U.S. Army			15. NUMBER OF PAGES 42	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unlimited	

Report Number 2539

Simulating Bridge Crossings

by
Russell Hepler



US Army Belvoir RD&E Center
Fort Belvoir, Virginia 22060-5606

May 1993

Distribution unlimited; approved for public release.

Table of Contents

	Page
Executive Summary.....	vi
Introduction.....	1
Research Paper Goals.....	2
HAB Program Adds Realism	3
Durability Requirement	8
Durability Failure Definition.....	8
Durability Testing	9
Purpose of Durability Testing.....	9
Current Test Method for HAB.....	9
Why Research Alternate Testing?	9
How to Simulate Crossings	10
Background on Fatigue	10
Analyze the "Effects" a Bridge Experiences in Field Operations	12
Theory of Crossing Simulation.....	14
Proposed Test Set-Up.....	17
Realism in Loading.....	19
How 9000 Loadings Compare to 3,000 Tank Crossings.....	20
Other Thoughts.....	25
Recommendations for Further Research	25
Conclusions.....	26
References.....	27
Figures	
1 Load Frame Schematic.....	2
2a HAB Candidates.....	4
2b Scissor HAB Launch Procedures.....	5
2c No. 10 HAB Launch Procedures.....	6
2d Leguan HAB Launch Procedures.....	7
3 Results of Many Fatigue Tests for Aluminum	11
4 Stress Amplitude Effect on Fatigue	11
5 "Effects" Experienced by Bridge in Operational Use.....	12
6 Effects to Simulate	13
7 Bending Moments from Crossing Vehicles.....	15
8 Bending Moments from Loading Apparatus.....	16
9 Load Placements	17
10 Loading Pattern	18
11 Moment Curves for Crossing Simulation	20
12 S-N Slopes for Aluminum.....	21
13 Reduction in Stress Causes Increased Fatigue Life	23
14 Calculated Equivalent Crossings	24

Executive Summary

Belvoir RDE Center (Belvoir) and Combat Systems Test Activity (CSTA) conducted a joint study to determine the feasibility and advisability of alternate methods of durability testing of military bridges. The objective was to reduce bridge test costs by substituting simulated crossings for a portion of the field crossings test used to assess the bridge durability requirement of 5000 crossings.

A viable test procedure was developed which uses the loading equipment in the Belvoir bridge hangar to simulate tank crossings. The simulation test method outlined in this paper provides the following:

1. Significant savings in cost and time over field crossings.
2. A method for using the bridge hangar equipment to create stresses in the bridge prototypes equal to the stresses created by tank crossings.
3. A method of incorporating strain data found during field crossings to ensure that the loads applied during the simulation are representative of the loads that occur during field crossings.
4. A consistent test procedure that is not altered based on the bridge design being tested. This approach eliminates the errors that might be caused by subjective evaluations from engineers' analysis of bridge designs.

For the Heavy Assault Bridge (HAB) durability assessment, it is recommended that 2000 field crossings be performed on each of the HAB candidate designs followed by 3000 equivalent crossings under the load apparatus at Belvoir.

Recommendations for further research are provided.

STUDY GROUP MEMBERS

Belvoir RDE Center

Russell Hepler
Jonathan Taylor
Suzanne Culkin
Brian Hornbeck
Mark Evans

Combat Systems Test Activity

James Faller
James Horchner
Wayne Ziegler

Special Consultants

Dr. Wallace Sanders
Mr. Donald Webber

Introduction

A study group was formed to research alternate methods of testing military bridges. The premise of the research was that the test for bridge durability might be accomplished in a way other than the expensive and time consuming method of driving actual 70 ton tanks across a bridge as many as 5000 times.

The study group was aware of industry programs to improve highway bridge designs through lab testing of the new designs. We sought to research methods currently used for other bridge systems to see if they had applicability to military assault bridges. Our research methods were: search the literature, talk to experts in the fatigue field, and combine the testing experience of the government testers at Combat Systems Test Activity (CSTA) with the bridge design experience of the engineers at Belvoir RDE Center.

Our first fatigue consultant was Mr. Donald Webber, the British Army's expert in bridging whose work in fatigue aspects of bridge design is extensively published (see Appendix A). Mr. Webber provided the study group with valuable insight into the British military bridge testing programs. Our second consultant was Dr. Wallace Sanders, Professor of Civil Engineering at Iowa State University. A list of his publications, found in Appendix A, demonstrates his extensive experience with fatigue in bridges. Dr. Sanders is especially knowledgeable in fatigue related to aluminum structures. Military bridges are almost exclusively fabricated from aluminum because of the weight saving necessities. Aluminum reacts significantly different than steel in many aspects, thus a special knowledge of aluminum is essential. Each consultant provided written feedback to the study group which is available upon request.

The combined experience of consultant engineers, the test engineers of the Combat Systems Test Activity (CSTA), and the bridge engineers of Belvoir helped to ensure that we were including all important aspects of bridge field operation while at the same time confirming that the simulated test would be sufficiently rigorous on the bridges.

DTIC QUALITY INSPECTED 3.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

Research Paper Goals

The two goals of the research paper are as follows:

1. Research theories to see if bridge durability testing is feasible through simulated loading techniques.
2. Propose a practical test for simulating loadings using the load frame equipment available at the Belvoir RDE Center Bridge Hangar.

To further expound on the goals, we sought a method to realistically duplicate the loads experienced by a bridge in field tests through applying loads on a Load Frame, in effect, simulating tank crossing loads. If simulation proved to be viable in theory, the second goal of the study was to propose a test program using the equipment available in the Belvoir Bridge Hangar. Figure 1 describes the load frame apparatus.




Figure 1. Load Frame Schematic

HAB Program Adds Realism

Contributing to an ongoing Army test program provided the study group with a reality check. We were fortunate to be involved with an actual Army program with actual equipment to force us into clear, practical thinking which greatly facilitated our planning efforts. The Army program was the evaluation test of the Heavy Assault Bridge (HAB). We had the task of not only developing a theoretical basis for a load frame test, but we had to flesh out the details sufficiently to describe an actual test using available equipment and data.

The HAB is a competitive program between three different assault bridge designs (see Figure 2a-d). The HAB systems shown in Figure 2a, are currently undergoing field tests at Aberdeen Proving Grounds (APG), Maryland. Strain data is available from actual tank crossings performed at APG. As shown in Figures 2a through 2d, the three designs have different characteristics. In our effort to develop a proposed simulation test, we considered the fairness of the test to each design and we sought to develop a test that would be equally rigorous on each design. If we designed a test that only loaded the bridges at midspan, for instance, it would likely be tougher on the bridge designs with connection points at midspan and less rigorous on the design with no connection point at midspan.

Because fairness was an essential element in the simulation, we sought a test approach that involved no subjective evaluation from engineers. We wanted to avoid a test approach that was altered according to the bridge designs involved. In other words, we attempted to develop a "black box" approach to the simulation using feedback from the field testing as much as possible to enhance test realism.

IMI: SCISSORS BRIDGE



TDP: # 10 BRIDGE



MAN: LEGUAN BRIDGE



Figure 7a. HAB Candidates




Figure 2b. Scissor HAB Launch Procedures




Figure 2c. No. 10 HAB Launch Procedures




Figure 2d. Leguan HAB Launch Procedures

Durability Requirement

The nature of the test we are undertaking is an evaluation test, that is, it is a "met/not met" test of the HAB bridges against the durability requirement as stated in the HAB Required Operational Capabilities (ROC) document (ref 1). The HAB durability requirement as delineated in the ROC is:

"The bridge durability requirement is 5000 MLC 70 vehicle crossings []"¹

While the simple definition in the Required Operational Capabilities (ROC) document doesn't specify whether the total number of crossings must be accomplished under a variety of spans and/or under a variety of bank conditions, you will see that the study group has considered variations of span and bank conditions in making an appropriate test. The group referred to resources such as the Operational Mode Summary/Mission Profile (OMS/MP) and the field experience of the Armored Vehicle Launched Bridge (AVLB) to consider all effects that can reasonably be encountered by an assault bridge in its 20 year life.

Durability Failure Definition

It is important that we use a common definition of a durability failure. The definition used by the Test and Evaluation Command (TECOM) evaluator is as follows:

"A malfunction that precludes further operation of the bridge and is great enough in cost, safety, or time to restore that the bridge must be replaced or rebuilt. Durability failures are failures that are uneconomical to repair, failures whose repairs require system replacement or rebuild at the General Support (GS) or Depot level of maintenance, or the onset of suddenly increasing failure rate indicative of overall system wearout."

The definition shows that a durability test is not concerned with routine failures that are repaired at the Direct Support (DS) or lower levels of maintenance. Hose breaks, deck wear, and failures in parts that are replaceable at the lower maintenance shops are not durability failures. These non-durability failures are thoroughly addressed in other aspects of bridge testing. Durability failures are only those failures that are serious structural problems that cause a large cost or safety concern.

¹ Military Load Class (MLC) 70 is for most practical purposes a 70 ton vehicle load. For the HAB, the vehicle of primary concern is the 70 ton Abrams tank.

Durability Testing

Let us step back for a little more background on why research into an alternate test method was done. We know what the durability requirement is, and we have agreed on what a durability failure is, now let us discuss why we might want to consider doing the durability testing in a different manner.

PURPOSE OF DURABILITY TESTING

The purpose of durability testing is to gather data to support an assessment of whether a bridge meets the durability requirement.

CURRENT TEST METHOD FOR HAB

The method currently planned to assess durability of the HAB bridges is to emplace a single bridge over a full span gap and run the crossing vehicle over it 5000 times. These crossings are done per the mission scenario described in the ROC (ref 1) which consists of driving the launch vehicle, with the bridge in the transport mode, for a few miles, approaching the launch site, launching the bridge, allowing 70 crossings by crossing vehicles, retrieving the bridge, and beginning the cycle again. A mixture of bank slopes is used throughout the total number of 5000 cycles. Only one bridge is used because of the limited number available. If no durability failures occur, per the definition stated earlier, then the assessment can be made that the requirement has been met.

It should be recognized that the first 2000 crossings are performed for assessments other than durability. This means that 2000 actual crossings will be done regardless of a durability assessment and are not candidates for replacement by an alternate test method.

WHY RESEARCH ALTERNATE TESTING?

Cost savings is the principle motivation for trying to discover alternate methods. The expense of running a 3000 vehicle crossing test at APG using 70 ton Abrams tanks is estimated as follows:

3000 Tank Crossings at APG (up to 3 bridges, 12 weeks)

Operating and Maintenance Expenses	\$ 275 k
Test Personnel/Operators	\$ 50 k
	\$ 325 k

Hanger Test at Belvoir (3 bridges, 9 weeks)

Equipment Costs (operating and capitalization)	\$ 60 k
Test Engineers and Support Personnel	\$ 50 k
	\$ 110 k

Potential Savings	\$ 225 k
-------------------	----------

Recent Department of the Army (DA) policy has directed that simulation test methods should be used whenever possible. It is widely recognized that with the trend in testing budget reductions, durability testing by simulation may be the only option available in the not-too-distant future. Field tests may be unfunded, therefore limiting the choice to simulation or no test. This is not the case with the current HAB program however.

For the HAB program, 3000 field crossings are planned for a later phase of testing. Following the 3000 crossings the durability assessment can be made. Due to the affordability restrictions of testing three different bridge designs, the tank crossings cannot be done during this phase of testing and thus the durability assessment will not be contributing information to the selection between the three candidate designs. If simulation is an acceptable test, the durability test could be performed on all three designs in an affordable manner by a combination of 2000 actual crossings and 3000 simulated crossings. With 5000 equivalent crossings being done during the current phase of testing, the durability assessment could contribute data to the downselect decision.

How to Simulate Crossings

Now that we have made the case for why an alternate test method is needed, we can discuss how simulating crossings can be accomplished. At the point in government testing when a bridge is ready to undergo durability testing, it has proven that it can withstand crossing loads and has experienced at least 2000 crossings. The purpose of the simulation test is to uncover design flaws that show up above 2000 crossings but less than the 5000 crossings requirement. A structural failure that would occur after many cycles, that didn't occur after one cycle, is known as a fatigue failure because it is caused by fatigue of components.

BACKGROUND ON FATIGUE

A component may fail after repeated stress loadings even if the stress never exceeds the yield strength of the material. Continued cyclic loading causes fatigue fractures that are progressive, beginning as minute cracks that grow to become large cracks, that can lead to fracture of the part or structure.

The behavior of a material (e.g. 7005 Aluminum) under repeated loadings can be evaluated in a fatigue laboratory test. A sample is loaded repeatedly from zero stress to a known stress, and the number of applications of that stress is counted until the sample fails. This procedure is repeated for different stress levels. The results of many of these tests can be graphed in what is called an S-N curve, as shown in Figure 3.

For any given stress level, say σ_p in Figure 3, the corresponding number of applications of the stress which will cause failure is known as the fatigue life. The fatigue life is just the number of cycles of stress required to cause failure.





Figure 3. Results of Many Fatigue Tests for Aluminum

The ordinate on the S-N curve is "Change in Stress ($\Delta\sigma$)" signifying that the amplitude of the stress cycle is very important, see Figure 4.



Condition (A) causes more fatigue than Condition (B) or (C)

Figure 4. Stress Amplitude Effect on Fatigue

High stress fluctuations (high $\Delta\sigma$) cause the most fatigue. Low stress fluctuations (low $\Delta\sigma$) cause the least fatigue. The key to simulating crossings is repeating the high stresses in the bridge that are caused by tank crossings.

ANALYZE THE "EFFECTS" A BRIDGE EXPERIENCES IN FIELD OPERATIONS

The study group developed a list of all of the "effects" a bridge experiences in its normal operation, see Figure 5.

Various Bank Seat Conditions

- Side slope
- Racked slope
- Longitudinal slope
- Prepared/Unprepared abutments
- Variations of gap length from 0-24 meters

Load Spectrum

- Various crossing vehicles of various weights (max 70 tons)
- Accumulation of mud
- Eccentric loading when vehicle moves left or right on treadway
- Impact factor from fast moving vehicle slamming down on the bridge
- Vibrations caused by vehicle
- Vehicle braking, accelerating, or steering
- Shear stress reversals as a moving load crosses over a specific location
- Crossing from either end of the bridge
- Dead load of bridge

Sequence of Loading

- Sometimes heaviest loads precede light loads
- Sometimes light loads precede heavy loads

Launching/Retrieving

Environmental Effects

- Wind, rain, snow, temperature change, gravel, etc.

Figure 5. "Effects" Experienced by Bridge in Operational Use

Not everything that a bridge experiences contributes to fatigue, because not everything causes stress fluctuations.

Upon reviewing the list of effects, the study group separated the list into those effects which are unimportant to recreate beyond 2000 crossings (because they don't cause high stress fluctuations), and those which are important to simulate beyond 2000 crossings (because they may cause high stress fluctuations) see Figure 6.

Actual	No need to simulate	Simulate
Slopes (level, rack long, side)	Slopes (long.)	Slopes (level, rack, side)
Sequence of Slopes		Sequence of slopes
Span ($\leq 24\text{m}$)	Span ($<24\text{m}$)	Span (fixed at 24m)
Vehicle (MLC 10, 30, 60, 70 T)	Vehicle ($<70\text{ T}$ and wheeled)	Vehicle (70 T)
Speed ($\leq 10\text{ mph}$)	Cycle time	Impact factor
Launch and retrieve cycle	—	L/R cycle
Braking/Steering	Braking/Steering	—
Environment (mud, ice snow, gravel, wind, temperature.)	Environment	—
Dead load	—	Dead load

Figure 6. Effects to Simulate

THEORY OF CROSSING SIMULATION

After determining what to simulate, we worked to create a practical method of simulation. Remember that the key to simulation is recreating the stresses that the bridge experiences in operation. From strain gage data taken during actual tank crossings, we have a measure of how a tank crossing stresses the particular bridges we are interested in. When we apply loading to the bridge under the load frame, we will recreate the strains, therefore the stresses, experienced by the bridges in the field.

The stresses in the bridge caused by the tank crossing are directly proportional to the bending moments applied to the bridge by the tank. Recall the formula for bending stresses:

$$\sigma_b = \frac{MC}{I}$$

where: M = bending moment
 C = distance from neutral axis
 I = moment of inertia

C and I are built into the equipment at the time of manufacture and cannot be altered. So at any position along the length of the bridge, σ_b varies directly with M . By replicating the moments on the bridge caused by a tank crossing, we replicate the stresses in the bridge caused by a tank crossing.

Figure 7 illustrates the "crossing moments" applied by the tank. The high moments move along with the vehicle (see parts A, B, and C on Figure 7) with the highest moments occurring when the tank is at midspan. An envelope of maximum moments can be drawn (see part D of Figure 7). It is this envelope of moments we are trying to match in the simulation.

Figure 8 shows how loading the bridge using the load frame apparatus, at three carefully chosen positions, can recreate the crossing moments envelope with quite good fidelity. Creating the crossing moments in the bridge creates the stresses throughout the bridge exactly identical to the stresses caused by a tank crossing.




Figure 7. Bending Moments from Crossing Vehicles




Figure 8. Bending Moments from Loading Apparatus

Proposed Test Set-Up

The suggested load placement locations are shown in Figure 9. Figure 9 is drawn to scale thus illustrating the extent of coverage that can be achieved by loading at the 1/4 span, 1/2 span, and 2/3 span positions. Recall that the bridge has symmetrical fabrication to the left and right of midspan. Symmetry of bridge construction means that the bridge components that are missed at the portion of the bridge between the 1/4 span loading position and 1/2 span loading position are loaded when testing identical components that are at the 2/3 loading position.

The proposed test uses the bridge that experienced the 2000 field crossings at APG and applies an additional 9000 loadings (3000 loadings at each of three positions described in Figure 9). The 9000 loadings equate to between 3000 and 5000 equivalent crossings as will be explained later in this research paper.




Figure 9. Load Placements

A mixture of bank conditions and eccentricity is suggested for the proposed test to account for certain "effects" listed in Figures 5 and 6. The suggested mixture is shown in Figure 10. Bank conditions and eccentricity are created in the lab vice simulated. Bank conditions are created by the supports used to place the bridge under the load frame. The bank supports can be varied throughout the test as necessary. Eccentricity is created by offsetting the load to one side of the bridge.

Actual Field Crossings: 2000		
Simulated Crossings: Total of 9000 loadings, 3000 loadings in 3 positions as follows,		
1/4 Span position	1/2 Span position	2/3 Span position
3000 Total loadings	3000 Total loadings	3000 Total loadings
2000 Level	2000 Level	2000 Level
1000 Centric	1000 Centric	1000 Centric
500 Left Eccentric	500 Left Eccentric	500 Left Eccentric
500 Right Eccentric	500 Right Eccentric	500 Right Eccentric
500 Side Slope	500 Side Slope	500 Side Slope
250 Right Side Slope	250 Right Side Slope	250 Right Side Slope
250 Left Side Slope	250 Left Side Slope	250 Left Side Slope
500 Racked	500 Racked	500 Racked

Figure 10. Loading Pattern

Realism in Loading

Since we have strain data from the field tests, we are able to repeat the strains experienced at particular loading points just as the tank crossing at 10 mph created stresses at those loading points. This is the key to the authenticity of the test. By recreating strains, we remove the subjectivity from the decision of how much load to apply. The load will likely be different for each bridge design at each load placement position because different bridge designs act differently under vehicle crossings. By recreating strains, we do not unnecessarily "punish" one bridge design by applying the "worst case" load.

The Launch/Retrieve (L/R) cycle can be recreated in the lab if necessary. On an appropriate periodic basis, the launcher can be connected to the bridge so that a retrieval and launch can be performed, just as it was done in the field. The literature (ref 7) shows that L/R stresses may be an insignificant contributor to bridge fatigue because of the relatively low ratio of L/R per crossings (i.e. one L/R per 70 crossings). A simple calculation can be done to determine if the L/R cycle is necessary for the simulation test. If the stress from a retrieval is not at least one half of the stress from crossing (i.e. $|\sigma_{L/R}| > |1/2 \sigma_{crossings}|$) then the L/R cycle is unimportant to the simulation. The strain data available from the field tests is sufficient to determine the stresses from L/R and crossings.

How 9000 Loadings Compares to 3000 Tank Crossings

An ideal simulation test would create exactly 3000 equivalent crossings to combine with the 2000 field crossings, summing to make a test of exactly 5000 equivalent crossings to evaluate the bridge against the 5000 crossing requirement. Our research has discovered that it is not possible to attain exactly 3000 equivalent crossings through the use of the load frame apparatus. What can be achieved is a minimum of 3000 crossings and some extra crossings that we believe are not enough to be unreasonably strict on the bridge.

Creating the minimum 3000 equivalent crossings is done by cyclic loading from 0 to 70 tons² 3000 times at each of the three loading positions shown in Figure 9. This loading will closely recreate the moment envelope throughout the length of the bridge as discussed earlier in Figures 7 and 8. Figure 11 shows a more precise moment-to-span drawing.




Figure 11. Moment Curves for Crossing Simulation

² Load applied will be more than 70 tons to recreate strains found in field tests.

Extra crossings occur because of the overlapping of the three load position moments curves. Let us examine the effect at the 1/4 span position for further clarification. At 1/4 span, 3000 full stress cycles will be applied by the load apparatus when it is at 1/4 span. Additional stress cycles (of lower magnitude) are caused at 1/4 span when the load apparatus is placed at the 1/2 span position. Further stress cycles (of even lower magnitude) are caused at 1/4 span when the load apparatus is placed at the 2/3 span position. Lower stress means much lower fatigue effect as explained by fatigue theory.

Empirical data shows that for aluminum, the S-N curve slope varies from 1/3 to 1/4.5 depending on the stress concentrations in the test samples (ref 5), see Figure 12. To be the most conservative, we will assume a slope of -1/3 applies to military bridges.




Figure 12. S-N Slopes for Aluminum

Because the ordinate and abscissa on the S-N curve are both logarithmic scale the following relations hold true.

$$\log S = m \log N + \log C$$

where S = stress range
m = slope constant
N = fatigue life defined as the number of cycles to failure corresponding to a particular stress range.
C = intercept constant

$$\log S = \log N^m + \log C$$

$$S = N^m \times C$$

$$\frac{S}{C} = N^m$$

$$\left(\frac{S}{C}\right)^{1/m} = N$$

For aluminum alloys the slope constant lies between -1/3 and -1/4 depending on the fatigue classification of the structural detail, the more sensitive to fatigue the detail the lower the number (see Figure 12). If it is desired to quantify the effect of a change in stress range on fatigue life, the preceding equation can be rewritten in ratio form as

$$\begin{aligned} \frac{N_2}{N_1} &= \frac{\left(\frac{S_2}{C}\right)^{1/m}}{\left(\frac{S_1}{C}\right)^{1/m}} \\ &= \left(\frac{S_2}{S_1}\right)^{1/m} \end{aligned}$$

Taking, as an example, a stress range ratio of 1/2 ($S_2 = 1/2 S_1$) and a slope constant of $m = -1/3$, then substituting into the above equation yields

$$\begin{aligned} \frac{N_2}{N_1} &= \left(\frac{S_1}{2S_1}\right)^{-3} \\ &= 8 \end{aligned}$$

This formula tells us that a reduction in stress results in a cubed increase in fatigue life or a cubed reduction in fatigue effect. For example, reducing the stress by 1/2 results in a fatigue life increase of $(1/2)^{-3} = 8$. This means that 8 times the life can be expected at the lower stress, or said another way, the reduced stress had only 1/8 the fatigue effect of the higher stress. An illustrative example is shown in Figure 13.




Figure 13. Reduction in Stress Causes Increased Fatigue Life

By this method, a reduction in stress can be converted into an equivalent number of crossings. If a stress cycle of 0-20 ksi represents one crossing in Figure 13, then a stress cycle of 0-10 ksi would represent 1/8 of a crossing. Recall from earlier discussions, that crossing stresses in a bridge are directly proportional to the moment applied. Equivalent crossings are derived from the moment values represented on Figure 11.

Figure 14 shows the calculated values of the equivalent number of crossings that a bridge will experience after undergoing 2000 field crossings then loading at the three proposed locations.

Equivalent crossings effect at	LOADING POINT		
	1/4 Span	1/2 Span	2/3 Span
1/4 Span	3000	512	232
1/2 Span	1211	3000	1829
2/3 Span	<u>346</u>	<u>1132</u>	<u>3000</u>
Simulated Crossings	4557	4644	5081
Field Crossings	<u>+2000</u>	<u>+2000</u>	<u>+2000</u>
Total Equiv Crossings	6557	6644	7081

Figure 14. Calculated Equivalent Crossings

The total equivalent crossings will range from 5000 at a minimum to approximately 7000 at a maximum. For a criteria of 5000 required crossings, 7000 calculated equivalent crossings is not an unreasonably strict test.

Other Thoughts

IMPORTANCE OF THE SEQUENCE OF LOADING

The loadings described in Figure 13 should be applied in a mixed order, e.g. 500 loadings at 1/4 span, then 500 loadings at 1/2 span, then 500 loadings at 2/3 span. Performing all loadings at 1/4 span, then doing all loadings at 1/2 span, followed by all loadings at 2/3 span, will give a different effect to the bridge than mixing the positions.

SEPARATING THE TREADWAYS

During our research we considered separating the treadways for the simulation test in order to have more samples, thus a higher statistical significance. Several weaknesses were discovered. The bridges involved in the test must have identical treadway sections in order for the method even to be feasible. The Leguan bridge design uses a different fabrication for the inner bottom chord, and outer bottom chord because the outer chord is designed to withstand higher stresses. Separating the treadways would likely cause the inner chord to undergo higher stress, thus causing more fatigue than would occur in the field. A second problem with separating the treadways is the assumption that the stress transfer between the treadways is negligible. Field data causes us to suspect that in some bridge designs the stress transfer is not small and should not be neglected.

Recommendations for Further Research

COMPONENT TESTING

Bridge durability may be enhanced through component testing and subsystem testing prior to fabrication.

PERIODIC OVERLOADING

The literature suggests that periodic overloading can be beneficial to fatigue strength because in certain circumstances the overload has shown a crack arresting effect.

Conclusions

1. Bridge stresses caused by tank crossings can be reproduced using a loading apparatus.
2. Repeated cycling of the loading apparatus in various predetermined positions on the bridge will fatigue structural members of the bridge just as they would be fatigued under vehicle crossings.
3. For a bridge durability assessment, a viable test alternative to a bridge undergoing 5000 field crossings is for the bridge to undergo 2000 field crossings plus 3000 equivalent crossings under the loading apparatus.

References

1. RAM Rational Report, Appendix 3 to the Required Operational Capabilities (ROC) for the Heavy Assault Bridge (HAB), U.S. Army Training and Doctrine Command, Fort Monroe, VA, 3 April 1990.
2. Heavy Assault Bridge System (HABS) Operational Mode Summary/ Mission Profile (OMS/MP), Appendix 4 to the Required Operational Capabilities (ROC) for the Heavy Assault Bridge (HAB), U.S. Army Training and Doctrine Command, Fort Monroe, VA, 3 April 1990.
2. Evans, M. "A Collection of Thoughts on Fatigue Testing of Bridges", Belvoir RD & E Center, 1992.
3. Trilateral Design and Test Code for Military Bridging and Gap Crossing Equipment", I.C.S.T., January 1980.
4. Webber, D. "Heavy Assault Bridge (HAB) Durability Testing Programme", Unpublished Report to Belvoir RD & E Center October 1992.
5. "Structural Use of Aluminium: Part 1 - Code of practice for design/Part 2 - Specifications for materials, workmanship and protection", BS 8118-1991, British Standards Institute, London, England, 1991.
6. "European Recommendations for Aluminium Alloy Structures Fatigue Design" (First Edition), Document No. 68, European Convention for Construction Steelworks, Brussels, Belgium, 1992.
7. Lanciotti, A. and Lazzeri, L. "Effects of Spectrum variations on fatigue crack growth", International Journal of Fatigue 14 No 5, 1992 pp. 319-324.
8. Shigley, J.E., Mechanical Engineering Design

Appendix A

List of Articles Published by Study Group Consultant Engineers

D WEBBER - SOLE AND JOINT PUBLICATIONS IN THE OPEN LITERATURE

D. Webber, Working stresses related to fatigue in military bridges, Stresses in Service, Institution of Civil Engineers. London, 1967.

D. Webber, Constant amplitude and cumulative damage fatigue tests on Bailey bridges. Effects of environment and complex load history on fatigue life. ASTM STP 462 American Society for Testing Materials, Philadelphia, 1970.

D. Webber, Fatigue results on welded 90 ton f/in² maraging steel. Welding and Metal Fabrication, Vol 36, No 6, pp 223-231, June 1968.

F. E. Brine, D. Webber, and H. G. Baron, A note on the effect of maraging on the fatigue properties of 18% Ni maraging steel plate and weld specimens. Welding and Metal Fabrication Vol 36, No. 9, pp 349-351, 1968.

F. E. Brine, D. Webber, and H. G. Baron, Effect of shot peening on the fatigue properties of maraging steel and Al Zn Mg alloy. British Welding Journal, Vol 15., No. 11, pp 541-546, November 1968.

D. Webber, Fatigue of Welded Maraging Steel, paper 10.

J. G. Whitman and D. Webber, The problem of cumulative damage in welded structures, Paper 17. Proceedings of the Conference on Fatigue of Welded Structures. The Welding Institute, Cambridge, 1971.

J. Livesey, B. Smith, and D. Webber, Recording and interpretation of strain measurements in military bridges. Conference on the recording and interpretation of engineering measurements. The Institute of Marine Engineers, London, 1972.

D. Webber and S. J. Maddox, Problems in the detection and monitoring of fatigue cracks in Al-Zn-Mg alloy fillet welds. Detection and Measurement of Cracks. The Welding Institute. Cambridge 1976.

D. Webber, Damage Tolerance of Military Bridges. Fracture Mechanics in Engineering Practice. Ed P. Stanley. Applied Science Publishers London 1977.

- N. J. Adams and D. Webber, The characterization crack growth and fracture in a military bridge. Case Studies in Fracture Mechanics. Ed T. P. Rich and D. J. Cartwright AMMRC Massachusetts 1977.
- D. Webber, S. J. Maddox, Evaluation of life improvement methods for Al-Zn-Mg alloy fillet welded details and Crack propagation in AL-Zn-Mg alloy fillet welded joints.
- D. Webber, Fatigue Testing of Weldments. Ed. D. W. Hooppner ASTM STP 648 Philadelphia 1978.
- D. Webber, The evaluation of possible life improvement method for Aluminum Alloy fillet welded joints. Welding Institute Seminar Coventry 1981.
- D. Webber, The effect of transverse fillet welds on the fatigue life of DGFVE 232A (7019) Al-Zn-Mg alloy, International Institute of Welding. Boston Paper XIII-129 1984.
- D. Webber and S. J. Maddox, Aluminum alloy cylindrical jack body failure investigation Journal of Strain Analysis, Vol. 19, No. 2, pp. 121-125, April 1984.
- D. Webber and D. L. McDiamid, A comparison of various welded aluminum alloy joint specimens in tensile fatigue at short lives. International Institute of Welding, Boston Paper XIII-128-1984.
- D. Webber, The fatigue design and testing of an Al-Zn-Mg alloy bridge guide 3rd International Conference on Aluminum Weldments, Munich, April 1985.
- S. J. Maddox and D. Webber, The effect of tensile residual stresses on the fatigue strength of transverse fillet welded Al-Zn-Mg alloy. Paper 69. Fatigue of Welded Construction. The Welding Institute, 1987.
- D. Webber, Connections for rapidly assembled military bridges components and their performance. Mobile and Rapidly Assembled Structures. Computational Mechanics Publications, Southampton, 1991.
- T. R. Gurney and D. Webber, Tests to Investigate the Performance of Fatigue Gauges in Conjunction with Fillet Welded Joints in Al-Zn-Mg alloys. Structural Integrity Assessment Elsevier Applied Science 1992.
- D. Webber, The effect of some programme variables on fillet weld cumulative fatigue damage results 5th International Conference on Aluminum Welding, Munchen 1992.

TECHNICAL PUBLICATIONS (SINCE 1983)

Dunker, K. F., Klaiber, F. W., Daoud, F. and Sanders, W. W. "Strengthening of Continuous Composite Bridges," Journal of Structural Division, ASCE, Vol. 116, No. 9, pp. 2464-2480, 1990.

Klaiber, F. W., Dunker, K. F. and Sanders, W. W. "Strengthening of Existing Bridges (Simple and Continuous) by Post-Tensioning," ACI External Prestressing in Bridges, Special Publication SP-120, American Concrete Institute, pp. 207-228, 1990.

Klaiber, F. W. Dunker, R. F., Wipf, T. J. and Sanders, W. W., "Summary of NCHRP Project 12-28(4); Methods of Strengthening of Existing Highway Bridges," Transportation Research Record 1180, pp. 1-6, 1988.

Klaiber, F. W., Dunker, K. F., Wipf, T. J. and Sanders, W. W., "Methods of Strengthening Existing Highway Bridges," National Cooperative Highway Research Program Report 293, Transportation Research Board, Washington, 1987.

Dunker, K. F., Klaiber, F. W. and Sanders, W. W., "Bridge Strengthening Needs in the United States," Transportation Research Record 1118, pp. 1-8, 1987.

Dunker, K. F., Klaiber, F. W. and Sanders, W. W., "Strengthening of Steel Stringer Bridges by Selective Stiffening," Transportation Research Record 1118, pp. 43-48, 1987.

Wipf, T. J., Klaiber, F. W., and Sanders W. W., "Load Distribution Criteria for Glued-Laminated Longitudinal Timber Deck Bridges," Transportation Research Record No. 1053 (Timber Bridges), pp. 31-40, 1986.

Dunker, K. F., Klaiber, F. W., and Sanders, W. W., "Post-Tensioning Distribution in Composite Bridges," Journal of Structural Engineering, ASCE, Vol. 108, No. 11, pp. 2540-2553, 1986.

Wipf, T. J. Klaiber, F. W., Junke, R. W. and Sanders, W. W., "Experimental and Analytical Load Distribution Behavior of Glued Laminated Deck Bridges," Proceedings of the Second International Conference on Short and Medium Span Bridges, Ottawa, Canada, August 1986.

Klaiber, F. W., Beck, B. L., Dunker, K. F. and Sanders, W. W., "Experience in Bridge Strengthening by Post-Tensioning," Proceedings of the Second Annual International Bridge Conference, Pittsburgh, pp. 10-14, June 1985.

Sanders, W. W., "Distribution of Wheel Loads on Highway Bridges," National Cooperative Highway Research Program Synthesis of Highway Practice Report 111, Transportation Research Board, 1984.

Sanders, W. W. and Day, R. H., "Fatigue Behavior of Aluminum Alloy Weldments," Bulletin 286, Welding Research Council, New York, 1983. (Original report translated into and published in Japanese).

BOOKS OR CHAPTERS OF BOOKS

Milek, W., Dickerson, P., Rager, D., and Sanders, W., "Design for Welding," Welding Handbook, Vol. 1, Chapter 5, pp. 126-192, American Welding Society, Miami, 1987.

NON-REFERRED PROCEEDING ARTICLES

Klaiber, F. W., Wipf, T. J., Dunker, K. F. and Sanders, W. W., "Bridge Strengthening Research at Iowa State University," Proceedings of the Annual Meeting - Canadian Society of Civil Engineering, St. Johns, Newfoundland, Vol. IA, pp. 454-475, June 1989.

Klaiber, F. W., Wipf, T. J., Dunker, K. F., Fanous, F. and Sanders, W. W., "Current Bridge Research at Iowa State University," Proceedings of the U.S. - Japan Symposium on Bridges, A.S.C.E. Structures Congress 1989, San Francisco, pp. 816-825, April 1989..

Dunker, K. F., Klaiber, F. W., and Sanders, W. W., "Post-Tension Strengthening of a Three-Span Continuous Bridge," Proceedings of the Symposium on Bridge Research in Progress, Des Moines, pp.: 103-106, September 1988.

Sanders, W. W., "Fatigue Design of Aluminum Structures," Proceedings of the Fourth International Conference on Aluminum Weldments, Tokyo, Japan, pp. 5.70-5.82 (Paper 508), April 1988.

Klaiber, F. W., Dunker, K. F., Wipf, T. J. and Sanders, W. W., "Bridge Strengthening, A Viable Alternative," Proceedings of International Conference on Structural Faults and Repair, (Volume 2), University of London (England), pp. 265-272, July 1987.

Klaiber, F. W., Dunker, K. F., Wipf, T. J. and Sanders, W. W., "Bridge Strengthening Research at Iowa State University," Proceedings of U.S. - European Workshop on Rehabilitation of Bridges, Paris, France, June 1987.

Klaiber, F. W., Dunker, K. F. and Sanders, W. W., "Strengthening of Single Span Steel Beam Composite Bridges by Post-Tensioning," Proceedings of the Second International Conference on Structural Faults and Repair, London, England, pp. 1-5, April 1985.

Kosteas, D. and Sanders, W. W., "Evaluation of Fatigue Strength for Common Welded Joints in Aluminum Alloys," Proceedings of the Third International Conference on Aluminum Weldments, Munich, West Germany, pp. IV.4.1-18, April 1985.

Klaiber, F. W. and Sanders, W. W., "Bridge Strengthening by Post-Tensioning," Proceedings of Twelfth Congress of International Association for Bridge and Structural Engineers, Vancouver, pp. 1116-1117, September 1984.

Lee, D. Y., Kennedy, W. J. Huisman, C. L., and Sanders, W. W., "Data Bank for Recycled Bituminous Payments," Proceedings of the International Transport Congress, Montreal, pp. C53-C68, September 1984.

Sanders, W. W. and Klaiber, F. W., "Performance of Steel Beam Highway Bridge," Proceedings of W. H. Munse Symposium on Behavior of Metal Structures, American Society of Civil Engineers, pp. 174-192, May 1983.

Distribution for Report #2539

DEPARTMENT OF DEFENSE

- | | | | |
|---|--|---|--|
| 1 | Director, Technical Information
Defense Advanced Research
Projects Agency
1400 Wilson Blvd
Arlington, VA 22209 | 1 | US Army Chemical Research,
Development and Engineering Center
ATTN: AMSMC-QAV
Edgewood, MD 21010-5423 |
| 1 | Director
Defense Nuclear Agency
ATTN: TITL
Washington, DC 20305 | 1 | US Army Armament Research and
Development Center
ATTN: SMCAR-QAH
Picatinny Arsenal, NJ 07806-5000 |
| 2 | Defense Technical Information Center
Cameron Station
Alexandria, VA 22314 | 1 | Commander
US Army Aviation Systems Command
ATTN: AMSAV-Q
4300 Goodfellow Blvd
St. Louis, MO 63120-1738 |
| 1 | Commander
US Army Materiel Command
ATTN: AMCCE-Q
5001 Eisenhower Ave
Alexandria, VA 22333-0001 | 1 | Commander
US Army Depot System Command
ATTN: AMSDS-Q
Chambersburg, PA 17201-4170 |
| 1 | Commander
US Army Armament, Munitions, and
Chemical Command
ATTN: AMSMC-QA
Rock Island, IL 61299-6000 | 1 | Commander
US Army Missile Command
ATTN: AMSMI-Q
Redstone Arsenal, AL 35898-5290 |
| 1 | Commander
US Troop Support Command
ATTN: AMSTR-Q
4300 Goodfellow Blvd
St. Louis, MO 63120 | 1 | Commander
US Army Tank-Automotive Command
ATTN: AMSTA-Q
Warren, MI 48397-5000 |
| 1 | Commander
US Army Natick RD&E Center
ATTN: STRNC-EP
Natick, MA 01760-5014 | 1 | Commander
US Army Test and Evaluation Command
ATTN: AMSTE-AD
Aberdeen Proving Ground, MD 21005-5055 |
| 1 | Commander
Army Research Laboratory
ATTN: AMSLC-PA
Adelphi, MD 20783-1145 | 1 | Commander
US Army Logistics Management Center
ATTN: AMXMC-ACM-MA
Fort Lee, VA 23801-6042 |
| 1 | Commander
US Army Communication Electronics
Command
ATTN: AMSEL-ED
Fort Monmouth, NJ 07703-5000 | 1 | Director
US Army Management Engineering College
ATTN: AMXOM-DO
Rock Island, IL 61299-7040 |
| 1 | Commander
US Army Communication Electronics
Command
ATTN: AMSEL-ED-GS
Fort Monmouth, NJ 07703-5000 | 1 | Chief
Product Assurance and Test Field Activity
ATTN: AMXQA
Lexington, KY 40511-5105 |
| | | 1 | Director
US Army Materiel Systems Analysis
Agency
ATTN: AMXSY-R
Aberdeen Proving Ground, MD 21005-5071 |

DEPARTMENT OF THE ARMY

- 1 Commander, HQ TRADOC
ATTN: ATEN-ME
Ft. Monroe, VA 23651
- 1 HQDA (DAMA-AOA-M)
Washington, DC 20310
- 1 HQDA (DAEN-RDL)
Washington, DC 20314
- 1 HQDA (DAEN-MPE-T)
Washington, DC 20314
- 1 Commander
US Army Missile Command
ATTN: DRSMI-RR
Redstone Arsenal, AL 35809
- 1 Director
US Army Materiel Systems Analysis
Agency
ATTN: DRXSY-CM
Aberdeen Proving Ground, MD 21005
- 1 Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-TSD-S (STINFO)
Aberdeen Proving Ground, MD 21005
- 1 Commander
US Army Engineer School and Center
ATTN: ATSE-DAC-LC
Canadian Liaison Office (Maj. S. Allan)
Fort Leonard Wood, MO 65473
- 1 Commander and Director
USAE Waterways Experiment Station
ATTN: CEWES-IM-MI-R
A. Clark, CD Dept 10660
3909 Halls Ferry Road
Vicksburg, MS 3918 6199

BELVOIR RD&E CENTER

Circulate

- 1 Commander, SATBE-Z
Technical Director, SATBE-ZT
Assoc Tech Dir (E&A), SATBE-ZTE
Assoc Tech Dir (R&D), SATBE-ZTR
Admin Officer, SATBE-ZA
Operations Sergeant, SATBE-ZM
- 1 Advanced Systems Concepts Dir, SATBE-H
Dir., Resource Management, SATBE-C
Dir., Automated Services Dir, SATBE-B
Dir., Facilities and Support Dir, SATBE-W
Dir., Product Assurance & Engr Dir,
SATBE-T
Dir., Combat Engineering Dir, SATBE-J
Dir., Logistics Equipment, SATBE-F
- 20 SATBE-JBA

- 2 Tech Report Office, ASQNK-BRS-G
- 1 Security Ofc, SATBE-WS
- 2 Tech Library, SATBE-BT
- 1 Public Affairs Office, SATBE-I
- 1 Ofc of Chief Counsel, SATBE-L

AMC LIBRARIES

- 1 US Army Aberdeen Proving Ground
ATTN: STEAP-IM-AL
Aberdeen Proving Ground, MD 21005-5001
- 1 Director, US Army Ballistic Research Lab
ATTN: AMXBR-OD-ST
Aberdeen Proving Ground, MD 21005-5066
- 1 HQ, US Army TECOM
ATTN: AMSTE-TO-F
Aberdeen Proving Ground, MD 21005-5055
- 1 Director, US Army Laboratory Command
Materials Technology Laboratory
ATTN: SLCMT-ML
Watertown, MA 02172-0001
- 1 Commander, USA Communications &
Electronics Command
ATTN: AMSEL-ME-PSL
Ft. Monmouth, NJ 07703-5007
- 1 HQ, US Army CECOM
ATTN: AMSEL-LG-JA
Ft. Monmouth, NJ 07703-5010
- 1 Commander
US Army Aviation Systems Command
ATTN: AMSAV-DIL
4300 Goodfellow Blvd, East 2
St. Louis, MO 63120-1798
- 1 Commander
US Army Armament, Munitions &
Chemical Command
ATTN: AMSMC-MPL
Rock Island, IL 61299-6000
- 1 Commander
US Army Missile Command
ATTN: AMSMI-RPR
Redstone Scientific Information Center
Redstone Arsenal, AL 35898-5241
- 1 Commander
US Army Missile Command
ATTN: AMSMI-YDL
Redstone Arsenal, AL 35898-5500
- 1 Director
White Sands Missile Range
ATTN: STEWS-TE-TL
White Sands Missile Range, NM 8002-5029

- 1 Commander
White Sands Missile Range
ATTN: STEWS-DP-ML
White Sands Missile Range, NM 88002-5039
- 1 HQ, US Army Materiel Command
ATTN: AMCDMA-ML
5001 Eisenhower Ave
Alexandria, VA 22333-0001
- 1 Commander
US Army Tank Automotive Command
ATTN: AMSTA-TSL
Warren, MI 48397-5000
- 1 Commander
Automated Logistics Mgmt Systems Activity
ATTN: AMXAL-AAG
PO Box 1578
St. Louis, MO 63188-1578
- 1 US Army Armament RD&E Center
ATTN: SMCAR-TSS
Bldg 59
Dover, NJ 07801-5001
- 1 Commander, USA Aviation Research &
Technology Activity
Applied Technology Directorate
ATTN: SAVDL-ATL-TSC, Bldg 401
Ft. Eustis, VA 23604-5577
- 1 US Army Natick RD&E Center
ATTN: STRNC-ML
Natick, MA 01760-5000
- 1 US Army Tank Automotive Command
ATTN: AMSTA-TSL
Warren, MI 48090-5000
- 1 Commander
US Army Armament RD&E Center
Benet Weapons Lab
ATTN: SMCAR-CCB-TL
Watervliet Arsenal
Watervliet, NY 12189-5000
- 1 Commander
US Army Yuma Proving Ground
ATTN: STEYP-IM-AT
Yuma, AZ 85365-9102
- 1 Commandant
US Army School of Engineering & Logistics
ATTN: AMXMC-SEL-L
Red River Army Depot
Texarkana, TX 75507-5000
- 1 Commander
Letterkenny Army Depot
ATTN: SDSLE-SWIM
Chambersburg, PA 17201-4150

- 1 Commander
New Cumberland Army Depot
ATTN: SDSNC-D-DA
New Cumberland, PA 17070-4150
- 1 Commander
Seneca Army Depot
ATTN: SDSSE-TR
Romulus, NY 14541-5110
- 1 Commander
Sierra Army Depot
ATTN: SDSSI-CSB
Herlong, CA 96113-5110
- 1 Commander
Sharpe Army Depot
ATTN: SDSSH-AMW-MSA
Lathrop, CA 95331-5124
- 1 Commander
Tobyhanna Army Depot
ATTN: SDSTO-DA-T
Tobyhanna, PA 18466-5099
- 1 Commander
Tobyhanna Army Depot
ATTN: SDSTO-TM
Tobyhanna, PA 18466-5097
- 1 Commander
Sacramento Army Depot
ATTN: SDSSA-AAD-W
Sacramento, CA 95813-5009
- 1 Commander
Corpus Christi Army Depot
ATTN: SDSSC-AAR
Corpus Christi, TX 78419-6020
- 1 US Army Foreign Science & Technology Ctr
ATTN: AMXST-IS3
220 7th Street, NE
Charlottesville, VA 22901-5396

OTHER ARMY LIBRARIES

- 1 Director
US Army TRADOC Systems Analysis Acty
ATTN: ATAA-SL (Tech Library)
White Sands Missile Range, NM 88002
- 1 US Army Aviation School Library
PO Drawer 0
Ft. Rucker, AL 36360
- 1 US Military Academy
ATTN: Mr. Egon Weiss, Librarian
West Point, NY 10996
- 1 Commandant
US Army Engineer School
ATTN: Library
Ft. Leonard Wood, MO 65473

- 1 US Army Humphrey's Engr Spt Activity
ATTN: Library Branch
Ft. Belvoir, VA 22060
- 1 Engineer Topographic Lab
ATTN: STINFO
Ft. Belvoir, VA 22060
- 1 Pentagon Library
ATTN: Chief, Reader's Services Branch
The Pentagon, Room 1A518
Washington, DC 20310
- 1 US Army Corps of Engineers
ATTN: DAEN-AS-Tech Library
20 Massachusetts Ave, NW
Room 3119
Washington, DC 20314
- 1 US Army Operational Test &
Evaluation Agency
ATTN: Tech Library
5600 Columbia Pike, Room 503
Falls Church, VA 22401

DOD LIBRARIES

- 1 Naval Mine Warfare Engineering Activity
Code 322
Yorktown, VA 23691
- 1 Commander
Naval Facilities Engineering Command
ATTN: Library
200 Stovall St
Alexandria, VA 22332
- 1 David W. Taylor Naval Ship RD&E Center
Library Division, Code 5220
Bethesda, MD 20084
- 1 Naval Air Systems Command
ATTN: Tech Library
Air 00D4
Washington, DC 20361
- 1 Naval Surface Weapons Center
ATTN: Tech Library
Dahlgren, VA 22448
- 1 Naval Research Lab
ATTN: Tech Library
Washington, DC 20375
- 1 Naval Surface Weapons Center
ATTN: Tech Library
Silver Spring, MD 20910
- 1 Naval Sea Systems Command
Library Documentation Branch
Sea 9661
Washington, DC 20362

- 1 Naval Ship System Engineering Station
Technical Library
Code 011F
Bldg 619
Philadelphia, PA 19112
- 1 Naval Training Equipment Center
ATTN: Technical Library
Orlando, FL 32813
- 1 HQ, USMC
Marine Corps Technical Library
Code LMA-1
Washington, DC 20314
- 1 Air Force Systems Command
Technical Information Center
HQ AFSC/MPSLT
Andrews AFB, DC 20334
- 1 HQ AF Engineering & Services Center
Tech Library FL 7050
Tyndall AFB, FL 32403
- 1 Defense Systems Management College
ATTN: Library
Bldg 205
Ft. Belvoir, VA 22060
- 1 Director, Defense Nuclear Agency
ATTN: TITL
Washington, DC 20305

OTHER FEDERAL LIBRARIES

- 1 Geological Survey Library (GIS)
National Center, Stop 950
12201 Sunrise Valley Drive
Reston, VA 22092
- 1 National Bureau of Standards (NBS)
E01 Administration Building
Washington, DC 20234
- 1 Department of Transportation Library
FOB 10A, M494-6
800 Independence Ave, SW
Washington, DC 20591