


AD-A268 301



Handwritten signature or initials

Atlas of Formability:

Cast Aluminum 6061
Flow Stress Curves,



DTIC
ELECTE
AUG 18 1993
S B D

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

93-18844



Handwritten number 2388

NCEM

93 8 16 02 3

REPORT DOCUMENTATION PAGEForm Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204 Arlington, VA 22202-4302 and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 31, 1991		3. REPORT TYPE AND DATES COVERED Final, October 31, 1990-January 31, 1991	
4. TITLE AND SUBTITLE Atlas of Formability Cast Aluminum 6061				5. FUNDING NUMBERS C-N00140-88-C-RC21	
6. AUTHOR(S) Howard A. Kuhn					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Center for Excellence in Metalworking Technology (NCEMT) 1450 Scalp Avenue Johnstown, PA 15904				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Naval Industrial Resources Support Activity Building 75-2, Naval Base Philadelphia, PA 19112-5078				10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) In this investigation, flow behavior of Aluminum 6061 alloy was studied by conducting compression tests over a wide range of temperatures and strain rates. Stress-strain curves were recorded for each test condition. These data are essential in metalworking process design or finite element analysis of high temperature deformation.					
14. SUBJECT TERMS Aluminum 6061, High Temperature Deformation, Metalworking				15. NUMBER OF PAGES 22	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT		

**ATLAS OF FORMABILITY
CAST ALUMINUM 6061**

by

Howard A. Kuhn

**National Center for Excellence in Metalworking Technology
1450 Scalp Avenue
Johnstown, PA 15904**

for

**Naval Industrial Resource Support Activity
Building 75-2, Naval Base
Philadelphia, PA 19112-5078**

January 31, 1991

The views, opinions, and/or findings contained in this report are those of the authors and should not be construed as an official Department of the Navy position, policy, or decision, unless so designated by other documentation

TABLE OF CONTENTS

Testing Parameters	1
Stress-Strain Curves	2

DTIC QUALITY INSPECTED 3


ST #A, AUTH USNAVIRSA (MR PLONSKY 8/443-6684)
PER TELECON, 17 AUG 93 CB

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By <i>per telecon</i>	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
<i>A-1</i>	


Cast Aluminum 6061

Testing Parameters


Strain Rate (1/sec.)	Temperature (deg. C)	Graph Number	Page Number
0.01	300	66117	2
0.01	420	66116	3
0.01	540	66119	4
0.01	Combination	66123	5
0.1	360	66114	6
0.1	480	66115	7
0.1	Combination	66124	8
1.0	300	66122	9
1.0	420	66109	10
1.0	540	66112	11
1.0	Combination	66125	12
5.0	360	66101	13
5.0	480	66102	14
5.0	Combination	66126	15
12.0	300	66104	16
12.0	420	66103	17
12.0	540	66106	18
12.0	Combination	66127	19



NCEMT




NCEMT




NCEMT


GRAPH NO: 66123
STRAIN RATE: 0.01/SEC




NCEMT




NCEMT




GRAPH NO: 66124
STRAIN RATE: 0.1/SEC




NCEMT



NCEMT




NCEMT




NCEMT


GRAPH NO: 66125
STRAIN RATE: 1.0/SEC



NCEMT




NCEMT




NCEMT

GRAPH NO: 66126


STRAIN RATE: 5.0/SEC




NCEMT




NCEMT



NCEMT



NCEMT



NCEMT