



USAISEC

AD-A268 377



2

*US Army Information Systems Engineering Command
Fort Huachuca, AZ 85613-5300*

U.S. ARMY INSTITUTE FOR RESEARCH
IN MANAGEMENT INFORMATION,
COMMUNICATIONS, AND COMPUTER SCIENCES

SAMeDL: Technical Report Appendix C – Developmental Environment Test Plan

DTIC
ELECTE
AUG 16 1993
S A D

ASQB-GI-92-016

September 1992

This document has been approved
for public release and sale; its
distribution is unlimited.

93-18743



177106

AIRMICS
115 O'Keefe Building
Georgia Institute of Technology
Atlanta, GA 30332-0800



REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188
Exp. Date: Jun 30, 1986

1. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS NONE	
2. SECURITY CLASSIFICATION AUTHORITY N/A		3. DISTRIBUTION/AVAILABILITY OF REPORT N/A	
4. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A		5. MONITORING ORGANIZATION REPORT NUMBER(S) N/A	
6. PERFORMING ORGANIZATION REPORT NUMBER(S)		7a. NAME OF MONITORING ORGANIZATION N/A	
7. NAME OF PERFORMING ORGANIZATION		7b. ADDRESS (City, State, and ZIP Code) N/A	
8. ADDRESS (City, State, and Zip Code)		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
9. NAME OF FUNDING/SPONSORING ORGANIZATION Software Technology Branch, ARL		10. SOURCE OF FUNDING NUMBERS	
10. ADDRESS (City, State, and ZIP Code) 115 O'Keefe Bldg. Georgia Institute of Technology Atlanta, GA 30332-0800		PROGRAM ELEMENT NO.	PROJECT NO.
11. TITLE (Include Security Classification) SAmEDL: Technical Report Appendix C - Development Environment Test Plan		TASK NO.	WORK UNIT ACCESSION NO.
12. PERSONAL AUTHOR(S) MS. Deb Waterman			
13a. TYPE OF REPORT Technical Paper	13b. TIME COVERED FROM Apr 91 TO Sept 92	14. DATE OF REPORT (Year, Month, Day) Sept 15, 1992	15. PAGE COUNT 174
16. SUPPLEMENTARY NOTATION			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUBGROUP	
		Ada Database Access, SAmEDL, Ada extension module, SQL	
19. ABSTRACT (Continue on reverse if necessary and identify by block number)			
This report details the research efforts into the SQL Ada Module Database Description Language (SAmEDL). Four compilers are presented (Oracle, Informix, XDB, and Sybase) that allow Ada application programs to access database using a standard SQL query language. Copies of the compiler can be obtained from the DoD Ada Joint Program Office 703/614-0209.			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL LTC David S. Stevens		22b. TELEPHONE (Include Area Code) (404) 894-3110	22c. OFFICE SYMBOL AMSRL-CI-CD

This research was performed by Statistica Inc., contract number DAKF11-91-C-0035, for the Army Institute for Research in Management Information, Communications, and Computer Sciences (AIRMICS), the RDTE organization of the U. S. Army Information Systems Engineering Command (USAISEC). This final report discusses a set of SAMeDL compilers and work environment that were developed during the contract. Request for copies of the compiler can be obtained from the DoD Ada Joint Program Office, 703/614/0209. This research report is not to construed as an official Army or DoD Position, unless so designated by other authorized documents. Material included herein is approved for public release, distribution unlimited. Not protected by copyright laws.

THIS REPORT HAS BEEN REVIEWED AND IS APPROVED



Glenn E. Racine, Chief
Computer and Information
Systems Division



James D. Gantt, Ph.D.
Director
AIRMICS

DTIC QUALITY INSPECTED 3

Accession For	
NTIS CRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

SAMeDL.TR.10.15 Sep 92

APPENDIX C

**SAMeDL Development Environment
Test Plan**

SAMeDL Development Environment Test Plan

Intermetrics, Inc.

Document	IR-VA-014
Date	03-March-1992

Published by
Intermetrics, Inc.
733 Concord Avenue, Cambridge, Massachusetts 02138

Copyright (c) 1992 by Intermetrics, Inc.

This material may be reproduced by or for the U.S. Government pursuant to the copyright license under the clause at DFARS 252.227-7013 (Oct. 1988).

Table Of Contents

Chapter 1	About This Manual.....	1
	1.1 Purpose	1
	1.2 Organization	1
	1.3 References	1
Chapter 2	Module Manager Testing Procedure	3
	2.1 sde.clearlib	3
	2.2 sde.creatlib	3
	2.3 sde.creatar	4
	2.4 sde.ls	4
	2.5 sde.mkscript	5
	2.6 sde.purge	5
	2.7 sde.rm	5
	2.8 sde.rmlib	6
Chapter 3	Compiler Testing Procedure.....	7
	3.1 Introduction	7
	3.2 Correct Tests.....	7
	3.3 End-to-End Tests	7
	3.4 Error Tests	8
Chapter 4	Compiler Testing Cross Reference	9
	4.1 Diagram 1	
	Correct Testing Cross Reference.....	10
	4.2 Diagram 2	
	End-to-End Testing Cross Reference	13
	4.3 Diagram 3	
	Error Testing Cross Reference	14
Appendix A	Compiler Test Suite Source Code	15
	A.1 Correct Tests.....	15
	A.1.1 t1/ci.sme.....	15
	A.1.2 t1/cii.sme.....	15
	A.1.3 t1/ciii.sme	17
	A.1.4 t1/civ.sme.....	19
	A.1.5 t1/cv.sme.....	23
	A.1.6 t1/cvi.sme.....	28
	A.1.7 t1/cvii.sme.....	32
	A.1.8 t1/cviii.sme	36
	A.1.9 t1/cix.sme.....	40
	A.1.10 t1/ct1.sme.....	44
	A.1.11 t1/ct2.sme.....	46
	A.1.12 t1/ct3.sme.....	47
	A.1.13 t1/ct4.sme.....	59
	A.1.14 t1/ct5.sme.....	60
	A.1.15 t1/ct6.sme.....	62
	A.1.16 t1/ct7.sme.....	63
	A.1.17 t1/ct8.sme.....	64
	A.1.18 t1/ct9.sme.....	65
	A.1.19 t1/ct10.sme.....	66

A.1.20	t1/ct11.sme	66
A.1.21	t1/ct12.sme	67
A.1.22	t1/ct13.sme	68
A.1.23	t1/ct14.sme	70
A.1.24	t1/ct15.sme	72
A.1.25	t1/ct16.sme	75
A.1.26	t3/t1.sme	77
A.1.27	t3/t2.sme	81
A.1.28	t3/t3.sme	82
A.1.29	t3/t4.sme	83
A.1.30	t3/t5.sme	87
A.1.31	t3/t6.sme	90
A.1.32	t3/t7.sme	91
A.1.33	t3/t8.sme	93
A.1.34	t3/t9.sme	94
A.1.35	t3/t10.sme	96
A.1.36	t3/t11.sme	97
A.1.37	t3/t12.sme	99
A.1.38	t3/t13.sme	99
A.1.39	t3/t14.sme	101
A.2	End-to-End Tests	101
A.2.1	t2/t2.sme	101
A.2.2	t2/driver.a	114
A.2.3	t2/initbank.sql	137
A.2.4	t2/initi.sql	138
A.3	Error Tests	138
A.3.1	t1/et1.sme	138
A.3.2	t1/et2.sme	140
A.3.3	t1/et3.sme	140
A.3.4	t1/et4.sme	140
A.3.5	t1/et5.sme	142
A.3.6	t1/et6.sme	147
A.3.7	t1/et7.sme	148
A.3.8	t1/et8.sme	157
A.3.9	t1/et9.sme	159
A.3.10	t1/et10.sme	160
A.3.11	t1/et11.sme	161
A.3.12	t1/et12.sme	165
A.3.13	t3/e1.sme	168
A.3.14	t3/e2.sme	170
A.3.15	t3/e3.sme	171

Chapter 1 About This Manual

1.1 Purpose

The purpose of this manual is to describe the test plan for the SAMeDL Development Environment (SDE), consisting of the SAMeDL compiler and the Module Manager. These tools and their features are documented in the *SAMeDL Development Environment User Manual* [User]. The language supported by the SAMeDL compiler is defined in the *SAMeDL Language Reference Manual* [LRM].

1.2 Organization

The organization of this document is as follows:

- Chapter 2, *Module Manager Testing Procedure*, outlines the testing process to be followed in testing the SDE Module Manager commands.
- Chapter 3, *Compiler Testing Procedure*, contains an overview of the testing strategy to be followed for the SAMeDL compiler.
- Chapter 4, *Compiler Testing Cross Reference*, provides a cross reference of compiler testing objectives (in terms of [LRM] section numbers) against test source files.
- Appendix A, *Compiler Test Suite Source Code*, contains a listing of the source code files that comprise the SAMeDL compiler test suite.

1.3 References

1. [DSC] *Database System Concepts*, Korth and Silberschatz, McGraw-Hill, 1986.
1. [LRM] *SAMeDL Language Reference Manual*, Intermetrics, Inc., IR-VA-011, 28 February 1992.
2. [SAMEGuide] *Guidelines for the Use of the SAME*, Marc Graham: Software Engineering Institute/Carnegie Mellon University, Technical Report CMU/SEI-89-TR-16, May 1989.
3. [User] *SAMeDL Development Environment User Manual*, Intermetrics, Inc., IR-VA-012, 28 February 1992.

Chapter 2 Module Manager Testing Procedure

Testing of the Module Manager consists of invoking each of the commands (**sde.cleanlib**, **sde.creatar**, **sde.creatlib**, **sde.ls**, **sde.mkscript**, **sde.purge**, **sde.rm**, and **sde.rmlib**) in a variety of scenarios and manually inspecting the results. The process to be followed for each of the tools is outlined below.

2.1 sde.cleanlib

1. No arguments (i.e., default current directory).
2. Pathname argument.
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).
5. No samedl.lib directory in current directory and call with no arguments (*error*).
6. No samedl.lib directory in specified pathname directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory containing samedl.lib. (*error*).

2.2 sde.creatlib

1. No arguments (i.e., default current directory).
2. Pathname argument.
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).
5. samedl.lib directory already exists in current directory (*error*).
6. samedl.lib directory already exists in specified directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory where to create samedl.lib (*error*).

2.3 sde.creatar

1. No arguments (*error*).
2. Only archive name specified (*error*).
3. Only archive name and non-abstract module name specified (*error*).
4. Only archive name and abstract module name specified.
5. Add library Pathname argument.
6. Incorrect options (*error*).
7. samedl.lib directory does not exists in current directory (*error*).
8. samedl.lib directory does not exist in specified directory (*error*).
9. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
10. No permission to write in samedl.lib (*error*).
11. No permission to write in the directory where to create archive (*error*).
12. Non-existent modules (*error*).
13. Specify multiple modules.

2.4 sde.ls

1. No arguments (i.e., default current directory).
2. Pathname argument.
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).
5. No samedl.lib directory in current directory and call with no arguments (*error*).
6. No samedl.lib directory in specified pathname directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory containing samedl.lib (*error*).
10. Different permutations of the -i -a and -v options (*error*).
11. Multiple module names as arguments (*error*).
12. Non-existent modules names as arguments (*error*).

2.5 sde.mkscript

1. No pathname argument (current directory default) + def/abs module name.
2. Pathname argument + def/abs module name
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).
5. No samedl.lib directory in current directory and call with no arguments (*error*).
6. No samedl.lib directory in specified pathname directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory containing samedl.lib (*error*).
10. Multiple module names as arguments.
11. Non-existent modules as arguments (*error*).

2.6 sde.purge

1. No arguments (i.e., default current directory).
2. Pathname argument.
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).
5. No samedl.lib directory in current directory and call with no arguments (*error*).
6. No samedl.lib directory in specified pathname directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory containing samedl.lib. (*error*).

2.7 sde.rm

1. No pathname argument (current directory default) + module name.
2. Pathname argument + module name
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).

5. No samedl.lib directory in current directory and call with no arguments (*error*).
6. No samedl.lib directory in specified pathname directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory containing samedl.lib (*error*).
10. Multiple module names as arguments.
11. Non-existent modules names as arguments (*error*).
12. Interactive option (test yes/no).

2.8 sde.rmlib

1. No arguments (i.e., default current directory).
2. Pathname argument.
3. Incorrect number of arguments (*error*).
4. Incorrect options (*error*).
5. No samedl.lib directory in current directory and call with no arguments (*error*).
6. No samedl.lib directory in specified pathname directory (*error*).
7. On a locked library (simulate by creating ./samedl.lib/samedl.lock) (*error*).
8. No permission to write in samedl.lib (*error*).
9. No permission to write in the directory containing samedl.lib (*error*).

Chapter 3 Compiler Testing Procedure

3.1 Introduction

Testing of the SAMeDL compiler will be divided into three basic areas:

1. Verify that the SAMeDL compiler recognizes and processes proper (as defined by [LRM]) syntactical and semantic constructs submitted to it. These tests will be known as the *Correct Tests*.
2. Verify that the output of the SAMeDL compiler will functionally (as defined by [LRM]) interface with the target database. These tests will be known as the *End-to-End Tests*.
3. Verify that the SAMeDL compiler identifies improper syntactical and semantic constructs (as defined by [LRM]) as errors. These tests will be known as the *Error Tests*.

3.2 Correct Tests

Proper syntactic and semantic constructs will be tested using a series of SAMeDL program modules that will contain all facets of the SAMeDL language described in the LRM. Diagram 1 in Chapter 4 shows the tests and which sections of the LRM are validated after the successful compilation of the program module.

A correct test is said to *pass* if:

1. The SAMeDL source code for the test can be compiled by the SAMeDL compiler without issuing an error message; and
2. Where interface files should be generated (see [LRM], [User]), the interface files are correctly generated and can be compiled without error by the appropriate compiler and/or pre-compiler (i.e., Ada compiler, C/ESQL pre-compiler, C compiler, Ada/SQL Module Language compiler) without error. (*Note:* depending on the specific configuration of the SAMeDL compiler, not all of the above compilers/pre-compilers may be applicable, or if applicable, may be invoked transparently by the SAMeDL compiler. Refer to [User] to determine the situation that applies.)

Otherwise, a correct test is said to *fail*.

3.3 End-to-End Tests

To test the output of the SAMeDL compiler for proper interfaces with the database management system, a program will be written in Ada that will exercise all the Procedure and Cursor definitions from the SAMeDL modules. Upon its execution, the program will initialize the database and start the testing procedures. The initialization and verification routines will set up the database for the following tests while testing the data structure interface and basic SAMeDL procedure and cursor functionality. The more complex cursor and procedure tests will then be run individually. The Ada application program will be written such that it is self-checking.

At the conclusion of each step of initialization and testing the driver will:

1. Report on the outcome of the test.
2. If the test has completed successfully, the driver will progress to the next test (if any).
3. If the test has failed, the driver will exit the testing procedure.

This area is covered by the single t2 test (see Section A.2) which consists of 6 subtests for procedures and 11 subtests for cursors. Diagram 2 in Chapter 4 shows the cross-reference matrix of the tests to the portions of the LRM they are testing. LRM Chapters 2 through 4 are not explicitly tested for functionality, but are implicitly tested during the other tests.

The database design used in the test suite was based on an example database from [DSC]. It consists of 5 tables defining basic banking information:

CUSTOMER TABLE

Name	Street	City	State	Zip	SSN
------	--------	------	-------	-----	-----

SAVINGS_ACCOUNT TABLE

Account #	Balance	Customer SSN	Branch ID
-----------	---------	--------------	-----------

CHECKING_ACCOUNT TABLE

Account #	Balance	Customer SSN	Branch ID
-----------	---------	--------------	-----------

LOAN_ACCOUNT TABLE

Account #	Balance	Payment	Customer SSN	Branch Id
-----------	---------	---------	--------------	-----------

BRANCH_INFO TABLE

Branch ID	Assets
-----------	--------

This design was chosen because the full range of SAMeDL data types and data manipulation statements could be implemented in a meaningful fashion.

3.4 Error Tests

An error test consists of a single SAMeDL source code file containing one or more errors; errors will be marked in the source code through SAMeDL comments. These tests will be said to *pass* if the marked errors are appropriately detected when compiled by the SAMeDL compiler.

Diagram 3 in Chapter 4 shows the cross-reference matrix of the error tests to the portions of the LRM they are testing.

Chapter 4 Compiler Testing Cross Reference

This chapter provides a cross reference of compiler testing objectives (in terms of [LRM] section numbers) against test source files.

4.1 Diagram 1: Correct Testing Cross Reference

LRM Section	t1/cXXXX Tests																
	i	ii	iii	iv	v	vi	vii	viii	ix	t1	t2	t3	t4	t5	t6	t7	t8
2.1	x											x					
2.2	x											x					
2.3	x											x					
2.4	x	x										x					
2.5	x											x					
2.6	x	x	x	x	x	x	x	x	x			x				x	x
3.1	x		x	x		x			x		x	x					x
3.2			x	x		x			x		x	x		x			
3.3				x	x						x	x					
3.4	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
3.5	x			x	x	x		x	x			x			x		
3.6				x	x			x	x		x	x	x				
3.7												x					
4.1	x	x							x		x	x				x	x
4.1.1																	
4.1.2	x	x									x	x					
4.1.3	x	x									x	x					
4.1.4	x											x			x		
4.1.5		x					x			x	x	x					
4.1.6	x	x		x							x	x					
4.1.7																	
4.1.8				x							x	x	x				
4.2			x			x			x		x	x					
4.2.1			x								x	x					
4.2.2																	
4.3	x			x	x			x			x	x			x		
5.1				x	x			x	x	x	x	x					
5.2				x					x	x	x	x					
5.3				x					x	x	x	x					
5.4					x	x	x	x		x	x	x					
5.5					x	x	x	x		x	x	x					
5.6				x	x	x		x	x		x	x					
5.7				x	x	x		x		x	x	x					
5.8									x			x					
5.9				x				x	x	x	x	x					
5.10	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.11				x	x		x				x	x					
5.11.1				x	x						x	x					
5.11.2						x						x					
5.11.3						x						x					
5.11.4						x						x					
5.11.5						x						x					
5.11.6							x					x					
5.11.7						x						x					
5.12				x		x	x					x					
5.13				x	x						x	x	x				

LRM Section	t1/cXXXX Tests															
	t9	t10	t11	t12	t13	t14	t15	t16	---	---	---	---	---	---	---	---
2.1																
2.2																
2.3																
2.4						x	x									
2.5																
2.6																
3.1	x	x	x	x												
3.2	x	x	x	x												
3.3					x											
3.4	x	x	x	x	x	x	x	x								
3.5						x	x									
3.6																
3.7																
4.1																
4.1.1																
4.1.2																
4.1.3																
4.1.4						x	x									
4.1.5								x								
4.1.6							x									
4.1.7																
4.1.8																
4.2	x	x														
4.2.1																
4.2.2																
4.3						x										
5.1			x	x	x											
5.2					x		x									
5.3					x		x									
5.4					x			x								
5.5					x			x								
5.6					x											
5.7					x			x								
5.8							x									
5.9					x		x	x								
5.10	x	x	x	x	x	x	x	x								
5.11																
5.11.1																
5.11.2																
5.11.3																
5.11.4																
5.11.5																
5.11.6																
5.11.7																
5.12																
5.13																

LRM Section	t3/XXXX Tests																
	t1	t2	t3	t4	t5	t6	t7	t8	t9	t10	t11	t12	t13	t14	---	---	---
2.1																	
2.2																	
2.3																	
2.4																	
2.5																	
2.6																	
3.1																	
3.2																	
3.3			x														
3.4	x	x	x	x	x	x	x	x	x	x	x	x	x	x			
3.5	x	x															
3.6	x			x	x												
3.7																	
4.1																	
4.1.1																	
4.1.2																	
4.1.3																	
4.1.4																	
4.1.5	x	x				x	x		x	x							
4.1.6																	
4.1.7	x																
4.1.8	x			x	x												
4.2				x													
4.2.1				x													
4.2.2																	
4.3	x																
5.1																	
5.2	x			x	x				x	x							
5.3	x			x	x				x	x							
5.4	x	x	x	x	x	x	x	x	x	x							
5.5	x	x	x	x	x	x	x	x	x	x							
5.6	x			x	x												
5.7	x	x		x	x												
5.8	x			x	x												
5.9	x			x	x				x	x							
5.10	x	x	x	x	x	x	x	x	x	x	x	x	x	x			
5.11							x	x									
5.11.1																	
5.11.2																	
5.11.3																	
5.11.4																	
5.11.5																	
5.11.6																	
5.11.7																	
5.12						x	x	x									
5.13	x			x	x				x	x							

4.2 Diagram 2: End-to-End Testing Cross Reference

LRM Section	Procedure Tests (PTxxxx)						Cursor Tests (CTxxxx)										
	1	2	3	4	5	6	1	2	3	4	5	6	7	8	9	10	11
5.1	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.2	x	x	x	x	x	x											
5.3	x	x	x	x	x	x											
5.4	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.5	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.6	x		x	x		x	x	x	x	x	x	x	x	x	x	x	x
5.7	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.8	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.9	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.10	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
5.11	x		x	x		x	x	x	x	x	x	x	x	x	x	x	x
5.11.1	x		x	x		x	x	x	x	x	x	x					
5.11.2													x	x			
5.11.3															x		
5.11.4																x	
5.11.5																	x
5.11.6																	x
5.11.7																	x
5.12																	x
5.13	x				x	x	x	x	x	x	x	x	x	x	x	x	x

4.3 Diagram 3: Error Testing Cross Reference

LRM Section	t1/XXXX Tests												t3/XXXX Tests				
	et1	et2	et3	et4	et5	et6	et7	et8	et9	et10	et11	et12	e1	e2	e3	---	---
2.1																	
2.2																	
2.3																	
2.4		x															
2.5																	
2.6																	
3.1																	
3.2																	
3.3																	
3.4																	
3.5					x		x	x			x	x					
3.6																	
3.7																	
4.1									x								
4.1.1																	
4.1.2																	
4.1.3																	
4.1.4						x											
4.1.5	x								x		x	x	x	x	x		
4.1.6																	
4.1.7																	
4.1.8									x								
4.2																	
4.2.1																	
4.2.2																	
4.3																	
5.1																	
5.2	x									x							
5.3								x		x	x						
5.4	x											x	x	x	x		
5.5												x					
5.6																	
5.7				x			x				x	x	x	x	x		
5.8																	
5.9	x										x	x	x	x	x		
5.10																	
5.11																	
5.11.1																	
5.11.2																	
5.11.3																	
5.11.4			x														
5.11.5																	
5.11.6																	
5.11.7																	
5.12																	
5.13																	

Appendix A Compiler Test Suite Source Code

A.1 Correct Tests

A.1.1 t1/ci.sme

```
-- *****
-- *** Test I
-- *****

DEFINITION MODULE D_cI IS

-- the previous line tests the newline separator
--
-- testing full character set
--
  DOMAIN Character_set_domain IS
    NEW SQL_CHAR(length => 43);
  CONSTANT letters : character_set_domain
    IS 'the quick brown fox jumps over the lazy dog';
  CONSTANT all_caps : character_set_domain
    IS 'THE QUICK BROWN FOX JUMPS OVER THE LAZY DOG';
  CONSTANT digit_as_char : character_set_domain
    IS '1234567890';
  CONSTANT digits_as_num
    IS 1234567890;

  DOMAIN integer_domain IS
    NEW SQL_INT;
  DOMAIN real_domain IS
    NEW SQL_REAL;
  CONSTANT integer_literal : integer_domain
    IS (12-4+5*2);
  CONSTANT real_literal : real_domain
    IS 12.456/.09 + 1. ;
  CONSTANT float_literal
    IS (0.1E1) + (10.E-1) + ( .1E+1) ;

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
  DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_CHAR
      (ENUMERATION => Loan_types, MAP => IMAGE);
  CONSTANT personal_loan : loan_type_domain
    IS personal ;

END D_cI;
```

A.1.2 t1/cii.sme

```
-- *****
-- *** Test II
-- *****
```

```
DEFINITION MODULE D_cII IS
--
--   enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
--   domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 50);
  DOMAIN SSN_domain IS
    NEW SQL_CHAR NOT NULL (length => 9);
  DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN City_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
  DOMAIN Branch_name_domain IS
    NEW SQL_CHAR(length => 25);
--
--   domain integer declarations
--
  DOMAIN ZIP_code_domain IS
    NEW SQL_INT( FIRST => 0, LAST => 999999999);
  DOMAIN ZIP2_code_domain IS
    NEW SQL_INT NOT NULL;
  DOMAIN Account_number_domain IS
    NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
  DOMAIN Account2_number_domain IS
    NEW SQL_SMALLINT NOT NULL;
--
--   domain real declarations
--
  DOMAIN Balance_domain IS
    NEW SQL_REAL;
  DOMAIN Interest_rate_domain IS
    NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
  DOMAIN Loan_payment_domain IS
    NEW SQL_REAL NOT NULL;
  DOMAIN Branch_assets_domain IS
    NEW SQL_REAL NOT NULL (FIRST => 0.0, LAST => 1.0E+10);
--
--   domain enumeration declarations
--
  DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_CHAR
      (ENUMERATION => Loan_types, MAP => IMAGE);
  DOMAIN Loan2_type_domain IS
```

```

NEW SQL_ENUMERATION_AS_CHAR NOT NULL
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
    (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street         : Addr_domain NOT NULL;
  City           : City_domain;
  State          : State_domain;
  ZIP            : ZIP_code_domain;
END customer_record;

END D_cII;

```

A.1.3 t1/ciii.sme

```

-- *****
-- *** Test III
-- *****

DEFINITION MODULE D_cIII IS
--
--  enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
--  domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 50);
  DOMAIN SSN_domain IS
    NEW SQL_CHAR NOT NULL (length => 9);
  DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN City_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
  DOMAIN Branch_name_domain IS
    NEW SQL_CHAR(length => 25);
--

```

```
--      domain integer declarations
--
DOMAIN ZIP_code_domain IS
  NEW SQL_INT( FIRST => 0, LAST => 999999999);
DOMAIN ZIP2_code_domain IS
  NEW SQL_INT NOT NULL;
DOMAIN Account_number_domain IS
  NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
DOMAIN Account2_number_domain IS
  NEW SQL_SMALLINT NOT NULL;
--
--      domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL NOT NULL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL NOT NULL (FIRST => 0.0, LAST => 1.0E+10);
--
--      domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR
    (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
    (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
    (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street         : Addr_domain NOT NULL;
  City           : City_domain;
  State          : State_domain;
  ZIP            : ZIP_code_domain;
END customer_record;

END D_cIII;

WITH D_cIII;
USE D_cIII;
SCHEMA MODULE T1_III IS
--
--      Basic customer information
--
TABLE Customer IS
  Cust_Name      : Customer_name_domain,
```

```

        SSN not null      : SSN_domain ,
        Street_addr : Addr_domain,
        City_addr   : addr_domain,
        State_addr  : State_domain,
        ZIP_addr    : ZIP_code_domain
    END Customer;
--
-- Savings account
--
    TABLE Savings_account IS
        SBranch_number : Branch_number_domain,
        SAccount_number : Account_number_domain ,
        SBalance       : Balance_domain,
        SCustomer_SSN not null : SSN_domain
    END ;
--
-- Checking account
--
    TABLE Checking_account IS
        CBranch_number : Branch_number_domain,
        CAccount_number : Account_number_domain ,
        CBalance       : Balance_domain,
        CCustomer_SSN not null : SSN_domain
    END Checking_account;
--
-- loan account
--
    TABLE loan_account IS
        LBranch_number : Branch_number_domain,
        LAccount_number : Account_number_domain ,
        LBalance       : Balance_domain,
        LPayment not null : Loan_Payment_domain,
        LCustomer_SSN not null : SSN_domain
    END loan_account;
--
-- Branch information
--
    TABLE Branch_info IS
        Branch_name : Branch_name_domain ,
        Branch_number : Branch_number_domain ,
        Assets not null : Branch_assets_domain
    END Branch_info;

END T1_III;

```

A.1.4 t1/civ.sme

```

-- *****
-- *** Test IV
-- *****

DEFINITION MODULE D_cIV IS
--
--     enumeration declarations
--
    ENUMERATION Branches IS
        ( Bethesda,
          Silver_Spring,

```

```
        Gaithersburg,
        Potomac);

ENUMERATION Loan_types IS
( mortgage,
  auto,
  personal);

--
--      domain character declarations
--
DOMAIN Customer_name_domain IS
  NEW SQL_CHAR(length => 50);
DOMAIN SSN_domain IS
  NEW SQL_CHAR NOT NULL (length => 9);
DOMAIN Addr_domain IS
  NEW SQL_CHAR(length => 25);
DOMAIN City_domain IS
  NEW SQL_CHAR(length => 25);
DOMAIN State_domain IS
  NEW SQL_CHAR(length => 2);
DOMAIN Branch_name_domain IS
  NEW SQL_CHAR(length => 25);
--
--      domain integer declarations
--
DOMAIN ZIP_code_domain IS
  NEW SQL_INT( FIRST => 0, LAST => 999999999);
DOMAIN ZIP2_code_domain IS
  NEW SQL_INT NOT NULL;
DOMAIN Account_number_domain IS
  NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
DOMAIN Account2_number_domain IS
  NEW SQL_SMALLINT NOT NULL;
--
--      domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL NOT NULL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--
--      domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR
    (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
    (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
```

```

        (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
    Cust_Name      : Customer_name_domain;
    SSN             : SSN_domain;
    Street_addr    : Addr_domain;
    City_addr      : City_domain;
    State_addr     : State_domain;
    ZIP_addr       : ZIP_code_domain;
END customer_record;

END D_cIV;

WITH D_cIV;
USE D_cIV;
SCHEMA MODULE T1_III IS
--
-- Basic customer information
--
TABLE Customer IS
    Cust_Name      : Customer_name_domain,
    SSN not null   : SSN_domain ,
    Street_addr    : Addr_domain,
    City_addr      : City_domain,
    State_addr     : State_domain,
    ZIP_addr       : ZIP_code_domain
END Customer;
--
-- Savings account
--
TABLE Savings_account IS
    SBranch_number : Branch_number_domain,
    SAccount_number : Account_number_domain ,
    SBalance       : Balance_domain,
    SCustomer_SSN not null: SSN_domain
END ;
--
-- Checking account
--
TABLE Checking_account IS
    CBranch_number : Branch_number_domain,
    CAccount_number : Account_number_domain ,
    CBalance       : Balance_domain,
    CCustomer_SSN not null: SSN_domain
END Checking_account;
--
-- loan account
--
TABLE loan_account IS
    LBranch_number : Branch_number_domain,
    LAccount_number : Account_number_domain ,
    LBalance       : Balance_domain,
    LPayment not null: Loan_Payment_domain,
    LCustomer_SSN not null: SSN_domain
END loan_account;
--

```

```
-- Branch information
--
TABLE Branch_info IS
  Branch_name : Branch_name_domain ,
  Branch_number : Branch_number_domain ,
  Assets not null : Branch_assets_domain
END Branch_info;

END T1_III;

WITH D_cIV;
USE D_cIV;
ABSTRACT MODULE A_cIV IS
  AUTHORIZATION T1_III

  ENUMERATION Bool IS
    ( true,
      false);

  STATUS Stat_Map1 USES Bool IS
    (0 => true, 100 => false);

  STATUS Stat_Map2 NAMED Stat_Map2_Renamed USES Bool IS
    (0 => true, 100 => false);

--
-- procedures
--
--
--   commit statement
--
PROCEDURE Commit_work IS
  COMMIT WORK STATUS Stat_Map1;
--
--   delete statement
--
PROCEDURE Delete_customer_loan (loan_number_in :
Account_number_domain) IS
  DELETE FROM
    T1_III.Loan_account
  WHERE
    T1_III.Loan_account.LAccount_number = loan_number_in
  STATUS Stat_Map1 NAMED Stat_Map1_Renamed;

PROCEDURE Delete_customers IS
  DELETE FROM
    T1_III.customer
  STATUS Stat_Map2;
--
--   rollback statement
--
PROCEDURE rollback_work IS
  ROLLBACK WORK STATUS Stat_Map2 NAMED Standard_Map;
--
--   update statement
--
PROCEDURE Update_savings_account_balance
```

```

        (account_number_in NAMED acct : account_number_domain NOT
NULL;
        transaction      : balance_domain )
    IS
    UPDATE
        T1_III.savings_account
    SET
        T1_III.savings_account.Sbalance =
            T1_III.savings_account.Sbalance + transaction
    WHERE
        T1_III.savings_account.Saccount_number = account_number_in;

PROCEDURE Savings_and_loan_transaction IS
    UPDATE
        T1_III.loan_account
    SET
        T1_III.loan_account.Lbalance = 0.0;
--
-- insert statement (query)
--
PROCEDURE move_checking_to_savings
    (account_num_in : account_number_domain)
    IS
    INSERT INTO
        T1_III.savings_account
    SELECT *
    FROM
        T1_III.checking_account
    WHERE
        T1_III.checking_account.Caccount_number >= account_num_in;
--
-- insert statement (values)
--
PROCEDURE New_custpmer IS
    INSERT INTO
        T1_III.customer
    FROM
        New_customer_info : customer_record
    VALUES;
--
-- select statement
--
PROCEDURE Get_customer_profile (SSN_in : SSN_domain) IS
    SELECT *
    INTO
        Customer_Profile : customer_record
    FROM
        customer
    WHERE
        customer.SSN = SSN_in;

END A_cIV;

```

A.1.5 t1/cv.sme

```

-- *****
-- *** Test V
-- *****

```

```
DEFINITION MODULE D_cv IS
--
--   enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
--   domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 50);
  DOMAIN SSN_domain IS
    NEW SQL_CHAR NOT NULL (length => 9);
  DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN City_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
  DOMAIN Branch_name_domain IS
    NEW SQL_CHAR(length => 25);
--
--   domain integer declarations
--
  DOMAIN ZIP_code_domain IS
    NEW SQL_INT( FIRST => 0, LAST => 999999999);
  DOMAIN ZIP2_code_domain IS
    NEW SQL_INT NOT NULL;
  DOMAIN Account_number_domain IS
    NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
  DOMAIN Account2_number_domain IS
    NEW SQL_SMALLINT NOT NULL;
--
--   domain real declarations
--
  DOMAIN Balance_domain IS
    NEW SQL_REAL;
  DOMAIN Interest_rate_domain IS
    NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
  DOMAIN Loan_payment_domain IS
    NEW SQL_REAL NOT NULL;
  DOMAIN Branch_assets_domain IS
    NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--
--   domain enumeration declarations
--
  DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_CHAR
      (ENUMERATION => Loan_types, MAP => IMAGE);
```

```

DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
  (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
  (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street_Addr    : Addr_domain NOT NULL;
  City_Addr      : City_domain;
  State_addr     : State_domain;
  ZIP_addr       : ZIP_code_domain;
END customer_record;

END D_cV;

WITH D_cV AS Def_Mod;
USE Def_Mod;
SCHEMA MODULE T1_III IS
--
-- Basic customer information
--
TABLE Customer IS
  Cust_Name      : Def_Mod.Customer_name_domain,
  SSN not null   : SSN_domain ,
  Street_addr    : Addr_domain,
  City_addr      : addr_domain,
  State_addr     : State_domain,
  ZIP_addr       : ZIP_code_domain
END Customer;
--
-- Savings account
--
TABLE Savings_account IS
  SBranch_number : Branch_number_domain,
  SAccount_number : Account_number_domain ,
  SBalance       : Balance_domain,
  SCustomer_SSN not null : SSN_domain
END ;
--
-- Checking account
--
TABLE Checking_account IS
  CBranch_number : Branch_number_domain,
  CAccount_number : Account_number_domain ,
  CBalance       : Balance_domain,
  CCustomer_SSN not null : SSN_domain
END Checking_account;
--
-- loan account
--

```

```

TABLE loan_account IS
  LBranch_number      : Branch_number_domain,
  LAccount_number     : Account_number_domain ,
  LBalance            : Balance_domain,
  LPayment not null   : Loan_Payment_domain,
  LCustomer_SSN not null : SSN_domain
END loan_account;

--
-- Branch information
--
TABLE Branch_info IS
  Branch_name : Branch_name_domain ,
  Branch_number      : Branch_number_domain ,
  Assets not null    : Branch_assets_domain
END Branch_info;

END T1_III;

WITH D_cV AS Def_Mod;
USE Def_Mod;
ABSTRACT MODULE A_cV IS
  AUTHORIZATION T1_III
--
-- cursors
--
  CURSOR List_customers FOR
    SELECT *
    FROM
      T1_III.Customer
    ORDER BY
      T1_III.Customer.SSN ;

--
-- cursors with different predicates in the WHERE statement
--

--
-- compound comparison predicate =
--
  CURSOR customer_accounts(SSN_in : SSN_domain) FOR
    SELECT
      T1_III.customer.cust_name,
      T1_III.customer.street_addr,
      T1_III.customer.city_addr,
      T1_III.customer.state_addr,
      T1_III.customer.ZIP_addr,
      T1_III.savings_account.Saccount_number,
      T1_III.savings_account.Sbalance,
      T1_III.checking_account.Caccount_number,
      T1_III.checking_account.Cbalance
    FROM
      T1_III.Customer,
      T1_III.Savings_account,
      T1_III.Checking_account
    WHERE
      T1_III.customer.ssn = ssn_in          AND
      T1_III.savings_account.Scustomer_ssn = ssn_in AND
      T1_III.checking_account.Ccustomer_ssn = ssn_in ;

```

```
--
-- comparison predicate >=
--
CURSOR loans_over(loan_balance_in : balance_domain) FOR
SELECT
    T1_III.Loan_account.Laccount_number,
    T1_III.Loan_account.Lbranch_number,
    T1_III.Loan_account.Lcustomer_ssn,
    T1_III.Loan_account.Lbalance
FROM
    T1_III.Loan_account
WHERE
    T1_III.Loan_account.Lbalance >= loan_balance_in
;

--
-- comparison predicate <=
--
CURSOR loans_under(loan_balance_in : balance_domain) FOR
SELECT
    T1_III.Loan_account.Laccount_number,
    T1_III.Loan_account.Lbranch_number,
    T1_III.Loan_account.Lcustomer_ssn,
    T1_III.Loan_account.Lbalance
FROM
    T1_III.Loan_account
WHERE
    T1_III.Loan_account.Lbalance <= loan_balance_in
;

--
-- comparison predicate >
--
CURSOR checking_balance_over ( account_bal_in : Balance_domain ) FOR
SELECT
    T1_III.checking_account.Caccount_number,
    T1_III.checking_account.Ccustomer_ssn,
    T1_III.checking_account.Cbalance
FROM
    T1_III.checking_account
WHERE
    T1_III.checking_account.Cbalance > account_bal_in
;

--
-- comparison predicate <
--
CURSOR savings_balance_under ( account_bal_in : Balance_domain ) FOR
SELECT
    T1_III.savings_account.Saccount_number,
    T1_III.savings_account.Scustomer_ssn,
    T1_III.savings_account.Sbalance
FROM
    T1_III.savings_account
WHERE
    T1_III.savings_account.Sbalance < account_bal_in
;

--
```

```
--      comparison predicate <>
--
CURSOR other_branch_names ( branch_name_in : branch_name_domain) FOR
  SELECT
    T1_III.branch_info.branch_name
  FROM
    T1_III.branch_info
  WHERE
    T1_III.branch_info.branch_name <> branch_name_in
;

END A_cV;
```

A.1.6 t1/cvi.sme

```
-- *****
-- *** Test VI
-- *****

DEFINITION MODULE D_cVI IS
--
--      enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
--      domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 50);
  DOMAIN SSN_domain IS
    NEW SQL_CHAR NOT NULL (length => 9);
  DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN City_domain IS
    NEW SQL_CHAR(length => 25);
  DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
  DOMAIN Branch_name_domain IS
    NEW SQL_CHAR(length => 25);
--
--      domain integer declarations
--
  DOMAIN ZIP_code_domain IS
    NEW SQL_INT( FIRST => 0, LAST => 999999999);
  DOMAIN ZIP2_code_domain IS
    NEW SQL_INT NOT NULL;
  DOMAIN Account_number_domain IS
    NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
  DOMAIN Account2_number_domain IS
```

```

NEW SQL_SMALLINT NOT NULL;
--
-- domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL NOT NULL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--
-- domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
  (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
  (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street         : Addr_domain NOT NULL;
  City           : City_domain;
  State          : State_domain;
  ZIP            : ZIP_code_domain;
END customer_record;

END D_cVI;

WITH D_cVI;
USE D_cVI;
SCHEMA MODULE T1_III IS
--
-- Basic customer information
--
TABLE Customer IS
  Cust_Name      : Customer_name_domain,
  SSN not null   : SSN_domain ,
  Street_addr    : Addr_domain,
  City_addr      : addr_domain,
  State_addr     : State_domain,
  ZIP_addr       : ZIP_code_domain
END Customer;
--
-- Checking account
--

```

```

TABLE Checking_account IS
  CBranch_number      : Branch_number_domain,
  CAccount_number     : Account_number_domain ,
  CBalance            : Balance_domain,
  CCustomer_SSN not null : SSN_domain
END Checking_account;
--
-- loan account
--
TABLE loan_account IS
  LBranch_number      : Branch_number_domain,
  LAccount_number     : Account_number_domain ,
  LBalance            : Balance_domain,
  LPayment not null   : Loan_Payment_domain,
  LCustomer_SSN not null : SSN_domain
END loan_account;
--
-- Branch information
--
TABLE Branch_info IS
  Branch_name : Branch_name_domain ,
  Branch_number      : Branch_number_domain ,
  Assets not null    : Branch_assets_domain
END Branch_info;

END T1_III;

WITH D_cVI;
SCHEMA MODULE T1_III_2 IS
--
-- Savings account
--
TABLE Savings_account IS
  SBranch_number      : D_cVI.Branch_number_domain,
  SAccount_number     : D_cVI.Account_number_domain ,
  SBalance            : D_cVI.Balance_domain,
  SCustomer_SSN not null : D_cVI.SSN_domain
END ;
END T1_III_2;

WITH D_cVI;
WITH SCHEMA T1_III_2;
USE D_cVI;
ABSTRACT MODULE A_cVI IS
  AUTHORIZATION T1_III
--
-- cursors
--
--
-- between predicate
--
CURSOR large_deposits FOR
  SELECT *
  FROM    T1_III_2.savings_account
  WHERE   T1_III_2.savings_account.Sbalance

```

```

        BETWEEN AVG(T1_III_2.savings_account.Sbalance)
            AND MAX(T1_III_2.savings_account.Sbalance)
    ;
--
--    not between predicate
--
CURSOR large_loans FOR
    SELECT
        T1_III.loan_account.Laccount_number,
        T1_III.loan_account.Lcustomer_ssn,
        T1_III.loan_account.Lbalance
    FROM
        T1_III.loan_account
    WHERE
        T1_III.loan_account.Lbalance
            NOT BETWEEN AVG(T1_III.loan_account.Lbalance)
                AND MIN(T1_III.loan_account.Lbalance)
    ;
--
--    in predicate
--
CURSOR Loan_count ( Branch_in: branch_number_domain ) FOR
    SELECT
        *
    FROM
        T1_III.Loan_account
    WHERE
        T1_III.Loan_account.LBranch_number IN (Branch_in)
    ;
--
--    not in predicate
--
CURSOR customer_count FOR
    SELECT
        *
    FROM
        T1_III.customer
    WHERE
        T1_III.customer.ssn
            NOT IN (SELECT T1_III.loan_account.Lcustomer_ssn
                    FROM   T1_III.loan_account)
    ;
--
--    like predicate
--
CURSOR find_customer (name_in : customer_name_domain) FOR
    SELECT
        T1_III.customer.cust_name
    FROM
        T1_III.customer
    WHERE
        T1_III.customer.cust_name LIKE name_in
    ;
--
--    null predicate

```

```
--
CURSOR find_empty_account FOR
  SELECT
    T1_III.checking_account.Caccount_number,
    T1_III.checking_account.Ccustomer_SSN
  FROM
    T1_III.checking_account
  WHERE
    T1_III.checking_account.Cbalance IS NULL
;
--
-- exists predicate
--
CURSOR find_joint_accounts FOR
  SELECT
    T1_III_2.savings_account.Scustomer_ssn,
    T1_III_2.savings_account.Saccount_number,
    checking_account.Caccount_number
  FROM
    T1_III_2.savings_account, T1_III.checking_account
  WHERE
    EXISTS
      (SELECT *
       FROM
         T1_III_2.savings_account, T1_III.checking_account
        WHERE
          T1_III_2.savings_account.Scustomer_ssn =
            T1_III.checking_account.Ccustomer_ssn)
;
END A_cVI;
```

A.1.7 t1/cvii.sme

```
-- *****
-- *** Test VII
-- *****

DEFINITION MODULE D_cVII IS
--
-- enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
-- domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 50);
  DOMAIN SSN_domain IS
```

```

    NEW SQL_CHAR NOT NULL (length => 9);
DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 25);
DOMAIN City_domain IS
    NEW SQL_CHAR(length => 25);
DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
DOMAIN Branch_name_domain IS
    NEW SQL_CHAR(length => 25);
--
--    domain integer declarations
--
DOMAIN ZIP_code_domain IS
    NEW SQL_INT( FIRST => 0, LAST => 999999999);
DOMAIN ZIP2_code_domain IS
    NEW SQL_INT NOT NULL;
DOMAIN Account_number_domain IS
    NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
DOMAIN Account2_number_domain IS
    NEW SQL_SMALLINT NOT NULL;
--
--    domain real declarations
--
DOMAIN Balance_domain IS
    NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
    NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
    NEW SQL_REAL NOT NULL;
DOMAIN Branch_assets_domain IS
    NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--
--    domain enumeration declarations
--
DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_CHAR
    (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Loan2_type_domain IS
    NEW SQL_ENUMERATION_AS_CHAR NOT NULL
    (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
    NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
    NEW SQL_ENUMERATION_AS_INT NOT NULL
    (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record NAMED Cust_Rec_Renamed IS
    Cust_Name      : Customer_name_domain;
    SSN            : SSN_domain;
    Street         : Addr_domain NOT NULL;
    City           : City_domain;
    State          : State_domain;
    ZIP            : ZIP_code_domain;
END customer_record;

```

```
END D_cVII;

WITH D_cVII;
USE D_cVII;
SCHEMA MODULE T1_III IS
--
-- Basic customer information
--
TABLE Customer IS
    Cust_Name      : Customer_name_domain,
    SSN not null   : SSN_domain ,
    Street_addr    : Addr_domain,
    City_addr      : addr_domain,
    State_addr     : State_domain,
    ZIP_addr       : ZIP_code_domain
END Customer;
--
-- Savings account
--
TABLE Savings_account IS
    SBranch_number : Branch_number_domain,
    SAccount_number : Account_number_domain ,
    SBalance       : Balance_domain,
    SCustomer_SSN not null : SSN_domain
END ;
--
-- Checking account
--
TABLE Checking_account IS
    CBranch_number : Branch_number_domain,
    CAccount_number : Account_number_domain ,
    CBalance       : Balance_domain,
    CCustomer_SSN not null : SSN_domain
END Checking_account;
--
-- loan account
--
TABLE loan_account IS
    LBranch_number : Branch_number_domain,
    LAccount_number : Account_number_domain ,
    LBalance       : Balance_domain,
    LPayment not null : Loan_Payment_domain,
    LCustomer_SSN not null : SSN_domain
END loan_account;
--
-- Branch information
--
TABLE Branch_info IS
    Branch_name : Branch_name_domain ,
    Branch_number : Branch_number_domain ,
    Assets not null : Branch_assets_domain
END Branch_info;

END T1_III;

WITH D_cVII;
USE D_cVII;
ABSTRACT MODULE A_cVII IS
```

```

AUTHORIZATION T1_III
--
-- cursors
--
--
-- quantified predicate = ALL
--
CURSOR List_Bethesda_checking FOR
  SELECT *
  FROM
    T1_III.checking_account
  WHERE
    T1_III.checking_account.Cbranch_number = ALL
      -- (SELECT * -- GDT: Result expr can't be *
      (SELECT Cbranch_number
      FROM T1_III.checking_account
      WHERE T1_III.checking_account.Cbranch_number =
bethesda)
  ;
IS
  procedure Open_Cursor IS OPEN;
END List_Bethesda_checking;
--
-- quantified predicate <> ALL
--
CURSOR checking_only FOR
  SELECT
    T1_III.checking_account.Ccustomer_ssn
  FROM
    T1_III.checking_account
  WHERE
    T1_III.checking_account.Ccustomer_ssn
      <> ALL (SELECT T1_III.savings_account.Scustomer_ssn
      FROM T1_III.savings_account)
  ;
IS
  procedure Open_Curs IS OPEN checking_only;
END checking_only;
--
-- quantified predicate > ALL
--
CURSOR large_checking FOR
  SELECT *
  FROM
    T1_III.checking_account
  WHERE
    T1_III.checking_account.Cbalance >
      ALL (SELECT T1_III.savings_account.Sbalance
      FROM T1_III.savings_account)
  ;
--
-- quantified predicate < ALL
--
CURSOR small_checking FOR
  SELECT *
  FROM
    T1_III.checking_account

```

```

WHERE
    T1_III.checking_account.Cbalance <
        ALL (SELECT T1_III.savings_account.Sbalance
              FROM T1_III.savings_account)
;
--
-- quantified predicate >= ALL
--
CURSOR largest_savings FOR
    SELECT *
    FROM
        T1_III.savings_account
    WHERE
        T1_III.savings_account.Sbalance >=
            ALL (SELECT T1_III.savings_account.Sbalance
                  FROM T1_III.savings_account)
;
--
-- quantified predicate <= ALL
--
CURSOR smallest_savings FOR
    SELECT *
    FROM
        T1_III.savings_account
    WHERE
        T1_III.savings_account.Sbalance <=
            ALL (SELECT T1_III.savings_account.Sbalance
                  FROM T1_III.savings_account)
;
--
-- quantified predicate = ANY
--
CURSOR loan_and_save FOR
    SELECT
        T1_III.savings_account.Scustomer_ssn
    FROM
        T1_III.savings_account
    WHERE
        T1_III.savings_account.Scustomer_ssn = ANY
            (SELECT T1_III.loan_account.Lcustomer_ssn
              FROM T1_III.loan_account)
;
--
-- quantified predicate <= SOME
--
CURSOR all_checking FOR
    SELECT
        T1_III.checking_account.Ccustomer_ssn
    FROM
        T1_III.checking_account
    WHERE
        T1_III.checking_account.Cbalance <=
            SOME (SELECT T1_III.checking_account.Cbalance
                  FROM T1_III.checking_account)
;
END A_cVII;

```

A.1.8 tl/cviii.sme

```

-- *****
-- *** Test VIII
-- *****

DEFINITION MODULE D_cVIII IS
--
--     enumeration declarations
--
    ENUMERATION Branches IS
        ( Bethesda,
          Silver_Spring,
          Gaithersburg,
          Potomac);

    ENUMERATION Loan_types IS
        ( mortgage,
          auto,
          personal);
--
--     domain character declarations
--
    DOMAIN Customer_name_domain IS
        NEW SQL_CHAR(length => 50);
    DOMAIN SSN_domain IS
        NEW SQL_CHAR NOT NULL (length => 9);
    DOMAIN Addr_domain IS
        NEW SQL_CHAR(length => 25);
    DOMAIN City_domain IS
        NEW SQL_CHAR(length => 25);
    DOMAIN State_domain IS
        NEW SQL_CHAR(length => 2);
    DOMAIN Branch_name_domain IS
        NEW SQL_CHAR(length => 25);
--
--     domain integer declarations
--
    DOMAIN ZIP_code_domain IS
        NEW SQL_INT( FIRST => 0, LAST => 999999999);
    DOMAIN ZIP2_code_domain IS
        NEW SQL_INT NOT NULL;
    DOMAIN Account_number_domain IS
        NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
    DOMAIN Account2_number_domain IS
        NEW SQL_SMALLINT NOT NULL;
--
--     domain real declarations
--
    DOMAIN Balance_domain IS
        NEW SQL_REAL;
    DOMAIN Interest_rate_domain IS
        NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
    DOMAIN Loan_payment_domain IS
        NEW SQL_REAL NOT NULL;
    DOMAIN Branch_assets_domain IS
        NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--

```

```
--      domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
  (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
  (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record NAMED Cust_Rec IS
  Cust_Name      : Customer_name_domain;
  SSN             : SSN_domain;
  Street          : Addr_domain NOT NULL;
  City            : City_domain;
  State           : State_domain;
  ZIP             : ZIP_code_domain;
END customer_record;

END D_cVIII;

WITH D_cVIII;
USE D_cVIII;
SCHEMA MODULE T1_III IS
--
-- Basic customer information
--
TABLE Customer IS
  Cust_Name      : Customer_name_domain,
  SSN not null   : SSN_domain ,
  Street_addr    : Addr_domain,
  City_addr      : City_domain,
  State_addr     : State_domain,
  ZIP_addr       : ZIP_code_domain
END Customer;
--
-- Savings account
--
TABLE Savings_account IS
  SBranch_number : Branch_number_domain,
  SAccount_number : Account_number_domain ,
  SBalance       : Balance_domain,
  SCustomer_SSN not null : SSN_domain
END ;
--
-- Checking account
--
TABLE Checking_account IS
  CBranch_number : Branch_number_domain,
  CAccount_number : Account_number_domain ,
  CBalance       : Balance_domain,
```

```

        CCustomer_SSN not null : SSN_domain
    END Checking_account;

--
-- loan account
--
    TABLE loan_account IS
        LBranch_number : Branch_number_domain,
        LAccount_number : Account_number_domain ,
        LBalance : Balance_domain,
        LPayment not null : Loan_Payment_domain,
        LCustomer_SSN not null : SSN_domain
    END loan_account;

--
-- Branch information
--
    TABLE Branch_info IS
        Branch_name : Branch_name_domain ,
        Branch_number : Branch_number_domain ,
        Assets not null : Branch_assets_domain
    END Branch_info;

END T1_III;

WITH D_cVIII;
USE D_cVIII;
ABSTRACT MODULE A_cVIII IS
    AUTHORIZATION T1_III

--
-- cursors
--

--
-- cursor procs
--

    CURSOR customer_list FOR
        SELECT *
        FROM
            T1_III.customer
        ORDER BY
            T1_III.customer.ssn;
    IS
    PROCEDURE open_customer IS
        OPEN customer_list;

    PROCEDURE close_customer IS
        CLOSE customer_list;

    PROCEDURE fetch_customer IS
        FETCH customer_list INTO : new_customer_record;

    PROCEDURE update_customer( new_name : customer_name_domain ;
                                new_ssn : ssn_domain ;
                                new_street : addr_domain ;
                                new_city : city_domain ;
                                new_state : state_domain ;
                                new_zip : zip_code_domain) IS
        UPDATE T1_III.customer
        SET T1_III.customer.cust_name = new_name,

```

```

        T1_III.customer.ssn = new_ssn,
        T1_III.customer.street_addr = new_street,
        T1_III.customer.city_addr = new_city,
        T1_III.customer.state_addr = new_state,
        T1_III.customer.zip_addr = new_zip
    WHERE CURRENT OF customer_list;

PROCEDURE delete_customer IS
    DELETE FROM T1_III.customer;

END customer_list;

END A_cVIII;

```

A.1.9 t1/cix.sme

```

-- *****
-- *** Test IX
-- *****

DEFINITION MODULE D_cIX_1 IS
--
--     enumeration declarations
--
    ENUMERATION Branches IS
        ( Bethesda,
          Silver_Spring,
          Gaithersburg,
          Potomac);

    ENUMERATION Loan_types IS
        ( mortgage,
          auto,
          personal);
--
--     domain character declarations
--
    DOMAIN Customer_name_domain IS
        NEW SQL_CHAR(length => 50);
    DOMAIN SSN_domain IS
        NEW SQL_CHAR NOT NULL (length => 9);
    DOMAIN Addr_domain IS
        NEW SQL_CHAR(length => 25);
    DOMAIN City_domain IS
        NEW SQL_CHAR(length => 25);
    DOMAIN State_domain IS
        NEW SQL_CHAR(length => 2);
    DOMAIN Branch_name_domain IS
        NEW SQL_CHAR(length => 25);
END D_cIX_1;

with D_cIX_1; use D_cIX_1;
DEFINITION MODULE D_cIX_2 IS
--
--     domain integer declarations
--
    DOMAIN ZIP_code_domain IS
        NEW SQL_INT( FIRST => 0, LAST => 999999999);

```

```

DOMAIN ZIP2_code_domain IS
  NEW SQL_INT NOT NULL;
DOMAIN Account_number_domain IS
  NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
DOMAIN Account2_number_domain IS
  NEW SQL_SMALLINT NOT NULL;
--
-- domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL NOT NULL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--
-- domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
  (ENUMERATION => Branches, MAP => POS);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
  (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street         : Addr_domain;
  City           : City_domain;
  State          : State_domain;
  ZIP            : ZIP_code_domain;
END customer_record;

END D_cIX_2;

WITH D_cIX_1,D_cIX_2;
USE D_cIX_1,D_cIX_2;
SCHEMA MODULE S_cIX_1 IS
--
-- Basic customer information
--
TABLE Customer IS
  Cust_Name      : Customer_name_domain,
  SSN not null   : SSN_domain ,
  Street_addr    : Addr_domain,
  City_addr      : City_domain,
  State_addr     : State_domain,

```

```

        ZIP_addr      : ZIP_code_domain
    END Customer;
--
-- Savings account
--
    TABLE Savings_account IS
        SBranch_number : Branch_number_domain,
        SAccount_number : Account_number_domain ,
        SBalance        : Balance_domain,
        SCustomer_SSN not null : SSN_domain
    END ;
--
-- Checking account
--
    TABLE Checking_account IS
        CBranch_number : Branch_number_domain,
        CAccount_number : Account_number_domain ,
        CBalance        : Balance_domain,
        CCustomer_SSN not null : SSN_domain
    END Checking_account;

END S_cIX_1;

WITH D_cIX_1,D_cIX_2;
USE D_cIX_1,D_cIX_2;
SCHEMA MODULE S_cIX_2 IS
--
-- loan account
--
    TABLE loan_account IS
        LBranch_number : Branch_number_domain,
        LAccount_number : Account_number_domain ,
        LBalance        : Balance_domain,
        LPayment not null : Loan_Payment_domain,
        LCustomer_SSN not null : SSN_domain
    END loan_account;
--
-- Branch information
--
    TABLE Branch_info IS
        Branch_name : Branch_name_domain ,
        Branch_number : Branch_number_domain ,
        Assets not null : Branch_assets_domain
    END Branch_info;

END S_cIX_2;

WITH D_cIX_1,D_cIX_2;
USE D_cIX_1; USE D_cIX_2;
WITH SCHEMA S_cIX_2;
ABSTRACT MODULE A_cIX_1 IS
    AUTHORIZATION S_cIX_1
--
-- procedures
--
--
    commit statement
--

```

```

PROCEDURE Commit_work IS
    COMMIT WORK;
--
-- delete statement
--
PROCEDURE Delete_customer_loan (loan_number_in :
Account_number_domain) IS
    DELETE FROM
        S_cIX_2.Loan_account
    WHERE
        S_cIX_2.Loan_account.Laccount_number = loan_number_in;

PROCEDURE Delete_customers IS
    DELETE FROM
        S_cIX_1.Customer;
--
-- rollback statement
--
PROCEDURE rollback_work IS
    ROLLBACK WORK;
--
-- update statement
--
PROCEDURE Update_savings_account_balance
    (account_number_in : account_number_domain;
    transaction         : balance_domain )
    IS
    UPDATE
        S_cIX_1.Savings_account
    SET
        S_cIX_1.Savings_account.Sbalance
        = S_cIX_1.Savings_account.Sbalance + transaction
    WHERE
        S_cIX_1.Savings_account.Saccount_number = account_number_in;
END A_cIX_1;

WITH D_cIX_1,D_cIX_2;
USE D_cIX_1;
USE D_cIX_2;
WITH SCHEMA S_cIX_1;
ABSTRACT MODULE A_cIX_2 IS
    AUTHORIZATION S_cIX_2

    PROCEDURE Savings_and_loan_transaction IS
        UPDATE
            S_cIX_2.loan_account
        SET
            S_cIX_2.loan_account.Lbalance = 0.0;
--
-- insert statement (query)
--
PROCEDURE move_checking_to_savings
    (account_num_in : account_number_domain)
    IS
    INSERT INTO
        S_cIX_1.savings_account
    SELECT *
    FROM

```

```
        S_cIX_1.checking_account
WHERE
        S_cIX_1.checking_account.Caccount_number >= account_num_in;
--
--      insert statement (values)
--
PROCEDURE New_customer IS
  INSERT INTO
        S_cIX_1.Customer
  FROM
        New_customer_info : new cust_record
  VALUES;
--
--      select statement
--
PROCEDURE Get_customer_profile (SSN_in : SSN_domain) IS
  SELECT *
  INTO
        Customer_Profile : customer_record
  FROM
        S_cIX_1.Customer
  WHERE
        S_cIX_1.Customer.SSN = SSN_in;

END A_cIX_2;
```

A.1.10 tl/ctl.sme

```
definition module d_ctl is
  -- Member Information
  domain MemName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
        MAP => POS, ENUMERATION => SexEnum);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;
  domain Sum_Domain is new SQL_SMALLINT Not Null;
  domain Count_Domain is new SQL_INT;

end d_ctl;

with d_ctl; use d_ctl;
schema module s_recdb is
  table Members is
    MemberName not null      : MemName,
    MemberSSN not null       : SSN,
    ClubNumber not null      : Club_Number,
```

```

        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null : County
    end Members;

end s_recdb;

with d_ctl; use d_ctl;
abstract module a_ctl is
    authorization s_recdb

    record MemberRec is
        R_MemberName    : MemName;
        R_Sum           : Sum_Domain;
        R_Count         : Count_Domain;
    end;

    procedure P_MemberSelect (Req_MemberSSN : SSN) is
        select MemberName, SUM(MemberAge), COUNT(*)
        into Row : MemberRec
        from s_recdb.Members
        where s_recdb.Members.MemberSSN = Req_MemberSSN ;

    procedure MP_MemberSelect (Req_MemberSSN : SSN) is
        select MemberName, Sum_Domain(SUM(MemberAge)),
        Count_Domain(COUNT(*))
        into Row : MemberRec
        from s_recdb.Members
        where s_recdb.Members.MemberSSN = Req_MemberSSN ;

    procedure MPD_MemberSelect (Req_MemberSSN : SSN) is
        select MemberName, Sum_Domain(SUM(MemberAge)) named foo,
        Count_Domain(COUNT(*)) named ct
        from s_recdb.Members
        where s_recdb.Members.MemberSSN = Req_MemberSSN ;

    cursor M_MemberSelect (Req_MemberSSN : SSN) for
        select MemberName, Sum_Domain(SUM(MemberAge)) named foo,
        Count_Domain(COUNT(*)) named ct
        from s_recdb.Members
        where s_recdb.Members.MemberSSN = Req_MemberSSN ;
    is
        procedure FetchIt is
            fetch into Row : new MemRec;
        end M_MemberSelect;

    cursor MD_MemberSelect (Req_MemberSSN : SSN) for
        select MemberName, Sum_Domain(SUM(MemberAge)) named foo,
        Count_Domain(COUNT(*)) named ct
        from s_recdb.Members
        where s_recdb.Members.MemberSSN = Req_MemberSSN ;
    is
        procedure FetchIt is
            fetch;

```

```
end MD_MemberSelect;

end a_ct1;
```

A.1.11 t1/ct2.sme

```
-- This test is the simple demo (input.sme)

definition module d_ct2 is
  -- Member Information
  domain MemName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    MAP => POS, ENUMERATION => SexEnum);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;
end d_ct2;

with d_ct2; use d_ct2;
schema module s_ct2 is
  table Members is
    MemberName not null : MemName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
  end Members;
end s_ct2;

with d_ct2; use d_ct2;
abstract module a_ct2 is
  authorization s_ct2

  record MemberRec is
    MemberName : MemName;
    MemberSSN : SSN;
    ClubNumber : Club_Number;
    MemberAge : Age;
    MemberSex : Sex;
    MemberPhone : Phone;
    MemberStreet : Street;
```

```

        MemberCity    : City;
        MemberCnty    : County;
    end;

    procedure CommitWork is
        commit work;

    procedure MemberInsert is
        insert into s_ct2.Members
        from Row : MemberRec
        values;

    cursor MemberSelect (Req_MemberSSN : SSN) for
        select *
        from s_ct2.Members
        where s_ct2.Members.MemberSSN = Req_MemberSSN ;
    is
        procedure FetchIt is
            fetch into Row : new MemRec;

        end MemberSelect;

    end a_ct2;

```

A.1.12 t1/ct3.sme

```

-- The big demo test (T2)

DEFINITION MODULE d_ct3 IS
--
--     enumeration declarations
--
    ENUMERATION Branches IS
        ( Bethesda,
          Silver_Spring,
          Gaithersburg,
          Potomac);

    ENUMERATION Loan_types IS
        ( mortgage,
          auto,
          personal);

--
--     domain character declarations
--
    DOMAIN Customer_name_domain IS
        NEW SQL_CHAR(length => 15);
    DOMAIN Addr_domain IS
        NEW SQL_CHAR(length => 15);
    DOMAIN City_domain IS
        NEW SQL_CHAR(length => 15);
    DOMAIN State_domain IS
        NEW SQL_CHAR(length => 2);

--
--     domain integer declarations
--
    DOMAIN SSN_domain IS
        NEW SQL_INT NOT NULL ( FIRST => 0, LAST => 999999999);

```

```
DOMAIN acct_num_domain IS
  NEW SQL_SMALLINT NOT NULL ( FIRST => 0, LAST => 9999);
--
-- domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL;
```

```
--
--      domain enumeration declarations
--
:      DOMAIN Loan_type_domain IS
:      NEW SQL_ENUMERATION_AS_int
:      (MAP => POS, ENUMERATION => Loan_types);
:
:      DOMAIN branch_num_domain IS
:      NEW SQL_ENUMERATION_AS_INT
:      (MAP => POS, ENUMERATION => Branches);
--
-- record definitions
--
      RECORD Customer_record IS
      Cust_Name      : Customer_name_domain;
      SSN            : SSN_domain;
      Street         : Addr_domain;
      City           : City_domain;
      State          : State_domain;
      END customer_record;

      RECORD Savings_entry IS
      branch_num      : branch_num_domain;
      acct_num        : acct_num_domain;
      Balance         : Balance_domain;
      cust_ssn        : SSN_domain;
      END Savings_entry;

      RECORD Chequeing_entry IS
      branch_num      : branch_num_domain;
      acct_num        : acct_num_domain;
      Balance         : Balance_domain;
      cust_ssn        : SSN_domain;
      END Chequeing_entry;

      RECORD loan_entry IS
      branch_num      : branch_num_domain;
      acct_num        : acct_num_domain;
      Balance         : Balance_domain;
      Loan_type       : Loan_type_domain;
      cust_ssn        : SSN_domain;
      END loan_entry;

      RECORD Branch_entry IS
      branch_num      : branch_num_domain ;
      Assets          : Branch_assets_domain;
      END Branch_entry;

END d_ct3;
```

```
WITH d_ct3;
USE d_ct3;
SCHEMA MODULE s_ct3 IS
--
-- Basic customer information
--
TABLE Cust IS
    Cust_Name : Customer_name_domain,
    SSN not null : SSN_domain,
    Street_addr : Addr_domain,
    City_addr : City_domain,
    State_addr : State_domain
END cust;
--
-- Checking account
--
TABLE cheque IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance : Balance_domain,
    cust_ssn not null : SSN_domain
END cheque;
--
-- Savings account
--
TABLE Save IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance : Balance_domain,
    cust_ssn not null : SSN_domain
END Save;
--
-- loan account
--
TABLE loan IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance : Balance_domain,
    Loan_type : loan_type_domain,
    cust_ssn not null : SSN_domain
END loan;
--
-- Branch information
--
TABLE Branch IS
    num : branch_num_domain ,
    Assets : Branch_assets_domain
END Branch;

END s_ct3;
```

```

WITH d_ct3;
USE d_ct3;
ABSTRACT MODULE a_ct3 IS
    AUTHORIZATION s_ct3
--
-- procedures
--
--    commit statement
--
PROCEDURE Commit_work IS
    COMMIT WORK;
--
--    delete statement
--
PROCEDURE Delete_customer_loan
    (loan_number_in : acct_num_domain) IS
    DELETE FROM
        s_ct3.Loan
    WHERE
        s_ct3.Loan.acct_num = loan_number_in;
--
--    rollback statement
--
PROCEDURE rollback_work IS
    ROLLBACK WORK;
--
--    update statement
--
PROCEDURE Up_save_acct_bal
    (acct_num_in : acct_num_domain;
     transaction   : balance_domain )
    IS
    UPDATE
        s_ct3.save
    SET
        s_ct3.save.balance =
            s_ct3.save.balance + transaction
    WHERE
        s_ct3.save.acct_num = acct_num_in;

PROCEDURE S_and_L IS
    UPDATE
        s_ct3.Loan
    SET
        s_ct3.Loan.balance = 0.0;
--
--    insert statement (query)
--
PROCEDURE move_cheque_to_save
    (account_num_in : acct_num_domain)
    IS
    INSERT INTO
        s_ct3.save
    SELECT *
    FROM

```

```
      s_ct3.cheque  
WHERE  s_ct3.cheque.acct_num >= account_num_in;
```

```
--
--      insert statement (values)
--
--
--      select statement
--
--
PROCEDURE Get_cust_profile (SSN_in : SSN_domain) IS
  SELECT *
  INTO
    Customer_Profile : customer_record
  FROM
    s_ct3.cust
  WHERE
    s_ct3.cust.SSN = SSN_in;
--
--      insert statement (values)
--
--
--      select statement
--
PROCEDURE Get_save_record
  (acct_num_in : acct_num_domain) IS
  SELECT *
  INTO
    savings_record : savings_entry
  FROM
    s_ct3.save
  WHERE
    s_ct3.save.acct_num =
      acct_num_in;
--
-- cursors
--
--
-- cursors with different predicates in the WHERE statement
--
--
-- comparison predicate =
--
CURSOR customer_accounts(SSN_in : SSN_domain) FOR
  SELECT
    s_ct3.save.cust_ssn,
    s_ct3.save.acct_num,
    s_ct3.save.balance
  FROM
    s_ct3.save
  WHERE
    s_ct3.save.cust_ssn = ssn_in
;
```

```
--
--      comparison predicate >=
--
CURSOR loans_over(loan_balance_in : balance_domain) FOR
  SELECT
    s_ct3.Loan.acct_num,
    s_ct3.Loan.branch_num,
    s_ct3.Loan.cust_ssn,
    s_ct3.Loan.balance
  FROM
    s_ct3.Loan
  WHERE
    s_ct3.Loan.balance >= loan_balance_in
;

--
--      comparison predicate <=
--
CURSOR loans_under(loan_balance_in : balance_domain) FOR
  SELECT
    s_ct3.Loan.acct_num,
    s_ct3.Loan.branch_num,
    s_ct3.Loan.cust_ssn,
    s_ct3.Loan.balance
  FROM
    s_ct3.Loan
  WHERE
    s_ct3.Loan.balance <= loan_balance_in
;

--
--      comparison predicate >
--
CURSOR cheque_bal_over ( account_bal_in : Balance_domain ) FOR
  SELECT
    s_ct3.cheque.acct_num,
    s_ct3.cheque.balance
  FROM
    s_ct3.cheque
  WHERE
    s_ct3.cheque.balance > account_bal_in
;

--
--      comparison predicate <
--
CURSOR save_bal_under ( account_bal_in : Balance_domain ) FOR
  SELECT
    s_ct3.save.acct_num,
    s_ct3.save.balance
  FROM
    s_ct3.save
  WHERE
    s_ct3.save.balance < account_bal_in
;
```

```

--      comparison predicate <>
--
--      CURSOR other_branches
--          ( branch_num_in : branch_num_domain ) FOR
--          SELECT
--              s_ct3.Branch.num
--          FROM
--              s_ct3.Branch
--          WHERE
--              s_ct3.Branch.num <> branch_num_in
--      ;
--
--      between predicate
--
--      CURSOR large_deposits
--          ( lower_bound : balance_domain; upper_bound :balance_domain) FOR
--          SELECT *
--          FROM
--              s_ct3.save
--          WHERE
--              s_ct3.save.balance
--                  BETWEEN lower_bound
--                  AND upper_bound
--      ;
--
--      not between predicate
--
--      CURSOR large_loans
--          ( lower_bound : balance_domain; upper_bound :balance_domain) FOR
--          SELECT
--              s_ct3.Loan.acct_num,
--              s_ct3.Loan.balance,
--              s_ct3.Loan.cust_ssn
--          FROM
--              s_ct3.Loan
--          WHERE
--              s_ct3.Loan.balance NOT BETWEEN lower_bound AND upper_bound
--      ;

```

```
--
--   like predicate
--
CURSOR find_customer (name_in : customer_name_domain) FOR
  SELECT
    s_ct3.cust.cust_name
  FROM
    s_ct3.cust
  WHERE
    s_ct3.cust.cust_name LIKE name_in
;

--
--   in predicate
--
CURSOR Loan_count ( Branch_in: branch_num_domain ) FOR
  SELECT
    *
  FROM
    s_ct3.Loan
  WHERE
    s_ct3.Loan.Branch_num IN (Branch_in)
;

--
--   cursor procs
--
CURSOR customer_list FOR
  SELECT *
  FROM
    s_ct3.cust
;
IS
PROCEDURE open_customer IS
  OPEN customer_list;

PROCEDURE close_customer IS
  CLOSE customer_list;

PROCEDURE fetch_customer IS
  FETCH customer_list INTO next_customer : new c_record;

PROCEDURE update_customer (new_street : Addr_domain) IS
  UPDATE    s_ct3.cust
  SET      s_ct3.cust.street_addr = new_street
  WHERE CURRENT OF customer_list;

PROCEDURE delete_customer IS
  DELETE FROM s_ct3.cust;

END customer_list;
```

```
--  
--      procedures and cursors used to initialize the database and  
--      verify the contents of tables after test transactions  
--
```

```
PROCEDURE New_customer IS  
  INSERT INTO  
    s_ct3.cust  
  FROM  
    New_customer_info : new cust_record  
  VALUES;
```

```
PROCEDURE New_chequeing IS  
  INSERT INTO  
    s_ct3.cheque  
  FROM  
    New_chequeing_info : chequeing_entry  
  VALUES;
```

```
PROCEDURE New_savings IS  
  INSERT INTO  
    s_ct3.save  
  FROM  
    New_savings_info : savings_entry  
  VALUES;
```

```
PROCEDURE New_loan IS  
  INSERT INTO  
    s_ct3.Loan  
  FROM  
    New_loan_info : loan_entry  
  VALUES;
```

```
PROCEDURE New_branch IS  
  INSERT INTO  
    s_ct3.Branch  
  FROM  
    New_branch_info : new b_entry  
  VALUES;
```

```
PROCEDURE Delete_customers IS  
  DELETE FROM  
    s_ct3.cust;
```

```
PROCEDURE Delete_chequeing IS  
  DELETE FROM  
    s_ct3.cheque;
```

```
PROCEDURE Delete_savings IS  
  DELETE FROM  
    s_ct3.save;
```

```
PROCEDURE Delete_loans IS  
  DELETE FROM  
    s_ct3.Loan;
```

```
PROCEDURE Delete_Branches IS
```

```
DELETE FROM  
  s_ct3.Branch;
```

```

CURSOR List_customers FOR
  SELECT *
  FROM
    s_ct3.cust
  ORDER BY
    s_ct3.cust.SSN
;

CURSOR List_chequeing FOR
  SELECT *
  FROM
    s_ct3.cheque
  ORDER BY
    s_ct3.cheque.acct_num
;

CURSOR List_savings FOR
  SELECT *
  FROM
    s_ct3.save
  ORDER BY
    s_ct3.save.acct_num
;

CURSOR List_loans FOR
  SELECT *
  FROM
    s_ct3.Loan
  ORDER BY
    s_ct3.Loan.acct_num
;

CURSOR List_branches FOR
  SELECT *
  FROM
    s_ct3.Branch
  ORDER BY
    s_ct3.Branch.num
;

END a_ct3;

```

A.1.13 t1/ct4.sme

```

-- Test named as phrases on status declarations
-- Test generation of status code and param names

definition module d_ct4 is
  domain MemName is new SQL_CHAR Not Null (Length => 30);

  enumeration SQL_Code_Enum is (Ok, Bad, WhoKnows);
  status SQL_Status1 uses SQL_Code_Enum is (
    0 => ok,
    1 => bad,
    3 => WhoKnows);

  status SQL_Status2 named Status2 uses SQL_Code_Enum is (

```

```
0 => ok,
1 => bad,
3 => WhoKnows);

end d_ct4;

with d_ct4; use d_ct4;
schema module s_ct4 is
    table Members is
        MemberName not null    : MemName
    end Members;
end s_ct4;

with d_ct4; use d_ct4;
abstract module a_ct4 is
    authorization s_ct4

    procedure CommitWork1_1 is
        commit work
        status SQL_Status1;

    procedure CommitWork1_2 is
        commit work
        status SQL_Status1 named CW1_2;

    procedure CommitWork2_1 is
        commit work
        status SQL_Status2;

    procedure CommitWork2_2 is
        commit work
        status SQL_Status2 named CW2_2;

end a_ct4;
```

A.1.14 t1/ct5.sme

```
-- Tests AS PHRASES on context clauses

definition module d_ct5 is
    -- Member Information
    domain MemName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        MAP => POS, ENUMERATION => SexEnum);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;
```

```

end d_ct5;

with d_ct5 as SM;
use SM;
definition module d_ct5_2 is
    constant C_Name : SM.MemName is '123456789012345678901234567890';
    constant C_SSN : SM.SSN is '123456789';
    constant C_Club_Number : SM.Club_Number is 10;
    constant C_Age : SM.Age is 39;
    constant C_Sex : SM.Sex is SM.F;
    constant C_Phone : SM.Phone is '12345678';
    constant C_Street : SM.Street is '123456789012345678901234567890';
    constant C_City : SM.City is '123456789012345';
    constant C_County : SM.County is 'MO';
end d_ct5_2;

```

```

with d_ct5 as SM;
use SM;
schema module s_ct5 is
    table Members is
        MemberName not null : MemName,
        MemberSSN not null : SSN,
        ClubNumber not null : Club_Number,
        MemberAge : Age,
        MemberSex : Sex,
        MemberPhone : Phone,
        MemberStreet : Street,
        MemberCity : City,
        MemberCnty not null : County
    end Members;

    table Members2 is
        MemberName2 not null : SM.MemName,
        MemberSSN2 not null : SM.SSN,
        ClubNumber2 not null : SM.Club_Number,
        MemberAge2 : SM.Age,
        MemberSex2 : SM.Sex,
        MemberPhone2 : SM.Phone,
        MemberStreet2 : SM.Street,
        MemberCity2 : SM.City,
        MemberCnty2 not null : SM.County
    end Members2;

```

```

end s_ct5;

```

```

with d_ct5 as SM;
use SM;
schema module Qs_ct5 is
    table QMembers is
        QMemberName not null : MemName,
        QMemberSSN not null : SSN,
        QClubNumber not null : Club_Number,
        QMemberAge : Age,
        QMemberSex : Sex,
        QMemberPhone : Phone,
        QMemberStreet : Street,

```

```
        QMemberCity      : City,
        QMemberCnty not null : County
    end QMembers;

end Qs_ct5;

with d_ct5; use d_ct5;
with schema Qs_ct5 as QQ;
abstract module a_ct5 is
    authorization s_ct5

    procedure CommitWork1_1 is
        commit work;

    procedure MemberInsert is
        insert into QQ.QMembers
        values;

end a_ct5;
```

A.1.15 **t1/ct6.sme**

```
DEFINITION MODULE D_ct6 IS
    DOMAIN Character_set_domain IS
        NEW SQL_CHAR(length => 43);
    DOMAIN integer_domain IS
        NEW SQL_INT;
    DOMAIN sm_integer_domain IS
        NEW SQL_SMALLINT;
    DOMAIN real_domain IS
        NEW SQL_REAL;

    ENUMERATION Loan_types IS
        ( mortgage,
          auto,
          personal);
    DOMAIN Loan_type_domain IS
        NEW SQL_ENUMERATION_AS_CHAR
        (ENUMERATION => Loan_types, map => image);

    CONSTANT personal_loan : loan_type_domain
        IS      personal ;

    CONSTANT one IS 1;
    CONSTANT Domc_one IS integer_domain(one);
    CONSTANT one_dot_zero IS 1.0;
    CONSTANT one_float IS 10.0E-1;

    CONSTANT D_one : sm_integer_domain IS 1;
    CONSTANT D_Domc_one : integer_domain IS integer_domain(one);
    CONSTANT D_one_dot_zero : real_domain IS 1.0;
    CONSTANT D_one_float : real_domain IS 10.0E-1;

    CONSTANT u1 IS -1;
    CONSTANT u2 IS +1;
    CONSTANT u3 IS -1.0;
    CONSTANT u4 IS +1.0;
```

```

CONSTANT u5 IS -1.0E+00;
CONSTANT u6 IS +1.0E-00;

CONSTANT p1 IS (-1);
CONSTANT p2 IS (+1);
CONSTANT p3 : real_domain IS (-1.0);
CONSTANT p4 IS (+1.0);
CONSTANT p5 IS (-1.0E+00);
CONSTANT p6 : real_domain IS (+1.0E-00);

CONSTANT a1 IS 1+(-1);
CONSTANT a2 IS p1+(+1);
CONSTANT a3 IS 1.0E0+(-1.0);
CONSTANT a4 IS p3+(+1.0);
CONSTANT a5 IS 1.0+(-1.0E+00);
CONSTANT a6 IS p5+(+1.0E-00);
CONSTANT a7 IS real_domain(1.0) + real_domain((-1));
--##
CONSTANT a8 IS p6 + real_domain((+1));
CONSTANT a9 IS real_domain(1.0E0) + real_domain((-1));
CONSTANT a0 IS real_domain(p3) + real_domain((+1));

CONSTANT s1 IS 1-(-1);
CONSTANT s2 IS p1-(-1);
CONSTANT s3 IS 1.0E0-(-1.0);
CONSTANT s4 IS p3-(-1.0);
CONSTANT s5 IS 1.0-(-1.0E+00);
CONSTANT s6 IS p5-(-1.0E-00);
CONSTANT s7 IS real_domain(1.0) - real_domain((-1));
CONSTANT s8 IS -p6 - real_domain((+1));
CONSTANT s9 IS real_domain(1.0E0) - real_domain((-1));
CONSTANT s0 IS real_domain(p3) - real_domain((+1));

CONSTANT m1 IS (4 - (-6))*(+5 + 5);
CONSTANT d1 IS (4 - (-6))/(+5 + 5);
CONSTANT m2 IS (4.0 - (-6.0))*(+5 + 5);
CONSTANT d2 IS (4.0 - (-6.0))/(+5 + 5);
CONSTANT m3 IS (4 - (-6))*(+5.0 + 5.0);
CONSTANT d3 IS real_domain(4 - (-6))/real_domain(+5.0 + 5.0);
CONSTANT m4 IS (4.0 - (-6.0))*(+5.0 + 5.0);
CONSTANT d4 IS (4.0 - (-6.0))/(+5.0 + 5.0);
CONSTANT m5 IS (4.0E0 - (-6.0))*(+5.0E0 + 5.0);
CONSTANT d5 IS (4.0 - (-6.0E0))/(+5.0 + 5.0E0);
CONSTANT m6 IS (4.0 - (-6.0))*(+5.0E0 + 5.0);
CONSTANT d6 IS (4.0 - (-6.0))/(+5.0 + 5.0E0);
CONSTANT m7 IS (4.0E0 - (-6.0))*(+5.0 + 5.0);
CONSTANT d7 IS (4.0 - (-6.0E0))/(+5.0 + 5.0);

END D_ct6;

```

A.1.16 t1/ct7.sme

```

DEFINITION MODULE D_ct7 IS
--
--   enumeration declarations
--
ENUMERATION Branches IS
    ( Bethesda,

```

```
        Silver_Spring,
        Gaithersburg,
        Potomac);

ENUMERATION Loan_types IS
( mortgage,
  auto,
  personal);

--
--      domain character declarations
--
DOMAIN Customer_name_domain IS
  NEW SQL_CHAR(length => 50);
DOMAIN SSN_domain IS
  NEW SQL_CHAR NOT NULL (length => 9);
DOMAIN Addr_domain IS
  NEW SQL_CHAR(length => 25);
DOMAIN City_domain IS
  NEW SQL_CHAR(length => 25);
DOMAIN State_domain IS
  NEW SQL_CHAR(length => 2);
DOMAIN Branch_name_domain IS
  NEW SQL_CHAR(length => 25);
END D_ct7;
```

A.1.17 t1/ct8.sme

```
--!reference d_ct7
with D_ct7; use D_ct7;
DEFINITION MODULE D_ct8 IS
--
--      domain integer declarations
--
DOMAIN ZIP_code_domain IS
  NEW SQL_INT( FIRST => 0, LAST => 999999999);
DOMAIN ZIP2_code_domain IS
  NEW SQL_INT NOT NULL;
DOMAIN Account_number_domain IS
  NEW SQL_SMALLINT( FIRST => 0, LAST => 9999);
DOMAIN Account2_number_domain IS
  NEW SQL_SMALLINT NOT NULL;
--
--      domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL NOT NULL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL NOT NULL ( FIRST => 0.0, LAST => 1.0E+10);
--
--      domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR
    (ENUMERATION => Loan_types, MAP => IMAGE);
```

```

DOMAIN Loan2_type_domain IS
  NEW SQL_ENUMERATION_AS_CHAR NOT NULL
  (ENUMERATION => Loan_types, MAP => IMAGE);
DOMAIN Branch_number_domain IS
  NEW SQL_ENUMERATION_AS_INT
  (MAP => POS, ENUMERATION => Branches);
DOMAIN Branch2_number_domain IS
  NEW SQL_ENUMERATION_AS_INT NOT NULL
  (MAP => POS, ENUMERATION => Branches);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain NOT NULL;
  Street         : Addr_domain;
  City           : City_domain;
  State          : State_domain;
  ZIP            : ZIP_code_domain;
END customer_record;

END D_ct8;

```

A.1.18 t1/ct9.sme

```

--!reference d_ct7
--!reference d_ct8
WITH D_ct7,D_ct8;
USE D_ct7,D_ct8;
SCHEMA MODULE S_ct9 IS
--
-- Basic customer information
--
TABLE Customer IS
  Cust_Name      : Customer_name_domain,
  SSN not null   : SSN_domain ,
  Street_addr    : Addr_domain,
  City_addr      : City_domain,
  State_addr     : State_domain,
  ZIP_addr       : ZIP_code_domain
END Customer;
--
-- Savings account
--
TABLE Savings_account IS
  SBranch_number : Branch_number_domain,
  SAccount_number : Account_number_domain ,
  SBalance       : Balance_domain,
  SCustomer_SSN not null : SSN_domain
END ;
--
-- Checking account
--
TABLE Checking_account IS
  CBranch_number : Branch_number_domain,
  CAccount_number : Account_number_domain ,
  CBalance       : Balance_domain,
  CCustomer_SSN not null : SSN_domain

```

END Checking_account;

END S_ct9;

A.1.19 t1/ct10.sme

```
--!reference s_ct9
WITH D_ct7,D_ct8;
USE D_ct7,D_ct8;
SCHEMA MODULE S_ct10 IS
--
-- loan account
--
TABLE loan_account IS
  LBranch_number : Branch_number_domain,
  LAccount_number : Account_number_domain ,
  LBalance : Balance_domain,
  LPayment not null : Loan_Payment_domain,
  LCustomer_SSN not null : SSN_domain
END loan_account;
--
-- Branch information
--
TABLE Branch_info IS
  Branch_name : Branch_name_domain ,
  Branch_number : Branch_number_domain ,
  Assets not null : Branch_assets_domain
END Branch_info;

END S_ct10;
```

A.1.20 t1/ct11.sme

```
--!reference s_ct10
WITH D_ct7,D_ct8;
USE D_ct7; USE D_ct8;
WITH SCHEMA S_ct10;
ABSTRACT MODULE A_ct11 IS
  AUTHORIZATION S_ct9
--
-- procedures
--
-- commit statement
--
PROCEDURE Commit_work IS
  COMMIT WORK;
--
-- delete statement
--
PROCEDURE Delete_customer_loan (loan_number_in :
Account_number_domain) IS
  DELETE FROM
    S_ct10.Loan_account
  WHERE
    S_ct10.Loan_account.Laccount_number = loan_number_in;

PROCEDURE Delete_customers IS
```

```

        DELETE FROM
            S_ct9.Customer;
--
--      rollback statement
--
PROCEDURE rollback_work IS
    ROLLBACK WORK;
--
--      update statement
--
PROCEDURE Update_savings_account_balance
    (account_number_in : account_number_domain;
      transaction       : balance_domain )
IS
    UPDATE
        S_ct9.Savings_account
    SET
        S_ct9.Savings_account.Sbalance
        = S_ct9.Savings_account.Sbalance + transaction
    WHERE
        S_ct9.Savings_account.Saccount_number = account_number_in;
END A_ct11;

```

A.1.21 t1/ct12.sme

```

--!reference a_ct11
WITH D_ct7,D_ct8;
USE D_ct7;
USE D_ct8;
WITH SCHEMA S_ct9;
ABSTRACT MODULE A_ct12 IS
    AUTHORIZATION S_ct10

    PROCEDURE Savings_and_loan_transaction IS
        UPDATE
            S_ct10.loan_account
        SET
            S_ct10.loan_account.Lbalance = 0.0;
--
--      insert statement (query)
--
PROCEDURE move_checking_to_savings
    (account_num_in : account_number_domain)
IS
    INSERT INTO
        S_ct9.savings_account
    SELECT *
    FROM
        S_ct9.checking_account
    WHERE
        S_ct9.checking_account.Caccount_number >= account_num_in;
--
--      insert statement (values)
--
PROCEDURE New_customer IS
    INSERT INTO
        S_ct9.Customer
    FROM

```

```
        New_customer_info : new c_rec
VALUES;
--
--  select statement
--
PROCEDURE Get_customer_profile (SSN_in : SSN_domain) IS
  SELECT *
  INTO
    Customer_Profile : customer_record
  FROM
    S_ct9.Customer
  WHERE
    S_ct9.Customer.SSN = SSN_in;

END A_ct12;
```

A.1.22 t1/ct13.sme

```
definition module D_ct13 is
  -- Member Information
  domain MemName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    MAP => POS, ENUMERATION => SexEnum);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;
  domain Sum_Domain is new SQL_SMALLINT Not Null;
  domain Count_Domain is new SQL_INT;

end D_ct13;

with D_ct13; use D_ct13;
schema module RecDB is
  table Members is
    MemberName not null    : MemName,
    MemberSSN not null     : SSN,
    ClubNumber not null    : Club_Number,
    MemberAge      : Age,
    MemberSex      : Sex,
    MemberPhone    : Phone,
    MemberStreet   : Street,
    MemberCity     : City,
    MemberCnty not null   : County
  end Members;

  table Members2 is
    MemberName2 not null   : MemName,
```

```

        MemberSSN2 not null    : SSN,
        ClubNumber2 not null  : Club_Number,
        MemberAge2           : Age,
        MemberSex2           : Sex,
        MemberPhone2         : Phone,
        MemberStreet2        : Street,
        MemberCity2          : City,
        MemberCnty2 not null  : County
    end Members2;

end RecDB;

with D_ct13; use D_ct13;
abstract module A_ct13 is
    authorization RecDB

    record MemberRec is
        R_MemberName      : MemName;
        R_Sum              : Sum_Domain;
        R_Count            : Count_Domain;
    end;

    procedure P_MemberSelect (Req_MemberSSN : SSN) is
        select MemberName, SUM(MemberAge), COUNT(*)
        into Row : MemberRec
        from RecDB.Members
        where RecDB.Members.MemberSSN = Req_MemberSSN ;

    procedure MP_MemberSelect (Req_MemberSSN : SSN) is
        select MemberName, Sum_Domain(SUM(MemberAge)),
        Count_Domain(COUNT(*))
        into Row : MemberRec
        from RecDB.Members
        where RecDB.Members.MemberSSN = Req_MemberSSN ;

    procedure MPD_MemberSelect (Req_MemberSSN : SSN) is
        select MemberName, Sum_Domain(SUM(MemberAge)) named x,
        Count_Domain(COUNT(*)) named foo
        from RecDB.Members
        where RecDB.Members.MemberSSN = Req_MemberSSN ;

    cursor M_MemberSelect (Req_MemberSSN : SSN) for
        select MemberName, Sum_Domain(SUM(MemberAge)) named sm,
        Count_Domain(COUNT(*)) named ct
        from RecDB.Members
        where RecDB.Members.MemberSSN = Req_MemberSSN ;
    is
        procedure FetchIt is
            fetch into Row : new MRec;
        end M_MemberSelect;

    cursor MD_MemberSelect (Req_MemberSSN : SSN) for
        select MemberName, Sum_Domain(SUM(MemberAge)) named msum,
        Count_Domain(COUNT(*)) named foo
        from RecDB.Members
        where RecDB.Members.MemberSSN = Req_MemberSSN ;
    is

```

```
        procedure FetchIt is
            fetch;
        end MD_MemberSelect;

    end A_ct13;
```

A.1.23 **t1/ct14.sme**

```
-- Check replacement of constants and enum literals in embedded
-- C-code

DEFINITION MODULE d_ct14 IS
--
--     enumeration declarations
--
    ENUMERATION Branches IS
        ( Bethesda,
          Silver_Spring,
          Gaithersburg,
          Potomac);

    ENUMERATION Loan_types IS
        ( mortgage,
          auto,
          personal);
--
--     domain enumeration declarations
--
    DOMAIN Loan_type_domain IS
        NEW SQL_ENUMERATION_AS_int
        (MAP => POS, ENUMERATION => Loan_types);

    DOMAIN branch_num_domain IS
        NEW SQL_ENUMERATION_AS_Char
        (ENUMERATION => Branches, MAP => IMAGE);

    constant C1 : loan_type_domain is mortgage;
    constant C2 : loan_type_domain is loan_type_domain (loan_type_domain
    (
                                auto));
    constant C3 : branch_num_domain is Bethesda;
    constant C4 : branch_num_domain is branch_num_domain
    (branch_num_domain (
                                Silver_Spring));

END d_ct14;
```

```
WITH d_ct14;  
USE d_ct14;  
SCHEMA MODULE s_ct14 IS  
  
    TABLE Cust IS  
        Col1 : loan_type_domain,  
        Col2 : loan_type_domain,  
        Col3 : branch_num_domain,  
        Col4 : branch_num_domain,  
        Col5 : loan_type_domain,  
        Col6 : branch_num_domain  
    END cust;  
  
END s_ct14;
```

```
WITH d_ct14;
USE d_ct14;
ABSTRACT MODULE a_ct14 IS
  AUTHORIZATION s_ct14

  PROCEDURE New_customer IS
    INSERT INTO
      s_ct14.cust
    VALUES (C1, C2, C3, C4, personal, Gaithersburg);

  PROCEDURE Sel_Cust IS
    SELECT *
    FROM s_ct14.cust
    where Col1 = C1 and
          Col2 = C2 and
          Col3 = C3 and
          Col4 = C4 and
          Col5 = loan_type_domain(personal) and
          Col6 = Gaithersburg;

  PROCEDURE Upd_Cust IS
    UPDATE s_ct14.cust
    SET
      Col1 = C1,
      Col2 = C2,
      Col3 = C3,
      Col4 = C4,
      Col5 = personal,
      Col6 = Gaithersburg;

END a_ct14;
```

A.1.24 t1/ct15.sme

-- Various insert values tests

DEFINITION MODULE d_ct15 IS

--
--
--

enumeration declarations

ENUMERATION Branches IS

(Bethesda,
 Silver_Spring,
 Gaithersburg,
 Potomac);

ENUMERATION Loan_types IS

(mortgage,
 auto,
 personal);

--
--
--

domain character declarations

DOMAIN Customer_name_domain IS

NEW SQL_CHAR(length => 15);

DOMAIN Addr_domain IS

NEW SQL_CHAR(length => 15);

```

DOMAIN City_domain IS
  NEW SQL_CHAR(length => 15);
DOMAIN State_domain IS
  NEW SQL_CHAR(length => 2);
--
--   domain integer declarations
--
DOMAIN SSN_domain IS
  NEW SQL_INT NOT NULL ( FIRST => 0, LAST => 999999999);
DOMAIN acct_num_domain IS
  NEW SQL_SMALLINT NOT NULL ( FIRST => 0, LAST => 9999);
--
--   domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL;
--
--   domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_int
    (MAP => POS, ENUMERATION => Loan_types);
DOMAIN branch_num_domain IS
  NEW SQL_ENUMERATION_AS_INT
    (MAP => POS, ENUMERATION => Branches);
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN             : SSN_domain;
  Street          : Addr_domain;
  City            : City_domain;
  State           : State_domain;
END customer_record;

END d_ct15;

WITH d_ct15;
USE d_ct15;
SCHEMA MODULE s_ct15 IS
--
--   Basic customer information
--
TABLE Cust IS
  Cust_Name      : Customer_name_domain,
  SSN not null   : SSN_domain,
  Street_addr    : Addr_domain,
  City_addr      : City_domain,
  State_addr     : State_domain
END cust;
--
--   Savings account

```

```
--
TABLE Save IS
  branch_num : branch_num_domain,
  acct_num not null : acct_num_domain,
  Balance      : Balance_domain,
  cust_ssn not null : SSN_domain
END Save;

END s_ct15;

WITH d_ct15;
USE d_ct15;
ABSTRACT MODULE a_ct15 IS
  AUTHORIZATION s_ct15

  RECORD customer_record_minus is
    Cust_Name : Customer_name_domain;
    SSN       : SSN_domain;
    City      : City_domain;
    State     : State_domain;
  END customer_record_minus;

  PROCEDURE New_customer IS
    INSERT INTO
      s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
    FROM
      New_customer_info : new c_record
    VALUES;

  PROCEDURE New_customer1 IS
    INSERT INTO
      s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
    FROM
      New_customer_info
    VALUES (Cust_Name, SSN, Street_addr, City_addr, State_addr);

  PROCEDURE New_customer2 IS
    INSERT INTO
      s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
    FROM
      New_customer_info2
    VALUES (Cust_Name, SSN, NULL, City_addr, State_addr);

  PROCEDURE New_customer3 IS
    INSERT INTO
      s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
    FROM
      New_customer_info3
    VALUES (Cust_Name, SSN, '11261 Col Pike', City_addr,
State_addr);

  PROCEDURE New_customer4 IS
    INSERT INTO
```

```

        s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
        FROM : new row_type1
        VALUES;

PROCEDURE New_customer5 IS
    INSERT INTO
        s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
        FROM : new row_type2
        VALUES (Cust_Name, SSN, Street_addr, City_addr, State_addr);

PROCEDURE New_customer6 IS
    INSERT INTO
        s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
        FROM : new row_type3
        VALUES (Cust_Name, SSN, NULL, City_addr, State_addr);

PROCEDURE New_customer7 IS
    INSERT INTO
        s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
        FROM : new row_type4
        VALUES (Cust_Name, SSN, '11261 Col Pike', City_addr,
State_addr);

PROCEDURE New_customer8 IS
    INSERT INTO
        s_ct15.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
        FROM : new row_type5
        VALUES (Cust_Name, SSN, NULL, City_addr, State_addr);

END a_ct15;

```

A.1.25 t1/ct16.sme

```

definition module d_ct16 is
    -- Member Information
    domain MemName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        MAP => POS, ENUMERATION => SexEnum);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;

    constant C_Name : MemName is '123456789012345678901234567890';
    constant C_SSN : SSN is '123456789';

```

```
constant C_Club_Number : Club_Number is 10;
constant C_Age : Age is 39;
constant C_Sex : Sex is F;
constant C_Phone : Phone is '12345678';
constant C_Street : Street is '123456789012345678901234567890';
constant C_City : City is '123456789012345';
constant C_County : County is 'MO';
end d_ctl6;

with d_ctl6; use d_ctl6;
schema module RecDB is
  table Members is
    MemberName not null : MemName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
  end Members;

end RecDB;

with d_ctl6; use d_ctl6;
abstract module a_ctl6 is
  authorization RecDB

  record MemberRec named Named_MemberRec is
    -- record MemberRec is
    R_MemberName : MemName;
    R_MemberSSN : SSN;
    R_ClubNumber : Club_Number;
    R_MemberAge : Age;
    R_MemberSex : Sex;
    R_MemberPhone : Phone;
    R_MemberStreet : Street;
    R_MemberCity : City not null;
    R_MemberCnty : County ;
  end;

  cursor MemberSelect2 (Req_MemberSSN named Req_MemberSSN : SSN) for
    select
      MemberName named NS_MemberName,
      MemberSSN,
      ClubNumber,
      MemberAge,
      MemberSex,
      MemberPhone Not Null,
      MemberStreet named NS_MemberStreet Not Null,
      MemberCity,
      MemberCnty
    from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN
  UNION
```

```

select
    MemberName      named NS_MemberName,
    MemberSSN,
    ClubNumber,
    MemberAge,
    MemberSex,
    MemberPhone Not Null,
    MemberStreet named NS_MemberStreet Not Null,
    MemberCity,
    MemberCnty
from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN
UNION
select
    MemberName      named NS_MemberName,
    MemberSSN,
    ClubNumber,
    MemberAge,
    MemberSex,
    MemberPhone Not Null,
    MemberStreet named NS_MemberStreet Not Null,
    MemberCity,
    MemberCnty
from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN
UNION
select
    MemberName      named NS_MemberName,
    MemberSSN,
    ClubNumber,
    MemberAge,
    MemberSex,
    MemberPhone Not Null,
    MemberStreet named NS_MemberStreet Not Null,
    MemberCity,
    MemberCnty
from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN;
is
    procedure FetchIt is
        -- fetch into Row_Name : MemberRec;
        -- fetch into : MemberRec;
        -- fetch into Row_Name;
        fetch ;
        -- fetch into Row_Name : new New_Row_Type;
        -- fetch into : new New_Row_Type;
    end MemberSelect2;

end a_ctl6;

```

A.1.26 t3/t1.sme

```

definition module t_4 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

```

```
enumeration SexEnum is (F, M);
domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum,
    Map `=> Pos);

domain Phone is new SQL_CHAR (Length => 8);
domain Street is new SQL_CHAR (Length => 30);
domain City is new SQL_CHAR (Length => 15);

domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;

exception Record_Not_Found;

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise record_not_found);

status bool_map uses boolean is
    (100=>true, 0=>false);

end t_4;

with t_4; use t_4;
schema module s_4 is
    table Members is
        MemberName not null : MemberName,
        MemberSSN not null : SSN,
        ClubNumber not null : Club_Number,
        MemberAge : Age,
        MemberSex : Sex,
        MemberPhone : Phone,
        MemberStreet : Street,
        MemberCity : City,
        MemberCnty not null : County
    end Members;
end s_4;

with t_4; use t_4;
abstract module a_4 is
    authorization s_4

    record memberec2 named insertrec is
        MemberName : MemberName;
        MemberSex : Sex not null;
    end memberec2;

    record memberec3 is
        junk dblelength named nameind : MemberName;
        MemberSex : Sex;
    end memberec3;

    record memberec is
```

```

        MemberName      : MemberName;
        MemberSex       : Sex;
end memberec;

procedure DeleteMember1 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status bool_map;

procedure DeleteMember2 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status bool_map named delete_status;

procedure DeleteMember3 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status fetch_map;

procedure DeleteMember4 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status fetch_map named delete_status;

is
    procedure DeleteMember5 ( Input_name named Delete_Me : membername)
        delete from members
        where Membername = Input_Name
        status bool_map;

    procedure SelectMember1 is
        select membersex not null, membername from s_4.Members;

    procedure MemberInsert0 is
        insert into s_4.Members Values;

    procedure MemberInsert1 is
        insert into s_4.Members (membername, membersex) Values;

    procedure MemberInsert2 is
        insert into s_4.Members (Membername named myname, membersex
named
        mysex not null) Values;

    procedure MemberInsert3 is
        insert into s_4.Members (Membername named myname, membersex
named
        mysex) Values (membername,membersex);

    procedure MemberInsert4 is
        insert into s_4.Members (Membername named junk, membersex)
        from :memberec3 Values (membername,membersex);

    procedure MemberInsert5 is
        insert into s_4.Members (Membername , membersex )
        from the_row : memberec Values (membername,membersex);

    procedure MemberInsert6 is

```

```
        insert into s_4.Members (Membername named myname, membersex
named      mysex) from the_row Values (membername,membersex);

        procedure MemberInsert7 is
named      insert into s_4.Members (Membername named myname, membersex
named      mysex) from : new rec7 Values (membername,membersex);

        procedure MemberInsert8 is
named      insert into s_4.Members (s_4.members.Membername , membersex
named      mysex) from the_row : new rec8 Values (membername,membersex);

        procedure MemberInsert9 is
named      insert into s_4.Members (Membername, membersex)
named      from :memberrec2 Values (membername,membersex);

        procedure MemberInsert10 is
named      insert into s_4.Members (s_4.members.Membername , membersex )
named      from the_row : memberrec2 Values (membername,membersex);

        procedure MemberInsert11 is
named      insert into s_4.Members (Membername named myname, membersex
named      mysex) from : new rec11 Values (membername,membersex);

        procedure MemberInsert12 is
named      insert into s_4.Members (Membername named myname, clubnumber
named      mycounty) from the_row : new rec12 Values (membername,clubnumber);

        cursor MemberSelect (Req_MemberSSN : SSN) for
named      select s_4.members.membername , membersex named mysex,
named      clubnumber * 6 named club,
named      memberssn named myssn
named      from s_4.Members
named      where memberssn = Req_MemberSSN;

        cursor MemberSelect2 (Req_MemberSSN named myssn : SSN) for
named      select s_4.members.membername named junk dblelength named nameind,
named      membersex
named      from s_4.Members
named      where memberssn = Req_MemberSSN;

        is
named      procedure FetchIt is
named      fetch into :memberrec3
named      status standard_map ;

        procedure updateit is
named      update members
named      set s_4.members.membersex = null
named      where current of memberselect2;
named      end MemberSelect2;

end a_4;
```

A.1.27 t3/t2.sme

```

definition module t_10 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum,
    Map => Pos);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;

  exception Record_Not_Found;

  enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

  status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
      0 => SQL_Ok,
      100 => raise record_not_found);

  status bool_map uses boolean is
    (100=>true, 0=>false);

end t_10;

with t_10; use t_10;
schema module s_10 is
  table Members is
    MemberName not null : MemberName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
  end Members;

end s_10;

with t_10; use t_10;
abstract module a_10 is
  authorization s_10

  record memberec2 named insertrec is
    MemberName : MemberName;

```

```
        MemberSex      : Sex not null;
end memberec2;

record memberec3 is
    junk dblength named nameind : MemberName;
    MemberSex : Sex;
end memberec3;

record memberec is
    MemberName : MemberName;
    MemberSex  : Sex;
end memberec;

cursor MemberSelect2 (Req_MemberSSN named myssn : SSN) for
    select s_10.members.membername named junk dblength named
nameind,
        membersex
    from s_10.Members
        where memberssn = Req_MemberSSN
    union
        select members.membername named junk dblength named nameind,
            membersex
        from s_10.Members;
is
    procedure FetchIt is
        fetch into :memberec3
        status standard_map ;

    procedure updateit is
        update members
        set s_10.members.membersex = null
        where current of memberselect2;
    end MemberSelect2;

end a_10;
```

A.1.28 **t3/t3.sme**

```
definition module t_11 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        ENUMERATION => SexEnum, Map => POS);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;

    exception Record_Not_Found;
```

```

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise record_not_found);

end t_11;

with t_11; use t_11;
schema module s_11 is
    table Members is
        MemberName not null    : MemberName,
        MemberSSN not null     : SSN,
        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null   : County
    end Members;

end s_11;

with t_11; use t_11;
abstract module a_11 is
    authorization s_11

        record MemberRec is
            MemberName    : MemberName;
            MemberSSN     : SSN;
            ClubNumber    : Club_Number;
            MemberAge     : Age;
            MemberSex     : Sex;
            MemberPhone    : Phone;
            MemberStreet   : Street;
            MemberCity     : City;
            MemberCnty    : County;
        end;

        cursor MemberSelect (Req_MemberSSN : SSN) for
            select MemberSSN, MemberName
            from s_11.Members as t1
            where t1.MemberSSN = '012345678';

end a_11;

```

A.1.29 t3/t4.sme

```

definition module t_8 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);

```

```
domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

enumeration SexEnum is (F, M);
domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum,
    Map => Pos);

domain Phone is new SQL_CHAR (Length => 8);
domain Street is new SQL_CHAR (Length => 30);
domain City is new SQL_CHAR (Length => 15);

domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;

exception Record_Not_Found;

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status f_map named is_found is
    ( 100 => raise record_not_found);

status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299 .. -298 => Not_Logged_In,
        0 => SQL_OK,
      100 => raise record_not_found);

status bool_map uses boolean is
    (100=>true, 0=>false);

end t_8;

with t_8; use t_8;
schema module s_8 is

    -- table mytable is
    -- unique(ssn)
    -- end mytable;

    table Members is
        MemberName char(30) default 'jennifer' not null primary key:
MemberName,
        MemberSSN character default user not null : SSN,
        ClubNumber int not null : Club_Number,
        MemberAge references mytable : Age,
        MemberSex check(MemberSex <> f) : Sex,
        MemberPhone : Phone,
        MemberStreet : Street,
        MemberCity : City,
        MemberCnty not null unique : County,
        foreign key (memberAge,membername) references anothertable
(age,mname),
        primary key (memberssn),
        unique (membername,memberphone),
        check (membercnty <> 'PG')
    end Members;
```

```

grant all privileges on jc.anothertable to jc, gdt, am with grant
option;

grant select, insert, delete on informix.customer to jc;

end s_8;

with t_8; use t_8;
abstract module a_8 is
  authorization s_8

    record memberec2 named insertrec is
      MemberName : MemberName;
      MemberSex  : Sex not null;
    end memberec2;

    record memberec3 is
      junk dblength named nameind : MemberName;
      MemberSex : Sex;
    end memberec3;

    record memberec is
      MemberName : MemberName;
      MemberSex  : Sex;
    end memberec;

    procedure DeleteMember1 ( Input_name : membername) is
      delete from members
      where Membername = Input_Name
      status bool_map;

    procedure DeleteMember2 ( Input_name : membername) is
      delete from members
      where Membername = Input_Name
      status bool_map named delete_status;

    procedure DeleteMember3 ( Input_name : membername) is
      delete from members
      where Membername = Input_Name
      status f_map;

    procedure DeleteMember4 ( Input_name : membername) is
      delete from members
      where Membername = Input_Name
      status fetch_map named delete_status;

    procedure DeleteMember5 ( Input_name named Delete_Me : membername)
is
      delete from members
      where Membername = Input_Name
      status bool_map;

    procedure SelectMember1 is

```

```
select membersex not null, membername from s_8.Members;

procedure MemberInsert0 is
  insert into s_8.Members Values;

procedure MemberInsert1 is
  insert into s_8.Members (membername, membersex) Values;

procedure MemberInsert2 is
  insert into s_8.Members (Membername named myname, membersex
named
  mysex not null) Values;

procedure MemberInsert3 is
  insert into s_8.Members (Membername named myname, membersex
named
  mysex) Values (membername,membersex);

procedure MemberInsert4 is
  insert into s_8.Members (Membername named junk, membersex)
  from :memberec3 Values (membername,membersex);

procedure MemberInsert5 is
  insert into s_8.Members (Membername , membersex )
  from the_row : memberec Values (membername,membersex);

procedure MemberInsert6 is
  insert into s_8.Members (Membername named myname, membersex
named
  mysex) from the_row Values (membername,membersex);

procedure MemberInsert7 is
  insert into s_8.Members (Membername named myname, membersex
named
  mysex) from : new rec7 Values (membername,membersex);

procedure MemberInsert8 is
  insert into s_8.Members (s_8.members.Membername , membersex
named
  mysex) from the_row : new rec8 Values (membername,membersex);

procedure MemberInsert9 is
  insert into s_8.Members (Membername, membersex)
  from :memberec2 Values (membername,membersex);

procedure MemberInsert10 is
  insert into s_8.Members (s_8.members.Membername , membersex )
  from the_row : memberec2 Values (membername,membersex);

procedure MemberInsert11 is
  insert into s_8.Members (Membername named myname, membersex
named
  mysex) from : new rec11 Values (membername,membersex);

procedure MemberInsert12 is
  insert into s_8.Members (Membername named myname, clubnumber
named
```

```

mycounty) from the_row : new rec12 Values (membername,clubnumber);

cursor MemberSelect (Req_MemberSSN : SSN) for
    select s_8.members.membername , membersex named mysex,
           clubnumber * 6 named club,
           memberssn named myssn
    from s_8.Members
    where memberssn = a_8.memberselect.Req_MemberSSN;

cursor MemberSelect2 (Req_MemberSSN named myssn : SSN) for
    select s_8.members.membername named junk dblength named nameind,
           membersex
    from s_8.Members
    where memberssn = Req_MemberSSN;
is
    procedure FetchIt is
        fetch into :memberec3
        status f_map ;

    procedure updateit is
        update members
        set s_8.members.membersex = null
        where current of memberselect2;
    end MemberSelect2;

end a_8;

```

A.1.30 t3/t5.sme

```

definition module t_9 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        Enumeration => SexEnum,
        Map => Pos);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;

    exception Record_Not_Found;

    enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

    status fetch_map named is_found uses Failtype is
        ( -999 .. -300 => SQL_Fail,
          -299, -298 => Not_Logged_In,
           0 => SQL_Ok,
          100 => raise record_not_found);

```

```
status bool_map uses boolean is
  (100=>true, 0=>false);

end t_9;

with t_9; use t_9;
schema module s_9 is
  table Members is
    MemberName not null : MemberName,
    MemberSSN not null  : SSN,
    ClubNumber not null : Club_Number,
    MemberAge           : Age,
    MemberSex           : Sex,
    MemberPhone         : Phone,
    MemberStreet        : Street,
    MemberCity          : City,
    MemberCnty not null : County
  end Members;

end s_9;

with t_9; use t_9;
abstract module a_9 is
  authorization s_9

  record memberec2 named insertrec is
    MemberName : MemberName;
    MemberSex  : Sex not null;
  end memberec2;

  record memberec3 is
    junk dblength named nameind : MemberName;
    MemberSex : Sex;
  end memberec3;

  record memberec is
    MemberName : MemberName;
    MemberSex  : Sex;
  end memberec;

  procedure DeleteMember1 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status bool_map;

  procedure DeleteMember2 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status bool_map named delete_status;

  procedure DeleteMember3 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
    status fetch_map;

  procedure DeleteMember4 ( Input_name : membername) is
    delete from members
    where Membername = Input_Name
```

```

        status fetch_map named delete_status;

procedure DeleteMember5 ( Input_name named Delete_Me : membername)
is
    delete from members
    where Membername = Input_Name
    status bool_map;

procedure SelectMember1 is
    select membersex not null, membername from s_9.Members;

procedure MemberInsert0 is
    insert into s_9.Members Values;

procedure MemberInsert1 is
    insert into s_9.Members (membername, membersex) Values;

procedure MemberInsert2 is
    insert into s_9.Members (Membername named myname, membersex
named
    mysex not null) Values;

procedure MemberInsert3 is
    insert into s_9.Members (Membername named myname, membersex
named
    mysex) Values (membername,membersex);

procedure MemberInsert4 is
    insert into s_9.Members (Membername named junk, membersex)
    from :memberec3 Values (membername,membersex);

procedure MemberInsert5 is
    insert into s_9.Members (Membername , membersex )
    from the_row : memberec Values (membername,membersex);

procedure MemberInsert6 is
    insert into s_9.Members (Membername named myname, membersex
named
    mysex) from the_row Values (membername,membersex);

procedure MemberInsert7 is
    insert into s_9.Members (Membername named myname, membersex
named
    mysex) from : new rec7 Values (membername,membersex);

procedure MemberInsert8 is
    insert into s_9.Members (s_9.members.Membername , membersex
named
    mysex) from the_row : new rec8 Values (membername,membersex);

procedure MemberInsert9 is
    insert into s_9.Members (Membername, membersex)
    from :memberec2 Values (membername,membersex);

procedure MemberInsert10 is
    insert into s_9.Members (s_9.members.Membername , membersex )
    from the_row : memberec2 Values (membername,membersex);

```

```
procedure MemberInsert11 is
  insert into s_9.Members (Membername named myname, membersex
named      mysex) from : new rec11 Values (membername,membersex);

procedure MemberInsert12 is
  insert into s_9.Members (Membername named myname, clubnumber
named      mycounty) from the_row : new rec12 Values (membername,clubnumber);

cursor MemberSelect (Req_MemberSSN : SSN) for
  select s_9.members.membername , membersex named mysex,
         clubnumber * 6 named club,
         memberssn named myssn
  from s_9.Members
  where memberssn = a_9.memberselect.Req_MemberSSN;

cursor MemberSelect2 (Req_MemberSSN named myssn : SSN) for
  select s_9.members.membername named junk dblength named nameind,
         membersex
  from s_9.Members
  where memberssn = Req_MemberSSN
union
  select s_9.members.membername named junk dblength named nameind,
         membersex
  from s_9.Members;
is
  procedure FetchIt is
    fetch into :memberec3
    status standard_map ;

    procedure updateit is
      update members
      set s_9.members.membersex = null
      where current of memberselect2;
    end MemberSelect2;

end a_9;
```

A.1.31 **t3/t6.sme**

```
definition module t_12 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, Map => POS);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;
```

```

exception Record_Not_Found;

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise record_not_found);

end t_12;

with t_12; use t_12;
schema module s_12 is
    table Members is
        MemberName not null    : MemberName,
        MemberSSN not null     : SSN,
        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet    : Street,
        MemberCity     : City,
        MemberCnty not null    : County
    end Members;

    table Members2 is
        MemberName not null    : MemberName,
        MemberSSN not null     : SSN,
        ClubNumber not null    : Club_Number
    end Members2;

end s_12;

with t_12; use t_12;
abstract module a_12 is
    authorization s_12

        record MemberRec is
            MemberName    : MemberName;
            MemberSSN      : SSN;
            ClubNumber     : Club_Number;
            MemberAge      : Age;
            MemberSex      : Sex;
            MemberPhone    : Phone;
            MemberStreet    : Street;
            MemberCity     : City;
            MemberCnty     : County;
        end;

        cursor MemberSelect (Req_MemberSSN : SSN) for
            select MemberSSN, s_12.Members.Membername
            from s_12.Members
            where MemberSSN = (select MemberSSN
                              from Members2

```

```
where s_12.members2.membername = 'John');
```

```
end a_12;
```

A.1.32 t3/t7.sme

```
definition module t_13 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, Map => POS);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;

  exception Record_Not_Found;

  enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

  status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail;
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
        100 => raise record_not_found);

end t_13;

with t_13; use t_13;
schema module s_13 is
  table Members is
    MemberName not null : MemberName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
  end Members;

  table Members2 is
    MemberName not null : MemberName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number
  end Members2;

end s_13;
```

```

with t_13; use t_13;
abstract module a_13 is
  authorization s_13

    record MemberRec is
      MemberName   : MemberName;
      MemberSSN    : SSN;
      ClubNumber   : Club_Number;
      MemberAge    : Age;
      MemberSex    :- Sex;
      MemberPhone  : Phone;
      MemberStreet : Street;
      MemberCity   : City;
      MemberCnty   : County;
    end;

    cursor MemberSelect (Req_MemberSSN : SSN) for
      select MemberSSN, Members.Membername
      from s_13.Members
      where MemberSSN = (select MemberSSN
                        from Members2
                        where s_13.members2.membername = 'John');

end a_13;

```

A.1.33 t3/t8.sme

```

definition module t_14 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, Map => POS);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;

  exception Record_Not_Found;

  enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

  status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise record_not_found);

end t_14;

```

```
with t_14; use t_14;
schema module s_14 is
  table Members is
    MemberName not null    : MemberName,
    MemberSSN not null     : SSN,
    ClubNumber not null    : Club_Number,
    MemberAge      : Age,
    MemberSex      : Sex,
    MemberPhone    : Phone,
    MemberStreet   : Street,
    MemberCity     : City,
    MemberCnty not null   : County
  end Members;

  table Members2 is
    MemberName not null    : MemberName,
    MemberSSN not null     : SSN,
    ClubNumber not null    : Club_Number
  end Members2;

end s_14;

with t_14; use t_14;
abstract module a_14 is
  authorization s_14

  record MemberRec is
    MemberName : MemberName;
    MemberSSN  : SSN;
    ClubNumber : Club_Number;
    MemberAge  : Age;
    MemberSex  : Sex;
    MemberPhone : Phone;
    MemberStreet : Street;
    MemberCity : City;
    MemberCnty : County;
  end;

  cursor MemberSelect (Req_MemberSSN : SSN) for
    select MemberSSN, Members.Membername
    from s_14.Members
    where MemberSex = (select MemberSex
                       from Members
                       where s_14.members.membersex =
                         t_14.f );

end a_14;
```

A.1.34 t3/t9.sme

```
definition module t_15 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);
```

```

enumeration SexEnum is (F, M);
domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, Map => POS);

domain Phone is new SQL_CHAR (Length => 8);
domain Street is new SQL_CHAR (Length => 30);
domain City is new SQL_CHAR (Length => 15);

domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;

exception Record_Not_Found;

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise record_not_found);

end t_15;

with t_15; use t_15;
schema module s_15 is
    table Members is
        MemberName not null    : MemberName,
        MemberSSN not null     : SSN,
        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null    : County
    end Members;

end s_15;

with t_15; use t_15;
abstract module a_15 is
    authorization s_15

    record MemberRec is
        MemberName    : MemberName;
        MemberSSN     : SSN;
        ClubNumber     : Club_Number;
        MemberAge      : Age;
        MemberSex      : Sex;
        MemberPhone    : Phone;
        MemberStreet   : Street;
        MemberCity     : City;
        MemberCnty     : County;
    end;

```

```
procedure CommitWork is
    commit work;

procedure MemberInsert is
    insert into s_15.Members
    from Row : MemberRec VALUES;

cursor MemberSelect (Req_MemberSSN : SSN) for
    select *
    from s_15.Members
    where s_15.Members.MemberSSN = Req_MemberSSN;
is
    procedure FetchIt is
        fetch into Row : new MemberRec
        status Fetch_Map named Rec_Status;

    end MemberSelect;

end a_15;
```

A.1.35 t3/t10.sme

```
definition module t_5 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        Enumeration => SexEnum, Map => Pos);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;

    exception Record_Not_Found;

    enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

    status fetch_map named is_found uses Boolean is
        ( -999 .. -300 => False,
          0 => True,
          100 => raise record_not_found);

end t_5;

with t_5; use t_5;
schema module s_5 is
    table Members is
        MemberName not null    : MemberName,
        MemberSSN not null     : SSN,
```

```

        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null    : County
    end Members;

end s_5;

with t_5; use t_5;
abstract module a_5 is
    authorization s_5

        record MemberRec is
            MemberName      : MemberName;
            MemberSSN       : SSN;
            ClubNumber       : Club_Number;
            MemberAge       : Age;
            MemberSex       : Sex;
            MemberPhone     : Phone;
            MemberStreet    : Street;
            MemberCity      : City;
            MemberCnty      : County;
        end;

        procedure CommitWork is
            commit work;

        procedure MemberInsert is
            insert into s_5.Members
            from Row : MemberRec VALUES;

        cursor MemberSelect (Req_MemberSSN : SSN) for
            select *
            from s_5.Members
            where s_5.Members.MemberSSN = Req_MemberSSN;
        is
            procedure FetchIt is
                fetch into Row : new MemberRec
                status Fetch_Map named Rec_Status;

            end MemberSelect;

    end a_5;

```

A.1.36 t3/t11.sme

```

definition module t_6 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (

```

```

                                Enumeration => SexEnum, Map => Pos);

domain Phone is new SQL_CHAR (Length => 8);
domain Street is new SQL_CHAR (Length => 30);
domain City is new SQL_CHAR (Length => 15);

domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;

exception Record_Not_Found;

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status fetch_map named is_found uses Boolean is
    ( -999 .. -300 => False,
      0 => True,
      100 => raise record_not_found);

end t_6;

with t_6; use t_6;
schema module s_6 is
    table Members is
        MemberName not null    : MemberName,
        MemberSSN not null     : SSN,
        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null    : County
    end Members;

end s_6;

with t_6; use t_6;
abstract module a_6 is
    authorization s_6

    record MemberRec is
        MemberName    : MemberName;
        MemberSSN     : SSN;
        ClubNumber    : Club_Number;
        MemberAge     : Age;
        MemberSex     : Sex;
        MemberPhone   : Phone;
        MemberStreet  : Street;
        MemberCity    : City;
        MemberCnty    : County;
    end;

    procedure CommitWork is
        commit work;
```

```

procedure MemberInsert is
  insert into s_6.Members
  from Row : MemberRec VALUES;

  cursor MemberSelect (Req_MemberSSN : SSN) for
    select *
    from s_6.Members
    where s_6.Members.MemberSSN = Req_MemberSSN;

end a_6;

```

A.1.37 t3/t12.sme

```

-- *****
-- *** Test I
-- *****

DEFINITION MODULE D_cI IS
-- the previous line tests the newline separator
--
-- testing full character set
--
  DOMAIN Character_set_domain IS
    NEW SQL_CHAR(length => 43);
  CONSTANT letters : character_set_domain
    IS 'the quick brown fox jumps over the lazy dog';
  CONSTANT all_caps : character_set_domain
    IS 'THE QUICK BROWN FOX JUMPS OVER THE LAZY DOG';
  CONSTANT digit_as_char : Character_set_domain
    IS '1234567890';
  CONSTANT digits_as_num
    IS 1234567890;

  DOMAIN integer_domain IS
    NEW SQL_INT;
  DOMAIN real_domain IS
    NEW SQL_REAL;
  CONSTANT integer_literal : integer_domain
    IS (12-4+5*2);
  CONSTANT real_literal : real_domain
    IS 12.456/.09 + 1. ;
  CONSTANT float_literal
    IS (0.1E1) + (10.E-1) + ( .1E+1) ;

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
  DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_CHAR
    (ENUMERATION => Loan_types, MAP => IMAGE);
  CONSTANT personal_loan : loan_type_domain
    IS personal ;

END D_cI;

```

A.1 38 t3/t13.sme

```
definition module t_16 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, MAP => pos);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;

  exception Record_Not_Found;

  enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

  status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise record_not_found);

end t_16;

with t_16; use t_16;
schema module s_16 is
  table Members is
    MemberName not null    : MemberName,
    MemberSSN not null     : SSN,
    ClubNumber not null    : Club_Number,
    MemberAge      : Age,
    MemberSex      : Sex,
    MemberPhone    : Phone,
    MemberStreet   : Street,
    MemberCity     : City,
    MemberCnty not null   : County
  end Members;

end s_16;

with t_16; use t_16;
abstract module a_16 is
  authorization s_16

  record MemberRec is
    MemberName : MemberName;
    MemberSSN  : SSN;
```

```

        ClubNumber    : Club_Number;
        MemberAge     : Age;
        MemberSex      : Sex;
        MemberPhone    : Phone;
        MemberStreet   : Street;
        MemberCity     : City;
        MemberCnty     : County;
    end;

    cursor MemberSelect (Req_MemberSSN : SSN) for
        select t1.MemberSSN, t2.MemberName
        from s_16.Members as t1, s_16.Members as t2
        where t1.MemberSSN = t2.MemberSSN;

end a_16;

```

A.1.39 t3/t14.sme

```

definition module t_7 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        Enumeration => SexEnum,
        Map => Pos);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;

    exception Record_Not_Found;

    enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

    status fetch_map named is_found uses Failtype is
        ( -999 .. -300 => SQL_Fail,
          -299, -298 => Not_Logged_In,
           0 => SQL_Ok,
          100 => raise record_not_found);

    status bool_map named not_found uses boolean is
        (100=>true, 0=>false);

end t_7;

```

A.2 End-to-End Tests

The end-to-end tests are comprised of the SAMeDL file **t2.sme** and the Ada application program file **driver.a**. Also included for convenience are the database schema files **initbank.sql** and **init1.sql** used for initially setting up the database.

A.2.1 t2/t2.sme

```
DEFINITION MODULE Bank_def IS
--
--   enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
--   domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 15);
  DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 15);
  DOMAIN City_domain IS
    NEW SQL_CHAR(length => 15);
  DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
--
--   domain integer declarations
--
  DOMAIN SSN_domain IS
    NEW SQL_INT NOT NULL ( FIRST => 0, LAST => 999999999);
  DOMAIN acct_num_domain IS
    NEW SQL_SMALLINT NOT NULL ( FIRST => 0, LAST => 9999);
--
--   domain real declarations
--
  DOMAIN Balance_domain IS
    NEW SQL_REAL;
  DOMAIN Interest_rate_domain IS
    NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
  DOMAIN Loan_payment_domain IS
    NEW SQL_REAL;
  DOMAIN Branch_assets_domain IS
    NEW SQL_REAL;
```

```
--
--      domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_int
    (ENUMERATION => Loan_types, MAP => POS);
DOMAIN branch_num_domain IS
  NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN             : SSN_domain;
  Street          : Addr_domain;
  City            : City_domain;
  State           : State_domain;
END customer_record;

RECORD New_Customer_record IS
  New_Name       : Customer_name_domain;
  New_SSN        : SSN_domain;
  New_Street     : Addr_domain;
  New_City       : City_domain;
  New_State      : State_domain;
END new_customer_record;

RECORD Fetch_Customer_record IS
  Bank_Cust_Name : Customer_name_domain;
  Bank_Cust_SSN  : SSN_domain;
  Bank_Cust_Street_Addr : Addr_domain;
  Bank_Cust_City_Addr : City_domain;
  Bank_Cust_State_Addr : State_domain;
END fetch_customer_record;

RECORD Savings_entry IS
  branch_num : branch_num_domain;
  acct_num   : acct_num_domain;
  Balance    : Balance_domain;
  cust_ssn   : SSN_domain;
END Savings_entry;

RECORD Chequeing_entry IS
  branch_num : branch_num_domain;
  acct_num   : acct_num_domain;
  Balance    : Balance_domain;
  cust_ssn   : SSN_domain;
END Chequeing_entry;

RECORD loan_entry IS
  branch_num : branch_num_domain;
  acct_num   : acct_num_domain;
  Balance    : Balance_domain;
  Loan_type  : Loan_type_domain;
  cust_ssn   : SSN_domain;
END loan_entry;
```

```
RECORD Branch_entry IS
    branch_num : branch_num_domain ;
    Assets      : Branch_assets_domain;
END Branch_entry;

RECORD new_Branch_entry IS
    num : branch_num_domain ;
    Assets : Branch_assets_domain;
END new_Branch_entry;

ENUMERATION sql_enum IS (SQL_Found, SQL_Not_Found, SQL_Error);
STATUS fail_type NAMED Is_Found USES sql_enum IS
    (-999..-1 => SQL_Error,
     0 => SQL_Found,
     100 => SQL_Not_Found);

END Bank_def;
```

```

WITH Bank_def;
USE Bank_def;
SCHEMA MODULE Bank IS
--
-- Basic customer information
--
TABLE Cust IS
    Cust_Name : Customer_name_domain,
    SSN not null : SSN_domain,
    Street_addr : Addr_domain,
    City_addr : City_domain,
    State_addr : State_domain
END cust;
--
-- Checking account
--
TABLE cheque IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance : Balance_domain,
    cust_ssn not null : SSN_domain
END cheque;
--
-- Savings account
--
TABLE savings IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance : Balance_domain,
    cust_ssn not null : SSN_domain
END savings;
--
-- loan account
--
TABLE loan IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance : Balance_domain,
    Loan_type : loan_type_domain,
    cust_ssn not null : SSN_domain
END loan;
--
-- Branch information
--
TABLE Branch IS
    num : branch_num_domain,
    Assets : Branch_assets_domain
END Branch;

END Bank;

```

```
WITH Bank_def;
USE Bank_def;
EXTENDED ABSTRACT MODULE Bank_proc IS
  AUTHORIZATION Bank
--
-- procedures
--
--
--   commit statement
--
  PROCEDURE Commit_work.IS
    COMMIT WORK;
--
--   delete statement
--
  PROCEDURE Delete_customer_loan
    (loan_number_in : acct_num_domain) IS
    DELETE FROM
      Bank.Loan
    WHERE
      Bank.Loan.acct_num = loan_number_in;
--
--   rollback statement
--
  PROCEDURE rollback_work IS
    ROLLBACK WORK;
--
--   update statement
--
  PROCEDURE Up_save_acct_bal
    (acct_num_in : acct_num_domain;
     transaction   : balance_domain )
  IS
  UPDATE
    Bank.savings
  SET
    Bank.savings.balance =
      Bank.savings.balance + transaction
  WHERE
    Bank.savings.acct_num = acct_num_in;

  PROCEDURE S_and_L IS
  UPDATE
    Bank.Loan
  SET
    Bank.Loan.balance = 0.0;
--
--   insert statement (query)
--
  PROCEDURE move_cheque_to_save
    (account_num_in : acct_num_domain)
  IS
  INSERT INTO
    Bank.savings
  SELECT *
  FROM
```

```
Bank.cheque  
WHERE  
Bank.cheque.acct_num >= account_num_in;
```

```
--
--      insert statement (values)
--
--      select statement
--
PROCEDURE Get_cust_profile (SSN_in : SSN_domain) IS
  SELECT *
  INTO
    Customer_Profile : customer_record
  FROM
    Bank.cust
  WHERE
    Bank.cust.SSN = SSN_in;

--      insert statement (values)
--
--      select statement
--
PROCEDURE Get_save_record
  (acct_num_in : acct_num_domain) IS
  SELECT *
  INTO
    savings_record : savings_entry
  FROM
    Bank.savings
  WHERE
    Bank.savings.acct_num =
      acct_num_in;

-- cursors
--
--
--      cursors with different predicates in the WHERE statement
--
--
--      comparison predicate =
--
CURSOR customer_accounts(SSN_in : SSN_domain) FOR
  SELECT
    Bank.savings.cust_ssn,
    Bank.savings.acct_num,
    Bank.savings.balance
  FROM
    Bank.savings
  WHERE
    Bank.savings.cust_ssn = SSN_in ;

--
--      comparison predicate >=
--
CURSOR loans_over(loan_balance_in : balance_domain) FOR
  SELECT
    Bank.Loan.acct_num,
    Bank.Loan.branch_num,
    Bank.Loan.cust_ssn,
```

```

        Bank.Loan.balance
FROM      Bank.Loan .
WHERE     Bank.Loan.balance >= loan_balance_in ;

--
--      comparison predicate <=
--
CURSOR loans_under(loan_balance_in : balance_domain) FOR
SELECT
        Bank.Loan.acct_num,
        Bank.Loan.branch_num,
        Bank.Loan.cust_ssn,
        Bank.Loan.balance
FROM      Bank.Loan
WHERE     Bank.Loan.balance <= loan_balance_in ;

--
--      comparison predicate >
--
CURSOR cheque_bal_over ( account_bal_in : Balance_domain ) FOR
SELECT
        Bank.cheque.acct_num,
        Bank.cheque.balance
FROM      Bank.cheque
WHERE     Bank.cheque.balance > account_bal_in ;

--
--      comparison predicate <
--
CURSOR save_bal_under ( account_bal_in : Balance_domain ) FOR
SELECT
        Bank.savings.acct_num,
        Bank.savings.balance
FROM      Bank.savings
WHERE     Bank.savings.balance < account_bal_in ;

--
--      comparison predicate <>
--
CURSOR other_branches
        ( branch_num_in : branch_num_domain ) FOR
SELECT
        Bank.Branch.num
FROM      Bank.Branch
WHERE     Bank.Branch.num <> branch_num_in ;

--
--      between predicate
--
CURSOR large_deposits
        ( lower_bound : balance_domain; upper_bound :balance_domain) FOR

```

```
SELECT *
FROM
    Bank.savings
WHERE
    Bank.savings.balance
        BETWEEN lower_bound
            AND upper_bound ;

--
-- not between predicate
--

CURSOR large_loans
( lower_bound : balance_domain; upper_bound :balance_domain) FOR
SELECT
    Bank.Loan.acct_num,
    Bank.Loan.balance,
    Bank.Loan.cust_ssn
FROM
    Bank.Loan
WHERE
    Bank.Loan.balance NOT BETWEEN lower_bound AND upper_bound ;

--
-- like predicate
--

CURSOR find_customer (name_in : customer_name_domain) FOR
SELECT
    Bank.cust.cust_name
FROM
    Bank.cust
WHERE
    Bank.cust.cust_name LIKE name_in
ORDER BY
    Bank.cust.cust_name ;

--
-- exists predicate/null predicate/subquery/quantified predicate
--

CURSOR Cust_Null_Count FOR
SELECT
    ssn
FROM
    Cust t1, Savings t2
WHERE
    t1.street_addr IS NULL AND
    t1.ssn = t2.cust_ssn AND
    t2.balance > SOME (SELECT balance FROM bank.savings) AND
    EXISTS (SELECT * FROM loan WHERE loan.cust_ssn=t1.ssn)
;

--
-- in predicate
--

CURSOR Loan_count ( Branch_in: branch_num_domain ) FOR
SELECT
```

```

        *
    FROM      Bank.Loan
    WHERE
        Bank.Loan.Branch_num IN (Branch_in) ;

--
--      cursor procs
--
CURSOR customer_list FOR
    SELECT *
    FROM
        Bank.cust ;
IS
PROCEDURE open_customer IS
    OPEN customer_list;

PROCEDURE close_customer IS
    CLOSE customer_list;

PROCEDURE fetch_customer IS
    FETCH customer_list
    INTO next_customer : fetch_customer_record
    STATUS fail_type;

PROCEDURE update_customer (new_street : Addr_domain) IS
    UPDATE      Bank.cust
    SET  Bank.cust.street_addr = new_street
    WHERE CURRENT OF customer_list;

PROCEDURE update_customer_null IS
    UPDATE      Bank.cust
    SET  Bank.cust.street_addr = null
    WHERE CURRENT OF customer_list;

PROCEDURE delete_customer IS
    DELETE FROM Bank.cust;

END customer_list;

```

```
--
-- procedures and cursors used to initialize the database and
-- verify the contents of tables after test transactions
--

EXTENDED PROCEDURE Connect_Bank is
    CONNECT Bank ;

PROCEDURE New_customer IS
    INSERT INTO
        Bank.cust (cust_name named new_name,
                   ssn named new_ssn,
                   street_addr named new_street,
                   city_addr named new_city,
                   state_addr named new_state)
    FROM
        New_customer_info : new_customer_record
    VALUES;

PROCEDURE New_chequeing IS
    INSERT INTO
        Bank.cheque
    FROM
        New_chequeing_info : chequeing_entry
    VALUES;

PROCEDURE New_savings IS
    INSERT INTO
        Bank.savings
    FROM
        New_savings_info : savings_entry
    VALUES;

PROCEDURE New_loan IS
    INSERT INTO
        Bank.Loan
    FROM
        New_loan_info : loan_entry
    VALUES;

PROCEDURE New_branch IS
    INSERT INTO
        Bank.Branch
    FROM
        New_branch_info : new_branch_entry
    VALUES (num,assets);

PROCEDURE Delete_customers IS
    DELETE FROM
        Bank.cust;

PROCEDURE Delete_chequeing IS
    DELETE FROM
        Bank.cheque;

PROCEDURE Delete_savings IS
    DELETE FROM
        Bank.savings;
```

```
PROCEDURE Delete_loans IS
  DELETE FROM
    Bank.Loan;
```

```
PROCEDURE Delete_Branches IS
  DELETE FROM
    Bank.Branch;
```

```
CURSOR List_customers FOR
  SELECT *
  FROM
    Bank.cust
  ORDER BY
    Bank.cust.SSN
;

CURSOR List_chequeing FOR
  SELECT *
  FROM
    Bank.cheque
  ORDER BY
    Bank.cheque.acct_num
;

CURSOR List_savings FOR
  SELECT *
  FROM
    Bank.savings
  ORDER BY
    Bank.savings.acct_num
;

CURSOR List_loans FOR
  SELECT *
  FROM
    Bank.Loan
  ORDER BY
    Bank.Loan.acct_num
;

CURSOR List_branches FOR
  SELECT *
  FROM
    Bank.Branch
  ORDER BY
    Bank.Branch.num
;

END Bank_proc;
```

A.2.2 t2/driver.a

```
with text_io;
with Bank_def;
with Bank_proc;

procedure Test_driver is

  use text_io;
  use Bank_def;
  use Bank_proc;
  use customer_name_domain_ops;
  use addr_domain_ops;
  use city_domain_ops;
  use state_domain_ops;
```

```

use balance_domain_ops;
use branch_assets_domain_ops;

--
--   I/O declarations
--
subtype prompt_length is integer range 1..60;
subtype prompt_line is string (1..prompt_length'last);
subtype prompt_index is integer range 1..9;
type test_count is range 1..18;
type prompt_array is array(prompt_index) of prompt_line;
beginning : constant string := "Beginning SAMeDL T2 test program";
heading : constant string :=
"TEST   DESCRIPTION           TEST   DESCRIPTION";
test_list : constant prompt_array := prompt_array'(
("PT1           CT4           "),
("PT2           CT5           "),
("PT3           CT6           "),
("PT4           CT7           "),
("PT5           CT8           "),
("PT6           CT9           "),
("CT1           CT10          "),
("CT2           CT11          "),
("CT3           "));
prompt1: constant string :=
"Enter starting test number or A to run entire test set:";
answer: string(1..80):=
";
line: prompt_index;
prompt2: constant string := " Try again (test letters must be
caps)";
prompt_count : integer range 1..10 := 1;
length: natural range 0..80;
test_number : test_count := 1;
found : boolean := false;

--
--   database interaction declarations
--
type customer_index is range 1..16;
type checking_index is range 1..14;
type savings_index is range 1..17;
type loan_index is range 1..12;
type branch_index is range 1..4;
type customer_rec is
  record
    name      :      customer_name_domain_not_null;
    ssn       :      ssn_domain_not_null;
    street    :      addr_domain_not_null;
    city      :      city_domain_not_null;
    state     :      state_domain_not_null;
  end record;

type Savings_rec is
  record
    acct_num  :      acct_num_domain_not_null;
    balance  :      balance_domain_not_null;

```

```
        cust_ssn      :    ssn_domain_not_null;
        branch_num    :    branch_num_domain_not_null;
    end record;

type Checking_rec IS
    record
        acct_num      :    acct_num_domain_not_null;
        balance :      balance_domain_not_null;
        cust_ssn      :    ssn_domain_not_null;
        branch_num    :    branch_num_domain_not_null;
    end record;

type loan_rec IS
    record
        acct_num      :    acct_num_domain_not_null;
        balance :      balance_domain_not_null;
        loan_type      :    loan_type_domain_not_null;
        cust_ssn      :    ssn_domain_not_null;
        branch_num    :    branch_num_domain_not_null;
    end record;

type Branch_rec IS
    record
        branch_num    :    branch_num_domain_not_null;
        assets :      branch_assets_domain_not_null;
    end record;

type customer_array is array (customer_index) of customer_rec;
type checking_array is array (checking_index) of checking_rec;
type savings_array is array (savings_index) of savings_rec;
type loan_array is array (loan_index) of loan_rec;
type branch_array is array (branch_index) of branch_rec;

customers : constant customer_array := customer_array'(
    ("Scarlett      ",111111111,"Byrd      ", "Potomac
", "Md"),
    ("Smith         ",111345678,"North     ", "Gaithersburg
", "Md"),
    ("Glenn         ",123456789,"Sand Hill", "Potomac
", "Md"),
    ("Green         ",123546789,"Walnut   ", "Bethesda
", "Md"),
    ("Brown         ",123987654,"Chestnut", "Alexandria
", "Va"),
    ("Plum          ",132549876,"Bethesda", "Bethesda
", "Md"),
    ("Mustard       ",222222222,"Spice    ", "Hyattsville
", "Md"),
    ("Jones         ",222345678,"Main     ", "Arlington
", "Va"),
    ("Hayes         ",333345678,"Bridge   ", "Potomac
", "Md"),
    ("Curry        ",444345678,"Tree     ", "Columbia
", "Md"),
    ("Lindsay       ",555345678,"Park     ", "Bethesda
", "Md"),
    ("Turner        ",666345678,"Putnam   ", "Fairfax
", "Va"),
```

```

        ("Williams      ", 777345678, "Nassau      ", "Gaithersburg
", "Md"),
        ("Adams         ", 888345678, "Spring     ", "Silver Spring
", "Md"),
        ("Brooks        ", 987654321, "Senator     ", "Washington
", "DC"),
        ("Johnson      ", 999345678, "Alma       ", "Silver Spring
", "Md"));

```

```

checking_list : constant checking_array := checking_array'(
    (1,1000.0,222345678,bethesda),
    (2,50.0,111345678,gaithersburg),
    (3,50000.0,333345678,potomac),
    (4,300.0,444345678,silver_spring),
    (5,2500.0,555345678,bethesda),
    (6,500.0,777345678,gaithersburg),
    (7,1500.0,888345678,silver_spring),
    (8,15000.0,123456789,potomac),
    (9,1250.0,987654321,bethesda),
    (10,-10.0,123546789,silver_spring),
    (11,150.0,123546789,gaithersburg),
    (12,350.0,123987654,potomac),
    (13,4500.0,132549876,bethesda),
    (14,40000.0,222222222,gaithersburg) );

```

```

savings_list : constant savings_array := savings_array'(
    (101,3000.0,222345678,bethesda),
    (102,4000.0,111345678,gaithersburg),
    (103,2000.0,111345678,potomac),
    (104,50.0,333345678,potomac),
    (105,1500.0,444345678,silver_spring),
    (106,50000.0,555345678,bethesda),
    (107,50000.0,555345678,silver_spring),
    (108,50000.0,555345678,potomac),
    (109,200.0,666345678,gaithersburg),
    (110,300.0,777345678,gaithersburg),
    (111,200.0,777345678,silver_spring),
    (112,4000.0,999345678,silver_spring),
    (113,200.0,123456789,potomac),
    (114,60000.0,987654321,bethesda),
    (115,10000.0,123546789,bethesda),
    (116,50000.0,132549876,potomac),
    (117,20.0,222222222,gaithersburg));

```

```

loan_list : constant loan_array := loan_array'(
    (201,3000.0,personal,111345678,gaithersburg),
    (202,300000.0,mortgage,333345678,potomac),
    (203,32000.0,auto,444345678,bethesda),
    (204,150000.0,mortgage,555345678,bethesda),
    (205,1500.0,personal,777345678,gaithersburg),
    (206,1500.0,personal,999345678,potomac),
    (207,50000.0,mortgage,123456789,potomac),
    (208,320000.0,mortgage,987654321,bethesda),
    (209,180000.0,mortgage,123546789,bethesda),
    (210,5000.0,auto,123987654,potomac),
    (211,240000.0,mortgage,132549876,potomac),
    (212,14000.0,auto,111111111,silver_spring));

```

```
branch_list : constant branch_array := branch_array'(
    (bethesda,814250.0),
    (silver_spring,71490.0),
    (gaithersburg,49720.0),
    (potomac,764100.0));

fetch_results : boolean := false;
test_results : boolean := false;
current_test : string(1..4) := " ";

procedure init_customer_db is

    customer_row : customer_index;
    next_customer: customer_rec;
    new_cust : new_customer_record;

begin
    init_customer: for customer_row in customer_index loop
        next_customer := customers(customer_row);
        assign (new_cust.new_name,with_null(next_customer.name));
        new_cust.new_ssn := next_customer.ssn;
        assign (new_cust.new_street,with_null(next_customer.street));
        assign (new_cust.new_city,with_null(next_customer.city));
        assign (new_cust.new_state,with_null(next_customer.state));
        new_customer (new_cust);
    end loop init_customer;
    commit_work;
end init_customer_db;

-- procedure verify_customer_db(verified: out boolean) is
function verify_customer_db return boolean is

    customer_row : customer_index;
    db_customer: list_customers.row_type;
    in_customer: customer_rec;
    is_same : boolean := true;

begin
    list_customers.open;
    check_customer: for customer_row in customer_index loop
        list_customers.fetch(db_customer,fetch_results);
        in_customer := customers(customer_row);
        is_same := is_same and
            (db_customer.bank_cust_cust_name
             = with_null(in_customer.name)) and
            (db_customer.bank_cust_ssn = in_customer.ssn) and
            (db_customer.bank_cust_street_addr
             = with_null(in_customer.street)) and
            (db_customer.bank_cust_city_addr
             = with_null(in_customer.city)) and
            (db_customer.bank_cust_state_addr
             = with_null(in_customer.state));
    end loop check_customer;
-- verified := is_same;
    list_customers.close;
    commit_work;
    return is_same;
```

```

end verify_customer_db;

Procedure init_checking_db is
  input_entry  : checking_rec;
  db_entry     : chequeing_entry;
  checking_row : checking_index;
begin
  init_checking: for checking_row in checking_index loop
    input_entry := checking_list(checking_row);
    db_entry.acct_num := input_entry.acct_num;
    db_entry.cust_ssn := input_entry.cust_ssn;
    assign (db_entry.balance , with_null(input_entry.balance));
    assign (db_entry.branch_num ,
            with_null(input_entry.branch_num));
    new_chequeing (db_entry);
  end loop init_checking;
  commit_work;
end init_checking_db;

--  procedure verify_checking_db (verified : out boolean ) is
function verify_checking_db return boolean is

  checking_row : checking_index;
  db_checking: list_chequeing.row_type;
  in_checking: checking_rec;
  is_same : boolean := true;

begin
  list_chequeing.open;
  check_checking: for checking_row in checking_index loop
    in_checking := checking_list(checking_row);
    list_chequeing.fetch(db_checking, fetch_results);
    is_same := is_same and
      (db_checking.bank_cheque_acct_num = in_checking.acct_num) and
      (db_checking.bank_cheque_cust_ssn = in_checking.cust_ssn) and
      (db_checking.bank_cheque_balance = with_null(in_checking.balance))
and
    (db_checking.bank_cheque_branch_num
     = with_null(in_checking.branch_num));
  end loop check_checking;
--  verified := is_same;
  list_chequeing.close;
  commit_work;
  return is_same;
end verify_checking_db;

procedure init_savings_db is

  input_entry  : savings_rec;
  db_entry     : savings_entry;
  savings_row  : savings_index;
begin
  init_savings: for savings_row in savings_index loop
    input_entry := savings_list(savings_row);
    db_entry.acct_num := input_entry.acct_num;
    db_entry.cust_ssn := input_entry.cust_ssn;
    assign (db_entry.balance , with_null(input_entry.balance));

```

```
        assign (db_entry.branch_num ,
                with_null(input_entry.branch_num));
        new_savings (db_entry);
    end loop init_savings;
    commit_work;
end init_savings_db;

--  procedure verify_savings_db (verified : out boolean ) is
function verify_savings_db return boolean is

    savings_row : savings_index;
    db_savings: list_savings.row_type;
    in_savings: savings_rec;
    is_same : boolean := true;

begin
    list_savings.open;
    check_savings: for savings_row in savings_index loop
        in_savings := savings_list(savings_row);
        list_savings.fetch(db_savings,fetch_results);
        is_same := is_same and
            (db_savings.bank_savings_acct_num = in_savings.acct_num) and
            (db_savings.bank_savings_cust_ssn = in_savings.cust_ssn) and
            (db_savings.bank_savings_balance = with_null(in_savings.balance))
    and
        (db_savings.bank_savings_branch_num =
with_null(in_savings.branch_num));
    end loop check_savings;
    list_savings.close;
    commit_work;
    return is_same;
end verify_savings_db;

procedure init_loan_db is

    input_entry : loan_rec;
    db_entry : loan_entry;
    loan_row : loan_index;
begin
    init_loan: for loan_row in loan_index loop
        input_entry := loan_list(loan_row);
        db_entry.acct_num := input_entry.acct_num;
        db_entry.cust_ssn := input_entry.cust_ssn;
        assign (db_entry.loan_type,
                with_null(input_entry.loan_type));
        assign (db_entry.balance , with_null(input_entry.balance));
        assign (db_entry.branch_num ,
                with_null(input_entry.branch_num));
        new_loan (db_entry);
    end loop init_loan;
    commit_work;
end init_loan_db;

--  procedure verify_loan_db (verified : out boolean ) is
function verify_loan_db return boolean is

    loan_row : loan_index;
```

```

db_loan: list_loans.row_type;
in_loan: loan_rec;
is_same : boolean := true;

begin
  list_loans.open;
  check_loan: for loan_row in loan_index loop
    in_loan := loan_list(loan_row);
    list_loans.fetch(db_loan,fetch_results);
    is_same := is_same and
      (db_loan.bank_loan_acct_num = in_loan.acct_num) and
      (db_loan.bank_loan_cust_ssn = in_loan.cust_ssn) and
      (db_loan.bank_loan_loan_type = with_null(in_loan.loan_type)) and
      (db_loan.bank_loan_balance = with_null(in_loan.balance)) and
      (db_loan.bank_loan_branch_num = with_null(in_loan.branch_num));
  end loop check_loan;
  list_loans.close;
  commit_work;
  return is_same;
end verify_loan_db;

procedure init_branch_db is

  input_entry : branch_rec;
  db_entry    : new_branch_entry;
  branch_row  : branch_index;

begin
  init_branch: for branch_row in branch_index loop
    input_entry := branch_list(branch_row);
    assign (db_entry.num,
      with_null(input_entry.branch_num));
    assign (db_entry.assets, with_null(input_entry.assets));
    new_branch ( db_entry);
  end loop init_branch;
  commit_work;
end init_branch_db;

-- procedure verify_branch_db (verified : out boolean) is
function verify_branch_db return boolean is

  branch_row : branch_index;
  db_branch: list_branches.row_type;
  in_branch: branch_rec;
  is_same : boolean := true;

begin
  list_branches.open;
  check_branch: for branch_row in branch_index loop
    in_branch := branch_list(branch_row);
    list_branches.fetch(db_branch,fetch_results);
    is_same := is_same and
      (db_branch.bank_branch_num =
with_null(in_branch.branch_num))
      and
      (db_branch.bank_branch_assets =
with_null(in_branch.assets));

```

```
        end loop check_branch;
--      verified := is_same;
        list_branches.close;
        commit_work;
        return is_same;
    end verify_branch_db;

procedure PT_1 ( results : out boolean) is
--
--  verify delete procedure
--
    subtype PT1_index is loan_index range 1..11;
    type PT1_array is array (PT1_index) of loan_rec;
    loan_list : constant PT1_array := PT1_array'(
        (201,3000.0,personal,111345678,gaithersburg),
        (202,300000.0,mortgage,333345678,potomac),
        (203,32000.0,auto,444345678,bethesda),
        (204,150000.0,mortgage,555345678,bethesda),
        (206,1500.0,personal,999345678,potomac),
        (207,50000.0,mortgage,123456789,potomac),
        (208,320000.0,mortgage,987654321,bethesda),
        (209,180000.0,mortgage,123546789,bethesda),
        (210,5000.0,auto,123987654,potomac),
        (211,240000.0,mortgage,132549876,potomac),
        (212,14000.0,auto,111111111,silver_spring));
    loan_number : acct_num_domain_not_null := 205;
    in_loan : loan_rec;
    db_loan : list_loans.row_type;
    loan_row : PT1_index := 1;
    good_check : boolean :=true;
begin
    delete_customer_loan (loan_number);
    commit_work;
    list_loans.open;
    while good_check and (loan_row < PT1_index'last) loop
        in_loan := loan_list(loan_row);
        list_loans.fetch(db_loan,fetch_results);
        good_check := good_check and
            (db_loan.bank_loan_acct_num = in_loan.acct_num) and
            (db_loan.bank_loan_cust_ssn = in_loan.cust_ssn) and
            (db_loan.bank_loan_loan_type = with_null(in_loan.loan_type)) and
            (db_loan.bank_loan_balance = with_null(in_loan.balance)) and
            (db_loan.bank_loan_branch_num = with_null(in_loan.branch_num));
        loan_row := loan_row + 1;
    end loop;
    list_loans.close;
    delete_loans;
    commit_work;
    init_loan_db;
    results := good_check;
end PT_1;

procedure PT_2 (results: out boolean) is
--
--  verify rollback procedure
--
begin
    delete_customers;
```

```

        rollback_work;
        results := verify_customer_db; --(results);
    end PT_2;

    procedure PT_3 (results: out boolean) is
    --
    -- verify select procedure
    --
        SSN : SSN_domain_not_null := 123456789;
        in_profile : customer_rec :=
            ("Glenn", 123456789, "Sand Hill", "Potomac", "Md");
        db_customer : customer_record;

        begin
            get_cust_profile (SSN, db_customer);
            results := (db_customer.cust_name = with_null(in_profile.name))
and
                        (db_customer.ssn = in_profile.ssn) and
                        (db_customer.street = with_null(in_profile.street)) and
                        (db_customer.city = with_null(in_profile.city)) and
                        (db_customer.state = with_null(in_profile.state)) ;
            rollback_work;
        end PT_3;

    procedure PT_4 (results: out boolean) is
    --
    -- verify update procedure (single row)
    --
        acct_num : acct_num_domain_not_null := 103;
        transaction : balance_domain_not_null := 100.0;
        savings_record : savings_entry;
        new_balance : balance_domain_not_null := 2100.0;

        begin
            Up_save_acct_bal(acct_num, with_null(transaction));
            get_save_record(acct_num, savings_record);
            results := with_null(new_balance) = savings_record.balance;
            rollback_work;
        end PT_4;

    procedure PT_5 ( results : out boolean ) is
    --
    -- verify update procedure (entire table)
    --

        loan_record : list_loans.row_type;
        zero : balance_domain_not_null := 0.0;
        is_zero : boolean := true;

        begin
            s_and_1;
            list_loans.open;
            verify : for loan_row in loan_index loop
                list_loans.fetch(loan_record, fetch_results);
                is_zero := is_zero and (loan_record.bank_loan_balance
                    = with_null(zero));
            end loop verify;

```

```

results := is_zero;
rollback_work;
end pt_5;

procedure PT_6 ( results : out boolean ) is
--
-- verify insert procedure (query)
--
type PT6_index is range 1..20;
type PT6_array is array (PT6_index) of savings_rec;
answer_array : constant PT6_array := PT6_array'(
    (12,350.0,123987654,potomac),
    (13,4500.0,132549876,bethesda),
    (14,40000.0,222222222,gaithersburg),
    (101,3000.0,222345678,bethesda),
    (102,4000.0,111345678,gaithersburg),
    (103,2000.0,111345678,potomac),
    (104,50.0,333345678,potomac),
    (105,1500.0,444345678,silver_spring),
    (106,50000.0,555345678,bethesda),
    (107,50000.0,555345678,silver_spring),
    (108,50000.0,555345678,potomac),
    (109,200.0,666345678,gaithersburg),
    (110,300.0,777345678,gaithersburg),
    (111,200.0,777345678,silver_spring),
    (112,4000.0,999345678,silver_spring),
    (113,200.0,123456789,potomac),
    (114,60000.0,987654321,bethesda),
    (115,10000.0,123546789,bethesda),
    (116,50000.0,132549876,potomac),
    (117,20.0,222222222,gaithersburg));
lower_bound : acct_num_domain_not_null := 12;
row_index : PT6_index;
is_same : boolean := true;
db_savings : list_savings.row_type;
in_savings : savings_rec;

begin
    move_cheque_to_save (lower_bound);
    list_savings.open;
    verify : for row_index in PT6_index loop
        in_savings := answer_array(row_index);
        list_savings.fetch(db_savings,fetch_results);
        is_same := is_same and
            (db_savings.bank_savings_acct_num = in_savings.acct_num) and
            (db_savings.bank_savings_cust_ssn = in_savings.cust_ssn) and
            (db_savings.bank_savings_balance = with_null(in_savings.balance))
    and
        (db_savings.bank_savings_branch_num =
with_null(in_savings.branch_num));
    end loop verify;
    list_savings.close;
    rollback_work;
    results := is_same;
end PT_6;

procedure CT_1 ( results: out boolean) is
--

```

```
-- verify cursor select with comparison predicate
--
type CT1_index is range 1..2;
type CT1_row is
    record
        ssn : ssn_domain_not_null;
        account_num : acct_num_domain_not_null;
        balance : balance_domain_not_null;
    end record;
type CT1_array is array (CT1_index) of CT1_row;
answer_array : constant ct1_array := ct1_array'(
    (111345678,102,4000.0),
    (111345678,103,2000.0));
row_num : CT1_index;
db_row : customer_accounts.row_type;
in_row : CT1_row;
ssn : ssn_domain_not_null := 111345678;
verified : boolean := true;
begin
    customer_accounts.open(ssn);
    verify : for row_num in CT1_index loop
        customer_accounts.fetch(db_row,fetch_results);
        in_row := answer_array(row_num);
        verified := verified and
            (db_row.cust_ssn = in_row.ssn) and
            (db_row.acct_num = in_row.account_num) and
            (db_row.balance = with_null(in_row.balance));
    end loop verify;
    results := verified;
    customer_accounts.close;
    rollback_work;
end CT_1;

procedure CT_2 ( results : out boolean) is
--
-- verify cursor select with >= predicate
--
type CT2_index is range 1..5;
type CT2_row is
    record
        acct_num : acct_num_domain_not_null;
        balance : balance_domain_not_null;
        ssn : ssn_domain_not_null;
        branch_num : branch_num_domain_not_null;
    end record;
type CT2_array is array (ct2_index) of CT2_row;
answer_array : constant ct2_array := ct2_array'(
    (202,300000.0,333345678,potomac),
    (204,150000.0,555345678,bethesda),
    (208,320000.0,987654321,bethesda),
    (209,180000.0,123546789,bethesda),
    (211,240000.0,132549876,potomac));
row_num : ct2_index;
in_row : ct2_row;
db_row : loans_over.row_type;
verified : boolean := true;
lower_bound : balance_domain_not_null := 150000.0;
```

```
begin
  loans_over.open(with_null(lower_bound));
  verify : for row_num in CT2_index loop
    loans_over.fetch(db_row,fetch_results);
    in_row := answer_array ( row_num );
    verified := verified and
      (db_row.acct_num = in_row.acct_num) and
      (db_row.balance = with_null(in_row.balance)) and
      (db_row.cust_ssn = in_row.ssn) and
      (db_row.branch_num = with_null(in_row.branch_num));
  end loop verify;
  results := verified;
  loans_over.close;
  rollback_work;
end CT_2;

procedure CT_3 (results : out boolean) is
--
-- verify cursor select with <= predicate
--
  type CT3_index is range 1..4;
  type CT3_row is
    record
      acct_num : acct_num_domain_not_null;
      balance   : balance_domain_not_null;
      ssn : ssn_domain_not_null;
      branch_num : branch_num_domain_not_null;
    end record;
  type CT3_array is array (ct3_index) of CT3_row;
  answer_array : constant ct3_array := ct3_array'(
    (201,3000.0,111345678,gaithersburg),
    (205,1500.0,777345678,gaithersburg),
    (206,1500.0,999345678,potomac),
    (210,5000.0,123987654,potomac));
  verified : boolean := true;
  row_num : ct3_index;
  db_row : loans_under.row_type;
  in_row : ct3_row;
  upper_bound : balance_domain_not_null := 5000.0;

  begin
    loans_under.open(with_null(upper_bound));
    verify : for row_num in CT3_index loop
      loans_under.fetch(db_row,fetch_results);
      in_row := answer_array(row_num);
      verified := verified and
        (db_row.acct_num = in_row.acct_num) and
        (db_row.balance = with_null(in_row.balance)) and
        (db_row.cust_ssn = in_row.ssn) and
        (db_row.branch_num = with_null(in_row.branch_num));
    end loop verify;
    results := verified;
    loans_under.close;
    rollback_work;
  end CT_3;

procedure CT_4 (results : out boolean) is
--
```

```

-- verify cursor select with > predicate
--
type CT4_index is range 1..7;
type CT4_row is
    record
        acct_num : acct_num_domain_not_null;
        balance : balance_domain_not_null;
    end record;
type CT4_array is array (ct4_index) of CT4_row;
answer_array : constant ct4_array := ct4_array'(
    (3,50000.0),
    (5,2500.0),
    (7,1500.0),
    (8,15000.0),
    (9,1250.0),
    (13,4500.0),
    (14,40000.0) );
db_row : cheque_bal_over.row_type;
in_row : ct4_row;
row_num : ct4_index;
verified : boolean := true;
lower_bound : balance_domain_not_null := 1001.0;

begin
cheque_bal_over.open(with_null(lower_bound));
verify : for row_num in CT4_index loop
    in_row := answer_array(row_num);
    cheque_bal_over.fetch(db_row,fetch_results);
    verified := verified and
        (db_row.acct_num = in_row.acct_num) and
        (db_row.balance = with_null(in_row.balance));
end loop verify;
results := verified;
cheque_bal_over.close;
rollback_work;
end CT_4;

procedure CT_5 (results : out boolean) is
--
-- verify cursor select with < predicate
--
type CT5_index is range 1..6;
type CT5_row is
    record
        acct_num : acct_num_domain_not_null;
        balance : balance_domain_not_null;
    end record;
type CT5_array is array (ct5_index) of CT5_row;
answer_array : constant ct5_array := ct5_array'(
    (104,50.0),
    (109,200.0),
    (110,300.0),
    (111,200.0),
    (113,200.0),
    (117,20.0));
db_row : save_bal_under.row_type;
in_row : ct5_row;
row_num : ct5_index;

```

```
verified : boolean := true;
upper_bound : balance_domain_not_null := 1500.0;

begin
save_bal_under.open(with_null(upper_bound));
verify : for row_num in CT5_index loop
    in_row := answer_array(row_num);
    save_bal_under.fetch(db_row,fetch_results);
    verified := verified and
        (db_row.acct_num = in_row.acct_num) and
        (db_row.balance = with_null(in_row.balance));
end loop verify;
results := verified;
save_bal_under.close;
rollback_work;
end CT_5;

procedure CT_6 (results : out boolean) is
--
-- verify cursor select with <> predicate
--
    type CT6_index is range 1..3;
    type CT6_array is array (ct6_index) of
branch_num_domain_not_null;
    answer_array : constant ct6_array := ct6_array'(
        (bethesda),
        (silver_spring),
        (gaithersburg));
    db_row : other_branches.row_type;
    in_row : branch_num_domain_not_null;
    row_num : ct6_index;
    verified : boolean := true;
    branch : branch_num_domain_not_null := potomac;

begin
other_branches.open(with_null(branch));
verify : for row_num in CT6_index loop
    other_branches.fetch(db_row,fetch_results);
    in_row := answer_array(row_num);
    verified := verified and
        (db_row.num = with_null(in_row));
end loop verify;
results := verified;
other_branches.close;
rollback_work;
end CT_6;

procedure CT_7 (results : out boolean) is
--
-- verify cursor select with between predicate
--
    type CT7_index is range 1..5;
    type CT7_array is array (ct7_index) of savings_rec;
    answer_array : constant ct7_array := ct7_array'(
        (106,50000.0,555345678,bethesda),
        (107,50000.0,555345678,silver_spring),
        (108,50000.0,555345678,potomac),
        (114,60000.0,987654321,bethesda),
```

```

        (116,50000.0,132549876,potomac));
db_row : large_deposits.row_type;
upper_bound : balance_domain_not_null := 60000.0;
lower_bound : balance_domain_not_null := 40000.0;
in_row : savings_rec;
row_num : ct7_index;
verified : boolean := true;

begin

large_deposits.open(with_null(lower_bound),with_null(upper_bound));

verify : for row_num in CT7_index loop
    in_row := answer_array(row_num);
    large_deposits.fetch(db_row,fetch_results);
    verified := verified and
    (db_row.bank_savings_acct_num = in_row.acct_num) and
    (db_row.bank_savings_cust_ssn = in_row.cust_ssn) and
    (db_row.bank_savings_balance = with_null(in_row.balance)) and
    (db_row.bank_savings_branch_num = with_null(in_row.branch_num));
end loop verify;
results := verified;
large_deposits.close;
rollback_work;
end CT_7;

procedure CT_8 (results : out boolean) is
--
-- verify cursor select with NOT BETWEEN predicate
--
type CT8_index is range 1..5;
type CT8_row is
    record
        acct_num : acct_num_domain_not_null;
        balance : balance_domain_not_null;
        ssn : ssn_domain_not_null;
    end record;
type CT8_array is array (ct8_index) of CT8_row;
answer_array : constant ct8_array := ct8_array'(
    (202,300000.0,333345678),
    (204,150000.0,555345678),
    (208,320000.0,987654321),
    (209,180000.0,123546789),
    (211,240000.0,132549876));
upper_bound : balance_domain_not_null := 60000.0;
lower_bound : balance_domain_not_null := 20.0;
db_row : large_loans.row_type;
in_row : CT8_row;
row_num : ct8_index;
verified : boolean := true;

begin
large_loans.open(with_null(lower_bound),with_null(upper_bound));
verify : for row_num in CT8_index loop
    in_row := answer_array (row_num);
    large_loans.fetch(db_row,fetch_results);
    verified := verified and
    (db_row.acct_num = in_row.acct_num) and

```

```
(db_row.cust_ssn = in_row.ssn) and
(db_row.balance = with_null(in_row.balance));
end loop verify;
results := verified;
large_loans.close;
rollback_work;
end CT_8;

procedure CT_9 (results : out boolean) is
--
-- verify cursor IN predicate
--
type CT9_index is range 1..5;
type CT9_array is array (ct9_index) of loan_rec;
answer_array : constant ct9_array := ct9_array'(
    (202,300000.0,mortgage,333345678,potomac),
    (206,1500.0,personal,999345678,potomac),
    (207,50000.0,mortgage,123456789,potomac),
    (210,5000.0,auto,123987654,potomac),
    (211,240000.0,mortgage,132549876,potomac));
verified : boolean := true;
in_row : loan_rec;
db_row : loan_count.row_type;
row_num : ct9_index;
branch : branch_num_domain_not_null := potomac;

begin
loan_count.open(with_null(branch));
verify : for row_num in CT9_index loop
    in_row := answer_array(row_num);
    loan_count.fetch(db_row,fetch_results);
    verified := verified and
        (db_row.bank_loan_acct_num = in_row.acct_num) and
        (db_row.bank_loan_cust_ssn = in_row.cust_ssn) and
        (db_row.bank_loan_loan_type = with_null(in_row.loan_type)) and
        (db_row.bank_loan_balance = with_null(in_row.balance)) and
        (db_row.bank_loan_branch_num = with_null(in_row.branch_num));
end loop verify;
results := verified;
loan_count.close;
rollback_work;
end CT_9;

procedure CT_10 (results : out boolean) is
--
-- verify cursor like predicate
--
type CT10_index is range 1..2;
type CT10_array is array (ct10_index) of
customer_name_domain_not_null;
answer_array : constant ct10_array := ct10_array'(
    ("Johnson"),
    ("Jones"));
db_row : find_customer.row_type;
in_row : customer_name_domain_not_null;
row_num : ct10_index;
verified : boolean := true;
name_in : customer_name_domain_not_null := "J%";
```

```
-- name_in : customer_name_domain_not_null := "J_____";

begin
find_customer.open(with_null(name_in));
verify : for row_num in CT10_index loop
    find_customer.fetch(db_row,fetch_results);
    in_row := answer_array(row_num);
    verified := verified and
        (db_row.cust_name = with_null(in_row));
end loop verify;
results := verified;
find_customer.close;
rollback_work;
end CT_10;

procedure CT_11 (results : out boolean) is
--
-- verify cursor procedures
--
    new_record : constant customer_rec := customer_rec'
        ("Smith",111345678,"South", "Gaithersburg", "Md");
    search_ssn : ssn_domain_not_null := 111345678;
    db_street : addr_domain_type;
    new_street : addr_domain_not_null := "South";
    customer_row : customer_index := 1;
    verified : boolean := false;
    db_row : fetch_customer_record;
    sqlval : sql_enum;

begin
customer_list.open_customer;
customer_list.fetch_customer(db_row,sqlval);
-- Check Status Code
    if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
        results := false;
        return;
    elsif sqlval = SQL_FOUND then
        customer_row := customer_row + 1;
    else
        results := false;
        return;
    end if;
    while (db_row.bank_cust_ssn /= search_ssn) and
        (customer_row < customer_index'last) loop
        customer_list.fetch_customer(db_row,sqlval);
-- Check Status Code
        if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
            results := false;
            return;
        elsif sqlval = SQL_FOUND then
            customer_row := customer_row + 1;
        else
            results := false;
            return;
        end if;
    end loop;
    if db_row.bank_cust_ssn = search_ssn then
```

```
assign (db_street,with_null(new_street));
customer_list.update_customer(db_street);
customer_list.close_customer;
commit_work;
customer_list.open_customer;
customer_row := 1;
customer_list.fetch_customer(db_row,sqlval);
-- Check Status Code
if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
    results := false;
    return;
elsif sqlval = SQL_FOUND then
    null;
else
    results := false;
    return;
end if;
while (db_row.bank_cust_ssn /= search_ssn) and
(customer_row < customer_index'last) loop
    customer_list.fetch_customer(db_row,sqlval);
-- Check Status Code
    if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
        results := false;
        return;
    elsif sqlval = SQL_FOUND then
        customer_row := customer_row + 1;
    else
        results := false;
        return;
    end if;
end loop;
verified := (db_row.bank_cust_ssn = search_ssn) and
( db_row.bank_cust_street_addr = db_street );
customer_list.close_customer;
else
    verified := false;
end if;
-- Update the customer street addr to null
if verified then
    customer_list.open_customer;
    customer_list.fetch_customer(db_row,sqlval);
-- Check Status Code
    if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
        results := false;
        return;
    elsif sqlval = SQL_FOUND then
        customer_row := customer_row + 1;
    else
        results := false;
        return;
    end if;
while (db_row.bank_cust_ssn /= search_ssn) and
(customer_row < customer_index'last) loop
    customer_list.fetch_customer(db_row,sqlval);
-- Check Status Code
    if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
        results := false;
        return;
```

```

        elsif sqlval = SQL_FOUND then
            customer_row := customer_row + 1;
        else
            results := false;
            return;
        end if;
    end loop;
    if db_row.bank_cust_ssn = search_ssn then
        customer_list.update_customer_null;
        customer_list.close_customer;
        commit_work;
        customer_list.open_customer;
        customer_row := 1;
        customer_list.fetch_customer(db_row, sqlval);
    -- Check Status Code
        if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
            results := false;
            return;
        elsif sqlval = SQL_FOUND then
            null;
        else
            results := false;
            return;
        end if;
        while (db_row.bank_cust_ssn /= search_ssn) and
            (customer_row < customer_index'last) loop
            customer_list.fetch_customer(db_row, sqlval);
    -- Check Status Code
            if sqlval = SQL_NOT_FOUND or sqlval = SQL_ERROR then
                results := false;
                return;
            elsif sqlval = SQL_FOUND then
                customer_row := customer_row + 1;
            else
                results := false;
                return;
            end if;
        end loop;
        verified := (db_row.bank_cust_ssn = search_ssn) and
            is_null(db_row.bank_cust_street_addr);
        customer_list.close_customer;
    else
        verified := false;
    end if;
end if;
if verified then
    declare
        cust_row : cust_null_count.row_type;
        isok      : boolean;
    begin
        cust_null_count.open;
        cust_null_count.fetch(cust_row, isok);
        if isok = FALSE then
            results := false;
            return;
        end if;
        results := (cust_row.ssn = search_ssn);
    end;
end;

```

```
        else
            results := false;
        end if;
        rollback_work;
        end CT_11;

begin
    put_line(beginning);
    put_line(heading);
    loop1: for line in prompt_index loop
        put_line(test_list(line));
    end loop loop1;
    put(prompt1);
    while not found and (prompt_count < 10) loop
        prompt_count := prompt_count + 1;
        get_line(answer,length);
        case length is
            when 1 =>
                case answer(1) is
                    when 'a' | 'A' =>
                        found := true;
                        test_number := 1;
                    when others =>
                        put(prompt2);
                    end case;
            when 2 =>
                if (answer(1..2) = "a1") or
                   (answer(1..2) = "A1") or
                   (answer(1..2) = "aL") or
                   (answer(1..2) = "AL") then
                    found:= true;
                    test_number := 1;
                else
                    put(prompt2);
                end if;
            when 3 =>
                if answer(1..3) = "PT1" then
                    found := true;
                    test_number := 1;
                elsif answer(1..3) = "PT2" then
                    found:= true;
                    test_number := 2;
                elsif answer(1..3) = "PT3" then
                    found:= true;
                    test_number := 3;
                elsif answer(1..3) = "PT4" then
                    found:= true;
                    test_number := 4;
                elsif answer(1..3) = "PT5" then
                    found:= true;
                    test_number := 5;
                elsif answer(1..3) = "PT6" then
                    found:= true;
                    test_number := 6;
                elsif answer(1..3) = "CT1" then
                    found:= true;
                    test_number := 7;
                end if;
            end case;
        end while;
    end;
```

```

        elsif answer(1..3) = "CT2" then
            found:= true;
            test_number := 8;
        elsif answer(1..3) = "CT3" then
            found:= true;
            test_number := 9;
        elsif answer(1..3) = "CT4" then
            found:= true;
            test_number := 10;
        elsif answer(1..3) = "CT5" then
            found:= true;
            test_number := 11;
        elsif answer(1..3) = "CT6" then
            found:= true;
            test_number := 12;
        elsif answer(1..3) = "CT7" then
            found:= true;
            test_number := 13;
        elsif answer(1..3) = "CT8" then
            found:= true;
            test_number := 14;
        elsif answer(1..3) = "CT9" then
            found:= true;
            test_number := 15;
        else
            put (prompt2);
        end if;

    when 4 =>
        if answer(1..4) = "CT10" then
            found := true;
            test_number := 16;
        elsif answer(1..4) = "CT11" then
            found := true;
            test_number := 17;
        else
            put (prompt2);
        end if;
    when others =>
        put(prompt2);
    end case;
end loop;
if prompt_count >= 10 then
    put_line("exceeded attempt limit: try again later");
else
    connect_bank;
    init_customer_db;
    test_results := verify_customer_db; --(test_results);
    if test_results then
        init_checking_db;
        test_results := verify_checking_db; --(test_results);
        if test_results then
            init_savings_db;
            test_results := verify_savings_db; --(test_results);
            if test_results then
                init_loan_db;
                test_results := verify_loan_db; --(test_results);
                if test_results then

```

```
        init_branch_db;
        test_results := verify_branch_db; --(test_results);
        if test_results then
            put_line
                (" databases initialize successfully");
        else
            put_line
                (" Branch database failed to initialize");
        end if;
    else
        put_line
            ("Loan database failed to initialize");
        end if;
    else
        put_line
            ("Savings database failed to initialize");
        end if;
    else
        put_line ("Checking database failed to initialize");
        end if;
else
    put_line ("Customer database failed to initialize");
end if;

if test_results = true then
    while test_number < test_count'last loop
        case test_number is
            when 1 =>
                current_test := "PT1 ";
                PT_1(test_results);
            when 2 =>
                current_test := "PT2 ";
                PT_2(test_results);
            when 3 =>
                current_test := "PT3 ";
                PT_3(test_results);
            when 4 =>
                current_test := "PT4 ";
                PT_4(test_results);
            when 5 =>
                current_test := "PT5 ";
                PT_5(test_results);
            when 6 =>
                current_test := "PT6 ";
                PT_6(test_results);
            when 7 =>
                current_test := "CT1 ";
                CT_1(test_results);
            when 8 =>
                current_test := "CT2 ";
                CT_2(test_results);
            when 9 =>
                current_test := "CT3 ";
                CT_3(test_results);
            when 10 =>
                current_test := "CT4 ";
                CT_4(test_results);
            when 11 =>
```

```

        current_test := "CT5 ";
        CT_5(test_results);
    when 12 =>
        current_test := "CT6 ";
        CT_6(test_results);
    when 13 =>
        current_test := "CT7 ";
        CT_7(test_results);
    when 14 =>
        current_test := "CT8 ";
        CT_8(test_results);
    when 15 =>
        current_test := "CT9 ";
        CT_9(test_results);
    when 16 =>
        current_test := "CT10";
        CT_10(test_results);
    when 17 =>
        current_test := "CT11";
        CT_11(test_results);
    when others =>
        put_line ("we should not be here");
    end case;

    put (current_test);
    if test_results = false then
        put_line(" has failed");
        exit;
    else
        put_line(" has passed");
        test_number := test_number +1;
    end if;
end loop;
put_line (" the test set is complete");
end if;
end if;
end Test_driver;

```

A.2.3 t2/initbank.sql

```

create table cust
(cust_name      CHAR(15),
 SSN            INTEGER NOT NULL,
 Street_addr    CHAR(15),
 City_addr      CHAR(15),
 State_addr     CHAR(15));

create table savings
(Branch_num      SMALLINT,
 acct_num        SMALLINT NOT NULL,
 Balance         DECIMAL(12,2),
 cust_ssn        INTEGER NOT NULL);

create table cheque
(Branch_num      SMALLINT,
 acct_num        SMALLINT NOT NULL,
 Balance         DECIMAL(12,2),
 cust_ssn        INTEGER NOT NULL);

create table loan
(Branch_num      SMALLINT,

```

```
    acct_num      SMALLINT NOT NULL,  
    Balance       DECIMAL(12,2),  
    Loan_type     SMALLINT,  
    cust_ssn      INTEGER NOT NULL);  
create TABLE branch  
  (Num            SMALLINT,  
   Assets         DECIMAL(12,2) );
```

A.2.4 t2/initi.sql

```
create TABLE bank.cust  
  (Name          CHAR(15),  
   SSN           INTEGER NOT NULL,  
   Street_addr   CHAR(15),  
   City_addr     CHAR(15),  
   State_addr    CHAR(15));  
create TABLE bank.savings  
  (Branch_num    SMALLINT,  
   acct_num      SMALLINT NOT NULL,  
   Balance       DECIMAL(12,2),  
   cust_ssn      INTEGER NOT NULL);  
create TABLE bank.cheque  
  (Branch_num    SMALLINT,  
   acct_num      SMALLINT NOT NULL,  
   Balance       DECIMAL(12,2),  
   cust_ssn      INTEGER NOT NULL);  
create TABLE bank.loan  
  (Branch_num    SMALLINT,  
   acct_num      SMALLINT NOT NULL,  
   Balance       DECIMAL(12,2),  
   Loan_type     SMALLINT,  
   cust_ssn      INTEGER NOT NULL);  
create TABLE bank.branch  
  (Num            SMALLINT,  
   Assets         DECIMAL(12,2) );
```

A.3 Error Tests

A.3.1 t1/etl.sme

```
definition module d_etl is  
  -- Member Information  
  domain MemName is new SQL_CHAR Not Null (Length => 30);  
  domain SSN is new SQL_CHAR Not Null (Length => 9);  
  domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);  
  
  enumeration SexEnum is (F, M);  
  domain Sex is new SQL_ENUMERATION_AS_INT (  
    Enumeration => SexEnum, Map => Pos);  
  
  domain Phone is new SQL_CHAR (Length => 8);  
  domain Street is new SQL_CHAR (Length => 30);  
  domain City is new SQL_CHAR (Length => 15);  
  
  domain County is new SQL_CHAR Not Null (Length => 2);  
  
  domain Club_Number is new SQL_SMALLINT Not Null;
```

```

domain Sum_Domain is new SQL_SMALLINT Not Null;
domain Count_Domain is new SQL_INT;

end d_et1;

with d_et1; use d_et1;
schema module s_recdb is
  table Members is
    MemberName not null : MemName,
    MemberSSN not null  : SSN,
    ClubNumber not null : Club_Number,
    MemberAge   : Age,
    MemberSex   : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity  : City,
    MemberCnty not null : County
  end Members;

end s_recdb;

with d_et1; use d_et1;
abstract module a_et1 is
  authorization s_recdb

  record MemberRec is
    R_MemberName : MemName;
    R_Sum        : Sum_Domain;
    R_Count      : Count_Domain;
  end;

  -- Check row record conformance
  procedure PD_MemberSelect (Req_MemberSSN : SSN) is
    select MemberName, SUM(MemberAge), COUNT(*)
      -- ERR      ^      ^
    from s_recdb.Members
      where s_recdb.Members.MemberSSN = Req_MemberSSN ;

  cursor MemberSelect (Req_MemberSSN : SSN) for
    select MemberName, SUM(MemberAge), COUNT(*)
      -- ERR      ^      ^
    from s_recdb.Members
      where s_recdb.Members.MemberSSN = Req_MemberSSN ;
  is
    procedure FetchIt is
      fetch into Row : MemberRec;
      -- ERR      ^
    end MemberSelect;

  cursor D_MemberSelect (Req_MemberSSN : SSN) for
    select MemberName, SUM(MemberAge), COUNT(*)
      -- ERR      ^      ^
    from s_recdb.Members
      where s_recdb.Members.MemberSSN = Req_MemberSSN ;
  is
    procedure FetchIt is

```

```
        fetch;
    end D_MemberSelect;

end a_et1;
```

A.3.2 t1/et2.sme

```
DEFINITION MODULE d_et2 IS
    DOMAIN Branch_assets_domain IS
        NEW SQL_REAL NOT NULL (L => 0.0, R => 1E+10);
        -- Illegal Literal ^^
END d_et2;
```

A.3.3 t1/et3.sme

```
DEFINITION MODULE E_et3 IS

    DOMAIN Customer_name_domain IS
        NEW SQL_CHAR(length => 50);

    RECORD Customer_record IS
        CName      : Customer_name_domain;
    END customer_record;

END E_et3;

WITH E_et3;
USE E_et3;
SCHEMA MODULE T1_III IS

    TABLE Customer IS
        CName      : Customer_name_domain
    END Customer;

END T1_III;

WITH E_et3;
USE E_et3;
ABSTRACT MODULE A_et3 IS
    AUTHORIZATION T1_III

    CURSOR find_customer (name_in : customer_name_domain) FOR
        SELECT
            T1_III.customer.Cname
        FROM
            T1_III.customer
        WHERE
            name_in LIKE T1_III.customer.Cname
            -- ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^ Can only be input parm,
            -- literal, or USER

        ;

END A_et3;
```

A.3.4 t1/et4.sme

```
definition module D_et4 is
    -- Member Information
```

```

domain MemName is new SQL_CHAR Not Null (Length => 30);
domain SSN is new SQL_CHAR Not Null (Length => 9);
domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

enumeration SexEnum is (F, M);
domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, MAP => POS);

domain Phone is new SQL_CHAR (Length => 8);
domain Street is new SQL_CHAR (Length => 30);
domain City is new SQL_CHAR (Length => 15);

domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;
domain Sum_Domain is new SQL_SMALLINT Not Null;
domain Count_Domain is new SQL_INT;

end D_et4;

with D_et4; use D_et4;
schema module RecDB is
    table Members is
        MemberName not null    : MemName,
        MemberSSN not null     : SSN,
        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null    : County
    end Members;

    table Members2 is
        MemberName2 not null    : MemName,
        MemberSSN2 not null     : SSN,
        ClubNumber2 not null    : Club_Number,
        MemberAge2      : Age,
        MemberSex2      : Sex,
        MemberPhone2    : Phone,
        MemberStreet2   : Street,
        MemberCity2     : City,
        MemberCnty2 not null    : County
    end Members2;

end RecDB;

with D_et4; use D_et4;
abstract module A_et4 is
    authorization RecDB

    record MemberRec is
        R_MemberName      : MemName;
        R_Sum              : Sum_Domain;
        R_Count            : Count_Domain;

```

```
end;

procedure PD_MemberSelect (Req_MemberSSN : SSN) is
  select MemberName, SUM(MemberAge), COUNT(*)
  -- May not be NO_DOMAIN ^ ^
  from RecDB.Members
  where RecDB.Members.MemberSSN = Req_MemberSSN ;

  cursor MemberSelect (Req_MemberSSN : SSN) for
    select MemberName, SUM(MemberAge), COUNT(*)
  -- May not be NO_DOMAIN ^ ^
    from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN ;
  is
    procedure FetchIt is
      fetch into Row : MemberRec;
    end MemberSelect;

    cursor D_MemberSelect (Req_MemberSSN : SSN) for
      select MemberName, SUM(MemberAge), COUNT(*)
  -- May not be NO_DOMAIN ^ ^
      from RecDB.Members
      where RecDB.Members.MemberSSN = Req_MemberSSN ;
    is
      procedure FetchIt is
        fetch;
      end D_MemberSelect;
end A_et4;
```

A.3.5 t1/et5.sme

-- Check for various type/domain inconsistencies

DEFINITION MODULE d_et5 IS

--

-- enumeration declarations

--

ENUMERATION Branches IS

(Bethesda,
Silver_Spring,
Gaithersburg,
Potomac);

ENUMERATION Loan_types IS

(mortgage,
auto,
personal);

--

-- domain character declarations

--

DOMAIN Customer_name_domain IS

NEW SQL_CHAR(length => 15);

DOMAIN Addr_domain IS

NEW SQL_CHAR(length => 15);

DOMAIN City_domain IS

NEW SQL_CHAR(length => 15);

DOMAIN State_domain IS

```

    NEW SQL_CHAR(length => 2);
--
-- domain integer declarations
--
DOMAIN SSN_domain IS
    NEW SQL_INT NOT NULL ( FIRST => 0, LAST => 999999999);
DOMAIN acct_num_domain IS
    NEW SQL_SMALLINT NOT NULL ( FIRST => 0, LAST => 9999);
--
-- domain real declarations
--
DOMAIN Balance_domain IS
    NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
    NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
    NEW SQL_REAL;
DOMAIN Branch_assets_domain IS
    NEW SQL_REAL;

--
-- domain enumeration declarations
--
DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_int
    (ENUMERATION => Loan_types, MAP => POS);
DOMAIN branch_num_domain IS
    NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
    Cust_Name      : Customer_name_domain;
    SSN            : SSN_domain;
    Street         : Addr_domain;
    City           : City_domain;
    State          : State_domain;
END customer_record;

RECORD Savings_entry IS
    branch_num     : branch_num_domain;
    acct_num       : acct_num_domain;
    Balance        : Balance_domain;
    cust_ssn       : SSN_domain;
END Savings_entry;

RECORD Chequeing_entry IS
    branch_num     : branch_num_domain;
    acct_num       : acct_num_domain;
    Balance        : Balance_domain;
    cust_ssn       : SSN_domain;
END Chequeing_entry;

RECORD loan_entry IS
    branch_num     : branch_num_domain;
    acct_num       : acct_num_domain;
    Balance        : Balance_domain;

```

```
        Loan_type    : Loan_type_domain;
        cust_ssn     : SSN_domain;
    END loan_entry;

    RECORD Branch_entry IS
        branch_num    : branch_num_domain ;
        Assets        : Branch_assets_domain;
    END Branch_entry;

END d_et5;

WITH d_et5;
USE d_et5;
SCHEMA MODULE s_et5 IS
--
-- Basic customer information
--
    TABLE Cust IS
        Cust_Name      : Customer_name_domain,
        SSN not null    : SSN_domain,
        Street_addr    : Addr_domain,
        City_addr      : City_domain,
        State_addr     : State_domain
    END cust;
--
-- Checking account
--
    TABLE cheque IS
        branch_num      : branch_num_domain,
        acct_num not null : acct_num_domain,
        Balance         : Balance_domain,
        cust_ssn not null : SSN_domain
    END cheque;
--
-- Savings account
--
    TABLE Save IS
        branch_num      : branch_num_domain,
        acct_num not null : acct_num_domain,
        Balance         : Balance_domain,
        cust_ssn not null : SSN_domain
    END Save;
--
-- loan account
--
    TABLE loan IS
        branch_num      : branch_num_domain,
        acct_num not null : acct_num_domain,
        Balance         : Balance_domain,
        Loan_type       : loan_type_domain,
        cust_ssn not null : SSN_domain
    END loan;
--
-- Branch information
--
    TABLE Branch IS
        num             : branch_num_domain ,
        Assets          : Branch_assets_domain
```

```

        END Branch;

END s_et5;

WITH d_et5;
USE d_et5;
ABSTRACT MODULE a_et5 IS
    AUTHORIZATION s_et5

    CURSOR large_deposits1
        ( upper_bound :balance_domain) FOR
        SELECT *
        FROM
            s_et5.save
        WHERE
            s_et5.save.balance = (SELECT Cust_SSN FROM s_et5.save
                                   where s_et5.save.balance = 0.0)
-- ERR
;
--
    CURSOR large_deposits2
        ( upper_bound :balance_domain) FOR
        SELECT *
        FROM
            s_et5.save
        WHERE
            s_et5.save.balance = (SELECT balance FROM s_et5.save
                                   where s_et5.save.balance = 0.0)
-- OK
;
--
    CURSOR large_deposits3
        ( upper_bound :balance_domain) FOR
        SELECT *
        FROM
            s_et5.save
        WHERE
            s_et5.save.balance = (SELECT * FROM s_et5.save
                                   where s_et5.save.balance = 0.0)
-- ERR
;
--
    CURSOR large_deposits4
        ( upper_bound :balance_domain) FOR
        SELECT *
        FROM
            s_et5.save
        WHERE
            s_et5.save.balance
                BETWEEN 0 -- ERR
                AND upper_bound
;
--
    CURSOR large_deposits5
        ( upper_bound :balance_domain) FOR
        SELECT *
        FROM
            s_et5.save

```

```
WHERE
    s_et5.save.balance
        BETWEEN interest_rate_domain(0.0) -- ERR
        AND upper_bound
;

PROCEDURE Delete_customer_loan
    (loan_number_in : acct_num_domain) IS
DELETE FROM
    s_et5.Loan
WHERE
    SSN_domain(s_et5.Loan.acct_num) = loan_number_in; -- ERR

CURSOR loans_over(loan_balance_in : balance_domain) FOR
SELECT
    s_et5.Loan.acct_num,
    s_et5.Loan.branch_num,
    s_et5.Loan.cust_ssn,
    s_et5.Loan.balance
FROM
    s_et5.Loan
WHERE
    s_et5.Loan.balance >= Bethesda -- ERR
;

CURSOR loans_under(loan_balance_in : balance_domain) FOR
SELECT
    s_et5.Loan.acct_num,
    s_et5.Loan.branch_num,
    s_et5.Loan.cust_ssn,
    s_et5.Loan.balance
FROM
    s_et5.Loan
WHERE
    branch_num <= Bethesda -- OK
;

CURSOR large_loans
    ( lower_bound : balance_domain; upper_bound :balance_domain) FOR
SELECT
    s_et5.Loan.acct_num,
    s_et5.Loan.balance,
    s_et5.Loan.cust_ssn
FROM
    s_et5.Loan
WHERE
    Bethesda NOT BETWEEN Bethesda AND Bethesda -- ERR
;

--
-- like predicate
--
CURSOR find_customer (name_in : customer_name_domain) FOR
SELECT
    s_et5.cust.cust_name
FROM
    s_et5.cust
```

```

        WHERE
            s_et5.cust.cust_name LIKE 2.0  -- ERR
    ;
--
--    in predicate
--
    CURSOR Loan_count ( Branch_in: branch_num_domain ) FOR
        SELECT
            *
        FROM
            s_et5.Loan
        WHERE
            s_et5.Loan.Branch_num IN (Branch_in, Bethesda, Potomac) --
OK
    ;
--
    CURSOR Loan_count2 ( Branch_in: branch_num_domain ) FOR
        SELECT
            *
        FROM
            s_et5.Loan
        WHERE
            s_et5.Loan.Branch_num IN (Branch_in, Bethesda, auto) -- ERR
    ;
END a_et5;

```

A.3.6 t1/et6.sme

```

-- Tests error checking on constant decls

definition module d_et6 is
    -- Member Information
    domain MemName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    enumeration SexEN is (Female, Male);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        Enumeration => SexEnum, Map => Pos);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);
    domain City is new SQL_CHAR (Length => 15);

    domain County is new SQL_CHAR Not Null (Length => 2);

    domain Club_Number is new SQL_SMALLINT Not Null;
    domain Money is new SQL_REAL;

    constant C_Name1: MemName is '1234567890123456789012345678901'; --
ERR
    constant C_SSN : SSN is 123456789; -- ERR
    constant C_Club_Number : Club_Number is 10.0;
    constant C_Club_Number1: Club_Number is 10.0E+0; -- ERR
    constant C_M1 : Money is 39;
    constant C_M2 : Money is 39.0;
    constant C_M3 : Money is 39.E+0;

```

```
constant C_Sex is F; -- ERR
constant C_Sex1: Sex is Female; -- ERR
end d_et6;
```

A.3.7 t1/et7.sme

```
-- Check assignment conformance on selects

DEFINITION MODULE d_et7 IS
--
--    enumeration declarations
--
    ENUMERATION Branches IS
        ( Bethesda,
          Silver_Spring,
          Gaithersburg,
          Potomac);

    ENUMERATION Loan_types IS
        ( mortgage,
          auto,
          personal);
--
--    domain character declarations
--
    DOMAIN Customer_name_domain IS
        NEW SQL_CHAR(length => 15);
    DOMAIN Addr_domain IS
        NEW SQL_CHAR(length => 15);
    DOMAIN City_domain IS
        NEW SQL_CHAR(length => 15);
    DOMAIN State_domain IS
        NEW SQL_CHAR(length => 2);
--
--    domain integer declarations
--
    DOMAIN SSN_domain IS
        NEW SQL_INT NOT NULL ( FIRST => 0, LAST => 999999999);
    DOMAIN acct_num_domain IS
        NEW SQL_SMALLINT NOT NULL ( FIRST => 0, LAST => 9999);
--
--    domain real declarations
--
    DOMAIN Balance_domain IS
        NEW SQL_REAL;
    DOMAIN Interest_rate_domain IS
        NEW SQL_REAL( FIRST.=> 0.0, LAST => 1.0);
    DOMAIN Loan_payment_domain IS
        NEW SQL_REAL;
    DOMAIN Branch_assets_domain IS
        NEW SQL_REAL;
```

```
--
--      domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_int
    (ENUMERATION => Loan_types, MAP => POS);
DOMAIN branch_num_domain IS
  NEW SQL_ENUMERATION_AS_INT
    (ENUMERATION => Branches, MAP => POS);
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street         : Addr_domain;
  City           : City_domain;
  State          : State_domain;
END customer_record;

END d_et7;
```

```
WITH d_et7;
USE d_et7;
SCHEMA MODULE s_et7 IS
--
-- Basic customer information
--
TABLE Cust IS
    Cust_Name      : Customer_name_domain,
    SSN not null   : SSN_domain,
    Street_addr : Addr_domain,
    City_addr    : City_domain,
    State_addr   : State_domain
END cust;

--
-- Savings account
--
TABLE Save IS
    branch_num : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance     : Balance_domain,
    cust_ssn not null : SSN_domain
END Save;

END s_et7;
```

```

WITH d_et7;
USE d_et7;
ABSTRACT MODULE a_et7 IS
  AUTHORIZATION s_et7

  RECORD Savings_entry IS
    branch_num : branch_num_domain;
    acct_num   : acct_num_domain;
    Balance    : Balance_domain;
    cust_ssn   : SSN_domain;
  END Savings_entry;

  RECORD Savings_entry2 IS
    branch_num : branch_num_domain;
    acct_num   : acct_num_domain;
    Balance    : Balance_domain;
    cust_ssn   : SSN_domain;
    cust_ssn2  : SSN_domain;
  END Savings_entry2;

  RECORD Savings_entry3 IS
    branch_num : branch_num_domain;
    acct_num   : acct_num_domain;
    Balance    : Balance_domain;
  END Savings_entry3;

  RECORD Customer_record_plus IS
    branch_num : branch_num_domain;
    acct_num   : acct_num_domain;
    Balance    : Balance_domain;
    cust_ssn   : SSN_domain;

    Cust_Name   : Customer_name_domain;
    SSN         : SSN_domain;
    Street      : Addr_domain;
    City        : City_domain;
    State       : State_domain;
  END customer_record_plus;

  RECORD Customer_record_plus1 IS
    branch_num : branch_num_domain;
    acct_num   : acct_num_domain;
    Balance    : Balance_domain;
    cust_ssn   : SSN_domain;

    Cust_Name   : Customer_name_domain;
    SSN         : SSN_domain;
    Street      : Addr_domain;
    City        : City_domain;
    State       : State_domain;
    Statel      : State_domain;
  END customer_record_plus1;

  RECORD Customer_record_plus2 IS
    branch_num : branch_num_domain;
    acct_num   : acct_num_domain;
    Balance    : Balance_domain;

```

```
    cust_ssn      : SSN_domain;

    Cust_Name      : Customer_name_domain;
    SSN            : SSN_domain;
    Street         : Addr_domain;
    City          : City_domain;
END customer_record_plus2;

RECORD customer_record_minus is
    Cust_Name      : Customer_name_domain;
    Addr          : Addr_Domain;
    City          : City_domain;
    State         : State_domain;
END customer_record_minus;

PROCEDURE Get_save_record
    (acct_num_in : acct_num_domain) IS
    SELECT *
    INTO
        savings_record : savings_entry
    FROM
        s_et7.save
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record1
    (acct_num_in : acct_num_domain) IS
    SELECT * -- ERR
    INTO
        savings_record : savings_entry2
    FROM
        s_et7.save
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record2
    (acct_num_in : acct_num_domain) IS
    SELECT * -- ERR
    INTO
        savings_record : savings_entry3
    FROM
        s_et7.save
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record3
    (acct_num_in : acct_num_domain) IS
    SELECT *
    INTO
        savings_record : customer_record_plus
    FROM
        s_et7.save, cust
    WHERE
        s_et7.save.acct_num =
            acct_num_in;
```

```

PROCEDURE Get_save_record4
    (acct_num_in : acct_num_domain) IS
    SELECT * -- ERR
    INTO
        savings_record : customer_record_plus1
    FROM
        s_et7.save, cust
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record5
    (acct_num_in : acct_num_domain) IS
    SELECT * -- ERR
    INTO
        savings_record : customer_record_plus2
    FROM
        s_et7.save, cust
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record6
    (acct_num_in : acct_num_domain) IS
    SELECT branch_num, acct_num, Balance, cust_ssn
    INTO
        savings_record : savings_entry
    FROM
        s_et7.save
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record7
    (acct_num_in : acct_num_domain) IS
    SELECT branch_num, acct_num, Balance, cust_ssn --ERR
    INTO
        savings_record : savings_entry2
    FROM
        s_et7.save
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

PROCEDURE Get_save_record8
    (acct_num_in : acct_num_domain) IS
    SELECT branch_num, acct_num, Balance, cust_ssn --ERR
    INTO
        savings_record : savings_entry3
    FROM
        s_et7.save
    WHERE
        s_et7.save.acct_num =
            acct_num_in;

Cursor CGet_save_record
    (acct_num_in : acct_num_domain) FOR

```

```
SELECT *
FROM
    s_et7.save
WHERE
    s_et7.save.acct_num =
        acct_num_in;

IS
    procedure CFETCH IS FETCH INTO savings_record :
savings_entry;
END;

Cursor CGet_save_record1
    (acct_num_in : acct_num_domain) FOR
SELECT * -- ERR
FROM
    s_et7.save
WHERE
    s_et7.save.acct_num =
        acct_num_in;

IS
    procedure CFETCH IS FETCH INTO savings_record :
savings_entry2;
END;

Cursor CGet_save_record2
    (acct_num_in : acct_num_domain) FOR
SELECT * -- ERR
FROM
    s_et7.save
WHERE
    s_et7.save.acct_num =
        acct_num_in;

IS
    procedure CFETCH IS FETCH INTO savings_record :
savings_entry3;
END;

Cursor CGet_save_record3
    (acct_num_in : acct_num_domain) FOR
SELECT *
FROM
    s_et7.save, cust
WHERE
    s_et7.save.acct_num =
        acct_num_in;

IS
    procedure CFETCH IS FETCH INTO savings_record :
customer_record_plus;
END;

Cursor CGet_save_record4
    (acct_num_in : acct_num_domain) FOR
SELECT * -- ERR
FROM
    s_et7.save, cust
WHERE
    s_et7.save.acct_num =
        acct_num_in;
```

```

        IS
            procedure CFETCH IS FETCH INTO savings_record :
customer_record_plus1;
            END;

Cursor CGet_save_record5
(acct_num_in : acct_num_domain) FOR
SELECT * -- ERR
FROM
    s_et7.save, cust
WHERE
    s_et7.save.acct_num =
                        acct_num_in;

        IS
            procedure CFETCH IS FETCH INTO savings_record :
customer_record_plus2;
            END;

Cursor CGet_save_record6
(acct_num_in : acct_num_domain) FOR
SELECT branch_num, acct_num, Balance, cust_ssn
FROM
    s_et7.save
WHERE
    s_et7.save.acct_num =
                        acct_num_in;

        IS
            procedure CFETCH IS FETCH INTO savings_record :
savings_entry;
            END;

Cursor CGet_save_record7
(acct_num_in : acct_num_domain) FOR
SELECT branch_num, acct_num, Balance, cust_ssn --ERR
FROM
    s_et7.save
WHERE
    s_et7.save.acct_num =
                        acct_num_in;

        IS
            procedure CFETCH IS FETCH INTO savings_record :
savings_entry2;
            END;

Cursor CGet_save_record8
(acct_num_in : acct_num_domain) FOR
SELECT branch_num, acct_num, Balance, cust_ssn --ERR
FROM
    s_et7.save
WHERE
    s_et7.save.acct_num =
                        acct_num_in;

        IS
            procedure CFETCH IS FETCH INTO savings_record :
savings_entry3;
            END;

```

```
PROCEDURE New_customer IS
  INSERT INTO
    s_et7.cust -- ERR
  FROM
    New_customer_info : customer_record_minus
  VALUES;

PROCEDURE New_customer1 IS
  INSERT INTO
    s_et7.cust -- ERR
  FROM
    New_customer_info : customer_record
  VALUES (Cust_Name, SSN, City_addr, State_addr);

PROCEDURE New_customer2 IS
  INSERT INTO -- ERR
    s_et7.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
  FROM
    New_customer_info : customer_record_minus
  VALUES (Cust_Name, NULL, Street_addr, City_addr, State_addr);

PROCEDURE New_customer3 IS
  INSERT INTO -- ERR
    s_et7.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
  FROM
    New_customer_info : customer_record_minus
  VALUES (Cust_Name, SSN, '11261 Col Pike', City_addr,
State_addr);

PROCEDURE New_customer4 IS
  INSERT INTO -- ERR
    s_et7.cust (Cust_Name, Street_addr, City_addr, State_addr)
  VALUES (Cust_Name, City_addr, Street_addr, State_addr);

PROCEDURE New_customer5 IS
  INSERT INTO -- ERR
    s_et7.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
  VALUES (Cust_Name, SSN, Street_addr, City_addr, 'The State of
MD');

PROCEDURE New_customer6 IS
  INSERT INTO -- ERR
    s_et7.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
  VALUES (Cust_Name, SSN, NULL, City_addr);

PROCEDURE New_customer7 IS
  INSERT INTO -- ERR
    s_et7.cust (Cust_Name, SSN, Street_addr, City_addr,
State_addr)
  FROM
    New_customer_info : customer_record_minus
  VALUES ;

END a_et7;
```

A.3.8 t1/et8.sme

```

-- Check Assign conformance for set clauses

DEFINITION MODULE d_et8 IS
--
--   enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);
--
--   domain enumeration declarations
--
  DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_int
      (ENUMERATION => Loan_types, MAP => POS);

  DOMAIN branch_num_domain IS
    NEW SQL_ENUMERATION_AS_Char
      (ENUMERATION => Branches, MAP => IMAGE);

  constant C1 : loan_type_domain is mortgage;
  constant C2 : loan_type_domain is loan_type_domain (loan_type_domain
    (
      auto));
  constant C3 : branch_num_domain is Bethesda;
  constant C4 : branch_num_domain is branch_num_domain
    (branch_num_domain (
      Silver_Spring));

END d_et8;

```

```
WITH d_et8;
USE d_et8;
SCHEMA MODULE s_et8 IS

    TABLE Cust IS
        Col1 : loan_type_domain,
        Col2 : loan_type_domain,
        Col3 : branch_num_domain,
        Col4 : branch_num_domain,
        Col5 : loan_type_domain,
        Col6 : branch_num_domain
    END cust;

END s_et8;
```

```

WITH d_et8;
USE d_et8;
ABSTRACT MODULE a_et8 IS
  AUTHORIZATION s_et8

  PROCEDURE Upd_Cust IS
    UPDATE s_et8.cust
    SET
      Col1 = C1,
      Col2 = C3,  -- ERR
      Col3 = C3,
      Col4 = C4,
      Col5 = Gaithersburg, -- ERR
      Col6 = Gaithersburg;

  CURSOR Curs
    FOR SELECT * FROM s_et8.cust ;
  IS
    PROCEDURE Upd (val : branch_num_domain) IS
      update s_et8.cust
      SET
        Col1 = val, -- ERR
        Col2 = C3,  -- ERR
        Col3 = val,
        Col4 = C4,
        Col5 = Gaithersburg, -- ERR
        Col6 = Gaithersburg;

  END;

END a_et8;

```

A.3.9 t1/et9.sme

```

-- Check misc

DEFINITION MODULE d_et9 IS
--
--  enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);

--
--  domain enumeration declarations
--
  DOMAIN Loan_type_domain IS
    NEW SQL_ENUMERATION_AS_int
      (ENUMERATION => Loan_types, MAP => POS);

  DOMAIN branch_num_domain IS

```

```
NEW SQL_ENUMERATION_AS_Char
(ENUMERATION => Branches, MAP => IMAGE);

record Rec is
  cl : branch_num_domain;
end Rec_Name; -- ERR: name must match

status Stat uses branch_num_domain -- ERR
  is ( 1 => mortgage,
       2 => auto );

status Stat2 uses branches
  is ( 1 => mortgage,
       2.0 => auto ); -- ERR

status Stat3 uses boolean
  is ( 1 => true,
       2 => false );

END def_et9; -- ERR: name must match
```

A.3.10 t1/et10.sme

```
definition module d_et10 is
  -- Member Information
  domain MemName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, map => pos);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;
  domain Sum_Domain is new SQL_SMALLINT Not Null;
  domain Count_Domain is new SQL_INT;

end d_et10;

with d_et10; use d_et10;
schema module s_recdb is
  table Members is
    MemberName not null : MemName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
```

```

end Members;

end s_recdb;

with d_et10; use d_et10;
abstract module a_et10 is
  authorization s_recdb

  record MemberRec is
    R_MemberName   : MemName;
    R_Sum          : Sum_Domain;
    R_Count        : Count_Domain;
  end;

  procedure P_Del (Req_MemberSSN : SSN) is
    delete from MemberRec; -- ERR

  procedure P_Upd (Req_MemberSSN : SSN) is
    update MemberRec -- ERR
    set MemberName = Req_MemberRec;

  procedure P_Ins is
    insert into MemberRec -- ERR
    VALUES;

end a_et10;

```

A.3.11 t1/et11.sme

```
-- Check conformance on insert subquery statements
```

```

DEFINITION MODULE d_et11 IS
--
--   enumeration declarations
--
  ENUMERATION Branches IS
    ( Bethesda,
      Silver_Spring,
      Gaithersburg,
      Potomac);

  ENUMERATION Loan_types IS
    ( mortgage,
      auto,
      personal);

--
--   domain character declarations
--
  DOMAIN Customer_name_domain IS
    NEW SQL_CHAR(length => 15);
  DOMAIN Addr_domain IS
    NEW SQL_CHAR(length => 15);
  DOMAIN City_domain IS
    NEW SQL_CHAR(length => 15);
  DOMAIN State_domain IS
    NEW SQL_CHAR(length => 2);
--

```

```
--      domain integer declarations
--
DOMAIN SSN_domain IS
  NEW SQL_INT NOT NULL ( FIRST => 0, LAST => 999999999);
DOMAIN acct_num_domain IS
  NEW SQL_SMALLINT NOT NULL ( FIRST => 0, LAST => 9999);
--
--      domain real declarations
--
DOMAIN Balance_domain IS
  NEW SQL_REAL;
DOMAIN Interest_rate_domain IS
  NEW SQL_REAL( FIRST => 0.0, LAST => 1.0);
DOMAIN Loan_payment_domain IS
  NEW SQL_REAL;
DOMAIN Branch_assets_domain IS
  NEW SQL_REAL;
```

```
--
-- domain enumeration declarations
--
DOMAIN Loan_type_domain IS
  NEW SQL_ENUMERATION_AS_int
  (ENUMERATION => Loan_types, MAP => POS);
DOMAIN branch_num_domain IS
  NEW SQL_ENUMERATION_AS_INT
  (ENUMERATION => Branches, MAP => POS);
--
-- record definitions
--
RECORD Customer_record IS
  Cust_Name      : Customer_name_domain;
  SSN            : SSN_domain;
  Street         : Addr_domain;
  City           : City_domain;
  State          : State_domain;
END customer_record;

RECORD Savings_entry IS
  branch_num      : branch_num_domain;
  acct_num       : acct_num_domain;
  Balance         : Balance_domain;
  cust_ssn       : SSN_domain;
END Savings_entry;

RECORD Chequeing_entry IS
  branch_num      : branch_num_domain;
  acct_num       : acct_num_domain;
  Balance         : Balance_domain;
  cust_ssn       : SSN_domain;
END Chequeing_entry;

RECORD loan_entry IS
  branch_num      : branch_num_domain;
  acct_num       : acct_num_domain;
  Balance         : Balance_domain;
  Loan_type      : Loan_type_domain;
  cust_ssn       : SSN_domain;
END loan_entry;

RECORD Branch_entry IS
  branch_num      : branch_num_domain ;
  Assets          : Branch_assets_domain;
END Branch_entry;

END d_et11;
```

```
WITH d_et11;
USE d_et11;
SCHEMA MODULE s_et11 IS
--
-- Basic customer information
--
TABLE Cust IS
    Cust_Name      : Customer_name_domain,
    SSN not null   : SSN_domain,
    Street_addr    : Addr_domain,
    City_addr      : City_domain,
    State_addr     : State_domain
END cust;
--
-- Checking account
--
TABLE cheque IS
    branch_num     : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance         : Balance_domain,
    cust_ssn not null : SSN_domain
END cheque;
--
-- Savings account
--
TABLE Save IS
    branch_num     : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance         : Balance_domain,
    cust_ssn not null : SSN_domain
END Save;
--
-- loan account
--
TABLE loan IS
    branch_num     : branch_num_domain,
    acct_num not null : acct_num_domain,
    Balance         : Balance_domain,
    Loan_type      : loan_type_domain,
    cust_ssn not null : SSN_domain
END loan;
--
-- Branch information
--
TABLE Branch IS
    num            : branch_num_domain ,
    Assets         : Branch_assets_domain
END Branch;

END s_et11;
```

```

WITH d_et11;
USE d_et11;
ABSTRACT MODULE a_et11 IS
    AUTHORIZATION s_et11
--
--    insert statement (query)
--
    PROCEDURE move_loan_to_save
        (account_num_in : acct_num_domain)
    IS
    INSERT INTO
        s_et11.save
    SELECT *
    FROM
        s_et11.loan -- ERR
    WHERE
        s_et11.loan.acct_num >= account_num_in;

    PROCEDURE move_loan_to_save2
        (account_num_in : acct_num_domain)
    IS
    INSERT INTO
        s_et11.save
    SELECT branch_num, acct_num, Balance, cust_ssn
    FROM
        s_et11.loan
    WHERE
        s_et11.loan.acct_num >= account_num_in;

    PROCEDURE move_loan_to_save3
        (account_num_in : acct_num_domain)
    IS
    INSERT INTO
        s_et11.save
    SELECT branch_num, acct_num, cust_ssn, cust_ssn --ERR
    FROM
        s_et11.loan
    WHERE
        s_et11.loan.acct_num >= account_num_in;

END a_et11;

```

A.3.12 t1/et12.sme

```

definition module d_et12 is
-- Member Information
domain MemName is new SQL_CHAR Not Null (Length => 30);
domain SSN is new SQL_CHAR Not Null (Length => 9);
domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

enumeration SexEnum is (F, M);
domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, MAP => POS);

domain Phone is new SQL_CHAR (Length => 8);
domain Street is new SQL_CHAR (Length => 30);
domain City is new SQL_CHAR (Length => 15);

```

```
domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;

constant C_Name : MemName is '123456789012345678901234567890';
constant C_SSN : SSN is '123456789';
constant C_Club_Number : Club_Number is 10;
constant C_Age : Age is 39;
constant C_Sex : Sex is F;
constant C_Phone : Phone is '12345678';
constant C_Street : Street is '123456789012345678901234567890';
constant C_City : City is '123456789012345';
constant C_County : County is 'MO';
end d_et12;

with d_et12; use d_et12;
schema module RecDB is
  table Members is
    MemberName not null : MemName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
  end Members;
end RecDB;

with d_et12; use d_et12;
abstract module a_et12 is
  authorization RecDB

  record MemberRec named Named_MemberRec is
    -- record MemberRec is
    R_MemberName : MemName;
    R_MemberSSN : SSN;
    R_ClubNumber : Club_Number;
    R_MemberAge : Age;
    R_MemberSex : Sex;
    R_MemberPhone : Phone;
    R_MemberStreet : Street;
    R_MemberCity : City not null;
    R_MemberCnty : County ;
  end;

  cursor MemberSelect2 (Req_MemberSSN named Req_MemberSSN : SSN) for
    (select
      MemberName named NS_MemberName,
      MemberSSN,
      ClubNumber,
      MemberAge,
      MemberSex,
```

```

        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
    from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN
UNION
select
        MemberName      named NS_MemberName,
        MemberSSN,
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
    from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN)
UNION
(select
        MemberSSN,
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
    from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN
UNION
select
        MemberName      named NS_MemberName,
        MemberSSN,
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
    from RecDB.Members
    where RecDB.Members.MemberSSN = Req_MemberSSN);

cursor MemberSelect3 (Req_MemberSSN named Req_MemberSSN : SSN) for
    (select
        MemberName      named NS_MemberName,
        MemberSSN,

```

```
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone ,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
from RecDB.Members
  where RecDB.Members.MemberSSN = Req_MemberSSN
UNION
select
        MemberName      named NS_MemberName,
        MemberSSN,
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
from RecDB.Members
  where RecDB.Members.MemberSSN = Req_MemberSSN)
UNION
(select
        MemberName      named NS_MemberName,
        MemberSSN,
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
from RecDB.Members
  where RecDB.Members.MemberSSN = Req_MemberSSN
UNION
select
        MemberName      named NS_MemberName,
        MemberSSN,
        ClubNumber,
        MemberAge,
        MemberSex,
        MemberPhone Not Null,
        MemberStreet named NS_MemberStreet Not Null,
        MemberCity,
        MemberCnty
from RecDB.Members
```

```

        where RecDB.Members.MemberSSN = Req_MemberSSN);

end a_et12;

A.3.13      t3/el.sme

definition module t_1 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT (FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, MAP => Pos);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;

  exception Record_Not_Found;

  enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

  status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise samplemod.record_not_found);

end t_1;

with SampleMod; use SampleMod;
schema module RecDB is
  table Members is
    MemberName not null    : MemberName,
    MemberSSN not null     : SSN,
    ClubNumber not null    : Club_Number,
    MemberAge      : Age,
    MemberSex      : Sex,
    MemberPhone    : Phone,
    MemberStreet   : Street,
    MemberCity     : City,
    MemberCnty not null   : County
  end Members;

end RecDB;

with SampleMod; use SampleMod;
abstract module RecDML is

```

authorization RecDB

```
record MemberRec is
  MemberName   : MemberName;
  MemberSSN    : SSN;
  ClubNumber   : Club_Number;
  MemberAge    : Age;
  MemberSex    : Sex;
  MemberPhone  : Phone;
  MemberStreet : Street;
  MemberCity   : City;
  MemberCnty   : County;
end;

cursor MemberSelect (Req_MemberSSN : SSN) for
  select t1.MemberSSN, t2.Dummy
  from RecDB.Members as t1, RecDB.Members as t2
  where t1.MemberSSN = t2.MemberSSN;

end RecDML;
```

A.3.14 t3/e2.sme

```
definition module t_2 is
  -- Member Information
  domain MemberName is new SQL_CHAR Not Null (Length => 30);
  domain SSN is new SQL_CHAR Not Null (Length => 9);
  domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

  enumeration SexEnum is (F, M);
  domain Sex is new SQL_ENUMERATION_AS_INT (
    Enumeration => SexEnum, Map => POS);

  domain Phone is new SQL_CHAR (Length => 8);
  domain Street is new SQL_CHAR (Length => 30);
  domain City is new SQL_CHAR (Length => 15);

  domain County is new SQL_CHAR Not Null (Length => 2);

  domain Club_Number is new SQL_SMALLINT Not Null;

  exception Record_Not_Found;

  enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

  status fetch_map named is_found uses Failtype is
    ( -999 .. -300 => SQL_Fail,
      -299, -298 => Not_Logged_In,
        0 => SQL_Ok,
      100 => raise samplemod.record_not_found);

end t_2;

with t_2; use t_2;
schema module RecDB is
  table Members is
    MemberName not null : MemberName,
```

```

        MemberSSN not null      : SSN,
        ClubNumber not null    : Club_Number,
        MemberAge      : Age,
        MemberSex      : Sex,
        MemberPhone    : Phone,
        MemberStreet   : Street,
        MemberCity     : City,
        MemberCnty not null    : County
    end Members;

    table Members2 is
        MemberName not null      : MemberName,
        MemberSSN not null      : SSN,
        ClubNumber not null    : Club_Number
    end Members2;

end RecDB;

with t_2; use t_2;
abstract module RecDML is
    authorization RecDB

    record MemberRec is
        MemberName      : MemberName;
        MemberSSN       : SSN;
        ClubNumber      : Club_Number;
        MemberAge       : Age;
        MemberSex       : Sex;
        MemberPhone     : Phone;
        MemberStreet    : Street;
        MemberCity      : City;
        MemberCnty      : County;
    end;

    cursor MemberSelect (Req_MemberSSN : SSN) for
        select t1.MemberSSN, Recdb.Members.Membername
        from RecDB.Members as t1, Recdb.members as t2
        where t1.MemberSSN = (select MemberSSN
                               from t2
                               where Recdb.members.membername = 'John');

end RecDML;

```

A.3.15 t3/e3.sme

```

definition module t_3 is
    -- Member Information
    domain MemberName is new SQL_CHAR Not Null (Length => 30);
    domain SSN is new SQL_CHAR Not Null (Length => 9);
    domain Age is new SQL_SMALLINT ( FIRST => 1, LAST => 199);

    enumeration SexEnum is (F, M);
    domain Sex is new SQL_ENUMERATION_AS_INT (
        Enumeration => SexEnum, Map => POS);

    domain Phone is new SQL_CHAR (Length => 8);
    domain Street is new SQL_CHAR (Length => 30);

```

```
domain City is new SQL_CHAR (Length => 15);

domain County is new SQL_CHAR Not Null (Length => 2);

domain Club_Number is new SQL_SMALLINT Not Null;

exception Record_Not_Found;

enumeration FailType is (Not_Logged_In, SQL_Ok, SQL_Fail);

status fetch_map named is_found uses Failtype is
  ( -999 .. -300 => SQL_Fail,
    -299, -298 => Not_Logged_In,
      0 => SQL_Ok,
    100 => raise samplemod.record_not_found);

end t_3;

with t_3; use t_3;
schema module RecDB is
  table Members is
    MemberName not null : MemberName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number,
    MemberAge : Age,
    MemberSex : Sex,
    MemberPhone : Phone,
    MemberStreet : Street,
    MemberCity : City,
    MemberCnty not null : County
  end Members;

  table Members2 is
    MemberName not null : MemberName,
    MemberSSN not null : SSN,
    ClubNumber not null : Club_Number
  end Members2;

end RecDB;

with t_3; use t_3;
abstract module RecDML is
  authorization RecDB

  record MemberRec is
    MemberName : MemberName;
    MemberSSN : SSN;
    ClubNumber : Club_Number;
    MemberAge : Age;
    MemberSex : Sex;
    MemberPhone : Phone;
    MemberStreet : Street;
    MemberCity : City;
    MemberCnty : County;
  end;

end;
```

```
cursor MemberSelect (Req_MemberSSN : SSN) for
  select MemberSSN, Recdb.Members.Membername
  from RecDB.Members2 as t1, Recdb.members as t2
  where t1.MemberSSN = (select MemberSSN
                        from t2
                        where Recdb.members.membername = 'John');

.....
end RecDML;
```