

2

AD-A268 528



DODPOPHM/USA/DOD/NADTR93006

**PERFORMANCE ORIENTED PACKAGING TESTING
OF
TANK, POWDER, ALUMINUM, 16"/50, MK 4 MOD 0
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS**

Author:
Lewis Coutts
Mechanical Engineer

Performing Activity:
Packaging, Handling, Storage, and Transportation Center
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5023

August 1993

FINAL

**DTIC
ELECTE
AUG 18 1993
S B D**

DISTRIBUTION STATEMENT A
Approved for public release
Distribution Unlimited

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Surface Warfare Center
Indian Head Division (Code 5710R)
Indian Head, MD 20640-5035

93 8 17 06 5

93-19169

7028

REPORT DOCUMENTATION PAGEForm Approved
OMB No 0704-0188

Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 08/93	3. REPORT TYPE AND DATES COVERED POP Test (05/93)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Tank, Powder, Aluminum, 16"/50, Mk 4 Mod 0 for Packing Group II Solid Hazardous Materials			5. FUNDING NUMBERS	
6. AUTHOR(S) Lewis Coutts				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Packaging, Handling, Storage, and Transportation Center Naval Weapons Station Earle Colts Neck, NJ 07722-5023			8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR93006	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center Indian Head Division (Code 5710R) Indian Head, MD 20640-5035			10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A				
12a. DISTRIBUTION/AVAILABILITY STATEMENT			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) <p>This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Mk 4 Mod 0 16"/50 Aluminum Powder Tank (LD 58290) meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 106 through 178, dated 1 October 1992. The packaged commodity used for the test was a simulated load weighing 182 kg (400 pounds). This represents the current maximum commodity weight plus an additional 30 kg (65 pounds) to compensate for future growth variations in commodity and/or packaging. Gross weight of the loaded tank was 216 kg (475 pounds). The test results indicate that the tank has conformed to the POP requirements.</p>				
14. SUBJECT TERMS POP Test of Mk 4 Mod 0 16"/50 Aluminum Powder Tank			15. NUMBER OF PAGES 7	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 4 Mod 0 16"/50 Aluminum Powder Tank (LD 58290) meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 106 through 178, dated 1 October 1992. The packaged commodity used for the test was a simulated load weighing 182 kg (400 pounds). This represents the current maximum commodity weight plus an additional 30 kg (65 pounds) to compensate for future growth variations in commodity and/or packaging. Gross weight of the loaded tank was 216 kg (475 pounds).

Due to unavailability only two tanks were used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990. The tanks were identified as #1 and #2.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR 178.608. Tank #1 was placed horizontally on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the tank was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the tank left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour. This test was repeated with the container positioned vertically.

2. Stacking Test

This test was performed in accordance with Title 49 CFR 178.606. Tank #2 was used for this test. The tank was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked horizontally to a minimum height of 3 meters (including the test tank). A weight of 1,292 kg (2,850 pounds) was stacked on the test tank. The test was performed for 24 hours. The weight was then removed and the tank examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR 178.603. Six drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drops for each orientation):

- a. Horizontally using tank #1.
- b. Diagonally on the edge between the cover assembly and the top ring of the tank using tank #2.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test (Vertical Orientation)

The tank was placed upright with the input vibration frequency set to 3.5 Hz. Immediately after the vibration test was completed, the tank was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Base Level Vibration Test (Horizontal Orientation)

The tank was placed on its side with the input vibration frequency set to 4.1 Hz. Immediately after the vibration test was completed, the tank was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

3. Stacking Test

The tank was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

4. Drop Test

After each drop, the tank was inspected. The contents were completely retained by the tank.

REFERENCE MATERIAL

A. Code of Federal Regulations, Title 49 CFR, Parts 106-178.

B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
 ATTN: DTIC/FDA
 Bldg. 5, Cameron Station
 Alexandria, VA 22304-6145

DLA Depot Operations Support Office
 Bldg. 32F, DGSE
 ATTN: Dave Gay
 Richmond, VA 23297-5000

Commander
 Naval Surface Warfare Center
 ATTN: Crane Division (Code 4053)
 Crane, IN 47522-5000

Accession For		6
NTIS GRA&I	<input checked="" type="checkbox"/>	
DTIC TAB	<input type="checkbox"/>	
Unannounced	<input type="checkbox"/>	
Justification		
By _____		
Distribution/		
Availability Codes		
Dist	Avail and/or	
	Special	
A-1		

TEST DATA SHEET

POP MARKING:	
UN 1B2/Y216/S/**/USA/DOD/NAD	
**YEAR LAST PACKED OR MANUFACTURED	
Nomenclatur: Mk 4 Mod 0 16"/50 Aluminum Powder Tank	
Type: 1B2	NSN: NSN 8140-00-310-2808
Drawing Number or P/N: DL 58290	Outer Packaging Material: Aluminum
Dimensions: 55.4" L x 20.25" dia	Gross Weight: 216 kg (475 pounds)
Closure (Method/Type): Twist on cover with rubber gasket	Tare Weight: 34 kg (75 pounds)
Additional Description: Cylindrical container with cover at end	
PACKAGED COMMODITY:	
Name: See table 1	NSN(s): See table 1
United Nations Number: See table 1	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount Per Container: See table 1	Flash Point: N/A
Net Weight: See table 1	
PACKAGED COMMODITY USED FOR TEST:	
Name: Simulated powder charges	Physical State: Solid
Consistency: N/A	Density/Specific Gravity: N/A
Test Pressure (Liquids Only): N/A	Net Weight: 182 kg (400 pounds)
Additional Description: The net weight includes the current maximum commodity weight plus an additional 30 kg (65 pounds).	

N/A = Not Applicable

TABLE 1
Commodities Approved for Shipping in the
Mk 4 Mod 0 16"/50 Aluminum Powder Tank

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Document Number	Haz Class/Div	UN Number	Units/ Package	Total Net Weight kg (lb)	Total Gross Weight kg (lb)
D846	1320-01-230-4001	Charge, Propelling, 16"/50 Cal Full	DL 6107433 OR-68/128	1.3C	0242	3	152 (335)	186 (410)
D845	1320-00-089-9784	Charge, Propelling, 16"/50 Cal Reduced	DL 6107433 OR-68/128	1.3C	0242	3	64 (140)	98 (215)
D840	1320-00-089-9785	Charge, Propelling, 16"/50 Cal Reduced	DL 6107433 OR-68/128	1.3C	0242	3	64 (140)	98 (215)
B839	1320-01-139-1758	Charge, Propelling, 16"/50 Cal Full	DL 6107433 OR-68/128	1.3C	0242	3	152 (335)	186 (410)
B839	1320-01-125-2562	Charge, Propelling, 16"/50 Cal Full	DL 6107433 OR-68/128	1.3C	0242	3	152 (335)	186 (410)
J145	1340-01-371-6903	Mk 23 Mods JATO Rocket Motor	1133AS100	1.3C	0186	1	123 (272)	157 (347)