

AD-A269 719



2

DODPOPHM/USA/DOD/NADTR93010

Superseding
DODPOPHM/USA/DOD/NADTR92028
October 1992

PERFORMANCE ORIENTED PACKAGING TESTING
OF PACKING BOX FOR MK 117 MOD 0 JATO ROCKET MOTOR
FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

DTIC
ELECTE
SEP 21 1993
S A D

Author:
V. Saul
Mechanical Engineering Technician

Performing Activity:
Naval Packaging, Handling, Storage and Transportation Center
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5023

August 1993

This document has been approved
for public release and sale; its
distribution is unlimited.

FINAL

DISTRIBUTION UNLIMITED

Sponsoring Organization:
Naval Surface Warfare Center
Indian Head Division (Code 5710R)
Indian Head, MD 20640-5035

93 9 20 04 9

93-21855



978

REPORT DOCUMENTATION PAGE		Form Approved OMB No 0704-0188	
Public reporting burden of this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 08/93	3. REPORT TYPE AND DATES COVERED POP Test (08/93)	
4. TITLE AND SUBTITLE Performance Oriented Packaging Testing of Packing Box for Mk 117 Mod 0 JATO Rocket Motor for Packing Group II Solid Hazardous Materials		5. FUNDING NUMBERS	
6. AUTHOR(S) V. Saul			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Packaging, Handling, Storage and Transportation Center Naval Weapons Station Earle Colts Neck, NJ 07722-5023		8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR93010	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Commander, Naval Surface Warfare Center Indian Head Division (Code 571OR) Indian Head, MD 20640-5035		10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above	
11. SUPPLEMENTARY NOTES N/A			
12a. DISTRIBUTION/AVAILABILITY STATEMENT		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This Performance Oriented Packaging (POP) test was conducted to ascertain whether the packing box for the Mk 117 Mod 0 JATO Rocket Motor (Drawing 1638AS122) meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 106 through 178, dated 1 October 1992. The packaged commodity used for the test was two inert rocket motors weighing 23 kg (50 pounds) each. This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 4 kg (10 pounds) were added. The box was initially qualified for a gross weight of 59 kg (130 pounds) using Test Report DODPOPHM/USA/DOD/NADTR92028. This report qualifies the box for a gross weight of 64 kg (140 pounds). The test results indicate that the box has conformed to the POP requirements.			
14. SUBJECT TERMS POP Test of Packing Box for Mk 117 Mod 0 JATO Rocket Motor		15. NUMBER OF PAGES 7	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the packing box for the Mk 117 Mod 0 JATO Rocket Motor (Drawing 1638AS122) meets the Packing Group II requirements specified by the Code of Federal Regulations, Title 49 CFR, Parts 106 through 178, dated 1 October 1992. The packaged commodity used for the test was two inert rocket motors weighing 23 kg (50 pounds) each. This represents the current maximum commodity weight. To compensate for future growth variations in commodity and/or packaging, 4 kg (10 pounds) were added. The box was initially qualified for a gross weight of 59 kg (130 pounds) using Test Report DODPOPHM/USA/DOD/NADTR92028. This report qualifies the box for a gross weight of 64 kg (140 pounds).

Due to unavailability only two boxes were used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR 178.608. Box #1 was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the box was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the box left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR 178.606. Box #1 was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test box). A weight of 762 kg (1,680 pounds) was stacked on the test box. The test was performed for 24 hours. The weight was then removed and the box examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR 178.603. Five drops were performed from a height of 1.2 meters (4 feet), impacting the following surfaces:

- a. Flat bottom using box #1.
- b. Flat top using box #1.

- c. Flat on long side using box #1.
- d. Flat on short side using box #1.
- e. One corner using box #2.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION**1. Base Level Vibration Test**

The input vibration frequency was 3.6 Hz. Immediately after the vibration test was completed, the box was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The box was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the box was inspected. The contents were completely retained by the box.

REFERENCE MATERIAL

A. Code of Federal Regulations, Title 49 CFR, Parts 106-178.

B. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies)
ATTN: DTIC/FDA
Bldg. 5, Cameron Station
Alexandria, VA 22304-6145

DLA Depot Operations Support Office
Bldg. 32F, DGSE
ATTN: Tom McElwee
Richmond, VA 23297-5000

Commander
Naval Surface Warfare Center
ATTN: Crane Division (Code 4053)
Crane, IN 47522-5000

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution	
Availability Codes	
Dist	Avail and/or Special
A-1	

DTIC QUALITY INSPECTED 3

TEST DATA SHEET

POP MARKING:	
UN 4C1/Y64/S/**/USA/DOD/NAD	
**YEAR LAST PACKED OR MANUFACTURED	
Nomenclature: Packing Box for Mk 117 Mod 0 JATO Rocket Motor	
Type: 4C1	NSN: N/A
Drawing Number or P/N: 1638AS122	Outer Packaging Material: Wood
Dimensions: 34-1/8" L x 16-1/8" W x 9-13/16" H	Gross Weight: 64 kg (140 pounds)
Closure (Method/Type): two 5/8" straps and six 7-D nails	Tare Weight: 14 kg (30 pounds)
Additional Description:	
PACKAGED COMMODITY:	
Nomenclature: See table 1	NSN(s): See table 1
United Nations Number: See table 1	
United Nations Packing Group: II	
Physical State (Solid, Liquid, or Gas): Solid	
Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A	
Consistency/Viscosity: N/A	Density/Specific Gravity: N/A
Amount per Package: See table 1	Flash Point: N/A
Net Weight: See table 1	
PACKAGED COMMODITY USED FOR TEST:	
Name: Two inert Rocket Motors	Physical State: Solid
Consistency: N/A	Density/Specific Gravity: N/A
Test Pressure (Liquids Only): N/A	Net Weight: 50 kg (110 pounds)
Additional Description:	
The net weight includes the current maximum commodity weight plus an additional 4 kg (10 pounds).	

N/A = Not Applicable

TABLE 1
Commodities Approved for Shipping in the
Packing Box for the Mk 117 Mod 0 JATO Rocket Motor

NALC/ DODIC	NSN	Commodity Nomenclature	Packing Document Number	Haz Class/Div	UN Number	Units/ Package	Total Net Weight kg (lb)	Total Gross Weight kg (lb)
H341	1340-01-177-2502	Mk 117 Mod 0 JATO Rocket Motor	1638AS123	1.3C	0186	2	46 (100)	59 (130)