

2

AD-A275 644

NASA Contractor Report 191567
ICASE Report No. 93-86

ICASE



FLAMES IN DUSTY MIXTURES -- THEIR STRUCTURE AND STABILITY

J. Buckmaster
T. Jackson


S DTIC
ELECTE
FEB 15 1994 **D**
E

DTIC QUALITY INSPECTED 2

NASA Contract No. NAS1-19480
November 1993

Institute for Computer Applications in Science and Engineering
NASA Langley Research Center
Hampton, Virginia 23681-0001

Operated by the Universities Space Research Association



National Aeronautics and
Space Administration
Langley Research Center
Hampton, Virginia 23681-0001

94-04984



24pgs

94 2 14 025

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE November 1993	3. REPORT TYPE AND DATES COVERED Contractor Report	
4. TITLE AND SUBTITLE FLAMES IN DUSTY MIXTURES - THEIR STRUCTURE AND STABILITY		5. FUNDING NUMBERS C NAS1-19480 WU 505-90-52-01	
6. AUTHOR(S) J. Buckmaster T. Jackson		8. PERFORMING ORGANIZATION REPORT NUMBER ICASE Report No. 93-86	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Institute for Computer Applications in Science and Engineering Mail Stop 132C, NASA Langley Research Center Hampton, VA 23681-0001			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Langley Research Center Hampton, VA 23681-0001		10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA CR-191567 ICASE Report No. 93-86	
11. SUPPLEMENTARY NOTES Langley Technical Monitor: Michael F. Card Final Report Submitted to the 25th International Symposium on Combustion			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 34		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The structure and stability of flames in dusty mixtures is investigated. The presence of the dust leads to significant transport of energy by radiation and the fundamental goal of the analysis is to explore to what extent this displaces the classical non-hydrodynamical stability boundaries of the plane deflagration. An approximate description of the radiative transport permits analysis for arbitrary values of both the Planck length and the Boltzman number. It is shown that the pulsating/traveling-wave instability usually associated with values of Lewis number (Le) bigger than 1 is strongly enhanced by the presence of radiation and can be present even if $Le < 1$. On the other hand radiation tends to suppress the cellular instability normally associated with values of Le less than 1. The latter is consistent with preliminary experimental observations of Abbud-Madrid and Ronney.			
14. SUBJECT TERMS flames; stability; dusty mixtures		15. NUMBER OF PAGES 24	
		16. PRICE CODE A03	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT

NSN 7540-01-280-5500

☆ U.S. GOVERNMENT PRINTING OFFICE: 1994 - 528-064/86099

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std. Z39-18
298-102

ICASE Fluid Mechanics

Due to increasing research being conducted at ICASE in the field of fluid mechanics, future ICASE reports in this area of research will be printed with a green cover. Applied and numerical mathematics reports will have the familiar blue cover, while computer science reports will have yellow covers. In all other aspects the reports will remain the same; in particular, they will continue to be submitted to the appropriate journals or conferences for formal publication.

Accession For	
NTIS	<input checked="" type="checkbox"/>
CRA&I	<input checked="" type="checkbox"/>
DTIC	<input type="checkbox"/>
TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

FLAMES IN DUSTY MIXTURES – THEIR STRUCTURE AND STABILITY

*J. Buckmaster*¹

University of Illinois
Urbana, IL

*T. Jackson*¹

Institute for Computer Applications in Science and Engineering
NASA Langley Research Center
Hampton, VA

ABSTRACT

The structure and stability of flames in dusty mixtures is investigated. The presence of the dust leads to significant transport of energy by radiation and the fundamental goal of the analysis is to explore to what extent this displaces the classical non-hydrodynamical stability boundaries of the plane deflagration. An approximate description of the radiative transport permits analysis for arbitrary values of both the Planck length and the Boltzman number. It is shown that the pulsating/traveling-wave instability usually associated with values of Lewis number (Le) bigger than 1 is strongly enhanced by the presence of radiation and can be present even if $Le < 1$. On the other hand radiation tends to suppress the cellular instability normally associated with values of Le less than 1. The latter is consistent with preliminary experimental observations of Abbud-Madrid and Ronney.

¹This research was supported by the National Aeronautics and Space Administration under NAS1-19480 while the authors were in residence at the Institute for Computer Applications in Science and Engineering (ICASE), NASA Langley Research Center, Hampton, VA 23681.

Introduction

We are concerned with plane flames supported by mixtures that contain a large number of small inert particles (dusty gases). The particles substantially influence the radiative transport and make emission and absorption energetically significant. Partial motivation for the study comes from recent experimental observations which suggest that in combustion fields of this kind cellular instability (the Turing instability associated with values of Lewis number less than 1, [1]) can be suppressed [2]. A discussion of stability and the effect of particle loading on the location of the stability boundaries in the wave-number - Lewis-number plane is the central contribution of this paper.

The presence of particles and radiative transport presents serious technical obstacles to an analytical treatment, and these must be overcome by judicious modeling. We start by assuming that the mass loading is small and the only impact of the particles is on the radiative transport. The bulk particle density is $(4/3) \pi d^3 N \rho$ (N is the number density, d the particle diameter, ρ the substantive particle density) and the radiation effect is controlled by Nd^2 so that our treatment is formally valid in the limit $N \rightarrow \infty, d \rightarrow 0, Nd^2$ fixed. (Then $Nd^3 \rightarrow 0$)

A strategy for dealing with radiative transport which has been usefully employed by Joulin and his colleagues in a number of important studies (e.g. [3], [4]) is to assume that the Boltzman number is small, but we wish to avoid the restriction here since it is of limited applicability. Instead we start with the differential - equation approximation (the Eddington approximation)

$$L \nabla (\underline{L} \nabla \cdot \underline{q}) = \underline{q} + 4 L \nabla T^4 . \quad (1)$$

Since the nonlinearities here present serious difficulties we approximate the Planck length L by a constant and linearize the emission term, replacing Eqn. (1) by

$$L^2 \nabla (\underline{L} \nabla \cdot \underline{q}) = \underline{q} + 16 T_c^3 L \nabla T \quad (2)$$

where T_c is a constant characteristic (emitting) temperature. Then \underline{q} is irrotational so that we may introduce a generating function ψ so that

$$\underline{q} = \underline{\nabla} \psi . \quad (3)$$

Equation (2), after a single integration, is then equivalent to

$$L^2 \nabla^2 \psi = \underline{q} + 16 T_c^3 L (T - T_f) \quad (4)$$

where T_f is the remote cold-mixture temperature.

The other ingredients of our model are familiar and of proven merit. They are embodied in the equations

$$\begin{aligned} \rho (Y_t + u Y_x) &= \rho D \nabla^2 Y - B e^{-E/2R} \delta(n) \\ \rho C_p (T_t + u T_x) &= \lambda \nabla^2 T - \nabla^2 \psi + Q B e^{-E/2R} \delta(n) \end{aligned} \quad (5)$$

Here Y is the mixture mass fraction, T the temperature, and u is the steady flame speed so that the unperturbed flame is fixed. Reaction is modeled by a delta-function whose strength is an Arrhenius

function of the flame-temperature T_* ; n is the distance measured along the flame-sheet normal that points towards the burnt gas. And for the purposes of the stability analysis we adopt the constant-density model so that hydrodynamic effects are discarded.

Boundary conditions are:

$$\underline{x \rightarrow -\infty} \quad T \rightarrow T_f, \quad Y \rightarrow Y_f, \quad \psi \rightarrow 0 \quad (6)$$

We wish to construct the steady planar solution of the system (4) - (6) and to examine the linear stability of this solution to arbitrary perturbations. To this end it is convenient to introduce a flame-fixed coordinate system by replacing x by s where

$$s = x - Fy, \quad (7)$$

and the flame-sheet is located at $s = 0$. Equations (5) for $s \neq 0$ are then

$$\rho [Y_t + (u - F_t) Y_s] = \rho D \nabla^2 Y, \quad (8)$$

$$\rho C_p [T_t + (u - F_t) T_s] = \lambda \nabla^2 T - \nabla^2 \psi$$

where

$$\nabla^2 = (1 + F_y^2) \partial^2 / \partial s^2 + \partial^2 / \partial y^2 - 2F_y \partial^2 / \partial y \partial s - F_{yy} \partial / \partial s \quad (9)$$

The jump conditions at the flame-sheet are:

$$[\psi] = 0, \quad [\psi_s] = 0$$

$$[T] = 0, [Y] = 0 \quad (10)$$

$$(1 + F_y^2)[T_s] = -(QBA) \exp(-E_2 RT_s), (1 + F_y^2)[Y_s] = (B \rho D) \exp(-E_2 RT_s).$$

Steady Solution

The steady solution is constructed by seeking solutions for which

$$F = 0, T = T^s(s), Y = Y^s(s), \psi = \psi^s(s) \quad (11)$$

Consider the cubic

$$\alpha(\omega L)^3 - (\omega L)^2 - (3\alpha + \beta)(\omega L) + 3 = 0 \quad (12)$$

$$\text{where } \alpha = \lambda / L M C_p, \beta = 16 T_c^4 / M C_p T_c. \quad (13)$$

α is the familiar length $\lambda / M C_p$ divided by the Planck length; β is a Boltzman number.

Equation (12) only has real roots, two of which are positive (ω_1, ω_2), one negative (ω_3). In addition we define ω_4 by

$$\omega_4 = \rho u / \rho D = M / \rho D. \quad (14)$$

Then, without using the connection conditions (10), the steady solution has the form:

$$\begin{aligned} \underline{s < 0} \quad T^s &= T_f + C_1 e^{\omega_1 s} + C_2 e^{\omega_2 s} \\ \psi_s &= C_1 (M C_p - \lambda \omega_1) e^{\omega_1 s} - C_2 (M C_p - \lambda \omega_2) e^{\omega_2 s} \end{aligned} \quad (15)$$

$$Y^s = Y_f + C_4 e^{\omega_4 s}$$

$$s > 0 \quad T^s = T_a + C_3 e^{\omega_3 s}$$

$$\psi_s = C_3 (M C_p - \lambda \omega_3) e^{\omega_3 s} \quad (16)$$

$$Y = 0 .$$

Here $T_a \equiv T_f + Q_f / C_p$ is the adiabatic flame temperature, the temperature at $s \rightarrow \infty$ fixed by global energy conservation.

The various constants $\{C_i\}$ are determined by use of the connection conditions (10 a-d) whence

$$C_4 = Y_f \quad (17)$$

and, with the definitions

$$z_i = \alpha L \omega_i, \quad D_i = C_i (T_a - T_f) \quad (18)$$

we have

$$D_1 + D_2 - D_3 = 1$$

$$D_1 z_1 + D_2 z_2 - D_3 z_3 = 1 \quad (19)$$

$$D_1 z_1^2 + D_2 z_2^2 - D_3 z_3^2 = 1$$

Equations (19) have solution

$$D_1 = (z_2 - \alpha)(z_3 - \alpha)(z_2 - z_1)^{-1}(z_3 - z_1)^{-1}$$

$$D_2 = (z_1 - \alpha)(z_3 - \alpha)(z_1 - z_2)^{-1}(z_3 - z_2)^{-1}$$

$$D_3 = -(z_1 - \alpha)(z_2 - \alpha)(z_1 - z_3)^{-1}(z_2 - z_3)^{-1} \quad (20)$$

In order to determine the mass flux M (i.e. the flame speed) it is convenient to define M_0 by

$$M_0 = M(\beta - \alpha) \quad (21)$$

and since $T_s = T_a$ at this limit, Eqn. (10e) is

$$[T_s] = (M_0 C_p / \lambda) (T_a - T_f) \exp[E / 2RT_a - E / 2R] \quad (22)$$

It follows that

$$M / M_0 = \exp\left\{(E/2RT_a) D_3 [D_3 + T_a / (T_a - T_f)]^{-1}\right\}. \quad (23)$$

D_3 is defined by the roots z_1, z_2 and z_3 which, in turn, are defined by α and β , both of which depend on M . Thus Eqn. (23) is an implicit formula for the flame-speed.

The limit $\alpha \rightarrow \zeta$

It is of interest to examine the realistic limit $\alpha \rightarrow \zeta$, when the Planck length is much larger than the diffusive scale (i.e. the Reynolds number based on L is large). Then the temperature distribution is

$$\underline{s < 0} \quad T^s = T_f + (T_a - T_f) \left[\exp\left(\frac{MC_p}{\lambda} s\right) + f_+(\beta, s) \right],$$

$$\underline{s > 0} \quad T^s = T_a + (T_a - T_f) f_-(\beta, s) \quad (24)$$

where

$$f_{\pm}(\beta, s) = \beta (\beta^2 + 12)^{-1/2} \exp\left\{ \left[\left(-\frac{1}{2} \beta \pm \frac{1}{2} \sqrt{\beta^2 + 12} \right) / L \right] s \right\}$$

On the scale $s = O(L)$ there is a radiative preheat and *postheat* zone separated by a thin region ($s = O(\lambda/MC_p)$) in which the temperature increases from

$$T_1 \equiv T_f + (T_a - T_f) \beta (\beta^2 + 12)^{-1} \quad (25)$$

to

$$T_* \equiv T_a + (T_a - T_f) \beta (\beta^2 + 12)^{-1/2} \quad (26)$$

The flame-speed is the adiabatic flame speed corresponding to a cold mixture of temperature T_1 so that

$$M / M_o = \exp\left\{ (E/2RT_a) \beta \left[\beta + T_a (T_a - T_f)^{-1} (\beta^2 + 12)^{1/2} \right]^{-1} \right\} \quad (27)$$

In order to discuss this formula it is convenient to introduce the *virtual Boltzman number*

$$\beta_o = 16 T_c^4 / M_o C_p T_c \quad (28)$$

Using CH₄/air adiabatic flame calculations of Giovangigli and Smooke [6] and with T_c equal to the adiabatic flame temperature we can plot variations of β_0 with equivalence ratio, and these are shown in Fig. 1. This defines a realistic range of values of β_0 .

Figure 2 shows variations of M/M_0 and β with β_0 determined from Eqns. (27), (28). The enhancement in the burning rate was described in ref. [3] in the case of small β ($\beta = O(RT_a/E)$) and we call it the *Joulin effect*. It is analogous in its physical origins to the enhancement described by Weinberg in so-called excess enthalpy flames [5]. Here the temperature at the reaction zone is raised above the adiabatic flame temperature by radiative preheating, whereas in Weinberg's flames the increment is generated by providing a heat conduction path superior to that of the gas.

The limit $\alpha \rightarrow 0, \beta \rightarrow \infty, \alpha\beta = O(1)$

The formulas (24) and (27) are not uniformly valid in β . Indeed, there is a distinguished limit $\alpha \rightarrow 0, \beta \rightarrow \infty, \alpha\beta = O(1)$. In this limit

$$\begin{aligned} \omega_1 L &\sim (2\alpha)^{-1} [1 + \sqrt{1 + 4\beta}] , \quad \omega_2 L \sim \alpha / \alpha\beta \\ \omega_3 L &\sim (2\alpha)^{-1} [1 - \sqrt{1 + 4\beta}] \end{aligned} \tag{29}$$

Thus the radiative preheat zone has thickness $O(L^2 MC_p / \lambda)$ whereas the postheat zone has thickness $O(\lambda / MC_p)$. The temperature rises slowly from T_f to T_a ; increases rapidly from T_a to

$$T. \sim T_a + (T_a - T_f)(1 + 4\beta)^{-1/2} \quad (30)$$

and then decreases rapidly to T_a . The burning rate is given by the formula

$$M / M_o = \exp\left\{ (E/2RT_a) \left[1 + T_a(T_a - T_f)^{-1} \sqrt{1 + 4\beta} \right]^{-1} \right\} \quad (31)$$

It is well known that in the limit of infinite activation energy the reaction zone is unstable if the temperature falls off towards the burnt gas on the same scale ($O(\lambda/MC_p)$) as it falls off towards the fresh gas [7]. This is why, for example, the so-called premixed-flame domain of diffusion flame burning, for which the burning rate is a decreasing function of Damkohle number (a portion of the middle branch of the familiar S-shaped response), is unstable. Thus the steady solution described in this section may not be physically realizable.*

α Not Small

When α is not small we return to Eqn. (23) in order to calculate the burning rate. Some curves are shown in Fig. 2. It is noteworthy that for high particle loadings, when α is not small, and for large values of the virtual Boltzman number, there is little augmentation of the burning velocity. This result should be compared with the

* The reaction zone instability occurs on a fast-time scale with the combustion field beyond the reaction zone unchanged. It is not captured by the stability calculations of the present paper.

saturation observed experimentally [2]. Note that in an experiment β_0 is varied by changing the equivalence ratio, and α_0 can be varied with β_0 fixed by changing L (i.e. by changing the particle loading).

Stability Analysis

We seek infinitesimal perturbations of the steady solution by writing

$$\begin{aligned}
 T &= T^s + \varepsilon T_0(s) e^{iky + \omega t} \\
 Y &= Y^s + \varepsilon Y_0(s) e^{iky + \omega t} \\
 \psi &= \psi^s + \varepsilon \psi_0(s) e^{iky + \omega t} \\
 F &= \varepsilon \delta e^{iky + \omega t}
 \end{aligned} \tag{32}$$

where $\varepsilon \rightarrow 0$.

The coefficient functions satisfy the equations:

$$\begin{aligned}
 \rho C_p [\omega T_0 + u T_0' - \delta \omega T^s] &= \lambda [T_0'' - k^2 T_0 + \delta k^2 T^s] \\
 &\quad - [\psi_0'' - k^2 \psi_0 + \delta k^2 \psi^s] \\
 \rho [\omega Y_0 + u Y_0' - \delta \omega Y^s] &= \rho D [Y_0'' - k^2 Y_0 + \delta k^2 Y^s]
 \end{aligned} \tag{33}$$

$$L^2 [\psi_0'' - k^2 \psi_0 + \delta k^2 \psi^s] = 3\psi_0 + 10 T_c^3 L T_0$$

Solutions are:

$$\underline{s < 0} \quad T_0 = A_1 e^{\gamma_1 s} + A_2 e^{\gamma_2 s} + \delta G_1 e^{\omega_1 s} + \delta G_2 e^{\omega_2 s}$$

$$Y_0 = C e^{\mu s} + \delta G_7 e^{\omega_4 s} \quad (34)$$

$$\psi_0 = B_1 e^{\gamma_1 s} + B_2 e^{\gamma_2 s} + \delta G_4 e^{\omega_1 s} + \delta G_5 e^{\omega_2 s}$$

$$\underline{s > 0} \quad T_0 = A_3 e^{\gamma_3 s} + A_4 e^{\gamma_4 s} + \delta G_3 e^{\omega_3 s}$$

$$Y_0 = 0, \quad (35)$$

$$\psi_0 = B_3 e^{\gamma_3 s} + B_4 e^{\gamma_4 s} + \delta G_6 e^{\omega_3 s}$$

Here $\gamma_1, \gamma_2, \gamma_3$ and γ_4 are the roots of the quartic

$$(\gamma L)^4 - \alpha^{-1} (\gamma L)^3 - (\gamma L)^2 [2(kL)^2 + 3 + \alpha^{-1} (\beta + \omega L u^{-1})] + (\gamma L) \alpha^{-1} [(kL)^2 + 3]$$

$$+ (kL)^4 + (kL)^2 (3 + \alpha^{-1} (\beta + \omega L u^{-1})) + 3\alpha^{-1} \omega L u^{-1} = 0 \quad (36)$$

where $\text{Re}(\gamma_1, \gamma_2) > 0$ and $\text{Re}(\gamma_3, \gamma_4) < 0$. The constants G_1 through G_7 are known (particular solutions) and C, A_1, A_2, A_3, A_4 are unknown.

The constants $\{B_i\}$ are related to $\{A_i\}$ by

$$B_i = 16T_c^3 L [L^2(\gamma_i^2 - k^2) - 3]^{-1} A_i. \quad (37)$$

Moreover μ is given by the formula

$$\mu = \frac{1}{2} M(\rho D)^{-1} + \frac{1}{2} [M^2(\rho D)^{-2} + 4(k^2 + \rho \omega / \rho D)]^{1/2}. \quad (38)$$

Thus there are six unknown constants $(A_1, A_2, A_3, A_4, C, \delta)$.

The jump conditions (10), when linearized, are:

$$\begin{aligned}
 [T_o] = 0, [\psi_o] = 0, [\varphi_o] = 0, [Y_o] = 0, \\
 [T_o] = -E(T_a - T_f)T_o / 2RT_o^2 \alpha L, [Y_o] = EY_f MT_o / 2RT_o^2 \rho D.
 \end{aligned}
 \tag{39}$$

These provide six relations amongst the six constants and so define a linear homogeneous system which only has a non-trivial solution for certain values of the eigenvalue ω . In this way, stability boundaries in the wave-number, Lewis-number plane can be constructed.

Representative stability results are shown in Fig. 3 for an activation energy θ of 15. Plotted are neutral stability boundaries for (a) $\alpha = 1$, (b) $\alpha = 0.5$, (c) $\alpha = 0.1$, and (d) $\alpha = .02$, in the Lewis number ($Le = \lambda / \rho D C_p$) - scaled wave-number (αk) plane, and for various values of the Boltzman number (β).

The right stability boundary (denoted by dashed curves in Fig. 3) corresponds to a pulsating or traveling wave instability ($\text{Im } \omega \neq 0$), one that is not accessible for common mixtures when $\beta = 0$. But radiative effects push this boundary sharply to the left, to commonly achieved values of Le . Figure 4a shows the locus of the intersection of this boundary with the line $\alpha k = c$ in the Le - β plane for $c = .001, 0.1, 0.5$, and 1.0 , when $\alpha = 1.0$. The shift to the left (smaller Le) with increasing β is eventually reversed. This is no different from the effect of burner-induced heat losses on the stability boundary in which displacement to the left is followed in due course by reversal of the entire curve [8].

The right stability boundary is not shown in Fig. 3c ($\alpha = .02$). For small values of α the roots are extremely sensitive to variations

in β and there are serious convergence difficulties. Sensitivity to a parameter which is only roughly defined (because of the linearized transport equation) discouraged us from examining this situation more carefully. If it is to be done it should be done in the context of a more accurate model than the one considered here.

The analogy with burner-induced losses carries over to the left stability boundary (denoted by solid curves in Fig. 3) which corresponds to the familiar cellular flames and for which $\omega = 0$. There is a strong tendency to suppress the instability by displacement of the curve away from $Le = 1$. Ronney [2] has reported that lean methane/air flames are smoothed by the addition of dust, in agreement with these results. Cellular flames in dustless mixtures are usually unsteady, a consequence of the fact that the maximum Lewis number on the stability boundary is then achieved when $k = 0$ (see, for example, the numerical solutions of the Kuramoto-Sivashinsky equation in [9]). This characteristic does not in general survive the addition of dust. For example, when $\alpha = 0.1$, $\beta = 5$ the right most point on the boundary is located at $\alpha k \simeq 0.42$. Under this circumstance we anticipate a steady cellular structure on a scale defined by this special value of the wave number. The same effect is seen when burner-induced heat losses are accounted for [8], as seen in stationary polyhedral flames [10], [11].

Concluding Remarks

We have shown that the introduction of significant radiative transport by the addition of dust to combustible mixtures can have a significant effect on the thermal-diffusive stability boundaries. The

pulsating instability can be strongly enhanced and the cellular instability suppressed. Suppression of cellular instabilities in lean methane/air mixtures has been reported by Ronney [2].

The radiation model that we have adopted is a crude one, although it appears to retain the essential physics. One of its characteristics is that it leads naturally to the definition of a Boltzman number that contains the numerical factor 16 rather than 4 (cf. Eqn. (13b)). As a consequence too much significance should not be attributed to the precise values of β that appear in the discussion and in the figures. The order-of-magnitude is correct however. Should more detailed experimental data become available in the future it might be appropriate to carry out a more accurate analysis, together with more detailed exploration of the stability boundary locations.

Acknowledgment

The research of JB is supported by AFOSR and by the Nasa-Lewis Research Center. Much of the work described here was carried out during visits to ICASE.

References

- [1] F. Williams, *Combustion Theory*, Benjamin/Cummings, p. 349, 1985.
- [2] A. Abbud-Madrid and P. Ronney, "Premixed flame propagation in an optically-thick gas", paper to appear in the *AIAA Journal*.
- [3] G. Joulin and B. Deshaies, *Combustion Science and Technology*, 47: 299-315, 1986.
- [4] G. Joulin, *Combustion Science and Technology*, 52: 377-395, 1987.
- [5] F. Weinberg, *15th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, pp. 1-17, 1974.
- [6] V. Giovangigli and M.D. Smooke, *Combustion Science and Technology*, 87: 241-256, 1992.
- [7] N. Peters, *Combustion and Flame*, 33: 315-318, 1978.
- [8] J. Buckmaster, *SIAM J. on Applied Mathematics*, 43: 1335, 1983.
- [9] D.M. Michelson and G.I. Sivashinsky, *Acta Astronautica*, 4: 1207-1221, 1977.
- [10] F.A. Smith and S.F. Pickering, *U.S. Bureau of Standards Journal of Research*, 3: 65-74, 1929.
- [11] J. Buckmaster, *SIAM J. on Applied Mathematics*, 44: 40, 1984.




Fig. 1 Virtual Boltzman number vs. Equivalence Ratio for lean methane/air flames, calculated using the flame temperatures and speeds obtained numerically by Giovangigli and Smooke [6].




Fig. 2 Variations of the mass flux M/M_0 with virtual Boltzman number for $\alpha = 0, 0.1, 0.2, 0.5,$ and 1.0 when $\theta = 12, T_g/T_f = 5$. Also shown (dotted line) are variations of the Boltzman number when $\alpha = 0$.




Fig. 3 Stability boundaries in the wave-number - Lewis number plane for $\theta = 10$, $T_g/T_f = 5$, $\alpha = 1, 0.5, 0.1, 0.02$, and different values of β .




Fig. 4 Locus of the point $\text{Re}(\omega) = 0$, $\alpha k = c$ in the Lewis number - β plane.

4a. Right branch, $\theta = 15$, $\alpha = 1.0$, $T_g/T_f = 5$.

4b. Left branch, $\theta = 15$, $\alpha = 1.0$, $T_g/T_f = 5$.