

2
EVALUATION OF 'PUREAU' WATER FOR USE AS
EMERGENCY DRINKING WATER FOR ADF
AIRCRAFT

AR-008-562

GE DRIVER

MRL-TN-648

DECEMBER 1993

AD-A277 068



DTIC
ELECTE
MAR 18 1994
S E D

APPROVED

FOR PUBLIC RELEASE



Commonwealth of Australia

DTIC QUALITY INSPECTED

MATERIALS RESEARCH LABORATORY

DSTO

Evaluation of "Pureau" Water for Use as Emergency Drinking Water for ADF Aircraft

G.E. Driver

MRL Technical Note
MRL-TN-648

Abstract

A commercially available, purified water packed in PET bottles has been tested for suitability as an emergency drinking water for ADF aircraft.

The water meets chemical and organoleptic requirements of the ADF, and is preferred to the current product on the basis of taste and the lower permeability of the package to water.

The product failed to meet the ADF's stringent microbiological specifications.

Further testing is required to determine the ability of the package to withstand the forces of ejection, and the high temperatures within the cockpit of aircraft parked in the sun in tropical areas of Australia.

DEPARTMENT OF DEFENCE
DSTO MATERIALS RESEARCH LABORATORY

Accession For	
NTIS	CRA&I ☒
DTIC	TAB ☒
Unannounced	☐
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

1390 94-08749
■■■■■■■■■■

94 3 18-007

Published by

*DSTO Materials Research Laboratory
Cordite Avenue, Maribyrnong
Victoria, 3032 Australia*

*Telephone: (03) 246 8111
Fax: (03) 246 8999
© Commonwealth of Australia 1993
AR No. 008-562*

APPROVED FOR PUBLIC RELEASE

Contents

1. INTRODUCTION	5
2. METHODOLOGY	6
2.1 Storage	6
2.2 Microbiological Analysis	6
2.3 Organoleptic Assessment	6
2.4 Physical Testing	6
3. RESULTS AND DISCUSSION	7
3.1 Chemical Analysis	7
3.2 Water Permeation of Packaging Material	7
3.3 Microbiological Investigation	7
3.4 Organoleptic Assessment	8
3.5 Physical Characteristics	8
4. CONCLUSIONS	9
5. RECOMMENDATIONS	9
6. REFERENCES	10

Evaluation of "Pureau" Water for Use as Emergency Drinking Water for ADF Aircraft

1. Introduction

The RAAF require a source of potable, long-life water for use in Personal Survival Packs (PSP). These are stored in the ejection seats of high performance aircraft and on other ADF aircraft. The current water is supplied by MRL-Tasmania to RAAF Specification (RAAF, 1973). Scottsdale municipal water is filtered and packed in a PVC bag, constructed from the same material used for blood bags. The final sterilisation of the water is by irradiation, although in the past the bags have been filled hot after sterilisation of the water by boiling, and also by aseptic filling after sterilisation by filtration.

The small quantities required by RAAF, currently 4000 packs per annum, mean that it has been difficult to have the packaging carried out on a commercial basis.

The material used for the bag has disadvantages. Plasticisers added to the plastic migrate into the water during storage giving the water a taint or unpleasant taste. The components migrating into the water are not considered harmful.

PVC has poor gas and water vapour barrier properties. Of most concern for the current application is the ability of water to migrate through the package. It has previously been shown that Emergency Water pouches held in a warm dry environment can lose several grams of water per day by transmission through the plastic. While the loss of water by this method is expected to be much lower under realistic storage conditions, this loss of water is the major limitation leading to the useful shelf life of two years.

RAAF, through HQADF, asked for an evaluation of the shelf life of a commercial product, "Pureau", produced by Noble Beverages. "Pureau" is claimed to be an extremely pure, sterile water packed in a blown PET (polyethylene terephthalate) bottle similar to bottles used for soft drinks.

2. Methodology

2.1 Storage

Five samples of Pureau were stored at each of 30°C and 37°C, in temperature controlled rooms, further samples were stored at ambient temperature in the laboratory. No attempt was made to control humidity, but due to ambient temperatures being below storage room temperatures, humidity was low. Measurements on one occasion indicated relative humidities of 42% and 26% in 30°C and 37°C rooms respectively. Samples were unwrapped, and stored on open shelves so that there was free circulation of air around each bottle. The air in the room was circulated by integral fans.

All samples were weighed at regular intervals over a fifty-six day period.

2.2 Microbiological Analysis

The sterility of five bottles from each of the storage temperatures and water stored at ambient temperature was examined using the pour plate method with Plate Count Agar (PCA) and R2A agar, with incubation at 30° C for five days (APHA, 1985).

2.3 Organoleptic Assessment

Samples of water stored at 30°C, 37°C and ambient temperature for 56 days, and at 80°C for fifteen hours were presented in randomised fashion to ten tasters, and ranked for flavour. Scottsdale municipal water was included as a control. Results were analysed by normalisation of the data (Fisher and Yates, 1949) and analysis of variance (Beyer, 1968).

2.4 Physical Testing

Bottles were placed in a stirred water bath at 70°C, 75°C, 80°C and 85°C for two hours. They were then examined for distortion or other damage.

Bottles were placed in a vacuum chamber and the pressure reduced to below - 80 kPa gauge. The bottles were observed for signs of leakage or other damage.

3. Results and Discussion

3.1 Chemical Analysis

Pureau is a highly purified and sterilised water packed in 350 mL PET bottles. The specifications supplied by Noble Beverages indicate less than 0.1 ppm for a wide range of elements, with most figures listed as less than 0.001 ppm. Figures relate to the level of detection of the particular element, and do not appear to be based on any scientific reasoning for requiring such low levels.

Typical analysis figures were supplied by Noble from Australian Government Analytical Laboratories (AGAL). AGAL is registered under the National Association of Testing Authorities (NATA), although the analysis report did not indicate this.

Further chemical analysis of Pureau was not undertaken.

The levels of dissolved solids are extremely low and equate to distilled, deionised water. Water of such quality is not required for drinking, or for storage under the conditions required by RAAF.

Water with higher concentrations of dissolved solids should be satisfactory for the intended use by RAAF, and could possibly be preferred by taste. While this has not been broached with Noble Beverages, it is unlikely that they would be willing to run such water through their plant, given the small quantities used by RAAF, and their presumed desire not to contaminate their equipment. This could be a subject of future discussion between Noble Beverages, or another manufacturer of bottled water, and RAAF.

3.2 Water Permeation of Packaging Material

Water loss from the bottles averaged 0.037 and 0.057 g per day at 30°C and 37°C respectively, over a 56 day period. The PVC material previously used has been shown to lose up to 2.5 g per day under similar conditions.

The loss of water from the PET bottles is therefore only 2% of that of the PVC pouches. It takes approximately 60 days for 1% of the water to be lost under the most extreme storage conditions studied. This extrapolates to a loss of the order of 10% of contents over a two year period. While water is in the PSP or packaged in the store, there will be no air movement, and possibly some build up of humidity within the closed environment around the bottled water. Because of this higher humidity, even when external conditions of low humidity exist, the loss of water by permeation is likely to be less than in the experimental situation. The shelf life of the bottled water is therefore not limited by the loss of water.

3.3 Microbiological Investigation

Microbiological analysis figures supplied by Noble Beverages, indicate a total microbiological count of less than one colony forming unit per 100 mL of water. Analysis figures were supplied by two independent laboratories, AGAL and Stanford Consulting Laboratories. Neither laboratory indicates on their report if

they have NATA registration for the analysis undertaken. The reports do not claim to have incubated the bottled water prior to analysis.

These analyses indicate only three day incubation of the water samples. Bacteria contaminating stored, bottled water are stressed, and therefore initially grow slowly. It is therefore usual to incubate such samples for at least three days using PCA and five days using R2A medium (APHA, 1985, p.862). Previous testing of irradiated water has also indicated very slow growth for a particular organism found to contaminate this product. Microbiological analysis was therefore conducted on the samples of Pureau. R2A medium is a low nutrient medium designed for the testing of water. The low nutrient level helps prevent stress caused by transfer from the very low level of nutrients present in water to media such as PCA.

As the water had been stored (incubated) for a lengthy period before use, testing was carried out by plating rather than Millipore filtration. The filtration methods are more sensitive, but possibly too sensitive if any multiplication of organisms had occurred during storage.

Of the fifteen bottles analysed, thirteen had total plate counts of less than one organism per millilitre of water. However two bottles stored at 30°C and 37°C, had bacterial counts of 34 and 33 per millilitre respectively on PCA. Counts (39, 39) using R2A were marginally higher.

This level of contamination is within the Australian standard for Total Plate Counts of bottled water of 100 microorganisms per millilitre, using PCA (NH & MRC, 1991), but well outside Nobles specification of less than one microorganism per 100 mL. The bottles showing growth were also outside the RAAF Specification (RAAF, 1973) which calls for less than one microorganism per millilitre.

The organism isolated from the samples has been identified as a *Flavobacterium* spp. The identification was based on the pink pigmentation of the colony on PCA and the biochemical profile using API20NE (API System). *Flavobacteria* are widely distributed in soil, and fresh and marine waters. They are not generally considered pathogenic to humans.

A greater knowledge of the processing and filling technology employed by Nobles is necessary to comment on the possible cause of this minor contamination.

3.4 Organoleptic Assessment

Results of the ranking test of Pureau and Scottsdale town water gave rank totals from 25 to 37, based on ten tasters. There were no significant differences between the rank totals for any of the samples tested, including the sample subject to temperature abuse.

3.5 Physical Characteristics

One of the claimed advantages for the PVC material, that has been in use for over ten years, was its ability to withstand the forces of ejection. The bag was designed to withstand forces amounting to the weight of the pilot plus equipment being accelerated by the ejection seat. This could amount to 250 kg at 12 g, or

3 tonne. These figures are considered excessive, as most of the weight of the pilot is taken by the seat pan of the ejection seat.

No work has been carried out on the forces that this PET container is able to withstand. RAAF will need to carry out simulated ejections at AVMED, to determine the suitability of the container for ejection seat use.

The bottle suffered no damage or leakage when subjected to a pressure of - 80 kPa gauge.

Bottles were heated in a water bath to hasten the extraction of taints from the bottle material. Some bottles were observed to distort, and a study was therefore conducted. At temperatures above 60°C the main part of the bottle shrunk. This is due to the "memory" built into the bottle during the blowing operation. This shrinkage caused expansion in the neck region. At a temperature of 85°C, this distortion was sufficient to cause considerable weakening of the bottle, such that it would not be able to withstand ejection.

Temperature inside aircraft sitting in the open rise considerably above ambient temperature. RAAF need to consider what temperatures are achieved in Australia's tropical north, and whether the PET bottle is suitable for these conditions.

4. Conclusions

- a. Pureau bottled water produced by Noble Beverages is chemically suitable for its intended use in ADF aircraft.
- b. Pureau meets Australian standards for packaged water and is considered suitable for use in PSP. The failure to meet the manufacturer's specification should be brought to the manufacturer's attention.
- c. The shelf life of Pureau, based on water permeation through the bottle wall is well in excess of two years.

5. Recommendations

- a. The suitability of the bottle for ejection seat use should be tested by simulated ejection.
- b. The suitability of the bottle to withstand temperatures attained within aircraft needs to be ascertained.
- c. Other manufacturers of bottled water could be approached to obtain alternative suppliers, and competitive quotes.

6. References

1. APHA (1985).
Standard methods for the examination of water and wastewater, 16th Ed.,
American Public Health Association, Baltimore.
2. Beyer, W.H. (1968).
Handbook of tables for probability and statistics, 2nd Ed., The Chemical Rubber
Co., Cleveland.
3. Fisher, R.A. and Yates, F. (1949).
Statistical tables for biological, agricultural and medical research, Oliver and Boyd,
London.
4. NH&MRC (1991).
Food standard S5 - Packaged water and packaged ice. *Food Standards Code*,
Australian Government Publishing Service, Canberra.
5. RAAF (1973).
Drinking water 250 mL flexible pack. *RAAF Specification Engineering S4*, HQ
Support Command RAAF, Melbourne, 23 June 1973.

Evaluation of "Pureau" Water for Use as Emergency
Drinking Water for ADF Aircraft

G.E. Driver

(MRL-TN-648)

DISTRIBUTION LIST

Director, MRL - title page only
Chief, Ship Structures and Materials Division
Dr G.E. Driver
MRL Information Services

Chief Defence Scientist (for CDS, FASSP, ASSCM)
Director (for Library), Aeronautical Research Laboratory
Head, Information Centre, Defence Intelligence Organisation
OIC Technical Reports Centre, Defence Central Library
Officer in Charge, Document Exchange Centre
Army Scientific Adviser, Russell Offices
Air Force Scientific Adviser, Russell Offices
Navy Scientific Adviser - data sheet only
Scientific Adviser, Defence Central

1 copy only

Director General Force Development (Land)
Senior Librarian, Main Library DSTOS
Librarian - MRL Sydney - data sheet only
Librarian, H Block

8 copies

Serials Section (M List), Deakin University Library, Deakin University, Geelong 3217
NAPOC QWG Engineer NBCD c/- DENGERS-A, HQ Engineer Centre, Liverpool
Military Area, NSW 2174

Librarian, Australian Defence Force Academy
Counsellor, Defence Science, Embassy of Australia - data sheet only
Counsellor, Defence Science, Australian High Commission - data sheet only
Scientific Adviser to DSTC Malaysia, c/- Defence Adviser - data sheet only
Scientific Adviser to MRDC Thailand, c/- Defence Attache - data sheet only
Head of Staff, British Defence Research and Supply Staff (Australia)
NASA Senior Scientific Representative in Australia
INSPEC: Acquisitions Section Institution of Electrical Engineers
Head Librarian, Australian Nuclear Science and Technology Organisation
Senior Librarian, Hargrave Library, Monash University
Library - Exchange Desk, National Institute of Standards and Technology, US
Exchange Section, British Library Document Supply Centre
Periodicals Recording Section, Science Reference and Information Service, UK
Library, Chemical Abstracts Reference Service
Engineering Societies Library, US
Documents Librarian, The Center for Research Libraries, US

Dr Dougal Watson, Research Officer, Institute of Aviation Medicine, RAAF
Base Williams, Point Cook, VIC 3027
SO Science, HQ 1st Division, Gallipoli Barracks, Enoggera, QLD 4052

(MRL-TN-648)

DISTRIBUTION LIST
(Continued)

SO2 LE, DEGP-A, Materiel Division (Army), Russell Offices, Canberra ACT 2600	
DSFD(L) (B-3-5), Russell Offices, Canberra ACT 2600	
DSTIC, Department of Defence, Anzac Park West Offices, Canberra ACT 2600	18 copies
MRL Queensland, 496 Palmerston Highway, Innisfail, QLD 4860	
DGNHS, Department of Defence, Campbell Park Offices, Canberra ACT 2600	
Naval Support Command, PO Box 706, Darlinghurst NSW 2070	
Directorate of Fleet Supply Services, Dept. of Defence (Navy), Campbell Park 3-1-5, Canberra ACT 2600	
Assistant Chief Materiel - A (ACMAT-A), Russell Offices, Canberra ACT 2600	
Assistant Chief Logistics - A (ACLOG-A), Russell Offices, Canberra ACT 2600	
Director of Ordnance, MILPO, Bandiana VIC 3694	
Director Army Training and Doctrine, National Standardisation Office, Russell Offices, Canberra ACT 2600	6 copies
Director General of Army Health Services, Campbell Park Offices, Canberra ACT 2600	
Land Force Headquarters, Victoria Barracks, Paddington NSW 2021	
Director of Infantry, HQ Infantry Centre, MILPO Singleton NSW 2331	
Director of Catering, HQ Catering Centre, MILPO Puckapunyal VIC	
Senior Inspector Foodstuffs, Headquarters Logistic Command, GPO Box 1932R, Melbourne VIC 3001	
Headquarters Logistic Command, St James Plaza, GPO Box 1932R, Melbourne Vic 3001	3 copies
Headquarters Training Command, Naval PO, Balmoral NSW 2091	
Headquarters Land Warfare Centre, Kokoda Barracks, Canungra QLD 4275	
Head, Defence Centre - Brisbane, Locked Bag 4, Roma Street PO, Brisbane QLD 4003	
Head, Defence Centre - Sydney, PO Box 706, Darlinghurst NSW 2010	2 copies
Head, Defence Centre - Melbourne, GPO Box 1932R, Melbourne VIC 3007	2 copies
Librarian, H Block, Victoria Barracks, Melbourne VIC 3000	
Head, Defence Centre - Adelaide, Keswick Barracks, keswick SA 5035	
Head, Defence Centre - Perth, Locked Bag 5001, Fremantle WA 6160	
Head, Defence Centre - Hobart, Anglesea Barracks, Davey St, Hobart TAS 7001	
Head, Defence Centre - Darwin, GPO Box 4746, Darwin NT	
Librarian, Bridges Memorial College, Duntroon ACT 2600	
Commanding Officer/Chief Instructor, RAAOC Centre, MILPO Bandiana VIC 3662	3 copies
Director of Logistics Policy (LPOL2), Dept. of Defence (Air Force), Russell Offices, Canberra ACT 2600	
Director General Air Force Health Services, Dept. of Defence, Campbell Park Offices, Canberra ACT 2600	
Headquarters Operational Command (Staff Office Catering), RAAF Glenbrook NSW 2773	
Headquarters Support Command (CEO4/E41), RAAF Defence Centre, 366 St Kilda Rd, Melbourne VIC 3000	
Commanding Officer, Institute of Aviation Medicine, Point Cook VIC 3029	
Associate Professor C.W. Binns, head, School of Community Health, Curtin University of Technology, GPO Box U1987, Perth WA 6001	
Librarian, CSIRO Division of Food Processing, PO Box 52, North Ryde NSW 2113	
Australian Govt. Analyst, PO Box 65, Belconnen ACT 2616	
The Director, Australian Government Analytical Laboratories, PO Box 385, Pymble NSW 2073	
The Director, Australian Government Analytical Laboratories, 51-65 Clarke St, South Melbourne VIC 3205	

(MRL-TN-648)

DISTRIBUTION LIST
(Continued)

The Director, Australian Government Analytical Laboratories, 338 Tapleys Hill Rd,
Seaton SA 5023

The Director, Australian Government Analytical Laboratories, PO Box 83,
Cottesloe WA 6011

The Director, Australian Government Analytical Laboratories, PO Box 84,
Kingston TAS 7050

Librarian, Antarctic Division, Channel Highway, Kingston TAS 7050

Librarian, Dept. Community Services & Health, GPO Box 9848, Canberra
City ACT 2601 2 copies

Dr R.C. Hutchinson I.S.O., Derwentlaken Road, Otago, TAS 7017

Serials Section, State Library of Tasmania, Hobart TAS 7000 2 copies

Serials Unit, State Library of Queensland, PO Box 488, South Brisbane QLD 4101

Head, School of Food Technology, University of NSW, Kensington NSW 2033

Serials, Biomedical Library, University of NSW, Kensington NSW 2033

The Medical Library, Flinders University of South Australia, Bedford Park SA 5042

Australian Archives, Tasmanian Regional Office, 4 Rosny Hill Rd, Rosny Park TAS 7018 2 copies

Australian Army Representative, Australia House, Strand, London WC2 B4LA, UK

DGST(N) 82B, Room 91, D Block, MOD Ensleigh, Bath BA1 5AB, UK

Senior Food Chemist, Room 88, D Block, MOD Ensleigh, Bath BA1 5AB, UK

MOD, Defence Medical Services Directorate (EMR2), First Avenue House, High
Holborn, London WC1V 6HE, UK

Library, APRE, Building F138, c/- RAE Farnborough GU14 6TD, UK

Librarian, Leatherhead Food R.A. Randalls Road, Leatherhead KT22 7RY, UK

Dr D.A.T. Southgate, Nutrition & Food Quality Dept. Institute of Food Research,
Colney Lane, Norwich NR4 7UA, UK

Principal Food Chemist, Laboratory of the Government Chemist, Armed Services Food
Laboratory, Royal Clarence Yard, Gosport PO12 1AY, UK

Librarian, AFRC Institute of Food Research, Bristol Laboratory, Langford, Bristol BS18 7DY, UK

Food Science Laboratory - MAFF, 65 Romney St, London SW1, UK

D Food S, National Defence Headquarters, 101 Colonel By Drive, Ottawa, Ontario K1A 0K2, Canada

NDHQ Main Library (Att. Land Technical Library), National Defence Headquarters,
101 Colonel by Drive, Ottawa, Ontario K1A 0K2, Canada

Librarian, Research Branch, Food Research and Development Centre, 3600 Casavant Blvd West,
Saint-Hyacinthe, Quebec J2S 8E3, Canada

Director, Food Research & Nutrition Council, c/- Food Commissioner, Union Place,
Colombo, Sri Lanka

Armed Services Food Chemist, 89 Supply Depot RAOC (BFPO 40), Viersen, Germany

Defence Adviser, Ghana High Commission, 13 Belgrave Square, London SW1X 8PR, UK 5 copies

Director General, Research & Development Organisation, Ministry of Defence,
New Delhi 11, India 2 copies

Director, Food Research Laboratory, Jyothinagar, Mysore 570 010, India 2 copies

The Director, Defence Scientific Establishment, Ministry of Defence, Auckland Naval Base
Post Office, Auckland NZ

DTMC, RNZCT Directorate, Army General Staff, Private Bag, Wellington NZ

SO3 Foodstuffs/POL Section, Directorate of Supply, HQ PNGDF, Free Mail Bag,
Boroka NCD, Papua New Guinea

Science Research Supervisor, Food Research Division, Food & Nutrition Research Institute,
Manila, Philippines 3 copies

Mr Philip Brandler, Food Engineering Laboratory, US Army Natick RDT & E Center,
Attn: STRNC-Y, Natick MA 01760-5020, USA

Dr Elizabeth Sutphen, Department of the Army, US Army Foreign Science & Technology Center,
220 Seventh Street, NE, Charlottesville, Virginia 22901, USA

STRNC-W, US Army Natick R & D Center, Natick MA 01760-5020, USA

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

REPORT NO.
MRL-TN-648AR NO
AR-008-562REPORT SECURITY CLASSIFICATION
Unclassified

TITLE

Evaluation of "Pureau" water for use as emergency drinking water for ADF aircraft

AUTHOR(S)
G.E. DriverCORPORATE AUTHOR
DSTO Materials Research Laboratory
PO Box 50
Ascot Vale Victoria 3032REPORT DATE
December, 1993TASK NO.
ADF 90/073SPONSOR
DSFD(L)FILE NO.
G6/4/8-4626REFERENCES
5PAGES
11

CLASSIFICATION/LIMITATION REVIEW DATE

CLASSIFICATION/RELEASE AUTHORITY
Chief, Ship Structures and Materials Division

SECONDARY DISTRIBUTION

Approved for public release

ANNOUNCEMENT

Announcement of this report is unlimited

KEYWORDS

Potable water
Drinking water

Emergency water

Survival water

ABSTRACT

A commercially available, purified water packed in PET bottles has been tested for suitability as an emergency drinking water for ADF aircraft.

The water meets chemical and organoleptic requirements of the ADF, and is preferred to the current product on the basis of taste and the lower permeability of the package to water.

The product failed to meet the ADF's stringent microbiological specifications.

Further testing is required to determine the ability of the package to withstand the forces of ejection, and the high temperatures within the cockpit of aircraft parked in the sun in tropical areas of Australia.

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED