(1)

TION PAGE

Form Approved
OMB No. 0704-0188

1 AGENCY USE ONLY (Leave blank)	2 REPORT DATE	3 REPORT TYPE AND DATES COVERED
	March 1994	Professional Paper

4 TITLE AND SUBTITLE

A COMPARISON OF ROUGH SURFACE PARABOLIC EQUATION MODELS

5 FUNDING NUMBERS

PR: MP92
PE: 0602435N

6 AUTHOR(S)

A. E. Barrios

7 PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Command, Control and Ocean Surveillance Center (NCCOSC)
RDT&E Division
San Diego, CA 92152-5001

8 PERFORMING ORGANIZATION REPORT NUMBER

9 SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Command, Control and Ocean Surveillance Center (NCCOSC)
RDT&E Division
San Diego, CA 92152-5001

10 SPONSORING/MONITORING AGENCY REPORT NUMBER

11 SUPPLEMENTARY NOTES

12a DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

13 ABSTRACT (Maximum 200 words)

Several parabolic equation models currently exist that model radiowave propagation over the ocean. Few of these models can accurately account for rough surface effects over an ocean environment. Several techniques to account for these effects, implemented within the split-step parabolic equation (PE) algorithm, are investigated.

Published in *URSI National Radio Science Meeting Program*, January 1994, page 193.

14 SUBJECT TERMS

15 NUMBER OF PAGES

16 PRICE CODE

17 SECURITY CLASSIFICATION OF REPORT	18 SECURITY CLASSIFICATION OF THIS PAGE	19 SECURITY CLASSIFICATION OF ABSTRACT	20 LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	SAME AS REPORT

21a NAME OF RESPONSIBLE INDIVIDUAL	21b TELEPHONE *(Include Area Code)*	21c OFFICE SYMBOL
A. E. Barrios	(619) 553-1429	Code 543

A COMPARISON OF ROUGH SURFACE PARABOLIC EQUATION MODELS

Amalia E. Barrios
Naval Command, Control and Ocean Surveillance Center
RDT&E DIV 543
53170 WOODWARD ROAD
SAN DIEGO, CA 92152-7385

Several parabolic equation models currently exist that model radiowave propagation over the ocean. Few of these models can accurately account for rough surface effects over an ocean environment. Several techniques to account for these effects, implemented within the split-step parabolic equation (PE) algorithm, are investigated.

Two of the rough surface algorithms to be discussed were originally developed to model acoustic wave fields incident on a rough boundary. The first model (M.E. Moore-Head, E.S. Holmes, JASA, 86(1), 247-251, 1989) is based on an angle-dependent surface loss function that is applied to the field in a layer near the surface. The second model (Tappert, private communication) does not depend on incident angle, but instead modifies the PE by including the impedance boundary condition as a singular index of refraction. The third method uses the mixed transform algorithm (J.R Kuttler, G.D. Dockery, Radio Sci., Mar.-Apr., 381-393, 1991), in which the impedance boundary condition is directly applied to the field at each range step. This method relies on an equivalent rough surface reflection coefficient, which is angle-dependent. The final method simply modifies the starter field by multiplying the rough surface reflection coefficient and the reflected field.

All of the above models will be compared with a reference waveguide model that is shown to agree well with signals measured in the presence of slight to moderate sea states.

Note: Commision F. Prefer to precede H. Hitney