


AD-A279 980



NSWCDD/TR-93/169



WAVELET TRANSFORMATIONS FOR HELICOPTER IDENTIFICATION VIA ACOUSTIC SIGNATURES

**BY JEFFREY L. SOLKA CAREY E. PRIEBE
HALFORD I. HAYES GEORGE W. ROGERS
SYSTEMS RESEARCH AND TECHNOLOGY DEPARTMENT**

MAY 1994

**DTIC
ELECTE
JUN 09 1994
S F D**

Approved for public release; distribution is unlimited.

94-17515



2580



NAVAL SURFACE WARFARE CENTER

DAHLGREN DIVISION

DAHLGREN, VIRGINIA 22448-5100

94 6 8 120

NSWCDD/TR-83/169

WAVELET TRANSFORMATIONS FOR HELICOPTER IDENTIFICATION VIA ACOUSTIC SIGNATURES

BY JEFFREY L. SOLKA CAREY E. PRIEBE
HALFORD I. HAYES GEORGE W. ROGERS
SYSTEMS RESEARCH AND TECHNOLOGY DEPARTMENT

MAY 1994

Approved for public release; distribution is unlimited.

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

NAVAL SURFACE WARFARE CENTER
DAHLGREN DIVISION
DAHLGREN, VIRGINIA 22448-5100

FOREWORD

The role that the wavelet transformation might play in the identification of helicopters from their acoustic signals is explored in this document. The utility of using a feature extraction system employing both conventional Fourier transform techniques in combination with the wavelet transform is discussed. Depending on the nature of the mission, such a system could either improve the helicopter identification process by suppressing transient noise prior to feature extraction using conventional techniques or provide the opportunity to use transient signatures to identify a specific helicopter in a group consisting of homogenous model types.

This work was done in support of the Advanced Processors for Weapons Sensor Fusion program of the U. S. Marine Corps and has been conducted in the Advanced Computation Technology Group of the Systems Research and Technology Department.

This report has been reviewed by Dr. Richard A. Lorey, Head, Advanced Computation Technology Group.

Approved by:



D. B. COLBY, Head
Systems Research and Technology Department

ABSTRACT

The ability to classify helicopters based on their acoustic signature has applications to both detection and tracking. The current approach to this problem uses standard signal-processing techniques to extract features based on the fundamental harmonics of the helicopters' blades. This document examines the role that the wavelet transformation might play in this feature extraction process. It addresses ways to use the wavelet transform both to improve the performance of the existing approach and to expand the capabilities of the classification system.

CONTENTS

	Page
INTRODUCTION: HELICOPTER IDENTIFICATION PROBLEM	1
WAVELET TRANSFORMATION.....	1
RESULTS.....	5
SYSTEM DESIGN CONSIDERATIONS	12
CONCLUSION	13
REFERENCES.....	14
BIBLIOGRAPHY.....	15
DISTRIBUTION.....	(1)

ILLUSTRATIONS

Figure	Page
1 HAAR MOTHER WAVELET.....	2
2 BLURRING FUNCTION CORRESPONDING TO HAAR MOTHER WAVELET ..	3
3 GRAPH OF DAUBECHIES COMPACTLY SUPPORTED BLURRING FUNCTION 2^{ϕ}.....	4
4 GRAPH OF DAUBECHIES COMPACTLY SUPPORTED MOTHER WAVELET FUNCTION 2^{ψ}.....	5
5 TIME DOMAIN PLOT OF TWO SIGNALS.....	6
6 WAVELET TRANSFORM FOR HELICOPTER 110.....	6
7 WAVELET TRANSFORM FOR HELICOPTER 117.....	7
8 HISTOGRAM OF FEATURES AT RESOLUTION LEVEL OF 2^{-5} FOR TWO HELICOPTERS	7
9 $f(x) = \sin(x) + N(0,1)$	9
10 DAUBECHIES $N=8$ WAVELET COEFFICIENTS FOR SIGNAL OF FIGURE 9...	10
11 COEFFICIENTS AFTER PRUNING TECHNIQUES OF DONOHOE AND JOHNSTONE	11

ILLUSTRATIONS (CONTINUED)

Figure		Page
12	SIGNAL RECONSTRUCTED FROM PRUNED COEFFICIENTS	11
13	SYSTEM FLOWCHART	12

TABLE

Table		Page
1	FIRST TWO FEATURE VECTORS FOR EACH CLASS	8

INTRODUCTION: HELICOPTER IDENTIFICATION PROBLEM

The problem of interest here is the classification and tracking of helicopters from their acoustic signatures. These tasks are to take place under field conditions. The timeline requirement for these tasks is as close to real-time as possible.

There are several things that act to complicate this problem. First, there is the existence of transient battlefield signals such as gunshots, explosions, etc. Second, there are periodic processes that are part of the environment. These include generator noise and friendly craft signatures. The final factor is that there are usually several crafts' signals acting in concert with one another. These factors act either to degrade the signal of interest or to introduce artifacts into the signal that compromise the classification and tracking mission.

Current approaches to this problem use spectral analysis techniques to extract the fundamental frequencies of the main and tail rotor of the craft. A classification signature is formed using the ratio of these frequencies. Recent work by Poston¹ et al. has employed harmogram analysis to extract these frequencies.

This document examines the use of the wavelet transformation (WT) as an alternate approach to this feature extraction problem. Feature extraction schemes that only use the WT and hybrid wavelet transformation/fast Fourier transform (WT/FFT) schemes are discussed within. The use of the WT to circumvent some of the above mentioned problems is also discussed.

This document begins with a brief review of the mathematical underpinnings of the WT, including discussions of both continuous and discrete WT. With this background in hand, the application of the WT to signal processing will be considered with specific attention to the helicopter problem. These discussions include some information about available hardware for real-time implementation of the WT. This document concludes with recommendations for future work.

WAVELET TRANSFORMATION

As a starting point for the introduction to the WT, the concept of Fourier series expansion will be reviewed briefly. In Fourier series expansion, the sine and cosine functions are used at different frequencies as a basis for the space $L^2(\mathbb{R})$ of square integrable functions. This basis is very useful for decomposing functions of a periodic nature; i.e., those functions that are localized in frequency space.

The basis functions used in the WT are dilations and translations of a single function known as the mother wavelet Ψ . The k th order translation of Ψ at a resolution of order j is given by

$$\Psi_{jk}(x) = \sqrt{2^{-j}}\psi(2^{-j}x - k) \quad (1)$$

Given certain properties on this mother wavelet, the Ψ_{jk} 's form an orthonormal basis of $L^2(\mathbb{R})$.

A classical example of such a mother wavelet is the Haar function $\psi(x) = 1$, if $0 \leq x \leq 1/2$, -1 , if $1/2 \leq x \leq 1$, and 0 otherwise (see Figure 1). The Haar function is a good example of how simple a mother wavelet can be. The wavelets that are used within this document are smoother generalizations of the Haar wavelet.




FIGURE 1. HAAR MOTHER WAVELET

For the purposes of this mathematical development, discussions will be limited to the one-dimensional WT. The inner product of $f(x)$ with $g(x)$ is written as

$$\langle g(u), f(u) \rangle = \int_{-\infty}^{\infty} g(u)f(u) du \quad (2)$$

Before the implementation details of the discrete wavelet transform (DWT) are discussed, some background on the continuous wavelet transform is appropriate. Given a function $f(x)$, the goal is to expand the function in the wavelet basis. One desires to write

$$f(x) = \sum_{jk} d_{jk}\Psi(x) \quad (3)$$

where the expansion coefficients are given by

$$d_{jk} = \langle f(x), \psi_{jk} \rangle \quad (4)$$

In the DWT case, one starts with a data set $S^0 = \{x_1^0, x_2^0, \dots, x_N^0\}$ where N is a power of 2. This discussion of the DWT will be based on the multiresolution approach of Mallat. In this approach, one starts with a blurring function ϕ that along with its dilations and translations ϕ_{jk} spans the space of multiresolution approximations of the original function. This ϕ , in turn, induces a wavelet ψ and basis ψ_{jk} . These ϕ_{jk} and ψ_{jk} act together to span the space of $L^2(\mathbb{R})$. The blurring function for the Haar wavelet is just the characteristic function on $[0,1]$, i.e. $\chi(x) = 1$ if $x \in [0, 1]$ and $= 0$ otherwise (see Figure 2).




FIGURE 2. BLURRING FUNCTION CORRESPONDING TO HAAR MOTHER WAVELET

In this manner, the original signal at a resolution of 2^0 is split into a direct sum of a multiresolution approximation at a level of 2^{-1} (obtained using the appropriate ϕ_{jk} 's) and a detail signal (or set of wavelet coefficients) is obtained using the appropriate ψ_{jk} 's. Therefore, one symbolically writes

$$S^{2^0} = S^{2^{-1}} \oplus D^{2^{-1}} \quad (5)$$

where $D^{2^{-1}}$ is the detail signal at a resolution of 2^{-1} . In some sense, $S^{2^{-1}}$ can be thought of as the best approximation at a resolution level of 2^{-1} of the original signal and $D^{2^{-1}}$ is the set of details

that are lost in going from S^{2^0} to S^{2^1} . This process can be repeated using the multiresolution approximation to the signal at the level of 2^{-1} as the starting point. This leads to

$$S^{2^{-1}} = S^{2^{-2}} \oplus D^{2^{-2}} \quad (6)$$

which is analogous to Equation 5. Finally we may combine these equations together to write

$$S^{2^0} = (S^{2^{-2}} \oplus D^{2^{-2}}) \oplus D^{2^{-1}} \quad (7)$$

In this manner, the signal is reconstructed from its set of wavelet coefficients and lowest level multiresolution approximation.

An inherent drawback to the Haar wavelet is its lack of smoothness. This problem has been addressed by Daubechies³ and others by taking convolution powers of the Haar mother wavelet. The graphs of the $N=2$ second-order convolution powers for the blurring function and the mother wavelet are given in Figures 3 and 4.

By varying N , one can obtain different blurring functions N^\oplus and wavelet functions N^Ψ . The smoothness of these functions increases as N is allowed to increase. For a delightful introduction to the creation of wavelet bases, see the recent paper of Strichartz.⁴




FIGURE 3. GRAPH OF DAUBECHIES COMPACTLY SUPPORTED BLURRING FUNCTION 2^\oplus




FIGURE 4. GRAPH OF DAUBECHIES COMPACTLY SUPPORTED MOTHER WAVELET FUNCTION 2^ψ

RESULTS

In this section, some preliminary classification results are presented. These results were obtained using field collected signals from two different helicopter models. Ultimately, the fielded system must possess the ability to distinguish between several different models, but this proof of concept study only addresses the two-class problem.

The two helicopter signals are designated 110 and 117. The signals were collected at 2000 Hz. The time domain representation for approximately 2 sec (4096 samples) of signal data is given in Figure 5.

The dyadic Daubechies $N=2$ wavelet transform of each of the two signals is given in Figures 6 and 7. The coefficients are plotted bottom to top from a resolution level of $2^{-1} = 2048$ values to a resolution level of $2^{-11} = 2$ values. The decision to use the $N=2$ mother-wavelet for the subsequent discriminant analysis was made somewhat arbitrarily. Figure 8 shows the histogram for the two helicopters.




FIGURE 5. TIME DOMAIN PLOT OF TWO SIGNALS




FIGURE 6. WAVELET TRANSFORM FOR HELICOPTER 110




FIGURE 7. WAVELET TRANSFORM FOR HELICOPTER 117




FIGURE 8. HISTOGRAM OF FEATURES AT RESOLUTION LEVEL OF 2^{-5} FOR TWO HELICOPTERS

Given this set of coefficients, one is faced with the daunting task of extracting an appropriate set of features from them. The curse of dimensionality and common sense prevents one from conducting discriminant analysis in R^{4095} . With this end in mind, the following procedure was used.

Given $D^l = (d_1^l, d_2^l, \dots, d_{2^{l+1}}^l)$, the set of wavelet coefficients at level 2^l , the energy E^l at this resolution level can be estimated using

$$E^l \propto \sum_{i=1}^{2^{l+1}} (d_i^l)^2 \quad (8)$$

The set of 12 values $(E^0, E^1, \dots, E^{11})$ was then normalized by using a standard linear transformation to map the largest value to 1 and the smallest value to 0. The sampling window was then shifted 10 units to the right, and the process was repeated. In this manner, 591 twelve-dimensional data points were generated for each of the two signals.

These data will now be analyzed. Table 1 contains the first two feature vectors for each class. One notices that the maximum energy concentration occurs at a different resolution level for the two classes. In particular, Signal 110 obtains its maximum at a resolution level of 2^{-5} , while Signal 117's maximum occurs at level 2^{-6} . It would be very fortuitous from a discriminant analysis perspective if this trend persisted throughout the signal duration. In fact, the signals studied indicate this trend is consistent throughout the duration of the signal. The histogram of Figure 8 illustrates that there is no overlap between the histograms of the level 2^{-5} feature for 110 and 117. In fact, as with the first two examples, the value holds constant at 1; i.e., the maximum energy for Signal 110 consistently occurs at a resolution level of 2^{-5} .

TABLE 1. FIRST TWO FEATURE VECTORS FOR EACH CLASS

Level	110-1	110-2	117-1	117-2
2^{-12}	0.000	0.001	0.000	0.002
2^{-11}	0.004	0.000	0.000	0.000
2^{-10}	0.024	0.006	0.012	0.015
2^{-9}	0.253	0.283	0.011	0.011
2^{-8}	0.109	0.071	0.049	0.049
2^{-7}	0.137	0.120	0.060	0.057
2^{-6}	0.344	0.340	1.000	1.000
2^{-5}	1.000	1.000	0.617	0.607
2^{-4}	0.596	0.613	0.296	0.271
2^{-3}	0.161	0.137	0.118	0.126
2^{-2}	0.106	0.104	0.093	0.085
2^{-1}	0.111	0.101	0.131	0.129

It is certainly appropriate at this point to elaborate on the significance of this phenomena and to try to provide some explanation of the underlying mechanism that produces it. Note that perfect classification results can be obtained using the features of Figure 8. A $P(CC)=1.0$ can be obtained with a corresponding $P(FA)=0.0$ using a simple threshold between the two distributions, which clearly demonstrates the utility of this feature.

Given the periodic nature of the signals, it is possible for the energy to be partially concentrated at a particular resolution level. Similarly, the presence of transients in the signal can be manifested by energy concentration at a certain resolution level. The phenomena seen may be a combination of these two effects. If the concentration is solely frequency based, then this signature may be useless in distinguishing between two of the same models or between any two signals with similar frequency components. The utility of the signature is greatly enhanced if it is based on transients in the signal.

A capability of the WT that has not been discussed is noise/transient suppression. Given a signal that has been corrupted by some sort of stochastic process, it is possible to decompose the signal in a wavelet basis and then reconstruct the signal with the noise suppressed. The results section concludes with an illustration of this capability. The original signal $f(x)=\sin(x) + N(0,1)$ is displayed in Figure 9. The wavelet coefficients for a Daubechies wavelet $N = 8$ is plotted in Figure 10.




FIGURE 9. $f(x) = \sin(x) + N(0,1)$





FIGURE 10. DAUBECHIES N=8 WAVELET COEFFICIENTS
FOR SIGNAL OF FIGURE 9

The aim is to prune some of the coefficients of the noisy signal, while the ultimate goal is the removal of those coefficients produced by the noise component of the signal. The hard thresholding approach of Donoho and Johnstone⁵ is used here. In this approach, the variation of the coefficients is computed and a given coefficient d is kept if it satisfies

$$|d| \geq s\sqrt{2\log M} \quad (9)$$


where M is the number of wavelet coefficients. Thresholding can be applied to any number of levels.

The pruned coefficients from the sinusoidal signal are displayed in Figure 11. The pruning operator was applied across all the levels. As can be gleaned from Figure 11, the number of coefficients has decreased markedly.



**FIGURE 11. COEFFICIENTS AFTER PRUNING TECHNIQUES
OF DONOHOE AND JOHNSTONE**

The signal reconstructed from the pruned coefficients is plotted in Figure 12. As can be seen, the pruning process has removed a large component of the noise from the signal. In addition, the reconstruction process has faithfully reproduced the underlying structure of the data. This type of noise suppression technique or one of its variants would have application to the removal of battlefield transients, such as artillery blasts, from the helicopter signals.



**FIGURE 12. SIGNAL RECONSTRUCTED FROM
PRUNED COEFFICIENTS**

SYSTEM DESIGN CONSIDERATIONS

Before concluding, some of the system design and implementation issues will be considered. Some ideas will be presented as to how the WT can be used as part of a signal-processing suite, and appropriate hardware for its implementation will be discussed. The use of the WT for feature extraction and noise suppression has been demonstrated in the previous sections. The proposed classification system utilizes both of these capabilities, as illustrated in Figure 13.

After acquisition, the WT of the signal is performed using dedicated hardware, which will be discussed later. The signal is then reconstructed without transients and noise and passed to the harmogram analysis section. It must be noted that the WT section functions not only to *clean* the input signal but also to extract wavelet based features from the signal. These features are then fed to the classification section for fusion with the harmogram features. In the classifier section of the system, the WT and harmogram features are fused, and discriminant analysis is performed.

A good example of dedicated WT hardware is the AWARE Wavelet Transform Processor (WTP) chip. This device is capable of performing both the one- and two-dimensional wavelet transform in both the forward and inverse directions. This chip fully implements 2 (Harr), 4, and 6 coefficient transformations and can implement transformations requiring a longer supported wavelet via a cascading mechanism.⁶ The chip operates at a clock speed of 30 MHz and has a reported execution speed of 33 nsec per transformed coefficient. This speed is fast enough to meet the requirements of most acoustic and image processing systems.




FIGURE 13. SYSTEM FLOWCHART

CONCLUSION

Some preliminary results have been provided that detail the application of the WT to acoustic signal classification. Whether the behavior of the wavelet features is a manifestation of the periodic component of the signal or an as-yet unidentified transient component will be the subject of investigations. Other future work will focus on the multiclass problem, the use of nonorthogonal wavelet bases, and alternate techniques for feature extraction. In addition, the transient suppression ability of the WT on field collected artillery blast data will be evaluated.

REFERENCES

1. Poston, W.L.; Holland, O.T.; and Nichols, K.R., *Enhanced Harmogram Analysis Techniques for Extraction of Principal Frequency Components*, TR-92/313, Naval Surface Warfare Center Dahlgren Division, VA.
2. Mallat, S. G., "A Theory for Multiresolution Signal Decomposition: The Wavelet Representation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol.11, No. 7, July 1989, pp 674-693.
3. Daubechies, I., *Ten Lectures on Wavelets*, SIAM, Philadelphia, PA, 1992.
4. Strichartz, R. S., "How To Make Wavelets," *The American Mathematical Monthly*, The Mathematical Association of America, Washington DC, June-July 1993, pp. 539-556.
5. Donoho, D. L. and Johnstone, I. M., "Ideal spatial adaptation by wavelet shrinkage," *Biometrika (subject to revision)*, 1993.
6. Solka, Jeffrey facsimile communication with Christina Gorecki concerning "Aware Wavelet Transform Processor (WTP) Preliminary Specifications," Aware Inc., 1992.

BIBLIOGRAPHY

Combs, J. M.; Grossman, A.; and Tchamitchian Ph. (Eds.), *Wavelets Time-Frequency Methods and Phase Space*, Springer-Verlag, 1987.

Kadambe, S. and Boudreaux-Bartels G. F., "A Comparison of a Wavelet Functions for Pitch Detection of Speech Signals," in *Proc. 1991 IEEE Int. Conf. Acoust., Speech, Signal Proc.*, Toronto, Canada, 14-17 May, 1991, pp. 449-452.

Kronland-Martinet; R., Morlet, J.; and Grossmann, A., "Analysis of Sound Patterns Through Wavelet Transforms," *International Journal Pattern Recognition and Artificial Intelligence*, Vol 1, No. 2, 1987, pp 273-302, pp 97-126.

Mallat, S. G. and Zhong, S., *Complete Signal Representation With Multiscale Edges*, Technical Report No. 483, Courant Institute of Mathematical Sciences, New York, NY, Dec 1989.

Rioul, Olivier and Vetterli Martin, "Wavelets and Signal Processing," *IEEE SP Magazine*, Oct 1991, pp 14-38.

Tucker, M. and Smith, P., *The Wavelet Handbook*, Issued by U. S. Army Missile Command Under Contract # DAAH01-90-C-0606, 1991.

Tuteur, F. B., "Wavelet Transformations in Signal Detection," in *Proc. 1989 IEEE Int. Conf. Acoust., Speech, Signal Proc.*, New York, NY, 11-14 Apr, 1988, pp. 1435-1438.

DISTRIBUTION

	<u>COPIES</u>		<u>COPIES</u>
DOD ACTIVITIES (CONUS)		ATTN LT DANGELO	1
ATTN SIEGEL CODE 213	1	ARMSTRONG AEROSPACE MEDICAL	
THOMAS MCKENNA	1	MEDICAL RESEARCH LAB	
CLIFFORD LAU	1	WRIGHT PATTERSON AFB OH 45433	
OFFICE OF NAVAL RESEARCH		ATTN HALFORD HAYES CODE 5N615	1
BALLSTON TOWER 1		NAVAL WARFARE ANALYSIS CTR	
800 N QUINCY ST		18385 FRONTAGE RD	
ARLINGTON VA 22217-5660		DAHLGREN VA 22448-5500	
ATTN DSO YOUN	1	DEFENSE TECHNICAL INFORMATION CTR	
DEFENSE ADVANCED RESEARCH		CAMERON STATION	
PROJECTS AGENCY		ALEXANDRIA VA 22304-6145	12
1400 WILSON BLVD		ATTN CODE E29L	1
ROSLYN VA 22201		COMMANDING OFFICER	
ATTN PAUL WERBOS	1	CSSDD NSWC	
NATIONAL SCIENCE FOUNDATION		6703 W HIGHWAY 98	
ROOM 1151		PANAMA CITY FL 32407-7001	
WASHINGTON DC 20550		NON-DOD ACTIVITIES (CONUS)	
ATTN JIM MAAR R51	1	ATTN GIFT AND EXCHANGE DIV	
NATIONAL SECURITY AGENCY		LIBRARY OF CONGRESS	
FT MEADE MD 20755-6000		WASHINGTON DC 20540	4
ATTN MAJ WYSOCKI	1	THE CNA CORP	
COMMANDER		PO BOX 16268	
MARCORSYSCOM		ALEXANDRIA VA 22302-0268	1
2033 BARNETT AVE SUITE 315		INTERNAL	
QUANTICO VA 22134-5010		B10 PRIEBE	5
ATTN CURT WRIGHT	1	B10 SOLKA	5
USAARDEC		B10 ROGERS	5
BLDG 95N		B32 RICE	1
SMCAR FSF RM		B40 CAVARIS	1
DOVER NJ 07806-5000		B40 FARSAIE	1
ATTN TNI ATAYA CODE 8423	1	B40 TARR	1
NAVAL UNDERWATER WARFARE CTR		C	1
NEWPORT RI 02840			

DISTRIBUTION (CONTINUED)

		<u>COPIES</u>
D		1
D4		1
E231		3
E282	FINK	1
F41	GROSS	1
F41	SAPOS	1
G		1
G30		1
G305	STIEGLER	1
G33	EPPLING	1
G33	HOLLAND	3
G33	NICHOLS	1
G33	POSTON	1
K32	HYNSON	1
N74	GIDEP	1
R44	SZU	1

REPORT DOCUMENTATION PAGE

Form Approved
OBM No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE May 1994	3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Wavelet Transformations for Helicopter Identification via Acoustic Signatures			5. FUNDING NUMBERS	
6. AUTHOR(S) Jeffrey L. Solka, Carey E. Priebe, Halford I. Hayes, and George W. Rogers				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ATTN: Code B10 Commander Naval Surface Warfare Center Dahlgren Division 17320 Dahlgren Road Dahlgren, Virginia 22448-5100			8. PERFORMING ORGANIZATION REPORT NUMBER NSWCDD/TR-93/169	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) <p>The ability to classify helicopters based on their acoustic signature has applications to both detection and tracking. The current approach to this problem uses standard signal-processing techniques to extract features based on the fundamental harmonics of the helicopters' blades. This document examines the role that the wavelet transformation might play in this feature extraction process. It addresses ways to use the wavelet transform both to improve the performance of the existing approach and to expand the capabilities of the classification system.</p>				
14. SUBJECT TERMS Wavelet Transformations, Helicopter Identification, Signal Processing			15. NUMBER OF PAGES 25	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and its title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

BLOCK 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If Known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... . When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

- DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."
- DOE - See authorities.
- NASA - See Handbook NHB 2200.2
- NTIS - Leave blank

Block 12b. Distribution Code.

- DOD - Leave blank.
- DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.
- NASA - Leave blank.
- NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*)

Block 17.-19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of this page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited or SAR (same as report)). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.