

AD-A280 957

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENT

Form Approved
OMB No. 0704-01881a. REPORT SECURITY CLASSIFICATION
Unclassified

None

2a. SECURITY CLASSIFICATION AUTHORITY
N/A

3. DISTRIBUTION / AVAILABILITY OF REPORT

2b. DECLASSIFICATION / DOWNGRADING SCHEDULE
N/A

Distribution A: Unlimited

4. PERFORMING ORGANIZATION REPORT NUMBER(S)

5. MONITORING ORGANIZATION REPORT NUMBER(S)

DOD POP HMTR/AYD 93-023

6a. NAME OF PERFORMING ORGANIZATION

6b. OFFICE SYMBOL
(If applicable)

7a. NAME OF MONITORING ORGANIZATION

Packaging Division, AED

SMCAR-AEP

None

6c. ADDRESS (City, State, and ZIP Code)

US Army Armament Research, Development and
Engineering Center
Picatinny Arsenal, NJ 07806-5000

7b. ADDRESS (City, State, and ZIP Code)

None

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited8a. NAME OF FUNDING / SPONSORING
ORGANIZATION8b. OFFICE SYMBOL
(If applicable)

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

Packaging Division, AED

SMCAR-AEP

8c. ADDRESS (City, State, and ZIP Code)

uS Army Armament Research, Development and
Engineering Center
Picatinny Arsenal, NJ 07806-5000

10. SOURCE OF FUNDING NUMBERS

PROGRAM
ELEMENT NO.PROJECT
NO.TASK
NO.WORK UNIT
ACCESSION NO.

11. TITLE (Include Security Classification)

Performance Oriented Packaging (POP) Testing of Expulsion Charge Assembly for M483A1,
155 MM Projectile, packed one hundred ninety two (192) per wood box.

12. PERSONAL AUTHOR(S)

Raymond J. Siroy

13a. TYPE OF REPORT

Final

13b. TIME COVERED

FROM _____ TO _____

14. DATE OF REPORT (Year, Month, Day)

94-06-06

15. PAGE COUNT

16. SUPPLEMENTARY NOTATION

17. COSATI CODES

FIELD	GROUP	SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

1. Performance Oriented Packaging
2. Ammunition Packaging
3. Wood Box
4. Packaging

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

This Performance Oriented Packaging (POP) report is for the Expulsion Charge Assembly for the M483A1, 155MM Projectile, packed one hundred ninety two (192) per wood box in accordance with drawing 9395829. This report describes the results of testing conducted with Inert Expulsion Charge.

94--19984



DTIC QUALITY INSPECTED 2

20. DISTRIBUTION / AVAILABILITY OF ABSTRACT

☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT ☐ DTIC USERS

21. ABSTRACT SECURITY CLASSIFICATION

22a. NAME OF RESPONSIBLE INDIVIDUAL

STEVE RUFFINI

22b. TELEPHONE (Include Area Code)

201-724-2515

22c. OFFICE SYMBOL

SMCAR-AEP

I. Report Number: DOD POP HMTR/AYD 93-023

II. Title: Performance Oriented Packaging (POP) Testing of Expulsion Charge Assembly for M483A1, 155MM Projectile, Packed One Hundred Ninety Two (192) per Wood Box

**Author: Raymond J. Siroy
Packaging Engineer**

**Performing Activity: U.S. Army Armament Research, Development
and Engineering Center (ARDEC)**

**Address: Department of the Army
Commander, U.S. Army ARDEC
Attn: SMCAR-AEP
Picatinny Arsenal, N.J. 07806-5000**

Date: May 1994

Report Type: Final

Distribution Statement A.

Approved for public release; distribution is unlimited.

Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

1. DATA SHEET:

a. CONTAINER (Outer Pack)

Type: Box

UN Code: 4C1

Part Number: 9395828

Spec Number: MIL-B-2427

Material: Wood

Capacity: 3545.89 Cubic Inches (58106.96 cu. cm)

Dimensions:

Inside: 53.02 cm. x 35.40 cm x 30.95 cm
(20 7/8 in. x 13 15/16 in. x 12 3/16 in.)

Outside: 60.32 cm. x 39.21 cm x 36.51 cm
(23 3/4 in. x 15 7/16 in. x 14 3/8 in.)

Closure (Method/Type): Nailed and Strapped

Tare Weight: 9.54 kg (21 lbs)

b. CONTAINER (Inner Pack)

Type: Box

UN Code: 4G

Part Number: 9395825

Spec Number: PPP-B-636

Material: Fiberboard

Capacity: 1456.92 Cubic Inches (23875.54 cu.cm)

Dimensions:

Inside: 33.33 cm. x 24.92 cm x 28.73 cm
(13 1/8 in. x 9 13/16 in. x 11 5/16 in.)

Outside: 34.29 cm. x 25.87 cm x 30.32 cm
(13 1/2 in. x 10 3/16 in. x 11 15/16 in.)

Closure (Method/Type): Taped

Tare Weight: 3.18 Kg (7 lbs)

c. PRODUCT

Name: Expulsion Charge Assembly
United Nations Proper Shipping Name: Charges, Propelling
United Nations Number: 0491
NSN: 1320-01-2426568
Drawing Number: 9362556
Physical State: Solid
United Nations Packing Group: II
Quantity Per Wood Box: 192 Expulsion Charges

d. TEST MATERIALS:

Name: Inert Expulsion Charge Assembly
Physical State: Solid
Size:
Diameter = 1.490 inches max, except lid
Length = 5.325 inches max

Quantity: 192 Inert Expulsion Charge per Wood Box
Gross Weight: 70 pounds (31.81 kg)

2. BACKGROUND:

This report contains the testing and test results performed for Performance Oriented Packaging Certification of Expulsion Charge Assembly (Part Number 9362556) for the M483A1, 155MM Projectile, Packed One Hundred Ninety Two (192) per Wood Box in accordance with drawing 9395829. The POP Test were performed at cold temperature (- 40° F) as a precaution, since part of the Expulsion Charge consists of a polyethylene tube. The tube is filled with 58 grams of M10 propellant and ultrasonically sealed with aluminum foil forming a hermetic seal. The tube is further closed by a polyethylene lid. Tests were performed in accordance with Part 178, Subpart M-Testing of Non-bulk Packaging and Packages, Title 49 of the Code of Federal Regulations (CFR).

3. INTRODUCTION:

The Department of Transportation (DOT) per CFR, Title 49, Parts 100-180, dated 1 Oct 92, requires that hazardous materials be packed in containers which satisfy the Performance Oriented Packaging (POP) requirements.

The Wood Box, part number 9395828, is being used as the shipping container for Expulsion Charge Assembly (Part Number 9362556) for the M483A1, 155MM Projectile. The package contains one hundred ninety two (192) of Expulsion Charge Assemblies per wood box in accordance with drawing 9395829. Each packed wood box has an individual estimated gross weight of 66 pounds.

POP tests were conducted using Wood Boxes, each containing inert Expulsion Charge Assemblies for a total gross weight of 70 pounds, resulting in a weight which is higher than the heaviest pack (estimated at 66 pounds) to insure wood box integrity. The tests were conducted in accordance with referenced sections of CFR, Title 49 and are valid only when approved ammunition is packed in the wood box as specified above for the Department Of Defense.

A total of five (5) packed wood boxes were POP tested at cold temperature (- 40° F) and in accordance with part 178, Subpart M-Testing of Non-bulk Packaging and Packages, Title 49 of the CFR.

4. TESTS PERFORMED:

Note: The Stacking, Vibration and Drop Tests were conducted at cold (- 40° F) temperature. Prior to any tests, all packed wood boxes were conditioned to minus forty (- 40° F) degrees F for a period of 24 hours.

a. Stacking Test

The CFR requires that the minimum height of the stack including the test sample must be 3.0 meters (10 feet). Three test samples are required. Each packed wood box has an individual gross weight of 70 pounds.

A 3.0 meter stack height of samples is equivalent to 630 pounds (286.36 kg) of stack weight. Three different test samples were each subjected to a stack weight of 630 pounds for a period of 24 hours. The samples were then inspected for any damage or distortion. The above procedures were performed in strict manner in accordance with paragraph 178.606 "Stacking Test" of the CFR.

b. Vibration Test

Three packed wood boxes, each having an individual gross weight of 70 pounds were tightly closed (nailed and strapped), as for shipment. The boxes were then placed on a vibrating platform that has a vertical double-amplitude (peak-to-peak displacement) of one inch. The three packed wood boxes were then vibrated for one

hour to such a degree that a piece of steel strapping (1/16 inch thick) easily passed underneath any of the boxes at any given time throughout the test. The three boxes were horizontally prevented from falling off of the vibrating platform while being free to move vertically, bounce and rotate. Upon completion of the test, all three packed wood boxes were removed from the vibrating platform, turned on their side and observed for any evidence of breakage and leakage. The above procedures were performed in strict manner in accordance with paragraph 178.608 "Vibration Standards" of the CFR.

c. Drop Tests

The CFR specifies that one box should be used for each drop orientation. Each box shall be dropped from a height of 1.2 meters (3.9 feet) in the following orientations: drop flat on the bottom, drop flat on the top, drop flat on the long side, drop flat on the short side, and drop on the corner. A total of five (5) boxes are specified for the five different orientations with one box being dropped for each orientation. For this test, however, the same three packed wood boxes that were tested in paragraph 4a and 4b were used for the Drop Test. Since the number of packed wood boxes available were only three, each box was dropped twice at two different orientations (for a total of six drops), with an extra drop on the opposite corner of the box. This exceeds the requirement of one drop per box, for the total of five boxes. The above procedures were performed in strict manner in accordance with paragraph 178.603 "Drop Test" of the CFR.

5. PASS/FAIL (DOT CRITERIA):

- a. Stacking Test:** A test sample passes the stacking test when no test sample spills its contents. No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength or cause instability in stacks of packages.
- b. Vibration Test:** A packaging passes the vibration test if there is no rupture or spillage from any of the packages.
- c. Drop Test:** A package for explosives is considered to successfully pass the drop tests if for each sample tested, no rupture of the packing occurs.

6. TEST RESULTS:

a. Stacking Test

All three packed wood boxes were removed from the stacking platform after 24 hours of test. Each wood box was carefully inspected for any structural damage. All the wood boxes tested were tightly intact and showed no evidence of rupture or spillage. All packages passed the test.

b. Vibration Test

All three packed wood boxes were removed from the platform after one hour vibration. Each of the wood box was physically inspected for any damage or spillage. All the wood boxes tested were tightly intact and showed no evidence of deterioration. There was no spillage or any damage of the three packed wood boxes. All packages tested passed the test.

c. Drop Test

Upon completion of the drop tests, all three packed wood boxes tested were carefully inspected for any damage. There were no cracks in the wood, ruptures or spillage. All packages tested passed the test.

7. CONCLUSION:

Based upon the above successful POP testing, the following UN POP symbol has been applied to the wood box in accordance with drawing 9395829.



4C1/Y32/S/
USA/DOD/AYD**

**** Last two digits of year packed.**