

ARMY RESEARCH LABORATORY




Front Borerider Design Considerations for a Large-Caliber, Hypervelocity Kinetic Energy (KE) Projectile

Lawrence W. Burton
Christopher J. Jaeger

ARL-TR-729

March 1995



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

19950323 077

NOTICES


Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute endorsement of any commercial product.

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE March 1995	3. REPORT TYPE AND DATES COVERED Final, April-August 1994	
4. TITLE AND SUBTITLE Front Borerider Design Considerations for a Large-Caliber, Hypervelocity Kinetic Energy (KE) Projectile			5. FUNDING NUMBERS PR: IL162618AH80	
6. AUTHOR(S) Larry Burton and Christopher J. Jaeger				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-PD Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-729	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) There has been increased interest within the ballistic community to investigate the benefits of launching kinetic energy (KE) projectiles at hypervelocities, velocities in excess of 2 km/s. To facilitate such investigations, KE projectile designers have begun to employ 7-in cannons to achieve the higher desired velocities. Use of such large-bore guns results in increased aerodynamic loading on the front borerider scoop. Test firings of the AF4 7-in projectile resulted in catastrophic sabot failure upon muzzle exit. Based on these test data, a detailed investigation of the aerodynamic loads expected on a 7-in projectile launched at 2.4 km/s was undertaken as part of the Ballistics for Future Systems (BFUS) program. Three-dimensional finite element analysis techniques were used to determine the benefits of incorporating holes into the front borerider scoop. The benefits of utilizing splines were also examined. The result of this work is a design for a structurally robust, large-caliber, hypervelocity KE projectile.				
14. SUBJECT TERMS kinetic energy projectile, aerodynamic loads, sabot design			15. NUMBER OF PAGES 34	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

The authors would like to acknowledge the contributions of Mr. Brett Sorensen, Terminal Effects Division, Army Research Laboratory (ARL), and thank him for providing a two-dimensional design of an $L/D = 30$ penetrator. He also provided assistance in generating the three-dimensional geometry model used in this analysis from the final two-dimensional finite element design iteration.

Thanks is also extended to Dr. Steve Wilkerson, Propulsion and Flight Division (PFD), ARL, and Mr. Robert Phillabaum, Terminal Effects Division (TED), ARL, for their review of the draft manuscript and the insightful comments that improved this document.

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
ACKNOWLEDGMENTS	iii
LIST OF FIGURES	vii
LIST OF TABLES	vii
1. INTRODUCTION	1
2. INITIAL SABOT DESIGN	2
3. FORWARD SCOOP ANALYSIS	4
4. BORERIDER DESIGN ITERATIONS	6
5. CONCLUSIONS	18
6. REFERENCES	25
DISTRIBUTION LIST	27

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. KE projectile components	1
2. Stress plot of BFUS projectile	3
3. 3-D FE model of 45° section of front borerider and saddle region	5
4. Case 1 stress plot - full frontal scoop	7
5. Case 2 stress plot - 48.26-mm circular hole	9
6. Case 3 stress plot - 58-mm circular hole	10
7. Case 4 stress plot - 32° window	11
8. Case 5 stress plot - 60° window	12
9. Case 6 stress plot - smaller 60° window	13
10. Case 7 stress plot - spoked-wheel arrangement	15
11. Case 8 stress plot - reinforced borerider thickness	17
12. Case 9 stress plot - small spline addition	19
13. Case 10 stress plot - large spline addition	20
14. Case 11 stress plot - quad spline addition	21
15. Case 12 stress plot - quad spline addition, elastic-plastic analysis	22
16. Final modified BFUS sabot design configuration	23

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Material Property Data	3
2. Summary of FE Design Iterations	16

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

In the early 1980s, the U.S. Army ballistic community adopted the double-ramp sabot as the most mass efficient means of launching long-rod kinetic energy (KE) projectiles. Design rules which sized the front and rear ramp tapers of the double-ramp configuration were developed (Drysdale 1981). A main bulkhead was placed between these two ramps over the projectile's center of gravity to enhance the in-bore stability of the round and support the obturator. The size of the bulkhead was determined by calculating the gas pressure load on the structure and then ensuring sufficient thickness to withstand the induced shearing force (Burns, Burton, and Drysdale 1992). The final component of the sabot structure was the front borerider, which serves a dual-purpose role. First, it is intended to help stabilize the projectile during in-bore travel to minimize the effects of transverse loading. Its second function is to provide a lifting surface to aid with the sabot petals' discard as the projectile exits the gun barrel. A sketch of a typical KE round, with its various parts labeled, is shown in Figure 1.




Figure 1. KE projectile components.

Development of design criteria for the front borerider has not evolved to the same extent as that for the sabot ramps or bulkhead. Typical design practice for a KE projectile dictates that a quasi-static finite element (FE) analysis be performed assuming the peak gas pressure load (Sorensen 1991). This ensures a robust projectile design capable of withstanding the in-bore axial pressure loads. These loads are minimal in the front borerider section of the projectile and play no role in its sizing.

One factor which does affect the structure of the forward borerider is the magnitude of the aerodynamic loads experienced at muzzle exit. Attempts have been made to develop analytical methods

to estimate these aerodynamic loads (Plostins 1985). The results of this work found that the technique developed overpredicted the critical stress level by as much as a factor of 2. Later on, 3-D FE techniques were used to investigate front scoop failures experienced in test firings of metal matrix sabots (Burns 1994). In general, however, the design of sabot forward boreriders made of an isotropic material, typically aluminum, for current tank cannon bore sizes (up to 120 mm) has been a trivial exercise.

The recent interest within the ballistic community to examine the benefits of hypervelocity (muzzle velocities above 2 km/s) has led to the use of larger bore guns to experimentally attain this velocity regime (Colburn, Ruth, and Robbins 1992). Test firings of KE projectiles, the AF4's, were conducted with a 7-in gun at Aberdeen Proving Ground, MD. A series of 10 shots was planned initially; however, during each of the first two shots, the front bell of the sabot was seen to have failed in the downrange smear camera photographs at velocities of approximately 2 km/s (Phillabaum 1994). It was speculated that these failures were caused by excessive aerodynamic loading on the frontal area of the forward scoop. At about this time, another 7-in KE projectile was being designed in an attempt to attain a launch velocity of 2.4 km/s for the in-house Ballistics of Future Systems (BFUS) program. Because of the failures experienced with the AF4 rounds, a detailed analysis and redesign of the front borerider of the BFUS projectile was undertaken to ascertain and minimize the effects of the aerodynamic loading. The details of this investigation are provided in this report.

2. INITIAL SABOT DESIGN

The initial sabot design for the 7-in BFUS projectile was done using Sorensen's FE optimization routine (Sorensen 1991). The projectile consists of a tungsten rod penetrator with a length-to-diameter ratio (L/D) of 30, supported by an aluminum sabot. The stress plot in Figure 2 shows the maximum stress values in both the penetrator and sabot (values are in pascals) are well below the respective material strengths given in Table 1. The quasi-static analysis technique employed to derive the Figure 2 stress plot uses a balance of peak gas pressure and acceleration to load the structure. Note that this method only minimally loads the front borerider and results in very low stress values through this section of the sabot. So while this analysis shows a projectile design capable of withstanding the in-bore acceleration and pressure loads, it does not address the aerodynamic loads encountered upon muzzle exit. Based on the AF4 sabot failures, it was deemed necessary to do a more detailed analysis of the front borerider to investigate the effects of the expected aerodynamic loads.





Figure 2. Stress plot of BFUS projectile.

Table 1. Material Properties Used in FE Analysis

Material	Density (kg/m ³)	Elastic Modulus (psi)	Compressive Yield Strength (MPa)	Tensile Yield Strength (MPa)
Tungsten	17,800	51,000,000	1,558	1,620
Aluminum	2,875	10,000,000	565	565

3. FORWARD SCOOP ANALYSIS

Using the premise that the AF4 sabot failures resulted from excessive aerodynamic loading on the front bell, a more detailed analysis of the BFUS projectile's forward scoop and saddle region was undertaken. (The saddle refers to the front ramp of the sabot located between the bulkhead and borerider.)

The most severe loading of the forward scoop under the aerodynamic pressure load occurs when the projectile begins to exit the gun tube. As the projectile transitions from in-bore to out-of-bore, the front borerider clears the muzzle while, for a short time, the obturator and supporting bulkhead are still in-bore. It is at this time that the front bell and saddle are most severely stressed since the forward scoop is fully loaded while the bulkhead and obturator are confined by the gun barrel. This situation is analogous to a cantilevered beam undergoing bending.

To represent this cantilever bending phenomena, it was not necessary to model the entire projectile geometry. Only a portion of the projectile was modeled (namely, the front borerider scoop and the saddle region) to examine the effects of the aerodynamic load on the front scoop of the sabot. A fixed boundary constraint was used at the rear of the finite element geometry model to simulate containment of the bulkhead and obturator by the gun tube, which thus inhibits discard of the sabot petals and induces bending.

Only one-half of a single 90-sabot petal was modeled to take advantage of symmetry and reduce the modeling and computation time of the exercise. A symmetry boundary condition was placed on one edge of the model. Figure 3 shows three views of the 3-D FE model of the 45° section (one-half of a sabot petal) used for the analysis.

First, Figure 3 gives an isometric view of the front bell and saddle from below the front of the sabot. In addition, a top view of the sabot is shown with the bottom edge being along a seam in the sabot. Finally, Figure 3 provides a side view of the same model representation shown in the previous views.

The load on the face of the frontal scoop was based on the stagnation pressure which develops behind a normal shock to the freestream static pressure. Equation 1 is taken from Plostins (1985) and is used to calculate the stagnation pressure, P_s .






Figure 3. 3-D FE model of 45° section of front borerider and saddle region.

$$|P_s| = P_\infty \left(\frac{6M_\infty^2}{5} \right)^{\frac{7}{2}} \left(\frac{6}{7M_\infty^2 - 1} \right)^{\frac{5}{2}}, \quad (1)$$

where M_∞ is the mach number and P_∞ is the freestream static pressure. P_∞ was assumed to be 14.7 psi (101.4 MPa), while the mach number was calculated using

$$M_\infty = \frac{V_{\text{muz}}}{V_{\text{sound}}}, \quad (2)$$

where V_{muz} is the expected muzzle velocity and V_{sound} is the speed of sound and is given by

$$V_{\text{sound}} = 49.1\sqrt{T},$$

where T is the temperature in degree rankine and yields V_{sound} in feet/second. Assuming ambient temperature conditions ($T = 530$ R), equation 3 yields V_{sound} equal to 1,130.4 ft/s (344.5 m/s). Dividing this value into the desired muzzle velocity of 2.4 km/s produces a mach number of 6.966, per equation 2. Substitution of this mach number into equation 1 results in a pressure load of 925 psi (6.38 MPa) on the front scoop which was incorporated into the FE model.

4. BORERIDER DESIGN ITERATIONS

The initial baseline case was for a full, frontal borerider scoop loaded with 925-psi pressure. A plot of the resulting effective Von Mises' stress through the structure for an elastic analysis is shown in Figure 4. The stress contour values on the plot are given in pascals. The front borerider and saddle region are made of aluminum, which from Table 1 has a yield strength of 565 MPa. Thus, from the color contour plot, it is seen that the entire saddle region experiences stresses exceeding its load carrying capability. These high stress values result from the loading in the large scoop acting to cantilever the




Figure 4. Case 1 stress plot - full frontal scoop.

entire section about the pinned aft end. This situation is analogous to the condition that occurs at muzzle exit when the front of the projectile (front borerider) has cleared the barrel end while the bulkhead and obturator remain inside the launch tube. This is also consistent with the sabot failures experienced during the test firings of the AF4 projectile.

The first modification made to alleviate the stress state was to put a circular hole through the borerider scoop to reduce the frontal area loaded by the aerodynamic pressure. This initial hole size was selected to reduce the frontal area by 33%. Figure 5 shows the resulting stress plot with a 48.26-mm-diameter hole through the scoop. While a reduction in stress is achieved, it is not sufficient to prevent failure in the saddle. Also note that a high stress area can be seen at the base of the borerider due to the reduced thickness in this region.

The next iteration, case 3, maximized the hole size through the borerider. Here, a 58-mm-diameter hole was modeled with the stress plot shown in Figure 6. At this point, it is seen that the predominant high stress region is localized at the base of the borerider, while stresses in the saddle region still exceed the yield strength of the aluminum.

The case 3 analysis, showing the maximum allowable circular hole size to be insufficient in alleviating the high stress state, led to use of a window-shaped cutout being incorporated into the case 4 analysis. The window size was selected to be equal to the area of the 48.26-mm hole used in case 2, thus again reducing the frontal area by 33%. The stress plot results of case 4 are provided in Figure 7, and as with the previous case, there is a high localized stress region at the narrow base of the borerider support.

After examining the case 4 borerider design, it was felt that much of the material away from the borerider base could be removed without adversely affecting the strength of the structure. This led to a 60° window being incorporated into the front borerider for case 5 (30° in the 45° sabot petal model). Figure 8 shows the stresses which result from this modification, and while they are reduced, there is still a high stress region at the borerider base.

Case 6, shown in Figure 9, maintained the 60° window configuration but thickened the borerider base by adding material to the bottom of the cutout window. This design, while exhibiting a high localized stress region, shows significant portions of the saddle and borerider to be within the yield limits of the aluminum. These results led to one final modification of the window shape.







Figure 5. Case 2 stress plot - 48.26-mm circular hole.




Figure 6. Case 3 stress plot - 58-mm circular hole.







Figure 7. Case 4 stress plot - 32° window.







Figure 8. Case 5 stress plot - 60° window.







Figure 9. Case 6 stress plot - smaller 60° window.



The new modified window, seen in Figure 10, further opened up the top of the window, resulting in a uniform thickness radial support. This "spoked-wheel" arrangement, case 7, shows dramatic improvement in the region's stress state. The high localized stresses are reduced by 25%, while much of the through sections are below the yield criteria.

At this point in the analysis, it was felt that the material removed from the borerider scoop had been maximized and further modifications to the window configuration were impractical. Table 2 is provided to summarize the changes made in going from the full front scoop, case 1, to the spoked-wheel configuration of case 7. The region of high stress is listed for each case, in addition to the mass of the structure (total borerider and saddle mass) normalized against the case 1 value. Thus, from Table 2, the design of case 7 has a mass 36.3% less than the full scoop design.

Having run the gamut of modifications to the borerider window, it was time to examine the benefits of adding material back into the structure to strengthen it. The initial 2-D quasi-static design of the projectile (Figure 2) produced a predicted launch package mass of 17.8 lb (8.07 kg). Interior ballistic code runs estimated that a projectile of this mass could attain a 2.4 km/s launch velocity from a double-travel 7-in gun (Colburn 1994). Since attaining this velocity level was a principal goal of the BFUS projectiles, any additions to the saddle and borerider would have to keep the normalized mass below the baseline, case 1 value.

In this vein, the radial borerider, or "spoke," was thickened. The stress plots of this case 8 analysis are shown in Figure 11. The borerider spoke exhibits all through-section stress values below that of yield. The problem has now been isolated to the saddle region. It is ironic that we have now returned to the situation found in case 1—that is, acceptable borerider stress levels but excessive values in the saddle region. However, by comparing Figure 11 to Figure 4, we see that the maximum stress in the saddle has been reduced 68% while also achieving an 18% reduction in structure mass.

As was described previously for the case 1 results, the high saddle stresses result from the bending induced by the loading on the surface of the front scoop. Work done in other projectile design programs (Kaste and Wilkerson 1992) has shown that by incorporating splines or ribs into the sabot, one can greatly reduce the bending stress in the sabot. Thus, such an approach was adopted for case 9, which added a small spline to the saddle, aft of the borerider support. The resulting stress plot in Figure 12 shows that



[Dark Gray Box]	.198E+07
[Medium-Dark Gray Box]	.212E+09
[Medium Gray Box]	.422E+09
[Light Gray Box]	.632E+09
[White Box]	.842E+09
[Light Gray Box]	.105E+10
[Medium Gray Box]	.126E+10
[Dark Gray Box]	.147E+10
[Medium-Dark Gray Box]	.168E+10
[Dark Gray Box]	.189E+10




Figure 10. Case 7 stress plot - spoked-wheel arrangement.

Table 2. Summary of FE Design Iterations

No.	Sabot/Front Borerider Geometry Description	High Stress Region	Normalized Mass
1	Full front borerider scoop	Saddle	1.0
2	48.26-mm-diameter holes (1/3 frontal area)	Saddle	0.803
3	58-mm-diameter holes	Base of borerider	0.698
4	32° window in 1/4 section (16° in model)	Base of borerider	0.803
5	60° window in 1/4 section (30° in model)	Base of borerider	0.637
6	Smaller 60° window in 1/4 section	Saddle/base of borerider	0.690
7	Modified 60° window - spoked-wheel configuration	Saddle/base of borerider	0.637
8	Modified 60° window, reinforced borerider thickness	Saddle	0.820
9	Modified 60° window, reinforced borerider thickness, small spline	Saddle	0.862
10	Modified 60° window, reinforced borerider thickness, large spline	Saddle and spline	0.898
11	Modified 60° window, reinforced borerider thickness, quadrilateral spline	Localized at spline base	0.965
12	Modified 60° window, reinforced borerider thickness, quadrilateral spline (elastic-plastic analysis)	Localized stress concentration	0.965




Figure 11. Case 8 stress plot - reinforced borerider thickness.

all stress values in the borerider are well below the 565-MPa yield strength of aluminum. While there are no through-section stress values exceeding yield, there still exist substantial areas of the saddle which do.

The next iteration, case 10, used a longer spline which nearly extended to the end of the saddle region. Figure 13 shows that while the regions of high stress have been made smaller, they are still quite substantial. This led to a final modification, case 11, which used a quadrilateral, as opposed to triangular, spline configuration. This enlarged spline reduced all stress values below the yield criteria except for localized concentrations at the corner of the spline where it interfaces with the saddle (see Figure 14). As listed in Table 2, the mass of this geometry was 96.5% that of the baseline design, meaning further additions to the spline could not be made without exceeding the established mass criteria.

The final iteration, case 12, was made and examined the quadrilateral spline configuration with an elastic-plastic analysis. By incorporating plasticity into the model, the high stress concentration areas such as the notch at the base of the spline could be alleviated. Figure 15 gives the results of the elastic-plastic analysis. Nearly all of the structure is within the yield limits of the material. The few regions not below yield are highly localized and will likely be reduced further when the spline is actually configured as a blend into the saddle, as opposed to a notch. Figure 16 shows a schematic of the finalized sabot design.

5. CONCLUSIONS

The desire of KE projectile designers to investigate the benefits of higher launch velocities has led to the use of larger and more powerful cannons. In particular, 7-in guns have been used to test full-scale penetrators at velocities well above current ordnance. The combination of larger sabots and higher velocities requires that greater attention be paid to the details of the front borerider and saddle region design.

This report has provided a step-by-step design approach to minimize the effects of aerodynamic loads on the KE projectile structure. The 3-D FE analysis shows the benefits of reapportioning mass from the front scoop to a thicker borerider support and an abutting spline. The affect of the design iterations was to take a full front borerider scoop which was predicted to catastrophically fail and modify it into a robust configuration. These modifications were accomplished with no additional parasitic mass to the baseline configuration.









Figure 12. Case 9 stress plot - small spline addition.



	262710
	.155E+09
	.310E+09
	.464E+09
	.619E+09
	.774E+09
	.928E+09
	.108E+10
	.124E+10
	.139E+10






Figure 13. Case 10 stress plot - large spline addition.



	262712
	.154E+09
	.308E+09
	.462E+09
	.616E+09
	.770E+09
	.924E+09
	.108E+10
	.123E+10
	.139E+10




Figure 14. Case 11 stress plot - quad spline addition.







Figure 15. Case 12 stress plot - quad spline addition, elastic-plastic analysis.




Figure 16. Final modified BFUS sabot design configuration.

This work is intended to forewarn future KE designers of the importance of performing a more detailed analysis for large-caliber, hypervelocity projectiles. The use of a window in the front borerider is presented as a means of relieving the large aerodynamic force loading on the front bell. Incorporation of splines and the thickening of the borerider support serve to reduce the bending stress present in the sabot. This investigation resulted in a structurally sound design, capable of achieving 2.4 km/s, and did not look to optimize the final geometry of the splines or borerider windows.

Four projectiles have been fabricated in the configuration shown in Figure 16. It is intended to test fire these projectiles from a double-travel 7-in cannon to obtain penetration data and verify the structural integrity of the modified sabot predicted by this analysis. The details of these test firings will be recorded in a future report.

INTENTIONALLY LEFT BLANK.

6. REFERENCES

- Burns, B. P. "An Executive Summary of the M829A2 Sabot Technology Program." ARL-TR-50, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, February 1994.
- Burns, B. P., L. Burton, and W. H. Drysdale. "Methodologies for Forecasting Sabot Mass for Advanced Gun and Projectile Systems." BRL-TR-3387, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, September 1992.
- Colburn, J. W. Private Communication. U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, May 1994.
- Colburn, J. W., C. R. Ruth, F. W. Robbins, and A. W. Horst. "Hypervelocity Firings From A 7-Inch HARP Gun." BRL-TR-3344, U.S. Army Ballistic Research Laboratory, Aberdeen Proving, MD, May 1992.
- Drysdale, W. H. "Design of Kinetic Energy Projectiles for Structural Integrity." BRL-TR-02365, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, September 1981.
- Kaste, R. P., and S. A. Wilkerson. "An Improved Sabot Design and DYNA3D Analysis for the XM900E1 Kinetic Energy Projectile." BRL-TR-3359, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1992.
- Phillabaum, R. A., II. "HARP Gun Testing." US/France Technical Exchange, DEA FR1267, Aberdeen Proving Ground, MD, 3-6 May 1994.
- Plostins, P. "Estimation of the Initial Aerodynamic Loads on Sabot Components." BRL-MR-3455, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1985.
- Sorensen, B. R. "Design and Analysis of Kinetic Energy Projectiles Using Finite Element Optimization." BRL-TR-3289, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, November 1991.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	ADMINISTRATOR ATTN DTIC DDA DEFENSE TECHNICAL INFO CTR CAMERON STATION ALEXANDRIA VA 22304-6145	1	COMMANDER ATTN AMSMI RD CS R DOC US ARMY MISSILE COMMAND REDSTONE ARSNL AL 35898-5010
1	COMMANDER ATTN AMCAM US ARMY MATERIEL COMMAND 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001	1	COMMANDER ATTN AMSTA JSK ARMOR ENG BR US ARMY TANK AUTOMOTIVE CMD WARREN MI 48397-5000
1	DIRECTOR ATTN AMSRL OP SD TA US ARMY RESEARCH LAB 2800 POWDER MILL RD ADELPHI MD 20783-1145	1	DIRECTOR ATTN ATRC WSR USA TRADOC ANALYSIS CMD WSMR NM 88002-5502
3	DIRECTOR ATTN AMSRL OP SD TL US ARMY RESEARCH LAB 2800 POWDER MILL RD ADELPHI MD 20783-1145	1	COMMANDANT ATTN ATSH CD SECURITY MGR US ARMY INFANTRY SCHOOL FT BENNING GA 31905-5660
1	DIRECTOR ATTN AMSRL OP SD TP US ARMY RESEARCH LAB 2800 POWDER MILL RD ADELPHI MD 20783-1145	<u>ABERDEEN PROVING GROUND</u>	
2	COMMANDER ATTN SMCAR TDC US ARMY ARDEC PCTNY ARSNL NJ 07806-5000	2	DIR USAMSA ATTN AMXSY D AMXSY MP H COHEN
1	DIRECTOR ATTN SMCAR CCB TL BENET LABORATORIES ARSENAL STREET WATERVLIET NY 12189-4050	1	CDR USATECOM ATTN AMSTE TC
1	DIR USA ADVANCED SYSTEMS ATTN AMSAT R NR MS 219 1 R&A OFC AMES RESEARCH CENTER MOFFETT FLD CA 94035-1000	1	DIR USAERDEC ATTN SCBRD RT
1		1	CDR USACBDCOM ATTN AMSCB CII
1		1	DIR USARL ATTN AMSRL SL I
1		5	DIR USARL ATTN AMSRL OP AP L

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA ATTN SARD TT DR F MILTON WASH DC 20310-0103	3	COMMANDER ATTN SMCAR TD R PRICE V LINDER T DAVIDSON US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
1	HQDA ATTN SARD TT MR J APPEL WASH DC 20310-0103	1	COMMANDER ATTN F MCLAUGHLIN US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
1	HQDA ATTN SARD TT MS C NASH WASH DC 20310-0103	5	COMMANDER ATTN SMCAR CCH T S MUSALLI P CHRISTIAN K FEHSAL N KRASNOW R CARR US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
1	HQDA ATTN SARD TR DR R CHAIT WASH DC 20310-0103	1	COMMANDER ATTN SMCAR CCH V E FENNELL US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
1	HQDA ATTN SARD TR MS K KOMINOS WASH DC 201310-0103	1	COMMANDER ATTN SMCAR CCH J DELORENZO US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
1	DIRECTOR ATTN AMSRL CP CA D SNIDER USARL 2800 POWDER MILL RD ADELPHI MD 20783	2	COMMANDER ATTN SMCAR CC J HEDDERICH COL SINCLAIR US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
7	DIRECTOR ATTN AMSRL MA P L JOHNSON B HALPIN T CHOU AMSRL MA PA D GRANVILLE W HASKELL J CONNORS AMSRL MA MA G HAGNAUER USARL ARSNL ST WATERTOWN MA 02172-0001	1	COMMANDER ATTN SMCAR CCH P J LUTZ US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
4	COMMANDER ATTN SMCAR FSE T GORA E ANDRICOPOULOS B KNUTELSKY A GRAF US ARMY ARDEC PCTNY ARSNL NJ 07806-5000	2	COMMANDER ATTN SMCAR FSA M D DEMELLA F DIORIO US ARMY ARDEC PCTNY ARSNL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER ATTN SMCAR FSA C SPINELLI US ARMY ARDEC PCTNY ARSNL NJ 07806-5000
11	DIRECTOR ATTN SMCAR CCB C KITCHENS J KEANE T ALLEN J VASILAKIS G FRIAR T SIMKINS V MONTVORI J WRZOCHALSKI G D'ANDREA R HASENBEIN SMCAR CCB R S SOPOK BENET WEAPONS LABS WATERVLIET NY 12189
1	COMMANDER ATTN SMCWV QAE Q C HOWD BLDG 44 WATERVLIET ARSNL WATERVLIET NY 12189-4050
1	COMMANDER ATTN SMCWV SPM T MCCLOSKEY BLDG 25 3 WATERVLIET ARSNL WATERVLIET NY 12189-4050
1	COMMANDER ATTN SMCWV QA QS K INSCO WATERVLIET ARSNL WATERVLIET NY 12189-4050
1	COMMANDER ATTN AMSMC PBM K PBMA PCTNY ARSNL NJ 07806-5000
1	COMMANDER ATTN STRBE JBC C KOMINOS USABRDC FT BELVOIR VA 22060-5606

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DIRECTOR ATTN P DUTTA US ARMY CRREL 72 LYME RD HANOVER NH 03755
1	DIRECTOR ATTN AMSRL WT L D WOODBURY USARL 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	COMMANDER ATTN AMSMI RD W MCCORKLE AMSMI RD ST P DOYLE AMSMI RD ST CN T VANDIVER US ARMY MICOM REDSTONE ARSNL AL 35898
2	US ARMY RESEARCH OFFICE ATTN ANDREW CROWSON J CHANDRA PO BOX 12211 RSRH TRI PK NC 27709-2211
1	US ARMY RESEARCH OFFICE ATTN G ANDERSON PO BOX 12211 RSRH TRI PK NC 27709-2211
2	PROJECT MANAGER SADARM PCTNY ARSNL NJ 07806-5000
2	PROJECT MANAGER ATTN SFAE AR TMA COL BREGARD C KIMKER TANK MAIN ARMAMENT SYSTEMS PCTNY ARSNL NJ 07806-5000
3	PROJECT MANAGER ATTN SFAE AR TMA MD H YUEN J MCGREEN R KOWALSKI TANK MAIN ARMAMENT SYSTEMS PCTNY ARSNL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	PROJECT MANAGER ATTN SFAE AR TMA MS R JOINSON D GUZIEWICZ TANK MAIN ARMAMENT SYSTEMS PCTNY ARSNL NJ 07806-5000	2	NAVAL SURFACE WARFARE CTR CODE G33 DAHLGREN VA 224488
1	PROJECT MANAGER ATTN SFAE AR TMA MP W LANG TANK MAIN ARMAMENT SYSTEMS PCTNY ARSNL NJ 07806-5000	1	NAVAL RESEARCH LAB ATTN I WOLOCK CODE 6383 WASH DC 20375-5000
2	PROJECT EXECUTIVE OFFICER ATTN SFAE AR PM D ADAMS T MCWILLIAMS ARMAMENTS PCTNY ARSNL NJ 07806-5000	1	OFFICE OF NAVAL RSRCH MECH DIV ATTN YAPA RAJAPAKSE CODE 1132SM ARLINGTON VA 22217
1	PROJECT EXECUTIVE OFFICER ATTN SFAE FAS PM H GOLDMAN FIELD ARTILLERY SYSTEM PCTNY ARSNL NJ 07806-5000	1	NAVAL ORDNANCE STATION ATTN D HOLMES CODE 2011 ADVANCED SYSTEMS TECHNOLOGY BR LOUISVILLE KY 40214-5245
4	PROJECT MANAGER ATTN LTC D ELLIS G DELCOCO J SHIELDS B MACHAK AFAS PCTNY ARSNL NJ 07806 5000	1	DIRECTOR ATTN D RABERN MEE 13 MAIL STOP J 576 LANL PO BOX 1633 LOS ALAMOS NM 87545
2	COMMANDER ATTN J KELLY B WILCOX ARPA 3701 N FAIRFAX DR ARLINGTON VA 22203-1714	1	OAK RIDGE NATIONAL LAB ATTN R M DAVIS PO BOX 2008 OAK RIDGE TN 37831-6195
2	COMMANDER ATTN WL FIV A MAYER WRIGHT PATTERSON AFB DAYTON OH 45433	1	BATTELLE PNL ATTN M SMITH PO BOX 999 RICHLAND WA 99352
2	DIRECTOR ATTN AMSRL VS W ELBER AMSRL VS S F BARTLETT JR NASA LANGLEY RSRCH CTR MAIL STOP 266 HAMPTON VA 23681-0001	6	DIRECTOR ATTN C ROBINSON G BENEDETTI W KAWAHARA K PERANO D DAWSON P NIELAN SNL PO BOX 969 LIVERMORE CA 94550-0096
		1	DREXEL UNIVERSITY ATTN ALBERT SD WANG 32ND AND CHESTNUT STS PHILADELPHIA PA 19104

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
2	NORTH CAROLINA STATE UNIV ATTN W RASDORF L SPAINHOUR CIVIL ENGR DEPT PO BOX 7908 RALEIGH NC 27696-7908	1	CHAMBERLAIN MFG CORP ATTN T LYNCH R&D DIV 550 ESTHER ST WATERLOO IA 50704
1	PENNSYLVANIA STATE UNIV ATTN DAVID W JENSEN 223 N HAMMOND UNIVERSITY PARK PA 16802	1	CHAMBERLAIN MFG CORP ATTN M TOWNSEND R&D DIV 550 ESTHER ST WATERLOO IA 50704
1	PENNSYLVANIA STATE UNIV ATTN RICHARD MCNITT 227 HAMMOND BLDG UNIVERSITY PARK PA 16802	1	CUSTOM ANALYTICAL ENG SYS INC ATTN A ALEXANDER STAR ROUTE BOX 4A FLINTSTONE MD 21530
1	PENNSYLVANIA STATE UNIV ATTN RENATA S ENGEL 245 HAMMOND BUILDING UNIVERSITY PARK PA 16801	1	GDLS ATTN D BARTLE PO BOX 1901 WARREN MI 48090
1	PURDUE UNIV ATTN CT SUN SCHOOL OF AERO & ASTRO W LAFAYETTE IN 47907-1282	4	IAT ATTN T KIEHNE H FAIR P SULLIVAN S BLESS 4030 2 W BRAKER LN AUSTIN TX 78759
1	STANFORD UNIV ATTN S TSAI DEPT OF AERONAUTICS & AEROBALLISTICS DURANT BLDG STANFORD CA 94305	1	INTERFEROMETRICS INC ATTN R LARRIVA VP 8150 LEESBURG PIKE VIENNA VA 22100
1	THE UNIV OF TEXAS AT AUSTIN ATTN J PRICE CTR FOR ELECTROMECHANICS 10100 BURNET RD AUSTIN TX 78758-4497	2	KAMAN SCIENCES CORP ATTN D ELDER T HAYDEN PO BOX 7463 COLORADO SPRINGS CO 80933
1	ARMTEC DEFENSE PRODUCTS ATTN STEVE DYER 85 901 AVE 53 COACHELLA CA 92236	3	LORAL VOUGHT SYSTEMS ATTN G JACKSON K COOK L L HADDEN 1701 W MARSHALL DR GRAND PRAIRIE TX 75051
6	ALLIANT TECHSYSTEMS INC ATTN J BODE C CANDLAND K WARD 5901 LINCOLN DR MINNEAPOLIS MN 55346-1674		

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	MARTIN MARIETTA CORP ATTN P DEWAR L SPONAR 230 EAST GODDARD BLVD KING OF PRUSSIA PA 19406
2	OLIN CORP ATTN E STEINER B STEWART PO BOX 127 RED LION PA 17356
1	OLIN CORP ATTN L WHITMORE 10101 9TH ST NORTH ST PETERSBURG FL 33702
2	UNITED DEFENSE LP ATTN P PARA G THOMAS 1107 COLEMAN AVE BOX 367 SAN JOSE CA 95103
	<u>ABERDEEN PROVING GROUND</u>
59	DIRECTOR USARL ATTN AMSRL CI C MERMEGAN 394 AMSRL CI C W STUREK 1121 AMSRL CI CB R KASTE 394 AMSRL CI S A MARK 309 AMSRL SL B P DIETZ 328 AMSRL SL BA J WALBERT 1065 AMSRL SL BL D BELY 328 AMSRL SL I D HASKILL 1065 AMSRL WT P A HORST 390A AMSRL WT PA T MINOR 390 C LEVERITT 390 D KOOKER 390A AMSRL WT PB E SCHMIDT 120 P PLOSTINS 120 D LYON K SOENCKSEN AMSRL WT PC R FIFER 390A

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
	AMSRL WT PD B BURNS 390 W DRYSDALE 390 K BANNISTER 390 T BOGETTI 390 J BENDER 390 R MURRAY 390 R KIRKENDALL 390 T ERLINE 390 D HOPKINS 390 S WILKERSON 390 D HENRY 390 R KASTE 390 L BURTON 390 J TZENG 390 R LIEB 390 G GAZONAS 390 M LEADORE 390 AMSRL WT PD ALC A ABRAHAMIAN K BARNES M BERMAN H DAVISON A FRYDMAN T LI W MCINTOSH E SZYMANSKI AMSRL WT T W MORRISON 309 AMSRL WT TA W GILLICH 390 W BRUCHEY 390 AMSRL WT TC R COATES 309 W DE ROSSET 309 B SORENSEN 309 R PHILLABAUM 309 T BJERKE 309 AMSRL WT W C MURPHY 120 AMSRL WT WA H ROGERS 394 B MOORE 394 A BARAN 394 AMSRL WT WB F BRANDON 120 W D'AMICO 120 AMSRL WT WC J ROCCHIO 120 AMSRL WT WE J TEMPERLEY 120

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number ARL-TR-729 Date of Report March 1995

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.)

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS

Organization _____
Name _____
Street or P.O. Box No. _____
City, State, Zip Code _____

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD ADDRESS

Organization _____
Name _____
Street or P.O. Box No. _____
City, State, Zip Code _____

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
U.S. ARMY RESEARCH LABORATORY
ATTN: AMSRL-WT-PD
ABERDEEN PROVING GROUND, MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

