



מוסד הטכניון למחקר ופיתוח בע"מ  
TECHNION RESEARCH & DEVELOPMENT FOUNDATION LTD.



היחידה למחקר ופיתוח אלקטרואופטי  
ELECTRO - OPTICS RESEARCH & DEVELOPMENT UNIT

7497-EN-01


DTIC

Contract nb8171-44-C-9152

**ACOUSTIC SOUNDING SYSTEM FOR LONG RANGE  
PROPAGATION IN MIDDLE EAST SURROUNDINGS**

**Second Intern Report**

Item 0002



This document has been approved  
for public release and sale; its  
distribution is unlimited.

April 1995

Report No.: 5626/845

19950531 047

טכנולוגיות חישה מתקדמות, אלקטרו-אופטיקה, אקוסטיקה, גמ"מ  
ADVANCED SENSING TECHNIQUES, ELECTRO-OPTICS, ACOUSTICS, MMW

קרית הטכניון, חיפה 32000 Technion City, Haifa  
טל: 294230, 972-4-321058 Tel: 0044-2145 פקסימייליה: 972-4-326678 Fax:  
E-MAIL: EORDDDD@VMSA.TECHNION.AC.IL COMPUSERVE 70662, 3111

REPORT DOCUMENTATION PAGE			FORM APPROVED OMB No. 0704-0188
1.AGENCY USE ONLY(Leave blank)	2.REPORT DATE 30 Apr 1995	3.REPORT TYPE AND DATES Interim 2 Feb 95 to Apr 95	
4.TITLE AND SUBTITLE Acoustic Sounding system for long range propagation in Middle East surroundings		5.FUNDING NUMBERS N68171-94-C-9152	
6.AUTHOR(S) Dr. L. B. Salem, Dr. Z. Zlotnick			
7.PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Technion Research & Development Foundation EORD Division, Technion city 32000 Haifa, Israel		8.PERFORMING ORGANIZATION AGENCY REPORT NUMBER 5626/845	
9.SPONSORING, MONITORING AGENCY NAME(S) AND ADDRESS(ES) Mr. Jerry C. Comati, Environmental Sciences Branch, European Research Office, USARDSG-UK, 223 Old Marylebone Road, London, NW1 5TH, England		10.SPONSORING, MONITORING AGENCY REPORT NUMBER	
11.SUPPLEMENTARY NOTES Second Interim Report			
12a.DISTRIBUTION/AVAILABILITY STATEMENT Unlimited		12b.DISTRIBUTION CODE	
13.ABSTRACT(MAXIMUM 200 WORDS) This report covers work carried out during the second interim period. Two main tasks were carried out during this period. The first task dealt with the design and building of the Acoustic Power Source (APS) based on standard horn elements. The radiation pattern of the source was measured over an azimuth of 70 degrees surrounding the main lobe in the frequency range from 120 - 2,000 Hz. The second task dealt with the experimental determination of direction finding using the Acoustic Directive Receiver Antenna (ADRA). Representative graphs of the APS radiation pattern and a table containing measured direction angle versus geometrically determined source location are included. The effective beam width varied from 30°-60°. Direction accuracy was determined to within 5°.			
14. SUBJECT TERMS acoustics, propagation, phased array, beamforming		15.NUMBER OF PAGES: 9	
		16.PRICE CODE	
17.SECURITY CLASSIFICATION OF REPORT Unclassified	18.SECURITY CLASSIFICATION OF THIS PAGE -	19.SECURITY CLASSIFICATION OF ABSTRACT -	20.LIMITATION OF ABSTRACT Same As Report

### Title Page

1. Title of Research Project: Acoustic Sounding System for long range propagation in Middle east Surroundings.
2. Name of Principal Investigator: Dr. Z. Zlotnick, Dr. L.B. Salem.
3. Name of Contractor: EORD, Technion, Haifa, ISRAEL.
4. Contract Number: N68171-94-C-9152.
5. Report Number: Second interim Report, Item 0002.
6. Report Period: February 1995 - April 1995.
7. Statement: ~~" The Research reported in this document has been made possible through the support and sponsorship of the U.S. Government through its European Research Office of the U.S. Army. This report is intended only for the internal management use of the Contractor and U.S. Government.~~

Accession For	
NTIS CRABI	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification .....	
By .....	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

## Second Interim Report

This report briefly describes the design and field measurement activities carried out during the second interim period. The two main tasks performed were the experimental determination of the APS radiation pattern and the ADRA direction finding capability under field conditions.

1. The Acoustic Power Source -APS
  - 1.1 The maximum acoustical power from a single Atlas/Soundolier horn (DR72) using a PD-60T driver was determined at a distance of 2m and as a function of frequency. The measured results are given in Table 1 (see Appendix 1).
  - 1.2 In order to evaluate mutual coupling effects between the elements in a linear array mode, a linear arrangement of 3 horns was chosen as a representative unit. Adjacent horns were spaced at distances varying from 5 - 20cm. In addition rectangular slabs from different materials namely Aluminum, Wood and Polyurethane-foam were used as partitions between horns.
  - 1.3 The acoustic radiation pattern of the above source was determined as follows. A set of 8 microphones, equally spaced at  $10^\circ$  angles and at a radial distance of 30m from the horn array were used to simultaneously measure the acoustic signal. The source was driven at several frequencies in the range from 120-2,000 Hz.
  - 1.4 The measurements were arranged over 4 segments (of duration 2sec. each) and the results obtained from the 5cm spacing and no partition configuration is given in Appendix 1. In the graphs the azimuth angle of  $0^\circ$  corresponds to the direction directly in front of the horns. These results are representative in nature. A detailed analysis of all the configurations will be carried out to determine the optimal design for the complete 6 - element array.

## 2 The Acoustic Directive Receiver Antenna (ADRA)


2.1 The direction finding capability of the ADRA was determined experimentally as follows.

A single horn source driven at 300 Hz was positioned at various azimuthal and vertical positions around the antenna, in the far field. See attached photograph of the experimental set up.

2.2 The geometrical coordinates of the source with respect to a reference microphone of the horizontal array was determined. The source was moved with respect to the antenna array and its coordinates determined at each position.

2.3 The results obtained from this field experiment are given in Table 2 (see Appendix 1) The geometrical direction coordinates are compared with the source direction coordinates as determined by the ADRA system.

From Table 2 we see that the agreement between the two in the azimuthal plane is within  $3^\circ$ . In the vertical plane the agreement is within  $5^\circ$ .



3. The next stages of the research

The following are the main tasks we plan to perform in the next stages of the research:

1. Completion of radiation analysis of the 3 horn source.
2. Constructing of the APS.
3. Preliminary long range acoustical propagation measurements.
4. Computer simulation and comparison with long range acoustic transmission measurements.

APPENDIX 1

Table 1

FREQUENCY (Hz)	SPL (dB ze $2 \cdot 10^{-5}$ N/m <sup>2</sup> )
1,000	130
500	121.2
250	105
200	110.2
160	121.8
150	117.8
125	105


Sound pressure levels measured at 2 m from a single horn and driven at different frequencies.

Table 2


AZIMUTH ANGLE (DEG)		ZENITH ANGLE (DEG)	
Determined Geometrically	Determined by ADRA	Determined Geometrically	Determined by ADRA
0	0	0	0.5
15	13.5	9.6	13.5
30	32	20.3	25
45	48		
60	61.5		
75	75		
90	91.5		
120	120		
150	148		
180	178.5		

Comparison of geometric direction with that obtained from the ADRA system.

3-horn source, spacing=5cm; f=200Hz



3-horn source, spacing=5cm; f=300Hz



3-horn source, spacing=5cm; f=400Hz

