


REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302 and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 28 April 1995	3. REPORT TYPE AND DATES COVERED FINAL REPORT: 27 Sept. 1993 - 28 Feb. 1995	
4. TITLE AND SUBTITLE A NEW APPROACH FOR OPTIMUM GEAR DESIGN (Strengthening Spur Gears by Altering Stress Distribution)			5. FUNDING NUMBERS ARO Research Agreement No. DAAH04-93-2-0016	
6. AUTHOR(S) * William A. Grissom, Ph.D., P.E. ** Max L. Brown, Ph.D., P.E. ** Samer Masoud, Ph.D. ** Jeff Sutliff				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) * Central State University Department of Manufacturing Engineering Wilberforce, OH 45384 ** University of Cincinnati Department of Mechanical, Electrical & Nuclear Engineering Cincinnati, Ohio 45221-0072			8. PERFORMING ORGANIZATION REPORT NUMBER MFE/ISP-01	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARO 32442.3-EG-ISP	
11. SUPPLEMENTARY NOTES The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE 	
13. ABSTRACT (Maximum 200 words) A new approach was investigated for achieving lighter spur gears with longer service life by altering the stress distribution in the gear by introducing hollow and filled holes through the gear face parallel to the shaft axis. The study was conducted using two-dimensional I-DEAS and ANSYS finite element models. The intent was to strategically redistribute the stresses to reduce the critical stress at the root fillet of the tooth. Stresses at the contact area were also monitored. Three strategies were investigated: 1) various hollow hole patterns; 2) press/shrink-fit plugs in the holes to introduce a compressive preload; 3) a high modulus of elasticity insert in a gear blank of low modulus material. The hollow hole patterns reduced the fillet stress up to 5% while increasing contact stress and deflection slightly. Press/shrink-fit plugs which imparted an initial compressive stress at the fillet reduced the stress only slightly more than holes alone. High modulus inserts in a low modulus gear gave the best results, achieving up to 50% stress reduction at the fillet while also reducing the contact stress and tooth deflection. DTIC QUALITY INSPECTED 5				
14. SUBJECT TERMS spur gears, gear teeth, fatigue life, stress distribution, stress concentration, stress raiser, contact stress, bending stress, Von Mises stress, tooth deflection, finite element model			15. NUMBER OF PAGES 7	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

A NEW APPROACH FOR OPTIMUM GEAR DESIGN

F I N A L R E P O R T

Authors:

William A. Grissom, Ph.D., P.E. *
Max L. Brown, Ph.D., P.E. **
Samer Masoud, Ph.D. **
Jeff Sutliff **

* Department of Manufacturing Engineering
CENTRAL STATE UNIVERSITY
Wilberforce, Ohio 45384

** Department of Mechanical, Industrial, and Nuclear Engineering
UNIVERSITY OF CINCINNATI
Cincinnati, Ohio 45221-0072

28 MARCH 1995

U.S. ARMY RESEARCH OFFICE

Research Agreement No. DAAH04-93-2-0016

CENTRAL STATE UNIVERSITY
Wilberforce, Ohio 45384

APPROVED FOR PUBLIC RELEASE

DISTRIBUTION UNLIMITED

19950620 183

THE VIEWS, OPINIONS, AND/OR FINDINGS CONTAINED IN THIS REPORT ARE THOSE OF THE AUTHOR(S) AND SHOULD NOT BE CONSTRUED AS AN OFFICIAL DEPARTMENT OF THE ARMY POSITION, POLICY OR DECISION, UNLESS SO DESIGNATED BY OTHER DOCUMENTATION.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification _____	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

A NEW APPROACH FOR OPTIMUM GEAR DESIGN
(ARO Agreement No. DAAH04-93-2-0016)

**Central State University
Manufacturing Engineering Department
Wilberforce, Ohio 45384**

**University of Cincinnati
Department of Mechanical, Industrial and Nuclear Engineering
Cincinnati, Ohio**


STATEMENT OF THE PROBLEM

The objective of the research was to investigate a new approach for achieving lighter spur gears with longer service life. It is well known that holes or other geometric discontinuities can alter the stress distribution in a component. Furthermore, since fatigue life is very susceptible to stress concentration, it can be greatly increased by small reductions in stress in the area of highest stress concentration. These two principals were applied to spur gears by introducing hollow or filled holes, through the gear face parallel to the shaft axis, to improve the gear fatigue life. The intent was to strategically redistribute the stresses to reduce the critical stress at the root fillet of the tooth. Stresses at the contact area were also monitored.


Using a two-dimensional finite element model, three strategies to reduce the critical stresses were investigated. The first introduced various hole patterns through the gear face parallel to the axis of the shaft. The configurations were varied with respect to size, location and shape of the holes. The second strategy considered press/shrink-fit plugs in the holes to impart an initial compressive preload at the fillet. The third method incorporated a high modulus of elasticity insert in a gear blank of low modulus material. In this approach, the low modulus material at the stress concentration deforms within the elastic range shifting some of the stress to the high modulus material at a position removed from the stress concentration. Examples of the type of hole and insert patterns investigated are shown in the figures on page 2.

SUMMARY OF RESULTS


Hole patterns reduced the fillet stress up to 5% while increasing contact stress and deflection slightly. Press/shrink-fit plugs which imparted an initial compressive stress at the fillet reduced the stress only slightly more than holes alone. High modulus inserts in a low modulus gear gave the best results, achieving up to 50% stress reduction at the fillet while also reducing the contact stress and tooth deflection. The results of the study show promise for the proposed strategies. Additional work using optimization techniques to arrive at the most effective configurations should produce further stress reduction.




Circular Hole
at Tooth Center Line




Two Circular Holes
at Tooth Boundary




Circular Hole
at Root Center Line




Slot at Tooth
Center Line




Pressurized Circular Hole
Near Tooth Side



Multiple Pressurized
Holes



Two-Material Gear
(Straight Slot Insert)



Two-Material Gear
(Semicircular Insert)

A New Approach for Optimum Gear Design

HOLE AND INSERT PATTERNS INVESTIGATED

LIST OF ALL PUBLICATIONS AND TECHNICAL REPORTS

Masoud, Samer, "Improving Spur-Gear Performance," Ph.D., dissertation; University of Cincinnati; Division of Advanced Studies; Department of Mechanical, Industrial and Nuclear Engineering; College of Engineering; Cincinnati, Ohio, 1994.

Masoud, S. (1), M. Brown (1), W. Grissom (2) and J. Sutliff (1), "Strengthening Spur Gears by Altering Stress Distribution," (1) Dept. of Mechanical, Industrial and Nuclear Engineering, University of Cincinnati, (2) Department of Manufacturing Engineering, Central State University, manuscript to be submitted for publication, 1995.

REPORT OF INVENTIONS

No disclosures or patent applications filed to date.

LIST OF ALL PARTICIPATING SCIENTIFIC PERSONNEL

A. Central State University
 Department of Manufacturing Engineering
 1400 Brush Row Road
 Wilberforce, Ohio 45384
 (513) 376-6435

<u>Degree Earned</u>	<u>Position</u>	<u>Name</u>
---	Assoc. Professor	Mahmoud A. Abdallah, Ph.D.
---	Professor	A. J. Ajayi-Majebi, Ph.D.
---	Professor/Chair	William A. Grissom, Ph.D.
---	Assoc. Professor	August Morris, Jr., Ph.D.
---	Assoc. Professor	Nader I. Ralfa, Ph.D.
---	Asst. Professor	Alessandro Rengan, Ph.D.
---	Asst. Professor	John H. Sassen
---	BSMfE Sophomore	Willie Arnold
B.S.MfE	BSMfE Senior	Mohamed Ba
---	BSMfE Senior	Lanora Davis
---	BSMfE Sophomore	Eric Donkoh
---	BSMfE Sophomore	John Laryea
---	BSMfE Sophomore	Wilbur McClam
B.S.MfE	BSMfE Senior	Felipe Mesa
---	BSMfE Sophomore	Daniel Milo
---	BSMfE Sophomore	Spence Moore
---	BSMfE Sophomore	Jamal Newberry
---	BSMfE Senior	Tani Tambila

B. University of Cincinnati
 Department of Mechanical, Industrial and Nuclear Engineering
 Cincinnati, Ohio 45221-0072
 (513) 556-2738

<u>Degree Earned</u>	<u>Position</u>	<u>Name</u>
---	Professor	Max L. Brown, Ph.D.
Ph.D. M.E.	Ph.D. Candidate	Samer Masoud, Ph.D.
---	M.S. Candidate	Viorel Moga
---	M.S. Candidate	Prince Rodriguez
---	M.S. Candidate	Jeff Sutliff
---	BSME Junior	Mark Bauer
---	BSME Junior	Ric Bishop
---	BSME Junior	Keith Brandt
---	BSME Junior	Brad Libbey
---	BSME Junior	Earnest Nicholas
---	BSME Junior	Joe Servaites

BIBLIOGRAPHY

1. Boresi, Arthur P. and Den P. Chong, "Elasticity in Engineering Mechanics," Elsevier Science, 1987.
2. Chin, H., Danai, K. and Lewicki, D., Pattern Classifier for Health Monitoring of Helicopter Gearboxes, NASA Technical Memorandum 106099, AFSCOM Technical Report 92-C-033, April 1993.
3. Choy, F., Ruan, Y., Zakrajsek, J. and Oswald, F., Modal Simulation of Gearbox Vibration With Experimental Correlation, NASA Technical Memorandum 105702, AFSCOM Technical Report 92-C-018, July 1992.
4. Deutschman, A. D., Michels, W. J., and Wilson, C. E., Machine Design - Theory and Practice, Macmillan Publishing Co., Inc., New York, 1975, p. 118.
5. Dippery, Richard E., "A Study in Stress Concentration Optimization Using Boundary Element Methods," Ph.D. dissertation, University of Cincinnati, Cincinnati, Ohio 1990
6. Lawry, Mark H., "I-DEAS Student Guide," Structural Dynamics Research Corporation, 2000 Eastman Drive, Milford, Ohio 45150, 1991.
7. Savage, M. Prasanna, M. and Coe, H., Maximum Life Spiral Bevel Reduction Design, NASA Technical Memorandum 105790, AFSCOM Technical Report 92-C-004, July 1992.
8. Shigley, J. E. and C. R. Mischke, "Mechanical Engineering Design," 5th edition, McGraw-Hill, 1989.
9. Srinivasulu, B., Spur Gears - A New Approach to Tooth Design, AGMA Technical Paper No. 92FTMS1, American Gear Manufacturers Association 1500 King Street, Suite 201, Alexandria, VA 22314, October 1992.
10. Yang, T. Y., "Finite Element Structural Analysis," Prentice Hall Inc., Englewood Cliffs, N.J., 1986.
11. Zakrajsek, J, Townsend, D. and Decker, H., An Analysis of Gear Fault Detection Methods as Applied to Pitting Fatigue Failure Data, NASA Technical Memorandum 105950, AFSCOM Technical Report 92-C-035, April 1993.