


**Complementary 2-D MESFET for
Low Power Electronics**

Interim Report # 4

**Air Force SBIR Phase I
Contract Number: F33615-95-C-1679**

July 31, 1995



Delivered To:

**Dr. Edgar J. Martinez
BLDG 620
2241 Avionics Circle Ste 17
Wright-Patterson AFB OH 45433-7319
TEL: (513) 255-8636**

From:

**Advanced Device Technologies, Inc.
2015 Ivy Road, Ste. 308
Charlottesville, VA 22903
TEL: (804) 979-4103**

W.C.B. Peatman 7/31/95
Dr. William C.B. Peatman, President

DTIC QUALITY INSPECTED 8

Approved for public release; distribution is unlimited.

19950802 060

Complementary 2-D MESFET for Low Power Electronics (AirForce SBIR Contract F33615-95-C-1679)

Phase I Interim Report #4

As detailed in the Phase I proposal, the project has four major tasks. These are 1) assessment of the p-channel 2-D MESFET device fabrication, 2) development of a p-channel 2-D MESFET model and implementation of the model into AIM-SPICE, 3) circuit simulations of complementary 2-D MESFET circuits using AIM-SPICE and comparison with conventional circuits, and, 4) analysis of manufacturability and technology insertion issues. This report summarizes progress in each task area through 28 JUL 95.

Task 1: Assessment of p-Channel Device Fabrication

The assessment of the p-channel 2-D MESFET device fabrication is underway. Heterostructure modeling of a prospective AlGaAs/InGaAs/GaAs structure was completed and an order was placed for growth of the wafer. The wafer is scheduled to be delivered in mid-August. Fabrication of p-channel devices fabrication will begin in August/September.

Task 2: Development of p-Channel 2-D MESFET Model

The preliminary p-channel 2-D MESFET model has been implemented into AIM-Spice and is presently being used to simulate discrete p-channel 2-D MESFET $I-V$ characteristics as well as complementary 2-D MESFET logic circuits (see below). The p-channel device model uses a lower Schottky barrier height (typically 0.6V) compared with that of the n-channel device (typically 0.8 V). Also, the hole mobility has been set to $1000 \text{ cm}^2/\text{Vs}$, consistent with the observed trend of enhanced electron mobility in the n-channel devices.

Task 3: Complementary 2-D MESFET Circuit Simulations

Circuit simulations of complementary 2-D MESFET circuits are underway. In Fig. 1, we show the dc transfer characteristics of the complementary 2-D MESFET inverter at room temperature using the n- and p-channel device models implemented in AIM-Spice. The simulations predict excellent low power switching behavior including a noise margin of 0.23 V and voltage gain of 10 at a supply voltage of $V_{DD} = 0.6 \text{ V}$. While the use of this low V_{DD} value leads to good dc switching behavior, it may be necessary to increase the supply voltage in order to achieve high speed performance. We are looking at ways to reduce the p-channel leakage current and thereby permit higher supply voltages, if that should prove necessary. Power-delay simulations of all of these circuits are underway.

Task 4: Manufacturability and Technology Insertion Issues

This task will be summarized in the Final Report.

☒	
☐	
☐	
By _____	
Distribution / _____	
Availability Codes	
Dist	Avail and/or Special
A-1	




Fig. 1. Complementary 2-D MESFET DC inverter characteristics for two different p -channel threshold voltages at $V_{DD} = 0.6$ V. Both inverters have noise margins of above 0.2 V and voltage gains of about 10.

Distribution List

- 1 Dr. Edgar J. Martinez
BLDG 620
2241 Avionics Circle Ste. 17
Wright-Patterson AFB OH 45433-7319
TEL: (513) 255-8636
- 2 Mark D. Sauls, Contract Negotiator
Wright Laboratory WL/AAKE BLDG 7
2530 C ST
Wright Patterson AFB OH 45433-7607
- 3 Administrative Contracting Officer
DCMAO Baltimore
ATTN: Chesapeake
200 Towsontown Blvd. West
Towson, MD 21204-5299
- 4-5 Defense Technical Information Center
Building 5, Cameron Station
Alexandria, VA 22304-6145
- 6 Defense Contracts Office
U.S. Federal Court House, Rm 222
255 W. Main Street
Charlottesville, VA 22902
ATTN: Mr. Wade Payne