




## **A Novel Aircraft Instrument Display to Minimize the Risks of Spatial Disorientation**

By

**Simon J. Durnford  
Shannon L. DeRoche**



**Aircrew Health and Performance Division**

**June 1995**

**19950911 081**

DTIC QUALITY INSPECTED 5

Approved for public release; distribution unlimited.

**U.S. Army Aeromedical Research Laboratory  
Fort Rucker, Alabama 36362-0577**

## Notice

### Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

### Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

### Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.


### Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

### Human use

Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to AR 70-25 and USAMRDC Reg 70-25 on Use of Volunteers in Research.

Reviewed:




RICHARD R. LEVINE


LTC, MS

Director, Aircrew Health and  
Performance Division

Released for publication:



ROGER W. WILEY, O.D., Ph.D.  
Chairman, Scientific  
Review Committee



DENNIS F. SHANAHAN  
Colonel, MC, MFS  
Commanding

| REPORT DOCUMENTATION PAGE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |                                                     |                                                                                                                                                    | Form Approved<br>OMB No. 0704-0188    |                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|-----------------------------------|
| 1a. REPORT SECURITY CLASSIFICATION<br>Unclassified                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |       |                                                     | 1b. RESTRICTIVE MARKINGS                                                                                                                           |                                       |                                   |
| 2a. SECURITY CLASSIFICATION AUTHORITY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |       |                                                     | 3. DISTRIBUTION/AVAILABILITY OF REPORT<br>Public release; distribution unlimited                                                                   |                                       |                                   |
| 2b. DECLASSIFICATION/DOWNGRADING SCHEDULE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |                                                     |                                                                                                                                                    |                                       |                                   |
| 4. PERFORMING ORGANIZATION REPORT NUMBER(S)<br><br>USAARL Report No. 95-24                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |       |                                                     | 5. MONITORING ORGANIZATION REPORT NUMBER(S)                                                                                                        |                                       |                                   |
| 6a. NAME OF PERFORMING ORGANIZATION<br>U.S. Army Aeromedical<br>Research Laboratory                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       | 6b. OFFICE SYMBOL<br>(if applicable)<br>MCMR-UAS-AF | 7a. NAME OF MONITORING ORGANIZATION<br>U.S. Army Medical Research and Materiel<br>Command                                                          |                                       |                                   |
| 6c. ADDRESS (City, State, and ZIP Code)<br>P.O. Box 620577<br>Fort Rucker, AL 36362-0577                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |       |                                                     | 7b. ADDRESS (City, State, and ZIP Code)<br>Fort Detrick<br>Frederick, MD 21702-5012                                                                |                                       |                                   |
| 8a. NAME OF FUNDING / SPONSORING<br>ORGANIZATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       | 8b. OFFICE SYMBOL<br>(if applicable)                | 9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER                                                                                                    |                                       |                                   |
| 8c. ADDRESS (City, State, and ZIP Code)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |                                                     |                                                                                                                                                    |                                       |                                   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |                                                     | 10. SOURCE OF FUNDING NUMBERS                                                                                                                      |                                       |                                   |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |                                                     | PROGRAM<br>ELEMENT NO.<br>0602787A                                                                                                                 | PROJECT<br>NO. 3M162<br>787A879       | TASK<br>NO.<br>OA                 |
| 11. TITLE (Include Security Classification)<br>(U) A Novel Aircraft Instrument Display to Minimize the Risks of Spatial Disorientation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |       |                                                     |                                                                                                                                                    |                                       |                                   |
| 12. PERSONAL AUTHOR(S)<br>Simon J. Durnford and Shannon L. DeRoche                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |       |                                                     |                                                                                                                                                    |                                       |                                   |
| 13a. TYPE OF REPORT<br>Final                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       | 13b. TIME COVERED<br>FROM _____ TO _____            |                                                                                                                                                    | 14. DATE OF REPORT (Year, Month, Day) |                                   |
| 15. PAGE COUNT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |                                                     |                                                                                                                                                    |                                       |                                   |
| 16. SUPPLEMENTARY NOTATION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |       |                                                     |                                                                                                                                                    |                                       |                                   |
| 17. COSATI CODES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |                                                     | 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)<br>spatial disorientation, rotary-wing, instruments,<br>displays |                                       |                                   |
| FIELD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | GROUP | SUB-GROUP                                           |                                                                                                                                                    |                                       |                                   |
| 01                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 02    |                                                     |                                                                                                                                                    |                                       |                                   |
| 01                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 04    |                                                     |                                                                                                                                                    |                                       |                                   |
| 19. ABSTRACT (Continue on reverse if necessary and identify by block number)<br>A novel instrument display designed to reduce cognitive workload was tested against a standard instrument panel using a helicopter mockup linked to a computer flight simulator. Both pilots and nonpilots were used as subjects and tests involved recovery from unusual aircraft attitudes as well as flight maneuvering instruments. The novel display incorporates heading, speed, roll, and pitch into a single tracking task. Users set the desired heading and the desired speed (and the desired altitude and glide path). The display then guides control movements to achieve and maintain the desired parameters. Results from the unusual attitudes experiment showed significant benefits from the novel display, evident in improved performance on a secondary task (noise identification) and reduced control input errors. Results from the flying portion of the study showed significantly improved performance at the secondary task together with improved speed control when using the new display, although heading control was reduced. Further modifications to the new display have been introduced since these initial experiments, and further testing should be carried out using dynamic<br>(Continued on reverse) |       |                                                     |                                                                                                                                                    |                                       |                                   |
| 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT<br><input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       |                                                     | 21. ABSTRACT SECURITY CLASSIFICATION<br>Unclassified                                                                                               |                                       |                                   |
| 22a. NAME OF RESPONSIBLE INDIVIDUAL<br>Chief, Scientific Support Center                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |                                                     | 22b. TELEPHONE (Include Area Code)<br>205-255-6907                                                                                                 |                                       | 22c. OFFICE SYMBOL<br>MCMR-UAX-SS |

19. Abstract (Continued)

displays during unusual attitudes and continual data collection during flight. The display should be developed further to make it possible to utilize it in a HUD or other NVD and to give it the capability to display hover information.

|                    |                                     |
|--------------------|-------------------------------------|
| Accession For      |                                     |
| NTIS CRA&I         | <input checked="" type="checkbox"/> |
| DTIC TAB           | <input type="checkbox"/>            |
| Unannounced        | <input type="checkbox"/>            |
| Justification      |                                     |
| By                 |                                     |
| Distribution /     |                                     |
| Availability Codes |                                     |
| Dist               | Avail and/or<br>Special             |
| A-1                |                                     |

## Table of contents

|                                                        | <u>Page</u> |
|--------------------------------------------------------|-------------|
| Introduction.....                                      | 3           |
| Design aims of the novel display.....                  | 4           |
| Details of the novel display.....                      | 6           |
| Aircraft speed and heading.....                        | 6           |
| Aircraft altitude.....                                 | 7           |
| Methods.....                                           | 8           |
| Recovery from unusual attitudes.....                   | 8           |
| The flying task.....                                   | 11          |
| The secondary task.....                                | 14          |
| Subject questionnaires.....                            | 14          |
| Subjects.....                                          | 15          |
| Training and experimental profile.....                 | 15          |
| Results.....                                           | 17          |
| Objective results.....                                 | 17          |
| Unusual attitudes.....                                 | 17          |
| Flying data.....                                       | 19          |
| Subjective questionnaires.....                         | 22          |
| Pilots.....                                            | 22          |
| Nonpilots.....                                         | 22          |
| Discussion.....                                        | 22          |
| Recovery from unusual attitudes.....                   | 22          |
| Flying.....                                            | 24          |
| Laboratory results versus real life requirements.....  | 25          |
| Adapting the display for use in a HUD or NVD.....      | 25          |
| Adapting the display to provide hover information..... | 26          |
| Conclusions.....                                       | 26          |
| References.....                                        | 27          |
| Appendix.....                                          | 28          |

### List of tables

| <u>Table</u>                                                                                                                   | <u>Page</u> |
|--------------------------------------------------------------------------------------------------------------------------------|-------------|
| 1 Secondary task (zita) scores while recovering from unusual attitudes.....                                                    | 18          |
| 2 Numbers of control errors made during the recovery from unusual attitudes summed across subjects.....                        | 19          |
| 3 Mean scores on the secondary task (zita) during the flying portion of the study broken down by display and pilot status..... | 20          |
| 4 Final accuracy in achieving desired flight parameters broken down by display and pilot status.....                           | 21          |

### List of figures

| <u>Figure</u>                                             | <u>Page</u> |
|-----------------------------------------------------------|-------------|
| 1 The novel display.....                                  | 5           |
| 2 The cockpit mockup.....                                 | 9           |
| 3 The standard display.....                               | 10          |
| 4 An unusual attitude as displayed on the standard panel. | 12          |
| 5 An unusual attitude as displayed on the new display.... | 13          |

### Acknowledgments

The authors would like to acknowledge the debt they owe to the computer skills of USAARL's Dan Ranchino and Andy Higdon, together with those of Tom Marlow of Coryphaeus Software, Los Gatos, California. The novel display tested in this project was designed using Designer's Workbench Software, produced by Coryphaeus. We also are indebted greatly to USAARL's Al Lewis, Bob Dillard and Phil Johnson for creating the helicopter mockup cockpit.

## Introduction

It has long been known that humans cannot maintain straight and level flight in the absence of visual cues (Anderson, 1919). It also has long been known that the human organs of balance not only fail to give sufficient cues for accurate perception of position or motion during aviation, but may give erroneous cues (for overviews see Guedry, 1974 and Benson, 1988). The common result of insufficient or misperceived cues, whatever their origin, is a state of spatial disorientation (SD), commonly defined as the predicament "...when the aviator fails to sense correctly the position, motion, or attitude of his aircraft or of himself within the fixed coordinate system provided by the surface of the earth and the gravitational vertical" (Benson, 1988).

The significance of SD is demonstrated by 32 percent of U.S. Army class A-C rotary-wing accidents involved SD as the major contributing factor (Durnford et al., 1995). Many of these accidents would occur whatever type of instrument display was in use, since the aircrew are simply not looking at the instruments. However, there are a number of accidents which involve the classically disorientating conditions of inadvertent entry to instrument meteorological conditions (IMC), whiteout or brownout, and which might be amenable to improved instrument displays. These accidents represent some 25 percent of U.S. Army rotary-wing SD accidents, although they constitute a considerably higher proportion in other groups such as general aviation rotary-wing accidents (Adams, 1989). In addition to these accidents, there are those in which an easily understood instrument display may prevent the initial circumstances leading to disaster by either providing an easy source of information against which aircrew might check their progress or by providing a simple symbology which could be superimposed upon external views (as in a head-up display [HUD]).

Present day helicopter instrument panels are derived from fixed-wing aircraft and are designed to provide information about forward flight. They do not give reliable information about hovering. Even in forward flight, the panels are not easy to interpret because of the following five standard aircraft parameters that need to be monitored and integrated: aircraft

attitude, airspeed, altitude, rate-of-climb or rate-of-descent, and aircraft heading. Some aircrew have difficulty doing this even during routine instrument flight. The panic associated with SD makes reading and understanding five separate instruments even more difficult (Benson, 1988).

Although it is relatively easy to identify the possible benefits of an improved instrument display in which all five parameters were integrated, it is less easy to identify a suitable design. This is particularly true if one accepts the usual aim of giving the pilot a constant mental image of aircraft orientation. Under this traditional system, the pilot has to continually monitor the aircraft's orientation and react with the appropriate control inputs. Therefore, the pilot needs to gather information on all aspects of the aircraft's position and motion.

To reduce this workload means moving away from this traditional aim. A new concept was developed in which the pilot would be able to specify particular parameters (such as speed or heading) and then match his control inputs to a simple, integrated display which would ensure that those parameters were maintained (or, if necessary, recovered). In effect, the concept was to replace a high level cognitive task with a comparatively low level tracking task. In the new display, the pilot can check any parameter at any time (for example, altitude or airspeed), but is freed from the requirement to continually sample these parameters to maintain stable flight. Situational awareness is in no way reduced; the pilot is aware entirely of the aircraft's orientation, but is spared the burden of monitoring it.

This paper describes the initial results of tests on this display concept.

#### Design aims of the novel display

- To produce a simple display which would provide an easy source of information for reorientation during episodes of SD, while also providing an adequate source of information for standard instrument flight.




Figure 1. The novel display.

- To produce a prototype display which could be developed further as a head-up or injected symbology display.

- To produce a framework which could be used later to give hover information (either as an integral part of the complete display or as a switch over function).

### Details of the novel display

Figure 1 shows the novel display used in this experiment. The display has evolved further since it was tested (see conclusions).

The central field of the display consists of a series of squares (themselves arranged in a square) and a small triangle. The triangle moves across the squares as a function of aircraft speed and heading. (The x-axis represents heading and the y-axis speed.) Movement of the triangle along these axes is a derivative of the orientation functions of pitch and roll since speed depends on pitch inputs and heading on roll inputs.

### Aircraft speed and heading

Fore and aft cyclic movements are used to maintain the desired aircraft speed by steering the triangle to the midline on the x-axis. Lateral cyclic movements do the same for the heading using the y-axis. Thus, if the triangle is kept in the central box, the aircraft will remain steady on both the desired speed and heading.

The compass tape across the top gives the actual heading and the box below the desired heading.

The air speed indicator (ASI) below the central squares gives a digital readout of aircraft speed. The numbers inside the lateral squares give the relative speed corresponding to that position on the y-axis. Similarly, the numbers above and below the squares give the relative number of degrees away from the desired heading that is appropriate to that position on the x-axis.

Because speed and heading are in themselves no absolute indications of pitch and roll (and aerodynamics makes it essential that these are controlled), there is a vector that has its origin in the center of the triangle. As the aircraft pitches forward, the line extends forwards. As the aircraft pitches back, the line extends backwards. This vector also is linked to roll and therefore has a 360° arc of freedom. The size, as well as the direction, of the vector is resolved from both pitch and roll, thus making it possible for pilots to control these parameters. Furthermore, because speed and heading depend on pitch and roll, this vector points the way that the triangle shortly will begin to move. Pilots can anticipate speed and heading changes and use the vector to steer the triangle.

Since this experiment, the vector has been replaced with a much simpler system which drives the triangle's position through combinations of roll angle with heading and pitch angle with speed. Positioning the triangle within the central box now means that the aircraft will regain and then retain the desired speed and heading (see recommendations).

#### Aircraft altitude

Altitude is color coded. The triangle maintains a green color if the altitude is at the desired level (or up to 100 feet above), a red color if it is lower, and a blue color if it is higher. The altimeter to the right of the squares reinforces height information by showing the specific altitude (in digital readout form) as well as the difference between the actual altitude and the desired altitude (in color coded tape form). Boxes display the current settings for the desired altitude and pressure setting. The vertical speed indicator (VSI) on the left of the squares acts in much the same way as the color coded tape display of the altimeter. It is placed on the left because it is the instrument that responds most quickly to control inputs from the collective lever in the pilot's left hand. (Research has shown that information displays should, where possible, be on the same side as the relevant control, Hartzell et al., 1983).

## Methods

The novel display was tested against a standard instrument display using a helicopter cockpit mockup with full size controls linked to a simulator program run on a Silicon Graphics Iris Indigo XZ machine\*. A photograph of the cockpit mockup is at Figure 2. The standard display used is shown in Figure 3. For each subject, there were two series of experiments. One involved recovery from unusual attitudes and the other involved flying. Subject performance at these tasks was measured. In addition, the use of attentional resources was estimated by measuring performance at a secondary task involving the identification of high or low tones.

Unexpected software and hardware limitations meant that it was not possible to begin an episode of simulated flight in an unusual attitude. (Altitude, speed, and rate-of-climb or rate-of-descent could be varied at the start of each episode, but neither roll nor pitch could be.) This meant that only static displays were used in the experiments involving recovery from unusual attitudes. Similar limitations prevented us recording moment-to-moment flight path data, and so measurements in the flying experiments were restricted to how close subjects came to achieving the desired flight path by the end of each session.

### Recovery from unusual attitudes

Subjects were exposed to a series of eight static panels representing unusual aircraft attitudes. They then were exposed to a second series using the other instrument panel. Half the subjects used the standard display first, while the other half used the new display. Unknown to the subjects, the second set of unusual attitudes was the same as the first, but in reversed order so as to counterbalance any learning effects when data were pooled across subjects. These unusual attitudes involved pitch ranges from  $-30^{\circ}$  to  $+30^{\circ}$ , roll ranges from  $60^{\circ}$  left to  $60^{\circ}$  right, airspeeds from 35 kts to 135 kts, and vertical speed rates from

---

\*See manufacturers' list.




Figure 2. The cockpit mockup.




Figure 3. The standard display.

2000 fpm climb to 2000 fpm descent. Figures 4 and 5 show an identical unusual attitude as it would be presented on the standard and the novel displays.

Subjects had 15 seconds to respond to the display by making control movements in the appropriate direction for bringing the helicopter back to straight-and-level flight (phase 1). This task required the subject to respond to pitch, roll, and rate-of-climb or rate-of-descent. An observer monitored their control inputs in terms of cyclic fore/aft, cyclic left/right, and collective up/down. The observer also monitored any indecision, as evidenced by corrections to the control inputs.

During this 15-second period, subjects also were exposed to the secondary task described later.

After the 15 seconds, the display was removed from sight and subjects were asked what further control inputs would be necessary to return the aircraft to a heading of north, an altitude of 2000 feet, and a speed of 100 kts (assuming they had achieved straight-and-level flight at the heading, speed, and altitude originally displayed). This task was phase 2 and required subjects to remember information on the display concerning heading, altitude, and speed.

### The flying task

The flying task consisted of four flights with each display. Each flight lasted 1 minute, during which period subjects had to achieve the following parameters:

- 100 kts (from a starting speed of either 80 kts or 120 kts)
- 2000 ft (from a starting point of 1500 ft or 2500 ft)
- A heading of west or east (from a starting point of north)

Subjects also were exposed to the secondary task for the full period.




Figure 4. An unusual attitude as displayed on the standard panel.




Figure 5. An unusual attitude as displayed on the new display.

As for the unusual attitude part of the experiment, the order in which the displays were used were balanced across subjects. Each subject was exposed to the same starting parameters twice (once with each display).

Because it proved difficult to record moment-to-moment flight data, these episodes were scored on how close subjects came to achieving the desired parameters at the end of the minute period and on their scores for the secondary task. In addition, final roll angle, pitch angle, and rate-of-climb or descent were measured.

### The secondary task

The secondary task was incorporated into the experiments to give a measure of the spare attentional resources available to subjects while they were performing the primary tasks. An American Computer Zero Input Tracking Analyzer\* (ZITA) machine was used for this task. This machine has been extensively described in previous studies (see, for example, Simmons et al., 1989).

The subject was required to identify a high or a low tone by pressing an appropriate button on the cyclic handgrip before the next tone was played. Tones were played at a rate of 1 per second. The total number of responses, together with the numbers of correct and incorrect responses, were used as dependent measures.

### Subject questionnaires

Subjects were asked to rate the ease of use of the new display against the standard display by selecting one of the following options:

- The new display was much more difficult to use than the standard display.
- The new display was more difficult to use than the standard display.

- There was no difference in the ease of use of the two displays.

- The new display was easier to use than the standard display.

- The new display was much easier to use than the standard display.

Subjects did this immediately after the unusual attitudes part of the study and again immediately after the flying part of the study. In the latter part, pilot subjects also were asked how they would rate the new display if they had flown as many hours using the new display as they had previously flown using the standard form of panel.

### Subjects

Five aircrew in current flying practice and five nonaircrew subjects were used.

Each subject was in normal health and free from medication. All were able to easily hear and identify the low and high tones of the secondary task.

Subjects were given both a written and an oral brief. All signed volunteer consent forms.

### Training and experimental profile

Subjects were given a minimum of 1 hour of training on the helicopter simulator program, the two display formats, and the secondary task. Training began with a general explanation of the two displays. Subjects then were taken through the specific information provided by the two displays with regard to airspeed, heading, altitude and rate-of-climb (or descent). Once they confirmed they understood the information given by the displays, they were shown how changes in pitch and roll initiated by cyclic changes affected the attitude indicator on the standard panel and the yellow vector line on the novel display. Then, they also

were shown how changes in pitch and roll had secondary effects on speed, heading and rate of climb (or descent). During this phase they were encouraged to play with the cyclic controls until they felt familiar with how the displays responded. Next, they were shown how movements of the collective affected the displays in terms of rate of climb (or descent) and altitude. Again they were encouraged to play with the collective. Once they felt comfortable with the effects of moving the collective, they were asked to put cyclic and collective movements together to see the influence on the displays. Periods of rest were offered as and when needed.

Subjects only went forward to the next phase once they had confirmed they felt generally comfortable flying the two displays and, that they understood the information provided by the displays and how control inputs affected them. In this phase, they were given further training on how the displays provided information about unusually extreme aircraft attitudes, beginning with whichever display they would be using second in the experiment. The static displays used in training were similar to those used in the experiments, but care was taken to ensure that none of the experimental unusual attitudes were used for training. Subjects were trained until they demonstrated on at least four consecutive occasions that they could interpret correctly unusual attitudes involving deviations in airspeed, rates-of-climb (or descent), altitude and heading, and that they could integrate these with the information from the attitude indicator (or yellow vector) to derive the required control inputs to recover the aircraft to safe and level flight and then to the original flight path. Once they had confirmed they felt comfortable with the task using this first display, they received training on the other. After demonstrating competence with the second display, they entered the study. Following the first set of unusual attitudes, they received refresher training on the other display until they again confirmed that they felt comfortable enough to be exposed to the second set of unusual attitudes.

Prior to the flying part of the study, they were given further training and practice on maneuvering the simulator using the display most recently used for the unusual attitudes. No accuracy standards were required of subjects, other than the

ability to fly the aircraft for a period of 2 minutes or more without crashing since it was expected that proficiency would be highly variable. When they confirmed that they felt comfortable with this, they performed the four flying tasks with this display. They then received further training on maneuvering using the other display, and when comfortable with this, they performed the same four flying tasks again.

All subjects were introduced to the secondary task during the period they first started putting cyclic and collective control movements together to fly the simulator. Subsequently, the secondary task was introduced into the training for each experimental section as subjects began to demonstrate competence.

Subjects were told they would be scored on all parts of the experiment and should spread their attention across as many aspects as possible (with the single exception that they could, if necessary, concentrate on avoiding a crash during the flying phase).

## Results

### Objective results

The results for each subject were collapsed to give a mean for each dependant variable (except in the case of control errors, when the errors were summed). They then were analyzed in two groups, those resulting from the unusual attitude portion of the study and those from the flying part of the study.

### Unusual attitudes

Shapiro-Wilks' tests showed that the means on the secondary (ZITA) task were normally distributed (e.g.,  $p > 0.0897$  for the correct ZITA responses using the standard display,  $p > 0.820$  for correct responses using the new display). Therefore, these were analyzed using ANOVA with one grouping variable (pilots and non-pilots) and one repeated measure (standard display or new display).

The pattern of control errors, however, never came close to a normal distribution, even after various transformations (e.g., Shapiro-Wilks'  $p < 0.0004$  for errors on phase 2 after log transformation). Therefore, these results were analyzed using Wilcoxon tests.

Table 1 gives the mean ZITA responses grouped by display and pilot status. Univariate ANOVA showed a strong display effect on both the total number of responses and the number of correct responses ( $p = 0.003$  and  $p = 0.004$  respectively). There was no significant display effect on the number of incorrect responses and no pilot effect on any of the variables.

Table 1.

Secondary task (zita) scores while recovering from unusual attitudes.

|           | Mean total ZITA score |             | Mean correct ZITA score |             |
|-----------|-----------------------|-------------|-------------------------|-------------|
|           | Standard display      | New display | Standard display        | New display |
| Pilots    | 9.65                  | 11.88       | 6.75                    | 9.38        |
| Nonpilots | 10.74                 | 11.90       | 8.59                    | 9.34        |
| All SS    | 10.19                 | 11.89       | 7.67                    | 9.36        |

The scores given are mean total score and mean correct score broken down by pilot and display groups.

During the experiment, control error data were collected according to the control involved (cyclic or collective) and the direction of input, as well as by the task (recovery to straight and level flight, or recovery to the original flight path). The number of corrections to control inputs during the first phase also was recorded. In order to limit the number of statistical tests performed, these errors were summed across the two different groups (pilot and nonpilot), providing a set of paired data for a single Wilcoxon\* test (standard display versus new display). These total numbers of control errors are given in Table 2 below, together with the totals for the different phases. The Wilcoxon test on the grand total showed a significant reduction in control errors when the new display was used ( $p = 0.0077$ ).

Table 2.  
Numbers of control errors made during the recovery  
from unusual attitudes summed across subjects.

|            | Total errors |             | Errors in 1st phase |             | Corrected inputs |             | Errors in 2nd phase |             |
|------------|--------------|-------------|---------------------|-------------|------------------|-------------|---------------------|-------------|
|            | 'old' panel  | 'new' panel | 'old' panel         | 'new' panel | 'old' panel      | 'new' panel | 'old' panel         | 'new' panel |
| Pilots     | 67           | 38          | 28                  | 22          | 14               | 5           | 25                  | 11          |
| Non-pilots | 90           | 27          | 40                  | 13          | 18               | 8           | 32                  | 6           |
| All SS     | 157          | 65          | 68                  | 35          | 32               | 15          | 57                  | 17          |

Further investigation (by grouping the data according to pilot/nonpilot status and phase of recovery) revealed that these significant differences lay primarily in the nonpilot group. There were no significant differences in the pilot data when taken alone, whereas the nonpilot data showed display differences in both the number of corrected control inputs and the number of errors made on phase 2 (at the  $p=0.043$  level). Adding the pilot data strengthened the significance level in both these groups ( $p=0.019$  for the former and  $p=0.017$  for the latter), indicating that the pilot data was in a similar direction even if it did not reach significance.

#### Flying data

Secondary task scores during the flying portions of the experiment, like those during the unusual attitudes, showed normal distributions (e.g., Shapiro-Wilks'  $p>0.6$  for correct ZITA scores when using the standard display, and  $p>0.94$  when using the new display). These scores were analyzed using ANOVA.

Mean errors in accuracy at achieving the desired final flight parameters were not, on the whole, normally distributed (e.g., the Shapiro-Wilks'  $p$  value for the final roll angle when using the standard display was  $<0.0001$ ). Log transformation was able to bring them into an acceptably normal range (e.g., the new Shapiro-Wilks'  $p$  value for the log of the final roll angle when

using the standard display was 0.41). The sole exception was for the final pitch angle when using the standard display, whose Shapiro-Wilks' recovered only to  $p=0.03$  from an initial value of  $p<0.0000$ . ANOVA was performed on the log transformations.

Table 3 gives the mean secondary task (ZITA) scores for the flying portion of the study. ANOVA revealed a significant display effect on the number of incorrect responses ( $p=0.023$ ) but no pilot effect. There were no significant effects on the number of correct responses or on the total number of responses, although the display effect on the number of correct responses nearly reached significance ( $p=0.08$ ).

Table 3.

Mean scores on the secondary task (ZITA) during the flying portion of the study broken down by display and pilot status.

|           | Incorrect ZITA responses |             | Correct ZITA responses |             |
|-----------|--------------------------|-------------|------------------------|-------------|
|           | Standard display         | New display | Standard display       | New display |
| Pilots    | 12.95                    | 10.35       | 31.33                  | 35.15       |
| Nonpilots | 11.10                    | 8.80        | 30.15                  | 32.65       |
| All SS    | 12.03                    | 9.58        | 30.74                  | 33.90       |

Table 4 shows the final accuracy in achieving the desired flight parameters broken down by display and pilot status. ANOVA on the log of these values revealed display effects in airspeed and heading (the new display was associated with more accurate airspeed but less accurate heading,  $p=0.038$  and  $p=0.043$ , respectively). Pilot effects were shown on heading and altitude (pilots were more accurate than nonpilots,  $p=0.035$  and  $p=0.0074$ , respectively). No effects could be shown on rate-of-climb or descent, pitch angle or roll angle.

Table 4.  
Final accuracy in achieving desired flight parameters  
broken down by display and pilot status.

|           | Airspeed (kts)                             |      |             |       |
|-----------|--------------------------------------------|------|-------------|-------|
|           | Standard display                           |      | New display |       |
|           | Range                                      | Mean | Range       | Mean  |
| Pilots    | 7-38                                       | 16.0 | 4-28        | 10.75 |
| Nonpilots | 18-45                                      | 26.3 | 1-27        | 12.2  |
| All SS    | 7-45                                       | 21.1 | 1-28        | 11.5  |
|           | Heading (degrees)                          |      |             |       |
|           | Standard display                           |      | New display |       |
|           | Range                                      | Mean | Range       | Mean  |
| Pilots    | 2-9                                        | 6.0  | 4-42        | 14.8  |
| Nonpilots | 6-39                                       | 19.0 | 8-83        | 37.0  |
| All SS    | 2-39                                       | 12.5 | 4-83        | 26.1  |
|           | Altitude (feet)                            |      |             |       |
|           | Standard display                           |      | New display |       |
|           | Range                                      | Mean | Range       | Mean  |
| Pilots    | 129-337                                    | 229  | 270-415     | 335   |
| Nonpilots | 224-934                                    | 602  | 361-1060    | 667   |
| All SS    | 129-934                                    | 415  | 270-1060    | 501   |
|           | Rate of climb or descent (feet per minute) |      |             |       |
|           | Standard display                           |      | New display |       |
|           | Range                                      | Mean | Range       | Mean  |
| Pilots    | 4-20                                       | 12.4 | 4-34        | 15.8  |
| Nonpilots | 10-59                                      | 26.6 | 7-28        | 15.9  |
| All SS    | 4-59                                       | 19.5 | 4-34        | 15.9  |
|           | Pitch angle from zero (degrees)            |      |             |       |
|           | Standard display                           |      | New display |       |
|           | Range                                      | Mean | Range       | Mean  |
| Pilots    | 2-6                                        | 3.8  | 3-9         | 5.5   |
| Nonpilots | 3-35                                       | 10.9 | 2-7         | 4.5   |
| All SS    | 2-35                                       | 7.3  | 2-9         | 5.0   |
|           | Roll angle from zero (degrees)             |      |             |       |
|           | Standard display                           |      | New display |       |
|           | Range                                      | Mean | Range       | Mean  |
| Pilots    | 1-6                                        | 3.9  | 4-10        | 6.6   |
| Nonpilots | 1-31                                       | 9.6  | 2-6         | 4.0   |
| All SS    | 1-31                                       | 6.8  | 2-10        | 5.3   |

## Subjective questionnaires

### Pilots

Four out of the five pilots rated the new display as much easier to use for recovery from unusual attitudes; the other marked it as easier.

Given their present level of training and experience, three pilots considered the new display less easy to fly with than the standard panel; two considered it to be no different.

When considering how the new panel display would compare against the standard panel, given equal flying experience with both displays, one pilot considered the new panel would be much easier to use than the standard panel. Two considered it would be easier and one considered there would be no difference. One failed to record an opinion.

### Nonpilots

In an identical result to the pilot group, four out of the five nonpilots marked the new display as much easier to use for recovery from unusual attitudes; the other marked it as easier.

Given their present level of training and inexperience, two nonpilots considered the new display much easier to fly with than the standard panel, two considered it to be easier, and one considered it to be no different.

## Discussion

### Recovery from unusual attitudes

It is recognized that a static display of an unusual attitude is unrealistic in that aircrew receive a great deal of information from the manner in which their instruments change. Nonetheless, it is considered that the tests carried out here gave a fair indication of the ease with which subjects were able to extract information concerning flight parameters from each display. Further testing with dynamic displays is, of course,

essential and must be a future aim. (Such testing was the original aim of this study.)

The pattern of benefits associated with the new display was similar for both pilots and nonpilots. Although the ANOVA showed no pilot effects on ZITA scores, the benefits in the pilot group tended to show most in better ZITA scores, while the benefits in the nonpilots tended to show most in reduced control input error rates. Nonpilots were included in the study because of the potential bias in aircrew associated with their many hours of instrument flying using a standard panel. It was postulated that this bias might negate the possible workload benefits associated with the new display. Therefore, it is interesting and reassuring that the reduced workload (as implied by improvements in the secondary task scores) was observed mostly in the pilots. The findings in nonpilots suggest that the unusual attitude task was of sufficient difficulty for them to allocate a relatively fixed level of attentional resources to the task (whatever display was used). Also, this is suggested because, for them, the advantages of the new display showed up in a much reduced error rate.

These patterns lend objective evidence to support the questionnaire results, which showed that both pilots and nonpilots found the new display considerably easier to interpret than the standard panel.

During the experiments, one limitation with the new display was noted, namely that the vector could confuse rather than simplify. Subjects (both pilots and nonpilots) occasionally applied control inputs in the opposite direction to the vector line. The original intention of the display design was to create a simple put-the-triangle-in-the-box display without any need for vectors. This has been achieved subsequent to the experiment by linking the triangle's movement to pitch and roll and then adapting it to speed and heading. The triangle moves 1 cm for every  $10^\circ$  of roll (on the x-axis) or  $10^\circ$  of pitch (on the y-axis). This movement is not capped. The triangle also moves 1 cm for every  $20^\circ$  of deviation from the desired heading (x-axis) and 20 kts of deviation from the desired airspeed (y-axis). These latter movements are capped to a maximum of  $30^\circ$  heading difference and 25 kts airspeed difference. (These figures are

arbitrary experimental values and could be varied as needed). The result is that if the pilot returns the triangle to central square and keeps it there, the aircraft will regain and then retain its desired heading and speed using no more than a  $15^\circ$  angle of bank and  $12.5^\circ$  angle of pitch. The new version of the display should allow an even greater reduction in workload when dealing with unusual attitudes and should be as easy (or easier) to fly. Only further experimentation can confirm this.

### Flying

The principal concept behind the new display was to provide a "get-me-out-of-trouble" device. Nonetheless, it was important to find out whether the display could be used for normal instrument flight, and if so, what advantages and disadvantages might apply.

Overall, there appeared to be little difference in flying performance using the two displays. There were two significant results implying benefits from using the new display, namely improved speed control and fewer incorrect ZITA responses. There was one disadvantage, namely reduced heading control. With regard to heading control, two factors should be noted:

- The x-axis across which the triangle moved (from one side of the set of squares to the other) represented the whole  $360^\circ$  compass arc. The scale therefore was small and accuracy was difficult to obtain. The modifications to the display since the experiment have rectified this.

- Should the display ever be introduced into an aircraft, the intention would be that the pilot has the option of dialing up any required changes in heading and then flying the triangle back into the central box to attain that heading. In this experiment, software limitations prevented this strategy and subjects had to fly the triangle out of the box to a point that equated to a heading  $90^\circ$  from the original. This may have influenced the results.

Therefore, it seems likely that the new display, when reconfigured, will be no worse as a flying aid than the standard

panel and may well be better. This is supported by the subjective opinions of both the pilot and nonpilot groups. The objective results of this experiment are limited, however, by being based solely on the final parameters achieved. They give no information on aircraft control during each flight, and further experiments involving continual data collection are necessary. (No obvious differences in aircraft control were noted by the experimenters, and the only aircraft crash occurred when a nonpilot subject was using the standard panel.)

#### Laboratory results versus real life requirements

This experiment was carried out in a laboratory setting using a static helicopter mockup. Real flying takes place in very different conditions, and it is dangerous to assume that a source of flight information that appears better in a laboratory will necessarily prove better in the air. The next step in the development of this display should utilize a more realistic environment such as a full motion simulator (or a real aircraft).

It should be noted, in particular, that this new display intentionally gives no indication of the position of the horizon. Aircrew flying visually do so by orientating themselves to the horizon. If they fly into marginal weather or into mountainous terrain (where horizon lines may be difficult to determine), they may check their instruments to confirm the attitude of their aircraft. The new display will give no immediate confirmation of the position of the horizon, although it could easily be adapted to do so.

#### Adapting the display for use in a HUD or NVD

No attempt was made in this experiment to superimpose the display on a scene depicting the outside world. However, the display was designed with that use in mind, and further development along this path now might be warranted. The central squares, and all the other elements, could be replaced or adapted in such a way that they would be less obscuring.

## Adapting the display to provide hover information

Similarly, no attempt was made to provide hover information on the display. However, the design easily could be adapted for this purpose and further development along these lines might also be beneficial. It is envisaged that the display would be re-configured to give hover information by dialing the desired airspeed to zero. Airspeed figures then would become groundspeed figures and movement of the triangle from the central box would represent roll and pitch angles modified by the distance moved from the hover spot. The same sort of algorithms could be used as for the flight mode. This particular development would require accurate drift information from GPS or other systems. Hover mode would have to be differentiated clearly and visibly from flight mode to avoid aircrew confusion.

## Conclusions

The results of this experiment provide strong evidence that the concepts behind the new display are workable, and that the new display would make recovery from unusual attitudes (and quite probably instrument flying) easier than when using the standard panel.

However, limitations in the experimental design caused by software and hardware difficulties mean further testing is desirable. This testing should take place in an environment that is as realistic as possible and should use the postexperimental modifications to the display.

The display should be developed further to make it possible to superimpose it on outside scenes. In addition, it should be developed to be able to provide information on hovering.

## References

- Adams, R. J. 1989. Special considerations for helicopter safety. In: Aviation psychology. pp 210-230. Richard Jensen (ed). Vermont: Gower Publishing Company.
- Anderson, G. H. 1919. Medical and surgical aspects of aviation. London: Hodder and Stoughton.
- Benson, A. J. 1988. Spatial disorientation: general aspects. In: Aviation Medicine. 2nd ed. pp 277-296. J. Ernsting and P. King (eds). London: Butterworths and Co.
- Durnford, S. J., Rosado, N. R., Crowley, J. S., Harper, J. P., and DeRoche, S. L. 1995. Spatial disorientation: a survey of U.S. Army Accidents 1987-92. Fort Rucker, AL: U.S. Army Aeromedical Research Laboratory. USAARL Report No. 95-XX (in review).
- Guedry, F. 1974. Psychophysics of vestibular sensation. In: Handbook of sensory physiology: vestibular system, part 2, pp 5-136. H.H. Kornhuler (ed). New York, NY: Springer Verlag.
- Hartzell, E.J., Beveridge, R., Dunbar, S., and Cortilla, R. 1983. Helicopter pilot response latency as a function of the spatial arrangement of instruments and controls. Proceedings of the 18th annual conference on manual control Wright-Patterson Air Force Base, OH: Flight Dynamics Laboratory. AF WAL-TR-83-3021. 345-364.
- Simmons, R. R., Caldwell, J. A., Stephens, R. L., Stone, L. W., Carter, D. J., Behar, I., Mitchell, G. W., Knox, F. S., Jones, H. S., and Taylor, P. L. 1989. Effects of the chemical defense antidote atropine sulfate on helicopter pilot performance: a simulator study. Fort Rucker, AL: U.S. Army Aeromedical Research Laboratory. USAARL Report No. 89-17.

Appendix A.

List of manufacturers

American Computer and Electronics Corporation  
Gaithersburg, MD 20879

Coryphaeus Software  
985 University Avenue, Suite 31  
Los Gatos, CA 95030

Silicon Graphics Computer Systems  
2011 North Shoreline Boulevard  
Mountain View, CA 94039-1389

Initial distribution

Commander, U.S. Army Natick Research,  
Development and Engineering Center  
ATTN: SATNC-MIL (Documents  
Librarian)  
Natick, MA 01760-5040

Chairman  
National Transportation Safety Board  
800 Independence Avenue, S.W.  
Washington, DC 20594

Commander  
10th Medical Laboratory  
ATTN: Audiologist  
APO New York 09180

Naval Air Development Center  
Technical Information Division  
Technical Support Detachment  
Warminster, PA 18974

Commanding Officer, Naval Medical  
Research and Development Command  
National Naval Medical Center  
Bethesda, MD 20814-5044

Deputy Director, Defense Research  
and Engineering  
ATTN: Military Assistant  
for Medical and Life Sciences  
Washington, DC 20301-3080

Commander, U.S. Army Research  
Institute of Environmental Medicine  
Natick, MA 01760

Library  
Naval Submarine Medical Research Lab  
Box 900, Naval Sub Base  
Groton, CT 06349-5900

Executive Director, U.S. Army Human  
Research and Engineering Directorate  
ATTN: Technical Library  
Aberdeen Proving Ground, MD 21005

Commander  
Man-Machine Integration System  
Code 602  
Naval Air Development Center  
Warminster, PA 18974

Commander  
Naval Air Development Center  
ATTN: Code 602-B  
Warminster, PA 18974

Commanding Officer  
Armstrong Laboratory  
Wright-Patterson  
Air Force Base, OH 45433-6573

Director  
Army Audiology and Speech Center  
Walter Reed Army Medical Center  
Washington, DC 20307-5001

Commander/Director  
U.S. Army Combat Surveillance  
and Target Acquisition Lab  
ATTN: SFAE-IEW-JS  
Fort Monmouth, NJ 07703-5305

Director  
Federal Aviation Administration  
FAA Technical Center  
Atlantic City, NJ 08405

Director  
Walter Reed Army Institute of Research  
Washington, DC 20307-5100

Commander, U.S. Army Test  
and Evaluation Command  
Directorate for Test and Evaluation  
ATTN: AMSTE-TA-M (Human Factors  
Group)  
Aberdeen Proving Ground,  
MD 21005-5055

Naval Air Systems Command  
Technical Air Library 950D  
Room 278, Jefferson Plaza II  
Department of the Navy  
Washington, DC 20361

Director  
U.S. Army Ballistic  
Research Laboratory  
ATTN: DRXBR-OD-ST Tech Reports  
Aberdeen Proving Ground, MD 21005

Commander  
U.S. Army Medical Research  
Institute of Chemical Defense  
ATTN: SGRD-UV-AO  
Aberdeen Proving Ground,  
MD 21010-5425

Commander  
USAMRMC  
ATTN: SGRD-RMS  
Fort Detrick, Frederick, MD 21702-5012

HQ DA (DASG-PSP-O)  
5109 Leesburg Pike  
Falls Church, VA 22041-3258

Harry Diamond Laboratories  
ATTN: Technical Information Branch  
2800 Powder Mill Road  
Adelphi, MD 20783-1197

Headquarters (ATMD)  
U.S. Army Training

and Doctrine Command  
ATTN: ATBO-M  
Fort Monroe, VA 23651

U.S. Army Materiel Systems  
Analysis Agency  
ATTN: AMXSY-PA (Reports Processing)  
Aberdeen Proving Ground  
MD 21005-5071

U.S. Army Environmental  
Hygiene Agency  
ATTN: HSHB-MO-A  
Aberdeen Proving Ground, MD 21010

Technical Library Chemical Research  
and Development Center  
Aberdeen Proving Ground, MD  
21010-5423

Commander  
U.S. Army Medical Research  
Institute of Infectious Disease  
ATTN: SGRD-UIZ-C  
Fort Detrick, Frederick, MD 21702

Director, Biological  
Sciences Division  
Office of Naval Research  
600 North Quincy Street  
Arlington, VA 22217

Commandant  
U.S. Army Aviation  
Logistics School ATTN: ATSQ-TDN  
Fort Eustis, VA 23604

Eduardo Mera, M.D.  
P. O. Box 86715  
Bogota, Columbia

Naval Aerospace Medical  
Institute Library  
Building 1953, Code 03L  
Pensacola, FL 32508-5600

Command Surgeon  
HQ USCENTCOM (CCSG)  
U.S. Central Command  
MacDill Air Force Base, FL 33608

Director  
Directorate of Combat Developments  
ATTN: ATZQ-CD  
Building 515  
Fort Rucker, AL 36362

U.S. Air Force Institute  
of Technology (AFIT/LDEE)  
Building 640, Area B  
Wright-Patterson  
Air Force Base, OH 45433

Henry L. Taylor  
Director, Institute of Aviation  
University of Illinois-Willard Airport  
Savoy, IL 61874

Chief, National Guard Bureau  
ATTN: NGB-ARS  
Arlington Hall Station  
111 South George Mason Drive  
Arlington, VA 22204-1382

AAMRL/HEX  
Wright-Patterson  
Air Force Base, OH 45433

Commander  
U.S. Army Aviation and Troop Command  
ATTN: AMSAT-R-ES  
4300 Goodfellow Boulevard  
St. Louis, MO 63120-1798

U.S. Army Aviation and Troop Command  
Library and Information Center Branch  
ATTN: AMSAV-DIL  
4300 Goodfellow Boulevard  
St. Louis, MO 63120

Federal Aviation Administration  
Civil Aeromedical Institute  
Library AAM-400A  
P.O. Box 25082  
Oklahoma City, OK 73125

Commander  
U.S. Army Medical Department  
and School  
ATTN: Library  
Fort Sam Houston, TX 78234

Commander  
U.S. Army Institute of Surgical Research  
ATTN: SGRD-USM  
Fort Sam Houston, TX 78234-6200

Air University Library  
(AUL/LSE)  
Maxwell Air Force Base, AL 36112

Product Manager  
Aviation Life Support Equipment  
ATTN: SFAE-AV-LSE  
4300 Goodfellow Boulevard  
St. Louis, MO 63120-1798

Commander and Director  
USAE Waterways Experiment Station  
ATTN: CEWES-IM-MI-R,  
CD Department  
3909 Halls Ferry Road  
Vicksburg, MS 39180-6199

Commanding Officer  
Naval Biodynamics Laboratory  
P.O. Box 24907  
New Orleans, LA 70189-0407

Assistant Commandant  
U.S. Army Field Artillery School  
ATTN: Morris Swott Technical Library  
Fort Sill, OK 73503-0312

Mr. Peter Seib  
Human Engineering Crew Station  
Box 266  
Westland Helicopters Limited  
Yeovil, Somerset BA20 2YB UK

U.S. Army Dugway Proving Ground  
Technical Library, Building 5330  
Dugway, UT 84022

U.S. Army Yuma Proving Ground  
Technical Library  
Yuma, AZ 85364

AFFTC Technical Library  
6510 TW/TSTL  
Edwards Air Force Base,  
CA 93523-5000

Commander  
Code 3431  
Naval Weapons Center  
China Lake, CA 93555

Aeromechanics Laboratory  
U.S. Army Research and Technical Labs  
Ames Research Center, M/S 215-1  
Moffett Field, CA 94035

Sixth U.S. Army  
ATTN: SMA  
Presidio of San Francisco, CA 94129

Commander  
U.S. Army Aeromedical Center  
Fort Rucker, AL 36362

Strughold Aeromedical Library  
Document Service Section  
2511 Kennedy Circle  
Brooks Air Force Base, TX 78235-5122

Dr. Diane Damos  
Department of Human Factors  
ISSM, USC  
Los Angeles, CA 90089-0021

U.S. Army White Sands  
Missile Range  
ATTN: STEWS-IM-ST  
White Sands Missile Range, NM 88002

Director, Airworthiness Qualification Test  
Directorate (ATTC)  
ATTN: STEAT-AQ-O-TR (Tech Lib)  
75 North Flightline Road  
Edwards Air Force Base, CA 93523-6100

Ms. Sandra G. Hart  
Ames Research Center  
MS 262-3  
Moffett Field, CA 94035

Commander  
USAMRMC  
ATTN: SGRD-UMZ  
Fort Detrick, Frederick, MD 21702-5009

Commander  
U.S. Army Health Services Command  
ATTN: HSOP-SO  
Fort Sam Houston, TX 78234-6000

U. S. Army Research Institute  
Aviation R&D Activity  
ATTN: PERI-IR  
Fort Rucker, AL 36362

Commander  
U.S. Army Safety Center  
Fort Rucker, AL 36362

U.S. Army Aircraft Development  
Test Activity  
ATTN: STEBG-MP-P  
Cairns Army Air Field  
Fort Rucker, AL 36362

Commander  
USAMRMC  
ATTN: SGRD-PLC (COL R. Gifford)  
Fort Detrick, Frederick, MD 21702

TRADOC Aviation LO  
Unit 21551, Box A-209-A  
APO AE 09777

Netherlands Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

British Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

Italian Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

Directorate of Training Development  
Building 502  
Fort Rucker, AL 36362

Chief  
USAHEL/USAAVNC Field Office  
P. O. Box 716  
Fort Rucker, AL 36362-5349

Commander, U.S. Army Aviation Center  
and Fort Rucker  
ATTN: ATZQ-CG  
Fort Rucker, AL 36362

Dr. Sehchang Hah  
Dept. of Behavior Sciences and  
Leadership, Building 601, Room 281  
U. S. Military Academy  
West Point, NY 10996-1784

Canadian Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

German Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

French Army Liaison Office  
USAAVNC (Building 602)  
Fort Rucker, AL 36362-5021

Australian Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

Dr. Garrison Rapmund  
6 Burning Tree Court  
Bethesda, MD 20817

Commandant, Royal Air Force  
Institute of Aviation Medicine  
Farnborough, Hampshire GU14 6SZ UK

Defense Technical Information  
Cameron Station, Building 5  
Alexandra, VA 22304-6145

Commander, U.S. Army Foreign Science  
and Technology Center  
AIFRTA (Davis)  
220 7th Street, NE  
Charlottesville, VA 22901-5396

Commander  
Applied Technology Laboratory  
USARTL-ATCOM  
ATTN: Library, Building 401  
Fort Eustis, VA 23604

Commander, U.S. Air Force  
Development Test Center  
101 West D Avenue, Suite 117  
Eglin Air Force Base, FL 32542-5495

Aviation Medicine Clinic  
TMC #22, SAAF  
Fort Bragg, NC 28305

Dr. H. Dix Christensen  
Bio-Medical Science Building, Room 753  
Post Office Box 26901  
Oklahoma City, OK 73190

Commander, U.S. Army Missile  
Command  
Redstone Scientific Information Center  
ATTN: AMSMI-RD-CS-  
R/ILL Documents  
Redstone Arsenal, AL 35898

Aerospace Medicine Team  
HQ ACC/SGST3  
162 Dodd Boulevard, Suite 100  
Langley Air Force Base,  
VA 23665-1995

Commander  
USAMRMC  
ATTN: SGRD-ZC (COL John F. Glenn)  
Fort Detrick, Frederick, MD 21702-5012

U.S. Army Research and Technology  
Laboratories (AVSCOM)  
Propulsion Laboratory MS 302-2  
NASA Lewis Research Center  
Cleveland, OH 44135

Dr. Eugene S. Channing  
166 Baughman's Lane  
Frederick, MD 21702-4083

U.S. Army Medical Department  
and School  
USAMRDALC Liaison  
ATTN: HSMC-FR  
Fort Sam Houston, TX 78234

NVESD  
AMSEL-RD-NV-ASID-PST  
(Attn: Trang Bui)  
10221 Burbeck Road  
Fort Belvoir, VA 22060-5806

CA Av Med  
HQ DAAC  
Middle Wallop  
Stockbridge, Hants S020 8DY UK

Dr. Christine Schlichting  
Behavioral Sciences Department  
Box 900, NAVUBASE NLON  
Groton, CT 06349-5900

Commander  
Aviation Applied Technology Directorate  
ATTN: AMSAT-R-TV  
Fort Eustis, VA 23604-5577

COL Yehezkel G. Caine, MD  
Surgeon General, Israel Air Force  
Aeromedical Center Library  
P. O. Box 02166 I.D.F.  
Israel

HQ ACC/DOHP  
205 Dodd Boulevard, Suite 101  
Langley Air Force Base,  
VA 23665-2789

41st Rescue Squadron  
41st RQS/SG  
940 Range Road  
Patrick Air Force Base,  
FL 32925-5001

48th Rescue Squadron  
48th RQS/SG  
801 Dezonias Road  
Holloman Air Force Base,  
NM 88330-7715

HQ, AFOMA  
ATTN: SGPA (Aerospace Medicine)  
Bolling Air Force Base,  
Washington, DC 20332-6128

ARNG Readiness Center  
ATTN: NGB-AVN-OP  
Arlington Hall Station  
111 South George Mason Drive  
Arlington, VA 22204-1382

35th Fighter Wing  
35th FW/SG  
PSC 1013  
APO AE 09725-2055

66th Rescue Squadron  
66th RQS/SG  
4345 Tyndall Avenue  
Nellis Air Force Base, NV 89191-6076

71st Rescue Squadron  
71st RQS/SG  
1139 Redstone Road  
Patrick Air Force Base,  
FL 32925-5000

Director  
Aviation Research, Development  
and Engineering Center  
ATTN: AMSAT-R-Z  
4300 Goodfellow Boulevard  
St. Louis, MO 63120-1798

Commander  
USAMRMC  
ATTN: SGRD-ZB (COL C. Fred Tyner)  
Fort Detrick, Frederick, MD 21702-5012

Commandant  
U.S. Army Command and General Staff  
College  
ATTN: ATZL-SWS-L  
Fort Leavenworth, KS 66027-6900

Director  
Army Personnel Research Establishment  
Farnborough, Hants GU14 6SZ UK

Dr. A. Kornfield  
895 Head Street  
San Francisco, CA 94132-2813

Mr. George T. Singley, III  
Deputy Assistant Secretary of the Army  
for Research and Technology  
and Chief Scientist  
ATTN: Room 3E374  
103 Army Pentagon  
Washington, DC 20310-0103

The Honorable Gilbert F. Decker  
Assistant Secretary of the Army  
for Research, Development,  
and Acquisition  
ATTN: Room 2E672  
103 Army Pentagon  
Washington, DC 20310-0103

Dr. Craig Dorman  
Office of the Deputy Director,  
Defense Research and Engineering  
ATTN: Room 3D129LM  
103 Army Pentagon  
Washington, DC 20310-0103

HQ, AFOMA  
ATTN; SGPA (Aerospace Medicine)  
Bolling Air Force Base,  
Washington, DC 20332-6188

Cdr, PERSCOM  
ATTN: TAPC-PLA  
200 Stovall Street, Rm 3N25  
Alexandria, VA 22332-0413

DEPARTMENT OF THE ARMY  
U.S. Army Aeromedical  
Research Laboratory  
Fort Rucker, Alabama 36362-0577

---