

UNCLASSIFIED


ORDNANCE CORPS

BALLISTIC RESEARCH LABORATORIES


ABERDEEN PROVING GROUND, MD.

UNCLASSIFIED

acc & file



MEMORANDUM
REPORT No. 531




TECHNICAL LIBRARY
DRYER-12 (DLCG. 506)
ABERDEEN PROVING GROUND, MD. 21005

Vulnerability of B-47B Wing to Internal Blast

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION IS UNLIMITED


GROUP 3
EXCLUDED FROM AUTOMATICALLY DECLASSIFIED



W. E. BAKER

O. T. JOHNSON

UNCLASSIFIED




19960222 002

DTIC QUALITY INSPECTED 1

COPY NO. 1 10843

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

SUPPLEMENTARY

INFORMATION



REPLY TO
THE ATTENTION OF

DEPARTMENT OF THE ARMY
UNITED STATES ARMY RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND 21005-5066

ERRATA

AMSRL-MO-IS (380a)

1 February 1996

MEMORANDUM FOR Defense Technical Information Center, 8725 John J.
Kingman Road Suite 0944, Fort Belvoir, VA
22060-6218

SUBJECT: BRL Memorandum Report No. 531

1. References: BRL Memorandum Report No. 531, "Vulnerability of B-47B Wing to Internal Blast", by W. E. Baker and O. T. Johnson, March 1951, copy enclosed.

2. Our Laboratory has determined that the subject report does not contain any sensitive information. Therefore, we have marked the document with the following distribution statement:

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

3. Our action officer is Mr. Douglas J. Kingsley, telephone 410-278-6960.

Encl

①

P. Ann Brown

P. ANN BROWN
Chief, Security/CI Section
ARL, APG

ERRATA

AD-A 304469





DEPARTMENT OF THE ARMY
UNITED STATES ARMY RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND 21005-5066

REPLY TO
THE ATTENTION OF

AMSRL-MO-IS (380a)

1 February 1996

MEMORANDUM FOR Defense Technical Information Center, 8725 John J.
Kingman Road Suite 0944, Fort Belvoir, VA
22060-6218

SUBJECT: BRL Memorandum Report No. 531

1. References: BRL Memorandum Report No. 531, "Vulnerability of B-47B Wing to Internal Blast", by W. E. Baker and O. T. Johnson, March 1951, copy enclosed.
2. Our Laboratory has determined that the subject report does not contain any sensitive information. Therefore, we have marked the document with the following distribution statement:

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

3. Our action officer is Mr. Douglas J. Kingsley, telephone 410-278-6960.

Encl

P. Ann Brown

P. ANN BROWN
Chief, Security/CI Section
ARL, APG

ARL Information Release Record

This form is an approval record for ARL-generated information to be presented or disseminated externally.

Note: All manuscripts must be submitted in double-spaced format. See attached instructions.

If more space is needed, use reverse of form for continuations (include block numbers).

A. General information		1. Date MAR 51	2. Unclassified title BRL Memorandum Report No. 531, "Vulnerability of B-47B Wing to Internal Blast"				
3. Author(s) W. E. Baker and O. T. Johnson			4. Office symbol or affiliation		5. Telephone		
6. Contractor generated? ☐ no ☐ yes (if yes, enter contract No. and ARL POC)		7. Type: ☒ Report ☐ External publication ☐ Presentation (speech, briefing, slides, etc)					
		8. Key words				9. Abstract only? ☐ no ☐ yes	
10. Distribution statement (required): Is manuscript subject to export control? ☐ no ☐ yes		Circle appropriate letter and No. (see instructions for statement text) A B C D E F 1 2 3 4 5 6 7 8 9 10 11					11. Security classification
B. Reports NA	12. Series	13. Type	14. No. of pages	15. Project No.	16. Period covered	17. Sponsor	
C. External publications NA			18. Material in manuscript (MS) will be submitted for publication in _____				
19. Is MS an invited paper? ☐ no ☐ yes							
20. Is publication a refereed journal? ☐ no ☐ yes			(journal) _____ (country) _____				
D. Presentations NA	21. Conference name and location			22. Sponsor			
23. Conference date	24. Due date	25. Conference is ☐ open to general public ☐ unclassified/controlled access ☐ classified: _____					
26. For nonpublic meetings: Will foreign nationals be attending? ☐ no ☐ yes (if yes, list countries and identify international agreement)		27. Material in MS will be ☐ presented orally only. ☐ presented orally and MS will be published in _____ (if published, fill in blocks 19 and 20, section C)					
E. Approvals (see instructions)							
All information (for external dissemination/presentation)				32. Limited distribution information for release to foreign nationals			
28. Branch Chief/supervisor John K. Moring 23 Jan 96 (date)				Foreign Disclosure Officer _____ (date)			
29. Technical reviewer/panel chairman _____ (date)				33. Classified information Classified by _____ Declassify on _____ ARL Security Officer _____ (date)			
30. Editorial reviewer _____ (date)				34. Public release information (use distribution A) Contractor-generated information? ☐ no ☐ yes Contracting Officer/Specialist _____ (date) ☒ Manuscript has been reviewed for OPSEC policy. ARL Security Manager _____ (date) The information contained in this document ☒ is approved for public release. Public Affairs Officer (or designee) _____ (date)			
31. Division Chief PAUL H. DEITZ, C, BVLD 23 Jan 96 (date)							

UNCLASSIFIED

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 531

March 1951

VULNERABILITY OF B-47B WING TO INTERNAL BLAST

**W. E. Baker
O. T. Johnson**

ABERDEEN PROVING GROUND, MD. 21005

**Project No. TB3-0238A of the Research and
Development Division, Ordnance Corps**

ABERDEEN PROVING GROUND, MARYLAND

UNCLASSIFIED

UNCLASSIFIED



BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 531

WEBaker/OTJohnson/jld
Aberdeen Proving Ground, Md.
8 March 1951

VULNERABILITY OF B-47B WING TO INTERNAL BLAST

ABSTRACT

Some internal blast tests have been conducted on a B-47B wing. In this report are given the test findings and the predictions for LOOA, 50A, and OA damage for the entire wing.

UNCLASSIFIED



INTRODUCTION

As a part of the overall study of weapons effectiveness, internal blast tests against various semi-monocoque¹ and more nearly monocoque² type aircraft have been carried out and are reported³ in several BRL reports and memorandum reports. The results of these tests indicate that the aircraft of nearly full monocoque type construction are much more vulnerable to internal blast than those of semi-monocoque type construction.

The B-47B is a six-jet swept-wing medium bomber. Its wing consists of a strong box spar to which very light leading and trailing edges are attached. The box spar forms a nearly monocoque structure, i.e., most of its strength is in the very thick skin and spar webs. This type of construction is quite different from that of the B-17 or B-29 wings, both of which are so constructed that most of their strength lies in heavy stringers, spar caps, and ribs rather than in the skin. Typical cross-sections of a B-47 wing and a B-17 wing are shown below.


These tests continue the studies of internal blast vulnerability of nearly full monocoque aircraft structures. Rough estimates of the vulnerability of a B-47B wing to internal blast, based on firings against other aircraft, reported by Morgan G. Smith in BRL Report No. 733, "Passive Defense of Aircraft," August 1950, will have to be modified, based on the results of the actual firing tests reported herein.

EXPERIMENTAL PROCEDURES

The firings were conducted at Wichita Municipal Airport on a complete B-47B wing assembly minus the leading edge. Boeing Aircraft Company personnel and Captain R. P. Flanagan, U. S. Air Force, assisted by the making of arrangements and in the conduct of the tests. There was some pre-test damage which was the result of the wing being dropped during fabrication processes, weakening the left wing tip and the wing root section.


1. A-25, A-20, B-17, and B-29 aircraft.
2. Douglas D-558, B-36.
3. BRL Memorandum Report No. 436, "Report on Tests of the Effect of Blast from Bare and Cased Charges on Aircraft," James N. Sarmousakis, July 1946. BRL Report No. 645, "The Effect of Blast on Aircraft," Joseph Sperrazza and James N. Sarmousakis, August 1947. BRL Memorandum Report No. 490, "Vulnerability of B-29 Aircraft to Internal Blast," Joseph Sperrazza, June 1949. BRL Memorandum Report No. 520, "Vulnerability of Douglas D-558 Skystreak to Internal Blast," Joseph Sperrazza and Elaine Gilinson, September 1950.

TYPICAL B-17 WING CHORDWISE SECTION



- A Heavy spar caps
- B Heavy rib trusses
- C Inner corrugated skin
- D Heavy web truss running spanwise
- E Light outer skin

TYPICAL B-47 WING CHORDWISE SECTION



- A Light skin
- B Light rib panel
- C Stiffeners
- D Very heavy skin
- E Heavy plate spar web
- F Comparatively light spar caps
- G Light skin
- H Light bracing

The B-47B wing was supported on wooden cradles, and bare TNT or pentolite charges of the desired weight were placed at specified positions (See Figure 1). After each charge was detonated an assessor wrote a detailed description of the damage caused to the wing structure, and then estimated the probability that the damage fell in four categories designated by the letters A, B, C, and E.

- A: damage resulting in aircraft beginning to fall within five minutes.
- B: damage resulting in aircraft beginning to fall within two hours.
- C: damage resulting in aircraft being unable to complete its mission.
- E: damage resulting in crash on landing.

If the assessor thought that the damage would result in immediate loss of control the symbol K (meaning kill) was used in the A category.

The Aberdeen Proving Ground assessor was Capt. E. B. McClintick, U. S. Air Force. Structural engineers from the Boeing Seattle plant were on hand to aid the Aberdeen Proving Ground assessor in determining the extent of damage.

It was assumed that the aircraft was in level flight at normal cruising speed of about 450 mph.

A total of eight firings were made. The number of firings was limited since only one wing structure was available for the test. With the exception of the two and three pound TNT blocks all the charges were bare pentolite spheres, (1/4 lb., 1/2 lb., and 1 lb.) centrally initiated. This shape was used in order to obtain spherical shock wave distribution. The two and three pound TNT blocks were used because no spherical charges of that weight were available at the time.

Complete description and photographs of the damage from each individual charge will be found in special APG Firing Records dated 17 October 1950.

RESULTS

The results of individual firings are given in Table I. Firing positions are numbered in Figure 1.

The wing was divided into four sections chordwise; leading edge, spar box, structure aft of spar box and forward of flap and aileron hinge line, structure aft of flap and aileron hinge line. As can be seen from the airfoil cross-section in the introduction, marked differences in construction dictated this choice of sectioning. For convenience in estimating extent of damage from a single charge, each section was further divided into four

spanwise parts. Final subdivision of wing area is shown in Figure 1.

By some interpolation and considerable extrapolation from the results of Table I, weights of explosive necessary to just produce 100A and 50A damage in various portions of the wing were estimated. Also, appraisals were made of the "threshold" charge weight for OA damage, i.e., that charge weight which just fails to produce appreciable A damage. Table II gives these estimates.

In preparing Table II, several assumptions were made of the amount of damage the wing could sustain before the aircraft would fall out of control. For charges outside the spar box, it was assumed that loss of a portion of leading or trailing edge with no accompanying damage to the spar box would be considered as OA structural damage. Similarly, loss of a wing tip outboard of the outboard engine was assumed insufficient to cause the aircraft to fall out of control and was called OA.

TABLE I

Damage Assessments and Charge Weights for
Individual Firings within B-47 Wing

Firing No.	Charge Wt., Lbs.	A	Damage Assessment			E
			B	C		
1*	1/4	100	100	100		100
2	1/4	0	0	0		0
3	1/2	0	0	0		0
4	3**	25	70	0		0
5	2**	K	100	100		--
6	1/4	5	10	0		0
7	1/2	K	100	100		--
8	1	K	100	100		--

* Damage here was compounded by damage sustained in fall of aircraft wing in factory.

** These charges were block TNT; all others were spherical pentolite.

FIGURE I
B - 47B WING PLAN SHOWING WING AREAS OF TABLE II
AND LOCATIONS OF ALL CHARGES FIRED




TABLE II

Estimated Charge Weights (Pounds) for "A"
Structural Damage to B-47B Wing

Area *	100A	50A	0A
w_{11}	3	2	1-1/2
w_{21}	3	2	1-1/2
w_{31}	2-1/2	1-1/2	1
w_{41}	3	2	1-1/2
w_{12}	3/4	3/4	1/2
w_{22}	1/2	1/2	1/4
w_{32}	3/8	3/8	1/4
w_{42}	1/2	1/2	1/4
w_{13}	4	3	2
w_{23}	4	3	2
w_{33}	3	2	1
w_{43}	4	3	2
w_{14}	8	4	2
w_{24}	8	4	2
w_{34}	4	2	1
w_{44}	5	4	1

* Areas are shown on Figure 1.

DISCUSSION

Since all but one of the test charges were fired within the spar box, the estimates of vulnerability for that section are probably more accurate than the estimates for charges outside of the spar box. From the results of test charge No. 4, it is apparent that a charge outside of the spar box must be much larger than one within the box to damage the spar box enough to cause appreciable "A" damage.

In the light of these tests, the rough vulnerability estimates given in BRL 733 must be modified as shown in Table II.

Damage occurring from charges within the spar box was of the "all-or-nothing" variety. That is, a given weight of charge produced essentially no damage, while a slightly larger charge completely wrecked the spar box for a twenty foot length. Figures 2 and 3 show the left wing spar box after firing a 1/4 lb. pentolite charge. It can be seen that the only damage from this charge was carrying away of several very light internal spar box ribs. Yet a 1/2 lb. charge in the same portion of the right spar box completely wrecked the spar box. Figures 4, 5, and 6 show the damage from this charge. As a result of this sharp demarcation in amount of charge to do crippling damage, it was assumed that any charge within the spar box large enough to do 50A damage would also do 100A damage: i.e., there is no 50A vulnerable area in the spar box.

The nature of spar box damage may be due to the material of which it is constructed (75ST aluminum alloy). This alloy has a quite high elastic limit compared to such an alloy as 24ST, but it is more brittle and hence propagates fractures much more readily than the more ductile 24ST. So, a blast which would cause only localized damage in a structure made of 24ST might cause quite general damage in a similar equal strength structure of 75ST.

It is believed that the very light construction of the ribs within the spar box minimized the damage. They merely carried away without damaging the structure to which they were attached, thus effectively reducing the confinement of the blast. Figure 7 shows this type of internal damage resulting from a 1/2 lb. charge. It is thought that a suggestion by Captain McClintick, that it may be possible to further reduce vulnerability by installing a number of very light "explosion relief" panels in the spar box outer skin, has merit.

W. E. Baker

W. E. Baker

O. T. Johnson

O. T. Johnson



Figure 2. External View of Left Wing After Detonation of 1/4 lb. Spherical Pentolite Charge Within Spar Box.




Figure 3. Internal View of Damage to Left Wing Spar Box after the Detonation of a 1/4 lb. Spherical Pentolite Charge.




Figure 4. External View of Damage Resulting From the Detonation of a 1/2 lb. Spherical Pentolite Charge Within the Right Wing Spar Box.




Figure 5. External View of Damage Resulting From the Detonation of a 1/2 lb. Spherical Pentolite Charge Within The Right Wing Spar Box.




Figure 6. External View of Damage Resulting From the Detonation of a 1/2 lb. Spherical Pentolite Charge Within Right Wing Spar Box.




Figure 7. Internal View of Damage Resulting From a 1/2 lb. Spherical Pentolite Charge Detonated Within the Spar Box.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
10	Chief of Ordnance Washington 25, D. C. Attn: ORDTB - Bal Sec	1	Department of the Navy Operation Evaluation Group Washington, D. C. Attn: Dr. Jacinto Steinhardt
10	British - to ORDTB for distribution	1	Superintendent Postgraduate School U. S. Naval Academy Annapolis, Maryland
4	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Re3 Re2 Re8 ReXa	1	Commanding Officer Naval Aviation Ordnance Test Station Chincoteague, Virginia
1	Commanding Officer Naval Proving Ground Dahlgren, Virginia	9	Chief, Bureau of Aeronautics Department of the Navy Washington 25, D. C. Attn: Airborne Equip. Div., G. S. Schubart
2	Office of Naval Research Department of the Navy Washington 25, D. C. Attn: Scientific Literature Branch (N482)		2 - Armament Division 1 - Power Plant Division 1 - Research Division 1 - Design Elements Div. 1 - Evaluation Division 1 - Military Requirements Div. 1 - Piloted Aircraft Div.
2	Commander Naval Ordnance Laboratory White Oak Silver Spring 19, Maryland Of interest to: G.K. Hartman	1	Commanding General Air Proving Ground Eglin Air Force Base, Florida Attn: Director of Armament
1	Commander Naval Air Development Center Johnsville, Pennsylvania	2	Commanding General Air University Maxwell Air Force Base Montgomery, Alabama Attn: Air University Library
1	Commander U. S. Naval Ordnance Test Station Inyokern P. O. China Lake, California Attn: Technical Library and Editorial Section	2	Chief of Staff, USAF Washington 25, D. C. Attn: Director, Research & Dev., DCS/D Of interest to: Chief of Armament Div.

SECRET

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Chief of Staff, USAF Washington 25, D. C. Attn: Assistant for Operations Analysis, DCS/O	2	Director, Central Air Documents Office U. B. Building Dayton 2, Ohio Attn: CADO-D
1	Chief of Staff, USAF Washington 25, D. C. Attn: Director of Requirements, DCS/D	1	Director, Weapons System Evaluation Group Office, Secretary of Defense The Pentagon Washington 25, D. C.
1	Commanding General Research & Dev. Command Headquarters, USAF Washington 25, D. C.	1	Air Weapons Research Center University of Chicago Chicago 37, Illinois Attn: Dr. W. Bartky
8	Commanding General Air Materiel Command Wright-Patterson Air Force Base Dayton, Ohio Attn: MCREXG (1 copy) MCREXP (1 copy) MCREXM (1 copy) MCRR (1 copy) MCIAXS (1 copy) MCREXE (1 copy) MCREOA (2 copies)	THRU:	Chief, Chicago AFPFO 209 Jackson Blvd. Chicago 6, Illinois
1	Commanding General Continental Air Command Mitchell Air Force Base New York	1	Rand Corporation 1500 Fourth Street Santa Monica, California
2	Commanding General Strategic Air Command Offutt Air Force Base Omaha, Nebraska	THRU:	Chief, Los Angeles AFPFO 155 West Washington Blvd. Los Angeles 54, Calif.
1	Commanding General Tactical Air Command Langley Air Force Base Langley, Virginia	1	New Mexico School of Mines Research & Development Div. Socorro, New Mexico
1	Commanding General Air Defense Command Mitchell Air Force Base New York	THRU:	Dev. Contract Officer Research & Dev. Div. New Mexico School of Mines Socorro, New Mexico
		1	Cornell Aeronautical Lab., Inc. 4455 Genesee Street Buffalo 21, New York
		1	BuAer Representative, U.S.N. Douglas Aircraft Co., Inc. El Segundo Plant El Segundo, California

UNCLASSIFIED

DISTRIBUTION LIST

**No. of
Copies**

Organization

1

B-47 Project Officer
Office of USAF Plant Representative
Boeing Aircraft Company
Wichita, Kansas

4

Director, Operations Research Office
Department of the Army
Fort Leslie J. McNair
Washington 25, D. C.


1 - American Power Jet Company
363 Bloomfield Avenue
Montclair, New Jersey

1 - Columbia Research & Development
Corporation
4608 Indianola Avenue
Columbus 14, Ohio

UNCLASSIFIED

[REDACTED]

UNCLASSIFIED



UNCLASSIFIED

[REDACTED]